



FCC ID:2ANFRMT-303

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

| Modulation | Channel Freq. (GHz) | Conducted power (dBm) | Conducted power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculation | SAR Exclusion threshold | SAR test exclusion |
|------------|---------------------|-----------------------|----------------------|---------------------|-------------------------|------------------------|---------------|--------------------|-------------------------|--------------------|
| GFSK | 2.417 | 6.31 | 4.28 | 6 \pm 1 | 7.00 | 5.01 | <5 | 1.55836 | 3.00 | YES |
| | 2.447 | 5.66 | 3.68 | 6 \pm 1 | 7.00 | 5.01 | <5 | 1.56800 | 3.00 | YES |
| | 2.480 | 4.91 | 3.10 | 5 \pm 1 | 6.00 | 3.98 | <5 | 1.25388 | 3.00 | YES |

Conclusion:

For the max result : 1.56800W/Kg \leq FCC Limit 3.0 for 1g SAR.