



SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technological
Development District, Guangzhou, China 510663

Telephone: +86 (0) 20 82155555
Fax: +86 (0) 20 82075059
Email: ee.guangzhou@sgs.com

Report No.: GZEM170700433201
Page: 1 of 46
FCC ID: 2ANH3MEDIDOR1B

TEST REPORT

Application No.: GZEM1707004332HS
Applicant: Medidor Group LLC
Address of Applicant: 12344 26 mile road spc 6 Oakdale California 95361
Manufacturer: The Same as Applicant
Address of Manufacturer: The Same as Applicant
Factory: The Same as Applicant
Address of Factory: The Same as Applicant
Equipment Under Test (EUT):
FCC ID: 2ANH3MEDIDOR1B
EUT Name: Medidor 1
Model No.: Medidor 1 Bluetooth
Trade Mark: medidor®
Standards: 47 CFR Part 15, Subpart C:2016 section 15.247
Date of Receipt: 2017-07-17
Date of Test: 2017-08-09
Date of Issue: 2017-09-11

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Ricky Liu
Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.


The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2017-09-11		Original

Authorized for issue by:				
Tested By		 Vico_Cui /Project Engineer		2017-08-09 Date
Checked By		 Ricky_Liu /Reviewer		2017-09-11 Date



3 Test Summary

Test	Test Requirement	Test method	Result
Antenna Requirement	FCC PART 15 C section 15.247 (c) and Section 15.203	FCC PART 15 C section 15.247 (c) and Section 15.203	PASS
6 dB Bandwidth	FCC PART 15 C section 15.247 (a)(2)	ANSI C63.10: Clause 11.8	PASS
Maximum Peak Output Power	FCC PART 15 C section 15.247(b)(3)	ANSI C63.10: Clause 11.9	PASS
Peak Power Spectral Density	FCC PART 15 C section 15.247(e)	ANSI C63.10: Clause 11.10	PASS
Conducted Spurious Emission	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 11.11	PASS
Radiated Spurious Emission	FCC PART 15 C section 15.209	ANSI C63.10: Clause 11.12,6.3,6.5 and 6.6	PASS
Radiated Emissions which fall in the restricted bands	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 11.12,6.3,6.5 and 6.6	PASS
Band Edges Measurement	FCC PART 15 C section 15.247 (d) &15.205	ANSI C63.10: Clause 11.13	PASS
Remark1: N/A: not applicable. Refer to the relative section for the details. EUT: In this whole report EUT means Equipment Under Test. Tx: In this whole report Tx (or tx) means Transmitter. Rx: In this whole report Rx (or rx) means Receiver. RF: In this whole report RF means Radio Frequency. ANSI C63.10: the detail version is ANSI C63.10:2013 in the whole report. Conducted testing use a direct connection between the antenna port of the device and the spectrum analyzer, may through suitable attenuator, all the attenuation in the conducted RF path, include cable loss or external attenuation will be offset to the spectrum analyzer during testing. Detailed offset value, please refer to the corresponding test plot.			



4 Contents

1	Cover Page	1
2	Version.....	2
3	Test Summary	3
4	Contents	4
5	General Information.....	5
5.1	Details of E.U.T.	5
5.2	Description of Support Units	5
5.3	Deviation from Standards	5
5.4	Abnormalities from Standard Conditions	5
5.5	Other Information Requested by the Customer.....	5
5.6	Test Location.....	6
5.7	Measurement Uncertainty	6
5.8	Test Facility	7
6	Equipment List.....	8
7	Test Results	10
7.1	E.U.T. test conditions	10
7.2	Antenna Requirement.....	13
7.3	6 dB Bandwidth.....	14
7.4	Maximum Peak Output Power.....	17
7.5	Peak Power Spectral Density	21
7.6	Conducted Spurious Emissions.....	25
7.7	Radiated Spurious Emissions.....	31
7.8	Radiated Emissions which fall in the restricted bands	38
7.9	Band Edges Requirement	44



5 General Information

5.1 Details of E.U.T.

Operating Frequency	2402 MHz to 2480 MHz
Type of Modulation:	GFSK
Equipment types:	DSSS with Adaptive (Only one adaptive mode is implemented and could not operate in a non-adaptive mode.)
Number of Channels	40 Channels
Channel Separation:	2 MHz
Duty Cycle:	Continuous operation possible for testing purposes
Antenna Type	Integral PCB Antenna
Antenna Gain:	0dBi
Specialty:	Bluetooth 4.0 (BLE mode)
Function:	Safety box with Bluetooth function for data transmission
Power Supply:	DC 9V (size of "6LR61" alkaline battery)
Test Voltage:	DC 9V (size of "6F22" alkaline battery supplied by SGS for support testing only)
Cable:	N/A
RF Power:	≤10mw

5.2 Description of Support Units

The EUT has been tested with corresponding accessories as below supplied by SGS:

Description	Manufacturer	Model No.	SN/Certificate NO
NoteBook	IBM	T30	S/N78-3VMLX 06/01
BT test board	SGS EMC	RF 07	RF 07
DC 9V battery	NA	6F22	NA

Using the special software and development board we can enter the product for engineer mode then we can control the EUT to select the wanted channel for test. The test board and PC are only to configure the engineer mode and not used to final test

5.3 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

5.4 Abnormalities from Standard Conditions

None.

5.5 Other Information Requested by the Customer

None.



5.6 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663
Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

5.7 Measurement Uncertainty

No.	Item	Measurement uncertainty
1	Conducted emission	1.02dB(9kHz to 150kHz)
		1.05dB(150kHz to 30MHz)
2	Radiated emission	5.06dB(30MHz to 1GHz)
		5.06dB(1GHz to 26GHz)



5.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- **FCC Recognized 2.948 Listed Test Firm(Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

- **FCC Recognized Accredited Test Firm(Registration No.: 486818)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818, Jul 13, 2017.

- **Industry Canada (Registration No.: 4620B-1)**

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

- **VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co. Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.



6 Equipment List

FCC equipment						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date	Cal.Due date
					(YYYY-MM-DD)	(YYYY-MM-DD)
EMC0525	Compact Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2016-12-04	2019-12-03
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2017-01-20	2018-01-19
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	100236	2017-01-20	2018-01-19
EMC0528	RI High frequency Cable	SGS	20 m	N/A	2016-04-19	2018-04-18
EMC2025	Trilog Broadband Antenna 30-1000MHz	SCHWARZBECK MESS-ELEKTRONIK	VULB 9160	9160-3372	2016-09-08	2019-09-07
SEM003-18	Trilog Broadband Antenna 25-2000MHz	SCHWARZBECK MESS-ELEKTRONIK	VULB 9168	665	2016-06-29	2019-06-28
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2016-09-08	2019-09-07
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2017-05-04	2020-05-03
EMC2026	Horn Antenna 1-18GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	9120D-841	2016-09-09	2019-09-08
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2017-01-20	2018-01-19
EMC2065	Amplifier	HP	8447F	N/A	2017-06-19	2018-06-18
EMC2086	PRE AMPLIFIER MH648A	ANRITSU CORP	MH648A	N/A	2016-12-02	2017-12-01
EMC2063	Pre-amplifier 1GHz-26GHz	Compliance Direction Systems Lnc.	PAP-1G26-48	6279.628	2016-12-02	2017-12-01
EMC0523	Active Loop Antenna	EMCO	6502	42963	2016-02-27	2018-02-26
EMC2041	Broad-Band Horn Antenna (14)15-26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONI	BBHA 9170	9170-375	2017-05-23	2020-05-22
EMC2079	High Pass Filter(915MHz)	FSY MICROWAVE	HM1465-9SS	009	2017-01-20	2018-01-19
EMC2069	2.4GHz Filter	Micro-Tronics	BRM 50702	149	2017-01-20	2018-01-19
EMC0530	10m Semi-Anechoic Chamber	ETS	N/A	N/A	2016-04-30	2018-04-29
EMC0306	Shielding Room	Zhong Yu	8 x 3 x 3.8 m ³	N/A	N/A	N/A
EMC1801	V-LISN	EM Test/AG	NNBM 8125	81251342	2016-12-02	2017-12-01
EMC1802	V-LISN	EM Test/AG	NNBM 8125	81251345	2016-12-02	2017-12-01
EMC0506	EMI Test Receiver	Rohde & Schwarz	ESCS30	100085	2016-12-02	2017-12-01
EMC0107	Coaxial Cable	SGS	2m	N/A	2016-07-24	2018-07-23
EMC0106	Voltage Probe	SGS	N/A	N/A	2016-04-05	2018-04-04
EMC0069	Signal Analyzer	R&S	FSIQ26	100312	2016/12/2	2017/12/1
	(20Hz ~ 26.5Ghz)					



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM170700433201

Page: 9 of 46

FCC ID: 2ANH3MEDIDOR1B

General used equipment						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date	Cal.Due date
					(YYYY-MM-DD)	(YYYY-MM-DD)
EMC0006	DMM	Fluke	73	70681569	2016-09-01	2017-08-31
EMC0007	DMM	Fluke	73	70671122	2016-08-22	2017-08-21



7 Test Results

7.1 E.U.T. test conditions

Test Voltage: DC 9V

Temperature: 20.0 -25.0 °C

Humidity: 38-50 % RH

Atmospheric Pressure: 1000 -1010 mbar

Requirements: **15.31(e):** For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.
15.32: Power supplies and CPU boards used with personal computers and for which separate authorizations are required to be obtained shall be tested as follows: Testing shall be in accordance with the procedures specified in Section 15.31 of this part.

Test frequencies and frequency range: According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:



Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM170700433201

Page: 12 of 46

FCC ID: 2ANH3MEDIDOR1B

EUT channels and frequencies list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	27	2456
1	2404	28	2458
2	2406	29	2460
3	2408	30	2462
4	2410	31	2464
5	2412	32	2466
6	2414	33	2468
7	2416	34	2470
8	2418	35	2472
9	2420	36	2474
10	2422	37	2476
11	2424	38	2478
12	2426	39	2480
13	2428	40	/
14	2430	41	/
15	2432	42	/
16	2434	43	/
17	2436	44	/
18	2438	45	/
19	2440	46	/
20	2442	47	/
21	2444	48	/
22	2446	49	/
23	2448	50	/
24	2450	51	/
25	2452	52	/
26	2454	53	/

Using the special software and development board we can enter the product for engineer mode then we can control the EUT to select the wanted channel for test as above list.

Test frequencies are the lowest channel: 0 channel(2402MHz), middle channel: 19 channel(2440 MHz) and highest channel: 39 channel(2480 MHz)

7.2 Antenna Requirement

Standard requirement

15.203 requirement:


For intentional device. According to 15.203, an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna

The antenna is integrated PCB antenna and no consideration of replacement. The maximum gain of the antenna is 0dBi.



Test result: The unit does meet the FCC requirements.

7.3 6 dB Bandwidth


Test Requirement: FCC Part 15 C section 15.247

(a)(2) Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Method: ANSI C63.10: Clause 11.8

Test Status: Enter test mode for the product. Test in lowest Channel 2402MHz, middle Channel 2440MHz and highest Channel 2480MHz, keep in continuously transmitting status.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW=100 kHz. VBW = 300 kHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Set span to encompass the entire emission bandwidth of the signal.
3. Mark the peak power frequency and -6dB (upper and lower) power frequency.
4. Repeat until all the test status is investigated.
5. Report the worst case.



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM170700433201

Page: 15 of 46

FCC ID: 2ANH3MEDIDOR1B


Test Result:

Channel No.	Frequency (MHz)	Mode	Data Rate	Measured bandwidth (kHz)	Limit	Result
0	2402	GFSK	1 Mbps	711.4	≥500KHz	Pass
19	2440		1 Mbps	691.3		Pass
39	2480		1 Mbps	691.3		Pass

The unit does meet the FCC requirements.

Result plot as follows:

Channel 0: 2.402GHz:






SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM170700433201


Page: 16 of 46

FCC ID: 2ANH3MEDIDOR1B

Channel 19: 2.440GHz:



Channel 39: 2.480GHz:




7.4 Maximum Peak Output Power

Test Requirement: FCC Part 15 C section 15.247
 (b)(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.
 Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b) (1), (b) (2), and (b) (3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Method: ANSI C63.10: Clause 11.9

Test Status: Enter test mode for the product. Test in lowest Channel 2402MHz, middle Channel 2440MHz and highest Channel 2480MHz, keep in continuously transmitting status.

Test Configuration:





SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM170700433201

Page: 18 of 46

FCC ID: 2ANH3MEDIDOR1B

Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable from the antenna port to the spectrum.
2. Set the RBW $\geq$ DTS. bandwidth.
3. Set the VBW $\geq 3 \times$ RBW
4. Set the span $\geq 3 \times$ RBW
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. . Use peak marker function to determine the peak amplitude level.
10. Report the worst case.

Test result:

Channel No.	Frequency (MHz)	Mode	Measured Channel Power (dBm)	Limit	Result
0	2402	GFSK	0.1	1W(30dBm)	Pass
19	2440		0.3		Pass
39	2480		-0.5		Pass


Remark: Level = Read Level + Cable Loss

The unit does meet the FCC requirements.




Result plot as follows:

Channel 0: 2.402GHz:




Channel 19: 2.440GHz:






Channel 39:2.480GHz:



7.5 Peak Power Spectral Density

Test Requirement:	FCC Part 15 C section 15.247 (e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10: Clause 11.10
Test Status:	Enter test mode for the product. Test in lowest Channel 2402MHz, middle Channel 2440MHz and highest Channel 2480MHz, keep in continuously transmitting status.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer: RBW=3 kHz.
3. VBW $\geq 3 \times$ RBW sweep= Auto couple; Set the span to 1.5 times the DTS bandwidth.
4. Detector Function = Peak. Trace = Max Hold, Centre = the Peak Power of the signal.
5. Measure the Power Spectral Density of the test frequency with special test status.
6. Repeat until all the test status is investigated.
7. Report the worst case.



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM170700433201

Page: 22 of 46

FCC ID: 2ANH3MEDIDOR1B

Test Result:

Channel No.	Frequency (MHz)	Mode	Measured Peak Power Spectral Density (dBm/3KHz)	Limit	Result
0	2402	GFSK	-14.85	8dBm/3KHz	Pass
19	2440		-13.35		Pass
39	2480		-13.57		Pass


Level = Read Level + Cable Loss.

The unit does meet the FCC requirements.




Result plot as follows:

Channel 0: 2.402 GHz:



Channel 19: 2.440 GHz:






SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM170700433201

Page: 24 of 46

FCC ID: 2ANH3MEDIDOR1B

Channel 39: 2.480 GHz:



7.6 Conducted Spurious Emissions


Test Requirement: FCC Part 15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10: Clause 11.11

Test Status: Enter test mode for the product. Test in lowest Channel 2402MHz, middle Channel 2440MHz and highest Channel 2480MHz, keep in continuously transmitting status.

Test Configuration:



Test Procedure:


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer: RBW=100 KHz, VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Scan up through 10th harmonic.
3. Measure the Conducted Spurious Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worst case.




Result plot as follows:

Channel 0: 2.402 GHz

30 MHz to 1GHz



1GHz to 5GHz






SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM170700433201

Page: 27 of 46


FCC ID: 2ANH3MEDIDOR1B

5GHz to 25GHz



Channel 19: 2.440GHz

30 MHz to 1GHz






SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM170700433201


Page: 28 of 46

FCC ID: 2ANH3MEDIDOR1B

1GHz to 5GHz



5GHz to 25GHz





SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch


Report No.: GZEM170700433201

Page: 29 of 46


FCC ID: 2ANH3MEDIDOR1B

Channel 39: 2.480GHz

30 MHz to 1GHz



1GHz to 5GHz






SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM170700433201

Page: 30 of 46

FCC ID: 2ANH3MEDIDOR1B

5GHz to 25GHz



7.7 Radiated Spurious Emissions

Test Requirement: 47 CFR Part 15C Section 15.209 and 15.205

Test Method: ANSI C63.10: 2013

Test Status: Enter test mode for the product. Test in lowest Channel 2402MHz, middle Channel 2440MHz and highest Channel 2480MHz, keep in continuously transmitting status with GFSK modulation.
 For below 1GHz part, through pre-scan, the worst case is the lowest channel.

Test Site: Measurement Distance:3m

(Semi-Anechoic Chamber below 1GHz, Full Anechoic Chamber above 1GHz)

Receiver Setup:


Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:


Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.


Test Setup:



Below 30MHz



30MHz to 1GHz



Above 1 GHz

Test Procedure:

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 and 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degree to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel (2402MHz), the middle channel (2442MHz), the Highest channel (2480MHz)
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Test Result:

9KHz~30 MHz, Quasi-Peak Measurement

The measurements with Loop antenna and the amplitude of spurious emissions from the radiator are attenuated more than 20dB below the limit, so the test data were not recorded in the test report.

30MHz~1GHz, Quasi-Peak Measurement

The measurements with Log antenna and only the lowest channel test data was record in the report.

Lowest channel

	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	48.163	23.06	14.42	1.26	27.00	11.74	40.00	-28.26	HORIZONTAL	QP
2	63.536	23.66	13.68	1.47	27.00	11.81	40.00	-28.19	HORIZONTAL	QP
3	177.509	37.98	12.78	2.55	26.67	26.64	43.50	-16.86	HORIZONTAL	QP
4	192.419	36.41	11.67	2.66	26.61	24.13	43.50	-19.37	HORIZONTAL	QP
5	379.914	26.59	16.04	3.80	27.00	19.43	46.00	-26.57	HORIZONTAL	QP
6	896.997	24.81	23.38	5.90	27.72	26.37	46.00	-19.63	HORIZONTAL	QP

	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	31.620	25.94	14.06	1.10	27.10	14.00	40.00	-26.00	VERTICAL	QP
2	53.882	26.09	14.36	1.30	27.00	14.75	40.00	-25.25	VERTICAL	QP
3	74.919	31.82	11.15	1.60	27.00	17.57	40.00	-22.43	VERTICAL	QP
4	147.921	25.27	13.26	2.29	26.80	14.02	43.50	-29.48	VERTICAL	QP
5	175.652	27.61	12.85	2.52	26.68	16.30	43.50	-27.20	VERTICAL	QP
6	863.056	29.10	23.10	5.84	27.83	30.21	46.00	-15.79	VERTICAL	QP

Above 1GHz, Peak & Average Measurement

Lowest channel

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	3958.309	27.58	29.42	8.95	40.06	25.89	54.00	-28.11	HORIZONTAL	Averag
2	3958.309	41.01	29.42	8.95	40.06	39.32	74.00	-34.68	HORIZONTAL	Peak
3	4804.658	39.48	30.79	9.95	40.21	40.01	54.00	-13.99	HORIZONTAL	Averag
4	4804.658	54.22	30.79	9.95	40.21	54.75	74.00	-19.25	HORIZONTAL	Peak
5	7206.654	23.57	35.45	12.73	39.25	32.50	54.00	-21.50	HORIZONTAL	Averag
6	7206.654	36.01	35.45	12.73	39.25	44.94	74.00	-29.06	HORIZONTAL	Peak
7	9608.479	21.46	37.51	14.48	37.97	35.48	54.00	-18.52	HORIZONTAL	Averag
8	9608.479	31.40	37.51	14.48	37.97	45.42	74.00	-28.58	HORIZONTAL	Peak
9	12010.700	20.24	39.50	15.80	38.08	37.46	54.00	-16.54	HORIZONTAL	Averag
10	12010.700	32.35	39.50	15.80	38.08	49.57	74.00	-24.43	HORIZONTAL	Peak
11	14412.250	20.98	41.97	18.27	38.43	42.79	54.00	-11.21	HORIZONTAL	Averag
12	14412.250	32.69	41.97	18.27	38.43	54.50	74.00	-19.50	HORIZONTAL	Peak

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	4804.568	33.25	30.79	9.95	40.21	33.78	54.00	-20.22	VERTICAL	Averag
2	4804.568	48.86	30.79	9.95	40.21	49.39	74.00	-24.61	VERTICAL	Peak
3	7206.658	27.37	35.45	12.73	39.25	36.30	54.00	-17.70	VERTICAL	Averag
4	7206.658	40.16	35.45	12.73	39.25	49.09	74.00	-24.91	VERTICAL	Peak
5	7943.838	24.25	36.47	13.47	39.11	35.08	54.00	-18.92	VERTICAL	Averag
6	7943.838	34.11	36.47	13.47	39.11	44.94	74.00	-29.06	VERTICAL	Peak
7	9608.354	22.57	37.51	14.48	37.97	36.59	54.00	-17.41	VERTICAL	Averag
8	9608.354	31.56	37.51	14.48	37.97	45.58	74.00	-28.42	VERTICAL	Peak
9	12010.660	22.19	39.50	15.80	38.08	39.41	54.00	-14.59	VERTICAL	Averag
10	12010.660	33.88	39.50	15.80	38.08	51.10	74.00	-22.90	VERTICAL	Peak
11	14412.690	20.08	41.97	18.27	38.43	41.89	54.00	-12.11	VERTICAL	Averag
12	14412.690	33.58	41.97	18.27	38.43	55.39	74.00	-18.61	VERTICAL	Peak

Middle channel

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	3879.027	28.68	29.24	8.86	40.04	26.74	54.00	-27.26	HORIZONTAL	Averag
2	3879.027	41.27	29.24	8.86	40.04	39.33	74.00	-34.67	HORIZONTAL	Peak
3	4882.347	40.65	30.95	10.02	40.22	41.40	54.00	-12.60	HORIZONTAL	Averag
4	4882.347	56.43	30.95	10.02	40.22	57.18	74.00	-16.82	HORIZONTAL	Peak
5	7323.199	23.90	35.74	12.93	39.22	33.35	54.00	-20.65	HORIZONTAL	Averag
6	7323.199	36.10	35.74	12.93	39.22	45.55	74.00	-28.45	HORIZONTAL	Peak
7	9764.294	20.45	37.70	14.45	37.90	34.70	54.00	-19.30	HORIZONTAL	Averag
8	9764.294	30.63	37.70	14.45	37.90	44.88	74.00	-29.12	HORIZONTAL	Peak
9	12205.350	21.44	39.21	16.05	38.10	38.60	54.00	-15.40	HORIZONTAL	Averag
10	12205.350	34.84	39.21	16.05	38.10	52.00	74.00	-22.00	HORIZONTAL	Peak
11	14646.250	20.99	41.52	18.30	38.45	42.36	54.00	-11.64	HORIZONTAL	Averag
12	14646.250	32.64	41.52	18.30	38.45	54.01	74.00	-19.99	HORIZONTAL	Peak

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	4027.554	29.32	29.52	9.02	40.07	27.79	54.00	-26.21	VERTICAL	Averag
2	4027.554	41.13	29.52	9.02	40.07	39.60	74.00	-34.40	VERTICAL	Peak
3	4882.647	39.55	30.95	10.02	40.22	40.30	54.00	-13.70	VERTICAL	Averag
4	4882.647	53.64	30.95	10.02	40.22	54.39	74.00	-19.61	VERTICAL	Peak
5	7323.654	25.35	35.74	12.93	39.22	34.80	54.00	-19.20	VERTICAL	Averag
6	7323.654	37.72	35.74	12.93	39.22	47.17	74.00	-26.83	VERTICAL	Peak
7	9764.524	21.74	37.70	14.45	37.90	35.99	54.00	-18.01	VERTICAL	Averag
8	9764.524	34.33	37.70	14.45	37.90	48.58	74.00	-25.42	VERTICAL	Peak
9	12205.470	22.57	39.21	16.05	38.10	39.73	54.00	-14.27	VERTICAL	Averag
10	12205.470	32.55	39.21	16.05	38.10	49.71	74.00	-24.29	VERTICAL	Peak
11	14646.660	20.45	41.52	18.30	38.45	41.82	54.00	-12.18	VERTICAL	Averag
12	14646.660	31.14	41.52	18.30	38.45	52.51	74.00	-21.49	VERTICAL	Peak



SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

Report No.: GZEM170700433201

Page: 37 of 46

FCC ID: 2ANH3MEDIDOR1B

Highest channel

	Freq	ReadAntenna Level Factor	Cable Preamp Loss Factor	Level	Limit	Over	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	3981.257	29.14	29.46	8.98	40.06	27.52	54.00	-26.48 HORIZONTAL Averag
2	3981.257	41.41	29.46	8.98	40.06	39.79	74.00	-34.21 HORIZONTAL Peak
3	4960.354	43.70	31.05	10.07	40.23	44.59	54.00	-9.41 HORIZONTAL Averag
4	4960.354	58.29	31.05	10.07	40.23	59.18	74.00	-14.82 HORIZONTAL Peak
5	7440.247	23.30	35.92	13.04	39.20	33.06	54.00	-20.94 HORIZONTAL Averag
6	7440.247	37.66	35.92	13.04	39.20	47.42	74.00	-26.58 HORIZONTAL Peak
7	9920.526	21.97	37.92	14.41	37.84	36.46	54.00	-17.54 HORIZONTAL Averag
8	9920.526	33.63	37.92	14.41	37.84	48.12	74.00	-25.88 HORIZONTAL Peak
9	12400.140	20.13	38.93	16.29	38.12	37.23	54.00	-16.77 HORIZONTAL Averag
10	12400.140	33.35	38.93	16.29	38.12	50.45	74.00	-23.55 HORIZONTAL Peak
11	14880.270	22.48	40.62	18.30	38.47	42.93	54.00	-11.07 HORIZONTAL Averag
12	14880.270	34.84	40.62	18.30	38.47	55.29	74.00	-18.71 HORIZONTAL Peak

	Freq	ReadAntenna Level Factor	Cable Preamp Loss Factor	Level	Limit	Over	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	4015.929	29.89	29.51	9.01	40.07	28.34	54.00	-25.66 VERTICAL Averag
2	4015.929	41.35	29.51	9.01	40.07	39.80	74.00	-34.20 VERTICAL Peak
3	4960.354	40.23	31.05	10.07	40.23	41.12	54.00	-12.88 VERTICAL Averag
4	4960.354	53.66	31.05	10.07	40.23	54.55	74.00	-19.45 VERTICAL Peak
5	7440.354	25.70	35.92	13.04	39.20	35.46	54.00	-18.54 VERTICAL Averag
6	7440.354	37.23	35.92	13.04	39.20	46.99	74.00	-27.01 VERTICAL Peak
7	9920.368	19.66	37.92	14.41	37.84	34.15	54.00	-19.85 VERTICAL Averag
8	9920.368	29.56	37.92	14.41	37.84	44.05	74.00	-29.95 VERTICAL Peak
9	12400.370	20.73	38.93	16.29	38.12	37.83	54.00	-16.17 VERTICAL Averag
10	12400.370	33.48	38.93	16.29	38.12	50.58	74.00	-23.42 VERTICAL Peak
11	14880.150	20.75	40.62	18.30	38.47	41.20	54.00	-12.80 VERTICAL Averag
12	14880.150	34.96	40.62	18.30	38.47	55.41	74.00	-18.59 VERTICAL Peak

7.8 Radiated Emissions which fall in the restricted bands

Test Requirement: FCC Part 15 C section 15.247

(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Test Method: ANSI C63.10.2013

Test Status: Enter test mode for the product. Test in lowest channel 2402 MHz and highest channel 2480 MHz, keep in continuously transmitting status with GFSK modulation.

Test site: Measurement Distance: 3m (Semi-Anechoic Chamber)

Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value

Detector: For PK value:

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For AV value:

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW = 10Hz


Sweep = auto

Detector function = peak


Trace = max hold

Test Configuration:

- 1). 30 MHz to 1 GHz emissions:



- 2). Above 1 GHz emissions:





Test Procedure:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2010 was used to perform radiated emission test above 1 GHz.

The receiver scanned from the lowest frequency generated within the EUT to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

From 30MHz to 1GHz, read the Quasi-Peak field strength of the emissions with receiver QP detector RBW=120KHz.

Above 1GHz, read the Peak field strength and Average field strength.

Read the Peak field strength through RBW=1MHz,VBW=3MHz in spectrum analyzer setting;

Read the Average field strength through RBW=1MHz,VBW=10Hz in spectrum analyzer setting;

While maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the average field strength reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit.

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section. only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
10.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		

Test Result:

30 MHz to 1 GHz Measurement

The measurements with Log antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

Above 1GHz, Peak & Average Measurement

Lowest channel

	Freq	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2310.000	29.57	26.25	6.80	39.07	23.55	54.00	-30.45	HORIZONTAL Average
2	2310.000	42.25	26.25	6.80	39.07	36.23	74.00	-37.77	HORIZONTAL Peak
3	2390.000	45.68	26.43	6.87	39.10	39.88	54.00	-14.12	HORIZONTAL Average
4	2390.000	62.09	26.43	6.87	39.10	56.29	74.00	-17.71	HORIZONTAL Peak
5	2483.500	44.70	26.58	7.07	39.14	39.21	54.00	-14.79	HORIZONTAL Average
6	2483.500	59.46	26.58	7.07	39.14	53.97	74.00	-20.03	HORIZONTAL Peak
7	2500.000	39.50	26.60	7.10	39.14	34.06	54.00	-19.94	HORIZONTAL Average
8	2500.000	53.11	26.60	7.10	39.14	47.67	74.00	-26.33	HORIZONTAL Peak

	Freq	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2310.000	30.48	26.25	6.80	39.07	24.46	54.00	-29.54	VERTICAL Average
2	2310.000	45.49	26.25	6.80	39.07	39.47	74.00	-34.53	VERTICAL Peak
3	2390.000	46.45	26.43	6.87	39.10	40.65	54.00	-13.35	VERTICAL Average
4	2390.000	64.19	26.43	6.87	39.10	58.39	74.00	-15.61	VERTICAL Peak
5	2483.500	48.69	26.58	7.07	39.14	43.20	54.00	-10.80	VERTICAL Average
6	2483.500	65.50	26.58	7.07	39.14	60.01	74.00	-13.99	VERTICAL Peak
7	2500.000	32.67	26.60	7.10	39.14	27.23	54.00	-26.77	VERTICAL Average
8	2500.000	55.73	26.60	7.10	39.14	50.29	74.00	-23.71	VERTICAL Peak

Highest channel

	Freq	ReadAntenna Level Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	2310.000	28.24	26.25	6.80	39.07	22.22	54.00	-31.78	HORIZONTAL Average
2	2310.000	41.86	26.25	6.80	39.07	35.84	74.00	-38.16	HORIZONTAL Peak
3	2390.000	40.23	26.43	6.87	39.10	34.43	54.00	-19.57	HORIZONTAL Average
4	2390.000	53.47	26.43	6.87	39.10	47.67	74.00	-26.33	HORIZONTAL Peak
5	2483.500	50.57	26.58	7.07	39.14	45.08	54.00	-8.92	HORIZONTAL Average
6	2483.500	66.19	26.58	7.07	39.14	60.70	74.00	-13.30	HORIZONTAL Peak
7	2500.000	37.60	26.60	7.10	39.14	32.16	54.00	-21.84	HORIZONTAL Average
8	2500.000	48.07	26.60	7.10	39.14	42.63	74.00	-31.37	HORIZONTAL Peak

	Freq	ReadAntenna Level Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	2310.000	33.47	26.25	6.80	39.07	27.45	54.00	-26.55	VERTICAL Average
2	2310.000	49.16	26.25	6.80	39.07	43.14	74.00	-30.86	VERTICAL Peak
3	2390.000	44.68	26.43	6.87	39.10	38.88	54.00	-15.12	VERTICAL Average
4	2390.000	58.83	26.43	6.87	39.10	53.03	74.00	-20.97	VERTICAL Peak
5	2483.500	50.68	26.58	7.07	39.14	45.19	54.00	-8.81	VERTICAL Average
6	2483.500	68.68	26.58	7.07	39.14	63.19	74.00	-10.81	VERTICAL Peak
7	2500.000	38.69	26.60	7.10	39.14	33.25	54.00	-20.75	VERTICAL Average
8	2500.000	51.41	26.60	7.10	39.14	45.97	74.00	-28.03	VERTICAL Peak

Test result: The unit does meet the FCC requirements.

7.9 Band Edges Requirement

Test Requirement: FCC Part 15 C section 15.247


(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Frequency Band: 2400 MHz to 2483.5 MHz

Test Method: ANSI C63.10: Clause 11.13

Test Status: Enter test mode for the product. Test in lowest channel 2402 MHz and highest channel 2480 MHz, keep in continuously transmitting status with GFSK modulation.

Test Configuration:





Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set instrument center frequency to the frequency of the emission to be measured(must be within 2MHz of the authorized band edge).
3. Set span (wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.),
4. RBW=100kHz,
5. VBW $\geq$ 3 $\times$ RBW
6. Detector=peak
7. Sweep time =auto,
8. Trace mode=max hold.
9. Allow sweep to continue until the trace stabilizes(required measurement time may increase for low duty cycle applications)
10. Compute the power by integrating the spectrum over 1MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency(f_{emission}) $\pm$ 0.5MHz.If the instrument does not have a band power function,the sum the amplitude levels(in power units) at 100kHz intervals extending across the 1MHz spectrum defined by femission $\pm$ 0.5MHz.




Test result with plots as follows:

Compare with the output power of the lowest frequency, the Lower Edges attenuated more than 20dB


Compare with the output power of the highest frequency, the Upper Edges attenuated more than 20dB.

Result plot as follows:

Channel 0: 2.402 GHz



Channel 39: 2.480GHz



--End of Report--