

ISSUED BY Shenzhen BALUN Technology Co., Ltd.



FOR

Woobo Smart Robot

ISSUED TO Woobo Inc

198 River st. Cambridge, Massachusetts 02139, United States



Tested by: Hu Chao
Hu Chao
(Engineer)
Date Dec. 13, 2018

Approved by: Wei Yanquan
(Chief Engineer)
Date Dec. 15, 2018

Report No.: BL-HK18B0009-601
EUT Name: Woobo Smart Robot
WOOBO MINI
Brand Name: WOOBO

Test Standard: 47 CFR Part 15 Subpart C

FCC ID: 2ANIX-0003

Test Conclusion: Pass

Test Date: Nov. 05, 2018 ~ Dec. 08, 2018

Date of Issue: Dec. 13, 2018

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.



Revision History

VersionIssue DateRevisions ContentRev. 01Dec. 10, 2018Initial Issue

Rev. 02 Dec. 13, 2018

Add the channel list on page 7.delete the KDB 662911 and update the Conducted Emission test item on page 10 and page 50.update the band-edge on page 48.

TABLE OF CONTENTS

ADMIN	ISTRATIVE DATA (GENERAL INFORMATION)	5
1.1	Identification of the Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Laboratory Condition	5
1.4	Announce	5
PRODU	JCT INFORMATION	6
2.1	Applicant Information	6
2.2	Manufacturer Information	6
2.3	Factory Information	6
2.4	General Description for Equipment under Test (EUT)	6
2.5	Ancillary Equipment	6
2.6	Technical Information	7
2.7	Additional Instructions	9
SUMMA	ARY OF TEST RESULTS	. 10
3.1	Test Standards	. 10
3.2	Verdict	. 10
GENEF	RAL TEST CONFIGURATIONS	. 11
4.1	Test Environments	. 11
4.2	Test Equipment List	. 11
4.3	Measurement Uncertainty	. 13
4.4	Description of Test Setup	. 13
4.4.1	For Antenna Port Test	. 13
4.4.2	For AC Power Supply Port Test	. 14
4.4.3	For Radiated Test (Below 30 MHz)	. 14
	1.1 1.2 1.3 1.4 PRODU 2.1 2.2 2.3 2.4 2.5 2.6 2.7 SUMMA 3.1 3.2 GENER 4.1 4.2 4.3 4.4 4.4.1 4.4.2	1.1 Identification of the Testing Laboratory 1.2 Identification of the Responsible Testing Location 1.3 Laboratory Condition 1.4 Announce PRODUCT INFORMATION 2.1 Applicant Information 2.2 Manufacturer Information 2.3 Factory Information 2.4 General Description for Equipment under Test (EUT) 2.5 Ancillary Equipment 2.6 Technical Information 2.7 Additional Instructions SUMMARY OF TEST RESULTS 3.1 Test Standards 3.2 Verdict GENERAL TEST CONFIGURATIONS 4.1 Test Environments 4.2 Test Equipment List 4.3 Measurement Uncertainty 4.4 Description of Test Setup 4.4.1 For Antenna Port Test 4.4.2 For AC Power Supply Port Test.



	4.4.4	For Radiated Test (30 MHz-1 GHz)	. 15
	4.4.5	For Radiated Test (Above 1 GHz)	. 15
4	4.5	Measurement Results Explanation Example	. 16
	4.5.1	For conducted test items:	. 16
	4.5.2	For radiated band edges and spurious emission test:	. 16
5	TEST I	TEMS	. 17
į	5.1	Antenna Requirements	. 17
	5.1.1	Relevant Standards	. 17
	5.1.2	Antenna Anti-Replacement Construction	. 17
	5.1.3	Antenna Gain	. 18
į	5.2	Output Power	. 19
	5.2.1	Test Limit	. 19
	5.2.2	Test Setup	. 19
	5.2.3	Test Procedure	. 19
	5.2.4	Test Result	. 20
į	5.3	6dB Bandwidth	. 21
	5.3.1	Limit	. 21
	5.3.2	Test Setup	. 21
	5.3.3	Test Procedure	. 21
	5.3.4	Test Result	. 21
į	5.4	Conducted Spurious Emission	. 22
	5.4.1	Limit	. 22
	5.4.2	Test Setup	. 22
	5.4.3	Test Procedure	. 22
	5.4.4	Test Result	. 23
į	5.5	Band Edge (Authorized-band band-edge)	. 24
	5.5.1	Limit	. 24
	5.5.2	Test Setup	. 24
	5.5.3	Test Procedure	. 24
	5.5.4	Test Result	. 25
į	5.6	Conducted Emission	. 26
	5.6.1	Limit	. 26



5.6.2	Test Setup	26
5.6.3	Test Procedure	26
5.6.4	Test Result	26
5.7	Radiated Spurious Emission	27
5.7.1	Limit	27
5.7.2	Test Setup	27
5.7.3	Test Procedure	27
5.7.4	Test Result	30
5.8	Band Edge (Restricted-band band-edge)	31
5.8.1	Limit	31
5.8.2	Test Setup	31
5.8.3	Test Procedure	31
5.8.4	Test Result	31
5.9	Power Spectral density (PSD)	32
5.9.1	Limit	32
5.9.2	Test Setup	32
5.9.3	Test Procedure	32
5.9.4	Test Result	32
ANNEX A	TEST RESULT	33
A.1	Output Power	33
A.2	Bandwidth	34
A.3	Conducted Spurious Emissions	39
A.4	Band Edge (Authorized-band band-edge)	46
A.5	Conducted Emissions	49
A.6	Radiated Emission	50
A.7	Band Edge (Restricted-band band-edge)	61
A.8	Power Spectral Density (PSD)	65
ANNEX B	TEST SETUP PHOTOS	68
ANNEX C	EUT EXTERNAL PHOTOS	68
ANNEX D	EUT INTERNAL PHOTOS	68



1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road,
Address	Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

entineation of the	Responsible resting Location
Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road,
Address	Nanshan District, Shenzhen, Guangdong Province, P. R. China
	The laboratory has been listed by Industry Canada to perform
	electromagnetic emission measurements. The recognition numbers of
	test site are 11524A-1.
	The laboratory is a testing organization accredited by FCC as a
Accreditation	accredited testing laboratory. The designation number is CN1196.
	The laboratory is a testing organization accredited by American
Certificate	Association for Laboratory Accreditation(A2LA) according to ISO/IEC
	17025.The accreditation certificate is 4344.01.
	The laboratory is a testing organization accredited by China National
	Accreditation Service for Conformity Assessment (CNAS) according to
	ISO/IEC 17025. The accreditation certificate number is L6791.
	All measurement facilities used to collect the measurement data are
Description	located at Block B, FL 1, Baisha Science and Technology Park, Shahe
Description	Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R.
	China 518055

1.3 Laboratory Condition

_	and of the state o		
	Ambient Temperature	20°C to 25°C	
	Ambient Relative Humidity	45% to 55%	
	Ambient Pressure	100 kPa to 102 kPa	

1.4 Announce

- (1) The test report reference to the report template version v6.2.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.



2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Woobo Inc.
Address	198 River st. Cambridge, Massachusetts 02139, United States

2.2 Manufacturer Information

Manufacturer	Shenzhen Somy Technology Co., Ltd
Address	Building P No.10, Eastern, ShangXue Industrial PARK, BanTian,
Address	Long Gang District

2.3 Factory Information

Factory	Shenzhen Somy Technology Co., Ltd
Addross	Building P No.10, Eastern, ShangXue Industrial PARK, BanTian,
Address	Long Gang District

2.4 General Description for Equipment under Test (EUT)

EUT Name	Woobo Smart Robot
Model Name Under Test	WOOBO MINI
Series Model Name	N/A
Description of Model	N/A
name differentiation	N/A
Hardware Version	ET620-MB-V0.2
Software Version	zhuque_wifi_audio_803_20180910_V4.1
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Ancillary Equipment

Note: not applicable.



2.6 Technical Information

1	Network and Wireless	WIFI 802.11b, 802.11g and 802.11n (HT20)
C	connectivity	Wil 1 602.11b, 602.11g and 602.11ii (11120)

The requirement for the following technical information of the EUT was tested in this report:

all emerit for the following teermoon method for the Let was tested in this report.			
	802.11b/g/n(20 MHz): 2.412 GHz - 2.462 GHz		
Francisco Dance	f _c = 2412 MHz + (N-1)*5 MHz, where		
Frequency Range	- f _c = "Operating Frequency" in MHz,		
	- N = "Channel Number" with the range from 1 to 11.		
Modulation Type	DSSS, OFDM		
	☐ Mobile		
Product Type	□ Portable		
,,	☐ Fix Location		
Antenna System (eg., MIMO,	NI/Λ		
Smart Antenna)	N/A		
Categorization as Correlated or	N/A		
Completely Uncorrelated	IN/A		
Antenna Type	PIFA Antenna		
Antenna Gain	1.8 dBi		
USB Port	USB port is only used for factory debugging and upgrade,		
OOD FOIL	and cannot be used by end-user.		
About the Product	Only the WIFI 802.11b, 802.11g and 802.11n (HT20) was		
About the Floudet	tested in this report.		
	tested in this report.		

All channel was listed on the following table, the three bolded channels is the test channel:

Channel	Freq.	Channel	Freq.	Channel	Freq.	Channel	Freq.
number	(MHz)	number	(MHz)	number	(MHz)	number	(MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	/	1

Modulation technology	Modulation Type	Transfer Rate (Mbps)
	DBPSK	1
DSSS (802.11b)	DQPSK	2
	CCK	5.5/ 11
	BPSK	6 / 9
OFDM (802.11g)	QPSK	12 / 18
OFDW (802.11g)	16QAM	24 / 36
	64QAM	48 / 54
	BPSK	6.5
OFDM	QPSK	13/19.5
(802.11n-20MHz)	16QAM	26/39
	64QAM	52/58.5/65



Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Output Power	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11
6dB Bandwidth	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11
Conducted Spurious Emission	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11
Conducted Emission	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11
Radiated Spurious Emission	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11
Band Edge	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11
Power spectral density (PSD)	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11

Note: The above EUT information in section 2.4 and 2.6 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.



2.7 Additional Instructions

EUT Software Settings:


Mada	\boxtimes	Special software is used.
		The software provided by client to enable the EUT under
Mode		transmission condition continuously at specific channel
		frequencies individually.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

EUT Software Settings:

Power level setup in software				
Test Software Version XShell				
Mode	Channel	Soft Set		
802.11 b	All	3030		
802.11 g	All	5B60		
802.11 n20	All	5B60		

Run software:





3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
	47 CFR Part 15,	
1	Subpart C	Miscellaneous Wireless Communications Services
	(10-1-17)	
		GUIDANCE FOR COMPLIANCE MEASUREMENTS ON
2	KDB Publication	DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD
	558074 D01v05	SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING
		UNDER SECTION 15.247 OF THE FCC RULES
3	ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of
3	ANSI C03. 10-2013	Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC PART No.	Test Result	Verdict
1	Antenna Requirement	15.203; 15.247(b)	N/A	Pass ^{Note 1}
2	Output Power	15.247(b)	ANNEX A.1	Pass
3	6dB Bandwidth	15.247(a)	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	ANNEX A.3	Pass
5	Band Edge(Authorized-band	15.209; 15.247(d)	ANNEX A.4	Pass
	band-edge)	45.005	441415774.5	Nuta Nata 2
6	Conducted Emission	15.207	ANNEX A.5	N/A Note 3
7	Radiated Spurious Emission	15.209; 15.247(d)	ANNEX A.6	Pass
8	Band Edge(Restricted-band	15.209; 15.247(d)	ANNEX A.7	Pass
0	band-edge)	15.209, 15.247(u)	AININEA A.7	
9	Power spectral density (PSD)	15.247(e)	ANNEX A.8	Pass
10	Receiver Spurious Emissions	N/A	N/A	N/A Note 2

Note ¹: Please refer to section 5.1.

Note ²: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

Note ³: The EUT only powered by battery, USB port is only used for factory debugging and upgrade, and cannot be used by end-user.



4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%		
Atmospheric Pressure	100 kPa - 102 kPa		
Temperature	NT (Normal Temperature)	+22°C to +25°C	
Working Voltage of the EUT	NV (Normal Voltage)	6 V	

4.2Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2018.06.15	2019.06.14
Switch Unit with OSP- B157	ROHDE&SCHWARZ	OSP120	101270	2018.06.15	2019.06.14
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2018.11.07	2019.11.06
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2018.06.13	2019.06.12
LISN	SCHWARZBECK	NSLK 8127	8127-687	2018.06.13	2019.06.12
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2018.06.15	2019.06.14
Power Splitter	KMW	DCPD-LDC	1305003215		
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2018.06.15	2019.06.14
Attenuator (20 dB)	KMW	ZA-S1-201	110617091		
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189		
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2018.06.14	2019.06.13
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2018.06.26	2019.06.25
Test Antenna- Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2017.11.09	2019.11.08
Test Antenna- Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2017.07.22	2019.07.21
Test Antenna- Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2018.07.11	2020.07.10
Test Antenna- Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2018.06.21	2019.06.20
Test Antenna- Horn (18-40 GHz)	A-INFO	LB- 180400KF	J211060273	2017.01.06	2019.01.05
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2019.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60 *7.35m	N/A	2017.08.08	2019.08.07
Shielded Enclosure	ChangNing	CN-130701	130703		
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2018.06.15	2019.06.14
Power Amplifier	OPHIR RF	5225F	1037	2018.02.16	2019.02.15
Power Amplifier	OPHIR RF	5273F	1016	2018.02.16	2019.02.15
Directional Coupler	Werlantone	C5982-10	109275	N/A	N/A



			0 1 111	0.15.4	
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Directional Coupler	Werlantone	CHP-273E	S00801z-01	N/A	N/A
Feld Strength Meter	Narda	EP601	511WX51129	2018.05.21	2019.05.20
Mouth Simulator	B&K	4227	2423931	2018.11.15	2019.11.14
Sound Calibrator	B&K	4231	2430337	2018.11.15	2019.11.14
Sound Level Meter	B&K	NL-20	00844023	2018.11.15	2019.11.14
Ear Simulator	B&K	4185	2409449	2018.11.15	2019.11.14
Ear Simulator	B&K	4195	2418189	2018.11.15	2019.11.14
Audio analyzer	B&K	UPL 16	100129	2018.11.15	2019.11.14
Amplifier	COM-MW	KL_LNA_18 -40G-01	N/A	2018.06.26	2019.06.25
RF Cable 1	ROHDE&SCHWARZ	JUNFLON	APR0914004	2018.07.10	2019.10.09
RF Cable 2	Huber&suhner	RG_400_/U	N/A	2018.07.10	2019.10.09
RF Cable 3	Huber&suhner	RG_400_/U	N/A	2018.07.10	2019.10.09
RF Cable 4	Huber&suhner	SX_04172_ B-60	N/A	2018.07.10	2019.10.09
RF Cable 5	COM-MW	RFJA360- 2.92mm- J/J3M	N/A	2018.07.10	2019.10.09
Note: The calibration per	riod on the Cable is thre	e month.			



4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


Measurement	Value
Occupied Channel Bandwidth	±4%
RF output power, conducted	±1 .4 dB
Power Spectral Density, conducted	±2.5 dB
Unwanted Emissions, conducted	±2.8 dB
All emissions, radiated	±5.4 dB
Temperature	±1°C
Humidity	±4%

4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT: Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm



(Diagram 1)




4.4.2 For AC Power Supply Port Test



(Diagram 2)


4.4.3 For Radiated Test (Below 30 MHz)



(Diagram 3)




4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)



4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.5.2 For radiated band edges and spurious emission test:

$$E = EIRP - 20log D + 104.8$$

where:

E = electric field strength in $dB\mu V/m$,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP= Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)



5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (6)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.


If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
Compliance with 15.203, use of a	
standard antenna jack or electrical	The antenna is the unique connector with a wire antenna.
connector is prohibited.	





5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b); RSS-247, 5.4 (4)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Maximum conducted (average) output power (Reporting Only)

- a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.
- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
- At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.
- c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- d) Adjust the measurement in dBm by adding 10log (1/x), where x is the duty cycle to the measurement result.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.



Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value.

Set VBW ≥ RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T \leq 16.7 microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.



5.36dB Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-GEN, 6.6

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) \geq 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.



5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to \geq 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW \geq 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.



Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW \geq 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.



5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-GEN, 8.9, RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle \geq 98%). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than \pm 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW \geq 3 x RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) \pm 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission \pm 0.5 MHz.

Standard method(The 99% OBW of the fundamental emission is without 2 MHz of the authorized band):

Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.



Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.5.2.

Attenuation: Auto (at least 10 dB preferred).

Sweep time: Coupled.

Resolution bandwidth: 100 kHz.

Video bandwidth: 300 kHz.

Detector: Peak.

Trace: Max hold.

5.5.4 Test Result

Please refer to ANNEX A.4.



5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a $50\mu\text{H}/50\Omega$ line impedance stabilization network (LISN).

Frequency range	Conducted Limit (dBμV)		
(MHz)	Quai-peak	Average	
0.15 - 0.50	66 to 56	56 to 46	
0.50 - 5	56	46	
0.50 - 30	60	50	

5.6.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.



5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(c); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

- For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
- For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands

a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).



- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

E = EIRP - 20log D + 104.8

where:

 $E = electric field strength in dB\mu V/m$,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW \geq 3 x RBW.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz



> 1000 MHz	1 MHz
------------	-------

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle \geq 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than \pm 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x, of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW \geq 3 x RBW.
- e) Detector = RMS, if span/(# of points in sweep) ≤ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
- 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
- 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
- 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
- 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
- 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).



Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \ge 1$ GHz, 100 kHz for f < 1 GHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.



5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(c); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.



5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(d); RSS-247, 5.2 (2)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.9.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz \leq RBW \leq 100 kHz.

Set the VBW \geq 3 RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.



ANNEX A TEST RESULT

A.1 Output Power

Duty Cycle

Test Mode	Duty Cycle	T (ms)	1/T(kHz)
802.11b	1.00	1	1.0
802.11g	1.00	1	1.0
802.11n-20 MHz	1.00	1	1.0

Average Power Test Data

802.11b Mode:

Channel	Measured Outpu	t Average Power	Limit		Verdict
Chamer	dBm	mW	dBm	mW	Veruici
Low	9.48	8.87			Pass
Middle	9.45	8.81	30	1000	Pass
High	8.99	7.93			Pass

802.11g Mode:

Channal	Measured Outpu	t Average Power	Limit		Vardiat
Channel	dBm	mW	dBm	mW	Verdict
Low	9.18	8.28	30	1000	Pass
Middle	9.13	8.18			Pass
High	8.67	7.36			Pass

802.11n-20 MHz Mode:

Channel	Measured Outpu	t Average Power	Limit		Vardiet
	dBm	mW	dBm	mW	Verdict
Low	9.71	9.35		1000	Pass
Middle	9.15	8.22	30		Pass
High	9.19	8.30			Pass



A.2 Bandwidth

Test Data

802.11b Mode:

	Channel	6 dB Bandwidth	99% Bandwidth	6 dB Bandwidth
		(MHz)	(MHz)	Limits (kHz)
Ī	Low	10.162598	15.340087	≥500
Ī	Middle	10.162598	15.2822	≥500
	High	10.162598	15.2822	≥500

802.11g Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	16.470703	17.713459	≥500
Middle	16.470703	17.655572	≥500
High	16.470703	17.713459	≥500

802.11n-20MHz Mode:

Channe	el	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low		17.671875	18.465991	≥500
Middle)	17.671875	18.465991	≥500
High		17.671875	18.408104	≥500




Test plots


6 dB Bandwidth

802.11b LOW CHANNEL ₩ SGL Count 50/50 1Pk Max 0,79 dB) 2,4869187 GH 8 12 (lB) 2,4114750 GH 20 dBm-M2[1] ms mail 10 dBmdem--10 d8m--20 dBmum my -50 d8m -60 dBm-CF 2.412 GHz 800 pt Span 40.0 MHz Type | Ref | Trc | **Function Result** D1 M1 M2 Date: 5 NOV.2018 10:51:45


802.11b MIDDLE CHANNEL




802.11b HIGH CHANNEL



802.11g LOW CHANNEL



802.11g MIDDLE CHANNEL



802.11g HIGH CHANNEL







802.11n-20 MHz LOW CHANNEL

SEL Count 50/50 ### SEL Count 50/50 ### SER WIND HEZ ### SEL Count 50/50 ### SER WIND HEZ ### ma ∇ -5,60 dB) 2,4831641 GH B,40 dB) 2,4144750 GH M2[1] 10 dBmdBm--10 dBm -30 d8m-Warrange -50 dBm--60 dBm-Span 40.0 MHz CF 2.412 GHz 800 pts Y-value Function -5.80 dBm -0.32 dB 0.40 dBm X-value 2.4031641 GHz 17.6719 MHz 2.414475 GHz Type | Ref | Trc | **Function Result** D1 M1 M2 Date: 5.NOV.2018 12:51:13

802.11 n-20 MHz MIDDLE CHANNEL



802.11n-20 MHz HIGH CHANNEL





99% Bandwidth


802.11b LOW CHANNEL



802.11b MIDDLE CHANNEL



Date: 5.NOV.2018 10:51:54





802.11g MIDDLE CHANNEL



802.11g HIGH CHANNEL




Date: 5.NOV.2018 12:49:21




802.11n-20 MHz LOW CHANNEL

T V -30,45 dbr 2,4820000 GH 18,465991317 MH 10 d8mn dam--10 dBm--20 dBm--30 d8m -40 dBm--50 d8m--60 dBm--70 d8m-CF 2.412 GHz Span 40.0 MHz 691 pts X-value 2.432 GHz 2.4027381 GHz 2.4212041 GHz Y-value -30.43 dBm -2.54 dBm -2.64 dBm Type | Ref | Trc | Function **Function Result** 18.465991317 MHz Date: 5.NOV.2018 12:51:22

802.11 n-20 MHz MIDDLE CHANNEL



802.11n-20 MHz HIGH CHANNEL



Date: 5.NOV.2018 12:55:32



A.3 Conducted Spurious Emissions

Test Data

802.11b Mode:

	Measured Max. Out of	Limit (d	V	
Channel	Band Emission (dBm)	Carrier Level	Calculated 30 dBc Limit	Verdict
Low	-49.12	8.21	-21.79	Pass
Middle	-47.68	8.11	-21.89	Pass
High	-50.86	6.54	-23.46	Pass

802.11g Mode:

	Measured Max. Out of	Limit (Limit (dBm)				
Channel	Band Emission (dBm)	Carrier Level	Calculated 30 dBc Limit	Verdict			
Low	-50.22	0.70	-29.3	Pass			
Middle	-50.87	0.74	-29.26	Pass			
High	-50.78	0.17	-29.83	Pass			

802.11n-20MHz Mode:

Channel	Measured Max. Out of	Limit (d	Marshall	
	Band Emission (dBm)	Carrier Level	Calculated 30 dBc Limit	Verdict
Low	-51.04	0.72	-29.28	Pass
Middle	-50.08	0.53	-29.47	Pass
High	-50.91	0.06	-29.94	Pass




Test Plots

802.11b LOW CHANNEL CARRIER LEVEL



802.11b LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz

802.11b LOW CHANNEL, SPURIOUS 2 GHz \sim 25 GHz




802.11b MIDDLE CHANNEL CARRIER LEVEL






802.11b MIDDLE CHANNEL, SPURIOUS




802.11b MIDDLE CHANNEL, SPURIOUS






802.11b HIGH CHANNEL, SPURIOUS



802.11b HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz







802.11g LOW CHANNEL CARRIER LEVEL




802.11g LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11g LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11g MIDDLE CHANNEL CARRIER LEVEL







802.11g MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11g MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11g HIGH CHANNEL CARRIER LEVEL



802.11g HIGH CHANNEL, SPURIOUS




802.11g HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz






802.11n-20 LOW CHANNEL CARRIER LEVEL




802.11n-20 LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz

| Spectrum | Ref Level | 15.00 d8m | RBW | 100 kHz | TUP | RBW | 100 kHz | TUP | RBW | 100 kHz | RBW | RBW | 100 kHz | RBW | RBW

802.11n-20 LOW CHANNEL, SPURIOUS 2 GHz \sim 25 GHz




802.11n-20 MIDDLE CHANNEL CARRIER LEVEL







802.11n-20 MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-20 MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11n-20 HIGH CHANNEL CARRIER LEVEL



802.11n-20 HIGH CHANNEL, SPURIOUS



802.11n-20 HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz





A.4 Band Edge (Authorized-band band-edge)

Test Data

Note: The 99% OBW of the fundamental emission is without 2 MHz of the authorized band.

802.11b Mode:

	Measured Max. Band	Limit		
Channel	Edge Emission (dBm)	Carrier Level	Calculated 30 dBc Limit	Verdict
Low Channel	-25.72	8.21	-21.79	Pass
High Channel	-47.84	6.54	-23.46	Pass

802.11g Mode:

		Magazirad May Dand	Limit	Limit (dBm)				
Channel	Measured Max. Band Edge Emission (dBm)	Carrier Level	Calculated 30 dBc Limit	Verdict				
Low Cha	nnel	-37.08	0.70	-29.3	Pass			
High Cha	annel	-45.61	0.17	-29.83	Pass			

802.11n-20 MHz Mode:

	Measured Max. Band	Limit	(dBm)	
Channel	Edge Emission (dBm)	Carrier Level	Calculated 30 dBc Limit	Verdict
Low Channel	-36.72	0.72	-29.28	Pass
High Channel	-42.93	0.06	-29.94	Pass



Test Plots

802.11b LOW CHANNEL, Carrier level



802.11b LOW CHANNEL, Band Edge



802.11b HIGH CHANNEL, Carrier level




802.11b HIGH CHANNEL, Band Edge



802.11g LOW CHANNEL, Carrier level




802.11g LOW CHANNEL, Band Edge





802.11g HIGH CHANNEL. Carrier level



802.11g HIGH CHANNEL, Band Edge




802.11n-20 MHz LOW CHANNEL, Carrier level



802.11n-20 MHz LOW CHANNEL, Band Edge



802.11n-20 MHz HIGH CHANNEL, Carrier level



802.11n-20 MHz HIGH CHANNEL, Band Edge





A.5 Conducted Emissions

Note: this test item is not applicable.



A.6 Radiated Emission


Note ¹: The symbol of "--" in the table which means not application.

Note ²: For the test data above 1 GHz, According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


Note ⁴: The EUT is working in the Normal link mode below 1 GHz.

Test Data and Plots



No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	136.215	14.21	-26.96	33.5	-19.29	Peak	218.00	400	Н	Pass
2	320.030	19.48	-25.30	36.0	-16.52	Peak	360.00	400	Н	Pass
3	420.182	20.43	-22.41	36.0	-15.57	Peak	205.00	200	Н	Pass
4	480.080	26.04	-21.01	36.0	-9.96	Peak	73.00	200	Н	Pass
5	503.845	24.79	-20.50	36.0	-11.21	Peak	250.00	100	Н	Pass
6	639.995	37.76	-17.06	36.0	-0.76	Peak	98.00	123	Н	Pass
6*	639.995	36.76	-17.06	36.0	-1.14	QP	98.00	123	Н	Pass





No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	60.797	15.54	-27.99	30.0	-14.46	Peak	360.00	200	V	Pass
2	87.957	18.03	-31.09	30.0	-11.97	Peak	360.00	200	V	Pass
3	116.573	20.25	-28.26	33.5	-13.25	Peak	360.00	200	V	Pass
4	157.070	17.51	-25.79	33.5	-15.99	Peak	360.00	200	V	Pass
5	320.030	16.45	-25.30	36.0	-19.55	Peak	360.00	200	V	Pass
6	639.887	28.52	-17.07	36.0	-7.48	Peak	167.00	400	V	Pass



Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 12.75GHz-25GHz is noise only, do not show on the report.

1 GHz to 25 GHz, ANT V 802.11b Low Channe

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	31.11	-18.23	54.0	-22.89	AV	165.00	150	V	Pass
1	1080.000	39.29	-18.23	74.0	-34.71	Peak	165.00	150	V	Pass
2**	1743.500	44.73	-17.03	54.0	-9.27	AV	170.00	150	V	Pass
2	1743.500	53.34	-17.03	74.0	-20.66	Peak	170.00	150	V	Pass
3**	2415.000	88.36	-12.56	54.0	34.36	AV	73.00	150	V	N/A
3	2415.000	92.62	-12.56	74.0	18.62	Peak	73.00	150	V	N/A
4**	6667.000	44.28	1.87	54.0	-9.72	AV	69.00	150	V	Pass
4	6667.000	54.58	1.87	74.0	-19.42	Peak	69.00	150	V	Pass
5**	9471.062	38.48	-0.15	54.0	-15.52	AV	79.00	150	V	Pass
5	9471.062	49.88	-0.15	74.0	-24.12	Peak	79.00	150	V	Pass
6**	11817.062	39.42	1.14	54.0	-14.58	AV	320.00	150	V	Pass
6	11817.062	50.84	1.14	74.0	-23.16	Peak	320.00	150	V	Pass

1 GHz to 25 GHz, ANT H 802.11b Low Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	33.21	-18.23	54.0	-20.79	AV	251.00	150	Н	Pass
1	1080.000	40.84	-18.23	74.0	-33.16	Peak	251.00	150	Н	Pass
2**	1675.000	28.32	-17.06	54.0	-25.68	AV	118.00	150	Н	Pass
2	1675.000	42.61	-17.06	74.0	-31.39	Peak	118.00	150	Н	Pass
3**	2415.000	87.95	-12.56	54.0	33.95	AV	103.00	150	Н	N/A
3	2415.000	92.37	-12.56	74.0	18.37	Peak	103.00	150	Н	N/A
4**	4978.000	38.87	-2.87	54.0	-15.13	AV	232.00	150	Н	Pass
4	4978.000	50.79	-2.87	74.0	-23.21	Peak	232.00	150	Н	Pass
5**	6677.000	43.94	1.67	54.0	-10.06	AV	360.00	150	Н	Pass
5	6677.000	54.98	1.67	74.0	-19.02	Peak	360.00	150	Н	Pass
6**	11897.562	40.61	2.22	54.0	-13.39	AV	361.00	150	Н	Pass
6	11897.562	51.00	2.22	74.0	-23.00	Peak	361.00	150	Н	Pass



1 GHz to 25 GHz, ANT V 802.11b Middle Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	31.35	-18.23	54.0	-22.65	AV	166.00	150	V	Pass
1	1080.000	39.24	-18.23	74.0	-34.76	Peak	166.00	150	V	Pass
2**	1644.500	32.71	-17.29	54.0	-21.29	AV	153.00	150	V	Pass
2	1644.500	51.81	-17.29	74.0	-22.19	Peak	153.00	150	V	Pass
3**	2440.000	87.92	-12.82	54.0	33.92	AV	240.00	150	V	N/A
3	2440.000	92.19	-12.82	74.0	18.19	Peak	240.00	150	V	N/A
4**	4874.000	39.58	-2.60	54.0	-14.42	AV	306.00	150	V	Pass
4	4874.000	51.62	-2.60	74.0	-22.38	Peak	306.00	150	V	Pass
5**	6680.000	44.44	1.53	54.0	-9.56	AV	14.00	150	V	Pass
5	6680.000	54.80	1.53	74.0	-19.20	Peak	14.00	150	V	Pass
6**	11446.187	39.47	0.33	54.0	-14.53	AV	75.00	150	V	Pass
6	11446.187	51.41	0.33	74.0	-22.59	Peak	75.00	150	V	Pass

1 GHz to 25 GHz. ANT H 802.11b Middle Channe

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	33.61	-18.23	54.0	-20.39	AV	211.00	150	Н	Pass
1	1080.000	40.52	-18.23	74.0	-33.48	Peak	211.00	150	Н	Pass
2**	2129.000	30.92	-14.16	54.0	-23.08	AV	236.00	150	Н	Pass
2	2129.000	47.49	-14.16	74.0	-26.51	Peak	236.00	150	Н	Pass
3**	2440.000	87.39	-12.82	54.0	33.39	AV	107.00	150	Н	N/A
3	2440.000	91.64	-12.82	74.0	17.64	Peak	107.00	150	Н	N/A
4**	4643.000	38.12	-3.55	54.0	-15.88	AV	282.00	150	Н	Pass
4	4643.000	49.71	-3.55	74.0	-24.29	Peak	282.00	150	Н	Pass
5**	6662.000	44.06	1.74	54.0	-9.94	AV	321.00	150	Н	Pass
5	6662.000	54.64	1.74	74.0	-19.36	Peak	321.00	150	Н	Pass
6**	10994.813	39.58	-0.27	54.0	-14.42	AV	136.00	150	Н	Pass
6	10994.813	50.08	-0.27	74.0	-23.92	Peak	136.00	150	Н	Pass



1 GHz to 25 GHz, ANT V 802.11b High Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	31.40	-18.23	54.0	-22.60	AV	169.00	150	V	Pass
1	1080.000	39.26	-18.23	74.0	-34.74	Peak	169.00	150	V	Pass
2**	1643.500	30.52	-17.21	54.0	-23.48	AV	169.00	150	V	Pass
2	1643.500	54.11	-17.21	74.0	-19.89	Peak	169.00	150	V	Pass
3**	2465.000	88.09	-12.05	54.0	34.09	AV	299.00	150	V	N/A
3	2465.000	92.23	-12.05	74.0	18.23	Peak	299.00	150	V	N/A
4**	4924.000	38.14	-3.41	54.0	-15.86	AV	285.00	150	V	Pass
4	4924.000	50.61	-3.41	74.0	-23.39	Peak	285.00	150	V	Pass
5**	6672.000	44.59	2.00	54.0	-9.41	AV	353.00	150	V	Pass
5	6672.000	54.63	2.00	74.0	-19.37	Peak	353.00	150	V	Pass
6**	10608.125	39.18	-1.01	54.0	-14.82	AV	8.00	150	V	Pass
6	10608.125	50.33	-1.01	74.0	-23.67	Peak	8.00	150	V	Pass

1 GHz to 25 GHz, ANT H 802.11b High Channe

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	33.56	-18.23	54.0	-20.44	AV	246.00	150	Н	Pass
1	1080.000	40.41	-18.23	74.0	-33.59	Peak	246.00	150	Н	Pass
2**	1440.000	29.05	-17.32	54.0	-24.95	AV	355.00	150	Н	Pass
2	1440.000	40.44	-17.32	74.0	-33.56	Peak	355.00	150	Н	Pass
3**	1642.500	27.50	-17.14	54.0	-26.50	AV	115.00	150	Н	Pass
3	1642.500	43.23	-17.14	74.0	-30.77	Peak	115.00	150	Н	Pass
4**	2465.000	87.61	-12.05	54.0	33.61	AV	109.00	150	Н	N/A
4	2465.000	91.60	-12.05	74.0	17.60	Peak	109.00	150	Н	N/A
5**	6675.000	44.59	1.88	54.0	-9.41	AV	-2.00	150	Н	Pass
5	6675.000	54.49	1.88	74.0	-19.51	Peak	-2.00	150	Н	Pass
6**	10614.125	40.18	-1.06	54.0	-13.82	AV	16.00	150	Н	Pass
6	10614.125	51.33	-1.06	74.0	-22.67	Peak	16.00	150	Н	Pass



1 GHz to 25 GHz, ANT V 802.11g Low Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	31.30	-18.23	54.0	-22.70	AV	164.00	150	V	Pass
1	1080.000	38.73	-18.23	74.0	-35.27	Peak	164.00	150	V	Pass
2**	1666.000	32.89	-17.16	54.0	-21.11	AV	164.00	150	V	Pass
2	1666.000	50.58	-17.16	74.0	-23.42	Peak	164.00	150	V	Pass
3**	2405.500	88.22	-12.36	54.0	34.22	AV	237.00	150	V	N/A
3	2405.500	95.93	-12.36	74.0	21.93	Peak	237.00	150	V	N/A
4**	6675.000	44.50	1.88	54.0	-9.50	AV	78.00	150	V	Pass
4	6675.000	54.67	1.88	74.0	-19.33	Peak	78.00	150	V	Pass
5**	10858.250	39.61	0.65	54.0	-14.39	AV	153.00	150	V	Pass
5	10858.250	50.36	0.65	74.0	-23.64	Peak	153.00	150	V	Pass
6**	12274.187	39.77	1.84	54.0	-14.23	AV	174.00	150	V	Pass
6	12274.187	51.17	1.84	74.0	-22.83	Peak	174.00	150	V	Pass

1 GHz to 25 GHz, ANT H 802.11g Low Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1**	1080.000	33.00	-18.23	54.0	-21.00	AV	215.00	150	Н	Pass
1	1080.000	40.13	-18.23	74.0	-33.87	Peak	215.00	150	Н	Pass
2**	1748.000	28.63	-16.85	54.0	-25.37	AV	201.00	150	Н	Pass
2	1748.000	42.10	-16.85	74.0	-31.90	Peak	201.00	150	Н	Pass
3**	2405.500	87.71	-12.36	54.0	33.71	AV	111.00	150	Н	N/A
3	2405.500	95.29	-12.36	74.0	21.29	Peak	111.00	150	Н	N/A
4**	6675.000	44.57	1.88	54.0	-9.43	AV	0.00	150	Н	Pass
4	6675.000	54.03	1.88	74.0	-19.97	Peak	0.00	150	Н	Pass
5**	8837.125	38.82	-0.39	54.0	-15.18	AV	17.00	150	Н	Pass
5	8837.125	48.58	-0.39	74.0	-25.42	Peak	17.00	150	Н	Pass
6**	11782.563	39.73	1.34	54.0	-14.27	AV	283.00	150	Н	Pass
6	11782.563	50.94	1.34	74.0	-23.06	Peak	283.00	150	Н	Pass



1 GHz to 25 GHz, ANT V 802.11g Middle Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	29.45	-18.23	54.0	-24.55	AV	10.00	150	V	Pass
1	1080.000	37.69	-18.23	74.0	-36.31	Peak	10.00	150	V	Pass
2**	2128.500	29.28	-14.19	54.0	-24.72	AV	10.00	150	V	Pass
2	2128.500	45.71	-14.19	74.0	-28.29	Peak	10.00	150	V	Pass
3**	2444.000	86.95	-12.91	54.0	32.95	AV	10.00	150	V	N/A
3	2444.000	94.10	-12.91	74.0	20.10	Peak	10.00	150	V	N/A
4**	6661.000	43.59	1.64	54.0	-10.41	AV	4.00	150	V	Pass
4	6661.000	54.16	1.64	74.0	-19.84	Peak	4.00	150	V	Pass
5**	6994.000	42.96	1.47	54.0	-11.04	AV	15.00	150	V	Pass
5	6994.000	53.92	1.47	74.0	-20.08	Peak	15.00	150	V	Pass
6**	11817.062	39.35	1.14	54.0	-14.65	AV	3.00	150	V	Pass
6	11817.062	50.55	1.14	74.0	-23.45	Peak	3.00	150	V	Pass

1 GHz to 25 GHz, ANT H 802.11g Middle Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	29.20	-18.23	54.0	-24.80	AV	4.00	150	Н	Pass
1	1080.000	37.21	-18.23	74.0	-36.79	Peak	4.00	150	Н	Pass
2**	1920.000	29.48	-15.91	54.0	-24.52	AV	14.00	150	Н	Pass
2	1920.000	40.01	-15.91	74.0	-33.99	Peak	14.00	150	Н	Pass
3**	2432.000	80.53	-12.94	54.0	26.53	AV	4.00	150	Н	N/A
3	2432.000	88.54	-12.94	74.0	14.54	Peak	4.00	150	Н	N/A
4**	6678.000	44.00	1.62	54.0	-10.00	AV	5.00	150	Н	Pass
4	6678.000	54.59	1.62	74.0	-19.41	Peak	5.00	150	Н	Pass
5**	9854.875	39.56	-0.30	54.0	-14.44	AV	7.00	150	Н	Pass
5	9854.875	49.33	-0.30	74.0	-24.67	Peak	7.00	150	Н	Pass
6**	12327.375	39.79	1.84	54.0	-14.21	AV	12.00	150	Н	Pass
6	12327.375	51.58	1.84	74.0	-22.42	Peak	12.00	150	Н	Pass



1 GHz to 25 GHz, ANT V 802.11g High Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	31.18	-18.23	54.0	-22.82	AV	180.00	150	V	Pass
1	1080.000	39.27	-18.23	74.0	-34.73	Peak	180.00	150	V	Pass
2**	1634.500	29.10	-17.38	54.0	-24.90	AV	169.00	150	V	Pass
2	1634.500	51.51	-17.38	74.0	-22.49	Peak	169.00	150	V	Pass
3**	2469.000	88.25	-11.73	54.0	34.25	AV	72.00	150	V	N/A
3	2469.000	95.74	-11.73	74.0	21.74	Peak	72.00	150	V	N/A
4**	6675.000	44.30	1.88	54.0	-9.70	AV	360.00	150	V	Pass
4	6675.000	54.61	1.88	74.0	-19.39	Peak	360.00	150	V	Pass
5**	7907.062	37.69	-2.17	54.0	-16.31	AV	36.00	150	V	Pass
5	7907.062	49.02	-2.17	74.0	-24.98	Peak	36.00	150	V	Pass
6**	11500.812	39.67	0.27	54.0	-14.33	AV	168.00	150	V	Pass
6	11500.812	50.61	0.27	74.0	-23.39	Peak	168.00	150	V	Pass

1 GHz to 25 GHz, ANT H 802.11g High Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	33.20	-18.23	54.0	-20.80	AV	240.00	150	Н	Pass
1	1080.000	40.61	-18.23	74.0	-33.39	Peak	240.00	150	Н	Pass
2**	1748.500	27.79	-16.87	54.0	-26.21	AV	203.00	150	Н	Pass
2	1748.500	43.02	-16.87	74.0	-30.98	Peak	203.00	150	Н	Pass
3**	2455.500	87.19	-12.66	54.0	33.19	AV	105.00	150	Н	N/A
3	2455.500	95.00	-12.66	74.0	21.00	Peak	105.00	150	Н	N/A
4**	6675.000	44.55	1.88	54.0	-9.45	AV	274.00	150	Н	Pass
4	6675.000	54.24	1.88	74.0	-19.76	Peak	274.00	150	Н	Pass
5**	7530.438	37.50	-1.78	54.0	-16.50	AV	269.00	150	Н	Pass
5	7530.438	48.42	-1.78	74.0	-25.58	Peak	269.00	150	Н	Pass
6**	10424.125	39.08	0.61	54.0	-14.92	AV	241.00	150	Н	Pass
6	10424.125	50.73	0.61	74.0	-23.27	Peak	241.00	150	Н	Pass



1 GHz to 25 GHz, ANT V 802.11n20 Low Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	31.37	-18.23	54.0	-22.63	AV	166.00	150	V	Pass
1	1080.000	39.14	-18.23	74.0	-34.86	Peak	166.00	150	V	Pass
2**	1670.000	35.30	-17.11	54.0	-18.70	AV	172.00	150	V	Pass
2	1670.000	50.48	-17.11	74.0	-23.52	Peak	172.00	150	V	Pass
3**	2420.500	88.64	-12.61	54.0	34.64	AV	225.00	150	V	N/A
3	2420.500	96.11	-12.61	74.0	22.11	Peak	225.00	150	V	N/A
4**	4822.000	40.99	-2.52	54.0	-13.01	AV	8.00	150	V	Pass
4	4822.000	50.20	-2.52	74.0	-23.80	Peak	8.00	150	V	Pass
5**	8309.562	38.10	-1.12	54.0	-15.90	AV	199.00	150	V	Pass
5	8309.562	49.25	-1.12	74.0	-24.75	Peak	199.00	150	V	Pass
6**	10843.875	38.94	0.95	54.0	-15.06	AV	360.00	150	V	Pass
6	10843.875	50.76	0.95	74.0	-23.24	Peak	360.00	150	V	Pass

1 GHz to 25 GHz. ANT H 802.11n20 Low Channe

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	33.24	-18.23	54.0	-20.76	AV	245.00	150	Н	Pass
1	1080.000	40.64	-18.23	74.0	-33.36	Peak	245.00	150	Н	Pass
2**	1651.500	27.13	-17.43	54.0	-26.87	AV	120.00	150	Н	Pass
2	1651.500	42.01	-17.43	74.0	-31.99	Peak	120.00	150	Н	Pass
3**	2403.500	85.13	-12.11	54.0	31.13	AV	110.00	150	Н	N/A
3	2403.500	95.53	-12.11	74.0	21.53	Peak	110.00	150	Н	N/A
4**	6669.000	44.88	1.98	54.0	-9.12	AV	254.00	150	Н	Pass
4	6669.000	54.38	1.98	74.0	-19.62	Peak	254.00	150	Н	Pass
5**	7905.625	37.75	-2.12	54.0	-16.25	AV	0.00	150	Н	Pass
5	7905.625	49.87	-2.12	74.0	-24.13	Peak	0.00	150	Н	Pass
6**	11996.750	39.92	1.43	54.0	-14.08	AV	79.00	150	Н	Pass
6	11996.750	51.02	1.43	74.0	-22.98	Peak	79.00	150	Н	Pass



1 GHz to 25 GHz, ANT V 802.11n20 Middle Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	29.60	-18.23	54.0	-24.40	AV	2.00	150	V	Pass
1	1080.000	37.50	-18.23	74.0	-36.50	Peak	2.00	150	V	Pass
2**	1738.000	29.74	-16.71	54.0	-24.26	AV	1.00	150	V	Pass
2	1738.000	42.76	-16.71	74.0	-31.24	Peak	1.00	150	V	Pass
3**	2445.000	87.11	-12.87	54.0	33.11	AV	7.00	150	V	N/A
3	2445.000	94.16	-12.87	74.0	20.16	Peak	7.00	150	V	N/A
4**	6661.000	43.48	1.64	54.0	-10.52	AV	4.00	150	V	Pass
4	6661.000	54.35	1.64	74.0	-19.65	Peak	4.00	150	V	Pass
5**	8838.563	38.15	-0.38	54.0	-15.85	AV	3.00	150	V	Pass
5	8838.563	49.39	-0.38	74.0	-24.61	Peak	3.00	150	V	Pass
6**	11738.000	39.37	1.22	54.0	-14.63	AV	11.00	150	V	Pass
6	11738.000	50.93	1.22	74.0	-23.07	Peak	11.00	150	V	Pass

1 GHz to 25 GHz, ANT H 802.11n20 Middle Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	29.29	-18.23	54.0	-24.71	AV	11.00	150	Н	Pass
1	1080.000	37.90	-18.23	74.0	-36.10	Peak	11.00	150	Н	Pass
2**	2200.500	29.95	-13.01	54.0	-24.05	AV	11.00	150	Н	Pass
2	2200.500	40.63	-13.01	74.0	-33.37	Peak	11.00	150	Н	Pass
3**	2433.000	80.83	-12.88	54.0	26.83	AV	15.00	150	Н	N/A
3	2433.000	87.89	-12.88	74.0	13.89	Peak	15.00	150	Н	N/A
4**	6667.000	44.23	1.87	54.0	-9.77	AV	15.00	150	Н	Pass
4	6667.000	53.71	1.87	74.0	-20.29	Peak	15.00	150	Н	Pass
5**	9311.500	38.45	-0.74	54.0	-15.55	AV	7.00	150	Н	Pass
5	9311.500	49.30	-0.74	74.0	-24.70	Peak	7.00	150	Н	Pass
6**	11311.062	39.69	0.76	54.0	-14.31	AV	6.00	150	Н	Pass
6	11311.062	50.49	0.76	74.0	-23.51	Peak	6.00	150	Н	Pass



1 GHz to 25 GHz, ANT V 802.11n20 High Channel

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1**	1080.000	30.84	-18.23	54.0	-23.16	AV	167.00	150	V	Pass
1	1080.000	38.51	-18.23	74.0	-35.49	Peak	167.00	150	V	Pass
2**	1689.500	33.64	-17.12	54.0	-20.36	AV	167.00	150	V	Pass
2	1689.500	51.83	-17.12	74.0	-22.17	Peak	167.00	150	V	Pass
3**	2469.500	87.89	-11.58	54.0	33.89	AV	66.00	150	V	N/A
3	2469.500	95.32	-11.58	74.0	21.32	Peak	66.00	150	V	N/A
4**	6669.000	45.02	1.98	54.0	-8.98	AV	284.00	150	V	Pass
4	6669.000	54.12	1.98	74.0	-19.88	Peak	284.00	150	V	Pass
5**	9093.000	38.11	-0.83	54.0	-15.89	AV	290.00	150	V	Pass
5	9093.000	50.22	-0.83	74.0	-23.78	Peak	290.00	150	V	Pass
6**	11069.563	39.28	-0.65	54.0	-14.72	AV	0.00	150	V	Pass
6	11069.563	50.29	-0.65	74.0	-23.71	Peak	0.00	150	V	Pass

1 GHz to 25 GHz, ANT H 802.11n20 High Channe

No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1**	1080.000	33.30	-18.23	54.0	-20.70	AV	215.00	150	Н	Pass
1	1080.000	40.45	-18.23	74.0	-33.55	Peak	215.00	150	Н	Pass
2**	1653.000	30.16	-17.18	54.0	-23.84	AV	114.00	150	Н	Pass
2	1653.000	42.49	-17.18	74.0	-31.51	Peak	114.00	150	Н	Pass
3**	2469.500	87.23	-11.58	54.0	33.23	AV	106.00	150	Н	N/A
3	2469.500	94.48	-11.58	74.0	20.48	Peak	106.00	150	Н	N/A
4**	6670.000	44.58	2.08	54.0	-9.42	AV	120.00	150	Н	Pass
4	6670.000	54.15	2.08	74.0	-19.85	Peak	120.00	150	Н	Pass
5**	9499.813	38.45	-0.08	54.0	-15.55	AV	124.00	150	Н	Pass
5	9499.813	49.12	-0.08	74.0	-24.88	Peak	124.00	150	Н	Pass
6**	10818.000	39.90	0.88	54.0	-14.10	AV	211.00	150	Н	Pass
6	10818.000	50.19	0.88	74.0	-23.81	Peak	211.00	150	Н	Pass



A.7 Band Edge (Restricted-band band-edge)

Test Data

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.


Note ³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
	Low	2390	62.23	74	11.77	PEAK	Pass
802.11b		2390	43.49	54	10.51	AVERAGE	Pass
002.110	HIGH	2483.5	59.75	74	14.25	PEAK	Pass
		2483.5	42.51	54	11.49	AVERAGE	Pass
	Low	2390	56.39	74	17.61	PEAK	Pass
000 11 ~		2390	46.65	54	7.36	AVERAGE	Pass
802.11g	HIGH	2483.5	60.40	74	13.60	PEAK	Pass
		2483.5	43.90	54	10.10	AVERAGE	Pass
	Low	2390	55.15	74	18.85	PEAK	Pass
000 11=00	Low	2390	45.59	54	8.41	AVERAGE	Pass
802.11n20	HIGH	2483.5	57.19	74	16.81	PEAK	Pass
		2483.5	45.17	54	8.83	AVERAGE	Pass




802.11b Mode:


LOW CHANNEL, AV




HIGH CHANNEL, AV



LOW CHANNEL, PEAK



HIGH CHANNEL, PEAK






802.11g Mode:


LOW CHANNEL AV




HIGH CHANNEL AV



LOW CHANNEL. PEAK



HIGH CHANNEL. PEAK





802.11n-20 MHz Mode:


Low CHANNEL. AV




HIGH CHANNEL AV



Low CHANNEL, PEAK



HIGH CHANNEL. PEAK





A.8 Power Spectral Density (PSD)

Test Data

802.11b Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-14.55	8
Middle	-14.66	8
High	-16.06	8

802.11g Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)		
Low	-23.21	8		
Middle	-23.34	8		
High	-23.67	8		

802.11n-20 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-23.26	8
Middle	-23.44	8
High	-23.84	8



Test plots

802.11b LOW CHANNEL



802.11b MIDDLE CHANNEL




Date: 5.NOV.2018 10:56:02


802.11b HIGH CHANNEL




802.11a LOW CHANNEL



802.11g MIDDLE CHANNEL



802.11g HIGH CHANNEL




Date: 5.NOV.2018 12:50:22




802.11n-20 MHz LOW CHANNEL

802.11 n-20 MHz MIDDLE CHANNEL



802.11n-20 MHz HIGH CHANNEL





ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-HK18B0009-AR.pdf".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-HK18B0009-AW.pdf".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-HK18B0009-AI.pdf".

--END OF REPORT--