



FCC TEST REPORT

Prepared for :

**Shenzhen Yingshixun Electronic Technology Co., Ltd.
A-D Unit 18FL, Block B, BLD 6, Baoneng Technology Park,
Longhua District, Shenzhen, China**

Product: Network Camera

Trade Name: OPTJOY

Model Name: QC21, C10, C20, S101, S102, S103

Date of Test: June 08, 2017 ~ June 15, 2017

Date of Report: June 15, 2017

Report Number: HK1706080141-E

FCC ID: 2ANJX-QC21

Prepared By :

**Shenzhen HUAK Testing Technology Co., Ltd.
F1-008, Tai Yi Building, No.1, Haicheng West Road, Xixiang Street, Bao'an
District, Shenzhen City, China
TEL: +86-755-2302 9901 FAX: +86-755-2302 9901
E-mail: service@cer-mark.com http://www.cer-mark.com**



TEST REPORT VERIFICATION

Applicant : Shenzhen Yingshixun Electronic Technology Co.,Ltd.
Address : A-D Unit 18FL, Block B, BLD 6, Baoneng Technology Park,
Longhua District, Shenzhen, China
Manufacturer : Shenzhen Yingshixun Electronic Technology Co.,Ltd.
Address : A-D Unit 18FL, Block B, BLD 6, Baoneng Technology Park,
Longhua District, Shenzhen, China
EUT Description : Network Camera
(A) Model No. : QC21
(B) Serial No. : C10, C20, S101, S102, S103
(C) Power Supply : DC5V, 2A form Adapter with AC 120V/60Hz

Standards FCC Part 15 Subpart B
ANSI C63.4:2014

This device described above has been tested by HUAK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of HUAK, this document may be altered or revised by HUAK, personal only, and shall be noted in the revision of the document.

Test Result..... **Pass**

Date of Test: **June 08, 2017 ~ June 15, 2017**

Testing Engineer : 

(Eric Xie)

Technical Manager : 

(Dora Qin)

Authorized Signatory : 

(Kait Chen)



1 . TEST SUMMARY	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 DESCRIPTION OF TEST SETUP	8
2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	9
2.5 MEASUREMENT INSTRUMENTS LIST	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION	11
3.1.2 TEST PROCEDURE	12
3.1.3 TEST SETUP	12
3.1.4 EUT OPERATING CONDITIONS	12
3.1.5 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	15
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	15
3.2.2 TEST PROCEDURE	15
3.2.3 TEST SETUP	16
3.2.4 EUT OPERATING CONDITIONS	16
3.2.5 TEST RESULTS	17
3.2.6 TEST RESULTS(Above 1GHz)	19
4 . EUT TEST PHOTO	20



1. TEST SUMMARY

Test procedures according to the technical standards:

EMC Emission				
Standard	Test Item	Limit	Judgment	Remark
FCC Part 15 Subpart B ANSI C63.4:2014	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.



1.1 TEST FACILITY

Test Firm : QTC Certification & Testing Co., Ltd.
Certificated by FCC, Registration No.: 588523
Address 2nd Floor, B1 Building, Fengyeyuan Industrial Plant, Liuxian 2st. Road,
Xin'an Street, Bao'an District, Shenzhen, China

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
C01	ANSI	150 KHz ~ 30MHz	3.2	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
A01	ANSI	30MHz ~ 1000MHz	4.7	



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Network Camera					
Model Name	QC21					
Serial No	C10, C20, S101, S102, S103					
Model Difference	All models are identical except model names.					
Product Description	<p>The EUT is a Network Camera</p> <table border="1"><tr><td>Operating frequency:</td><td>40Mhz</td></tr><tr><td>Connecting I/O port:</td><td>N/A</td></tr></table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>		Operating frequency:	40Mhz	Connecting I/O port:	N/A
Operating frequency:	40Mhz					
Connecting I/O port:	N/A					
Power Source	DC5V, 2A form Adapter with AC 120V/60Hz					
Power Rating	DC5V, 2A form Adapter with AC 120V/60Hz					



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Running


For Conducted Test	
Final Test Mode	Description
Mode 1	Running

For Radiated Test	
Final Test Mode	Description
Mode 1	Running



2.3 DESCRIPTION OF TEST SETUP

Mode 1:





2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Network Camera	OPTJOY	QC21	N/A	EUT
E-2	AC Adapter	N/A	A8A-050200U-US1	N/A	

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



2.5 MEASUREMENT INSTRUMENTS LIST

2.5.1 CONDUCTED TEST SITE

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	R&S	ENV216	101313	Jul. 06, 2018
2	LISN	EMCO	3816/2	00042990	Jul. 06, 2018
3	50Ω Switch	ANRITSU CORP	MP59B	6200983704	Jul. 06, 2018
4	Test Cable	N/A	C01	N/A	Jul. 06, 2018
5	Test Cable	N/A	C02	N/A	Jul. 06, 2018
6	Test Cable	N/A	C03	N/A	Jul. 06, 2018
7	EMI Test Receiver	R&S	ESCI	101160	Jul. 06, 2018
8	Passive Voltage Probe	ESH2-Z3	R&S	100196	Jul. 06, 2018
9	Triple-Loop Antenna	EVERFINE	LIA-2	11020003	Jul. 06, 2018
10	Absorbing Clamp	R&S	MDS-21	100423	Jul. 08, 2018

2.5.2 RADIATED TEST SITE

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Bilog Antenna	TESEQ	CBL6111D	31216	Jul. 06, 2018
2	Test Cable	N/A	R-01	N/A	Jul. 06, 2018
3	Test Cable	N/A	R-02	N/A	Jul. 06, 2018
4	EMI Test Receiver	R&S	ESCI-7	101318	Jul. 06, 2018
5	Antenna Mast	EM	SC100_1	N/A	N/A
6	Turn Table	EM	SC100	060531	N/A
7	50Ω Switch	Anritsu Corp	MP59B	6200983705	Jul. 06, 2018
8	Spectrum Analyzer	Agilent	E4407B	MY45108040	Jul. 06, 2018
9	Horn Antenna	EM	EM-AH-10180	2011071402	Jul. 06, 2018
10	Amplifier	EM	EM-30180	060538	Jul. 06, 2018



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1. Support units were connected to second LISN.


2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.

3.1.5 TEST RESULTS


EUT :	Network Camera	Model Name. :	QC21
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2017-06-12
Test Mode :	Running	Phase :	L
Test Voltage :	120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.3740	42.44	9.80	52.24	58.41	-6.17	QP
2	0.3740	31.48	9.80	41.28	48.41	-7.13	AVG
3	0.9540	39.23	9.76	48.99	56.00	-7.01	QP
4	0.9900	27.62	9.76	37.38	46.00	-8.62	AVG
5	3.0140	22.17	9.71	31.88	46.00	-14.12	AVG
6	3.2020	37.45	9.70	47.15	56.00	-8.85	QP



EUT :	Network Camera	Model Name. :	QC21
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2017-06-12
Test Mode :	Running	Phase :	N
Test Voltage :	120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1900	41.57	9.81	51.38	64.04	-12.66	QP
2	0.3740	40.89	9.80	50.69	58.41	-7.72	QP
3	0.3740	26.36	9.80	36.16	48.41	-12.25	AVG
4	0.6620	21.76	9.79	31.55	46.00	-14.45	AVG
5	0.8900	21.25	9.77	31.02	46.00	-14.98	AVG
6*	0.8980	39.49	9.77	49.26	56.00	-6.74	QP



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

Notes:


- (1) The limit for radiated test was performed according to as following:
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

3.2.2 TEST PROCEDURE


- a. The measuring distance of at 10 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured, above 1G Average detector mode will be instead.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP(AV) Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.2.3 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz




3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



3.2.5 TEST RESULTS


EUT :	Network Camera	Model Name :	QC21
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2017-06-12
Test Mode :	Running	Polarization :	Horizontal
Test Power :	120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	80.9275	35.91	-16.27	19.64	40.00	-20.36	329	100	QP
2	166.6514	41.07	-14.76	26.31	43.50	-17.19	100	100	QP
3	199.9856	39.69	-11.60	28.09	43.50	-15.41	87	100	QP
4	265.6757	44.37	-9.91	34.46	46.00	-11.54	92	100	QP
5	451.1350	36.55	-7.07	29.48	46.00	-16.52	304	100	QP
6	535.7073	35.30	-5.80	29.50	46.00	-16.50	293	100	QP



EUT :	Network Camera	Model Name :	QC21
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2017-06-12
Test Mode :	Running	Polarization :	Vertical
Test Power :	120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	54.2610	36.66	-11.80	24.86	40.00	-15.14	252	100	QP
2	134.5592	41.69	-14.50	27.19	43.50	-16.31	95	100	QP
3	166.0680	43.75	-14.79	28.96	43.50	-14.54	54	100	QP
4	264.7456	36.60	-9.94	26.66	46.00	-19.34	105	100	QP
5	531.9634	43.24	-5.86	37.38	46.00	-8.62	169	100	QP
6	752.7432	38.12	-1.21	36.91	46.00	-9.09	266	100	QP



3.2.6 TEST RESULTS(Above 1GHz)

EUT :	Network Camera	Model Name :	QC21
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	N/A
Test Mode :	N/A		
Test Power :	N/A		


Note:

- 1) N/A - denotes test is not applicable in this test report
- 2) There was not any unintentional transmission in standby mode



4. EUT TEST PHOTO

Radiated Measurement Photos





Conducted Measurement Photos

