

Appendix 10

Prüfbericht - Nr.:
Test Report No.

19660333 001

Seite 1 von 2
Page 1 of 2

RF Exposure Report

Following FCC KDB 447498 D01 General SAR test exclusion guidelines

The corresponding SAR exclusion threshold condition, listed below:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation

Distances \leq 50 mm are determined by: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} (\text{GHz})] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g Extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison. The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion (447498 D01 General RF Exposure Guidance v05r02)

2) At 100 MHz to 6 GHz and for test separation distances $>$ 50 mm, the SAR test exclusion threshold is determined according to the following

- $[\text{Power allowed at numeric threshold for 50 mm in step 1} + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)] \text{ mW}$, at 100 MHz to 1500 MHz
- $[\text{Power allowed at numeric threshold for 50 mm in step 1} + (\text{test separation distance} - 50 \text{ mm}) \cdot 10] \text{ mW}$ at $>$ 1500 MHz and \leq 6 GHz

3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion,

- The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for test separation distances $>$ 50 mm and $<$ 200 mm
- The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances \leq 50 mm
- SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

Appendix 10

Prüfbericht - Nr.:

19660333 001

Test Report No.

Seite 2 von 2

Page 2 of 2

SAR Test Exclusion Thresholds

Maximum Measured Transmitter Power:

| Frequency (GHz) | Measured Max. Power (mW) | Tune up declared Power (mW) | Min. Test Separation distance | SAR Test Exclusion Calculation Values | 1-g Extremity SAR Test exclusion Thresholds |
|-----------------|--------------------------|-----------------------------|-------------------------------|---------------------------------------|---|
| 2.402 – 2.480 | 0.277 | 1.412 | 5mm | 0.1224 | 3 |

Hence, the EUT is exempted from routine SAR evaluation

Note:

1. Calculate SAR exclusion threshold from condition 1) formulas.
2. Minimum Separation distance considered as 5mm as per section 1.

Reference Image: