

RF Exposure Evaluation Report

Product : Zigbee PCB Module
Trade mark : ENNFU
Model/Type reference : T30PA127F2.4G
Serial Number : N/A
Report Number : EED32J00193102
FCC ID : 2ANLK-T30A
Date of Issue : Dec. 08, 2017
Test Standards : 47 CFR Part 1.1307(2015)
47 CFR Part 1.1310(2015)
KDB447498D01v06
Test result : PASS

Prepared for:

Ennfu Scientific Company Limited
A606, 6F, Area A, University Of Pioneer Park, No. 99, Daxue Road,
Tongshan District, Xuzhou, Jiangsu Province, P.R.China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested By:

Tom - chen
Tom chen (Test Project)

Compiled by:

Max . Liang
Max liang (Project Engineer)

Reviewed by:

Ware Xin
Ware xin (Reviewer)

Approved by:

Sheek . Luo
Sheek Luo (Lab supervisor)

Date:

Dec. 08, 2017

Check No.:2827583977



2 Version

Version No.	Date	Description
00	Dec. 08, 2017	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
3.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
3.4 TEST LOCATION.....	4
3.5 DEVIATION FROM STANDARDS.....	5
3.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
4 RF EXPOSURE EVALUATION.....	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
4.1.1 Limits.....	6
4.1.2 Test Procedure.....	7
4.1.3 EUT RF Exposure Evaluation.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	8

3.1 Client Information

Applicant:	Ennfu Scientific Company Limited
Address of Applicant:	A606, 6F, Area A, University Of Pioneer Park, No. 99, Daxue Road, Tongshan District, Xuzhou, Jiangsu Province, P.R.China
Manufacturer:	Ennfu Scientific Company Limited
Address of Manufacturer:	A606, 6F, Area A, University Of Pioneer Park, No. 99, Daxue Road, Tongshan District, Xuzhou, Jiangsu Province, P.R.China
Factory:	Ennfu Scientific Company Limited
Address of Factory:	A606, 6F, Area A, University Of Pioneer Park, No. 99, Daxue Road, Tongshan District, Xuzhou, Jiangsu Province, P.R.China

3.2 General Description of EUT

Product Name:	Zigbee PCB Module
Model No.(EUT):	T30PA127F2.4G
Trade Mark:	ENNFU
EUT Supports Radios application:	Zigbee

3.3 Product Specification subjective to this standard

Frequency Range:	2405MHz-2480MHz
Modulation Type:	QPSK
Number of Channels:	16
Test Power Grade:	N/A
Test Software of EUT:	SmartRF_Studio_7-2.6.0(manufacturer declare)
Antenna Type:	Modular antenna
Antenna Gain:	3dBi
Power Supply:	DC 3.3V
Conduct Peak Power:	1.802dBm
	The ERP data refer to the report EED32J00193101
Sample Received Date:	Aug. 30, 2017
Sample tested Date:	Aug. 30, 2017 to Dec. 07, 2017
The tested sample(s) and the sample information are provided by the client.	

3.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China 518101

Telephone: +86 (0) 755 3368 3668 Fax: +86 (0) 755 3368 3385

No tests were sub-contracted.

Report No. : EED32J00193102

Page 5 of 8

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	* (100)	6
3.0–30	1842/f	4.89/f	* (900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	* (100)	30
1.34–30	824/f	2.19/f	* (180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the centre of radiation of the antenna

EIRP = P*G

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user.

Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 3dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducted Peak Output Power(dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R (cm)	S (mW/cm ²)	Limit (mW/cm ²)	Result
Lowest	2405	1.802	3	4.802	3.02	20	0.0006	1.0	Pass

Note: Refer to report No. EED32I00193101 for EUT test Max Conducted Peak Output Power value.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32J00193101 for EUT external and internal photos.

***** End of Report *****

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.