

Radio Spectrum TEST REPORT

Report No.: 170600273TWN-001

Model No.: X1 PRO, X1, X2

Issued Date: Aug. 21, 2017

Applicant: Bonraybio Co., LTD.
4F., No. 118, Gongye 9th Rd., Dali Dist., Taichung City 41280,
Taiwan

Test Method/ Standard: 47 CFR FCC Part 15.247 & ANSI C63.10 2013
KDB 558074 D01 v04
KDB 662911 D01 v02r01

Registration No.: 960839

Test By: Intertek Testing Services Taiwan Ltd.
No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,
Shiang-Shan District, Hsinchu City, Taiwan

It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Intertek Laboratory. The test result(s) in this report only applies to the tested sample(s).




The test report was prepared by:


Sunny Liu/ Senior Officer

These measurements were taken by:


Durant Wei/ Engineer

The test report was reviewed by:


Name Jimmy Yang
Title Group Leader

Revision History

Report No.	Issue Date	Revision Summary
170600273TWN-001	Aug. 21, 2017	Original report

Table of Contents

SUMMARY OF TEST DATA	5
1. General information	6
1.1. Identification of the EUT	6
1.2. Adapter information	6
1.3. Description of the EUT	7
1.4. Antenna description	7
1.5. Operation mode	8
1.6. Applied test modes and channels	10
1.7. Power setting of test software	11
2. Minimum 6 dB Bandwidth	14
2.1. Instrument Setting	14
2.2. Test Procedure	14
2.3. Test Diagram	14
2.4. Limit	14
2.5. Operating Environment Condition	14
2.6. Test Results	15
3. Maximum Peak Conducted Output Power	20
3.1. Instrument Setting	20
3.2. Test Procedure	20
3.3. Test Diagram	20
3.4. Limit	20
3.5. Operating Environment Condition	20
3.6. Test Results	21
4. Power Spectral Density	22
4.1. Instrument Setting	22
4.2. Test Procedure	22
4.3. Test Diagram	22
4.4. Limit	22
4.5. Operating Environment Condition	22
4.6. Test Results	23
5. Emissions in Non-Restricted Frequency Bands	28
5.1. Instruments Setting	28
5.2. Test Procedure	28
5.3. Test Diagram	28

5.4. Limit	28
5.5. Operating Environment Condition	29
5.6. Test Results	30
6. Emissions in Restricted Frequency Bands (Radiated emission measurements)	38
6.1. Instrument Setting	38
6.2. Test Procedure	38
6.3. Test Diagram	39
6.4. Limit	41
6.5. Operating Environment Condition	41
6.6. Test Result	42
7. Emission on Band Edge	47
7.1. Instrument Setting	47
7.2. Test Procedure	47
7.3. Operating Environment Condition	47
7.4. Test Results	48
8. AC Power Line Conducted Emission	61
8.1. Measuring instrument setting	61
8.2. Test Procedure	61
8.3. Test Diagram	61
8.4. Limit	62
8.5. Operating Environment Condition	62
8.6. Test Results	63
APPENDIX A: TEST EQUIPMENT LIST	65
APPENDIX B: MEASUREMENT UNCERTAINTY	67

Summary of Test Data

Test Requirement	Applicable Rule (Section 15.247)	Result
Minimum 6 dB Bandwidth	15.247(a)(2)	Pass
Maximum Peak Conducted Output Power	15.247(b)(3)	Pass
Power Spectral Density	15.247(e)	Pass
Emissions In Non-Restricted Frequency Bands	15.247(d)	Pass
Emissions In Restricted Frequency Bands (Radiated emission measurements)	15.247(d), 15.205, 15.209	Pass
Emission On The Band Edge	15.247(d), 15.205	Pass
AC Power Line Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass

1. General information

1.1. Identification of the EUT

Product:	Semen Quality Analyzer
Model No.:	X1 PRO
Operating Frequency:	1. 2412 MHz ~ 2462 MHz for 802.11b, 802.11g, 802.11n HT20 2. 2422 MHz ~ 2452 MHz for 802.11n HT40
Channel Number:	1. 11 channels for 2412 MHz ~ 2462 MHz 2. 9 channels for 2422 MHz ~ 2452 MHz
Access scheme:	DSSS, OFDM
Rated Power:	1. DC 5 V from adapter 2. DC 3.7 V from battery
Power Cord:	N/A
Sample Received:	Aug. 2, 2017
Sample Received:	Workable
Test Date(s):	Aug. 3, 2017 ~ Aug. 16, 2017
Note 1: The test report only allows to be revised within three years from its original issued date unless further standard or the requirement was noticed. Note 2: When determining the test conclusion, the Measurement Uncertainty of test has been considered. Note 3: Except where explicitly agreed in writing, all work and services performed by Intertek is subject to our standard Terms and Conditions which can be obtained at our website: http://www.intertek-twn.com/terms/. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. <i>This report is made solely on the basis of your instructions and / or information and materials supplied by you and provide no warranty on the tested sample(s) be truly representative of the sample source. The report is not intended to be a recommendation for any particular course of action, you are responsible for acting as you see fit on the basis of the report results. Intertek is under no obligation to refer to or report upon any facts or circumstances which are outside the specific instructions received and accepts no responsibility to any parties whatsoever, following the issue of the report, for any matters arising outside the agreed scope of the works. This report does not discharge or release you from your legal obligations and duties to any other person. You are the only one authorized to permit copying or distribution of this report (and then only in its entirety). Any such third parties to whom this report may be circulated rely on the content of the report solely at their own risk.</i>	

1.2. Adapter information

The EUT will be supplied with a power supply from below list:

No.	Brand	Model no.	Specification
Adapter	UE	UES12LCP-050200SPA	I/P : 100-240V , 50-60Hz , 0.5A O/P : 5V , 2A

1.3. Description of the EUT

The customer confirmed the models listed as below were series model to model X1 PRO (EUT), the difference between main model and series model are listed as below.

Product name	Model Number	Difference
Semen Quality Analyzer	X1 PRO	Full Function
Semen Quality Analyzer	X1	NO HDMI, USB
Home Fertility Test Device	X2	NO HDMI, USB, Touch screen

For more detail features, please refer to user's Manual.

Modulation mode	Transmit path	
	Chain 0 / Main	Chain 1 / AUX
802.11b	V	X
802.11g	V	X
802.11n (HT20)	V	X
802.11n (HT40)	V	X

1.4. Antenna description

The antenna is affixed to the EUT using a unique connector, which allows for replacement of a broken antenna, but DOES NOT use a standard antenna jack or electrical connector.

.

Antenna Gain : 1.6 dBi
Antenna Type : CCD Antenna
Connector Type : I-PEX

1.5. Operation mode

The EUT was supplied with DC 5 V from adapter (Test voltage: 120 Vac, 60 Hz).

TX mode: EUT transmits continuously by entering test mode(TX Test mode), and Touchscreen to change different channel.

The signal is maximized through rotation and placement in the three orthogonal axes.



X axis



Y axis



Z axis

After verifying three axes, we found the maximum electromagnetic field was occurred at X axis. The final test data was executed under this configuration.

With individual verifying, the maximum output power were found out 1 Mbps data rate for 802.11b mode, 6 Mbps data rate for 802.11g mode, 6.5 Mbps data rate for 802.11n(HT20) mode and, 13.5 Mbps data rate for 802.11n(HT40) mode the final tests were executed under these conditions recorded in this report individually.

Mode	Channel	Data rate	Chain0 AV (dBm)
802.11b	ch6	1	16.43
802.11b	ch6	2	16.41
802.11b	ch6	5.5	16.31
802.11b	ch6	11	16.33
802.11g	ch6	6	16.57
802.11g	ch6	9	16.46
802.11g	ch6	12	16.41
802.11g	ch6	18	16.32
802.11g	ch6	24	16.17
802.11g	ch6	36	16.22
802.11g	ch6	48	16.15
802.11g	ch6	54	16.11
802.11n(HT20)	ch6	MCS0	16.44
802.11n(HT20)	ch6	MCS1	16.41
802.11n(HT20)	ch6	MCS2	16.33
802.11n(HT20)	ch6	MCS3	16.29
802.11n(HT20)	ch6	MCS4	16.26
802.11n(HT20)	ch6	MCS5	16.19
802.11n(HT20)	ch6	MCS6	16.25
802.11n(HT20)	ch6	MCS7	16.19
802.11n(HT40)	ch6	MCS0	16.02
802.11n(HT40)	ch6	MCS1	16.07
802.11n(HT40)	ch6	MCS2	16.01
802.11n(HT40)	ch6	MCS3	15.93
802.11n(HT40)	ch6	MCS4	15.96
802.11n(HT40)	ch6	MCS5	15.87
802.11n(HT40)	ch6	MCS6	15.84
802.11n(HT40)	ch6	MCS7	15.77

1.6. Applied test modes and channels

Test items	Mode	Data Rate (Mbps)	Channel	Antenna
Maximum Conducted Output Power	802.11b	1	1,6,11	Chain0
	802.11g	6	1,6,11	Chain0
	802.11n (HT20)	6.5	1,6,11	Chain0
	802.11n (HT40)	13.5	3,6,9	Chain0
Power Spectrum Density	802.11b	1	1,6,11	Chain0
	802.11g	6	1,6,11	Chain0
	802.11n (HT20)	6.5	1,6,11	Chain0
	802.11n (HT40)	13.5	3,6,9	Chain0
Emission BW	802.11b	1	1,6,11	Chain0
	802.11g	6	1,6,11	Chain0
	802.11n (HT20)	6.5	1,6,11	Chain0
	802.11n (HT40)	13.5	3,6,9	Chain0
Radiated spurious Emission 9kHz~1GHz	Worst case			
Emissions In Restricted Frequency Bands (Radiated emission measurements)	802.11b	1	1,6,11	Chain0
	802.11g	6	1,6,11	Chain0
	802.11n (HT20)	6.5	1,6,11	Chain0
	802.11n (HT40)	13.5	3,6,9	Chain0
Emission on The Band Edge	802.11b	1	1,6,11	Chain0
	802.11g	6	1,6,11	Chain0
	802.11n (HT20)	6.5	1,6,11	Chain0
	802.11n (HT40)	13.5	3,6,9	Chain0
AC Line Conducted Emission	Normal Link			

1.7. Power setting of test software


Channels & power setting software provided by the client was used to change the operating channels as well as the output power level and is going to be installed in the final end product.

Mode	Channel	Frequency	Power setting (Chain0)
802.11b	1	2412	19
	6	2437	19
	11	2462	19
802.11g	1	2412	20
	6	2437	20
	11	2462	20
802.11n(HT 20)	1	2412	20
	6	2437	20
	11	2462	20
802.11n(HT40)	3	2422	19
	6	2437	19
	9	2452	19


Note: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

Mode	Chain	Channel	Frequency (MHz)	Data rate (Mbps)	Signal on time(s)	Total signal transmit time(s)	Duty cycle	Duty Cycle factor
802.11b	Chain 0	6	2437	1	1.00	1.00	1.00	0.00
802.11g	Chain 0	6	2437	6	1.00	1.00	1.00	0.00
802.11n (HT20)	Chain 0	6	2437	6.5	1.00	1.00	1.00	0.00
802.11n (HT40)	Chain 0	6	2437	13.5	1.00	1.00	1.00	0.00


Ducty Cycle @ 802.11b Mode




Ducty Cycle @ 802.11g Mode



Ducty Cycle @ 802.11n(HT20) Mode



Ducty Cycle @ 802.11n(HT40) Mode



2. Minimum 6 dB Bandwidth


2.1. Instrument Setting

Spectrum Parameter	Setting
Detector	Peak
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Sweep	Auto couple
Trace	Allow the trace to stabilize.
Span	Between two times and five times the occupied bandwidth
Attenuation	Auto

2.2. Test Procedure

- Step 1 The transmitter output was connected to the spectrum analyzer.
- Step 2 Test was performed in accordance with clause 8.1 option1 of KDB 558074 D01.
- Step 3 Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

2.3. Test Diagram



2.4. Limit

The minimum 6 dB bandwidth shall be at least 500 kHz.


2.5. Operating Environment Condition

Temperature (°C) :	25
Relative Humidity (%) :	50
Atmospheric Pressure (hPa) :	1008
Test Date :	2017/8/14


2.6. Test Results

Mode	Chain	Channel	Frequency (MHz)	6dB BW (MHz)	Limit (MHz)
802.11b	Chain0	1	2412	9.130	>0.5
802.11b	Chain0	6	2437	9.118	>0.5
802.11b	Chain0	11	2462	9.121	>0.5
802.11g	Chain0	1	2412	16.382	>0.5
802.11g	Chain0	6	2437	16.371	>0.5
802.11g	Chain0	11	2462	16.372	>0.5
802.11n(HT20)	Chain0	1	2412	17.619	>0.5
802.11n(HT20)	Chain0	6	2437	17.598	>0.5
802.11n(HT20)	Chain0	11	2462	17.606	>0.5
802.11n(HT40)	Chain0	3	2422	36.157	>0.5
802.11n(HT40)	Chain0	6	2437	36.344	>0.5
802.11n(HT40)	Chain0	9	2452	36.088	>0.5


Chain0 : 6dB Bandwidth @ 802.11b Mode Ch 1




Chain0 : 6dB Bandwidth @ 802.11b Mode Ch 6




Chain0 : 6dB Bandwidth @ 802.11b Mode Ch11




Chain0 : 6dB Bandwidth @ 802.11g Mode Ch 1




Chain0 : 6dB Bandwidth @ 802.11g Mode Ch 6




Chain0 : 6dB Bandwidth @ 802.11g Mode Ch11




Chain0 : 6dB Bandwidth @ 802.11n(HT20) Mode Ch 1




Chain0 : 6dB Bandwidth @ 802.11n(HT20) Mode Ch 6




Chain0 : 6dB Bandwidth @ 802.11n(HT20) Mode Ch11




Chain0 : 6dB Bandwidth @ 802.11n(HT40) Mode Ch 3



Chain0 : 6dB Bandwidth @ 802.11n(HT40) Mode Ch 6



Chain0 : 6dB Bandwidth @ 802.11n(HT40) Mode Ch 9



3. Maximum Peak Conducted Output Power


3.1. Instrument Setting

Power Meter Parameter	Setting
Bandwidth	65MHz bandwidth is greater than the EUT emission bandwidth
Detector	Peak & Average

3.2. Test Procedure

Test procedures refer to clause 9.1.3 peak power meter method and clause 9.2.3.2 measurement using a gated RF average power meter of KDB 558074 D01.

3.3. Test Diagram



3.4. Limit

For systems using digital modulation in the 2400-2483.5 MHz: 1 Watt (30dBm)

3.5. Operating Environment Condition

Temperature (°C) : 25
Relative Humidity (%) : 50
Atmospheric Pressure (hPa) : 1008
Test Date : 2017/8/17

3.6. Test Results

Mode	Chain	Channel	Pk Output Power (dBm)	Pk Output Power (mW)	Av Output Power (dBm)	Av Output Power (mW)	Limit (dBm)	Margin (dB)
802.11b	Chain0	1	18.86	76.91	16.01	39.90	30.00	-11.14
802.11b	Chain0	6	19.45	88.1	16.43	43.95	30.00	-10.55
802.11b	Chain0	11	19.32	85.51	16.28	42.46	30.00	-10.68
802.11g	Chain0	1	24.54	284.45	16.81	47.97	30.00	-5.46
802.11g	Chain0	6	24.67	293.09	16.57	45.39	30.00	-5.33
802.11g	Chain0	11	24.6	288.49	16.50	44.67	30.00	-5.40
802.11n (HT20)	Chain0	1	24.05	254.1	16.53	44.98	30.00	-5.95
802.11n (HT20)	Chain0	6	24.1	257.04	16.44	44.06	30.00	-5.90
802.11n (HT20)	Chain0	11	24.69	294.44	16.68	46.56	30.00	-5.31
802.11n (HT40)	Chain0	3	22.84	192.31	15.63	36.56	30.00	-7.16
802.11n (HT40)	Chain0	6	22.98	198.61	16.02	39.99	30.00	-7.02
802.11n (HT40)	Chain0	9	22.81	190.99	15.93	39.17	30.00	-7.19

4. Power Spectral Density


4.1. Instrument Setting

Spectrum Function	Setting
Detector	Peak
RBW	≥ 3 kHz
VBW	$\geq 3 \times$ RBW
Sweep	Auto couple
Trace	Max hold
Span	1.5 times x 6dB bandwidth
Attenuation	Auto

4.2. Test Procedure

- Step 1 Test procedure refer to clause 10.2 method PKPSD (peak PSD) of KDB 558074 D01 and clause E) 2) c) of KDB 662911 D01 measure and sum spectral maxima across the outputs.
- Step 2 Using the maximum conducted output power in the fundamental emission demonstrates compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
- Step 3 Use the peak marker function to determine the maximum amplitude level within the RBW.

4.3. Test Diagram



4.4. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission

4.5. Operating Environment Condition

Temperature (°C) :	25
Relative Humidity (%) :	50
Atmospheric Pressure (hPa) :	1008
Test Date :	2017/8/14

4.6. Test Results

Mode	Chain	Channel	Frequency (MHz)	PSD (dBm) @10kHz	Correction Factor (dB)	PSD (dBm) @3kHz	Limit (dBm)	Margin (dB)
802.11b	Chain0	1	2412	-6.4	5.23	-11.63	8	-19.63
802.11b	Chain0	6	2437	-6.14	5.23	-11.37	8	-19.37
802.11b	Chain0	11	2462	-6.03	5.23	-11.26	8	-19.26
802.11g	Chain0	1	2412	-4.46	5.23	-9.69	8	-17.69
802.11g	Chain0	6	2437	-4.57	5.23	-9.8	8	-17.8
802.11g	Chain0	11	2462	-4.67	5.23	-9.9	8	-17.9
802.11n (HT20)	Chain0	1	2412	-4.39	5.23	-9.62	8	-17.62
802.11n (HT20)	Chain0	6	2437	-3.77	5.23	-9	8	-17
802.11n (HT20)	Chain0	11	2462	-4.24	5.23	-9.47	8	-17.47
802.11n (HT40)	Chain0	3	2422	-6.03	5.23	-11.26	8	-19.26
802.11n (HT40)	Chain0	6	2437	-6.67	5.23	-11.9	8	-19.9
802.11n (HT40)	Chain0	9	2452	-7.08	5.23	-12.31	8	-20.31

Note1: RBW Correction = $10 \cdot \log(10\text{kHz}/3\text{kHz}) = 5.229$

Note2: PSD in 3kHz = PSD in 10kHz – RBW Correction

Chain0 : Power Spectral Density @ 802.11b Mode Ch 1




Chain0 : Power Spectral Density @ 802.11b Mode Ch 6




Chain0 : Power Spectral Density @ 802.11b Mode Ch11




Chain0 : Power Spectral Density @ 802.11g Mode Ch 1




Chain0 : Power Spectral Density @ 802.11g Mode Ch 6




Chain0 : Power Spectral Density @ 802.11g Mode Ch11




Chain0 : Power Spectral Density @ 802.11n(HT20) Mode Ch 1




Chain0 : Power Spectral Density @ 802.11n(HT20) Mode Ch 6




Chain0 : Power Spectral Density @ 802.11n(HT20) Mode Ch11




Chain0 : Power Spectral Density @ 802.11n(HT40) Mode Ch 3



Chain0 : Power Spectral Density @ 802.11n(HT40) Mode Ch 6



Chain0 : Power Spectral Density @ 802.11n(HT40) Mode Ch 9



5. Emissions in Non-Restricted Frequency Bands


5.1. Instruments Setting

Spectrum Function	Setting (Reference Level)	Setting (Emission Level)
Detector	Peak	Peak
RBW	≥ 100 kHz	≥ 100 kHz
VBW	$\geq 3 \times$ RBW	$\geq 3 \times$ RBW
Sweep	Auto couple	Auto couple
Trace	Max hold	Max hold
Span	≥ 1.5 time 6dB bandwidth	
Attenuation	Auto	Auto

5.2. Test Procedure

- Step 1 The procedure was used in antenna-port conducted and connected to the spectrum analyzer.
- Step 2 Set instrument center frequency to center frequency.
- Step 3 Use the parameter configured in clause 6.3 to measure.
- Step 4 Use the peak marker function to determine the maximum amplitude level.

5.3. Test Diagram



5.4. Limit


The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

5.5. Operating Environment Condition


Temperature (°C) :	25
Relative Humidity (%) :	50
Atmospheric Pressure (hPa) :	1008
Test Date :	2017/8/14

5.6. Test Results


Chain0 : Conducted Spurious @ 802.11b Mode Ch 1




Chain0 : Conducted Spurious @ 802.11b Mode Ch 1




Chain0 : Conducted Spurious @ 802.11b Mode Ch 6




Chain0 : Conducted Spurious @ 802.11b Mode Ch 6




Chain0 : Conducted Spurious @ 802.11b Mode Ch11




Chain0 : Conducted Spurious @ 802.11b Mode Ch11




Chain0 : Conducted Spurious @ 802.11g Mode Ch 1




Chain0 : Conducted Spurious @ 802.11g Mode Ch 1




Chain0 : Conducted Spurious @ 802.11g Mode Ch 6




Chain0 : Conducted Spurious @ 802.11g Mode Ch 6




Chain0 : Conducted Spurious @ 802.11g Mode Ch11




Chain0 : Conducted Spurious @ 802.11g Mode Ch11




Chain0 : Conducted Spurious @ 802.11n(HT20) Mode Ch 1




Chain0 : Conducted Spurious @ 802.11n(HT20) Mode Ch 1




Chain0 : Conducted Spurious @ 802.11n(HT20) Mode Ch 6




Chain0 : Conducted Spurious @ 802.11n(HT20) Mode Ch 6




Chain0 : Conducted Spurious @ 802.11n(HT20) Mode Ch11




Chain0 : Conducted Spurious @ 802.11n(HT20) Mode Ch11




Chain0 : Conducted Spurious @ 802.11n(HT40) Mode Ch 3




Chain0 : Conducted Spurious @ 802.11n(HT40) Mode Ch 3




Chain0 : Conducted Spurious @ 802.11n(HT40) Mode Ch 6




Chain0 : Conducted Spurious @ 802.11n(HT40) Mode Ch 6



Chain0 : Conducted Spurious @ 802.11n(HT40) Mode Ch 9



Chain0 : Conducted Spurious @ 802.11n(HT40) Mode Ch 9



6. Emissions in Restricted Frequency Bands (Radiated emission measurements)

6.1. Instrument Setting

Receiver Function	Setting (Below 1GHz)	Setting (Above 1GHz)
Detector	QP	Peak and average
RBW	9-150 kHz ; 200-300 Hz 0.15-30 MHz; 9-10 kHz 30-1000 MHz; 100-120 kHz	1MHz
VBW	$\geq 3 \times$ RBW	3MHz
Sweep	Auto couple	Auto couple
Start Frequency	9 kHz	1GHz
Stop Frequency	1 GHz	Tenth harmonic
Attenuation	Auto	Auto


6.2. Test Procedure

- Step 1 Configure the EUT according to ANSI C63.10:2013. The EUT was placed on the top of the turntable 0.8 meter (below 1GHz) and 1.5 meter (above 1GHz) above ground. The center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- Step 2 Power on the EUT and all the companion devices. The turntable was rotated by 360 degree to find the position of the maximum emission level.
- Step 3 The height of the receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of the both horizontal and vertical polarization.
- Step 4 If find the frequencies above the limit or below within 3dB, the antenna tower was scan (from 1m to 4m) and then the turntable was rotated to find the maximum reading.
- Step 5 Set the test-receiver system to peak or CISPR quasi-peak detector with specified bandwidth under maximum hold mode.


- Step 6 For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for reading in spectrum analyzer.
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
- Step 7 If the emissions level of the EUT in peak mode was 3dB lower than the average limit specified then testing will be stopped and peak values of the EUT will be reported. Otherwise, the emissions which do not have 3dB margin will be measured using the quasi-peak method for below 1GHz.
- Step 8 For testing above 1GHz, The emissions level of the EUT in peak mode was lower than average limit, then testing will be stopped and peak values of the EUT will be reported, otherwise, the emission will be measured in average mode again and reported.
- Step 9 In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be quasi-peak measured by receiver.

6.3. Test Diagram


6.3.1. Radiated emission from 9kHz to 30MHz uses Loop Antenna:



6.3.2. Radiated emission below 1GHz using Bilog Antenna



6.3.3. Radiated emission above 1GHz using Horn Antenna



6.4. Limit

Frequency(MHz)	Field Strength(uV/m)	Measurement distance(m)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark:

1. In the above table, the tighter limit applies at the band edges.
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system

6.5. Operating Environment Condition

Temperature (°C) : 25
Relative Humidity (%) : 50
Atmospheric Pressure (hPa) : 1008
Test Date : 2017/8/8~2017/8/14

6.6. Test Result

6.6.1. Measurement results: frequencies 9kHz to 30MHz

The test was performed on EUT under 802.11b/g/n continuously transmitting mode. The worst case occurred at 802.11n(HT40) ch9.

Mode	Chain	Channel	Detector	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Corrected Reading (dBuV/m)	Limit (dBμV/m)	Margin (dB)
802.11n (HT40)	Chain0	9	QP	0.02	20.21	31.56	51.77	121.58	-69.81
802.11n (HT40)	Chain0	9	QP	0.03	20.35	38.29	58.64	118.06	-59.42
802.11n (HT40)	Chain0	9	QP	0.04	19.95	29.98	49.93	115.56	-65.63
802.11n (HT40)	Chain0	9	QP	0.07	19.45	23.78	43.23	110.7	-67.47
802.11n (HT40)	Chain0	9	QP	0.09	19.15	26.15	45.3	108.52	-63.22
802.11n (HT40)	Chain0	9	QP	0.12	19.05	23.81	42.86	106.02	-63.16
802.11n (HT40)	Chain0	9	QP	0.15	19.05	30.31	49.36	104.08	-54.72
802.11n (HT40)	Chain0	9	QP	0.69	19.12	25.71	44.83	70.83	-26.00
802.11n (HT40)	Chain0	9	QP	1.88	19.07	17.32	36.4	70	-33.6
802.11n (HT40)	Chain0	9	QP	3.13	18.94	11.77	30.71	70	-39.29
802.11n (HT40)	Chain0	9	QP	4.33	19.75	9.77	29.52	70	-40.48
802.11n (HT40)	Chain0	9	QP	5.64	20.28	10.05	30.33	70	-39.67

Remark: Corr. Factor = Antenna Factor + Cable Loss

Measurement results: frequencies below 1 GHz

The test was performed on EUT under 802.11b/g/n continuously transmitting mode. The worst case occurred at 802.11n(HT40) ch9.

Mode	Chain	Ch	Ant Polarity	Detector	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Corrected Reading (dBuV/m)	Limit (dBμV/m)	Margin (dB)
802.11n (HT40)	Chain0	9	H	QP	161.92	20.67	0.4	21.07	43.5	-22.43
802.11n (HT40)	Chain0	9	H	QP	315.18	22.14	13.2	35.34	46	-10.66
802.11n (HT40)	Chain0	9	H	QP	375.32	23.69	11.84	35.54	46	-10.46
802.11n (HT40)	Chain0	9	H	QP	402.48	24.41	9.11	33.52	46	-12.48
802.11n (HT40)	Chain0	9	H	QP	414.12	24.76	8.63	33.39	46	-12.61
802.11n (HT40)	Chain0	9	H	QP	897.18	33.47	4.31	37.78	46	-8.22
802.11n (HT40)	Chain0	9	V	QP	49.4	18.73	9.8	28.54	40	-11.46
802.11n (HT40)	Chain0	9	V	QP	80.44	16.03	6.58	22.61	40	-17.39
802.11n (HT40)	Chain0	9	V	QP	90.14	14.28	8.81	23.09	43.5	-20.41
802.11n (HT40)	Chain0	9	V	QP	154.16	20.61	2.35	22.96	43.5	-20.54
802.11n (HT40)	Chain0	9	V	QP	249.22	19.96	4.95	24.91	46	-21.09
802.11n (HT40)	Chain0	9	V	QP	730.34	31.21	2.33	33.54	46	-12.46

Remark: Corr. Factor = Antenna Factor + Cable Loss

6.6.2. Measurement results: frequency above 1GHz to 25GHz

Mode	Chain	Ch	Ant Polarity	Detector	Freq. (MHz)	Preamp (dB)	Factor (dB/m)	Reading (dBμV)	Corrected Reading (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11b	Chain0	1	H	PK	4824	40.03	3.07	50.99	54.06	74	-19.94
802.11b	Chain0	1	H	AV	4824	40.03	3.07	49.77	52.84	54	-1.16
802.11b	Chain0	1	H	PK	7236	38.15	9.99	31.76	41.75	74	-32.25
802.11b	Chain0	1	V	PK	2412	39.07	35.05	64.59	99.64	74	25.64
802.11b	Chain0	1	V	PK	2412	39.07	35.05	67.34	102.4	74	28.4
802.11b	Chain0	1	V	PK	2412	39.07	35.05	69.43	104.48	74	30.48
802.11b	Chain0	1	V	PK	4824	40.03	3.07	46.68	49.75	74	-24.25
802.11b	Chain0	1	V	PK	7236	38.15	9.99	31.45	41.44	74	-32.56
802.11b	Chain0	6	H	PK	4874	39.94	3.26	47.05	50.31	74	-23.69
802.11b	Chain0	6	H	PK	7311	38.07	10.29	36.89	47.19	74	-26.81
802.11b	Chain0	6	V	PK	4874	39.94	3.26	43.89	47.15	74	-26.85
802.11b	Chain0	6	V	PK	7311	38.07	10.29	34.34	44.63	74	-29.37
802.11b	Chain0	11	H	PK	4924	39.86	3.46	48.38	51.84	74	-22.16
802.11b	Chain0	11	H	PK	7386	37.99	10.6	30.88	41.47	74	-32.53
802.11b	Chain0	11	V	PK	3990	40.36	0.86	41.77	42.63	74	-31.37
802.11b	Chain0	11	V	PK	4924	39.86	3.46	45.14	48.6	74	-25.4
802.11g	Chain0	1	H	PK	4824	40.03	3.07	46.44	49.5	74	-24.5
802.11g	Chain0	1	H	PK	7236	38.15	9.99	30.95	40.94	74	-33.06
802.11g	Chain0	1	V	PK	3990	40.36	0.86	40.17	41.03	74	-32.97
802.11g	Chain0	1	V	PK	4824	40.03	3.07	42.98	46.05	74	-27.95
802.11g	Chain0	1	V	PK	7236	38.15	9.99	31	40.99	74	-33.01
802.11g	Chain0	6	H	PK	3990	40.36	0.86	39.14	40	74	-34
802.11g	Chain0	6	H	PK	4874	39.94	3.26	47.78	51.05	74	-22.95
802.11g	Chain0	6	H	PK	7311	38.07	10.29	31.24	41.53	74	-32.47
802.11g	Chain0	6	V	PK	3990	40.36	0.86	40.95	41.81	74	-32.19
802.11g	Chain0	6	V	PK	4874	39.94	3.26	42.55	45.81	74	-28.19
802.11g	Chain0	6	V	PK	7311	38.07	10.29	31.3	41.59	74	-32.41
802.11g	Chain0	11	H	PK	3990	40.36	0.86	38.68	39.55	74	-34.45
802.11g	Chain0	11	H	PK	4924	39.86	3.46	47.6	51.06	74	-22.94
802.11g	Chain0	11	H	PK	7386	37.99	10.6	31.21	41.81	74	-32.19
802.11g	Chain0	11	V	PK	3990	40.36	0.86	40.44	41.3	74	-32.7
802.11g	Chain0	11	V	PK	4924	39.86	3.46	43.82	47.28	74	-26.72
802.11g	Chain0	11	V	PK	7386	37.99	10.6	29.49	40.09	74	-33.91

Remark: Correction Factor = Antenna Factor + Cable Loss + High Pass Filter Loss - Pre_Amplifier Gain

Mode	Chain	Ch	Ant Polarity	Detector	Freq. (MHz)	Preamp (dB)	Factor (dB/m)	Reading (dBμV)	Corrected Reading (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11n (HT20)	Chain0	1	H	PK	3990	40.36	0.86	37.9	38.76	74	-35.24
802.11n (HT20)	Chain0	1	H	PK	4824	40.03	3.07	46.74	49.8	74	-24.2
802.11n (HT20)	Chain0	1	H	PK	7236	38.15	9.99	33.2	43.19	74	-30.81
802.11n (HT20)	Chain0	1	V	PK	3990	40.36	0.86	40.75	41.61	74	-32.39
802.11n (HT20)	Chain0	1	V	PK	4824	40.03	3.07	44.7	47.76	74	-26.24
802.11n (HT20)	Chain0	1	V	PK	7236	38.15	9.99	31.51	41.5	74	-32.5
802.11n (HT20)	Chain0	6	H	PK	4874	39.94	3.26	47.16	50.42	74	-23.58
802.11n (HT20)	Chain0	6	H	PK	7311	38.07	10.29	31.14	41.43	74	-32.57
802.11n (HT20)	Chain0	6	V	PK	3990	40.36	0.86	41.59	42.46	74	-31.54
802.11n (HT20)	Chain0	6	V	PK	4874	39.94	3.26	42.57	45.84	74	-28.16
802.11n (HT20)	Chain0	6	V	PK	7311	38.07	10.29	31.72	42.01	74	-31.99
802.11n (HT20)	Chain0	11	H	PK	3990	40.36	0.86	39.39	40.26	74	-33.74
802.11n (HT20)	Chain0	11	H	PK	4924	39.86	3.46	47.01	50.46	74	-23.54
802.11n (HT20)	Chain0	11	H	PK	7386	37.99	10.6	31.49	42.09	74	-31.91
802.11n (HT20)	Chain0	11	V	PK	3990	40.36	0.86	38.64	39.5	74	-34.5
802.11n (HT20)	Chain0	11	V	PK	4924	39.86	3.46	43.33	46.79	74	-27.21
802.11n (HT20)	Chain0	11	V	PK	7386	37.99	10.6	32.83	43.43	74	-30.57

Remark: Correction Factor = Antenna Factor + Cable Loss + High Pass Filter Loss - Pre_Amplifier Gain

Mode	Chain	Ch	Ant Polarity	Detector	Freq. (MHz)	Preamp (dB)	Factor (dB/m)	Reading (dBμV)	Corrected Reading (dBμV/m)	Limit (dBμV/m)	Margin (dB)
802.11n (HT40)	Chain0	3	H	PK	4844	40	3.14	42.13	45.27	74	-28.73
802.11n (HT40)	Chain0	3	H	PK	7266	38.12	10.11	31.54	41.65	74	-32.35
802.11n (HT40)	Chain0	3	V	PK	3990	40.36	0.86	41.23	42.1	74	-31.9
802.11n (HT40)	Chain0	3	V	PK	4844	40	3.14	41.74	44.89	74	-29.11
802.11n (HT40)	Chain0	3	V	PK	7266	38.12	10.11	31.3	41.41	74	-32.59
802.11n (HT40)	Chain0	6	H	PK	3990	40.36	0.86	38.87	39.73	74	-34.27
802.11n (HT40)	Chain0	6	H	PK	4874	39.94	3.26	43.22	46.48	74	-27.52
802.11n (HT40)	Chain0	6	H	PK	7311	38.07	10.29	30.84	41.14	74	-32.86
802.11n (HT40)	Chain0	6	V	PK	3990	40.36	0.86	41.38	42.25	74	-31.75
802.11n (HT40)	Chain0	6	V	PK	4874	39.94	3.26	40.75	44.01	74	-29.99
802.11n (HT40)	Chain0	6	V	PK	7311	38.07	10.29	30.76	41.05	74	-32.95
802.11n (HT40)	Chain0	9	H	PK	4904	39.89	3.38	43.07	46.45	74	-27.55
802.11n (HT40)	Chain0	9	H	PK	7356	38.02	10.48	29.92	40.39	74	-33.61
802.11n (HT40)	Chain0	9	V	PK	4904	39.89	3.38	40.69	44.07	74	-29.93
802.11n (HT40)	Chain0	9	V	PK	7356	38.02	10.48	29.9	40.38	74	-33.62

Remark: Correction Factor = Antenna Factor + Cable Loss + High Pass Filter Loss - Pre_Amplifier Gain

7. Emission on Band Edge

7.1. Instrument Setting

Spectrum Function	Setting
Detector	Peak and average
RBW	1MHz
VBW	3MHz
Sweep	Auto couple
Restrict bands	2310 MHz ~ 2390 MHz 2483.5 MHz ~ 2500 MHz
Attenuation	Auto

7.2. Test Procedure

The test procedure is the same as Emissions in Restricted Frequency Bands (Radiated emission measurements).

7.3. Operating Environment Condition


Temperature (°C) : 25
Relative Humidity (%) : 50
Atmospheric Pressure (hPa) : 1008
Test Date : 2017/8/11~2017/8/16

7.4. Test Results


Mode	Frequency (MHz)	Spectrum Analyzer Detector	Ant. Pol. (H/V)	Correction Factor (dB/m)	Reading (dBμV)	Corrected Reading (dBμV/m)	Limit @ 3 m (dBμV/m)	Margin (dB)	Restricted band (MHz)
802.11b Chain0	2365.81	PK	V	33.74	22.56	56.30	74	-17.70	2310~2390
	2390.00	AV	V	33.85	8.03	41.88	54	-12.12	
	2494.48	PK	V	34.35	21.51	55.86	74	-18.14	2483.5~2500
	2483.50	AV	V	34.30	8.67	42.97	54	-11.03	
802.11g Chain0	2390.00	PK	V	33.85	26.74	60.59	74	-13.41	2310~2390
	2390.00	AV	V	33.85	11.42	45.27	54	-8.73	
	2483.50	PK	V	34.30	30.73	65.03	74	-8.97	2483.5~2500
	2483.50	AV	V	34.30	15.15	49.45	54	-4.55	
802.11n (HT20) Chain0	2389.99	PK	V	33.85	32.70	66.55	74	-7.45	2310~2390
	2390.00	AV	V	33.85	13.24	47.09	54	-6.91	
	2483.50	PK	V	34.30	34.76	69.06	74	-4.94	2483.5~2500
	2483.50	AV	V	34.30	15.92	50.22	54	-3.78	
802.11n (HT40) Chain0	2388.94	PK	V	33.85	32.84	66.69	74	-7.31	2310~2390
	2390.00	AV	V	33.85	19.34	53.19	54	-0.81	
	2483.50	PK	V	34.30	38.96	73.26	74	-0.74	2483.5~2500
	2483.50	AV	V	34.30	18.98	53.28	54	-0.72	

Remark: Correction Factor = Antenna Factor + Cable Loss


Chain0 : Restricted Band Bandedge @ 802.11b Mode Ch1 PK




Chain0 : Restricted Band Bandedge @ 802.11b Mode Ch1 AV




Chain0 : Restricted Band Bandedge @ 802.11b Mode Ch11 PK




Chain0 : Restricted Band Bandedge @ 802.11b Mode Ch11 AV




Chain0 : Restricted Band Bandedge @ 802.11g Mode Ch1 PK




Chain0 : Restricted Band Bandedge @ 802.11g Mode Ch1 AV




Chain0 : Restricted Band Bandedge @ 802.11g Mode Ch11 PK




Chain0 : Restricted Band Bandedge @ 802.11g Mode Ch11 AV




Chain0 : Restricted Band Bandedge @ 802.11n(HT20) Mode Ch1 PK




Chain0 : Restricted Band Bandedge @ 802.11n(HT20) Mode Ch1 AV




Chain0 : Restricted Band Bandedge @ 802.11n(HT20) Mode Ch11 PK




Chain0 : Restricted Band Bandedge @ 802.11n(HT20) Mode Ch11 AV




Chain0 : Restricted Band Bandedge @ 802.11n(HT40) Mode Ch1 PK




Chain0 : Restricted Band Bandedge @ 802.11n(HT40) Mode Ch1 AV




Chain0 : Restricted Band Bandedge @ 802.11n(HT40) Mode Ch11 PK




Chain0 : Restricted Band Bandedge @ 802.11n(HT40) Mode Ch11 AV



Chain0 : Authorized Band Bandedge @ 802.11b ch1



Chain0 : Authorized Band Bandedge @ 802.11b ch1



[illegible]

Agilent Spectrum Analyzer - Swept SA

Marker 2 2.4835000000 GHz

Ref Offset 10.5 dB
Ref 10.50 dBm

PN0: Fast IF Gain: Low

Trig: Free Run
Atten: 10 dB

Avg Type: Log-Pwr
Avg/Hold: >100/100

09:59:00 AM Aug 16, 2017

TRACE [1] 3 of 5

TYPE [MANUAL]

DET [RMS]

Mkr2 2.483500 GHz
-55.875 dBm

Start 2.44000 GHz
#Res BW 100 kHz

#VBW 300 kHz


Stop 2.57000 GHz
Sweep 12.7 ms (9999 pts)

MR#	MODE	TRG	SCN	F	Y	FUNCTION	WIDTH	VALUE
1	N		f	2.462 625 GHz	-12.447 dBm			
2	N		f	2.483 500 GHz	-55.875 dBm			
3								
4								
5								
6								
7								
8								
9								
10								
11								
12								


MSG

STATUS


Chain0 : Authorized Band Bandedge @ 802.11n(HT20) ch1




Chain0 : Authorized Band Bandedge @ 802.11n(HT20) ch11



Chain0 : Authorized Band Bandedge @ 802.11n(HT40) CH3



Chain0 : Authorized Band Bandedge @ 802.11n(HT40) ch9



8. AC Power Line Conducted Emission


8.1. Measuring instrument setting

Receiver Function	Setting
Detector	QP
Start frequency	0.15MHz
Stop frequency	30MHz
IF bandwidth	9 kHz
Attenuation	10dB

8.2. Test Procedure

- Step 1 Configure the EUT according to ANSI C63.10:2013. The EUT or host of EHT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
- Step 2 Connect EUT or host of EUT to the power mains through a line impedance stabilization network.
- Step 3 All the companion devices are connected to the other LISN. The LISN should provide 50Uh/50ohms coupling impedance.
- Step 4 The frequency range from 150 kHz to 30MHz was searched.
- Step 5 Set the test-receiver system to peak detector and specified bandwidth with maximum hold mode.
- Step 6 The measurement has to be done between each power line and ground at the power terminal.

8.3. Test Diagram



8.4. Limit

Freq. (MHz)	Conducted Limit (dBuV)	
	Q.P.	Ave.
0.15~0.50	66 – 56	56 – 46
0.50~5.00	56	46
5.00~30.0	60	50

8.5. Operating Environment Condition

Temperature (°C) : 25
 Relative Humidity (%) : 50
 Atmospheric Pressure (hPa) : 1008
 Test Date : 2017/8/15


8.6. Test Results

Phase:	Live Line			
Temperature:	25	°C	Model No.:	X1 PRO
Relative Humidity:	50	%	Test Date:	Aug. 15, 2017
Atmospheric Pressure:	1009	hPa	Remark:	N/A

Frequency (MHz)	Corr. Factor (dB)	Level Qp (dBuV)	Limit Qp (dBuV)	Level Av (dBuV)	Limit Av (dBuV)	Margin (dB)	
						Qp	Av
0.158	9.70	45.08	65.56	32.91	55.56	-20.48	-22.65
0.263	9.70	42.85	61.34	33.14	51.34	-18.49	-18.20
0.352	9.70	44.98	58.91	32.69	48.91	-13.93	-16.22
0.456	9.70	42.26	56.76	31.51	46.76	-14.50	-15.25
0.535	9.70	39.92	56.00	30.93	46.00	-16.08	-15.07
0.743	9.71	38.69	56.00	30.12	46.00	-17.31	-15.88

Remark:

1. Corr. Factor (dB) = AMN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Level (dBuV) – Limit (dBuV)




Phase:	Neutral Line			
Temperature:	25	°C	Model No.:	X1 PRO
Relative Humidity:	50	%	Test Date:	Aug. 15, 2017
Atmospheric Pressure:	1009	hPa	Remark:	N/A

Frequency (MHz)	Corr. Factor (dB)	Level Qp (dBuV)	Limit Qp (dBuV)	Level Av (dBuV)	Limit Av (dBuV)	Margin (dB)	
						Qp	Av
0.165	9.73	46.94	65.21	36.63	55.21	-18.27	-18.58
0.391	9.73	41.96	58.03	32.72	48.03	-16.07	-15.31
0.499	9.73	39.37	56.01	28.93	46.01	-16.64	-17.08
0.598	9.73	37.51	56.00	30.00	46.00	-18.49	-16.00
0.739	9.73	36.98	56.00	28.31	46.00	-19.02	-17.69
0.862	9.73	36.63	56.00	27.06	46.00	-19.37	-18.94

Remark:

1. Corr. Factor (dB) = AMN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Level (dBuV) – Limit (dBuV)



Appendix A: Test equipment list

Test Equipment/ Test site	Brand	Model No.	Serial No.	Calibration Date	Next Calibration Date
ESCI EMI Test Receiver	Rohde & Schwarz	ESCI	100018	2016/11/30	2017/11/29
Spectrum Analyzer	Rohde & Schwarz	FSP30	100245	2017/02/15	2018/02/14
Horn Antenna (1-18G)	SHWARZBECK	BBHA 9120 D	9120D-456	2014/08/29	2017/08/27
Horn Antenna (14-42G)	SHWARZBECK	BBHA 9170	BBHA9170159	2014/09/16	2017/09/14
Broadband Antenna	SHWARZBECK	VULB 9168	9168-172	2017/04/05	2018/04/04
Pre-Amplifier	EMC Co.	EMC12635SE	980205	2016/10/08	2017/10/07
Pre-Amplifier	MITEQ	JS4-26004000--27-8A	828825	2016/09/12	2017/09/11
Power Meter	Anritsu	ML2495A	0844001	2016/11/09	2017/11/08
Power Sensor	Anritsu	MA2411B	0738452	2016/11/09	2017/11/08
Signal Analyzer	Agilent	N9030A	MY51380492	2016/09/13	2017/09/12
966-2(A) Cable 9kHz~26.5GHz	SUHNER	SMA / EX 100	N/A	2017/08/15	2018/08/14
966-2(B) Cable 9kHz~26.5GHz	SUHNER	SUCOFLEX 104P	CB0005	2017/08/15	2018/08/14
RF Cable 9kHz~26.5GHz	SUHNER	SUCOFLEX 102	CB0006	2017/05/04	2018/05/03
966-2_3m Semi-Anechoic Chamber	966_2	CEM-966_2	N/A	2017/03/29	2018/03/28
High Pass Filter	Wainwright	WHKX3.0/18G-12SS	N/A	2017/06/02	2018/06/01
Active Loop Antenna	SCHWARZBECK MESS-ELEKTRONIC	FMZB1519	1519-067	2017/03/30	2018/03/29

Note: No Calibration Required (NCR).

Test Equipment/ Test site	Brand	Model No.	Serial No.	Calibration Date	Next Calibration Date
EMI Test Receiver	R&S	ESR7	101822	2017/06/01	2018/05/31
Two-Line V-Network	R&S	ENV216	101160	2016/11/16	2017/11/15
Two-Line -V-Network	R&S	ESH3-Z5	838979/014	2016/09/30	2017/09/29
CON-2 Shielded Room	N/A	N/A	N/A	NCR	NCR
CON-2 Cable	SUHNER	BNC / RG-58	2146637	2017/05/08	2018/05/07
Test software	Audix	e3	4.20040112L	NCR	NCR

Note: No Calibration Required (NCR).

Appendix B: Measurement Uncertainty

This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of $k=2$.

Item	Uncertainty
Vertically polarized radiated disturbances from 30MHz~1GHz in a semi-anechoic chamber at a distance of 3m	5.14 dB
Horizontally polarized radiated disturbances from 30MHz~1GHz in a semi-anechoic chamber at a distance of 3m	5.22 dB
Vertically polarized Radiated disturbances from 1GHz~18GHz in a semi-anechoic chamber at a distance of 3m	3.64 dB
Horizontally polarized Radiated disturbances from 1GHz~18GHz in a semi-anechoic chamber at a distance of 3m	3.64 dB
Vertically polarized Radiated disturbances from 18GHz~40GHz in a semi-anechoic chamber at a distance of 3m	2.68 dB
Horizontally polarized Radiated disturbances from 18GHz~40GHz in a semi-anechoic chamber at a distance of 3m	2.68 dB
Radiated disturbances from 9kHz~30MHz in a semi-anechoic chamber at a distance of 3m	3.54 dB
Emission on the Band Edge Test	3.64 dB
Minimum 6dB Bandwidth	0.85 dB
Maximum Conducted Output Power	0.42 dB
Power Spectral Density	0.85 dB
Emissions In Non-Restricted Frequency Bands	0.85 dB
AC Power Line Conducted Emission	2.48 dB