



No.:  
**FCCSZ2025-0067-H**

## TEST REPORT

**FCC ID** : **2ANM3M2V6811X1**

**NAME OF SAMPLE** : **WiFi + BT Module**

**APPLICANT** : **Shenzhen Chuangwei-RGB Electronics Co., Ltd.**

**CLASSIFICATION OF TEST** : **N/A**

**CVC Testing Technology (Shenzhen) Co., Ltd.**



<b>Applicant</b>		Name: Shenzhen Chuangwei-RGB Electronics Co., Ltd.  Address: 13F-16F, Unit A, Skyworth Building, Shennan Road South, Nanshan District, Shenzhen, Guangdong, China	
<b>Equipment Under Test</b>		Product Name: WiFi + BT Module  Model Name: M2V6811X1  Brand Name: N/A  Serial NO.: N/A  Sample NO.: 202507101143-1	
Date of Receipt.	Jul. 10, 2025	Date of Testing	Jul. 10, 2025 ~ Aug. 08, 2025
Test Specification		Test Result	
FCC Part 2 (Section 2.1091) KDB 447498 D04 v01 IEEE C95.1		PASS	
<b>Evaluation of Test Result</b>		The equipment under test was found to comply with the requirements of the standards applied.	
		Seal of CVC  Issue Date: Aug. 08, 2025	
Compiled by:   Zhu Yulin Name      Signature	Reviewed by:   Mo Xianbiao Name      Signature	Approved by:   Dong Sanbi Name      Signature	
<b>Other Aspects: NONE.</b>			
Abbreviations:OK, Pass= passed		Fail = failed	N/A= not applicable
EUT= equipment, sample(s) under tested			

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



## TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	4
1. GENERAL PRODUCT INFORMATION .....	5
2. RF EXPOSURE LIMIT .....	6
4. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER .....	8



## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCCSZ2025-0067-H	Original release	Aug. 08, 2025



## 1. GENERAL PRODUCT INFORMATION

PRODUCT NAME	WiFi + BT Module	
BRAND NAME	N/A	
MODEL NAME	M2V6811X1	
ADDITIONAL MODEL NAME	N/A	
POWER SUPPLY	DC 3.3V from host unit	
MODULATION TYPE	BT	GFSK, $\pi/4$ DQPSK, 8DPSK for FHSS GFSK for DTS
	WiFi	CCK, DQPSK, DBPSK for DSSS 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM
OPERATING FREQUENCY	BT: 2402 ~ 2480MHz WiFi 2.4G: 2412 ~ 2472MHz, WiFi 5G: 5180 ~ 5240MHz, 5260 ~ 5320MHz, 5500 ~ 5700MHz, 5745 ~ 5825MHz	
ANTENNA TYPE  (Remark 4/5)	BT: PCB Antenna, with 4.30dBi gain	
	WiFi 2.4G: ANT1: PCB Antenna, with 3.01dBi gain ANT2: PCB Antenna, with 3.01dBi gain	
	WiFi 5G: ANT1: PCB Antenna, with 3.28dBi gain ANT2: PCB Antenna, with 3.28dBi gain	
HARDWARE VERSION:	M2V6811 N012406-003076-001 VER00.01 7E9.05.09	
SOFTWARE VERSION:	RTL8822CU_Golden_BT/WiFi_20230826	
I/O PORTS	Refer to User's Manual	
CABLE SUPPLIED	N/A	
Remark:  1. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report. 3. EUT photo refer to the report (Report NO.: FCCSZ2024-0030-EUT). 4. Please refer to the antenna report. 5. Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, CVC is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.		



## 2. RF EXPOSURE LIMIT

(Option B) According to FCC Part2.1091 and FCC Part1.1307b, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where:

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz;

and

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

(Option C) Or using Table 1 and the minimum separation distance ( $R$  in meters) from the body of a nearby person for the frequency ( $f$  in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply,  $R$  must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to §1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency (MHz)	Threshold ERP (W)
0.3 - 1.34	$1920R^2$
1.34 - 30	$3450R^2/f^2$
30 - 300	$3.38R^2$
300 - 1500	$0.0128R^2/f^2$
1500 - 100000	$19.2R^2$



For multiple RF sources: Multiple RF sources are exempt if:

- a) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).
- b) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for  $P_{th}$ , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

$P_i$  = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source  $i$  at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$  = the exemption threshold power ( $P_{th}$ ) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source  $i$ .

$ERP_j$  = the ERP of fixed, mobile, or portable RF source  $j$ .

$ERP_{th,j}$  = exemption threshold ERP for fixed, mobile, or portable RF source  $j$ , at a distance of at least  $\lambda/2\pi$  according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

$Evaluated_k$  = the maximum reported SAR or MPE of fixed, mobile, or portable RF source  $k$  either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure\ Limit_k$  = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source  $k$ , as applicable from § 1.1310 of this chapter.

### 3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



#### 4. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

Option	Mode	Frequency (MHz)	Maximum Conducted Power (dBm)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
B	BT	2402 ~ 2480	6.83	7	+1	6	8
	WiFi 2.4G MIMO	2412 ~ 2472	17.53	18	+1	17	19
	WiFi 5G MIMO	5180 ~ 5240	16.32	16	+1	15	17
		5260 ~ 5320	16.03	16	+1	15	17
		5500 ~ 5720	16.20	16	+1	15	17
		5745 ~ 5825	15.22	15	+1	14	16

Option	Mode	Maximum tune up power(dBm)	Maximum Antenna Gain(dBi)	EIRP (dBm)	ERP (dBm)	ERP (mW)	Part1.1307b Threshold (mW)	Ratio	Verify
B	BT	8	4.30	12.30	10.15	10.35	3060	0.003	PASS
	WiFi 2.4G MIMO	19	3.01	22.01	19.86	96.83	3060	0.032	PASS
	WiFi 5G MIMO	17	3.28	20.28	18.13	65.01	3060	0.021	PASS

#### CALCULATION FOR SIMULTANEOUS TRANSMISSION:

BT and WiFi can transmit simultaneously, the formula of calculated the MPE is

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Max: BT + 2.4G WiFi = 0.003 + 0.032 = 0.035 < 1, which is less than the "1" limit.

----- End of the Report -----



## Important

- (1) The test report is valid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of tester, reviewer and approval;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days;
- (6) Generally, commission test results apply to the samples as received. The sample information is provided by the customer and laboratory is not responsible for its authenticity;
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

Address: No. 1301-14&16, Guanguang Road, Xinlan Community, Guanlan Subdistrict, Longhua District, Shenzhen, Guangdong, China

Post Code: 518110      Tel: 0755-23763060-8805

Fax: 0755-23763060      E-mail: sz-kf@cvc.org.cn

<http://www.cvc.org.cn>