

XPW01 User Manual

Battery installation

Rotate the battery cover counterclockwise to the dot mark, open the battery cover and put new battery in, align the battery with the dot mark and close the batter cover, then rotate the batter cover clockwise (in the process, please don't lose or damage waterproof rubber gasket)

Sensor pairing

After installing the battery, wait for 2m until blue lamp on the power meter flickers. Then, start the sensor option of the stopwatch power meter for search until “find power meter” appears.

Calibration

Please calibrate the power meter prior to use each time. Rotate the crank for several circles and then make the crank vertical to the ground, with hands and feet leaving crank. Keep it for 2 minutes and then enter the stopwatch power meter calibration interface, click on calibration, until the stopwatch shows “calibration success”. If the returned value of stopwatch is zero, it means calibration failure. Please repeat calibrating.

FCC Statement:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.