

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093) and
IEEE Std 1528-2013**

Product Name : Smart Phone

Brand Name : OUKITEL

Model Name : WP200 Pro

Family Model : WP200, WP200 S, WP200 Plus,
WP200 Ultra, WP200 TITAN, WP200 GT

Report No. : S24110702506001

FCC ID : 2ANMU-24139

Prepared for

SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD
A2 2F BUILDING ENET NEW INDUSTRIAL PARK,DAFU INDUSTRIAL ZONE, GUANLAN,
LONGHUA SHENZHEN, 518XXX China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District,
Shenzhen, Guangdong, People's Republic of China
Tel. 0755-23200050 Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD
Address..... A2 2F BUILDING ENET NEW INDUSTRIAL PARK,DAFU INDUSTRIAL
ZONE, GUANLAN, LONGHUA SHENZHEN, 518XXX China

Manufacturer's Name . SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD
Address..... A2 2F BUILDING ENET NEW INDUSTRIAL PARK,DAFU INDUSTRIAL
ZONE, GUANLAN, LONGHUA SHENZHEN, 518XXX China

Product description

Product name Smart Phone
Brand Name OUKITEL
Model and/or type
reference WP200 Pro
Family Model WP200, WP200 S, WP200 Plus, WP200 Ultra, WP200 TITAN,
WP200 GT
FCC 47 CFR Part 2(2.1093)

Standards IEEE Std 1528-2013
Published RF exposure KDB procedures

This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093). The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Test Sample Number S241107025006

Date of Test

Date (s) of performance of tests... Nov.18, 2024~ Dec.11, 2024

Date of Issue Jan.08, 2025

Test Result..... **Pass**

Prepared By : Owen Xiao
Owen Xiao
(Project Engineer)

Reviewed By : Aaron Cheng
Aaron Cheng
(Supervisor)

Approved By : Alex Li
Alex Li
(Manager)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Jan.08, 2025	Owen Xiao

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits.....	6
1.2. Statement of Compliance	7
1.3. EUT Description	7
1.4. Test specification(s)	9
1.5. Ambient Condition.....	9
2. SAR Measurement System	10
2.1. SATIMO SAR Measurement Set-up Diagram	10
2.2. Robot	11
2.3. E-Field Probe.....	12
2.3.1. E-Field Probe Calibration	12
2.4. SAM phantoms	13
2.4.1. Technical Data	14
2.5. Device Holder	15
2.6. Test Equipment List	16
3. SAR Measurement Procedures	18
3.1. Power Reference	18
3.2. Area scan & Zoom scan.....	18
3.3. Description of interpolation/extrapolation scheme	20
3.4. Volumetric Scan	20
3.5. Power Drift	20
4. System Verification Procedure	21
4.1. Tissue Verification	21
4.1.1. Tissue Dielectric Parameter Check Results	22
4.2. System Verification Procedure	23
4.2.1. System Verification Results	24
5. SAR Measurement variability and uncertainty	25
5.1. SAR measurement variability.....	25
5.2. SAR measurement uncertainty	25
6. RF Exposure Positions	26
6.1. Ear and handset reference point	26
6.2. Definition of the cheek position	26
6.3. Definition of the tilt position	28
6.4. Body Worn Accessory	28
6.5. Wireless Router Devices	29
7. RF Output Power	30
7.1. GSM Conducted Power	30
7.2. WCDMA Conducted Power	30
7.3. LTE Conducted Power	32

7.4. NR Conducted Power	52
7.5. WLAN & Bluetooth Output Power	59
8. Antenna Location	63
9. Stand-alone SAR test exclusion	63
10. SAR Results	64
10.1. SAR measurement Result	64
10.1.1. SAR measurement Result of GSM850	64
10.1.2. SAR measurement Result of GSM1900	65
10.1.3. SAR measurement Result of WCDMA Band 2	66
10.1.4. SAR measurement Result of WCDMA Band 4	67
10.1.5. SAR measurement Result of WCDMA Band 5	68
10.1.6. SAR measurement Result of LTE Band 2	69
10.1.7. SAR measurement Result of LTE Band 4	71
10.1.8. SAR measurement Result of LTE Band 5	73
10.1.9. SAR measurement Result of LTE Band 7	75
10.1.10. SAR measurement Result of LTE Band 12	78
10.1.11. SAR measurement Result of LTE Band 17	80
10.1.12. SAR measurement Result of LTE Band 25	82
10.1.13. SAR measurement Result of LTE Band 26a	84
10.1.14. SAR measurement Result of LTE Band 26b	85
10.1.15. SAR measurement Result of LTE Band 66	87
10.1.16. SAR measurement Result of NR 78	89
10.1.17. SAR measurement Result of WLAN2.4G	93
10.1.18. SAR measurement Result of WLAN5.2G	94
10.1.19. SAR measurement Result of WLAN5.8G	95
10.2. Simultaneous Transmission Analysis	97
11. Appendix A. Photo documentation	100
12. Appendix B. System Check Plots	101
13. Appendix C. Plots of High SAR Measurement	126
14. Appendix D. Calibration Certificate	212

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE

HEAD AND TRUNK LIMIT
1.6 W/kg, Limb LIMIT 4.0 W/kg
APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for WP200 Pro are as follows.

RF Exposure Conditions		Equipment Class -Highest Reported SAR (W/kg)				Max. Reported SAR (W/kg)
		PCE	DTS	NII	DSS	
1-g Head		0.658	0.299	0.533	0.105	0.658
1-g Body-Worn (Separation distance of 10mm)		1.298	0.064	0.217	0.053	1.298
1-g Hotspot (Separation distance of 10mm)		1.298	0.064	0.217	0.053	
Max Simultaneous Tx	Head	0.763	0.752	0.925	0.763	0.918
	Body-Worn	1.515	1.362	1.515	1.351	1.515
	Hotspot	1.515	1.362	1.515	1.351	
	Extremity	1.707	1.577	1.707	1.501	1.707

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093), and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information	
Product Name	Smart Phone
Brand Name	OUKITEK
Model Name	WP200 Pro
Family Model	WP200, WP200 S, WP200 Plus, WP200 Ultra, WP200 TITAN, WP200 GT
Model Difference	All models are the same circuit and RF module, except for model names.
FCC ID	2ANMU-24139
Device Phase	Identical Prototype
Exposure Category	General population / Uncontrolled environment
Antenna Type	FPC Antenna
Battery Information	DC 3.87V, 8800mAh, 34.056Wh
HW Version	N/A
SW Version	V04

Device Operating Configurations			
Supporting Mode(s)	GSM850/1900,WCDMABand2/4/5,LTEBand2/4/5/7/12/17/25/26/66, NR SA n78,WLAN 2.4G/5G, Bluetooth, NFC		
Test Modulation	GSM(GMSK), WCDMA(QPSK), LTE(QPSK/16QAM), NR(DFT-s-OFDM:PI/2 BPSK/QPSK/16-QAM/64QAM/256QAMCP-OFDM:QPSK/16-QAM/64QAM/256QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK), NFC(ASK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 4	1710-1755	2110-2155
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 12	699-716	729-746
	LTE Band 17	704-716	734-746
	LTE Band 25	1850-1915	1930-1995
	LTE Band 26a	814-824	859-869
	LTE Band 26b	824-849	869-894
	LTE Band 66	1710-1780	2110-2200
	NR n78	3450-3550	
	WLAN 2.4G	2412-2462	
	WLAN 5.2G	5180-5240	
	WLAN 5.8G	5745-5825	
	Bluetooth	2402-2480	
	NFC	13.56	
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control “all 1”(WCDMA Band 2)		
	3, tested with power control “all 1”(WCDMA Band 4)		
	3, tested with power control “all 1”(WCDMA Band 5)		
	3, tested with power control all Max.(LTE Band 2)		
	3, tested with power control all Max.(LTE Band 4)		
	3, tested with power control all Max.(LTE Band 5)		
	3, tested with power control all Max.(LTE Band 7)		
	3, tested with power control all Max.(LTE Band 12)		
	3, tested with power control all Max.(LTE Band 17)		

	3, tested with power control all Max.(LTE Band 25)
	3, tested with power control all Max.(LTE Band 26)
	3, tested with power control all Max.(LTE Band 66)
	3, tested with power control all Max.(NR SA 78)

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices
KDB 941225 D06 Hotspot SAR
KDB 648474 D04 Handset SAR

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe 4024-EPGO-442 with following specifications is used



- Dynamic range: 0.01-100 W/kg
- Tip Diameter : 2.5 mm
- Distance between probe tip and sensor center: 1 mm
- Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
- Probe linearity: ± 0.06 dB
- Axial isotropy: ± 0.01 dB
- Hemispherical Isotropy: ± 0.01 dB
- Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
- Lower detection limit: 8mW/kg

Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by Mobile Phones.

2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positionner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm ±0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head(mm)		Right Head(mm)		Flat Part(mm)	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μm .

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	4024-EPGO-442	Oct.4.2024	Oct.3.2025
☒	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Feb. 21, 2024	Feb. 20, 2027
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Feb. 21, 2024	Feb. 20, 2027
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	3500 MHz Dipole	SID3500	SN 09/12 DIP 3G500-360	Oct. 15, 2022	Oct. 14, 2025
☐	MVG	3700 MHz Dipole	SID3700	SN 09/12 DIP 3G/700-361	Oct. 15 2022	Oct. 14 2025
☒	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	Nov. 29, 2024	Nov. 28, 2025
☒	R&S	Universal radio communication tester	CMU200	105747	Apr. 26, 2024	Apr. 25, 2025

☒	R&S	Wideband radio communication tester	CMW500	103917	Apr. 26, 2024	Apr. 25, 2025
☒	Anritsu	4G LTE comprehensive tester	MT8821C	6262192315	2024/7/17	2025/7/16
☒	Anritsu	5G NR comprehensive tester	MT8000A	6262186364	2024/7/17	2025/7/16
☒	HP	Network Analyzer	E5071C	LPS-461	Oct. 15, 2024	Oct. 14, 2025
☒	Agilent	MXG Vector Signal Generator	N5182A	MY47070317	Apr. 25, 2024	Apr. 24, 2025
☒	Agilent	Power meter	E4419B	MY45102538	Apr. 25, 2024	Apr. 24, 2025
☒	Agilent	Power sensor	E9301A	US39212148	Apr. 25, 2024	Apr. 24, 2025
☒	Agilent	Power sensor	E9301A	US39212148	Apr. 25, 2024	Apr. 24, 2025
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Apr. 26, 2024	Apr. 25, 2027
☒	N/A	Thermometer	N/A	LES-085	Mar. 27, 2023	Mar. 26, 2026
☒	MVG	SAM Phantom	SSM2	SN 16/15 SAM119	NCR	NCR
☒	MVG	Device Holder	SMPPD	SN 16/15 MSH100	NCR	NCR

Measurement Software

Manufacturer	Software Name	Software Version
SATIMO	OpenSAR	V4_02_31

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For Wi-Fi/BT power measurement, use engineering software to configure EUT Wi-Fi/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure Wi-Fi/BT output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT Wi-Fi/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan

above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	≤ 1.5 · $\Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful form multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is define in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.

4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r (\pm 5\%)$	σ (S/m) ($\pm 5\%$)	ϵ_r	σ (S/m)		
Head 750	750	41.96 (39.86~44.06)	0.89 (0.85~0.93)	40.77	0.90	21.6 °C	Dec. 13, 2024
Head 850	835	41.50 (39.43~43.58)	0.90 (0.86~0.95)	41.83	0.91	21.2 °C	Dec. 11, 2024
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.08	1.39	21.4 °C	Nov. 21, 2024
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.08	1.39	21.5 °C	Dec. 06, 2024
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.33	1.44	21.7 °C	Nov. 24, 2024
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.33	1.44	21.6 °C	Dec. 09, 2024
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	37.96	1.80	21.2 °C	Nov. 18, 2024
Head 2600	2600	39.01 (37.06~40.96)	1.96 (1.86~2.06)	38.88	1.98	21.4 °C	Nov. 25, 2024
Head 3500	3500	37.93 (36.04~39.82)	2.91 (2.77~3.05)	38.01	2.83	21.8 °C	Nov. 26, 2024
Head 5200	5200	36.00 (34.20~37.80)	4.66 (4.43~4.89)	34.65	4.50	21.3 °C	Dec. 11, 2024
Head 5800	5800	35.30 (33.54~37.07)	5.27 (5.01~5.53)	34.03	5.17	21.4 °C	Nov. 30, 2024

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W) ($\pm 10\%$)		Measured SAR			Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (W/Kg)	10-g (W/Kg)	Input Power	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
750MHz	8.60 (7.74~9.46)	5.78 (5.20~6.36)	20dBm	0.905	0.554	9.05	5.54	21.6 °C	Dec. 13, 2024
835MHz	9.40 (8.46~10.34)	6.28 (5.65~6.91)	18dBm	0.595	0.384	9.43	6.09	21.2 °C	Dec. 11, 2024
1800MHz	37.06 (33.35~40.77)	20.01 (18.01~22.01)	18dBm	2.380	1.232	38.08	19.71	21.4 °C	Nov. 21, 2024
1800MHz	37.06 (33.35~40.77)	20.01 (18.01~22.01)	18dBm	2.273	1.176	36.37	18.82	21.5 °C	Dec. 06, 2024
1900MHz	39.69 (35.72~43.66)	20.92 (18.83~23.01)	18dBm	2.510	1.231	40.16	19.70	21.7 °C	Nov. 24, 2024
1900MHz	39.69 (35.72~43.66)	20.92 (18.83~23.01)	18dBm	2.396	1.181	38.34	18.90	21.6 °C	Dec. 09, 2024
2450MHz	50.05 (45.05~55.06)	23.80 (21.42~26.18)	18dBm	3.347	1.404	53.55	22.46	21.2 °C	Nov. 18, 2024
2600MHz	54.16 (48.74~59.58)	24.85 (22.37~27.34)	20dBm	5.709	2.368	57.09	23.68	21.4 °C	Nov. 25, 2024
3500MHz	67.18 (60.47~73.89)	24.50 (22.05~26.95)	20dBm	7.000	2.339	70.00	23.39	21.8 °C	Nov. 26, 2024
5200MHz	162.59 (146.33~178.85)	56.21 (50.59~61.83)	20dBm	15.654	5.450	156.54	54.50	21.3 °C	Dec. 11, 2024
5800MHz	182.20 (163.98~200.42)	61.32 (55.19~67.45)	20dBm	19.246	6.543	192.46	65.43	21.4 °C	Nov. 30, 2024

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.



Fig 6.1.1 Front, back, and side views of SAM phantom

6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 6.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

6.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest

spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 6.4.1 – Test positions for body-worn devices

6.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

7. RF Output Power

7.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	128	189	251	Tune-up	128	189	251
Frequency (MHz)	(dBm)	824.2	836.4	848.8	Tune-up	824.2	836.4	848.8
GSM (GMSK)	32.50	32.29	32.07	31.90	23.47	23.26	23.04	22.87
GPRS(GMSK,1 Tx slot)	32.50	32.29	32.05	31.90	23.47	23.26	23.02	22.87
GPRS(GMSK,2 Tx slot)	32.00	31.67	31.45	31.16	25.98	25.65	25.43	25.14
GPRS(GMSK,3 Tx slot)	30.00	29.96	29.68	29.27	25.74	25.70	25.42	25.01
GPRS(GMSK,4 Tx slot)	29.00	28.86	28.84	27.94	25.99	25.85	25.83	24.93
EGPRS(8PSK,1 Tx slot)	26.50	26.26	26.42	25.88	17.47	17.23	17.39	16.85
EGPRS(8PSK,2 Tx slot)	25.50	25.29	24.98	24.78	19.48	19.27	18.96	18.76
EGPRS(8PSK,3 Tx slot)	23.50	23.15	22.76	22.82	19.24	18.89	18.50	18.56
EGPRS(8PSK,4 Tx slot)	22.00	21.91	21.78	21.64	18.99	18.90	18.77	18.63
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	512	661	810	Tune-up	512	661	810
Frequency (MHz)	(dBm)	1850.2	1880	1909.8	Tune-up	1850.2	1880	1909.8
GSM (GMSK)	30.00	29.43	29.64	29.65	20.97	20.40	20.61	20.62
GPRS(GMSK,1 Tx slot)	30.00	29.46	29.69	29.68	20.97	20.43	20.66	20.65
GPRS(GMSK,2 Tx slot)	29.50	29.01	29.23	29.23	23.48	22.99	23.21	23.21
GPRS(GMSK,3 Tx slot)	28.00	27.60	27.75	27.78	23.74	23.34	23.49	23.52
GPRS(GMSK,4 Tx slot)	27.00	26.50	26.66	26.72	23.99	23.49	23.65	23.71
EGPRS(8PSK,1 Tx slot)	27.00	26.50	26.29	26.16	17.97	17.47	17.26	17.13
EGPRS(8PSK,2 Tx slot)	25.50	25.47	25.48	25.33	19.48	19.45	19.46	19.31
EGPRS(8PSK,3 Tx slot)	23.50	23.14	23.05	23.20	19.24	18.88	18.79	18.94
EGPRS(8PSK,4 Tx slot)	22.00	21.95	21.87	21.42	18.99	18.94	18.86	18.41

7.2. WCDMA Conducted Power

WCDMA Band 2	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up	9262	9400	9538
Frequency (MHz)	(dBm)	1852.4	1880	1907.6
RMC12.2K	23.50	23.26	23.32	23.35
HSDPA Sub 1	22.50	22.35	22.40	22.39
HSDPA Sub 2	22.00	21.96	21.99	21.99

HSDPA Sub 3	21.00	20.54	20.58	20.61
HSDPA Sub 4	21.00	20.58	20.87	20.97
HSUPA Sub 1	22.50	21.20	22.19	22.13
HSUPA Sub 2	22.50	22.23	22.31	22.30
HSUPA Sub 3	21.00	20.65	20.90	20.86
HSUPA Sub 4	22.50	22.30	22.35	22.35
HSUPA Sub 5	22.00	20.80	21.70	21.52
WCDMA Band 4	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	1312	1413	1513
Frequency (MHz)		1712.4	1732.6	1752.6
RMC12.2K	23.50	23.13	23.22	23.22
HSDPA Sub 1	22.50	22.16	22.27	22.28
HSDPA Sub 2	22.00	21.75	21.72	21.90
HSDPA Sub 3	21.50	21.01	20.34	20.61
HSDPA Sub 4	21.00	20.92	20.93	20.75
HSUPA Sub 1	22.50	21.02	21.97	22.04
HSUPA Sub 2	22.50	22.03	22.13	22.12
HSUPA Sub 3	21.00	19.98	20.80	20.73
HSUPA Sub 4	22.50	22.20	22.29	22.28
HSUPA Sub 5	22.00	20.73	21.52	21.65
WCDMA Band 5	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC12.2K	23.50	23.26	23.32	23.35
HSDPA Sub 1	22.50	22.35	22.40	22.39
HSDPA Sub 2	22.00	21.96	21.99	21.99
HSDPA Sub 3	21.00	20.54	20.58	20.61
HSDPA Sub 4	21.00	20.58	20.87	20.97
HSUPA Sub 1	22.50	21.20	22.19	22.13
HSUPA Sub 2	22.50	22.23	22.31	22.30
HSUPA Sub 3	21.00	20.65	20.90	20.86
HSUPA Sub 4	22.50	22.30	22.35	22.35
HSUPA Sub 5	22.00	20.80	21.70	21.52

7.3. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	23.50	23.38	23.22	23.45
			1	2	23.50	23.41	23.21	23.44
			1	5	23.50	23.39	23.21	23.44
			3	0	24.00	23.40	23.30	23.52
			3	1	24.00	23.38	23.25	23.51
			3	2	24.00	23.40	23.23	23.50
			6	0	22.50	22.38	22.26	22.48
		16QAM	1	0	23.00	22.65	22.49	22.80
			1	2	23.00	22.63	22.44	22.72
			1	5	23.00	22.62	22.46	22.78
			3	0	23.00	22.37	22.28	22.42
			3	1	23.00	22.42	22.28	22.49
			3	2	23.00	22.33	22.22	22.51
			6	0	22.00	21.45	21.34	21.52
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band 2	3MHz	QPSK	1	0	23.50	23.35	23.21	23.37
			1	7	23.50	23.35	23.21	23.42
			1	14	23.50	23.28	23.20	23.46
			8	0	23.00	22.33	22.28	22.47
			8	4	23.00	22.31	22.19	22.50
			8	7	23.00	22.29	22.21	22.49
			15	0	22.50	22.34	22.22	22.49
		16QAM	1	0	23.00	22.65	22.42	22.66
			1	7	23.00	22.63	22.44	22.73
			1	14	23.00	22.51	22.53	22.74
			8	0	22.00	21.43	21.32	21.52
			8	4	22.00	21.39	21.31	21.56
			8	7	22.00	21.36	21.29	21.53
			15	0	22.00	21.33	21.26	21.51
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE	5MHz	QPSK	1	0	24.00	23.39	23.29	23.38

Band 2			1	12	24.00	23.33	23.24	23.47
			1	24	24.00	23.34	23.27	23.52
			12	0	23.00	22.37	22.33	22.51
			12	6	23.00	22.35	22.27	22.48
			12	11	23.00	22.31	22.27	22.45
			25	0	22.50	22.35	22.31	22.49
		16QAM	1	0	23.00	22.61	22.51	22.71
			1	12	23.00	22.53	22.46	22.75
			1	24	23.00	22.61	22.47	22.78
			12	0	22.00	21.34	21.33	21.52
			12	6	22.00	21.33	21.25	21.47
			12	11	22.00	21.31	21.23	21.42
			25	0	21.50	21.33	21.30	21.49
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	23.50	23.37	23.23	23.32
			1	24	23.50	23.31	23.28	23.44
			1	49	23.50	23.30	23.25	23.49
			25	0	22.50	22.35	22.29	22.46
			25	12	22.50	22.30	22.28	22.45
			25	24	22.50	22.28	22.29	22.41
			50	0	22.50	22.33	22.31	22.45
		16QAM	1	0	23.00	22.59	22.56	22.55
			1	24	23.00	22.55	22.42	22.69
			1	49	23.00	22.51	22.50	22.69
			25	0	21.50	21.33	21.34	21.43
			25	12	21.50	21.31	21.32	21.45
			25	24	21.50	21.32	21.24	21.43
			50	0	21.50	21.31	21.24	21.44
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band 2	15MHz	QPSK	1	0	23.50	23.34	23.16	23.24
			1	37	23.50	23.34	23.26	23.34
			1	74	23.50	23.18	23.16	23.44
			36	0	22.50	22.27	22.29	22.35
			36	18	22.50	22.34	22.29	22.43
			36	37	22.50	22.20	22.27	22.40
			75	0	22.50	22.32	22.29	22.42

		16QAM	1	0	23.00	22.62	22.31	22.54
		16QAM	1	37	23.00	22.63	22.56	22.64
		16QAM	1	74	23.00	22.47	22.44	22.64
		16QAM	36	0	21.50	21.31	21.25	21.39
		16QAM	36	18	21.50	21.33	21.31	21.37
		16QAM	36	37	21.50	21.25	21.14	21.41
		16QAM	75	0	21.50	21.29	21.25	21.35
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	23.50	23.30	23.11	23.22
			1	49	23.50	23.32	23.27	23.35
			1	99	23.50	23.12	23.12	23.42
			50	0	22.50	22.33	22.32	22.39
			50	24	22.50	22.36	22.33	22.40
			50	49	22.50	22.31	22.22	22.39
			100	0	22.50	22.32	22.21	22.32
		16QAM	1	0	23.00	22.57	22.36	22.49
			1	49	23.00	22.55	22.55	22.54
			1	99	23.00	22.32	22.47	22.60
			50	0	21.50	21.30	21.28	21.31
			50	24	21.50	21.35	21.30	21.42
			50	49	21.50	21.24	21.19	21.33
			100	0	21.50	21.30	21.22	21.34

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	23.50	23.13	23.34	23.27
			1	2	23.50	23.14	23.35	23.30
			1	5	23.50	23.16	23.33	23.28
			3	0	23.50	23.17	23.37	23.35
			3	1	23.50	23.20	23.36	23.33
			3	2	23.50	23.21	23.35	23.32
			6	0	22.50	22.21	22.33	22.30
		16QAM	1	0	23.00	22.28	22.56	22.57
			1	2	23.00	22.41	22.63	22.52
			1	5	23.00	22.42	22.64	22.54
			3	0	22.50	22.22	22.36	22.33

			3	1	22.50	22.20	22.38	22.35
			3	2	22.50	22.22	22.37	22.37
			6	0	21.50	21.22	21.41	21.38
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band 4	3MHz	QPSK	1	0	23.50	23.13	23.34	23.33
			1	7	23.50	23.14	23.32	23.31
			1	14	23.50	23.14	23.35	23.26
			8	0	22.50	22.12	22.32	22.31
			8	4	22.50	22.19	22.31	22.33
			8	7	22.50	22.18	22.33	22.29
			15	0	22.50	22.19	22.33	22.31
		16QAM	1	0	23.00	22.31	22.60	22.52
			1	7	23.00	22.27	22.63	22.61
			1	14	23.00	22.42	22.57	22.47
			8	0	21.50	21.25	21.38	21.37
			8	4	21.50	21.25	21.40	21.36
			8	7	21.50	21.31	21.41	21.36
			15	0	21.50	21.22	21.36	21.33
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5
LTE Band 4	5MHz	QPSK	1	0	23.50	23.17	23.37	23.36
			1	12	23.50	23.19	23.37	23.33
			1	24	23.50	23.24	23.40	23.33
			12	0	22.50	22.22	22.42	22.36
			12	6	22.50	22.23	22.37	22.37
			12	11	22.50	22.23	22.40	22.33
			25	0	22.50	22.23	22.41	22.35
		16QAM	1	0	23.00	22.46	22.59	22.67
			1	12	23.00	22.34	22.64	22.51
			1	24	23.00	22.51	22.63	22.61
			12	0	21.50	21.22	21.36	21.33
			12	6	21.50	21.20	21.35	21.34
			12	11	21.50	21.18	21.32	21.35
			25	0	21.50	21.28	21.38	21.38
Band	Band	Modulation	RB		Tune-up	Channel/Frequency(MHz)		

	Width		Configuration		(dBm)			
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band 4	10MHz	QPSK	1	0	23.50	23.16	23.37	23.36
			1	24	23.50	23.23	23.41	23.38
			1	49	23.50	23.37	23.41	23.32
			25	0	22.50	22.22	22.38	22.38
			25	12	22.50	22.27	22.38	22.35
			25	24	22.50	22.36	22.34	22.39
			50	0	22.50	22.34	22.44	22.40
		16QAM	1	0	23.00	22.37	22.58	22.57
			1	24	23.00	22.50	22.63	22.68
			1	49	23.00	22.60	22.56	22.64
			25	0	21.50	21.29	21.40	21.39
			25	12	21.50	21.30	21.42	21.38
			25	24	21.50	21.42	21.38	21.41
			50	0	21.50	21.29	21.39	21.34
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	23.50	23.11	23.24	23.31
			1	37	23.50	23.28	23.36	23.38
			1	74	23.50	23.31	23.32	23.26
			36	0	22.50	22.18	22.31	22.33
			36	18	22.50	22.32	22.40	22.43
			36	37	22.50	22.36	22.35	22.33
			75	0	22.50	22.34	22.38	22.33
		16QAM	1	0	23.00	22.33	22.50	22.61
			1	37	23.00	22.57	22.55	22.57
			1	74	23.00	22.62	22.66	22.58
			36	0	21.50	21.18	21.36	21.33
			36	18	21.50	21.31	21.33	21.40
			36	37	21.50	21.40	21.39	21.31
			75	0	21.50	21.25	21.32	21.33
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE	20MHz	QPSK	1	0	23.50	23.04	23.23	23.22

Band 4			1	49	23.50	23.36	23.41	23.39
			1	99	23.50	23.34	23.37	23.26
			50	0	22.50	22.27	22.37	22.42
			50	24	22.50	22.38	22.44	22.40
			50	49	22.50	22.43	22.42	22.32
			100	0	22.50	22.33	22.37	22.36
		16QAM	1	0	23.00	22.32	22.52	22.41
			1	49	23.00	22.63	22.69	22.66
			1	99	23.00	22.63	22.52	22.53
			50	0	21.50	21.25	21.37	21.32
			50	24	21.50	21.35	21.45	21.40
			50	49	21.50	21.39	21.39	21.33
			100	0	21.50	21.31	21.36	21.34

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	25.00	24.45	24.64	24.37
			1	2	25.00	24.51	24.66	24.35
			1	5	25.00	24.51	24.64	24.34
			3	0	25.00	24.47	24.72	24.43
			3	1	25.00	24.51	24.69	24.43
			3	2	25.00	24.51	24.65	24.43
			6	0	24.00	23.50	23.70	23.44
		16QAM	1	0	24.00	23.61	23.92	23.58
			1	2	24.00	23.67	23.94	23.58
			1	5	24.00	23.68	23.89	23.55
			3	0	24.00	23.47	23.75	23.48
			3	1	24.00	23.48	23.67	23.51
			3	2	24.00	23.52	23.62	23.48
			6	0	23.00	22.56	22.76	22.52
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	25.00	24.43	24.69	24.43
			1	7	25.00	24.50	24.68	24.42
			1	14	25.00	24.55	24.59	24.36
			8	0	24.00	23.47	23.65	23.44
			8	4	24.00	23.50	23.66	23.44
			8	7	24.00	23.47	23.62	23.40

			15	0	24.00	23.46	23.64	23.49
		16QAM	1	0	24.00	23.71	23.88	23.68
			1	7	24.00	23.78	23.86	23.58
			1	14	24.00	23.86	23.87	23.64
			8	0	23.00	22.55	22.76	22.54
			8	4	23.00	22.57	22.73	22.52
			8	7	23.00	22.59	22.73	22.47
			15	0	23.00	22.49	22.68	22.50
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	25.00	24.48	24.71	24.56
			1	12	25.00	24.53	24.73	24.45
			1	24	25.00	24.65	24.64	24.41
			12	0	24.00	23.54	23.76	23.58
			12	6	24.00	23.57	23.71	23.50
			12	11	24.00	23.58	23.68	23.45
			25	0	24.00	23.55	23.73	23.50
		16QAM	1	0	24.00	23.73	23.90	23.82
			1	12	24.00	23.71	23.93	23.73
			1	24	24.00	23.88	23.77	23.63
			12	0	23.00	22.53	22.73	22.61
			12	6	23.00	22.52	22.71	22.50
			12	11	23.00	22.52	22.67	22.43
			25	0	23.00	22.62	22.74	22.52
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE Band 5	10MHz	QPSK	1	0	25.00	24.45	24.67	24.65
			1	24	25.00	24.64	24.73	24.57
			1	49	25.00	24.67	24.60	24.36
			25	0	24.00	23.59	23.71	23.66
			25	12	24.00	23.59	23.69	23.55
			25	24	24.00	23.65	23.67	23.49
			50	0	24.00	23.67	23.76	23.58
		16QAM	1	0	24.00	23.74	23.95	23.92
			1	24	24.00	23.93	23.89	23.81
			1	49	24.00	23.83	23.85	23.60
			25	0	23.00	22.65	22.75	22.67
			25	12	23.00	22.62	22.72	22.59

			25	24	23.00	22.65	22.67	22.51
			50	0	23.00	22.59	22.67	22.60

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5
LTE Band 7	5MHz	QPSK	1	0	24.00	23.31	23.49	23.71
			1	12	24.00	23.40	23.57	23.68
			1	24	24.00	23.42	23.58	23.66
			12	0	23.00	22.36	22.65	22.82
			12	6	23.00	22.35	22.59	22.78
			12	11	23.00	22.40	22.59	22.78
			25	0	23.00	22.30	22.60	22.74
		16QAM	1	0	23.00	22.33	22.61	22.88
			1	12	23.00	22.39	22.71	22.83
			1	24	23.00	22.47	22.81	22.85
			12	0	22.00	21.35	21.62	21.80
			12	6	22.00	21.32	21.56	21.76
			12	11	22.00	21.36	21.57	21.74
			25	0	22.00	21.35	21.62	21.79

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	24.00	23.24	23.38	23.65
			1	24	24.00	23.31	23.58	23.71
			1	49	24.00	23.35	23.60	23.65
			25	0	23.00	22.32	22.60	22.74
			25	12	23.00	22.41	22.55	22.77
			25	24	23.00	22.44	22.61	22.75
			50	0	23.00	22.40	22.65	22.76
		16QAM	1	0	23.00	22.31	22.66	22.86
			1	24	23.00	22.47	22.80	22.88
			1	49	23.00	22.55	22.80	22.82
			25	0	22.00	21.40	21.66	21.79
			25	12	22.00	21.46	21.62	21.80
			25	24	22.00	21.49	21.68	21.76
			50	0	22.00	21.40	21.64	21.75

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5

LTE Band 7	15MHz	QPSK	1	0	24.00	23.18	23.30	23.53
			1	37	24.00	23.35	23.54	23.67
			1	74	24.00	23.26	23.54	23.61
			36	0	23.00	22.31	22.54	22.66
			36	18	23.00	22.39	22.63	22.70
			36	37	23.00	22.37	22.63	22.70
			75	0	23.00	22.42	22.57	22.67
		16QAM	1	0	23.00	22.38	22.54	22.69
			1	37	23.00	22.51	22.72	22.82
			1	74	23.00	22.41	22.70	22.73
			36	0	22.00	21.34	21.59	21.67
			36	18	22.00	21.44	21.59	21.73
			36	37	22.00	21.42	21.57	21.74
			75	0	22.00	21.38	21.56	21.65
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band 7	20MHz	QPSK	1	0	24.00	23.14	23.28	23.48
			1	49	24.00	23.35	23.59	23.67
			1	99	24.00	23.16	23.49	23.58
			50	0	23.00	22.42	22.66	22.64
			50	24	23.00	22.44	22.65	22.74
			50	49	23.00	22.35	22.57	22.72
			100	0	23.00	22.35	22.56	22.60
		16QAM	1	0	23.00	22.29	22.46	22.64
			1	49	23.00	22.44	22.75	22.78
			1	99	23.00	22.28	22.75	22.70
			50	0	22.00	21.35	21.66	21.59
			50	24	22.00	21.43	21.63	21.75
			50	49	22.00	21.34	21.59	21.69
			100	0	22.00	21.33	21.55	21.61

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23017/699.7	23095/707.5	23173/715.3
LTE Band 12	1.4MHz	QPSK	1	0	25.00	24.49	24.34	24.40
			1	2	25.00	24.52	24.29	24.52
			1	5	25.00	24.54	24.30	24.42
			3	0	25.00	24.57	24.36	24.53
			3	1	25.00	24.56	24.36	24.54

			3	2	25.00	24.57	24.39	24.47
			6	0	24.00	23.54	23.35	23.54
		16QAM	1	0	24.00	23.74	23.60	23.63
			1	2	24.00	23.65	23.57	23.64
			1	5	24.00	23.64	23.46	23.63
			3	0	24.00	23.60	23.39	23.50
			3	1	24.00	23.55	23.44	23.68
			3	2	24.00	23.51	23.46	23.65
			6	0	23.00	22.56	22.48	22.65
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23025/700.5	23095/707.5	23165/714.5
LTE Band 12	3MHz	QPSK	1	0	25.00	24.50	24.32	24.40
			1	7	25.00	24.44	24.28	24.44
			1	14	25.00	24.41	24.29	24.42
			8	0	24.00	23.51	23.31	23.49
			8	4	24.00	23.47	23.35	23.49
			8	7	24.00	23.46	23.32	23.53
			15	0	24.00	23.50	23.33	23.51
		16QAM	1	0	24.00	23.73	23.58	23.67
			1	7	24.00	23.64	23.56	23.63
			1	14	24.00	23.59	23.44	23.73
			8	0	23.00	22.59	22.42	22.56
			8	4	23.00	22.56	22.45	22.59
			8	7	23.00	22.51	22.37	22.58
			15	0	23.00	22.54	22.39	22.55
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23035/701.5	23095/707.5	23155/713.5
LTE Band 12	5MHz	QPSK	1	0	25.00	24.54	24.36	24.41
			1	12	25.00	24.45	24.34	24.41
			1	24	25.00	24.40	24.38	24.30
			12	0	24.00	23.52	23.41	23.52
			12	6	24.00	23.50	23.39	23.51
			12	11	24.00	23.46	23.38	23.48
			25	0	24.00	23.48	23.37	23.50
		16QAM	1	0	24.00	23.78	23.53	23.63
			1	12	24.00	23.58	23.53	23.53
			1	24	24.00	23.51	23.61	23.69
			12	0	23.00	22.52	22.39	22.47

			12	6	23.00	22.49	22.37	22.48
			12	11	23.00	22.43	22.40	22.46
			25	0	23.00	22.53	22.39	22.54
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23060/704	23095/707.5	23130/711
LTE Band 12	10MHz	QPSK	1	0	25.00	24.57	24.42	24.32
			1	24	25.00	24.39	24.40	24.42
			1	49	25.00	24.30	24.40	24.49
			25	0	23.50	23.42	23.37	23.41
			25	12	23.50	23.41	23.40	23.39
			25	24	23.50	23.41	23.34	23.45
			50	0	23.50	23.44	23.40	23.45
		16QAM	1	0	24.00	23.77	23.55	23.59
			1	24	24.00	23.61	23.53	23.58
			1	49	24.00	23.47	23.63	23.71
			25	0	22.50	22.49	22.47	22.48
			25	12	22.50	22.46	22.42	22.45
			25	24	22.50	22.47	22.40	22.46
			50	0	22.50	22.41	22.41	22.45

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23755/706.5	23790/710	23825/713.5
LTE Band 17	5MHz	QPSK	1	0	24.50	24.29	24.21	24.27
			1	12	24.50	24.26	24.23	24.31
			1	24	24.50	24.32	24.25	24.30
			12	0	23.50	23.29	23.30	23.34
			12	6	23.50	23.30	23.28	23.32
			12	11	23.50	23.25	23.22	23.31
			25	0	23.50	23.23	23.26	23.38
		16QAM	1	0	24.00	23.43	23.44	23.39
			1	12	24.00	23.40	23.48	23.54
			1	24	24.00	23.45	23.47	23.45
			12	0	22.50	22.27	22.30	22.36
			12	6	22.50	22.25	22.25	22.35
			12	11	22.50	22.26	22.23	22.32
			25	0	22.50	22.25	22.32	22.38
Band	Band	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		

	Width		RB Size	RB Offset	(dBm)	23780/709	23790/710	23800/711
LTE Band 17	10MHz	QPSK	1	0	24.50	24.22	24.23	24.25
			1	24	24.50	24.29	24.28	24.27
			1	49	24.50	24.26	24.29	24.29
			25	0	23.50	23.23	23.30	23.32
			25	12	23.50	23.26	23.27	23.29
			25	24	23.50	23.26	23.22	23.26
			50	0	23.50	23.30	23.31	23.34
		16QAM	1	0	24.00	23.45	23.35	23.50
			1	24	24.00	23.52	23.46	23.46
			1	49	24.00	23.44	23.49	23.54
			25	0	22.50	22.30	22.30	22.36
			25	12	22.50	22.32	22.29	22.33
			25	24	22.50	22.26	22.29	22.24
			50	0	22.50	22.26	22.34	22.30

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26047/1850.7	26365/1882.5	26683/1914.3
LTE Band 25	1.4MHz	QPSK	1	0	24.00	23.30	23.21	23.52
			1	2	24.00	23.32	23.24	23.51
			1	5	24.00	23.33	23.24	23.52
			3	0	24.00	23.35	23.30	23.55
			3	1	24.00	23.35	23.27	23.55
			3	2	24.00	23.36	23.25	23.55
			6	0	23.00	22.35	22.29	22.52
		16QAM	1	0	23.00	22.49	22.53	22.72
			1	2	23.00	22.47	22.49	22.84
			1	5	23.00	22.46	22.48	22.73
			3	0	23.00	22.38	22.31	22.57
			3	1	23.00	22.34	22.18	22.60
			3	2	23.00	22.36	22.29	22.60
			6	0	22.00	21.37	21.32	21.65
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26055/1851.5	26365/1882.5	26675/1913.5
LTE	3MHz	QPSK	1	0	24.00	23.31	23.25	23.45

Band 25			1	7	24.00	23.27	23.24	23.52
			1	14	24.00	23.31	23.20	23.52
			8	0	23.00	22.32	22.24	22.57
			8	4	23.00	22.29	22.20	22.55
			8	7	23.00	22.29	22.24	22.56
			15	0	23.00	22.31	22.22	22.55
		16QAM	1	0	23.00	22.48	22.46	22.66
			1	7	23.00	22.46	22.49	22.81
			1	14	23.00	22.52	22.38	22.80
			8	0	22.00	21.37	21.35	21.61
			8	4	22.00	21.38	21.27	21.61
			8	7	22.00	21.33	21.25	21.60
			15	0	22.00	21.33	21.25	21.60
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26065/1852.5	26365/1882.5	26665/1912.5
LTE Band 25	5MHz	QPSK	1	0	24.00	23.34	23.27	23.52
			1	12	24.00	23.36	23.26	23.55
			1	24	24.00	23.33	23.26	23.55
			12	0	23.00	22.35	22.35	22.64
			12	6	23.00	22.35	22.27	22.62
			12	11	23.00	22.34	22.23	22.56
			25	0	23.00	22.30	22.29	22.60
		16QAM	1	0	23.00	22.50	22.51	22.78
			1	12	23.00	22.60	22.46	22.73
			1	24	23.00	22.59	22.47	22.72
			12	0	22.00	21.35	21.31	21.61
			12	6	22.00	21.27	21.22	21.59
			12	11	22.00	21.31	21.16	21.59
			25	0	22.00	21.33	21.30	21.61
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26090/1855	26365/1882.5	26640/1910
LTE Band 25	10MHz	QPSK	1	0	24.00	23.32	23.27	23.42
			1	24	24.00	23.33	23.30	23.53
			1	49	24.00	23.34	23.24	23.55
			25	0	23.00	22.36	22.33	22.61
			25	12	23.00	22.33	22.33	22.52

			25	24	23.00	22.35	22.30	22.53
			50	0	23.00	22.37	22.32	22.62
		16QAM	1	0	23.00	22.58	22.48	22.65
			1	24	23.00	22.54	22.45	22.88
			1	49	23.00	22.55	22.52	22.74
			25	0	22.00	21.30	21.38	21.63
			25	12	22.00	21.33	21.33	21.53
			25	24	22.00	21.28	21.31	21.52
			50	0	22.00	21.33	21.35	21.59
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26115/1857.5	26365/1882.5	26615/1907.5
LTE Band 25	15MHz	QPSK	1	0	23.50	23.24	23.21	23.27
			1	37	23.50	23.34	23.27	23.43
			1	74	23.50	23.20	23.18	23.47
			36	0	23.00	22.33	22.33	22.37
			36	18	23.00	22.25	22.27	22.51
			36	37	23.00	22.30	22.19	22.43
			75	0	22.50	22.32	22.24	22.46
		16QAM	1	0	23.00	22.49	22.43	22.54
			1	37	23.00	22.59	22.57	22.66
			1	74	23.00	22.45	22.35	22.73
			36	0	21.50	21.26	21.28	21.41
			36	18	21.50	21.28	21.27	21.47
			36	37	21.50	21.24	21.19	21.48
			75	0	21.50	21.30	21.23	21.44
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26140/1860	26365/1882.5	26590/1905
LTE Band 25	20MHz	QPSK	1	0	23.50	23.20	23.11	23.24
			1	49	23.50	23.32	23.31	23.47
			1	99	23.50	23.12	23.11	23.45
			50	0	22.50	22.38	22.37	22.47
			50	24	22.50	22.40	22.39	22.47
			50	49	22.50	22.34	22.25	22.40
			100	0	22.50	22.27	22.32	22.46
		16QAM	1	0	23.00	22.48	22.28	22.46
			1	49	23.00	22.52	22.58	22.63

			1	99	23.00	22.40	22.36	22.73
			50	0	21.50	21.32	21.36	21.44
			50	24	21.50	21.36	21.27	21.41
			50	49	21.50	21.25	21.26	21.40
			100	0	21.50	21.28	21.23	21.38

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26697/814.7	26740/819	26783/823.3
LTE Band 26a	1.4MHz	QPSK	1	0	24.50	24.35	24.41	24.38
			1	2	24.50	24.36	24.40	24.38
			1	5	24.50	24.32	24.36	24.42
			3	0	24.50	24.42	24.44	24.45
			3	1	24.50	24.37	24.46	24.46
			3	2	24.50	24.37	24.46	24.47
		16QAM	6	0	23.50	23.39	23.43	23.45
			1	0	24.00	23.54	23.66	23.55
			1	2	24.00	23.46	23.60	23.65
			1	5	24.00	23.42	23.63	23.72
			3	0	24.00	23.44	23.50	23.50
			3	1	24.00	23.40	23.44	23.49
			3	2	24.00	23.32	23.44	23.54
			6	0	23.00	22.41	22.53	22.49
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26705/818.5	26740/819	26775/822.5
LTE Band 26a	3MHz	QPSK	1	0	24.50	24.30	24.40	24.38
			1	7	24.50	24.29	24.39	24.42
			1	14	24.50	24.24	24.38	24.45
			8	0	23.50	23.30	23.41	23.39
			8	4	23.50	23.28	23.43	23.43
			8	7	23.50	23.30	23.41	23.45
			15	0	23.50	23.31	23.46	23.44
		16QAM	1	0	24.00	23.49	23.63	23.58
			1	7	24.00	23.53	23.57	23.58
			1	14	24.00	23.47	23.57	23.66
			8	0	23.00	22.40	22.53	22.49
			8	4	23.00	22.37	22.52	22.52
			8	7	23.00	22.36	22.53	22.51
			15	0	23.00	22.32	22.49	22.50

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26715/816.5	26740/819	26765/821.5
LTE Band 26a	5MHz	QPSK	1	0	24.50	24.36	24.46	24.45
			1	12	24.50	24.32	24.43	24.42
			1	24	24.50	24.33	24.41	24.46
			12	0	24.00	23.42	23.50	23.43
			12	6	24.00	23.38	23.50	23.50
			12	11	24.00	23.35	23.50	23.52
			25	0	23.50	23.38	23.46	23.46
		16QAM	1	0	24.00	23.55	23.71	23.62
			1	12	24.00	23.53	23.57	23.51
			1	24	24.00	23.53	23.57	23.64
			12	0	23.00	22.37	22.48	22.41
			12	6	23.00	22.38	22.50	22.45
			12	11	23.00	22.36	22.50	22.55
			25	0	23.00	22.37	22.52	22.51
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		/	26740/819	/
LTE Band 26a	10MHz	QPSK	1	0	24.50		24.43	
			1	24	24.50		24.46	
			1	49	24.50		24.46	
			25	0	24.00		23.53	
			25	12	24.00		23.46	
			25	24	24.00		23.61	
			50	0	24.00		23.56	
		16QAM	1	0	24.00		23.60	
			1	24	24.00		23.59	
			1	49	24.00		23.64	
			25	0	23.00		22.55	
			25	12	23.00		22.52	
			25	24	23.00		22.62	
			50	0	23.00		22.60	

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26797/824.7	26915/836.5	27033/848.3
LTE Band	1.4MHz	QPSK	1	0	25.00	24.51	24.70	24.43
			1	2	25.00	24.54	24.74	24.40

26b			1	5	25.00	24.50	24.69	24.39
			3	0	25.00	24.54	24.80	24.47
			3	1	25.00	24.53	24.77	24.49
			3	2	25.00	24.55	24.73	24.48
			6	0	24.00	23.53	23.76	23.50
		16QAM	1	0	24.00	23.68	23.96	23.60
			1	2	24.00	23.72	23.90	23.66
			1	5	24.00	23.75	23.85	23.60
			3	0	24.00	23.57	23.75	23.53
			3	1	24.00	23.58	23.82	23.50
			3	2	24.00	23.58	23.79	23.56
			6	0	23.00	22.59	22.85	22.54
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26805/825.5	26915/836.5	27025/847.5
LTE Band 26b	3MHz	QPSK	1	0	25.00	24.47	24.74	24.45
			1	7	25.00	24.50	24.74	24.47
			1	14	25.00	24.54	24.64	24.39
			8	0	24.00	23.50	23.73	23.51
			8	4	24.00	23.51	23.71	23.48
			8	7	24.00	23.54	23.67	23.43
			15	0	24.00	23.53	23.77	23.54
		16QAM	1	0	24.50	23.75	23.95	23.64
			1	7	24.50	23.75	24.03	23.69
			1	14	24.50	23.82	23.88	23.62
			8	0	23.00	22.58	22.87	22.60
			8	4	23.00	22.59	22.79	22.54
			8	7	23.00	22.61	22.78	22.52
			15	0	23.00	22.55	22.77	22.56
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26815/826.5	26915/836.5	27015/846.5
LTE Band 26b	5MHz	QPSK	1	0	25.00	24.52	24.77	24.57
			1	12	25.00	24.56	24.77	24.46
			1	24	25.00	24.67	24.68	24.44
			12	0	24.00	23.58	23.82	23.62
			12	6	24.00	23.60	23.77	23.56
			12	11	24.00	23.58	23.73	23.49
			25	0	24.00	23.62	23.74	23.58
		16QAM	1	0	24.00	23.78	23.97	23.73

			1	12	24.00	23.77	23.97	23.65
			1	24	24.00	23.86	23.82	23.64
			12	0	23.00	22.55	22.80	22.58
			12	6	23.00	22.59	22.76	22.57
			12	11	23.00	22.60	22.73	22.50
			25	0	23.00	22.65	22.78	22.59
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26840/829	26915/836.5	26990/844
LTE Band 26b	10MHz	QPSK	1	0	25.00	24.50	24.75	24.65
			1	24	25.00	24.69	24.79	24.61
			1	49	25.00	24.74	24.65	24.41
			25	0	24.00	23.62	23.77	23.67
			25	12	24.00	23.66	23.75	23.59
			25	24	24.00	23.69	23.73	23.53
			50	0	24.00	23.71	23.78	23.65
		16QAM	1	0	24.50	23.66	23.96	23.95
			1	24	24.50	23.93	24.04	23.87
			1	49	24.50	23.93	23.95	23.63
			25	0	23.00	22.64	22.83	22.72
			25	12	23.00	22.72	22.71	22.60
			25	24	23.00	22.73	22.76	22.54
			50	0	23.00	22.66	22.75	22.63
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26865/831.5	26915/836.5	26965/841.5
LTE Band 26b	15MHz	QPSK	1	0	25.00	24.45	24.63	24.73
			1	37	25.00	24.71	24.75	24.60
			1	74	25.00	24.61	24.52	24.34
			36	0	24.00	23.61	23.74	23.65
			36	18	24.00	23.67	23.70	23.56
			36	37	24.00	23.69	23.66	23.48
			75	0	24.00	23.68	23.73	23.64
		16QAM	1	0	24.00	23.72	23.96	23.89
			1	37	24.00	23.92	23.94	23.89
			1	74	24.00	23.85	23.79	23.56
			36	0	23.00	22.61	22.73	22.68
			36	18	23.00	22.67	22.74	22.58
			36	37	23.00	22.71	22.60	22.44
			75	0	23.00	22.66	22.67	22.62

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		131979/1710.7	132322/1745	132665/1779.3
LTE Band 66	1.4MHz	QPSK	1	0	23.50	23.08	23.33	23.24
			1	2	23.50	23.13	23.33	23.27
			1	5	23.50	23.15	23.33	23.27
			3	0	23.50	23.19	23.37	23.33
			3	1	23.50	23.17	23.37	23.34
			3	2	23.50	23.20	23.36	23.33
			6	0	22.50	22.19	22.35	22.34
		16QAM	1	0	23.00	22.38	22.62	22.53
			1	2	23.00	22.36	22.60	22.51
			1	5	23.00	22.39	22.61	22.52
			3	0	22.50	22.16	22.40	22.42
			3	1	22.50	22.24	22.37	22.34
			3	2	22.50	22.20	22.30	22.33
			6	0	21.50	21.23	21.42	21.37
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		131987/1711.5	132322/1745	132657/1778.5
LTE Band 66	3MHz	QPSK	1	0	23.50	23.09	23.32	23.30
			1	7	23.50	23.16	23.37	23.29
			1	14	23.50	23.19	23.33	23.26
			8	0	22.50	22.17	22.34	22.34
			8	4	22.50	22.15	22.32	22.29
			8	7	22.50	22.23	22.33	22.32
			15	0	22.50	22.20	22.31	22.36
		16QAM	1	0	23.00	22.26	22.59	22.54
			1	7	23.00	22.40	22.57	22.49
			1	14	23.00	22.43	22.67	22.56
			8	0	21.50	21.22	21.41	21.40
			8	4	21.50	21.24	21.37	21.37
			8	7	21.50	21.25	21.39	21.37
			15	0	21.50	21.25	21.33	21.37
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB	RB		131997/1712.5	132322/1745	132647/1777.5

			Size	Offset				
LTE Band 66	5MHz	QPSK	1	0	23.50	23.17	23.39	23.33
			1	12	23.50	23.22	23.39	23.31
			1	24	23.50	23.30	23.36	23.33
			12	0	22.50	22.22	22.41	22.41
			12	6	22.50	22.30	22.36	22.37
			12	11	22.50	22.27	22.34	22.30
			25	0	22.50	22.26	22.33	22.38
		16QAM	1	0	23.00	22.44	22.66	22.51
			1	12	23.00	22.41	22.66	22.57
			1	24	23.00	22.49	22.59	22.59
			12	0	21.50	21.21	21.39	21.38
			12	6	21.50	21.22	21.36	21.36
			12	11	21.50	21.25	21.26	21.28
			25	0	21.50	21.26	21.37	21.39
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		132022/1715	132322/1745	132622/1775
LTE Band 66	10MHz	QPSK	1	0	23.50	23.14	23.33	23.38
			1	24	23.50	23.29	23.42	23.39
			1	49	23.50	23.31	23.39	23.33
			25	0	22.50	22.27	22.41	22.41
			25	12	22.50	22.33	22.40	22.38
			25	24	22.50	22.34	22.36	22.36
			50	0	22.50	22.32	22.40	22.41
		16QAM	1	0	23.00	22.32	22.52	22.58
			1	24	23.00	22.49	22.68	22.52
			1	49	23.00	22.47	22.60	22.56
			25	0	21.50	21.29	21.40	21.42
			25	12	21.50	21.36	21.33	21.40
			25	24	21.50	21.34	21.36	21.37
			50	0	21.50	21.31	21.41	21.38
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		132047/1717.5	132322/1745	132597/1772.5
LTE Band 66	15MHz	QPSK	1	0	23.50	23.07	23.28	23.19
			1	37	23.50	23.32	23.37	23.32
			1	74	23.50	23.34	23.31	23.16

			36	0	22.50	22.25	22.33	22.27
			36	18	22.50	22.31	22.38	22.24
			36	37	22.50	22.39	22.38	22.29
			75	0	22.50	22.37	22.34	22.29
		16QAM	1	0	23.00	22.26	22.56	22.48
			1	37	23.00	22.60	22.61	22.54
			1	74	23.00	22.49	22.64	22.43
			36	0	21.50	21.25	21.40	21.31
			36	18	21.50	21.36	21.34	21.29
			36	37	21.50	21.41	21.35	21.27
			75	0	21.50	21.28	21.34	21.25
			RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		132072/1720	132322/1745	132572/1770
LTE Band 66	20MHz	QPSK	1	0	23.50	23.06	23.22	23.17
			1	49	23.50	23.34	23.39	23.28
			1	99	23.50	23.28	23.31	23.16
			50	0	22.50	22.30	22.46	22.35
			50	24	22.50	22.44	22.43	22.33
			50	49	22.50	22.45	22.38	22.25
			100	0	22.50	22.35	22.34	22.29
		16QAM	1	0	23.00	22.26	22.47	22.38
			1	49	23.00	22.54	22.63	22.46
			1	99	23.00	22.51	22.59	22.34
			50	0	21.50	21.23	21.39	21.32
			50	24	21.50	21.38	21.40	21.30
			50	49	21.50	21.46	21.35	21.24
			100	0	21.50	21.34	21.35	21.28

7.4. NR Conducted Power

Band	SCS (kHz)	Bandwidth (MHz)	UL Channel	RB Allocation	Modulation	Tune-up (dBm)	Power (dBm)
n78	30	10	620334	1@1	DFT_BPSK	23.50	23.03
n78	30	10	620334	24@0	DFT_QPSK	22.50	22.05
n78	30	10	620334	12@6	DFT_QPSK	23.50	23.07
n78	30	10	620334	1@1	DFT_QPSK	23.50	23.05
n78	30	10	620334	1@22	DFT_QPSK	23.50	23.01
n78	30	10	620334	1@1	DFT_QAM16	22.50	22.16

n78	30	10	620334	1@1	DFT_QAM64	21.00	20.56
n78	30	10	620334	1@1	DFT_QAM256	19.00	18.52
n78	30	10	620334	1@1	CP_QPSK	22.00	21.61
n78	30	10	636666	1@1	DFT_BPSK	24.00	23.56
n78	30	10	636666	24@0	DFT_QPSK	23.00	22.57
n78	30	10	636666	12@6	DFT_QPSK	24.00	23.58
n78	30	10	636666	1@1	DFT_QPSK	24.00	23.57
n78	30	10	636666	1@22	DFT_QPSK	23.50	23.45
n78	30	10	636666	1@1	DFT_QAM16	23.00	22.6
n78	30	10	636666	1@1	DFT_QAM64	21.50	21.06
n78	30	10	636666	1@1	DFT_QAM256	19.50	19.05
n78	30	10	636666	1@1	CP_QPSK	22.50	22.12
n78	30	10	653000	1@1	DFT_BPSK	24.00	23.91
n78	30	10	653000	24@0	DFT_QPSK	23.00	23
n78	30	10	653000	12@6	DFT_QPSK	24.00	23.99
n78	30	10	653000	1@1	DFT_QPSK	24.00	23.88
n78	30	10	653000	1@22	DFT_QPSK	24.00	23.91
n78	30	10	653000	1@1	DFT_QAM16	24.00	22.97
n78	30	10	653000	1@1	DFT_QAM64	21.50	21.43
n78	30	10	653000	1@1	DFT_QAM256	19.50	19.42
n78	30	10	653000	1@1	CP_QPSK	22.50	22.45
n78	30	15	620500	1@1	DFT_BPSK	23.50	23.09
n78	30	15	620500	36@0	DFT_QPSK	22.50	22.11
n78	30	15	620500	18@9	DFT_QPSK	23.50	23.16
n78	30	15	620500	1@1	DFT_QPSK	23.50	23.07
n78	30	15	620500	1@36	DFT_QPSK	23.50	23.02
n78	30	15	620500	1@1	DFT_QAM16	22.50	22.06
n78	30	15	620500	1@1	DFT_QAM64	21.00	20.54
n78	30	15	620500	1@1	DFT_QAM256	19.00	18.55
n78	30	15	620500	1@1	CP_QPSK	22.00	21.61
n78	30	15	636666	1@1	DFT_BPSK	24.00	23.56
n78	30	15	636666	36@0	DFT_QPSK	23.00	22.55
n78	30	15	636666	18@9	DFT_QPSK	24.00	23.6
n78	30	15	636666	1@1	DFT_QPSK	24.00	23.53
n78	30	15	636666	1@36	DFT_QPSK	23.50	23.39
n78	30	15	636666	1@1	DFT_QAM16	23.00	22.54
n78	30	15	636666	1@1	DFT_QAM64	21.50	21.11
n78	30	15	636666	1@1	DFT_QAM256	19.50	19.05
n78	30	15	636666	1@1	CP_QPSK	22.50	22.13

n78	30	15	652832	1@1	DFT_BPSK	24.00	23.89
n78	30	15	652832	36@0	DFT_QPSK	23.00	22.98
n78	30	15	652832	18@9	DFT_QPSK	24.50	24.01
n78	30	15	652832	1@1	DFT_QPSK	24.00	23.86
n78	30	15	652832	1@36	DFT_QPSK	24.00	23.86
n78	30	15	652832	1@1	DFT_QAM16	23.00	22.85
n78	30	15	652832	1@1	DFT_QAM64	21.50	21.33
n78	30	15	652832	1@1	DFT_QAM256	19.50	19.38
n78	30	15	652832	1@1	CP_QPSK	22.50	22.42
n78	30	20	620668	1@1	DFT_BPSK	23.50	23.08
n78	30	20	620668	50@0	DFT_QPSK	22.50	22.17
n78	30	20	620668	25@12	DFT_QPSK	23.50	23.19
n78	30	20	620668	1@1	DFT_QPSK	23.50	23.05
n78	30	20	620668	1@49	DFT_QPSK	23.00	22.94
n78	30	20	620668	1@1	DFT_QAM16	22.50	22.1
n78	30	20	620668	1@1	DFT_QAM64	21.00	20.53
n78	30	20	620668	1@1	DFT_QAM256	19.00	18.55
n78	30	20	620668	1@1	CP_QPSK	22.00	21.58
n78	30	20	636666	1@1	DFT_BPSK	24.00	23.58
n78	30	20	636666	50@0	DFT_QPSK	23.00	22.55
n78	30	20	636666	25@12	DFT_QPSK	24.00	23.65
n78	30	20	636666	1@1	DFT_QPSK	24.00	23.54
n78	30	20	636666	1@49	DFT_QPSK	23.50	23.31
n78	30	20	636666	1@1	DFT_QAM16	22.50	22.49
n78	30	20	636666	1@1	DFT_QAM64	21.50	21.08
n78	30	20	636666	1@1	DFT_QAM256	19.50	19.05
n78	30	20	636666	1@1	CP_QPSK	22.50	22.12
n78	30	20	652666	1@1	DFT_BPSK	24.00	23.9
n78	30	20	652666	50@0	DFT_QPSK	23.50	23.06
n78	30	20	652666	25@12	DFT_QPSK	24.50	24.11
n78	30	20	652666	1@1	DFT_QPSK	24.00	23.86
n78	30	20	652666	1@49	DFT_QPSK	24.00	23.87
n78	30	20	652666	1@1	DFT_QAM16	23.00	22.83
n78	30	20	652666	1@1	DFT_QAM64	21.50	21.36
n78	30	20	652666	1@1	DFT_QAM256	19.50	19.36
n78	30	20	652666	1@1	CP_QPSK	22.50	22.39
n78	30	40	621334	1@1	DFT_BPSK	23.00	22.79
n78	30	40	621334	100@0	DFT_QPSK	22.00	21.93
n78	30	40	621334	50@25	DFT_QPSK	23.50	23.13

n78	30	40	621334	1@1	DFT_QPSK	23.00	22.73
n78	30	40	621334	1@104	DFT_QPSK	22.50	22.35
n78	30	40	621334	1@1	DFT_QAM16	22.00	21.7
n78	30	40	621334	1@1	DFT_QAM64	20.50	20.28
n78	30	40	621334	1@1	DFT_QAM256	18.50	18.28
n78	30	40	621334	1@1	CP_QPSK	21.50	21.31
n78	30	40	636666	1@1	DFT_BPSK	23.50	23.1
n78	30	40	636666	100@0	DFT_QPSK	22.50	22.39
n78	30	40	636666	50@25	DFT_QPSK	24.00	23.61
n78	30	40	636666	1@1	DFT_QPSK	23.50	23.11
n78	30	40	636666	1@104	DFT_QPSK	23.00	22.78
n78	30	40	636666	1@1	DFT_QAM16	22.50	22.09
n78	30	40	636666	1@1	DFT_QAM64	21.00	20.65
n78	30	40	636666	1@1	DFT_QAM256	19.00	18.64
n78	30	40	636666	1@1	CP_QPSK	22.00	21.7
n78	30	40	652000	1@1	DFT_BPSK	23.50	23.32
n78	30	40	652000	100@0	DFT_QPSK	23.00	22.92
n78	30	40	652000	50@25	DFT_QPSK	24.50	24.06
n78	30	40	652000	1@1	DFT_QPSK	23.50	23.32
n78	30	40	652000	1@104	DFT_QPSK	24.00	23.53
n78	30	40	652000	1@1	DFT_QAM16	22.50	22.3
n78	30	40	652000	1@1	DFT_QAM64	21.00	20.86
n78	30	40	652000	1@1	DFT_QAM256	19.00	18.89
n78	30	40	652000	1@1	CP_QPSK	22.00	21.89
n78	30	50	621668	1@1	DFT_BPSK	23.50	23.09
n78	30	50	621668	128@0	DFT_QPSK	22.00	21.93
n78	30	50	621668	64@32	DFT_QPSK	23.50	23.03
n78	30	50	621668	1@1	DFT_QPSK	23.50	23.03
n78	30	50	621668	1@131	DFT_QPSK	23.00	22.85
n78	30	50	621668	1@1	DFT_QAM16	22.50	22.06
n78	30	50	621668	1@1	DFT_QAM64	21.00	20.57
n78	30	50	621668	1@1	DFT_QAM256	19.00	18.54
n78	30	50	621668	1@1	CP_QPSK	22.00	21.6
n78	30	50	636666	1@1	DFT_BPSK	23.50	23.48
n78	30	50	636666	128@0	DFT_QPSK	22.50	22.46
n78	30	50	636666	64@32	DFT_QPSK	24.00	23.62
n78	30	50	636666	1@1	DFT_QPSK	23.50	23.44
n78	30	50	636666	1@131	DFT_QPSK	23.50	23.05
n78	30	50	636666	1@1	DFT_QAM16	22.50	22.48

n78	30	50	636666	1@1	DFT_QAM64	21.00	20.95
n78	30	50	636666	1@1	DFT_QAM256	19.00	18.94
n78	30	50	636666	1@1	CP_QPSK	22.50	22.01
n78	30	50	651666	1@1	DFT_BPSK	24.00	23.67
n78	30	50	651666	128@0	DFT_QPSK	23.50	23.01
n78	30	50	651666	64@32	DFT_QPSK	24.50	24.08
n78	30	50	651666	1@1	DFT_QPSK	24.00	23.6
n78	30	50	651666	1@131	DFT_QPSK	24.00	23.88
n78	30	50	651666	1@1	DFT_QAM16	23.00	22.62
n78	30	50	651666	1@1	DFT_QAM64	21.50	21.13
n78	30	50	651666	1@1	DFT_QAM256	19.50	19.18
n78	30	50	651666	1@1	CP_QPSK	22.50	22.17
n78	30	60	622000	1@1	DFT_BPSK	23.00	22.92
n78	30	60	622000	162@0	DFT_QPSK	22.00	21.93
n78	30	60	622000	81@40	DFT_QPSK	23.00	22.94
n78	30	60	622000	1@1	DFT_QPSK	23.00	22.86
n78	30	60	622000	1@160	DFT_QPSK	23.00	22.63
n78	30	60	622000	1@1	DFT_QAM16	22.00	21.92
n78	30	60	622000	1@1	DFT_QAM64	20.50	20.37
n78	30	60	622000	1@1	DFT_QAM256	18.50	18.36
n78	30	60	622000	1@1	CP_QPSK	21.50	21.42
n78	30	60	636666	1@1	DFT_BPSK	23.50	23.38
n78	30	60	636666	162@0	DFT_QPSK	22.50	22.43
n78	30	60	636666	81@40	DFT_QPSK	24.00	23.6
n78	30	60	636666	1@1	DFT_QPSK	23.50	23.37
n78	30	60	636666	1@160	DFT_QPSK	23.00	22.92
n78	30	60	636666	1@1	DFT_QAM16	22.50	22.35
n78	30	60	636666	1@1	DFT_QAM64	21.00	20.88
n78	30	60	636666	1@1	DFT_QAM256	19.00	18.89
n78	30	60	636666	1@1	CP_QPSK	22.00	21.9
n78	30	60	651332	1@1	DFT_BPSK	24.00	23.57
n78	30	60	651332	162@0	DFT_QPSK	23.50	23.06
n78	30	60	651332	81@40	DFT_QPSK	24.50	24.13
n78	30	60	651332	1@1	DFT_QPSK	24.00	23.55
n78	30	60	651332	1@160	DFT_QPSK	24.00	23.84
n78	30	60	651332	1@1	DFT_QAM16	23.00	22.58
n78	30	60	651332	1@1	DFT_QAM64	21.50	21.11
n78	30	60	651332	1@1	DFT_QAM256	19.50	19.14
n78	30	60	651332	1@1	CP_QPSK	22.50	22.12

n78	30	70	622334	1@1	DFT_BPSK	20.00	19.91
n78	30	70	622334	216@0	DFT_QPSK	20.00	19.89
n78	30	70	622334	108@54	DFT_QPSK	20.00	19.91
n78	30	70	622334	1@1	DFT_QPSK	20.00	19.89
n78	30	70	622334	1@215	DFT_QPSK	20.00	19.91
n78	30	70	622334	1@1	DFT_QAM16	20.00	19.89
n78	30	70	622334	1@1	DFT_QAM64	20.00	19.89
n78	30	70	622334	1@1	DFT_QAM256	20.00	19.91
n78	30	70	622334	1@1	CP_QPSK	20.00	19.91
n78	30	70	636666	1@1	DFT_BPSK	20.50	20.41
n78	30	70	636666	216@0	DFT_QPSK	20.50	20.39
n78	30	70	636666	108@54	DFT_QPSK	20.50	20.41
n78	30	70	636666	1@1	DFT_QPSK	20.50	20.41
n78	30	70	636666	1@215	DFT_QPSK	20.50	20.41
n78	30	70	636666	1@1	DFT_QAM16	20.50	20.42
n78	30	70	636666	1@1	DFT_QAM64	20.50	20.41
n78	30	70	636666	1@1	DFT_QAM256	20.50	20.41
n78	30	70	636666	1@1	CP_QPSK	20.50	20.42
n78	30	70	651000	1@1	DFT_BPSK	21.50	21.02
n78	30	70	651000	216@0	DFT_QPSK	21.50	21.06
n78	30	70	651000	108@54	DFT_QPSK	21.50	21.05
n78	30	70	651000	1@1	DFT_QPSK	21.50	21.06
n78	30	70	651000	1@215	DFT_QPSK	21.50	21.05
n78	30	70	651000	1@1	DFT_QAM16	21.50	21.05
n78	30	70	651000	1@1	DFT_QAM64	21.50	21.04
n78	30	70	651000	1@1	DFT_QAM256	21.50	21.05
n78	30	70	651000	1@1	CP_QPSK	21.50	21.03
n78	30	80	622668	1@1	DFT_BPSK	23.00	22.69
n78	30	80	622668	216@0	DFT_QPSK	22.00	21.85
n78	30	80	622668	108@54	DFT_QPSK	23.00	22.98
n78	30	80	622668	1@1	DFT_QPSK	23.00	22.69
n78	30	80	622668	1@215	DFT_QPSK	22.50	22.25
n78	30	80	622668	1@1	DFT_QAM16	22.00	21.71
n78	30	80	622668	1@1	DFT_QAM64	20.50	20.2
n78	30	80	622668	1@1	DFT_QAM256	19.00	18.14
n78	30	80	622668	1@1	CP_QPSK	21.50	21.21
n78	30	80	636666	1@1	DFT_BPSK	23.50	23.31
n78	30	80	636666	216@0	DFT_QPSK	22.50	22.43
n78	30	80	636666	108@54	DFT_QPSK	24.00	23.57

n78	30	80	636666	1@1	DFT_QPSK	23.50	23.3
n78	30	80	636666	1@215	DFT_QPSK	23.00	22.67
n78	30	80	636666	1@1	DFT_QAM16	22.50	22.33
n78	30	80	636666	1@1	DFT_QAM64	21.00	20.87
n78	30	80	636666	1@1	DFT_QAM256	19.00	18.82
n78	30	80	636666	1@1	CP_QPSK	22.00	21.83
n78	30	80	650666	1@1	DFT_BPSK	23.00	23
n78	30	80	650666	216@0	DFT_QPSK	23.00	22.99
n78	30	80	650666	108@54	DFT_QPSK	24.50	24.08
n78	30	80	650666	1@1	DFT_QPSK	23.00	22.99
n78	30	80	650666	1@215	DFT_QPSK	24.00	23.74
n78	30	80	650666	1@1	DFT_QAM16	22.50	22.06
n78	30	80	650666	1@1	DFT_QAM64	21.00	20.5
n78	30	80	650666	1@1	DFT_QAM256	19.00	18.51
n78	30	80	650666	1@1	CP_QPSK	21.50	21.47
n78	30	90	623000	1@1	DFT_BPSK	23.00	22.6
n78	30	90	623000	240@0	DFT_QPSK	22.00	21.81
n78	30	90	623000	120@60	DFT_QPSK	23.00	22.98
n78	30	90	623000	1@1	DFT_QPSK	23.00	22.58
n78	30	90	623000	1@243	DFT_QPSK	22.50	22.42
n78	30	90	623000	1@1	DFT_QAM16	22.00	21.52
n78	30	90	623000	1@1	DFT_QAM64	20.50	20.04
n78	30	90	623000	1@1	DFT_QAM256	18.50	18.04
n78	30	90	623000	1@1	CP_QPSK	21.50	21.12
n78	30	90	636666	1@1	DFT_BPSK	23.50	23.18
n78	30	90	636666	240@0	DFT_QPSK	22.50	22.41
n78	30	90	636666	120@60	DFT_QPSK	24.00	23.57
n78	30	90	636666	1@1	DFT_QPSK	23.50	23.16
n78	30	90	636666	1@243	DFT_QPSK	22.50	22.39
n78	30	90	636666	1@1	DFT_QAM16	22.50	22.19
n78	30	90	636666	1@1	DFT_QAM64	21.00	20.67
n78	30	90	636666	1@1	DFT_QAM256	19.00	18.64
n78	30	90	636666	1@1	CP_QPSK	22.00	21.74
n78	30	90	650332	1@1	DFT_BPSK	23.00	22.79
n78	30	90	650332	240@0	DFT_QPSK	23.00	22.85
n78	30	90	650332	120@60	DFT_QPSK	24.50	24.08
n78	30	90	650332	1@1	DFT_QPSK	23.00	22.78
n78	30	90	650332	1@243	DFT_QPSK	24.00	23.55
n78	30	90	650332	1@1	DFT_QAM16	22.00	21.8

n78	30	90	650332	1@1	DFT_QAM64	20.50	20.3
n78	30	90	650332	1@1	DFT_QAM256	19.50	18.34
n78	30	90	650332	1@1	CP_QPSK	21.50	21.31
n78	30	100	623334	1@1	DFT_BPSK	22.50	22.41
n78	30	100	623334	270@0	DFT_QPSK	22.00	21.81
n78	30	100	623334	135@67	DFT_QPSK	23.00	22.95
n78	30	100	623334	1@1	DFT_QPSK	22.50	22.42
n78	30	100	623334	1@271	DFT_QPSK	22.50	22.07
n78	30	100	623334	1@1	DFT_QAM16	21.50	21.39
n78	30	100	623334	1@1	DFT_QAM64	20.00	19.93
n78	30	100	623334	1@1	DFT_QAM256	18.00	17.89
n78	30	100	623334	1@1	CP_QPSK	21.00	20.98
n78	30	100	636666	1@1	DFT_BPSK	23.50	23.09
n78	30	100	636666	270@0	DFT_QPSK	22.50	22.4
n78	30	100	636666	135@67	DFT_QPSK	24.00	23.59
n78	30	100	636666	1@1	DFT_QPSK	23.50	23.07
n78	30	100	636666	1@271	DFT_QPSK	22.50	22.17
n78	30	100	636666	1@1	DFT_QAM16	22.50	22.03
n78	30	100	636666	1@1	DFT_QAM64	21.00	20.57
n78	30	100	636666	1@1	DFT_QAM256	19.00	18.51
n78	30	100	636666	1@1	CP_QPSK	22.00	21.63
n78	30	100	650000	1@1	DFT_BPSK	23.00	22.56
n78	30	100	650000	270@0	DFT_QPSK	23.00	22.82
n78	30	100	650000	135@67	DFT_QPSK	24.50	24.08
n78	30	100	650000	1@1	DFT_QPSK	21.00	22.52
n78	30	100	650000	1@271	DFT_QPSK	23.50	23.45
n78	30	100	650000	1@1	DFT_QAM16	22.00	21.55
n78	30	100	650000	1@1	DFT_QAM64	20.50	20.01
n78	30	100	650000	1@1	DFT_QAM256	18.50	18.01
n78	30	100	650000	1@1	CP_QPSK	21.50	21.06

7.5. WLAN & Bluetooth Output Power

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11b	1	2412	16.00	15.83
	6	2437	16.00	14.87
	11	2462	16.00	14.16
802.11g	1	2412	14.00	13.58

	6	2437	14.00	12.84
	11	2462	14.00	11.98
802.11n HT20	1	2412	12.00	11.81
	6	2437	12.00	10.93
	11	2462	12.00	10.12
802.11n HT40	3	2422	12.00	11.52
	6	2437	12.00	10.88
	9	2452	12.00	10.66
802.11ax20	1	2412	12.00	11.8
	6	2437	12.00	11.18
	11	2462	12.00	10.39
802.11ax40	3	2422	12.00	11.85
	6	2437	12.00	11.36
	9	2452	12.00	10.93

NOTE: Power measurement results of WLAN 2.4G.

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11a	36	5180	12.00	11.82
	40	5200	12.00	11.84
	48	5240	12.00	11.46
802.11n HT20	36	5180	11.50	10.80
	40	5200	11.50	11.20
	48	5240	11.50	10.36
802.11n HT40	38	5190	10.50	10.20
	46	5230	10.50	9.99
802.11ac VHT20	36	5180	11.50	10.96
	40	5200	11.50	11.11
	48	5240	11.50	10.54
802.11ac VHT40	38	5190	10.50	10.18
	46	5230	10.50	9.79
802.11ac VHT80	42	5210	10.00	9.80
802.11ax VHT20	36	5180	11.50	10.88
	40	5200	11.50	11.05
	48	5240	11.50	10.84
802.11ax VHT40	38	5190	10.50	10.32
	46	5230	10.50	9.87
802.11ax VHT80	42	5210	10.50	10.12

NOTE: Power measurement results of WLAN 5.2G.

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11a	149	5745	8.00	7.56
	157	5785	8.00	6.29
	165	5825	8.00	5.61
802.11n HT20	149	5745	8.00	7.61
	157	5785	8.00	6.16
	165	5825	8.00	5.83
802.11n HT40	151	5755	8.00	7.87
	159	5795	8.00	6.31
802.11ac VHT20	149	5745	7.50	7.47
	157	5785	7.50	6.15
	165	5825	7.50	5.68
802.11ac VHT40	151	5755	8.00	7.89
	159	5795	8.00	6.61
802.11ac VHT80	155	5775	7.00	6.95
802.11ax VHT20	149	5745	9.50	9.36
	157	5785	9.50	8.41
	165	5825	9.50	8.40
802.11ax VHT40	151	5755	9.50	9.42
	159	5795	9.50	8.41
802.11ax VHT80	155	5775	9.00	8.89

NOTE: Power measurement results of WLAN 5.8G.

BR+EDR	Output Power (dBm)				
	Data Rates	Tune-up (dBm)	Channel		
			0CH	39CH	78CH
	1M	4	3.77	3.15	2.81
	2M	4	3.29	2.40	1.95
	3M	4	3.66	2.70	2.34


BLE	Output Power (dBm)				
	Data Rates	Tune-up (dBm)	Channe		
			0CH	19CH	39CH
	1M	-1	-1.32	-2.19	-2.98
	2M	-1	-1.33	-2.16	-3.15

NOTE: Power measurement results of Bluetooth.

7.6. NFC

Channel Freq (MHz)	Min Distance (mm)	Max power (dBm)	tune-up power (dBm)	Max power (mW)	Limits (mW)	SAR Test Exclusion
13.56	10	-16.53	-16.53 ± 1	0.02799	443	Yes

8. Antenna Location



Note: Since the confidentiality request of EUT, the antenna location example diagram see as above.

Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN ANT 1	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	> 25mm
WWAN ANT 2	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm	≤25mm	> 25mm
WWAN ANT 3	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	> 25mm	≤ 25mm
WLAN & Bluetooth	≤ 25mm	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm	>25mm
Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN ANT 1	Yes	Yes	NO	Yes	NO	NO
WWAN ANT 2	Yes	Yes	NO	Yes	Yes	NO
WWAN ANT 3	Yes	Yes	Yes	Yes	NO	Yes
WLAN & Bluetooth	Yes	Yes	Yes	NO	Yes	NO

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation

- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P _{max} (dBm)	P _{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	4.00	2.512	5	2.480	2.807	3	Yes

NOTE: Standalone SAR test exclusion for Bluetooth.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f_{\text{(GHz)}}}/x] \text{ W/kg}$$
 for test separation distances $\leq 50\text{mm}$, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P _{max} (dBm)	P _{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Head	4.00	2.51	5	2.48	7.5	0.105
Bluetooth	Body	4.00	2.51	10	2.48	7.5	0.053
Bluetooth	Hotspot	4.00	2.51	10	2.48	7.5	0.053
Bluetooth	Extremity	4.00	2.51	5	2.48	18.75	0.042

NOTE: Estimated SAR calculation for Bluetooth

10. SAR Results

10.1. SAR measurement Result

10.1.1. SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(±5%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	189/836.4	GPRS(GMSK 4TS)	0.305	0.234	0.56	28.84	29.00	0.316	2024/11/26	1#
Left Tilt 15 Degree	189/836.4	GPRS(GMSK 4TS)	0.159	0.117	2.29	28.84	29.00	0.165	2024/11/26	
Right Cheek	189/836.4	GPRS(GMSK 4TS)	0.298	0.233	2.16	28.84	29.00	0.309	2024/11/26	

Right Tilt 15 Degree	189/836.4	GPRS(GMSK 4TS)	0.149	0.113	-2.48	28.84	29.00	0.155	2024/11/26	
----------------------------	-----------	-------------------	-------	-------	-------	-------	-------	-------	------------	--

NOTE: Head SAR test results of GSM850.

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	189/836.4	GPRS(GMSK 4TS)	0.510	0.298	0.96	28.84	29.00	0.529	2024/11/26	
Back Side	189/836.4	GPRS(GMSK 4TS)	0.508	0.300	-3.00	28.84	29.00	0.527	2024/11/26	

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	189/836.4	GPRS(GMSK 4TS)	0.510	0.298	0.96	28.84	29.00	0.529	2024/11/26	
Back Side	189/836.4	GPRS(GMSK 4TS)	0.508	0.300	-3.00	28.84	29.00	0.527	2024/11/26	2#
Left Side	189/836.4	GPRS(GMSK 4TS)	0.106	0.060	2.95	28.84	29.00	0.110	2024/11/26	
Right Side	189/836.4	GPRS(GMSK 4TS)	0.424	0.250	-3.73	28.84	29.00	0.440	2024/11/26	
Bottom Side	189/836.4	GPRS(GMSK 4TS)	0.657	0.365	2.60	28.84	29.00	0.682	2024/11/26	

NOTE: Hotspot SAR test results of GSM850

10.1.2. SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	661/1880	GPRS(GMSK 4TS)	0.140	0.081	0.14	26.66	27.00	0.151	2024/11/24	3#
Left Tilt	661/1880	GPRS(GMSK	0.079	0.044	-1.10	26.66	27.00	0.085	2024/11/24	

15 Degree		4TS)								
Right Cheek	661/1880	GPRS(GMSK 4TS)	0.129	0.073	-3.31	26.66	27.00	0.140	2024/11/24	
Right Tilt 15 Degree	661/1880	GPRS(GMSK 4TS)	0.070	0.038	-1.00	26.66	27.00	0.076	2024/11/24	

NOTE: Head SAR test results of GSM1900

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	661/1880	GPRS(GMSK 4TS)	0.078	0.039	-1.79	26.66	27.00	0.084	2024/11/24	
Back Side	661/1880	GPRS(GMSK 4TS)	0.218	0.115	-0.87	26.66	27.00	0.236	2024/11/24	4#

NOTE: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducte d power (dBm)	Tune-up power (dBm)	Scale d SAR 1g (W/K g)	Date	Plot
			1-g	10-g						
Front Side	661/1880	GPRS(GMSK 4TS)	0.078	0.039	-1.79	26.66	27.00	0.084	2024/11/24	
Back Side	661/1880	GPRS(GMSK 4TS)	0.218	0.115	-0.87	26.66	27.00	0.236	2024/11/24	4#
Left Side	661/1880	GPRS(GMSK 4TS)	0.104	0.054	-0.48	26.66	27.00	0.112	2024/11/24	
Right Side	661/1880	GPRS(GMSK 4TS)	0.026	0.013	3.86	26.66	27.00	0.028	2024/11/24	
Top Side	661/1880	GPRS(GMSK 4TS)	0.113	0.057	0.37	26.66	27.00	0.122	2024/11/24	

NOTE: Hotspot SAR test results of GSM1900

10.1.3. SAR measurement Result of WCDMA Band 2

Test Position of	Test channel	Test Mode	SAR Value (W/kg)	Power Drift	Conducted power	Tune-up power	Scaled SAR 1g	Date	Plot
---------------------	-----------------	-----------	---------------------	----------------	--------------------	------------------	------------------	------	------

Head	/Freq		1-g	10-g	(±5%)	(dBm)	(dBm)	(W/Kg)		
Left Cheek	9400/1880	RMC12.2K	0.153	0.092	4.24	23.32	23.50	0.159	2024/11/24	5#
Left Tilt 15 Degree	9400/1880	RMC12.2K	0.079	0.046	-1.90	23.32	23.50	0.082	2024/11/24	
Right Cheek	9400/1880	RMC12.2K	0.141	0.085	-0.30	23.32	23.50	0.147	2024/11/24	
Right Tilt 15 Degree	9400/1880	RMC12.2K	0.072	0.042	-1.41	23.32	23.50	0.075	2024/11/24	

NOTE: Head SAR test results of WCDMA Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	9400/1880	RMC12.2K	0.087	0.044	-1.69	23.32	23.50	0.091	2024/11/24	
Back Side	9400/1880	RMC12.2K	0.281	0.147	0.71	23.32	23.50	0.293	2024/11/24	6#

NOTE: Body-Worn SAR test results of WCDMA Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducte d power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plo t
			1-g	10-g						
Front Side	9400/1880	RMC12.2K	0.087	0.044	-1.69	23.32	23.50	0.091	2024/11/24	
Back Side	9400/1880	RMC12.2K	0.281	0.147	0.71	23.32	23.50	0.293	2024/11/24	6#
Left Side	9400/1880	RMC12.2K	0.116	0.059	-1.92	23.32	23.50	0.121	2024/11/24	
Right Side	9400/1880	RMC12.2K	0.030	0.015	-1.76	23.32	23.50	0.031	2024/11/24	
Top Side	9400/1880	RMC12.2K	0.131	0.069	3.49	23.32	23.50	0.137	2024/11/24	

NOTE: Hotspot SAR test results of WCDMA Band 2

10.1.4. SAR measurement Result of WCDMA Band 4

Test Position of Head	Test channel /Freq	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	1413/1732.6	RMC12.2K	0.058	0.039	-0.55	23.22	23.50	0.062	2024/11/21	5#

NOTE: Head SAR test results of WCDMA Band 4

NOTE: Body-Worn SAR test results of WCDMA Band 4

NOTE: Hotspot SAR test results of WCDMA Band 4

Test Position of Head	Test channel /Freq	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g	Date	Plot
			1-g	10-g						

								(W/Kg)		
Left Cheek	4182/836.4	RMC12.2K	0.188	0.147	-0.15	22.53	23.00	0.209	2024/11/26	7#
Left Tilt 15 Degree	4182/836.4	RMC12.2K	0.100	0.078	-3.82	22.53	23.00	0.111	2024/11/26	
Right Cheek	4182/836.4	RMC12.2K	0.183	0.140	0.77	22.53	23.00	0.204	2024/11/26	
Right Tilt 15 Degree	4182/836.4	RMC12.2K	0.094	0.071	1.24	22.53	23.00	0.105	2024/11/26	

NOTE: Head SAR test results of WCDMA Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	4182/836.4	RMC12.2K	0.350	0.201	2.01	22.53	23.00	0.390	2024/11/26	
Back Side	4182/836.4	RMC12.2K	0.329	0.195	0.00	22.53	23.00	0.367	2024/11/26	8#

NOTE: Body-Worn SAR test results of WCDMA Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	4182/836.4	RMC12.2K	0.350	0.201	2.01	22.53	23.00	0.390	2024/11/26	
Back Side	4182/836.4	RMC12.2K	0.329	0.195	0.00	22.53	23.00	0.367	2024/11/26	10#
Left Side	4182/836.4	RMC12.2K	0.074	0.044	3.06	22.53	23.00	0.082	2024/11/26	
Right Side	4182/836.4	RMC12.2K	0.288	0.171	-2.32	22.53	23.00	0.321	2024/11/26	
Bottom Side	4182/836.4	RMC12.2K	0.429	0.239	-0.51	22.53	23.00	0.478	2024/11/26	

NOTE: Hotspot SAR test results of WCDMA Band 5

10.1.6. SAR measurement Result of LTE Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						

1RB										
Left Cheek	18900/1880	20M QPSK(1,49)	0.189	0.114	1.81	23.27	23.50	0.199	2024/12/09	11#
Left Tilt 15 Degree	18900/1880	20M QPSK(1,49)	0.106	0.061	-3.86	23.27	23.50	0.112	2024/12/09	
Right Cheek	18900/1880	20M QPSK(1,49)	0.176	0.105	-1.12	23.27	23.50	0.186	2024/12/09	
Right Tilt 15 Degree	18900/1880	20M QPSK(1,49)	0.096	0.055	-0.31	23.27	23.50	0.101	2024/12/09	
50%RB										
Left Cheek	18900/1880	20M QPSK(50,24)	0.113	0.061	3.59	22.33	22.50	0.118	2024/12/09	
Left Tilt 15 Degree	18900/1880	20M QPSK(50,24)	0.062	0.032	3.9	22.33	22.50	0.064	2024/12/09	
Right Cheek	18900/1880	20M QPSK(50,24)	0.106	0.062	4.37	22.33	22.50	0.110	2024/12/09	
Right Tilt 15 Degree	18900/1880	20M QPSK(50,24)	0.051	0.032	-2.81	22.33	22.50	0.053	2024/12/09	

NOTE: Head SAR test results of LTE Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	18900/1880	20M QPSK(1,49)	0.087	0.044	-0.72	23.27	23.50	0.092	2024/12/09	
Back Side	18900/1880	20M QPSK(1,49)	0.255	0.135	-0.44	23.27	23.50	0.269	2024/12/09	12#
50%RB										
Front Side	18900/1880	20M QPSK(50,24)	0.052	0.023	-2.54	22.33	22.50	0.054	2024/12/09	
Back	18900/1880	20M	0.137	0.069	2.43	22.33	22.50	0.142	2024/12/09	

NOTE: Body-Worn SAR test results of LTE Band 2

NOTE: Hotspot SAR test results of LTE Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										

Left Cheek	20175/1732.5	20M QPSK(1,49)	0.054	0.036	1.56	23.41	23.50	0.055	2024/11/21	11#
Left Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.027	0.018	3.43	23.41	23.50	0.028	2024/11/21	
Right Cheek	20175/1732.5	20M QPSK(1,49)	0.050	0.033	3.11	23.41	23.50	0.051	2024/11/21	
Right Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.024	0.016	2.83	23.41	23.50	0.025	2024/11/21	
50%RB										
Left Cheek	20175/1732.5	20M QPSK(50,24)	0.03	0.019	0.03	22.44	22.50	0.030	2024/11/21	
Left Tilt 15 Degree	20175/1732.5	20M QPSK(50,24)	0.016	0.01	-0.9	22.44	22.50	0.016	2024/11/21	
Right Cheek	20175/1732.5	20M QPSK(50,24)	0.029	0.017	-2.63	22.44	22.50	0.029	2024/11/21	
Right Tilt 15 Degree	20175/1732.5	20M QPSK(50,24)	0.014	0.009	-1.51	22.44	22.50	0.014	2024/11/21	

NOTE: Head SAR test results of LTE Band 4

Test Position of Body- Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	20175/1732.5	20M QPSK(1,49)	0.030	0.021	1.60	23.41	23.50	0.031	2024/11/21	
Back Side	20175/1732.5	20M QPSK(1,49)	0.078	0.055	0.26	23.41	23.50	0.080	2024/11/21	12#
50%RB										
Front Side	20175/1732.5	20M QPSK(50,24)	0.016	0.011	-1.05	22.44	22.50	0.016	2024/11/21	
Back Side	20175/1732.5	20M QPSK(50,24)	0.04	0.03	2.99	22.44	22.50	0.041	2024/11/21	

NOTE: Body-Worn SAR test results of LTE Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	20175/1732.5	20M QPSK(1,49)	0.030	0.021	1.60	23.41	23.50	0.031	2024/11/21	
Back Side	20175/1732.5	20M QPSK(1,49)	0.078	0.055	0.26	23.41	23.50	0.080	2024/11/21	12#
Left Side	20175/1732.5	20M QPSK(1,49)	0.044	0.029	0.87	23.41	23.50	0.045	2024/11/21	
Right Side	20175/1732.5	20M QPSK(1,49)	0.012	0.010	-2.07	23.41	23.50	0.012	2024/11/21	
Top Side	20175/1732.5	20M QPSK(1,49)	0.036	0.025	-2.17	23.41	23.50	0.037	2024/11/21	
50%RB										
Front Side	20175/1732.5	20M QPSK(50,24)	0.016	0.011	-1.05	22.44	22.50	0.016	2024/11/21	
Back Side	20175/1732.5	20M QPSK(50,24)	0.04	0.03	2.99	22.44	22.50	0.041	2024/11/21	
Left Side	20175/1732.5	20M QPSK(50,24)	0.025	0.017	-3.58	22.44	22.50	0.025	2024/11/21	
Right Side	20175/1732.5	20M QPSK(50,24)	0.007	0.006	-3.51	22.44	22.50	0.007	2024/11/21	
Top Side	20175/1732.5	20M QPSK(50,24)	0.019	0.013	-3.1	22.44	22.50	0.019	2024/11/21	

NOTE: Hotspot SAR test results of LTE Band 4

10.1.8. SAR measurement Result of LTE Band 5

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	20525/836.5	10M QPSK(1,24)	0.307	0.239	-0.47	24.73	25.00	0.327	2024/11/23	13#
Left Tilt	20525/836.5	10M	0.180	0.136	0.74	24.73	25.00	0.192	2024/11/23	

15 Degree		QPSK(1,24)								
Right Cheek	20525/836.5	10M QPSK(1,24)	0.297	0.233	0.12	24.73	25.00	0.316	2024/11/23	
Right Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.183	0.135	3.53	24.73	25.00	0.195	2024/11/23	
50%RB										
Left Cheek	20525/836.5	10M QPSK(25,0)	0.177	0.143	-3.69	23.71	24.00	0.189	2024/11/23	
Left Tilt 15 Degree	20525/836.5	10M QPSK(25,0)	0.093	0.068	0.29	23.71	24.00	0.099	2024/11/23	
Right Cheek	20525/836.5	10M QPSK(25,0)	0.174	0.128	-1.62	23.71	24.00	0.186	2024/11/23	
Right Tilt 15 Degree	20525/836.5	10M QPSK(25,0)	0.096	0.077	3.08	23.71	24.00	0.103	2024/11/23	

NOTE: Head SAR test results of LTE Band 5

Test Position of Body-W orn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	20525/836.5	10M QPSK(1,24)	0.520	0.310	-0.37	24.73	25.00	0.553	2024/11/23	
Back Side	20525/836.5	10M QPSK(1,24)	0.480	0.289	-0.38	24.73	25.00	0.511	2024/11/23	14#
50%RB										
Front Side	20525/836.5	10M QPSK(25,0)	0.283	0.177	-0.92	23.71	24.00	0.303	2024/11/23	
Back Side	20525/836.5	10M QPSK(25,0)	0.257	0.156	-0.1	23.71	24.00	0.275	2024/11/23	

NOTE: Body-Worn SAR test results of LTE Band 5

Test	Test channel	Test Mode	SAR Value	Power	Conducted	Tune-up	Scaled	Date	Plot
------	--------------	-----------	-----------	-------	-----------	---------	--------	------	------

Position of Hotspot with 10mm	/Freq.		(W/kg)		Drift (±5%)	power (dBm)	power (dBm)	SAR 1g (W/Kg)		
			1-g	10-g						
1RB										
Front Side	20525/836.5	10M QPSK(1,24)	0.520	0.310	-0.37	24.73	25.00	0.553	2024/11/23	
Back Side	20525/836.5	10M QPSK(1,24)	0.480	0.289	-0.38	24.73	25.00	0.511	2024/11/23	14#
Left Side	20525/836.5	10M QPSK(1,24)	0.096	0.056	-2.15	24.73	25.00	0.102	2024/11/23	
Right Side	20525/836.5	10M QPSK(1,24)	0.424	0.255	2.82	24.73	25.00	0.451	2024/11/23	
Bottom Side	20525/836.5	10M QPSK(1,24)	0.645	0.367	-0.18	24.73	25.00	0.686	2024/11/23	
50%RB										
Front Side	20525/836.5	10M QPSK(25,0)	0.283	0.177	-0.92	23.71	24.00	0.303	2024/11/23	
Back Side	20525/836.5	10M QPSK(25,0)	0.257	0.156	-0.1	23.71	24.00	0.275	2024/11/23	
Left Side	20525/836.5	10M QPSK(25,0)	0.054	0.034	-4.82	23.71	24.00	0.058	2024/11/23	
Right Side	20525/836.5	10M QPSK(25,0)	0.225	0.149	1.77	23.71	24.00	0.241	2024/11/23	
Bottom Side	20525/836.5	10M QPSK(25,0)	0.348	0.215	-0.76	23.71	24.00	0.372	2024/11/23	

NOTE: Hotspot SAR test results of LTE Band 5

10.1.9. SAR measurement Result of LTE Band 7

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	21100/2535	20M QPSK(1,49)	0.353	0.182	0.60	23.59	24.00	0.388	2024/11/25	13#
Left Tilt 15	21100/2535	20M QPSK(1,49)	0.189	0.096	-1.95	23.59	24.00	0.208	2024/11/25	

Degree										
Right Cheek	21100/2535	20M QPSK(1,49)	0.599	0.262	-2.23	23.59	24.00	0.658	2024/11/25	
Right Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.301	0.151	1.07	23.59	24.00	0.331	2024/11/25	
50%RB										
Left Cheek	21100/2535	20M QPSK(50,0)	0.207	0.1	-0.26	22.66	23.00	0.224	2024/11/25	
Left Tilt 15 Degree	21100/2535	20M QPSK(50,0)	0.095	0.051	-4.43	22.66	23.00	0.103	2024/11/25	
Right Cheek	21100/2535	20M QPSK(50,0)	0.317	0.15	-0.42	22.66	23.00	0.343	2024/11/25	
Right Tilt 15 Degree	21100/2535	20M QPSK(50,0)	0.176	0.084	-4.87	22.66	23.00	0.190	2024/11/25	

NOTE: Head SAR test results of LTE Band 7

Test Position of Body-W orn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	21100/2535	20M QPSK(1,49)	0.183	0.085	-1.45	23.59	24.00	0.201	2024/11/25	
Back Side	21100/2535	20M QPSK(1,49)	1.181	0.574	-1.34	23.59	24.00	1.298	2024/11/25	14#
Back Side	20850/2510	20M QPSK(1,49)	1.101	0.541	0.21	23.35	24.00	1.279	2024/11/25	
Back Side	21350/2560	20M QPSK(1,49)	1.014	0.436	-0.83	23.67	24.00	1.094	2024/11/25	
BackSide Repeated	21100/2535	20M QPSK(1,49)	1.174	0.570	0.55	23.59	24.00	1.290	2024/11/25	
50%RB										
Front Side	20525/836.5	10M QPSK(25,0)	0.283	0.177	-0.92	23.71	24.00	0.303	2024/11/23	

Back Side	20525/836.5	10M QPSK(25,0)	0.257	0.156	-0.1	23.71	24.00	0.275	2024/11/23	
-----------	-------------	-------------------	-------	-------	------	-------	-------	-------	------------	--

NOTE: Body-Worn SAR test results of LTE Band 7

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	21100/2535	20M QPSK(1,49)	0.183	0.085	-1.45	23.59	24.00	0.201	2024/11/25	
Back Side	21100/2535	20M QPSK(1,49)	1.181	0.574	-1.34	23.59	24.00	1.298	2024/11/25	14#
Left Side	21100/2535	20M QPSK(1,49)	0.214	0.099	2.04	23.59	24.00	0.235	2024/11/25	
Right Side	21100/2535	20M QPSK(1,49)	0.060	0.029	3.07	23.59	24.00	0.066	2024/11/25	
Bottom Side	21100/2535	20M QPSK(1,49)	0.908	0.516	3.15	23.59	24.00	0.998	2024/11/25	
Back Side	20850/2510	20M QPSK(1,49)	1.101	0.541	0.21	23.35	24.00	1.279	2024/11/25	
Back Side	21350/2560	20M QPSK(1,49)	1.014	0.436	-0.83	23.67	24.00	1.094	2024/11/25	
Bottom Side	21100/2535	20M QPSK(1,49)	0.867	0.469	-2.61	23.35	24.00	1.007	2024/11/25	
Bottom Side	21100/2535	20M QPSK(1,49)	0.885	0.564	-1.51	23.67	24.00	0.955	2024/11/25	
BackSide Repeated	21100/2535	20M QPSK(1,49)	1.174	0.570	0.55	23.59	24.00	1.290	2024/11/25	
50%RB										
Front Side	21100/2535	20M QPSK(50,0)	0.108	0.046	3.24	22.66	23.00	0.117	2024/11/25	
Back Side	21100/2535	20M QPSK(50,0)	0.682	0.304	-3.34	22.66	23.00	0.738	2024/11/25	
Left Side	21100/2535	20M QPSK(50,0)	0.119	0.051	-1.26	22.66	23.00	0.129	2024/11/25	
Right Side	21100/2535	20M QPSK(50,0)	0.035	0.016	4.79	22.66	23.00	0.038	2024/11/25	

Bottom Side	21100/2535	20M QPSK(50,0)	0.541	0.305	-2.06	22.66	23.00	0.585	2024/11/25	
----------------	------------	-------------------	-------	-------	-------	-------	-------	-------	------------	--

NOTE: Hotspot SAR test results of LTE Band 7

Test Position of Hotspot with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Back Side	21100/2535	20M QPSK(1,49)	2.635	1.328	-2.61	23.59	24.00	1.459	2024/11/25	#39

NOTE: Extremity SAR test results of LTE Band 7

10.1.10. SAR measurement Result of LTE Band 12

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	23095/707.5	10M QPSK(1,24)	0.314	0.260	0.19	24.42	25.00	0.359	2024/11/27	15#
Left Tilt 15 Degree	23095/707.5	10M QPSK(1,24)	0.161	0.133	-1.23	24.42	25.00	0.184	2024/11/27	
Right Cheek	23095/707.5	10M QPSK(1,24)	0.308	0.253	-0.27	24.42	25.00	0.352	2024/11/27	
Right Tilt 15 Degree	23095/707.5	10M QPSK(1,24)	0.158	0.130	-2.22	24.42	25.00	0.181	2024/11/27	
50%RB										
Left Cheek	23095/707.5	10M QPSK(25,0)	0.164	0.133	-3.59	23.40	23.50	0.168	2024/11/27	
Left Tilt 15 Degree	23095/707.5	10M QPSK(25,0)	0.086	0.074	-1.02	23.40	23.50	0.088	2024/11/27	
Right Cheek	23095/707.5	10M QPSK(25,0)	0.184	0.129	0.1	23.40	23.50	0.188	2024/11/27	
Right	23095/707.5	10M	0.088	0.07	3.8	23.40	23.50	0.090	2024/11/27	

Tilt 15 Degree		QPSK(25,0)								
-------------------	--	------------	--	--	--	--	--	--	--	--

NOTE: Head SAR test results of LTE Band 12

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23095/707.5	10M QPSK(1,24)	0.350	0.219	0.23	24.42	25.00	0.400	2024/11/27	
Back Side	23095/707.5	10M QPSK(1,24)	0.301	0.196	-0.55	24.42	25.00	0.344	2024/11/27	16#
50%RB										
Front Side	23095/707.5	10M QPSK(25,0)	0.188	0.115	1.52	23.40	23.50	0.192	2024/11/27	
Back Side	23095/707.5	10M QPSK(25,0)	0.16	0.112	0.67	23.40	23.50	0.164	2024/11/27	

NOTE: Body-Worn SAR test results of LTE Band 12

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23095/707.5	10M QPSK(1,24)	0.350	0.219	0.23	24.42	25.00	0.400	2024/11/27	
Back Side	23095/707.5	10M QPSK(1,24)	0.301	0.196	-0.55	24.42	25.00	0.344	2024/11/27	16#
Left Side	23095/707.5	10M QPSK(1,24)	0.066	0.041	1.31	24.42	25.00	0.075	2024/11/27	
Right Side	23095/707.5	10M QPSK(1,24)	0.272	0.175	-2.08	24.42	25.00	0.311	2024/11/27	
Bottom Side	23095/707.5	10M QPSK(1,24)	0.406	0.237	-1.22	24.42	25.00	0.464	2024/11/27	
50%RB										
Front Side	23095/707.5	10M QPSK(25,0)	0.188	0.115	1.52	23.40	23.50	0.192	2024/11/27	

Back Side	23095/707.5	10M QPSK(25,0)	0.16	0.112	0.67	23.40	23.50	0.164	2024/11/27	
Left Side	23095/707.5	10M QPSK(25,0)	0.037	0.023	3.38	23.40	23.50	0.038	2024/11/27	
Right Side	23095/707.5	10M QPSK(25,0)	0.16	0.095	-2	23.40	23.50	0.164	2024/11/27	
Bottom Side	23095/707.5	10M QPSK(25,0)	0.225	0.14	-0.44	23.40	23.50	0.230	2024/11/27	

NOTE: Hotspot SAR test results of LTE Band 12

10.1.11. SAR measurement Result of LTE Band 17

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	23790/710	10M QPSK(1,24)	0.333	0.276	-0.27	24.29	25.00	0.392	2024/11/27	15#
Left Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.187	0.152	1.41	24.29	25.00	0.220	2024/11/27	
Right Cheek	23790/710	10M QPSK(1,24)	0.325	0.263	-1.36	24.29	25.00	0.383	2024/11/27	
Right Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.169	0.137	-0.87	24.29	25.00	0.199	2024/11/27	
50%RB										
Left Cheek	23790/710	10M QPSK(25,0)	0.194	0.14	2.7	23.30	23.50	0.203	2024/11/27	
Left Tilt 15 Degree	23790/710	10M QPSK(25,0)	0.097	0.089	1.19	23.30	23.50	0.102	2024/11/27	
Right Cheek	23790/710	10M QPSK(25,0)	0.165	0.136	1.22	23.30	23.50	0.173	2024/11/27	
Right Tilt 15 Degree	23790/710	10M QPSK(25,0)	0.087	0.075	4.33	23.30	23.50	0.091	2024/11/27	

NOTE: Head SAR test results of LTE Band 17

Test	Test channel	Test Mode	SAR Value	Power	Conducted	Tune-up	Scaled	Date	Plot
------	--------------	-----------	-----------	-------	-----------	---------	--------	------	------

Position of Body-Worn with 10mm	/Freq.		(W/kg)		Drift (±5%)	power (dBm)	power (dBm)	SAR 1g (W/Kg)		
			1-g	10-g						
1RB										
Front Side	23790/710	10M QPSK(1,24)	0.310	0.175	-0.77	24.29	25.00	0.365	2024/11/27	
Back Side	23790/710	10M QPSK(1,24)	0.300	0.169	-1.50	24.29	25.00	0.353	2024/11/27	16#
50%RB										
Front Side	23790/710	10M QPSK(25,0)	0.169	0.093	3.45	23.30	23.50	0.177	2024/11/27	
Back Side	23790/710	10M QPSK(25,0)	0.153	0.097	3.37	23.30	23.50	0.160	2024/11/27	

NOTE: Body-Worn SAR test results of LTE Band 17

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23790/710	10M QPSK(1,24)	0.310	0.175	-0.77	24.29	25.00	0.365	2024/11/27	
Back Side	23790/710	10M QPSK(1,24)	0.300	0.169	-1.50	24.29	25.00	0.353	2024/11/27	16#
Left Side	23790/710	10M QPSK(1,24)	0.064	0.034	0.51	24.29	25.00	0.075	2024/11/27	
Right Side	23790/710	10M QPSK(1,24)	0.248	0.133	-3.54	24.29	25.00	0.292	2024/11/27	
Bottom Side	23790/710	10M QPSK(1,24)	0.375	0.218	-1.18	24.29	25.00	0.442	2024/11/27	
50%RB										
Front Side	23790/710	10M QPSK(25,0)	0.169	0.093	3.45	23.30	23.50	0.177	2024/11/27	
Back Side	23790/710	10M QPSK(25,0)	0.153	0.097	3.37	23.30	23.50	0.160	2024/11/27	
Left Side	23790/710	10M QPSK(25,0)	0.037	0.019	4.67	23.30	23.50	0.039	2024/11/27	
Right	23790/710	10M	0.128	0.075	-0.27	23.30	23.50	0.134	2024/11/27	

Side		QPSK(25,0)								
Bottom Side	23790/710	10M QPSK(25,0)	0.222	0.115	-0.07	23.30	23.50	0.232	2024/11/27	

NOTE: Hotspot SAR test results of LTE Band 17

10.1.12. SAR measurement Result of LTE Band 25

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	26365/1882.5	20M QPSK(1,49)	0.195	0.117	-0.51	23.31	23.50	0.204	2024/12/09	17#
Left Tilt 15 Degree	26365/1882.5	20M QPSK(1,49)	0.108	0.062	-1.20	23.31	23.50	0.113	2024/12/09	
Right Cheek	26365/1882.5	20M QPSK(1,49)	0.170	0.098	-0.93	23.31	23.50	0.178	2024/12/09	
Right Tilt 15 Degree	26365/1882.5	20M QPSK(1,49)	0.083	0.048	2.95	23.31	23.50	0.087	2024/12/09	
50%RB										
Left Cheek	26365/1882.5	20M QPSK(25,24)	0.105	0.068	2.64	22.39	22.50	0.108	2024/12/09	
Left Tilt 15 Degree	26365/1882.5	20M QPSK(25,24)	0.057	0.034	-0.25	22.39	22.50	0.058	2024/12/09	
Right Cheek	26365/1882.5	20M QPSK(25,24)	0.089	0.055	-4.96	22.39	22.50	0.091	2024/12/09	
Right Tilt 15 Degree	26365/1882.5	20M QPSK(25,24)	0.045	0.026	0.16	22.39	22.50	0.046	2024/12/09	

NOTE: Head SAR test results of LTE Band 25

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						

1RB										
Front Side	26365/1882.5	20M QPSK(1,49)	0.084	0.043	2.16	23.31	23.50	0.088	2024/12/09	
Back Side	26365/1882.5	20M QPSK(1,49)	0.256	0.134	0.36	23.31	23.50	0.267	2024/12/09	18#
50%RB										
Front Side	26365/1882.5	20M QPSK(25,24)	0.046	0.024	-0.25	22.39	22.50	0.047	2024/12/09	
Back Side	26365/1882.5	20M QPSK(25,24)	0.147	0.073	3.85	22.39	22.50	0.151	2024/12/09	

NOTE: Body-Worn SAR test results of LTE Band 25

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	26365/1882.5	20M QPSK(1,49)	0.084	0.043	2.16	23.31	23.50	0.088	2024/12/09	
Back Side	26365/1882.5	20M QPSK(1,49)	0.256	0.134	0.36	23.31	23.50	0.267	2024/12/09	18#
Left Side	26365/1882.5	20M QPSK(1,49)	0.120	0.060	0.32	23.31	23.50	0.125	2024/12/09	
Right Side	26365/1882.5	20M QPSK(1,49)	0.029	0.015	3.93	23.31	23.50	0.030	2024/12/09	
Top Side	26365/1882.5	20M QPSK(1,49)	0.131	0.065	-3.00	23.31	23.50	0.137	2024/12/09	
50%RB										
Front Side	26365/1882.5	20M QPSK(25,24)	0.046	0.024	-0.25	22.39	22.50	0.047	2024/12/09	
Back Side	26365/1882.5	20M QPSK(25,24)	0.147	0.073	3.85	22.39	22.50	0.151	2024/12/09	
Left Side	26365/1882.5	20M QPSK(25,24)	0.07	0.035	4.66	22.39	22.50	0.072	2024/12/09	
Right Side	26365/1882.5	20M QPSK(25,24)	0.015	0.008	-1.91	22.39	22.50	0.015	2024/12/09	
Top Side	26365/1882.5	20M QPSK(25,24)	0.074	0.039	-1.37	22.39	22.50	0.076	2024/12/09	

NOTE: Hotspot SAR test results of LTE Band 25

10.1.13. SAR measurement Result of LTE Band 26a

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	26740/819	10M QPSK(1,24)	0.334	0.262	0.87	24.46	25.00	0.378	2024/12/11	17#
Left Tilt 15 Degree	26740/819	10M QPSK(1,24)	0.186	0.144	1.64	24.46	25.00	0.211	2024/12/11	
Right Cheek	26740/819	10M QPSK(1,24)	0.315	0.252	-1.90	24.46	25.00	0.357	2024/12/11	
Right Tilt 15 Degree	26740/819	10M QPSK(1,24)	0.169	0.126	1.26	24.46	25.00	0.191	2024/12/11	
50%RB										
Left Cheek	26740/819	10M QPSK(25,24)	0.184	0.154	-2.48	23.61	24.00	0.201	2024/12/11	
Left Tilt 15 Degree	26740/819	10M QPSK(25,24)	0.107	0.073	3.17	23.61	24.00	0.117	2024/12/11	
Right Cheek	26740/819	10M QPSK(25,24)	0.185	0.144	4.47	23.61	24.00	0.202	2024/12/11	
Right Tilt 15 Degree	26740/819	10M QPSK(25,24)	0.099	0.063	4	23.61	24.00	0.108	2024/12/11	

NOTE: Head SAR test results of LTE Band 26a

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
			1RB							
Front Side	26740/819	10M QPSK(1,24)	0.510	0.286	1.42	24.46	25.00	0.578	2024/12/11	
Back Side	26740/819	10M	0.468	0.262	-3.20	24.46	25.00	0.530	2024/12/11	18#

		QPSK(1,24)								
50%RB										
Front Side	26740/819	10M QPSK(25,24)	0.258	0.158	3.1	23.61	24.00	0.282	2024/12/11	
Back Side	26740/819	10M QPSK(25,24)	0.245	0.151	2.41	23.61	24.00	0.268	2024/12/11	

NOTE: Body-Worn SAR test results of LTE Band 26a

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	26740/819	10M QPSK(1,24)	0.510	0.286	1.42	24.46	25.00	0.578	2024/12/11	
Back Side	26740/819	10M QPSK(1,24)	0.468	0.262	-3.20	24.46	25.00	0.530	2024/12/11	18#
Left Side	26740/819	10M QPSK(1,24)	0.100	0.054	-2.34	24.46	25.00	0.113	2024/12/11	
Right Side	26740/819	10M QPSK(1,24)	0.392	0.208	-1.93	24.46	25.00	0.444	2024/12/11	
Bottom Side	26740/819	10M QPSK(1,24)	0.591	0.336	-0.06	24.46	25.00	0.669	2024/12/11	
50%RB										
Front Side	26740/819	10M QPSK(25,24)	0.258	0.158	3.1	23.61	24.00	0.282	2024/12/11	
Back Side	26740/819	10M QPSK(25,24)	0.245	0.151	2.41	23.61	24.00	0.268	2024/12/11	
Left Side	26740/819	10M QPSK(25,24)	0.05	0.028	1.56	23.61	24.00	0.055	2024/12/11	
Right Side	26740/819	10M QPSK(25,24)	0.215	0.106	-1.88	23.61	24.00	0.235	2024/12/11	
Bottom Side	26740/819	10M QPSK(25,24)	0.305	0.181	2.25	23.61	24.00	0.334	2024/12/11	

NOTE: Hotspot SAR test results of LTE Band 26a

10.1.14. SAR measurement Result of LTE Band 26b

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	26865/831.5	15M QPSK(1,37)	0.275	0.216	-0.82	24.75	25.00	0.291	2024/11/26	17#
Left Tilt 15 Degree	26865/831.5	15M QPSK(1,37)	0.155	0.121	1.28	24.75	25.00	0.164	2024/11/26	
Right Cheek	26865/831.5	15M QPSK(1,37)	0.266	0.199	1.48	24.75	25.00	0.282	2024/11/26	
Right Tilt 15 Degree	26865/831.5	15M QPSK(1,37)	0.149	0.115	-1.11	24.75	25.00	0.158	2024/11/26	
50%RB										
Left Cheek	26865/831.5	15M QPSK(36,0)	0.141	0.115	4.32	23.74	24.00	0.150	2024/11/26	
Left Tilt 15 Degree	26865/831.5	15M QPSK(36,0)	0.081	0.072	2.72	23.74	24.00	0.086	2024/11/26	
Right Cheek	26865/831.5	15M QPSK(36,0)	0.146	0.114	1.55	23.74	24.00	0.155	2024/11/26	
Right Tilt 15 Degree	26865/831.5	15M QPSK(36,0)	0.085	0.069	-1.65	23.74	24.00	0.090	2024/11/26	

NOTE: Head SAR test results of LTE Band 26b

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	26865/831.5	15M QPSK(1,37)	0.530	0.283	-3.33	24.75	25.00	0.561	2024/11/26	
Back Side	26865/831.5	15M QPSK(1,37)	0.489	0.275	1.00	24.75	25.00	0.518	2024/11/26	18#
50%RB										
Front Side	26865/831.5	15M QPSK(36,0)	0.307	0.165	-2.94	23.74	24.00	0.326	2024/11/26	

NOTE: Body-Worn SAR test results of LTE Band 26b

NOTE: Hotspot SAR test results of LTE Band 26b

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g	Date	Plot
			1-g	10-g						

								(W/Kg)		
1RB										
Left Cheek	132322/1745	20M QPSK(1,49)	0.079	0.050	0.85	23.39	23.50	0.081	2024/12/06	17#
Left Tilt 15 Degree	132322/1745	20M QPSK(1,49)	0.042	0.027	2.32	23.39	23.50	0.043	2024/12/06	
Right Cheek	132322/1745	20M QPSK(1,49)	0.068	0.041	0.80	23.39	23.50	0.070	2024/12/06	
Right Tilt 15 Degree	132322/1745	20M QPSK(1,49)	0.033	0.020	-3.55	23.39	23.50	0.034	2024/12/06	
50%RB										
Left Cheek	132322/1745	20M QPSK(50,0)	0.047	0.026	3.72	22.46	22.50	0.047	2024/12/06	
Left Tilt 15 Degree	132322/1745	20M QPSK(50,0)	0.021	0.014	3.14	22.46	22.50	0.021	2024/12/06	
Right Cheek	132322/1745	20M QPSK(50,0)	0.039	0.023	-0.64	22.46	22.50	0.039	2024/12/06	
Right Tilt 15 Degree	132322/1745	20M QPSK(50,0)	0.017	0.012	-3.49	22.46	22.50	0.017	2024/12/06	

NOTE: Head SAR test results of LTE Band 66

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	132322/1745	20M QPSK(1,49)	0.027	0.017	3.67	23.39	23.50	0.028	2024/12/06	
Back Side	132322/1745	20M QPSK(1,49)	0.089	0.059	-0.11	23.39	23.50	0.091	2024/12/06	18#
50%RB										
Front Side	132322/1745	20M QPSK(50,0)	0.014	0.009	-0.58	22.46	22.50	0.014	2024/12/06	
Back Side	132322/1745	20M QPSK(50,0)	0.049	0.03	4.58	22.46	22.50	0.049	2024/12/06	

NOTE: Body-Worn SAR test results of LTE Band 66

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			(W/kg)							
			1-g	10-g						
1RB										
Front Side	132322/1745	20M QPSK(1,49)	0.027	0.017	3.67	23.39	23.50	0.028	2024/12/06	
Back Side	132322/1745	20M QPSK(1,49)	0.089	0.059	-0.11	23.39	23.50	0.091	2024/12/06	18#
Left Side	132322/1745	20M QPSK(1,49)	0.052	0.034	-0.52	23.39	23.50	0.053	2024/12/06	
Right Side	132322/1745	20M QPSK(1,49)	0.010	0.008	-1.60	23.39	23.50	0.010	2024/12/06	
Top Side	132322/1745	20M QPSK(1,49)	0.045	0.030	-1.35	23.39	23.50	0.046	2024/12/06	
50%RB										
Front Side	132322/1745	20M QPSK(50,0)	0.014	0.009	-0.58	22.46	22.50	0.014	2024/12/06	
Back Side	132322/1745	20M QPSK(50,0)	0.049	0.03	4.58	22.46	22.50	0.049	2024/12/06	
Left Side	132322/1745	20M QPSK(50,0)	0.029	0.019	-1.36	22.46	22.50	0.029	2024/12/06	
Right Side	132322/1745	20M QPSK(50,0)	0.006	0.004	4.93	22.46	22.50	0.006	2024/12/06	
Top Side	132322/1745	20M QPSK(50,0)	0.025	0.015	1.38	22.46	22.50	0.025	2024/12/06	

NOTE: Hotspot SAR test results of LTE Band 66

10.1.16. SAR measurement Result of NR 78

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	636666/3549.99	30k, DFT QPSK 100M Edge_1RB_Left	0.230	0.180	-1.22	23.07	23.50	0.254	2024/11/23	17#

Left Tilt 15 Degree	636666/3549.99	30k, DFT QPSK 100M Edge_1RB_Left	0.135	0.106	0.06	23.07	23.50	0.149	2024/11/23	
Right Cheek	636666/3549.99	30k, DFT QPSK 100M Edge_1RB_Left	0.222	0.173	-2.33	23.07	23.50	0.245	2024/11/23	
Right Tilt 15 Degree	636666/3549.99	30k, DFT QPSK 100M Edge_1RB_Left	0.119	0.093	0.52	23.07	23.50	0.131	2024/11/23	
50%RB										
Left Cheek	636666/3549.99	30k, DFT QPSK 100M Inner_Full	0.125	0.091	1.02	22.40	22.50	0.128	2024/11/23	
Left Tilt 15 Degree	636666/3549.99	30k, DFT QPSK 100M Inner_Full	0.077	0.054	-4.05	22.40	22.50	0.079	2024/11/23	
Right Cheek	636666/3549.99	30k, DFT QPSK 100M Inner_Full	0.114	0.095	-2.36	22.40	22.50	0.117	2024/11/23	
Right Tilt 15 Degree	636666/3549.99	30k, DFT QPSK 100M Inner_Full	0.06	0.051	-4.76	22.40	22.50	0.061	2024/11/23	

NOTE: Head SAR test results of NR n78

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	636666/3549.99	30k, DFT QPSK 100M Edge_1RB_Left	0.324	0.230	2.74	23.07	23.50	0.358	2024/11/23	
Back Side	636666/3549.99	30k, DFT QPSK 100M Edge_1RB_Left	0.325	0.243	2.00	23.07	23.50	0.359	2024/11/23	18#
50%RB										
Front Side	636666/3549.99	30k, DFT QPSK 100M Inner_Full	0.179	0.132	2.03	22.40	22.50	0.183	2024/11/23	
Back Side	636666/3549.99	30k, DFT	0.187	0.134	-4.86	22.40	22.50	0.191	2024/11/23	

		QPSK 100M								
		Inner_Full								

NOTE: Body-Worn SAR test results of NR n78

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	636666/3549.99	30k, DFT QPSK 100M Edge_1RB_Left	0.324	0.230	2.74	23.07	23.50	0.358	2024/11/23	
Back Side	636666/3549.99	30k, DFT QPSK 100M Edge_1RB_Left	0.325	0.243	2.00	23.07	23.50	0.359	2024/11/23	36#
Left Side	636666/3549.99	30k, DFT QPSK 100M Edge_1RB_Left	0.082	0.059	3.91	23.07	23.50	0.091	2024/11/23	
Right Side	636666/3549.99	30k, DFT QPSK 100M Edge_1RB_Left	0.264	0.193	0.26	23.07	23.50	0.291	2024/11/23	
Bottom Side	636666/3549.99	30k, DFT QPSK 100M Edge_1RB_Left	0.512	0.290	-1.18	23.07	23.50	0.565	2024/11/23	
50%RB										
Front Side	636666/3549.99	30k, DFT QPSK 100M Inner_Full	0.179	0.132	2.03	22.40	22.50	0.183	2024/11/23	
Back Side	636666/3549.99	30k, DFT QPSK 100M Inner_Full	0.187	0.134	-4.86	22.40	22.50	0.191	2024/11/23	
Left Side	636666/3549.99	30k, DFT QPSK 100M Inner_Full	0.043	0.035	4.07	22.40	22.50	0.044	2024/11/23	
Right Side	636666/3549.99	30k, DFT QPSK 100M Inner_Full	0.137	0.104	4.78	22.40	22.50	0.140	2024/11/23	
Bottom	636666/3549.99	30k, DFT	0.265	0.172	4.74	22.40	22.50	0.271	2024/11/23	

Side		QPSK 100M								
		Inner_Full								

NOTE: Hotspot SAR test results of NR n78

10.1.17. SAR measurement Result of WLAN2.4G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	1/2412	802.11b	0.288	0.132	-0.13	15.83	16.00	0.299	2024/11/18	9#
Left Tilt 15 Degree	1/2412	802.11b	0.152	0.067	-2.47	15.83	16.00	0.158	2024/11/18	
Right Cheek	1/2412	802.11b	0.090	0.046	-0.30	15.83	16.00	0.094	2024/11/18	
Right Tilt 15 Degree	1/2412	802.11b	0.049	0.024	-0.66	15.83	16.00	0.051	2024/11/18	

NOTE: Head SAR test results of WLAN2.4G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	1/2412	802.11b	0.057	0.034	-0.21	15.83	16.00	0.059	2024/11/18	
Back Side	1/2412	802.11b	0.062	0.037	2.93	15.83	16.00	0.064	2024/11/18	10#

NOTE: Body-worn SAR test results of WLAN2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	1/2412	802.11b	0.057	0.034	-0.21	15.83	16.00	0.059	2024/11/18	
Back Side	1/2412	802.11b	0.062	0.037	2.93	15.83	16.00	0.064	2024/11/18	10#
Right Side	1/2412	802.11b	0.027	0.019	-0.05	15.83	16.00	0.028	2024/11/18	
Top Side	1/2412	802.11b	0.030	0.021	-4.61	15.83	16.00	0.031	2024/11/18	

Front Side	1/2412	802.11b	0.057	0.034	-0.21	15.83	16.00	0.059	2024/11/18	
------------	--------	---------	-------	-------	-------	-------	-------	-------	------------	--

NOTE: Hotspot SAR test results of WLAN2.4G

Test Position of Hotspot with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
			1RB							
Back Side	6/2437	802.11b	0.182	0.091	-1.62	14.87	16.00	0.118	2024/11/18	#40

NOTE: Extremity SAR test results of WLAN2.4G

10.1.18. SAR measurement Result of WLAN5.2G

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	40/5200	802.11a	0.170	0.097	-4.72	11.84	12.00	0.176	2024/11/19	13#
Left Tilt 15 Degree	40/5200	802.11a	0.098	0.055	-0.97	11.84	12.00	0.102	2024/11/19	
Right Cheek	40/5200	802.11a	0.082	0.043	0.32	11.84	12.00	0.085	2024/11/19	
Right Tilt 15 Degree	40/5200	802.11a	0.050	0.024	-3.01	11.84	12.00	0.052	2024/11/19	

NOTE: Head SAR test results of WLAN5.2G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	40/5200	802.11a	0.065	0.042	3.00	11.84	12.00	0.067	2024/11/19	
Back Side	40/5200	802.11a	0.111	0.073	-3.81	11.84	12.00	0.115	2024/11/19	15#

NOTE: Body-worn SAR test results of WLAN5.2G

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	40/5200	802.11a	0.065	0.042	3.00	11.84	12.00	0.067	2024/11/19	
Back Side	40/5200	802.11a	0.111	0.073	-3.81	11.84	12.00	0.115	2024/11/19	15#
Right Side	40/5200	802.11a	0.061	0.040	-0.49	11.84	12.00	0.063	2024/11/19	
Top Side	40/5200	802.11a	0.098	0.063	2.27	11.84	12.00	0.102	2024/11/19	

NOTE: Hotspot SAR test results of WLAN5.2G

Test Position of Hotspot with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Back Side	40/5200	802.11a	0.312	0.106	-2.51	11.84	12.00	0.110	2024/11/19	#41

NOTE: Extremity SAR test results of WLAN5.2G

10.1.19. SAR measurement Result of WLAN5.8G

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	151/5755	802.11a	0.516	0.183	-1.75	9.42	9.50	0.526	2024/11/30	14#
Left Tilt 15 Degree	151/5755	802.11a	0.268	0.091	2.50	9.42	9.50	0.273	2024/11/30	
Right	151/5755	802.11a	0.100	0.059	-2.43	9.42	9.50	0.102	2024/11/30	

Cheek										
Right Tilt 15 Degree	151/5755	802.11a	0.051	0.020	2.48	9.42	9.50	0.052	2024/11/30	

NOTE: Head SAR test results of WLAN5.8G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	151/5755	802.11a	0.125	0.063	1.72	9.42	9.50	0.127	2024/11/30	
Back Side	151/5755	802.11a	0.210	0.112	2.46	9.42	9.50	0.214	2024/11/30	16#

NOTE: Body-worn SAR test results of WLAN5.8G

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	151/5755	802.11a	0.125	0.063	1.72	9.42	9.50	0.127	2024/11/30	
Back Side	151/5755	802.11a	0.210	0.112	2.46	9.42	9.50	0.214	2024/11/30	16#
Right Side	151/5755	802.11a	0.113	0.059	0.20	9.42	9.50	0.115	2024/11/30	
Top Side	151/5755	802.11a	0.154	0.080	-0.82	9.42	9.50	0.157	2024/11/30	

NOTE: Hotspot SAR test results of WLAN5.8G

Test Position of Hotspot with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Back Side	157/5785	802.11ax VHT20	0.586	0.193	-1.62	8.41	9.50	0.248	2024/11/30	#42

10.2. Simultaneous Transmission Analysis

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation $< 1.6\text{W/kg}$.
- 2) $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DTS			
Head	Left Cheek	0.392	0.299	0.691	N/A	N/A
	Left Tilt 15 Degree	0.220	0.158	0.378	N/A	N/A
	Right Cheek	0.658	0.094	0.752	N/A	N/A
	Right Tilt 15 Degree	0.331	0.051	0.382	N/A	N/A
Body-Worn	Front Side	0.578	0.059	0.637	N/A	N/A
	Back Side	1.298	0.064	1.362	N/A	N/A
Hotspot	Front Side	0.578	0.059	0.637	N/A	N/A
	Back Side	1.298	0.064	1.362	N/A	N/A
	Left Side	0.235	N/A	0.235	N/A	N/A
	Right Side	0.451	0.028	0.479	N/A	N/A
	Top Side	0.982	0.031	1.013	N/A	N/A
	Bottom Side	1.007	N/A	1.007	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	NII			
Head	Left Cheek	0.392	0.533	0.925	N/A	N/A
	Left Tilt 15 Degree	0.220	0.273	0.493	N/A	N/A
	Right Cheek	0.658	0.102	0.76	N/A	N/A

	Right Tilt 15 Degree	0.331	0.052	0.383	N/A	N/A
Body-Worn	Front Side	0.578	0.127	0.705	N/A	N/A
	Back Side	1.298	0.217	1.515	N/A	N/A
Hotspot	Front Side	0.578	0.127	0.705	N/A	N/A
	Back Side	1.298	0.217	1.515	N/A	N/A
	Left Side	0.235	N/A	0.235	N/A	N/A
	Right Side	0.451	0.115	0.566	N/A	N/A
	Top Side	0.982	0.157	1.139	N/A	N/A
	Bottom Side	1.007	N/A	1.007	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DSS			
Head	Left Cheek	0.392	0.105	0.497	N/A	N/A
	Left Tilt 15 Degree	0.220	0.105	0.325	N/A	N/A
	Right Cheek	0.658	0.105	0.763	N/A	N/A
	Right Tilt 15 Degree	0.331	0.105	0.436	N/A	N/A
Body-Worn	Front Side	0.578	0.053	0.631	N/A	N/A
	Back Side	1.298	0.053	1.351	N/A	N/A
Hotspot	Front Side	0.578	0.053	0.631	N/A	N/A
	Back Side	1.298	0.053	1.351	N/A	N/A
	Left Side	0.235	N/A	0.235	N/A	N/A
	Right Side	0.451	0.053	0.504	N/A	N/A
	Top Side	0.982	0.053	1.035	N/A	N/A
	Bottom Side	1.007	N/A	1.007	N/A	N/A

NSA

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band2+NR n78	WIFI/BT			
Head	Left Cheek	0.413	0.526	0.939	N/A	N/A

	Left Tilt 15 Degree	0.231	0.273	0.504	N/A	N/A
	Right Cheek	0.392	0.102	0.494	N/A	N/A
	Right Tilt 15 Degree	0.206	0.052	0.258	N/A	N/A
Body-Worn	Front Side	0.449	0.127	0.576	N/A	N/A
	Back Side	0.652	0.214	0.866	N/A	N/A
Hotspot	Front Side	0.449	0.127	0.576	N/A	N/A
	Back Side	0.652	0.214	0.866	N/A	N/A
	Left Side	0.212	N/A	0.212	N/A	N/A
	Right Side	0.322	0.115	0.437	N/A	N/A
	Top Side	0.137	0.157	0.294	N/A	N/A
	Bottom Side	0.565	N/A	0.565	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 10-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DTS			
Extremity	Back Side	1.459	0.118	2.319	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 10-g SAR (W/Kg)	SPLSR	Remark
		WWAN	NII			
Extremity	Back Side	1.459	0.248	2.319	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 10-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DSS			
Extremity	Back Side	1.459	0.042	2.319	N/A	N/A

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - 750MHz
MEASUREMENT 2 System Performance Check - 835MHz
MEASUREMENT 3 System Performance Check - 835MHz
MEASUREMENT 4 System Performance Check - 1800MHz
MEASUREMENT 5 System Performance Check - 1800MHz
MEASUREMENT 6 System Performance Check - 1900MHz
MEASUREMENT 7 System Performance Check - 1900MHz
MEASUREMENT 8 System Performance Check - 2450MHz
MEASUREMENT 9 System Performance Check - 2600MHz
MEASUREMENT 10 System Performance Check - 3500MHz
MEASUREMENT 11 System Performance Check - 5200MHz
MEASUREMENT 12 System Performance Check - 5800MHz

MEASUREMENT 1


Date of measurement: 27/11/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.42</u>

B. SAR Measurement Results



Frequency (MHz)	750.000000
Relative permittivity (real part)	40.869524
Relative permittivity (imaginary part)	21.646004
Conductivity (S/m)	0.901917
Variation (%)	0.310000



Maximum location: X=3.00, Y=2.00

SAR Peak: 0.74 W/kg

SAR 10g (W/Kg)	0.366575
SAR 1g (W/Kg)	0.543400



MEASUREMENT 2

Date of measurement: 26/11/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.34</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	41.934568
Relative permittivity (imaginary part)	19.710231
Conductivity (S/m)	0.914336
Variation (%)	-0.150000

SURFACE SAR





VOLUME SAR



Maximum location: X=2.00, Y=2.00

SAR Peak: 0.80 W/kg

SAR 10g (W/Kg)	0.375675
SAR 1g (W/Kg)	0.574430



MEASUREMENT 3

Date of measurement: 11/12/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.34</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	41.827047
Relative permittivity (imaginary part)	19.592773
Conductivity (S/m)	0.908887
Variation (%)	-0.250000

SURFACE SAR





VOLUME SAR



Maximum location: X=2.00, Y=2.00

SAR Peak: 0.84 W/kg

SAR 10g (W/Kg)	0.383559
SAR 1g (W/Kg)	0.595418



MEASUREMENT 4


Date of measurement: 21/11/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.51</u>

B. SAR Measurement Results



Frequency (MHz)	1800.000000
Relative permittivity (real part)	39.077704
Relative permittivity (imaginary part)	13.865005
Conductivity (S/m)	1.386501
Variation (%)	-0.110000



Maximum location: X=2.00, Y=2.00

SAR Peak: 3.95 W/kg

SAR 10g (W/Kg)	1.231630
SAR 1g (W/Kg)	2.380187



MEASUREMENT 5


Date of measurement: 6/12/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.51</u>

B. SAR Measurement Results



Frequency (MHz)	1800.000000
Relative permittivity (real part)	38.970183
Relative permittivity (imaginary part)	13.747547
Conductivity (S/m)	1.374755
Variation (%)	-1.030000



Maximum location: X=2.00, Y=2.00

SAR Peak: 3.77 W/kg

SAR 10g (W/Kg)	1.175927
SAR 1g (W/Kg)	2.272606



MEASUREMENT 6

Date of measurement: 24/11/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.57</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	38.328712
Relative permittivity (imaginary part)	13.679631
Conductivity (S/m)	1.443961
Variation (%)	-0.190000

SURFACE SAR




VOLUME SAR




Maximum location: X=1.00, Y=0.00

SAR Peak: 4.16 W/kg


SAR 10g (W/Kg)	1.230521
SAR 1g (W/Kg)	2.509710



3D screen shot



Hot spot position



MEASUREMENT 7

Date of measurement: 9/12/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.57</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	38.457178
Relative permittivity (imaginary part)	13.792131
Conductivity (S/m)	1.455836
Variation (%)	-0.210000

SURFACE SAR




VOLUME SAR




Maximum location: X=0.00, Y=0.00

SAR Peak: 3.97 W/kg


SAR 10g (W/Kg)	1.181231
SAR 1g (W/Kg)	2.396499



3D screen shot



Hot spot position



MEASUREMENT 8


Date of measurement: 18/11/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.74</u>

B. SAR Measurement Results



Frequency (MHz)	2450.000000
Relative permittivity (real part)	37.962009
Relative permittivity (imaginary part)	13.205487
Conductivity (S/m)	1.797414
Variation (%)	-0.130000



Maximum location: X=-1.00, Y=0.00

SAR Peak: 6.57 W/kg

SAR 10g (W/Kg)	1.404082
SAR 1g (W/Kg)	3.347366



MEASUREMENT 9

Date of measurement: 25/11/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.51</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	38.878441
Relative permittivity (imaginary part)	13.731472
Conductivity (S/m)	1.983435
Variation (%)	-0.680000

SURFACE SAR





VOLUME SAR



Maximum location: X=-2.00, Y=0.00

SAR Peak: 11.17 W/kg

SAR 10g (W/Kg)	2.367676
SAR 1g (W/Kg)	5.709248



MEASUREMENT 10

Date of measurement: 26/11/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7, dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW3500</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.20</u>


B. SAR Measurement Results

Frequency (MHz)	3500.000000
Relative permittivity (real part)	38.014514
Relative permittivity (imaginary part)	14.574846
Conductivity (S/m)	2.833998
Variation (%)	-1.130000

SURFACE SAR





VOLUME SAR



Maximum location: X=-1.00, Y=2.00

SAR Peak: 9.07 W/kg

SAR 10g (W/Kg)	2.339256
SAR 1g (W/Kg)	7.000485



MEASUREMENT 11

Date of measurement: 19/11/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5200</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.89</u>


B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	34.612485
Relative permittivity (imaginary part)	15.678512
Conductivity (S/m)	4.529348
Variation (%)	-1.780000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=-1.00

SAR Peak: 28.22 W/kg

SAR 10g (W/Kg)	3.355712
SAR 1g (W/Kg)	9.746747



MEASUREMENT 12


Date of measurement: 30/11/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.90</u>

B. SAR Measurement Results



Frequency (MHz)	5800.000000
Relative permittivity (real part)	34.030204
Relative permittivity (imaginary part)	16.052683
Conductivity (S/m)	5.172531
Variation (%)	-0.760000



Maximum location: X=1.00, Y=-1.00

SAR Peak: 57.73 W/kg

SAR 10g (W/Kg)	6.542945
SAR 1g (W/Kg)	19.246353



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Head
MEASUREMENT 2 GSM 850 Body
MEASUREMENT 3 GSM 1900 Head
MEASUREMENT 4 GSM 1900 Body
MEASUREMENT 5 WCDMA Band 2 Head
MEASUREMENT 6 WCDMA Band 2 Body
MEASUREMENT 7 WCDMA Band 4 Head
MEASUREMENT 8 WCDMA Band 4 Body
MEASUREMENT 9 WCDMA Band 5 Head
MEASUREMENT 10 WCDMA Band 5 Body
MEASUREMENT 11 WLAN 5.2G Head
MEASUREMENT 12 WLAN 5.8G Head
MEASUREMENT 13 WLAN 5.8G Body
MEASUREMENT 14 WLAN 5.2G Body
MEASUREMENT 15 WLAN 2.4G Head
MEASUREMENT 16 WLAN 2.4G Body
MEASUREMENT 17 LTE Band 2 Head
MEASUREMENT 18 LTE Band 2 Body
MEASUREMENT 19 LTE Band 4 Head
MEASUREMENT 20 LTE Band 4 Body
MEASUREMENT 21 LTE Band 5 Head
MEASUREMENT 22 LTE Band 5 Body
MEASUREMENT 23 LTE Band 7 Head
MEASUREMENT 24 LTE Band 7 Body
MEASUREMENT 25 LTE Band 12 Head
MEASUREMENT 26 LTE Band 12 Body
MEASUREMENT 27 LTE Band 17 Head
MEASUREMENT 28 LTE Band 17 Body
MEASUREMENT 29 LTE Band 25 Head
MEASUREMENT 30 LTE Band 25 Body
MEASUREMENT 31 LTE Band 26a Head
MEASUREMENT 32 LTE Band 26a Body
MEASUREMENT 33 LTE Band 26b Head
MEASUREMENT 34 LTE Band 26b Body
MEASUREMENT 35 LTE Band 66 Head
MEASUREMENT 36 LTE Band 66 Body

MEASUREMENT 37 LTE Band SA n78Head

MEASUREMENT 38 LTE Band SA n78 Body

MEASUREMENT 39 LTE Band 7 Extremity

MEASUREMENT 40 WLAN 2.4G Extremity

MEASUREMENT 41 WLAN 5.2G Extremity

MEASUREMENT 42 WLAN 5.8G Extremity

MEASUREMENT 1

Date of measurement: 26/11/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 8.0)</u>
<u>ConvF</u>	<u>2.34</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	41.850227
Relative permittivity (imaginary part)	19.736071
Conductivity (S/m)	0.917069
Variation (%)	0.560000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-25.00

SAR Peak: 0.38 W/kg

SAR 10g (W/Kg)	0.233720
SAR 1g (W/Kg)	0.305082



MEASUREMENT 2


Date of measurement: 26/11/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 8.0)</u>
<u>ConvF</u>	<u>2.34</u>

B. SAR Measurement Results



Frequency (MHz)	836.400000
Relative permittivity (real part)	41.850227
Relative permittivity (imaginary part)	19.736071
Conductivity (S/m)	0.917069
Variation (%)	2.600000



Maximum location: X=2.00, Y=-10.00

SAR Peak: 1.04 W/kg

SAR 10g (W/Kg)	0.365218
SAR 1g (W/Kg)	0.657477



MEASUREMENT 3


Date of measurement: 24/11/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 8.0)</u>
<u>ConvF</u>	<u>2.57</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.415112
Relative permittivity (imaginary part)	13.697431
Conductivity (S/m)	1.430621
Variation (%)	0.140000



Maximum location: X=-21.00, Y=-35.00

SAR Peak: 0.20 W/kg

SAR 10g (W/Kg)	0.081104
SAR 1g (W/Kg)	0.140140



MEASUREMENT 4


Date of measurement: 24/11/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 8.0)</u>
<u>ConvF</u>	<u>2.57</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.415112
Relative permittivity (imaginary part)	13.697431
Conductivity (S/m)	1.430621
Variation (%)	-0.870000



Maximum location: X=18.00, Y=48.00

SAR Peak: 0.36 W/kg

SAR 10g (W/Kg)	0.114555
SAR 1g (W/Kg)	0.217957



MEASUREMENT 5


Date of measurement: 24/11/2024

A. Experimental conditions.

Area Scan	dx=15mm dy=15mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Left head
Device Position	Cheek
Band	Band2 WCDMA1900
Channels	Middle
Signal	WCDMA (Crest factor: 1.0)
ConvF	2.57

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.415112
Relative permittivity (imaginary part)	13.697431
Conductivity (S/m)	1.430621
Variation (%)	4.240000



Maximum location: X=-6.00, Y=-6.00

SAR Peak: 0.23 W/kg

SAR 10g (W/Kg)	0.091912
SAR 1g (W/Kg)	0.152522



MEASUREMENT 6


Date of measurement: 24/11/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.57</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.415112
Relative permittivity (imaginary part)	13.697431
Conductivity (S/m)	1.430621
Variation (%)	0.710000



Maximum location: X=20.00, Y=48.00

SAR Peak: 0.46 W/kg

SAR 10g (W/Kg)	0.146500
SAR 1g (W/Kg)	0.280523



MEASUREMENT 7


Date of measurement: 21/11/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.51</u>

B. SAR Measurement Results



Frequency (MHz)	1732.600000
Relative permittivity (real part)	39.537403
Relative permittivity (imaginary part)	13.817305
Conductivity (S/m)	1.329532
Variation (%)	-0.550000



Maximum location: X=-8.00, Y=5.00

SAR Peak: 0.08 W/kg

SAR 10g (W/Kg)	0.038599
SAR 1g (W/Kg)	0.058034



MEASUREMENT 8


Date of measurement: 21/11/2024

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>Band4 WCDMA1700</u>
Channels	<u>Middle</u>
Signal	<u>WCDMA (Crest factor: 1.0)</u>
ConvF	<u>2.51</u>

B. SAR Measurement Results



Frequency (MHz)	1732.600000
Relative permittivity (real part)	39.537403
Relative permittivity (imaginary part)	13.817305
Conductivity (S/m)	1.329532
Variation (%)	-1.410000



Maximum location: X=-21.00, Y=20.00

SAR Peak: 0.17 W/kg

SAR 10g (W/Kg)	0.062678
SAR 1g (W/Kg)	0.102712



MEASUREMENT 9


Date of measurement: 26/11/2024

A. Experimental conditions.

Area Scan	dx=15mm dy=15mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Left head
Device Position	Cheek
Band	Band5 WCDMA850
Channels	Middle
Signal	WCDMA (Crest factor: 1.0)
ConvF	2.34

B. SAR Measurement Results



Frequency (MHz)	836.400000
Relative permittivity (real part)	41.850227
Relative permittivity (imaginary part)	19.736071
Conductivity (S/m)	0.917069
Variation (%)	-0.150000



Maximum location: X=-51.00, Y=-23.00

SAR Peak: 0.23 W/kg

SAR 10g (W/Kg)	0.146752
SAR 1g (W/Kg)	0.188067



MEASUREMENT 10


Date of measurement: 26/11/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.34</u>

B. SAR Measurement Results



Frequency (MHz)	836.400000
Relative permittivity (real part)	41.850227
Relative permittivity (imaginary part)	19.736071
Conductivity (S/m)	0.917069
Variation (%)	-0.510000



Maximum location: X=1.00, Y=-11.00

SAR Peak: 0.68 W/kg

SAR 10g (W/Kg)	0.238795
SAR 1g (W/Kg)	0.429354



MEASUREMENT 11


Date of measurement: 19/11/2024

A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>IEEE 802.11a U-NII</u>
Channels	<u>Middle</u>
Signal	<u>IEEE802.11a (Crest factor: 1.0)</u>
ConvF	<u>1.89</u>

B. SAR Measurement Results



Frequency (MHz)	5200.000000
Relative permittivity (real part)	34.612484
Relative permittivity (imaginary part)	15.678512
Conductivity (S/m)	4.529348
Variation (%)	-4.720000



Maximum location: X=-5.00, Y=5.00

SAR Peak: 0.40 W/kg

SAR 10g (W/Kg)	0.097208
SAR 1g (W/Kg)	0.169684



MEASUREMENT 12


Date of measurement: 30/11/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11ax U-NII</u>
<u>Channels</u>	<u>Low</u>
<u>Signal</u>	<u>IEEE802.11ax (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.90</u>

B. SAR Measurement Results

Frequency (MHz)	5745.000000
Relative permittivity (real part)	34.206982
Relative permittivity (imaginary part)	16.034456
Conductivity (S/m)	5.126572
Variation (%)	-1.750000



Maximum location: X=-35.00, Y=23.00

SAR Peak: 1.70 W/kg

SAR 10g (W/Kg)	0.183003
SAR 1g (W/Kg)	0.515795