

TEST REPORT

Report No.: BCTC2506730956-5E

Applicant: SHENZHEN YUNJI INTELLIGENT TECHNOLOGY
CO.,LTD

Product Name: Smart Phone

Test Model: C68 Plus

Tested Date: 2025-06-27 to 2025-08-19

Issued Date: 2025-08-20

Shenzhen BCTC Testing Co., Ltd.



FCC ID: 2ANMU-C68PLUS

Product Name: Smart Phone

Trademark: OUKITEL

Model/Type reference: C68 Plus
C68 Pro, C68 GT, C68, C68 S, C68 E, C68 Ultra, C68 MAX

Prepared For: SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD

Address: A2 2F BUILDING ENET NEW INDUSTRIAL PARK, DAFU INDUSTRIAL ZONE,
GUANLAN, LONGHUA SHENZHEN, China

Manufacturer: SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD

Address: A2 2F BUILDING ENET NEW INDUSTRIAL PARK, DAFU INDUSTRIAL ZONE,
GUANLAN, LONGHUA SHENZHEN, China

Prepared By: Shenzhen BCTC Testing Co., Ltd.

Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road,
Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Sample Received Date: 2025-06-27

Sample tested Date: 2025-06-27 to 2025-08-19

Issue Date: 2025-08-20


Report No.: BCTC2506730956-5E

Test Standards: FCC CFR Title 47 Part 2
FCC CFR Title 47 Part22 Subpart H
FCC CFR Title 47 Part24 Subpart E
FCC CFR Title 47 Part27 Subpart L
ANSI/TIA-603-E-2016; [1] or • ANSI/TIA-102.CAAA-E-2016; [1] or • ANSI
C63.26-2015
FCC KDB 971168 D01 Power Meas. License Digital Systems v03v01

Test Results: PASS

Remark: This is GSM & WCDMAradio test report.

Tested by:



Brave Zeng/ Project Handler

Approved by:



Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table Of Content

Test Report Declaration	Page
1. Version	4
2. Test Summary	5
3. Measurement Uncertainty	6
4. Product Information And Test Setup	7
4.1 Product Information	7
4.2 Test Setup Configuration	8
4.3 Support Equipment	8
4.5 Test Mode	9
5. Test Facility And Test Instrument Used	10
5.1 Test Facility	10
5.2 Test Instrument Used	10
6. RF Output Power	12
6.1 Block Diagram Of Test Setup	12
6.2 Limit	13
6.3 Test procedure	14
6.4 Test Result	14
7. Peak-to-average Ratio(PAR) of Transmitter	23
7.1 Block Diagram Of Test Setup	23
7.2 Limit	23
7.3 Test procedure	23
7.4 Test Result	24
8. Emission Bandwidth	40
8.1 Block Diagram Of Test Setup	40
8.2 Limit	40
8.3 Test procedure	40
8.4 Test Result	41
9. Out of Band Emissions at Antenna Terminal	57
9.1 Block Diagram Of Test Setup	57
9.2 Limit	57
9.3 Test procedure	57
9.4 Test Result	57
10. Spurious Radiated Emissions	76
10.1 Block Diagram Of Test Setup	76
10.2 Limit	77
10.3 Test procedure	77
10.4 Test Result	78
11. Frequency Stability	81
11.1 Block Diagram Of Test Setup	81
11.2 Limit	81
11.3 Test procedure	81
11.4 Test Result	82
12. EUT Photographs	85
13. EUT Test Setup Photographs	86

(Note: N/A Means Not Applicable)


1. Version

Report No.	Issue Date	Description	Approved
BCTC2506730956-5E	2025-08-20	Original	Valid

2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No.	Results
1	RF Exposure	§1.1307, §2.1093	PASS
2	RF Output Power	§22.913 (a), §24.232 (c), §27.50, §2.1046	PASS
3	Peak-to-average Ratio(PAR) of Transmitter	§24.232(d), §22.913, §27.50, §2.1046	PASS
4	Emission Bandwidth	§22.917 (b), §24.238(b), §27.53, §2.1049	PASS
5	Spurious Emissions at Antenna Terminal	§22.917 (a), §24.238 (a), §27.53, §2.1051	PASS
6	Spurious Radiation Emissions	§22.917 (a), §24.238 (a), §27.53, §2.1051	PASS
7	Out of Band Emissions	§22.917 (a), §24.238 (a), §27.53, §2.1051	PASS
8	Frequency Stability	§22.355, §24.235, §27.54, §2.1055	PASS



3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
2	3m chamber Radiated spurious emission(9KHz-30MHz)	U=3.7dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
5	Conducted Emission (150kHz-30MHz)	U=3.20dB
6	Conducted Adjacent channel power	U=1.38dB
7	Conducted output power uncertainty Above 1G	U=1.576dB
8	Conducted output power uncertainty below 1G	U=1.28dB
9	humidity uncertainty	U=5.3%
10	Temperature uncertainty	U=0.59°C

4. Product Information And Test Setup

4.1 Product Information

Model/Type reference:	C68 Plus C68 Pro, C68 GT, C68, C68 S, C68 E, C68 Ultra, C68 MAX
Model differences:	All the model are the same circuit and RF module, except model names.
Hardware Version:	J574_9230ED4FUM11_C20V
Software Version:	OUKITELE_C68_Plus_EEA_NFC_V06_20250814
Operation Frequency:	GSM/GPRS/EGPRS 850: TX: 824~849MHz; RX: 869~894MHz; GSM/GPRS/EGPRS 1900: TX:1850~1910MHz; RX:1930~1990MHz; WCDMA Band II: TX: 1852.40~1907.60MHz; Rx: 1932.60~1987.40MHz; WCDMA Band IV: TX: 1712.40~1752.60MHz; RX: 2112.60 – 2452.40MHz; WCDMA Band V: TX: 826.40~846.60MHz; RX: 871.40~ 891.60MHz;
GPRS Class:	Class 12
Max RF Output Power:	GSM/GPRS/EGPRS 850: 33.74 dBm, GSM/GPRS/EGPRS 1900: 29.33 dBm WCDMA Band II: 22.26 dBm WCDMA Band IV: 22.55 dBm WCDMA Band V: 24.16 dBm
Type of Modulation:	GSM with GMSK Modulation WCDMA Mode with BPSK Modulation HSDPA Mode with QPSK, 16QAM Modulation HSUPA Mode with QPSK, 16QAM Modulation
Type of Emission:	GSM/GPRS 850: 245KGXW EGPRS 850:244KG7W GSM/GPRS 1900: 250KGXW EGPRS 1900:252KG7W WCDMA Band II: 4M17F9W WCDMA Band IV: 4M17F9W WCDMA Band V: 4M19F9W
Antenna installation:	Internal antenna
Antenna Gain:	GSM850: -1.05 dBi GSM1900: -0.93 dBi WCDMA Band II: -0.93 dBi WCDMA Band IV: 1.15 dBi WCDMA Band V: -1.05 dBi Remark: ☐ The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information. ☒ The antenna gain of the product is provided by the customer, and the test data is affected by the customer information.
Connecting I/O Port(s)	Please refer to the User's Manual
Ratings:	DC 9V from adapter/DC 3.93V from battery
Adapter Information:	Model: HJ-PD18W-US Input: 100-240V~50/60Hz 0.6A Output: DC 5.0V 3.0A 15.0W OR DC 9.0V 2.0A 18.0W OR DC 12.0V 1.5A 18.0W MAX

4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.

4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Smart Phone	OUKITEL	C68 Plus	N/A	EUT
E-2	Adapter	/	HJ-PD18W-US	N/A	Auxiliary
E-3	TF card	SanDisk	32G	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C-1	N/A	N/A	0M	DC cable unshielded

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.5 Test Mode

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
GSM 850	GSM/GPRS/EGPRS	824.2 MHz	128
		836.6 MHz	190
		848.8 MHz	251
PCS 1900	GSM/GPRS/EGPRS	1850.2 MHz	512
		1880.0 MHz	661
		1909.8 MHz	810
WCDMA Band II	RMC/HSDPA/ HSUPA	1852.4 MHz	9262
		1880.0 MHz	9400
		1907.6 MHz	9538
WCDMA Band IV	RMC/HSDPA/ HSUPA	1712.4 MHz	1312
		1740 MHz	1450
		1752.6 MHz	1513
WCDMA Band V	RMC/HSDPA/ HSUPA	826.4 MHz	4132
		836.4 MHz	4182
		846.6 MHz	4233
Note 1: the transmitter has been tested on the communications mode of WCDMA, HSDPA, HSUPA compliance test and record the worst case. Note 2: Both the SIM 1 and SIM 2 were tested, the worst mode is the SIM 1, the data recording in the report.			

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/ Without Core
/	/	/	/
/	/	/	/

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
/	/	/	/

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/ Without Core
/	/	/	/

5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address:1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

A2LA certificate registration number is: CN1212


ISED Registered No.: 23583

ISED CAB identifier: CN0017

5.2 Test Instrument Used

RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power meter	Keysight	E4419	\	May 14, 2025	May 13, 2026
Power Sensor (AV)	Keysight	E9300A	\	May 14, 2025	May 13, 2026
Signal Analyzer20kHz-26.5GHz	Keysight	N9020A	MY49100060	May 14, 2025	May 13, 2026
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	100363	May 14, 2025	May 13, 2026
Communication test set	R&S	CMW500	126173	May 14, 2025	May 13, 2026
Radio frequency control box	MAIWEI	MW200-RFCB	\	\	\
Software	MAIWEI	MTS 8200	\	\	\


Radiated Emissions Test (966 Chamber02)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	SKET	966 Room	966	Oct. 31. 2024	Oct. 30. 2027
Receiver	R&S	ESR3	102075	May 14, 2025	May 13, 2026
Receiver	R&S	ESR317	100010	May 14, 2025	May 13, 2026
Amplifier	SKET	LNPA-30M01G-30	SK2021082004	May 14, 2025	May 13, 2026
TRILOG Broadband Antenna	Schwarzbeck	VULB9168	1323	May 24, 2025	May 23, 2026
Loop Antenna(9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	May 24, 2025	May 23, 2026
Amplifier	SKET	LAPA_01G18 G-45dB	SK2021040901	May 14, 2025	May 13, 2026
Horn Antenna	Schwarzbeck	BBHA9120D	1541	May 24, 2025	May 23, 2026
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35-HG	2034381	May 14, 2025	May 13, 2026
Horn Antenna(18G Hz-40GHz)	Schwarzbeck	BBHA9170	00822	May 24, 2025	May 23, 2026
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	\	May 14, 2025	May 13, 2026
Communication test set	R&S	CMW500	126173	Nov. 11. 2024	Nov. 10, 2025
Software	Frad	EZ-EMC	FA-03A2 RE	\	\



6. RF Output Power


6.1 Block Diagram Of Test Setup

Conducted output power test method:




Radiated power test method:

(A) Test site-up for radiated ERP and/or EIRP measurements



(B) Substitution method set-up for radiated emission



6.2 Limit

According to §22.913(a)(2), The ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to §24.232 (c), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §27.50(d)(4), Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

6.3 Test procedure

Radiated power test method:

1. The setup of EUT is according with per ANSI/TIA-603-E-2016 and ANSI C63.26-2015 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

6.4 Test Result

ERP For GSM Mode GSM850

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 22H Limits (dBm)	Result
Low Channel						
824.2	H	54.05	-26.29	27.76	38.45	PASS
824.2	V	54.14	-26.29	27.85	38.45	PASS
Middle Channel						
836.6	H	53.66	-26.35	27.31	38.45	PASS
836.6	V	53.11	-26.35	26.76	38.45	PASS
High Channel						
848.8	H	54.25	-26.42	27.83	38.45	PASS
848.8	V	54.12	-26.42	27.70	38.45	PASS

EIRP For GSM Mode PCS1900

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel						
1850.2	H	54.86	-26.93	27.93	33.00	PASS
1850.2	V	54.72	-26.93	27.79	33.00	PASS
Middle Channel						
1880	H	54.13	-26.86	27.27	33.00	PASS
1880	V	54.05	-26.86	27.19	33.00	PASS
High Channel						
1909.8	H	54.26	-26.80	27.46	33.00	PASS
1909.8	V	53.93	-26.80	27.13	33.00	PASS

ERP For GPRS Mode GSM850

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 22H Limits (dBm)	Result
Low Channel						
824.2	H	53.52	-26.29	27.23	38.45	PASS
824.2	V	53.22	-26.29	26.93	38.45	PASS
Middle Channel						
836.6	H	53.70	-26.35	27.35	38.45	PASS
836.6	V	53.79	-26.35	27.44	38.45	PASS
High Channel						
848.8	H	54.36	-26.42	27.94	38.45	PASS
848.8	V	54.13	-26.42	27.71	38.45	PASS

EIRP For GPRS Mode PCS1900

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel						
1850.2	H	54.33	-26.93	27.40	33.00	PASS
1850.2	V	54.39	-26.93	27.46	33.00	PASS
Middle Channel						
1880	H	54.53	-26.86	27.67	33.00	PASS
1880	V	53.84	-26.86	26.98	33.00	PASS
High Channel						
1909.8	H	54.32	-26.80	27.52	33.00	PASS
1909.8	V	53.97	-26.80	27.17	33.00	PASS

Note: All modes have been tested and only the worst mode is represented, with the worst data being Subtest1.

ERP For EGPRS Mode GSM850

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 22H Limits (dBm)	Result
Low Channel						
824.2	H	53.76	-26.29	27.47	38.45	PASS
824.2	V	53.37	-26.29	27.08	38.45	PASS
Middle Channel						
836.6	H	53.36	-26.35	27.01	38.45	PASS
836.6	V	53.01	-26.35	26.66	38.45	PASS
High Channel						
848.8	H	53.78	-26.42	27.36	38.45	PASS
848.8	V	53.90	-26.42	27.48	38.45	PASS

EIRP For EGPRS Mode PCS1900

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel						
1850.2	H	54.41	-26.93	27.48	33.00	PASS
1850.2	V	54.08	-26.93	27.15	33.00	PASS
Middle Channel						
1880	H	54.25	-26.86	27.39	33.00	PASS
1880	V	54.37	-26.86	27.51	33.00	PASS
High Channel						
1909.8	H	54.47	-26.80	27.67	33.00	PASS
1909.8	V	54.39	-26.80	27.59	33.00	PASS

Note: All modes have been tested and only the worst mode is represented, with the worst data being Subtest1.

EIRP For RMC 12.2Kbps Mode Band II

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel						
1852.4	H	50.23	-26.92	23.31	33.00	PASS
1852.4	V	48.89	-26.92	21.97	33.00	PASS
Middle Channel						
1880	H	49.52	-26.86	22.66	33.00	PASS
1880	V	48.52	-26.86	21.66	33.00	PASS
High Channel						
1907.6	H	48.79	-26.80	21.99	33.00	PASS
1907.6	V	48.63	-26.80	21.83	33.00	PASS

EIRP For HSDPA Mode Band II

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel						
1852.4	H	49.35	-26.92	22.43	33.00	PASS
1852.4	V	49.14	-26.92	22.22	33.00	PASS
Middle Channel						
1880	H	49.70	-26.86	22.84	33.00	PASS
1880	V	48.74	-26.86	21.88	33.00	PASS
High Channel						
1907.6	H	48.56	-26.80	21.76	33.00	PASS
1907.6	V	48.72	-26.80	21.92	33.00	PASS

EIRP For HSUPA Mode Band II

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel						
1852.4	H	50.16	-26.92	23.24	33.00	PASS
1852.4	V	49.24	-26.92	22.32	33.00	PASS
Middle Channel						
1880	H	48.74	-26.86	21.88	33.00	PASS
1880	V	49.17	-26.86	22.31	33.00	PASS
High Channel						
1907.6	H	49.55	-26.80	22.75	33.00	PASS
1907.6	V	48.77	-26.80	21.97	33.00	PASS

Note: The worst mode of HSDPA and HSUPA is Subtest1.

EIRP For RMC 12.2Kbps Mode Band IV

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 27L Limits (dBm)	Result
Low Channel						
1712.4	H	48.91	-27.23	21.68	33.00	PASS
1712.4	V	49.06	-27.23	21.83	33.00	PASS
Middle Channel						
1740	H	49.71	-27.19	22.52	33.00	PASS
1740	V	49.34	-27.19	22.15	33.00	PASS
High Channel						
1752.6	H	49.32	-27.14	22.18	33.00	PASS
1752.6	V	49.21	-27.14	22.07	33.00	PASS

EIRP For HSDPA Mode Band IV

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 27L Limits (dBm)	Result
Low Channel						
1712.4	H	48.25	-27.23	21.02	33.00	PASS
1712.4	V	47.57	-27.23	20.34	33.00	PASS
Middle Channel						
1740	H	48.92	-27.19	21.73	33.00	PASS
1740	V	48.10	-27.19	20.91	33.00	PASS
High Channel						
1752.6	H	48.05	-27.14	20.91	33.00	PASS
1752.6	V	47.72	-27.14	20.58	33.00	PASS

EIRP For HSUPA Mode Band IV

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 27L Limits (dBm)	Result
Low Channel						
1712.4	H	49.99	-27.23	22.76	33.00	PASS
1712.4	V	48.41	-27.23	21.18	33.00	PASS
Middle Channel						
1740	H	50.07	-27.19	22.88	33.00	PASS
1740	V	48.98	-27.19	21.79	33.00	PASS
High Channel						
1752.6	H	48.86	-27.14	21.72	33.00	PASS
1752.6	V	48.81	-27.14	21.67	33.00	PASS

Note: The worst mode of HSDPA and HSUPA is Subtest1.

ERP For RMC 12.2Kbps Mode Band V

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 22H Limits (dBm)	Result
Low Channel						
826.4	H	49.58	-26.29	23.29	38.45	PASS
826.4	V	48.80	-26.29	22.51	38.45	PASS
Middle Channel						
836.4	H	48.91	-26.35	22.56	38.45	PASS
836.4	V	48.98	-26.35	22.63	38.45	PASS
High Channel						
846.6	H	49.51	-26.42	23.09	38.45	PASS
846.6	V	48.67	-26.42	22.25	38.45	PASS

ERP For HSDPA Mode Band V

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 22H Limits (dBm)	Result
Low Channel						
826.4	H	50.25	-26.29	23.96	38.45	PASS
826.4	V	48.63	-26.29	22.34	38.45	PASS
Middle Channel						
836.4	H	48.35	-26.35	22.00	38.45	PASS
836.4	V	48.96	-26.35	22.61	38.45	PASS
High Channel						
846.6	H	50.10	-26.42	23.68	38.45	PASS
846.6	V	48.52	-26.42	22.10	38.45	PASS

ERP For HSUPA Mode Band V

Frequency (MHz)	Polar (H/V)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 22H Limits (dBm)	Result
Low Channel						
826.4	H	49.33	-26.29	23.04	38.45	PASS
826.4	V	48.50	-26.29	22.21	38.45	PASS
Middle Channel						
836.4	H	50.29	-26.35	23.94	38.45	PASS
836.4	V	48.77	-26.35	22.42	38.45	PASS
High Channel						
846.6	H	48.91	-26.42	22.49	38.45	PASS
846.6	V	48.59	-26.42	22.17	38.45	PASS

Note: The worst mode of HSDPA and HSUPA is Subtest1.

Max. Conducted Output Power

For Cellular Band (GSM850)

Band	GSM850		
Channel	128	190	251
Frequency(MHz)	824.2	836.6	848.8
GSM	33.74	33.60	33.42
GPRS Subtest-1	33.25	33.65	33.47
GPRS Subtest-2	31.56	31.69	31.43
GPRS Subtest-3	29.73	29.92	29.62
GPRS Subtest-4	27.73	27.93	27.65
EGPRS Subtest-1	25.79	26.9	26.17
EGPRS Subtest-2	25.57	26.04	25.37
EGPRS Subtest-3	22.82	23.36	22.94
EGPRS Subtest-4	21.22	21.16	21.1


For PCS Band (GSM1900)

Band	GSM1900		
Channel	512	661	810
Frequency(MHz)	1850.2	1880	1909.8
GSM	28.65	28.89	29.22
GPRS Slot -1	28.79	28.99	29.33
GPRS Slot -2	26.51	26.69	26.97
GPRS Slot -3	24.97	25.17	25.46
GPRS Slot -4	23.03	23.22	23.53
EGPRS Slot -1	25.33	25.25	25.81
EGPRS Slot -2	23.93	24.06	24.22
EGPRS Slot -3	22.2	21.93	22.47
EGPRS Slot -4	19.37	19.58	20.51

Band	WCDMA Band II		
Channel	9262	9400	9538
Frequency(MHz)	1852.4	1880.0	1907.6
WCDMA RMC 12.2K	21.34	21.90	22.26
HSDPA Subtest-1	21.57	21.55	21.52
HSDPA Subtest-2	21.24	21.34	21.24
HSDPA Subtest-3	21.10	21.12	21.08
HSDPA Subtest-4	20.56	20.79	20.93
HSUPA Subtest-1	21.54	21.36	21.40
HSUPA Subtest-2	21.49	21.56	21.55
HSUPA Subtest-3	21.13	20.97	21.21
HSUPA Subtest-4	21.41	21.57	21.52
HSUPA Subtest-5	21.18	21.31	21.32


Band	WCDMA Band IV		
Channel	1312	1450	1513
Frequency(MHz)	1712.4	1740	1752.6
WCDMA RMC 12.2K	22.51	22.18	22.22
HSDPA Subtest-1	22.55	21.86	22.07
HSDPA Subtest-2	22.29	21.60	21.69
HSDPA Subtest-3	21.78	21.39	21.49
HSDPA Subtest-4	21.94	21.20	21.21
HSUPA Subtest-1	22.45	21.66	22.08
HSUPA Subtest-2	22.50	21.84	22.07
HSUPA Subtest-3	21.87	21.49	21.77
HSUPA Subtest-4	22.52	21.81	22.10
HSUPA Subtest-5	22.14	21.31	21.79

Band	WCDMA Band V		
Channel	4132	4182	4233
Frequency(MHz)	826.4	836.4	846.6
WCDMA RMC 12.2K	24.16	23.85	23.97
HSDPA Subtest-1	23.46	23.21	23.76
HSDPA Subtest-2	23.22	22.93	23.45
HSDPA Subtest-3	22.88	22.48	22.88
HSDPA Subtest-4	23.07	22.64	22.91
HSUPA Subtest-1	23.41	23.05	23.72
HSUPA Subtest-2	23.42	23.19	23.69
HSUPA Subtest-3	23.27	23.25	23.61
HSUPA Subtest-4	23.42	23.22	23.71
HSUPA Subtest-5	23.10	22.80	23.48



7. Peak-to-average Ratio(PAR) of Transmitter

7.1 Block Diagram Of Test Setup



7.2 Limit

According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

According to §27.50(B), the peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.


According to §22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.


7.3 Test procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded. Record the maximum PAPR level associated with a probability of 0.1%.


7.4 Test Result

Band	Channel	Frequency (MHz)	Result (dB)	high Limit (dB)	Verdict
GSM850	128	824.2	2.65	13.00	PASS
GSM850	190	836.6	2.63	13.00	PASS
GSM850	251	848.8	2.62	13.00	PASS
GSM1900	512	1850.2	2.69	13.00	PASS
GSM1900	661	1880	2.67	13.00	PASS
GSM1900	810	1909.8	2.67	13.00	PASS
GPRS850	128	824.2	2.68	13.00	PASS
GPRS850	190	836.6	2.68	13.00	PASS
GPRS850	251	848.8	2.65	13.00	PASS
GPRS1900	512	1850.2	2.73	13.00	PASS
GPRS1900	661	1880	2.71	13.00	PASS
GPRS1900	810	1909.8	2.70	13.00	PASS
EGPRS850	128	824.2	9.14	13.00	PASS
EGPRS850	190	836.6	9.62	13.00	PASS
EGPRS850	251	848.8	9.87	13.00	PASS
EGPRS1900	512	1850.2	6.14	13.00	PASS
EGPRS1900	661	1880	6.19	13.00	PASS
EGPRS1900	810	1909.8	6.21	13.00	PASS







GSM850 Channel=128 NVNT




GSM850 Channel=190 NVNT




GSM850 Channel=251 NVNT




GSM1900 Channel=512 NVNT




GSM1900 Channel=661 NVNT




GSM1900 Channel=810 NVNT




GPRS850 Channel=128 NVNT




GPRS850 Channel=190 NVNT




GPRS850 Channel=251 NVNT




GPRS1900 Channel=512 NVNT




GPRS1900 Channel=661 NVNT




GPRS1900 Channel=810 NVNT




EGPRS850 Channel=128 NVNT




EGPRS850 Channel=190 NVNT




EGPRS850 Channel=251 NVNT



EGPRS1900 Channel=512 NVNT




EGPRS1900 Channel=661 NVNT




EGPRS1900 Channel=810 NVNT


Band	Channel	Frequency (MHz)	Result (dB)	high Limit (dB)	Verdict
WCDMA Band2	9262	1852.4	3.12	13	PASS
WCDMA Band2	9400	1880	2.99	13	PASS
WCDMA Band2	9538	1907.6	3.05	13	PASS
WCDMA Band4	1312	1712.4	2.97	13	PASS
WCDMA Band4	1450	1740	2.75	13	PASS
WCDMA Band4	1513	1752.6	3.08	13	PASS
WCDMA Band5	4132	826.4	3.05	13	PASS
WCDMA Band5	4182	836.4	3.02	13	PASS
WCDMA Band5	4233	846.6	2.61	13	PASS

Note: In WCDMA, RMC, HSDPA and HSUPA all three tests only reflect the worst mode RMC.







WCDMA Band2 Channel=9262 NVNT




WCDMA Band2 Channel=9400 NVNT




WCDMA Band2 Channel=9538 NVNT




WCDMA Band4 Channel=1312 NVNT




WCDMA Band4 Channel=1450 NVNT




WCDMA Band4 Channel=1513 NVNT



WCDMA Band5 Channel=4132 NVNT




WCDMA Band5 Channel=4182 NVNT



8. Emission Bandwidth

8.1 Block Diagram Of Test Setup



8.2 Limit

According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


According to §27.53, The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


8.3 Test procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 10kHz for GSM mode and 100kHz for WCDMA mode, VBW shall be at least 3 times the RBW, and the 26dB bandwidth was recorded.


8.4 Test Result

Band	Channel	Frequency (MHz)	99% OBW (kHz)	-26dB EBW (kHz)	Verdict
GSM850	128	824.2	245.280	319.030	PASS
GSM850	190	836.6	243.020	313.480	PASS
GSM850	251	848.8	242.658	310.366	PASS
GSM1900	512	1850.2	249.864	314.258	PASS
GSM1900	661	1880	246.404	319.514	PASS
GSM1900	810	1909.8	246.936	314.073	PASS
GPRS850	128	824.2	240.748	314.402	PASS
GPRS850	190	836.6	243.467	316.567	PASS
GPRS850	251	848.8	240.848	301.924	PASS
GPRS1900	512	1850.2	242.418	318.749	PASS
GPRS1900	661	1880	244.542	321.182	PASS
GPRS1900	810	1909.8	243.076	324.525	PASS
EGPRS850	128	824.2	240.111	294.261	PASS
EGPRS850	190	836.6	243.787	300.981	PASS
EGPRS850	251	848.8	241.169	296.558	PASS
EGPRS1900	512	1850.2	251.728	306.409	PASS
EGPRS1900	661	1880	239.872	298.410	PASS
EGPRS1900	810	1909.8	245.027	304.275	PASS







GSM850 Channel=128 NVNT




GSM850 Channel=190 NVNT




GSM850 Channel=251 NVNT




GSM1900 Channel=512 NVNT




GSM1900 Channel=661 NVNT




GSM1900 Channel=810 NVNT




GPRS850 Channel=128 NVNT




GPRS850 Channel=190 NVNT




GPRS850 Channel=251 NVNT




GPRS1900 Channel=512 NVNT




GPRS1900 Channel=661 NVNT




GPRS1900 Channel=810 NVNT




EGPRS850 Channel=128 NVNT




EGPRS850 Channel=190 NVNT




EGPRS850 Channel=251 NVNT



EGPRS1900 Channel=512 NVNT




EGPRS1900 Channel=661 NVNT




EGPRS1900 Channel=810 NVNT


Band	Channel	Frequency (MHz)	99% OBW (kHz)	-26dB EBW (kHz)	Verdict
WCDMA Band2	9262	1852.4	4157.655	4633.341	PASS
WCDMA Band2	9400	1880	4165.004	4649.565	PASS
WCDMA Band2	9538	1907.6	4163.304	4662.918	PASS
WCDMA Band4	1312	1712.4	4152.306	4659.770	PASS
WCDMA Band4	1450	1740	4165.489	4691.260	PASS
WCDMA Band4	1513	1752.6	4165.013	4650.872	PASS
WCDMA Band5	4132	826.4	4155.090	4687.459	PASS
WCDMA Band5	4182	836.4	4138.558	4664.507	PASS
WCDMA Band5	4233	846.6	4189.545	4682.394	PASS

Note: In WCDMA, RMC, HSDPA and HSUPA all three tests only reflect the worst mode RMC.







WCDMA Band2 Channel=9262 NVNT




WCDMA Band2 Channel=9400 NVNT




WCDMA Band2 Channel=9538 NVNT




WCDMA Band4 Channel=1312 NVNT




WCDMA Band4 Channel=1450 NVNT





WCDMA Band4 Channel=1513 NVNT



WCDMA Band5 Channel=4132 NVNT




WCDMA Band5 Channel=4182 NVNT



9. Out of Band Emissions at Antenna Terminal

9.1 Block Diagram Of Test Setup



9.2 Limit

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.


9.3 Test procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100 kHz and 1 MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10th harmonic. At the edge of the authorized Frequency block/band: RBW set 1%-5%OBW.


9.4 Test Result




GSM850 Channel=128 NVNT




GSM850 Channel=251 NVNT




GSM1900 Channel=512 NVNT




GSM1900 Channel=810 NVNT




GSM850 Channel=128 NVNT



GSM850 Channel=190 NVNT



GSM850 Channel=251 NVNT



GSM1900 Channel=512 NVNT