

Tilt 15 Degree		QPSK(50,0)								
-------------------	--	------------	--	--	--	--	--	--	--	--

NOTE: Head SAR test results of LTE Band 38

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	38000/2595	20M QPSK(1,0)	0.156	0.073	1.52	23.58	24.00	0.172	2025/5/14	
Back Side	38000/2595	20M QPSK(1,0)	0.046	0.021	-2.95	23.58	24.00	0.051	2025/5/14	
50%RB										
Front Side	38000/2595	20M QPSK(50,0)	0.088	0.040	-3.10	22.92	23.50	0.101	2025/5/14	
Back Side	38000/2595	20M QPSK(50,0)	0.028	0.012	-2.06	22.92	23.50	0.032	2025/5/14	

NOTE: Body-Worn SAR test results of LTE Band 38

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	38000/2595	20M QPSK(1,0)	0.156	0.073	1.52	23.58	24.00	0.172	2025/5/14	
Back Side	38000/2595	20M QPSK(1,0)	0.046	0.021	-2.95	23.58	24.00	0.051	2025/5/14	
Left Side	38000/2595	20M QPSK(1,0)	0.024	0.011	3.38	23.58	24.00	0.026	2025/5/14	
Right Side	38000/2595	20M QPSK(1,0)	0.012	0.010	2.92	23.58	24.00	0.013	2025/5/14	
Bottom Side	38000/2595	20M QPSK(1,0)	0.213	0.099	-2.64	23.58	24.00	0.235	2025/5/14	36#
50%RB										
Front	38000/2595	20M	0.088	0.040	-3.10	22.92	23.50	0.101	2025/5/14	

Side		QPSK(50,0)								
Back Side	38000/2595	20M QPSK(50,0)	0.028	0.012	-2.06	22.92	23.50	0.032	2025/5/14	
Left Side	38000/2595	20M QPSK(50,0)	0.013	0.006	-3.96	22.92	23.50	0.015	2025/5/14	
Right Side	38000/2595	20M QPSK(50,0)	0.006	0.005	-1.16	22.92	23.50	0.007	2025/5/14	
Bottom Side	38000/2595	20M QPSK(50,0)	0.115	0.051	3.03	22.92	23.50	0.131	2025/5/14	

NOTE: Hotspot SAR test results of LTE Band 38

Tested by : Jack Peng

10.1.16. SAR measurement Result of LTE Band 41

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	40620/2593	20M QPSK(1,49)	0.024	0.014	2.85	23.61	24.50	0.029	2025/5/14	37#
Left Tilt 15 Degree	40620/2593	20M QPSK(1,49)	0.013	0.011	2.15	23.61	24.50	0.016	2025/5/14	
Right Cheek	40620/2593	20M QPSK(1,49)	0.021	0.012	3.21	23.61	24.50	0.026	2025/5/14	
Right Tilt 15 Degree	40620/2593	20M QPSK(1,49)	0.010	0.008	-2.09	23.61	24.50	0.012	2025/5/14	
50%RB										
Left Cheek	40620/2593	20M QPSK(50,0)	0.014	0.008	-2.15	22.76	23.50	0.017	2025/5/14	
Left Tilt 15 Degree	40620/2593	20M QPSK(50,0)	0.007	0.006	-0.19	22.76	23.50	0.008	2025/5/14	
Right Cheek	40620/2593	20M QPSK(50,0)	0.011	0.006	4.52	22.76	23.50	0.013	2025/5/14	
Right Tilt 15 Degree	40620/2593	20M QPSK(50,0)	0.005	0.004	2.87	22.76	23.50	0.006	2025/5/14	

NOTE: Head SAR test results of LTE Band 41

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	40620/2593	20M QPSK(1,49)	0.132	0.061	1.42	23.61	24.50	0.162	2025/5/14	
Back Side	40620/2593	20M QPSK(1,49)	0.052	0.024	3.71	23.61	24.50	0.064	2025/5/14	
50%RB										
Front Side	40620/2593	20M QPSK(50,0)	0.072	0.031	0.52	22.76	23.50	0.085	2025/5/14	
Back Side	40620/2593	20M QPSK(50,0)	0.028	0.012	-1.61	22.76	23.50	0.033	2025/5/14	

NOTE: Body-Worn SAR test results of LTE Band 41

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	40620/2593	20M QPSK(1,49)	0.132	0.061	1.42	23.61	24.50	0.162	2025/5/14	
Back Side	40620/2593	20M QPSK(1,49)	0.052	0.024	3.71	23.61	24.50	0.064	2025/5/14	
Left Side	40620/2593	20M QPSK(1,49)	0.025	0.011	-3.42	23.61	24.50	0.031	2025/5/14	
Right Side	40620/2593	20M QPSK(1,49)	0.012	0.010	-1.13	23.61	24.50	0.015	2025/5/14	
Bottom Side	40620/2593	20M QPSK(1,49)	0.212	0.098	-2.45	23.61	24.50	0.260	2025/5/14	38#
50%RB										
Front Side	40620/2593	20M QPSK(50,0)	0.072	0.031	0.52	22.76	23.50	0.085	2025/5/14	
Back Side	40620/2593	20M QPSK(50,0)	0.028	0.012	-1.61	22.76	23.50	0.033	2025/5/14	

Left Side	40620/2593	20M QPSK(50,0)	0.015	0.006	4.40	22.76	23.50	0.018	2025/5/14	
Right Side	40620/2593	20M QPSK(50,0)	0.006	0.006	-0.94	22.76	23.50	0.007	2025/5/14	
Bottom Side	40620/2593	20M QPSK(50,0)	0.117	0.052	1.08	22.76	23.50	0.139	2025/5/14	

NOTE: Hotspot SAR test results of LTE Band 41

Tested by : Jack Peng

10.1.17. SAR measurement Result of LTE Band 66

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	132322/1745	20M QPSK(1,99)	0.147	0.093	-0.08	23.26	23.50	0.155	2025/5/11	39#
Left Tilt 15 Degree	132322/1745	20M QPSK(1,99)	0.081	0.051	0.22	23.26	23.50	0.086	2025/5/11	
Right Cheek	132322/1745	20M QPSK(1,99)	0.139	0.084	0.43	23.26	23.50	0.147	2025/5/11	
Right Tilt 15 Degree	132322/1745	20M QPSK(1,99)	0.074	0.046	1.03	23.26	23.50	0.078	2025/5/11	
50%RB										
Left Cheek	132322/1745	20M QPSK(50,49)	0.082	0.051	-1.41	22.58	23.00	0.090	2025/5/11	
Left Tilt 15 Degree	132322/1745	20M QPSK(50,49)	0.041	0.028	-3.03	22.58	23.00	0.045	2025/5/11	
Right Cheek	132322/1745	20M QPSK(50,49)	0.072	0.048	-3.41	22.58	23.00	0.079	2025/5/11	
Right Tilt 15 Degree	132322/1745	20M QPSK(50,49)	0.041	0.027	-1.66	22.58	23.00	0.045	2025/5/11	

NOTE: Head SAR test results of LTE Band 66

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	132322/1745	20M QPSK(1,99)	0.150	0.080	1.32	23.26	23.50	0.159	2025/5/11	
Back Side	132322/1745	20M QPSK(1,99)	0.126	0.069	1.59	23.26	23.50	0.133	2025/5/11	
50%RB										
Front Side	132322/1745	20M QPSK(50,49)	0.077	0.048	4.97	22.58	23.00	0.085	2025/5/11	
Back Side	132322/1745	20M QPSK(50,49)	0.075	0.039	1.91	22.58	23.00	0.083	2025/5/11	

NOTE: Body-Worn SAR test results of LTE Band 66

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	132322/1745	20M QPSK(1,99)	0.150	0.080	1.32	23.26	23.50	0.159	2025/5/11	
Back Side	132322/1745	20M QPSK(1,99)	0.126	0.069	1.59	23.26	23.50	0.133	2025/5/11	
Left Side	132322/1745	20M QPSK(1,99)	0.120	0.065	2.84	23.26	23.50	0.127	2025/5/11	
Right Side	132322/1745	20M QPSK(1,99)	0.038	0.021	-3.60	23.26	23.50	0.040	2025/5/11	
Bottom Side	132322/1745	20M QPSK(1,99)	0.209	0.115	-0.50	23.26	23.50	0.221	2025/5/11	40#
50%RB										
Front Side	132322/1745	20M QPSK(50,49)	0.077	0.048	4.97	22.58	23.00	0.085	2025/5/11	
Back Side	132322/1745	20M QPSK(50,49)	0.075	0.039	1.91	22.58	23.00	0.083	2025/5/11	
Left Side	132322/1745	20M	0.068	0.036	1.49	22.58	23.00	0.075	2025/5/11	

		QPSK(50,49)								
Right Side	132322/1745	20M QPSK(50,49)	0.023	0.011	-0.57	22.58	23.00	0.025	2025/5/11	
Bottom Side	132322/1745	20M QPSK(50,49)	0.125	0.061	-3.46	22.58	23.00	0.138	2025/5/11	

NOTE: Hotspot SAR test results of LTE Band 66

Tested by : Jack Peng

10.1.18. SAR measurement Result of WLAN2.4G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	6/2437	802.11b	0.618	0.293	-1.25	14.89	15.00	0.634	2025/5/16	15#
Left Tilt 15 Degree	6/2437	802.11b	0.345	0.157	0.17	14.89	15.00	0.354	2025/5/16	
Right Cheek	6/2437	802.11b	0.566	0.266	-0.84	14.89	15.00	0.581	2025/5/16	
Right Tilt 15 Degree	6/2437	802.11b	0.281	0.128	2.08	14.89	15.00	0.288	2025/5/16	

NOTE: Head SAR test results of WLAN 2.4G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	6/2437	802.11b	0.120	0.060	-0.26	14.89	15.00	0.123	2025/5/16	16#
Back Side	6/2437	802.11b	0.105	0.050	1.47	14.89	15.00	0.108	2025/5/16	

NOTE: Body-worn SAR test results of WLAN 2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						

Front Side	6/2437	802.11b	0.120	0.060	-0.26	14.89	15.00	0.123	2025/5/16	16#
Back Side	6/2437	802.11b	0.105	0.050	1.47	14.89	15.00	0.108	2025/5/16	
Right Side	6/2437	802.11b	0.085	0.044	0.06	14.89	15.00	0.087	2025/5/16	
Top Side	6/2437	802.11b	0.080	0.039	3.53	14.89	15.00	0.082	2025/5/16	

NOTE: Hotspot SAR test results of WLAN2.4G

Tested by : Max Zhou

10.1.19. SAR measurement Result of WLAN5.2G

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	40/5200	802.11a	0.307	0.100	1.62	9.76	10.50	0.364	2025/5/06	11#
Left Tilt 15 Degree	40/5200	802.11a	0.167	0.052	3.76	9.76	10.50	0.198	2025/5/06	
Right Cheek	40/5200	802.11a	0.278	0.086	0.81	9.76	10.50	0.330	2025/5/06	
Right Tilt 15 Degree	40/5200	802.11a	0.128	0.041	0.26	9.76	10.50	0.152	2025/5/06	

NOTE: Head SAR test results of WLAN5.2G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	40/5200	802.11a	0.035	0.016	-3.73	9.76	10.50	0.042	2025/5/06	
Back Side	40/5200	802.11a	0.056	0.025	1.16	9.76	10.50	0.066	2025/5/06	

NOTE: Body-worn SAR test results of WLAN5.2G

Test Position of Hotspot	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						

with 10mm										
Front Side	40/5200	802.11a	0.035	0.016	-3.73	9.76	10.50	0.042	2025/5/06	
Back Side	40/5200	802.11a	0.056	0.025	1.16	9.76	10.50	0.066	2025/5/06	
Right Side	40/5200	802.11a	0.095	0.043	-2.37	9.76	10.50	0.113	2025/5/06	12#
Top Side	40/5200	802.11a	0.035	0.015	-1.10	9.76	10.50	0.042	2025/5/06	

NOTE: Hotspot SAR test results of WLAN5.2G

Tested by : Max Zhou

10.1.20. SAR measurement Result of WLAN5.8G

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	149/5745	802.11n HT20	0.314	0.098	4.37	9.89	10.50	0.361	2025/5/15	13#
Left Tilt 15 Degree	149/5745	802.11n HT20	0.169	0.051	3.84	9.89	10.50	0.194	2025/5/15	
Right Cheek	149/5745	802.11n HT20	0.274	0.081	0.72	9.89	10.50	0.315	2025/5/15	
Right Tilt 15 Degree	149/5745	802.11n HT20	0.150	0.047	3.05	9.89	10.50	0.173	2025/5/15	

NOTE: Head SAR test results of WLAN5.8G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	149/5745	802.11n HT20	0.048	0.020	-2.00	9.89	10.50	0.055	2025/5/15	
Back Side	149/5745	802.11n HT20	0.072	0.029	0.38	9.89	10.50	0.083	2025/5/15	

NOTE: Body-worn SAR test results of WLAN5.8G

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	149/5745	802.11n HT20	0.048	0.020	-2.00	9.89	10.50	0.055	2025/5/15	
Back Side	149/5745	802.11n HT20	0.072	0.029	0.38	9.89	10.50	0.083	2025/5/15	
Right Side	149/5745	802.11n HT20	0.168	0.070	-3.44	9.89	10.50	0.193	2025/5/15	14#
Top Side	149/5745	802.11n HT20	0.074	0.030	3.13	9.89	10.50	0.085	2025/5/15	

NOTE: Hotspot SAR test results of WLAN5.8G

Tested by : Max Zhou

10.2. Simultaneous Transmission Analysis

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- Scalar SAR summation < 1.6W/kg.
- $SPLSR = (SAR_1 + SAR_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DTS			
Head	Left Cheek	0.458	0.634	1.092	N/A	N/A
	Left Tilt 15 Degree	0.258	0.354	0.612	N/A	N/A
	Right Cheek	0.433	0.581	1.014	N/A	N/A
	Right Tilt 15 Degree	0.201	0.288	0.489	N/A	N/A
Body-Worn	Front Side	0.397	0.123	0.520	N/A	N/A
	Back Side	0.453	0.108	0.561	N/A	N/A

Hotspot	Front Side	0.397	0.123	0.520	N/A	N/A
	Back Side	0.453	0.108	0.561	N/A	N/A
	Left Side	0.223	N/A	0.223	N/A	N/A
	Right Side	0.255	0.087	0.342	N/A	N/A
	Top Side	N/A	0.082	0.082	N/A	N/A
	Bottom Side	0.406	N/A	0.406	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	NII			
Head	Left Cheek	0.458	0.364	0.822	N/A	N/A
	Left Tilt 15 Degree	0.258	0.198	0.456	N/A	N/A
	Right Cheek	0.433	0.330	0.763	N/A	N/A
	Right Tilt 15 Degree	0.201	0.173	0.374	N/A	N/A
Body-Worn	Front Side	0.397	0.055	0.452	N/A	N/A
	Back Side	0.453	0.083	0.536	N/A	N/A
Hotspot	Front Side	0.397	0.055	0.452	N/A	N/A
	Back Side	0.453	0.083	0.536	N/A	N/A
	Left Side	0.223	N/A	0.223	N/A	N/A
	Right Side	0.255	0.193	0.448	N/A	N/A
	Top Side	N/A	0.085	0.085	N/A	N/A
	Bottom Side	0.406	N/A	0.406	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DSS			
Head	Left Cheek	0.458	0.067	0.525	N/A	N/A
	Left Tilt 15 Degree	0.258	0.067	0.325	N/A	N/A
	Right Cheek	0.433	0.067	0.500	N/A	N/A

	Right Tilt 15 Degree	0.201	0.067	0.268	N/A	N/A
Body-Worn	Front Side	0.397	0.033	0.430	N/A	N/A
	Back Side	0.453	0.033	0.486	N/A	N/A
Hotspot	Front Side	0.397	0.033	0.430	N/A	N/A
	Back Side	0.453	0.033	0.486	N/A	N/A
	Left Side	0.223	N/A	0.223	N/A	N/A
	Right Side	0.255	0.033	0.288	N/A	N/A
	Top Side	N/A	0.033	0.033	N/A	N/A
	Bottom Side	0.406	N/A	0.406	N/A	N/A

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - 750MHz
MEASUREMENT 2 System Performance Check - 835MHz
MEASUREMENT 3 System Performance Check - 1800MHz
MEASUREMENT 4 System Performance Check - 1900MHz
MEASUREMENT 5 System Performance Check - 2450MHz
MEASUREMENT 6 System Performance Check - 2600MHz
MEASUREMENT 7 System Performance Check - 5200MHz
MEASUREMENT 8 System Performance Check - 5800MHz

1# System check at 750 MHz
Date of measurement: 9/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.39
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW750
Channels/Frequency	Middle
Signal	CW

B. Permittivity

Middle TX Frequency (MHz)	750.000
Relative permittivity (real part)	40.90
Relative permittivity (imaginary part)	21.38
Conductivity (S/m)	0.89

C. SAR Surface and Volume




Maximum location: X=3.00, Y=3.00 ; SAR Peak: 1.14 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.605
SAR 1g (W/Kg)	0.871
Variation (%)	-0.21
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	74.74

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.135	0.901	0.674	0.512	0.386	0.295	0.243



F. 3D Image



2# System check at 835 MHz

Date of measurement: 17/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Signal	CW
Channels/Frequency	Middle

B. Permittivity

Middle TX Frequency (MHz)	835.00
Relative permittivity (real part)	42.39
Relative permittivity (imaginary part)	20.04
Conductivity (S/m)	0.93

C. SAR Surface and Volume




Maximum location: X=5.00, Y=3.00 ; SAR Peak: 1.50 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.604
SAR 1g (W/Kg)	0.989
Variation (%)	0.07
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	64.47

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.471	1.024	0.660	0.446	0.302	0.224	0.151



F. 3D Image



3# System check at 1800 MHz

Date of measurement: 11/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.50
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Signal	CW
Channels/Frequency	Middle

B. Permittivity

Middle TX Frequency (MHz)	1800.00
Relative permittivity (real part)	38.73
Relative permittivity (imaginary part)	13.68
Conductivity (S/m)	1.37

C. SAR Surface and Volume




Maximum location: X=3.00, Y=2.00 ; SAR Peak: 6.80 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.019
SAR 1g (W/Kg)	4.000
Variation (%)	-0.23
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	54.71

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	6.709	4.211	2.304	1.318	0.773	0.461	0.278



F. 3D Image



4# System check at 1900 MHz
Date of measurement: 10/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Signal	CW
Channels/Frequency	Middle

B. Permittivity

Middle TX Frequency (MHz)	1900.00
Relative permittivity (real part)	38.43
Relative permittivity (imaginary part)	13.72
Conductivity (S/m)	1.45

C. SAR Surface and Volume




Maximum location: X=5.00, Y=2.00 ; SAR Peak: 6.66 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	1.971
SAR 1g (W/Kg)	4.004
Variation (%)	-0.05
Horizontal validation criteria: minimum distance (mm)	11.31
Vertical validation criteria: SAR ratio M2/M1 (%)	54.35

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	6.483	4.063	2.208	1.254	0.720	0.424	0.252



F. 3D Image



5# System check at 2450 MHz
Date of measurement: 16/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.63
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Signal	CW
Channels/Frequency	Middle

B. Permittivity

Middle TX Frequency (MHz)	2450.00
Relative permittivity (real part)	38.13
Relative permittivity (imaginary part)	13.21
Conductivity (S/m)	1.80

C. SAR Surface and Volume




Maximum location: X=5.00, Y=0.00 ; SAR Peak: 9.57 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.199
SAR 1g (W/Kg)	5.111
Variation (%)	-2.07
Horizontal validation criteria: minimum distance (mm)	10.00
Vertical validation criteria: SAR ratio M2/M1 (%)	48.05

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	9.244	5.367	2.579	1.298	0.686	0.359	0.194



F. 3D Image



6# System check at 2600 MHz
Date of measurement: 14/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.52
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Signal	CW
Channels/Frequency	Middle

B. Permittivity

Middle TX Frequency (MHz)	2600.00
Relative permittivity (real part)	39.33
Relative permittivity (imaginary part)	13.42
Conductivity (S/m)	1.94

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=1.00 ; SAR Peak: 10.99 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.494
SAR 1g (W/Kg)	5.903
Variation (%)	0.06
Horizontal validation criteria: minimum distance (mm)	10.00
Vertical validation criteria: SAR ratio M2/M1 (%)	49.17

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	10.725	6.348	3.121	1.504	0.768	0.377	0.186



F. 3D Image



7# System check at 5200 MHz

Date of measurement: 6/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.37
Area Scan	dx=10mm dy=10mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Signal	CW
Channels/Frequency	Middle

B. Permittivity

Middle TX Frequency (MHz)	5200.00
Relative permittivity (real part)	37.41
Relative permittivity (imaginary part)	15.83
Conductivity (S/m)	4.57

C. SAR Surface and Volume




Maximum location: X=0.00, Y=-2.00 ; SAR Peak: 4.68 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.538
SAR 1g (W/Kg)	1.584
Variation (%)	0.42
Horizontal validation criteria: minimum distance (mm)	11.31
Vertical validation criteria: SAR ratio M2/M1 (%)	54.80

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SAR (W/Kg)	4.37 4	2.71 0	1.48 5	0.84 2	0.46 5	0.24 7	0.14 1	0.07 4	0.04 8	0.02 4	0.04 3	0.03 0



F. 3D Image



8# System check at 5800 MHz
Date of measurement: 15/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.35
Area Scan	dx=10mm dy=10mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Signal	CW
Channels/Frequency	Middle

B. Permittivity

Middle TX Frequency (MHz)	5800.00
Relative permittivity (real part)	35.93
Relative permittivity (imaginary part)	15.84
Conductivity (S/m)	5.11

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 5.35 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.605
SAR 1g (W/Kg)	1.812
Variation (%)	-1.85
Horizontal validation criteria: minimum distance (mm)	8.94
Vertical validation criteria: SAR ratio M2/M1 (%)	54.81

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SAR (W/Kg)	4.98 7	3.08 4	1.69 0	0.95 9	0.52 4	0.28 3	0.15 6	0.06 7	0.03 7	0.02 5	0.00 7	0.01 2



F. 3D Image



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Head
MEASUREMENT 2 GSM 850 Body
MEASUREMENT 3 GSM 1900 Head
MEASUREMENT 4 GSM 1900 Body
MEASUREMENT 5 WCDMA Band 2 Head
MEASUREMENT 6 WCDMA Band 2 Body
MEASUREMENT 7 WCDMA Band 4 Head
MEASUREMENT 8 WCDMA Band 4 Body
MEASUREMENT 9 WCDMA Band 5 Head
MEASUREMENT 10 WCDMA Band 5 Body
MEASUREMENT 11 WLAN 5.2G Head
MEASUREMENT 12 WLAN 5.2G Body
MEASUREMENT 13 WLAN 5.8G Head
MEASUREMENT 14 WLAN 5.8G Body
MEASUREMENT 15 WLAN 2.4G Head
MEASUREMENT 16 WLAN 2.4G Body
MEASUREMENT 17 LTE Band 2 Head
MEASUREMENT 18 LTE Band 2 Body
MEASUREMENT 19 LTE Band 4 Head
MEASUREMENT 20 LTE Band 4 Body
MEASUREMENT 21 LTE Band 5 Head
MEASUREMENT 22 LTE Band 5 Body
MEASUREMENT 23 LTE Band 7 Head
MEASUREMENT 24 LTE Band 7 Body
MEASUREMENT 25 LTE Band 12 Head
MEASUREMENT 26 LTE Band 12 Body
MEASUREMENT 27 LTE Band 17 Head
MEASUREMENT 28 LTE Band 17 Body
MEASUREMENT 29 LTE Band 25 Head
MEASUREMENT 30 LTE Band 25 Body
MEASUREMENT 31 LTE Band 26a Head
MEASUREMENT 32 LTE Band 26a Body
MEASUREMENT 33 LTE Band 26b Head
MEASUREMENT 34 LTE Band 26b Body
MEASUREMENT 35 LTE Band 38 Head

MEASUREMENT 36 LTE Band 38 Body

MEASUREMENT 37 LTE Band 41 Head

MEASUREMENT 38 LTE Band 41 Body

MEASUREMENT 39 LTE Band 66 Head

MEASUREMENT 40 LTE Band 66 Body

1# SAR Measurement at GPRS850 (Cheek, Right)


Date of measurement: 17/5/2025

A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	GPRS850
Signal	TDMA (GPRS)
Channels/Frequency	Middle (189)/ frequency 836.40 Mhz
Modulation	GMSK (CS-4)
TX-slots	4

B. Permittivity

Middle TX Frequency (MHz)	836.40
Relative permittivity (real part)	42.31
Relative permittivity (imaginary part)	20.06
Conductivity (S/m)	0.93

C. SAR Surface and Volume


Maximum location: X=-41.00, Y=-36.00 ; SAR Peak: 0.28 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.160
SAR 1g (W/Kg)	0.214
Variation (%)	-1.93
Horizontal validation criteria: minimum distance (mm)	22.63
Vertical validation criteria: SAR ratio M2/M1 (%)	77.36


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.283	0.219	0.169	0.151	0.120	0.104	0.082




F. 3D Image

3D screen shot



Hot spot position



2# SAR Measurement at GPRS850 (Body, Validation Plane)

Date of measurement: 17/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS850
Signal	TDMA (GPRS)
Channels/Frequency	Middle (189)/ frequency 836.40 Mhz
Modulation	GMSK (CS-4)
TX-slots	4

B. Permittivity

Middle TX Frequency (MHz)	836.40
Relative permittivity (real part)	42.31
Relative permittivity (imaginary part)	20.06
Conductivity (S/m)	0.93

C. SAR Surface and Volume




Maximum location: X=5.00, Y=-41.00 ; SAR Peak: 0.38 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.143
SAR 1g (W/Kg)	0.257
Variation (%)	-2.01
Horizontal validation criteria: minimum distance (mm)	0.00
Vertical validation criteria: SAR ratio M2/M1 (%)	0.00

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.366	0.257	0.168	0.132	0.075	0.068	0.035



F. 3D Image



3# SAR Measurement at GPRS1900 (Cheek, Right)


Date of measurement: 10/5/2025

A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	GPRS1900
Signal	TDMA (GPRS)
Channels/Frequency	Middle (661)/ frequency 1880.00 Mhz
Modulation	GMSK (CS-4)
TX-slots	4

B. Permittivity

Middle TX Frequency (MHz)	1880.00
Relative permittivity (real part)	38.52
Relative permittivity (imaginary part)	13.74
Conductivity (S/m)	1.44

C. SAR Surface and Volume


Maximum location: X=-51.00, Y=-22.00 ; SAR Peak: 0.06 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.027
SAR 1g (W/Kg)	0.041
Variation (%)	0.81
Horizontal validation criteria: minimum distance (mm)	17.89
Vertical validation criteria: SAR ratio M2/M1 (%)	74.25


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.053	0.043	0.032	0.024	0.016	0.012	0.009




F. 3D Image

3D screen shot



Hot spot position



4# SAR Measurement at GPRS1900 (Body, Validation Plane)

Date of measurement: 10/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS1900
Signal	TDMA (GPRS)
Channels/Frequency	Middle (661)/ frequency 1880.00 Mhz
Modulation	GMSK (CS-4)
TX-slots	4

B. Permittivity

Middle TX Frequency (MHz)	1880.00
Relative permittivity (real part)	38.52
Relative permittivity (imaginary part)	13.74
Conductivity (S/m)	1.44

C. SAR Surface and Volume




Maximum location: X=5.00, Y=5.00 ; SAR Peak: 0.30 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.104
SAR 1g (W/Kg)	0.193
Variation (%)	-0.07
Horizontal validation criteria: minimum distance (mm)	17.89
Vertical validation criteria: SAR ratio M2/M1 (%)	61.65

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.366	0.191	0.080	0.066	0.036	0.026	0.015



F. 3D Image



5# SAR Measurement at Band 2 (1900) (Cheek, Left)

Date of measurement: 10/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Left head
Device Position	Cheek
Band	Band 2 (1900)
Signal	WCDMA
Channels/Frequency	Middle (9400)/ frequency 1880.00 Mhz
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	1880.00
Relative permittivity (real part)	38.52
Relative permittivity (imaginary part)	13.74
Conductivity (S/m)	1.44

C. SAR Surface and Volume




Maximum location: X=-50.00, Y=-51.00 ; SAR Peak: 0.18 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.078
SAR 1g (W/Kg)	0.127
Variation (%)	-0.15
Horizontal validation criteria: minimum distance (mm)	17.89
Vertical validation criteria: SAR ratio M2/M1 (%)	70.13


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.167	0.126	0.088	0.063	0.044	0.032	0.023




F. 3D Image

3D screen shot



Hot spot position



6# SAR Measurement at Band 2 (1900) (Body, Validation Plane)

Date of measurement: 10/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 2 (1900)
Signal	WCDMA
Channels/Frequency	Middle (9400)/ frequency 1880.00 Mhz
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	1880.00
Relative permittivity (real part)	38.52
Relative permittivity (imaginary part)	13.74
Conductivity (S/m)	1.44

C. SAR Surface and Volume




Maximum location: X=6.00, Y=5.00 ; SAR Peak: 0.51 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.178
SAR 1g (W/Kg)	0.328
Variation (%)	0.38
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	59.97

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.514	0.345	0.207	0.125	0.076	0.047	0.029



F. 3D Image



7# SAR Measurement at Band 4 (1700) (Cheek, Right)


Date of measurement: 11/5/2025

A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.50
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	Band 4 (1700)
Signal	WCDMA
Channels/Frequency	Middle (1413)/ frequency 1732.60 Mhz
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	1732.60
Relative permittivity (real part)	39.20
Relative permittivity (imaginary part)	13.62
Conductivity (S/m)	1.31

C. SAR Surface and Volume


Maximum location: X=-49.00, Y=8.00 ; SAR Peak: 0.09 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.034
SAR 1g (W/Kg)	0.058
Variation (%)	1.78
Horizontal validation criteria: minimum distance (mm)	17.89
Vertical validation criteria: SAR ratio M2/M1 (%)	66.48


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.084	0.061	0.040	0.027	0.019	0.012	0.009




F. 3D Image

3D screen shot



Hot spot position



8# SAR Measurement at Band 4 (1700) (Body, Validation Plane)

Date of measurement: 11/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.50
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 4 (1700)
Signal	WCDMA
Channels/Frequency	Middle (1413)/ frequency 1732.60 Mhz
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	1732.60
Relative permittivity (real part)	39.20
Relative permittivity (imaginary part)	13.62
Conductivity (S/m)	1.31

C. SAR Surface and Volume




Maximum location: X=6.00, Y=3.00 ; SAR Peak: 0.25 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.092
SAR 1g (W/Kg)	0.163
Variation (%)	-0.65
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	62.56

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.244	0.170	0.106	0.066	0.042	0.026	0.018



F. 3D Image



9# SAR Measurement at Band 5 (850) (Cheek, Left)

Date of measurement: 17/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Left head
Device Position	Cheek
Band	Band 5 (850)
Signal	WCDMA
Channels/Frequency	Middle (4182)/ frequency 836.40 Mhz
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	836.40
Relative permittivity (real part)	42.31
Relative permittivity (imaginary part)	20.06
Conductivity (S/m)	0.93

C. SAR Surface and Volume




Maximum location: X=-40.00, Y=-7.00 ; SAR Peak: 0.25 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.161
SAR 1g (W/Kg)	0.209
Variation (%)	-1.77
Horizontal validation criteria: minimum distance (mm)	0.00
Vertical validation criteria: SAR ratio M2/M1 (%)	0.00


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.245	0.210	0.174	0.147	0.121	0.099	0.082




F. 3D Image

3D screen shot



Hot spot position



10# SAR Measurement at Band 5 (850) (Body, Validation Plane)

Date of measurement: 17/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Band 5 (850)
Signal	WCDMA
Channels/Frequency	Middle (4182)/ frequency 836.40 Mhz
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Middle TX Frequency (MHz)	836.40
Relative permittivity (real part)	42.31
Relative permittivity (imaginary part)	20.06
Conductivity (S/m)	0.93

C. SAR Surface and Volume




Maximum location: X=-5.00, Y=-26.00 ; SAR Peak: 0.37 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.169
SAR 1g (W/Kg)	0.263
Variation (%)	-1.03
Horizontal validation criteria: minimum distance (mm)	0.00
Vertical validation criteria: SAR ratio M2/M1 (%)	0.00

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.336	0.263	0.192	0.139	0.099	0.071	0.050



F. 3D Image



11# SAR Measurement at U-NII-1 (Cheek, Left)

Date of measurement: 6/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.37
Area Scan	dx=10mm dy=10mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Left head
Device Position	Cheek
Band	U-NII-1
Signal	IEEE 802.11 a
Channels/Frequency	Middle (40)/ frequency 5200.00 Mhz

B. Permittivity

Middle TX Frequency (MHz)	5200.00
Relative permittivity (real part)	37.40
Relative permittivity (imaginary part)	15.83
Conductivity (S/m)	4.57

C. SAR Surface and Volume




Maximum location: X=-26.00, Y=24.00 ; SAR Peak: 0.86 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.100
SAR 1g (W/Kg)	0.307
Variation (%)	1.62
Horizontal validation criteria: minimum distance (mm)	5.66
Vertical validation criteria: SAR ratio M2/M1 (%)	56.41


E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SAR (W/Kg)	0.59	0.35	0.20	0.10	0.05	0.03	0.02	0.01	0.01	0.00	0.01	0.00
	4	8	2	1	9	6	0	8	6	6	0	9




F. 3D Image

3D screen shot



Hot spot position



12# SAR Measurement at U-NII-1 (Body, Validation Plane)

Date of measurement: 6/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.37
Area Scan	dx=10mm dy=10mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-1
Signal	IEEE 802.11 a
Channels/Frequency	Middle (40)/ frequency 5200.00 Mhz

B. Permittivity

Middle TX Frequency (MHz)	5200.00
Relative permittivity (real part)	37.40
Relative permittivity (imaginary part)	15.83
Conductivity (S/m)	4.57

C. SAR Surface and Volume




Maximum location: X=0.00, Y=39.00 ; SAR Peak: 0.26 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.043
SAR 1g (W/Kg)	0.095
Variation (%)	-2.37
Horizontal validation criteria: minimum distance (mm)	14.42
Vertical validation criteria: SAR ratio M2/M1 (%)	61.40

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SAR (W/Kg)	0.23 3	0.14 8	0.08 9	0.05 8	0.03 6	0.02 6	0.02 2	0.02 0	0.01 9	0.01 0	0.01 5	0.01 5



F. 3D Image



13# SAR Measurement at U-NII-3 (Cheek, Left)

Date of measurement: 15/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.35
Area Scan	dx=10mm dy=10mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Left head
Device Position	Cheek
Band	U-NII-3
Signal	IEEE 802.11 n
Channels/Frequency	Middle (149)/ frequency 5745.00 Mhz

B. Permittivity

Middle TX Frequency (MHz)	5745.00
Relative permittivity (real part)	36.00
Relative permittivity (imaginary part)	15.72
Conductivity (S/m)	5.05

C. SAR Surface and Volume




Maximum location: X=-26.00, Y=24.00 ; SAR Peak: 0.97 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.098
SAR 1g (W/Kg)	0.314
Variation (%)	4.37
Horizontal validation criteria: minimum distance (mm)	8.00
Vertical validation criteria: SAR ratio M2/M1 (%)	52.37


E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SAR (W/Kg)	0.628	0.369	0.193	0.097	0.057	0.036	0.025	0.026	0.018	0.019	0.018	0.016




F. 3D Image

3D screen shot



Hot spot position



14# SAR Measurement at U-NII-3 (Body, Validation Plane)

Date of measurement: 15/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.35
Area Scan	dx=10mm dy=10mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-3
Signal	IEEE 802.11 n
Channels/Frequency	Middle (149)/ frequency 5745.00 Mhz

B. Permittivity

Middle TX Frequency (MHz)	5745.00
Relative permittivity (real part)	36.00
Relative permittivity (imaginary part)	15.72
Conductivity (S/m)	5.05

C. SAR Surface and Volume




Maximum location: X=6.00, Y=45.00 ; SAR Peak: 0.49 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.070
SAR 1g (W/Kg)	0.168
Variation (%)	-3.44
Horizontal validation criteria: minimum distance (mm)	11.31
Vertical validation criteria: SAR ratio M2/M1 (%)	54.19

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SAR (W/Kg)	0.429	0.265	0.136	0.091	0.058	0.046	0.033	0.030	0.020	0.020	0.020	0.023



F. 3D Image



15# SAR Measurement at ISM (Cheek, Left)

Date of measurement: 16/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.63
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Left head
Device Position	Cheek
Band	ISM
Signal	IEEE 802.11 b
Channels/Frequency	Middle (6)/ frequency 2437.00 Mhz

B. Permittivity

Middle TX Frequency (MHz)	2437.00
Relative permittivity (real part)	38.18
Relative permittivity (imaginary part)	13.12
Conductivity (S/m)	1.78

C. SAR Surface and Volume




Maximum location: X=-24.00, Y=16.00 ; SAR Peak: 1.11 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.293
SAR 1g (W/Kg)	0.618
Variation (%)	-1.25
Horizontal validation criteria: minimum distance (mm)	11.18
Vertical validation criteria: SAR ratio M2/M1 (%)	51.73


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.104	0.675	0.349	0.177	0.094	0.048	0.025




F. 3D Image

3D screen shot



Hot spot position



16# SAR Measurement at ISM (Body, Validation Plane)

Date of measurement: 16/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.63
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	ISM
Signal	IEEE 802.11 b
Channels/Frequency	Middle (6)/ frequency 2437.00 Mhz

B. Permittivity

Middle TX Frequency (MHz)	2437.00
Relative permittivity (real part)	38.18
Relative permittivity (imaginary part)	13.12
Conductivity (S/m)	1.78

C. SAR Surface and Volume




Maximum location: X=18.00, Y=46.00 ; SAR Peak: 0.21 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.060
SAR 1g (W/Kg)	0.120
Variation (%)	-0.26
Horizontal validation criteria: minimum distance (mm)	18.03
Vertical validation criteria: SAR ratio M2/M1 (%)	53.59

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.238	0.126	0.053	0.035	0.019	0.012	0.007



F. 3D Image



17# SAR Measurement at LTE band 2 (Cheek, Right)


Date of measurement: 10/5/2025

A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 2
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (18900)/ frequency 1880.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	1880.00

B. Permittivity

Middle TX Frequency (MHz)	1880.00
Relative permittivity (real part)	38.52
Relative permittivity (imaginary part)	13.74
Conductivity (S/m)	1.44

C. SAR Surface and Volume


Maximum location: X=-51.00, Y=-21.00 ; SAR Peak: 0.09 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.041
SAR 1g (W/Kg)	0.067
Variation (%)	-0.10
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	72.31


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.090	0.071	0.051	0.035	0.026	0.017	0.014




F. 3D Image

3D screen shot



Hot spot position



18# SAR Measurement at LTE band 2 (Body, Validation Plane)

Date of measurement: 10/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 2
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (18900)/ frequency 1880.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	1880.00

B. Permittivity

Middle TX Frequency (MHz)	1880.00
Relative permittivity (real part)	38.52
Relative permittivity (imaginary part)	13.74
Conductivity (S/m)	1.44

C. SAR Surface and Volume




Maximum location: X=3.00, Y=3.00 ; SAR Peak: 0.57 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.190
SAR 1g (W/Kg)	0.358
Variation (%)	-1.69
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	60.18

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.549	0.368	0.222	0.134	0.084	0.050	0.031



F. 3D Image



19# SAR Measurement at LTE band 4 (Cheek, Right)


Date of measurement: 11/5/2025

A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.50
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 4
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (20175)/ frequency 1732.50 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	1732.50

B. Permittivity

Middle TX Frequency (MHz)	1732.50
Relative permittivity (real part)	39.20
Relative permittivity (imaginary part)	13.62
Conductivity (S/m)	1.31

C. SAR Surface and Volume


Maximum location: X=-52.00, Y=-5.00 ; SAR Peak: 0.08 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.032
SAR 1g (W/Kg)	0.054
Variation (%)	1.89
Horizontal validation criteria: minimum distance (mm)	11.31
Vertical validation criteria: SAR ratio M2/M1 (%)	69.33


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.098	0.057	0.029	0.024	0.016	0.011	0.010




F. 3D Image

3D screen shot



Hot spot position



20# SAR Measurement at LTE band 4 (Body, Validation Plane)

Date of measurement: 11/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.50
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 4
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (20175)/ frequency 1732.50 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	1732.50

B. Permittivity

Middle TX Frequency (MHz)	1732.50
Relative permittivity (real part)	39.20
Relative permittivity (imaginary part)	13.62
Conductivity (S/m)	1.31

C. SAR Surface and Volume




Maximum location: X=5.00, Y=3.00 ; SAR Peak: 0.31 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.107
SAR 1g (W/Kg)	0.193
Variation (%)	0.04
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	62.25

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.298	0.204	0.127	0.081	0.051	0.032	0.020



F. 3D Image



21# SAR Measurement at LTE band 5 (Cheek, Left)

Date of measurement: 17/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Left head
Device Position	Cheek
Band	LTE band 5
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (20525)/ frequency 836.50 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	836.50

B. Permittivity

Middle TX Frequency (MHz)	836.50
Relative permittivity (real part)	42.31
Relative permittivity (imaginary part)	20.06
Conductivity (S/m)	0.93

C. SAR Surface and Volume




Maximum location: X=-49.00, Y=-14.00 ; SAR Peak: 0.36 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.227
SAR 1g (W/Kg)	0.299
Variation (%)	-1.84
Horizontal validation criteria: minimum distance (mm)	0.00
Vertical validation criteria: SAR ratio M2/M1 (%)	0.00


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.356	0.304	0.249	0.199	0.163	0.138	0.112




F. 3D Image

3D screen shot



Hot spot position



22# SAR Measurement at LTE band 5 (Body, Validation Plane)


Date of measurement: 17/5/2025

A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 5
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (20525)/ frequency 836.50 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	836.50

B. Permittivity

Middle TX Frequency (MHz)	836.50
Relative permittivity (real part)	42.31
Relative permittivity (imaginary part)	20.06
Conductivity (S/m)	0.93

C. SAR Surface and Volume


Maximum location: X=18.00, Y=-44.00 ; SAR Peak: 0.45 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.155
SAR 1g (W/Kg)	0.304
Variation (%)	0.06
Horizontal validation criteria: minimum distance (mm)	22.63
Vertical validation criteria: SAR ratio M2/M1 (%)	67.68

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.437	0.309	0.197	0.124	0.080	0.054	0.036



F. 3D Image



23# SAR Measurement at LTE band 7 (Cheek, Left)


Date of measurement: 14/5/2025

A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.52
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Left head
Device Position	Cheek
Band	LTE band 7
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (21100)/ frequency 2535.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	2535.00

B. Permittivity

Middle TX Frequency (MHz)	2535.00
Relative permittivity (real part)	39.67
Relative permittivity (imaginary part)	13.28
Conductivity (S/m)	1.87

C. SAR Surface and Volume


Maximum location: X=-48.00, Y=-48.00 ; SAR Peak: 0.04 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.018
SAR 1g (W/Kg)	0.027
Variation (%)	0.28
Horizontal validation criteria: minimum distance (mm)	15.81
Vertical validation criteria: SAR ratio M2/M1 (%)	72.52


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.041	0.029	0.020	0.016	0.013	0.012	0.012




F. 3D Image

3D screen shot



Hot spot position



24# SAR Measurement at LTE band 7 (Body, Validation Plane)

Date of measurement: 14/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.52
Area Scan	dx=12mm dy=12mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 7
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (21100)/ frequency 2535.00 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	2535.00

B. Permittivity

Middle TX Frequency (MHz)	2535.00
Relative permittivity (real part)	39.67
Relative permittivity (imaginary part)	13.28
Conductivity (S/m)	1.87

C. SAR Surface and Volume




Maximum location: X=-14.00, Y=2.00 ; SAR Peak: 0.32 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.088
SAR 1g (W/Kg)	0.183
Variation (%)	-0.87
Horizontal validation criteria: minimum distance (mm)	10.00
Vertical validation criteria: SAR ratio M2/M1 (%)	55.62

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.312	0.201	0.112	0.054	0.029	0.018	0.010



F. 3D Image



25# SAR Measurement at LTE band 12 (Cheek, Left)


Date of measurement: 9/5/2025

A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.39
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Left head
Device Position	Cheek
Band	LTE band 12
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (23095)/ frequency 707.50 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	707.50

B. Permittivity

Middle TX Frequency (MHz)	707.50
Relative permittivity (real part)	41.44
Relative permittivity (imaginary part)	21.69
Conductivity (S/m)	0.85

C. SAR Surface and Volume


Maximum location: X=-52.00, Y=-22.00 ; SAR Peak: 0.29 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.190
SAR 1g (W/Kg)	0.241
Variation (%)	-2.50
Horizontal validation criteria: minimum distance (mm)	0.00
Vertical validation criteria: SAR ratio M2/M1 (%)	0.00


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.295	0.246	0.203	0.173	0.149	0.125	0.103




F. 3D Image

3D screen shot



Hot spot position



26# SAR Measurement at LTE band 12 (Body, Validation Plane)


Date of measurement: 9/5/2025

A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.39
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 12
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (23095)/ frequency 707.50 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	707.50

B. Permittivity

Middle TX Frequency (MHz)	707.50
Relative permittivity (real part)	41.44
Relative permittivity (imaginary part)	21.69
Conductivity (S/m)	0.85

C. SAR Surface and Volume


Maximum location: X=-9.00, Y=18.00 ; SAR Peak: 0.42 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.255
SAR 1g (W/Kg)	0.334
Variation (%)	-0.45
Horizontal validation criteria: minimum distance (mm)	0.00
Vertical validation criteria: SAR ratio M2/M1 (%)	0.00

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.416	0.341	0.272	0.217	0.177	0.138	0.109



F. 3D Image



27# SAR Measurement at LTE band 17 (Cheek, Left)

Date of measurement: 9/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.39
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Left head
Device Position	Cheek
Band	LTE band 17
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (23790)/ frequency 710.00 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	710.00

B. Permittivity

Middle TX Frequency (MHz)	710.00
Relative permittivity (real part)	41.43
Relative permittivity (imaginary part)	21.63
Conductivity (S/m)	0.85

C. SAR Surface and Volume




Maximum location: X=-52.00, Y=-22.00 ; SAR Peak: 0.31 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.200
SAR 1g (W/Kg)	0.256
Variation (%)	-0.70
Horizontal validation criteria: minimum distance (mm)	0.00
Vertical validation criteria: SAR ratio M2/M1 (%)	0.00


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.313	0.263	0.216	0.182	0.152	0.128	0.107




F. 3D Image

3D screen shot



Hot spot position



28# SAR Measurement at LTE band 17 (Body, Validation Plane)


Date of measurement: 9/5/2025

A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.39
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 17
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (23790)/ frequency 710.00 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	710.00

B. Permittivity

Middle TX Frequency (MHz)	710.00
Relative permittivity (real part)	41.43
Relative permittivity (imaginary part)	21.63
Conductivity (S/m)	0.85

C. SAR Surface and Volume


Maximum location: X=-9.00, Y=18.00 ; SAR Peak: 0.42 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.250
SAR 1g (W/Kg)	0.340
Variation (%)	-0.85
Horizontal validation criteria: minimum distance (mm)	0.00
Vertical validation criteria: SAR ratio M2/M1 (%)	0.00

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.426	0.349	0.279	0.219	0.179	0.143	0.111



F. 3D Image



29# SAR Measurement at LTE band 25 (Cheek, Right)

Date of measurement: 10/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 25
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (26365)/ frequency 1882.50 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	1882.50

B. Permittivity

Middle TX Frequency (MHz)	1882.50
Relative permittivity (real part)	38.50
Relative permittivity (imaginary part)	13.75
Conductivity (S/m)	1.44

C. SAR Surface and Volume




Maximum location: X=-51.00, Y=-21.00 ; SAR Peak: 0.11 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.044
SAR 1g (W/Kg)	0.073
Variation (%)	3.73
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	67.56

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.108	0.078	0.052	0.038	0.027	0.020	0.014



F. 3D Image



30# SAR Measurement at LTE band 25 (Body, Validation Plane)

Date of measurement: 10/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.58
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 25
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (26365)/ frequency 1882.50 Mhz
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	1882.50

B. Permittivity

Middle TX Frequency (MHz)	1882.50
Relative permittivity (real part)	38.50
Relative permittivity (imaginary part)	13.75
Conductivity (S/m)	1.44

C. SAR Surface and Volume




Maximum location: X=5.00, Y=3.00 ; SAR Peak: 0.57 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.192
SAR 1g (W/Kg)	0.364
Variation (%)	-0.53
Horizontal validation criteria: minimum distance (mm)	11.31
Vertical validation criteria: SAR ratio M2/M1 (%)	60.62

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.531	0.361	0.219	0.134	0.080	0.051	0.032



F. 3D Image



31# SAR Measurement at LTE band 26A (Cheek, Left)

Date of measurement: 17/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Left head
Device Position	Cheek
Band	LTE band 26A
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (26740)/ frequency 819.00 Mhz
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	819.00

B. Permittivity

Middle TX Frequency (MHz)	819.00
Relative permittivity (real part)	42.58
Relative permittivity (imaginary part)	20.04
Conductivity (S/m)	0.91

C. SAR Surface and Volume




Maximum location: X=-49.00, Y=-17.00 ; SAR Peak: 0.51 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.317
SAR 1g (W/Kg)	0.415
Variation (%)	-1.95
Horizontal validation criteria: minimum distance (mm)	0.00
Vertical validation criteria: SAR ratio M2/M1 (%)	0.00


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.504	0.425	0.347	0.287	0.237	0.192	0.156




F. 3D Image

3D screen shot



Hot spot position



32# SAR Measurement at LTE band 26B (Cheek, Left)

Date of measurement: 17/5/2025


A. Experimental conditions.

Probe	0725-EPGO-448
ConvF	1.32
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5.0mm,Complete
Phantom	Left head
Device Position	Cheek
Band	LTE band 26B
Signal	LTE FDD
Channel Center [EARFCN] / Channel Center [MHz]	Middle (26865)/ frequency 831.50 Mhz
Cell Bandwidth	15 Mhz
Modulation	SC-OFDM - QPSK
Middle TX Frequency (MHz)	831.50

B. Permittivity

Middle TX Frequency (MHz)	831.50
Relative permittivity (real part)	42.36
Relative permittivity (imaginary part)	20.05
Conductivity (S/m)	0.93

C. SAR Surface and Volume




Maximum location: X=-49.00, Y=-16.00 ; SAR Peak: 0.43 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.279
SAR 1g (W/Kg)	0.364
Variation (%)	-3.30
Horizontal validation criteria: minimum distance (mm)	0.00
Vertical validation criteria: SAR ratio M2/M1 (%)	0.00


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.421	0.372	0.309	0.254	0.203	0.165	0.136



F. 3D Image

3D screen shot



Hot spot position

