

# RF TEST REPORT



Report No.: 17070831-FCC-R

Supersede Report No.: N/A

Applicant	99iot(Shenzhen )co.,ltd	
Product Name	WIFI Module	
Model No.	AF-W121T	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013	
Test Date	September 01 to October 09, 2017	
Issue Date	October 10, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification		<input checked="" type="checkbox"/>
Equipment did not comply with the specification		<input type="checkbox"/>
Loren Luo	David Huang	
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	17070831-FCC-R
Page	3 of 54

---

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION .....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	7
5. TEST SUMMARY .....	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	9
6.1 ANTENNA REQUIREMENT .....	9
6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH .....	10
6.3 MAXIMUM OUTPUT POWER .....	17
6.4 POWER SPECTRAL DENSITY .....	21
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS .....	25
6.6 AC POWER LINE CONDUCTED EMISSIONS .....	31
6.7 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND .....	37
ANNEX A. TEST INSTRUMENT .....	45
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS .....	46
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT .....	49
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST .....	53
ANNEX E. DECLARATION OF SIMILARITY .....	54

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070831-FCC-R	NONE	Original	October 10, 2017

## 2. Customer information

Applicant Name	99iot(Shenzhen )co.,ltd
Applicant Add	Room 609C North cangsong building,No 7 tairan road,Futian district,Shenzhen,China
Manufacturer	99iot(Shenzhen )co.,ltd
Manufacturer Add	Room 609C North cangsong building,No 7 tairan road,Futian district,Shenzhen,China

## 3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMС(ver.lcp-03A1)

Test Report No.	17070831-FCC-R
Page	6 of 54

---

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

## 4. Equipment under Test (EUT) Information

Description of EUT:	WIFI Module
Main Model:	AF-W121T
Serial Model:	N/A
Date EUT received:	August 31, 2017
Test Date(s):	September 01 to October 09, 2017
Equipment Category :	DTS
Antenna Gain:	2dBi
Antenna Type:	PCB antenna
Type of Modulation:	802.11b/g/n: DSSS, OFDM
RF Operating Frequency (ies):	WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz
Max. Output Power:	802.11b: 16.34 dBm 802.11g: 13.90 dBm 802.11n(20M): 12.68 dBm 802.11n(40M): 12.71 dBm
Number of Channels:	WIFI :802.11b/g/n(20M): 11CH WIFI :802.11n(40M): 7CH
Port:	N/A
Input Power:	N/A
Trade Name :	99IoT
FCC ID:	2ANN4-99IOTW121

## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band-Edge & Unwanted Emissions into Restricted Frequency Bands and Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

## **6. Measurements, Examination And Derived Results**

### **6.1 Antenna Requirement**

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has 1 antenna:

A permanently attached PCB antenna for WIFI, the gain is 2dBi for WIFI.

**The antenna meets up with the ANTENNA REQUIREMENT.**

**Result:** Compliance.

## 6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	25 °C
Relative Humidity	56%
Atmospheric Pressure	1018mbar
Test date :	September 09, 2017
Tested By :	Loren Luo

	case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A

Test Plot  Yes (See below)  N/A


#### Measurement result



Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.06	$\geq 0.5$
	Mid	2437	10.08	$\geq 0.5$
	High	2462	10.08	$\geq 0.5$
802.11g	Low	2412	16.39	$\geq 0.5$
	Mid	2437	16.39	$\geq 0.5$
	High	2462	16.38	$\geq 0.5$
802.11n (20M)	Low	2412	17.59	$\geq 0.5$
	Mid	2437	17.61	$\geq 0.5$
	High	2462	17.60	$\geq 0.5$
802.11n (40M)	Low	2422	35.40	$\geq 0.5$
	Mid	2437	35.96	$\geq 0.5$
	High	2452	35.90	$\geq 0.5$

Test mode	CH	Freq (MHz)	20dB Bandwidth (MHz)
802.11b	Low	2412	17.18
	Mid	2437	17.20
	High	2462	17.18
802.11g	Low	2412	19.56
	Mid	2437	19.81
	High	2462	19.57
802.11n (20M)	Low	2412	20.27
	Mid	2437	20.52
	High	2462	20.43
802.11n (40M)	Low	2422	38.37
	Mid	2437	38.41
	High	2452	38.34

## Test Plots



### 6dB Bandwidth measurement result







### 802.11n20 6dB Bandwidth - Low CH 2412

### 802.11n20 6dB Bandwidth - Mid CH 2437



### 802.11n20 6dB Bandwidth - High CH 2462


### 802.11n40 6dB Bandwidth - Low CH 2422





### 802.11n40 6dB Bandwidth - Mid CH 2437


### 802.11n40 6dB Bandwidth - High CH 2452

## 20 dB Bandwidth measurement result







### 802.11n20 20dB Bandwidth - Low CH 2412




### 802.11n20 20dB Bandwidth - Mid CH 2437



### 802.11n20 20dB Bandwidth - High CH 2462



### 802.11n40 20dB Bandwidth - Low CH 2422




### 802.11n40 20dB Bandwidth - Mid CH 2437

### 802.11n40 20dB Bandwidth - High CH 2452

### 6.3 Maximum Output Power

Temperature	25°C
Relative Humidity	57%
Atmospheric Pressure	1023mbar
Test date :	September 27, 2017
Tested By :	Loren Luo

#### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3), RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with $\geq$ 75 channels: $\leq$ 1 Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: $\leq$ 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: $\leq$ 0.125 Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with $\geq$ 50 channels: $\leq$ 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with $\geq$ 25 & $< 50$ channels: $\leq$ 0.25 Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: $\leq$ 1 Watt	<input checked="" type="checkbox"/>
Test Setup		 <b>Spectrum Analyzer</b> <b>EUT</b>	
Test Procedure		<p>558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method</p> <p>Maximum output power measurement procedure</p> <ul style="list-style-type: none"> <li>- a) Set span to at least 1.5 times the OBW.</li> <li>- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.</li> <li>- c) Set VBW <math>\geq</math> 3 x RBW.</li> <li>- d) Number of points in sweep <math>\geq</math> 2 <math>\times</math> span / RBW. (This gives bin-to-bin spacing <math>\leq</math> RBW/2, so that narrowband signals are not lost between frequency bins.)</li> <li>- e) Sweep time = auto.</li> <li>- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.</li> <li>- g) If transmit duty cycle <math>&lt;</math> 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum</li> </ul>	

	<p>power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle <math>\geq 98\%</math>, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “ free run” .</p> <ul style="list-style-type: none"> <li>- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.</li> <li>- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’ s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A


Test Plot  Yes (See below)  N/A


#### Output Power measurement result

Type	Test mode	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	Low	2412	16.15	30	Pass
		Mid	2437	16.29	30	Pass
		High	2462	<b>16.34</b>	30	Pass
	802.11g	Low	2412	13.48	30	Pass
		Mid	2437	<b>13.90</b>	30	Pass
		High	2462	13.88	30	Pass
	802.11n (20M)	Low	2412	12.41	30	Pass
		Mid	2437	12.61	30	Pass
		High	2462	<b>12.68</b>	30	Pass
	802.11n (40M)	Low	2422	12.39	30	Pass
		Mid	2437	12.50	30	Pass
		High	2452	<b>12.71</b>	30	Pass


## Test Plots

### The Average Power






### 802.11n20 - AV Output power - Low CH 2412




### 802.11n20 - AV Output power - Mid CH 2437



### 802.11n20 - AV Output power - High CH 2462



### 802.11n40 - AV Output power - Low CH 2422



### 802.11n40 - AV Output power - Mid CH 2437

### 802.11n40 - AV Output power - High CH 2452

## 6.4 Power Spectral Density

Temperature	25°C
Relative Humidity	57%
Atmospheric Pressure	1023mbar
Test date :	September 27, 2017
Tested By :	Loren Luo

Test Data  Yes  N/A  
 Test Plot  Yes (See below)  N/A

### Power Spectral Density measurement result

Type	Test mode	CH	Freq (MHz)	PSD	Limit (dBm)	Result
				(dBm)		
PSD	802.11b	Low	2412	-13.754	8	Pass
		Mid	2437	-13.605	8	Pass
		High	2462	-13.559	8	Pass
	802.11g	Low	2412	-14.998	8	Pass
		Mid	2437	-14.897	8	Pass
		High	2462	-14.999	8	Pass
	802.11n (20M)	Low	2412	-15.575	8	Pass
		Mid	2437	-15.299	8	Pass
		High	2462	-15.936	8	Pass
	802.11n (40M)	Low	2422	-16.252	8	Pass
		Mid	2437	-16.187	8	Pass
		High	2452	-16.147	8	Pass

## Test Plots

### Power Spectral Density measurement result




PSD - Low CH 2412 - 802.11b




PSD - Mid CH 2437 – 802.11b




PSD - High CH 2462 - 802.11b





PSD - Low CH 2412 -802.11g



PSD - Mid CH 2437 – 802.11g





PSD - High CH 2462 - 802.11g





PSD - Low CH 2412 - 802.11n20

PSD - Mid CH 2437 – 802.11n20



PSD - High CH 2472 - 802.11n20

PSD - Low CH 2422 - 802.11n40




PSD - Mid CH 2437 – 802.11n40

PSD - High CH 2452 - 802.11n40

## 6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1020mbar
Test date :	September 28, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>
Test Setup	 <p>The diagram illustrates the test setup. An 'EUT &amp; Support Units' is positioned on a 'Turn Table' at a height of '0.8/1.5m' above a 'Ground Plane'. A 'Test Receiver' is connected to the turn table. A '1-4m Variable' length 'Ant. Tower' is mounted on the turn table, extending vertically upwards. A horizontal line connects the center of the turn table to the top of the antenna tower, labeled '3m'.</p>		
Test Procedure	<p>Radiated Method Only</p> <ul style="list-style-type: none"> <li>- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.</li> <li>- 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.</li> </ul>		


	<ul style="list-style-type: none"> <li>- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below:           <ul style="list-style-type: none"> <li>a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</li> <li>b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> <li>c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</li> </ul> </li> <li>- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.</li> <li>- 5. Repeat above procedures until all measured frequencies were complete.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A


Test Plot  Yes (See below)  N/A

## Test Plots


### Band Edge measurement result




Note: Both Horizontal and vertical polarities were investigated



Note: Both Horizontal and vertical polarities were investigated



Note: Both Horizontal and vertical polarities were investigated



Note: Both Horizontal and vertical polarities were investigated

## 6.6 AC Power Line Conducted Emissions

Temperature	23 °C
Relative Humidity	55%
Atmospheric Pressure	1012mbar
Test date :	September 04, 2017
Tested By :	Loren Luo

### Requirement(s):


Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	<p>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.</p> <table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dB<math>\mu</math>V)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency ranges (MHz)	Limit (dB $\mu$ V)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50	<input checked="" type="checkbox"/>
Frequency ranges (MHz)	Limit (dB $\mu$ V)																
	QP	Average															
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup																	
Procedure	<ol style="list-style-type: none"> <li>1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.</li> <li>2. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.</li> <li>3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss</li> </ol>																

	<p>coaxial cable.</p> <ol style="list-style-type: none"> <li>4. All other supporting equipment were powered separately from another main supply.</li> <li>5. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.</li> <li>7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz.</li> <li>8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).</li> </ol>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A

Test Plot  Yes (See below)  N/A


**Test Mode:** Transmitting Mode



Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Corrected (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)
1	L1	0.2046	43.82	QP	10.02	53.84	63.42	-9.58
2	L1	0.2046	27.95	AVG	10.02	37.97	53.42	-15.45
3	L1	0.3372	34.49	QP	10.02	44.51	59.27	-14.76
4	L1	0.3372	21.30	AVG	10.02	31.32	49.27	-17.95
5	L1	3.4173	29.32	QP	10.05	39.37	56.00	-16.63
6	L1	3.4173	15.38	AVG	10.05	25.43	46.00	-20.57
7	L1	9.2556	25.65	QP	10.13	35.78	60.00	-24.22
8	L1	9.2556	19.12	AVG	10.13	29.25	50.00	-20.75
9	L1	11.8725	25.77	QP	10.16	35.93	60.00	-24.07
10	L1	11.8725	18.78	AVG	10.16	28.94	50.00	-21.06
11	L1	19.7232	26.40	QP	10.26	36.66	60.00	-23.34
12	L1	19.7232	15.57	AVG	10.26	25.83	50.00	-24.17

**Test Mode:** Transmitting Mode




**Test Data**

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Corrected (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)
1	N	0.1968	45.52	QP	10.03	55.55	63.74	-8.19
2	N	0.1968	29.34	AVG	10.03	39.37	53.74	-14.37
3	N	0.3294	32.99	QP	10.03	43.02	59.47	-16.45
4	N	0.3294	22.64	AVG	10.03	32.67	49.47	-16.80
5	N	0.5946	27.30	QP	10.03	37.33	56.00	-18.67
6	N	0.5946	20.80	AVG	10.03	30.83	46.00	-15.17
7	N	1.1367	25.46	QP	10.03	35.49	56.00	-20.51
8	N	1.1367	18.93	AVG	10.03	28.96	46.00	-17.04
9	N	3.3393	27.09	QP	10.06	37.15	56.00	-18.85
10	N	3.3393	12.41	AVG	10.06	22.47	46.00	-23.53
11	N	13.5729	24.33	QP	10.20	34.53	60.00	-25.47
12	N	13.5729	16.34	AVG	10.20	26.54	50.00	-23.46


**Test Mode:** Transmitting Mode



Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Corrected (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)
1	L1	0.1968	43.29	QP	10.03	53.32	63.74	-10.42
2	L1	0.1968	21.19	AVG	10.03	31.22	53.74	-22.52
3	L1	0.2670	41.05	QP	10.03	51.08	61.21	-10.13
4	L1	0.2670	24.20	AVG	10.03	34.23	51.21	-16.98
5	L1	0.6726	29.86	QP	10.03	39.89	56.00	-16.11
6	L1	0.6726	14.37	AVG	10.03	24.40	46.00	-21.60
7	L1	4.9656	31.12	QP	10.08	41.20	56.00	-14.80
8	L1	4.9656	20.94	AVG	10.08	31.02	46.00	-14.98
9	L1	9.2673	29.24	QP	10.14	39.38	60.00	-20.62
10	L1	9.2673	25.29	AVG	10.14	35.43	50.00	-14.57
11	L1	20.2809	29.85	QP	10.31	40.16	60.00	-19.84
12	L1	20.2809	22.71	AVG	10.31	33.02	50.00	-16.98

**Test Mode:** Transmitting Mode



**Test Data**

**Phase Neutral Plot at 240Vac, 60Hz**



No.	P/L	Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Corrected (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)
1	N	0.2007	47.61	QP	10.03	57.64	63.58	-5.94
2	N	0.2007	33.50	AVG	10.03	43.53	53.58	-10.05
3	N	0.2670	41.16	QP	10.03	51.19	61.21	-10.02
4	N	0.2670	28.65	AVG	10.03	38.68	51.21	-12.53
5	N	2.8020	29.22	QP	10.05	39.27	56.00	-16.73
6	N	2.8020	24.18	AVG	10.05	34.23	46.00	-11.77
7	N	3.9906	31.49	QP	10.07	41.56	56.00	-14.44
8	N	3.9906	24.34	AVG	10.07	34.41	46.00	-11.59
9	N	4.6575	32.54	QP	10.08	42.62	56.00	-13.38
10	N	4.6575	22.27	AVG	10.08	32.35	46.00	-13.65
11	N	20.2653	24.75	QP	10.31	35.06	60.00	-24.94
12	N	20.2653	21.36	AVG	10.31	31.67	50.00	-18.33

## 6.7 Radiated Spurious Emissions & Restricted Band

Temperature	23 °C
Relative Humidity	55%
Atmospheric Pressure	1012mbar
Test date :	September 04, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable																
47CFR§15. 247(d), RSS210	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (μV/m)</th> </tr> </thead> <tbody> <tr> <td>0.009~0.490</td> <td>2400/F(KHz)</td> </tr> <tr> <td>0.490~1.705</td> <td>24000/F(KHz)</td> </tr> <tr> <td>1.705~30.0</td> <td>30</td> </tr> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216~960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (μV/m)	0.009~0.490	2400/F(KHz)	0.490~1.705	24000/F(KHz)	1.705~30.0	30	30 – 88	100	88 – 216	150	216~960	200	Above 960	500	<input checked="" type="checkbox"/>
Frequency range (MHz)	Field Strength (μV/m)																		
0.009~0.490	2400/F(KHz)																		
0.490~1.705	24000/F(KHz)																		
1.705~30.0	30																		
30 – 88	100																		
88 – 216	150																		
216~960	200																		
Above 960	500																		
	b)	<p>For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required</p> <p><input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down</p>	<input checked="" type="checkbox"/>																
	c)	or restricted band, emission must also comply with the radiated emission limits specified in 15.209	<input checked="" type="checkbox"/>																

<b>Test Setup</b>	 <p>The diagram shows the test setup. An EUT (Equipment Under Test) is placed on a turntable, which is positioned on a ground plane. A loop antenna is positioned 3 meters above the EUT. An RF test receiver is connected to the loop antenna. The EUT is mounted on a support unit, and the height of the EUT is 0.8m.</p>  <p>The diagram shows the test setup from a different perspective. The EUT and support units are on a turntable, which is on a ground plane. The turntable is 0.8/1.5m from the EUT. An antenna tower is positioned 3m from the EUT. The antenna height is 1-4m variable. A test receiver is connected to the antenna tower.</p>
<b>Procedure</b>	<ol style="list-style-type: none"> <li>1. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:             <ol style="list-style-type: none"> <li>a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</li> <li>b. The EUT was then rotated to the direction that gave the maximum emission.</li> <li>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</li> </ol> </li> <li>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</li> <li>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> </ol>

	<p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A

Test Plot  Yes (See below)  N/A

## Test Result:

Test Mode:	Transmitting Mode
------------	-------------------

Frequency range: 9KHz - 30MHz

Freq. (MHz)	Detection value	Factor (dB/m)	Reading (dBuV/m)	Result (dBuV/m)	Limit@3m (dBuV/m)	Margin (dB)
--	--	--	--	--	--	>20
--	--	--	--	--	--	>20

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

**Test Mode:** Transmitting Mode

**30MHz -1GHz**




**Test Data**

**Vertical Polarity Plot @3m**

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	V	119.8556	32.76	peak	13.87	22.36	1.16	25.43	43.50	-18.07	100	150
2	V	233.3487	38.59	peak	11.63	22.32	1.65	29.55	46.00	-16.45	100	157
3	V	181.2834	38.68	peak	11.07	22.26	1.38	28.87	43.50	-14.63	100	220
4	V	214.5143	36.70	peak	11.90	22.35	1.59	27.84	43.50	-15.66	200	319
5	V	552.8833	31.81	peak	18.44	21.69	2.48	31.04	46.00	-14.96	100	244
6	V	42.8998	31.36	peak	11.99	22.29	0.77	21.83	40.00	-18.17	100	36

### 30MHz -1GHz



### Test Data

#### Horizontal Polarity Plot @3m

N o.	P/ L	Frequency (MHz)	Reading (dBuV/m )	Detect or	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degr ee
1	H	119.8556	40.50	peak	13.87	22.36	1.16	33.17	43.50	-10.33	100	339
2	H	232.5318	45.08	peak	11.64	22.32	1.64	36.04	46.00	-9.96	100	211
3	H	333.6867	41.65	peak	14.31	22.20	1.96	35.72	46.00	-10.28	100	320
4	H	216.7828	41.34	peak	11.87	22.35	1.59	32.45	46.00	-13.55	100	291
5	H	277.0935	41.22	peak	12.59	22.29	1.75	33.27	46.00	-12.73	100	13
6	H	451.1350	35.85	peak	16.72	21.91	2.14	32.80	46.00	-13.20	100	16

### Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

#### Low Channel (2412 MHz) (n20 mode worst case)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4824	38.74	AV	V	33.39	7.22	48.46	30.89	54	-23.11
4824	38.86	AV	H	33.39	7.22	48.46	31.01	54	-22.99
4824	48.13	PK	V	33.39	7.22	48.46	40.28	74	-33.72
4824	47.75	PK	H	33.39	7.22	48.46	39.9	74	-34.1
6582	24.57	AV	V	35.52	7.84	48.71	19.22	54	-34.78
6582	22.97	AV	H	35.52	7.84	48.71	17.62	54	-36.38
6582	40.13	PK	V	35.52	7.84	48.71	34.78	74	-39.22
6582	39.35	PK	H	35.52	7.84	48.71	34	74	-40

#### Middle Channel (2437 MHz) (n20 mode worst case)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4874	37.8	AV	V	33.62	7.53	48.36	30.59	54	-23.41
4874	39.12	AV	H	33.62	7.53	48.36	31.91	54	-22.09
4874	48.4	PK	V	33.62	7.53	48.36	41.19	74	-32.81
4874	47.31	PK	H	33.62	7.53	48.36	40.1	74	-33.9
12458	24.67	AV	V	40.44	13.42	46.15	32.38	54	-21.62
12458	21.91	AV	H	40.44	13.42	46.15	29.62	54	-24.38
12458	39.61	PK	V	40.44	13.42	46.15	47.32	74	-26.68
12458	39.9	PK	H	40.44	13.42	46.15	47.61	74	-26.39

**High Channel (2462 MHz) (b mode worst case)**

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4924	39.59	AV	V	33.74	7.78	48.34	32.77	54	-21.23
4924	39.11	AV	H	33.74	7.78	48.34	32.29	54	-21.71
4924	47.44	PK	V	33.74	7.78	48.34	40.62	74	-33.38
4924	47.78	PK	H	33.74	7.78	48.34	40.96	74	-33.04
17958	23.51	AV	V	43.15	19.35	44.5	41.51	54	-12.49
17958	23.71	AV	H	43.15	19.35	44.5	41.71	54	-12.29
17958	39.52	PK	V	43.15	19.35	44.5	57.52	74	-16.48
17958	39.59	PK	H	43.15	19.35	44.5	57.59	74	-16.41

**Note:**

- 1, The testing has been conformed to  $10 \times 2462\text{MHz} = 24,620\text{MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
- 4, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.


## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>AC Line Conducted</b>					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
ISN	ISN T800	34373	09/24/2016	09/23/2017	<input type="checkbox"/>
Transient Limiter	LIT-153	531118	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
<b>RF conducted test</b>					
Agilent ESA-E SERIES	E4407B	MY45108319	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
Horn Antenna	BBHA9170	3145226D1	09/28/2016	09/27/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	<input checked="" type="checkbox"/>
Active Antenna (9kHz-30MHz)	AL-130	121031	10/13/2016	10/12/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>


## Annex B. EUT and Test Setup Photographs

### Annex B.i. Photograph: EUT External Photo

EUT - Front View




EUT - Rear View




Annex B.ii. Photograph: EUT Internal Photo


EUT without Shielding – Front View



EUT - Rear View




**Annex B.iii. Photograph: Test Setup Photo**




## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions ( Below 1GHz ) .



Block Configuration Diagram for Radiated Emissions ( Above 1GHz ) .



## Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

### Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Cherry mobile	Adapter	CM-1000	N/A
Lenovo	Laptop	thinkpad e40	N/A

### Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
Power Cable	Un-shielding	No	0.8m	N/A

Test Report No.	17070831-FCC-R
Page	53 of 54

## Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

## Annex E. DECLARATION OF SIMILARITY

N/A