

# RF EXPOSURE REPORT



Report No.: 17070850-FCC-H2

Supersede Report No.: N/A

Applicant	Wheredouwannago.com LLC	
Product Name	Census Smart Counter	
Model No.	CSC1	
Serial No.	CSC2	
Test Standard	FCC 2.1093:2016	
Test Date	September 14 to October 19, 2017	
Issue Date	October 20, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification		<input checked="" type="checkbox"/>
Equipment did not comply with the specification		<input type="checkbox"/>
Loren Luo	David Huang	
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

---

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.8	
5.1 RF EXPOSURE.....	8
5.2 TEST RESULT .....	9

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070850-FCC-H2	NONE	Original	October 20, 2017

## 2. Customer information

Applicant Name	Wheredouwannago.com LLC
Applicant Add	521 Garner Park Dr, Georgetown, TX 78628 USA
Manufacturer	Shenzhen ALMsound Technology Ltd
Manufacturer Add	C802 Yinxing Hi-Tech Building, Guanguang Rd, Guanlan St, Longhua Dist, Shenzhen China

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

#### **4. Equipment under Test (EUT) Information**

Description of EUT: Census Smart Counter

Main Model: CSC1

Serial Model: CSC2

Date EUT received: September 13, 2017

Test Date(s): September 14 to October 19, 2017

GSM850: 0.5dBi

PCS1900: 0.5dBi

UMTS-FDD Band V: 0.5dBi

UMTS-FDD Band II: 0.5dBi

WIFI: 0dBi

Bluetooth/BLE: 0dBi

Antenna Type: PIFA Antenna

GSM / GPRS: GMSK

EGPRS: GMSK

UMTS-FDD: QPSK

Type of Modulation: 802.11b/g/n: DSSS, OFDM

Bluetooth: GFSK, π /4DQPSK, 8DPSK

BLE: GFSK

Test Report	17070850-FCC-H2
Page	7 of 10

RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz
Number of Channels:	GSM 850: 124CH PCS1900: 299CH UMTS-FDD Band V: 102CH UMTS-FDD Band II: 277CH WIFI :802.11b/g/n(20M): 11CH WIFI :802.11n(40M): 7CH Bluetooth: 79CH BLE: 40CH
Port:	USB Port
Input Power:	Adapter: Model: TBA0050500100VU-U Input: AC100-240V~50/60Hz,150mA Output: DC5V~1000mA Battery: Spec: 1800~1850mAh Charger Voltage: 4.35~5V
Trade Name :	N/A
GPRS/EGPRS Multi-slot class	8/10/11/12
FCC ID:	2ANOB001

## 5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

### 5.1 RF Exposure

#### **Standard Requirement:**

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16}$  where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

## 5.2 Test Result

### Bluetooth Mode:

Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	3.778	3±1	4	2.512	0.78	3
	Mid	2441	3.845	3±1	4	2.512	0.78	3
	High	2480	2.948	3±1	4	2.512	0.79	3
$\pi/4$ DQPSK	Low	2402	3.548	3±1	4	2.512	0.78	3
	Mid	2441	3.633	3±1	4	2.512	0.78	3
	High	2480	2.740	3±1	4	2.512	0.79	3
8-DPSK	Low	2402	3.601	3±1	4	2.512	0.78	3
	Mid	2441	3.715	3±1	4	2.512	0.78	3
	High	2480	2.799	3±1	4	2.512	0.79	3

### WIFI Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
802.11b	Low	2412	9.10	8.7±1	9.7	9.333	2.90	3
	Mid	2437	9.08	8.7±1	9.7	9.333	2.91	3
	High	2462	<b>9.29</b>	8.7±1	9.7	9.333	2.93	3
802.11g	Low	2412	9.36	8.7±1	9.7	9.333	2.90	3
	Mid	2437	9.16	8.7±1	9.7	9.333	2.91	3
	High	2462	<b>9.38</b>	8.7±1	9.7	9.333	2.93	3
802.11n (20M)	Low	2412	<b>9.31</b>	8.7±1	9.7	9.333	2.90	3
	Mid	2437	9.12	8.7±1	9.7	9.333	2.91	3
	High	2462	9.10	8.7±1	9.7	9.333	2.93	3
802.11n (40M)	Low	2422	<b>9.62</b>	8.7±1	9.7	9.333	2.90	3
	Mid	2437	9.04	8.7±1	9.7	9.333	2.91	3
	High	2452	8.81	8.7±1	9.7	9.333	2.92	3

**BLE Mode:**

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-4.460	-5±1	-4	0.398	0.12	3
	Mid	2440	-4.209	-5±1	-4	0.398	0.12	3
	High	2480	-5.198	-5±1	-4	0.398	0.13	3

**Result:** Compliance

No SAR measurement is required.