

FCC TEST REPORT(Bluetooth)

for

London Drugs Limited

Powered speaker system

Model Number : TAPS1S

FCC ID: 2ANQE-TAPS1S

IC:23216-TAPS1S

Prepared for : London Drugs Limited

Address : Riverside Industrial Park, 12831 Horseshoe Place,
Richmond,British Columbia, Canada,V7A 4X5

Prepared by : Keyway Testing Technology Co., Ltd.

Address : Building 1, Baishun Industrial Zone, Zhangmutou Town,
Dongguan, Guangdong, China

Tel: 86-769-8718 2258

Fax: 86-769-8718 1058

Report No. : TR17090137-E-001

Date of Test : Jul.3~10, 2017

Date of Report : Jul.11, 2017

Keyway Testing Technology Co., Ltd.

Applicant:	London Drugs Limited		
Address:	Riverside Industrial Park, 12831 Horseshoe Place, Richmond, British Columbia, Canada, V7A 4X5		
Manufacturer:	London Drugs Limited		
Address:	Riverside Industrial Park, 12831 Horseshoe Place, Richmond, British Columbia, Canada, V7A 4X5		
E.U.T:	Powered speaker system		
Model Number:	TAPS1S		
Trade Name:	-----		
Date of Receipt:	Jul. 3, 2017	Date of Test:	Jul.3~10, 2017
Test Specification:	FCC Part 15, Subpart C Section 15.247: 2017 ANSI C63.10:2013 KDB558074 D01 DTS Meas Guidance v04 RSS-247 Issue 2, 2017 RSS-Gen Issue 4 November 2014		
Test Result:	The equipment under test was found to be compliance with the requirements of the standards applied.		
Issue Date: Jul. 11, 2017			
Tested by:	Reviewed by:	Approved by:	
			
Keven Wu/ Engineer	Mark Li / Supervisor	Andy Gao / Supervisor	
Other Aspects:			
None.			
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Keyway Testing Technology Co., Ltd.			

TABLE OF CONTENTS

Test Report Declaration	Page
1. TEST SUMMARY	5
2. GENERAL PRODUCT INFORMATION	6
2.1. Product Function.....	6
2.2. Description of Device (EUT).....	6
2.3. Difference between Model Numbers	6
2.4. Independent Operation Modes	6
2.5. Test Supporting System	6
2.6. Product Version.....	6
2.7. Test Facilities.....	7
2.8. List of Test and Measurement Instruments	8
3. TEST SET-UP AND OPERATION MODES.....	9
3.1. Principle of Configuration Selection	9
3.2. Block Diagram of Test Set-up.....	9
3.3. Test Operation Mode and Test Software	9
3.4. Special Accessories and Auxiliary Equipment	9
3.5. Test Environment:.....	9
4. MAXIMUM PEAK OUTPUT POWER.....	10
4.1. Limits.....	10
4.2. Test Procedure.....	10
4.3. Test Setup.....	10
4.4. Test Results.....	11
5. EMISSION TEST RESULTS	17
5.1. Conducted Emission at the Mains Terminals Test	17
5.2. Radiated Emission Test.....	22
6. 20DB OCCUPY BANDWIDTH.....	45
6.1. Limits.....	45
6.2. Test Procedure.....	45
6.3. Test Setup.....	45
6.4. Test Results.....	46
7. FREQUENCY SEPARATION.....	52
7.1. Limits.....	52
7.2. Test Procedure.....	52
7.3. Test Setup.....	52
7.4. Test Results.....	53
8. NUMBER OF HOPPING FREQUENCY	59
8.1. Limits.....	59
8.2. Test Procedure.....	59
8.3. Test Setup.....	59
8.4. Test Results.....	60
9. DWELL TIME	61
9.1. Limits.....	61
9.2. Test Procedure.....	61
9.3. Test Setup.....	61
9.4. Test Results.....	62
10. BAND EDGE COMPLIANCE TEST	68
10.1. Limits.....	68
10.2. Test Setup.....	68

10.3.	Test Procedure	69
10.4.	Test Results	70
11.	ANTENNA REQUIREMENTS	77
11.1.	Limits	77
11.2.	Test Result	77
12.	PHOTOGRAPHS OF TEST SET-UP	78
13.	PHOTOGRAPHS OF THE EUT	80

1. TEST SUMMARY

Test Items	Test Requirement	Result
Conducted Emissions	15.207/ RSS-Gen §8.8	PASS
Radiated Emissions	15.205(a)/15.209 15.247(d) / RSS-Gen §6.13	PASS
20dB Bandwidth	15.247(a)(1) / RSS-247 §5.1(1) &RSS-Gen§6.6	PASS
99% Bandwidth	RSS-247 §5.1(1) &RSS-Gen§6.6	PASS
Frequency Separation	15.247(a)(1) / RSS-247 §5.1(2)	PASS
Maximum Peak Output Power	15.247(b)(1) / RSS-247§5.4(2) &RSS-Gen§6.12	PASS
Number of Hopping Frequency	15.247(a)(1)(iii) / RSS-247 §5.1(4)	PASS
Dwell time	15.247(a)(1)(iii) / RSS-247 §5.1(4)	PASS
Emissions from out of band	15.247(d) / RSS-247 §5.5	PASS
Antenna Requirement	15.203/ RSS-Gen§8.3	PASS

2.GENERAL PRODUCT INFORMATION

2.1.Product Function

Refer to Technical Construction Form and User Manual.

2.2. Description of Device (EUT)

Product Name:	Powered speaker system
Model No.:	TAPS1S
Operation Frequency:	2402MHz ~2480MHz
Channel numbers:	79 Channels
Channel spacing	1MHz
Modulation technology:	BT BR(1Mbps): GFSK BT EDR(2Mbps): $\pi/4$ -DQPSK BT EDR(3Mbps): 8-DPSK
Bit Rate of Transmitter	1Mbps/2Mbps/3Mbps
Antenna Type:	PCB Antenna
Antenna gain:	0dBi
Power supply:	AC 120V

2.3. Difference between Model Numbers

None.

2.4.Independent Operation Modes

2.4.1. EUT work BT mode and Test mode as below:

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	Link Mode

2.5. Test Supporting System

N/A.

2.6. Product Version

Product SW version	V1.0
Product HW version	V1.1
Radio SW version	V1.1_0822
Radio HW version	V1_0224F
Test SW Version	Blue Test 3

Note: SW means software, HW means hardware.

2.7. Test Facilities

Lab Qualifications : 944 Shielded Room built by ETS-Lindgren, USA
Date of completion: March 28, 2011

966 Chamber built by ETS-Lindgren, USA
Date of completion: March 28, 2011

Certificated by TUV Rheinland, Germany.
Registration No.: UA 50207153
Date of registration: July 13, 2011

Certificated by UL, USA
Registration No.: 100567-237
Date of registration: September 1, 2011

Certificated by Intertek
Registration No.: 2011-RTL-L1-31
Date of registration: October 11, 2011

Certificated by Industry Canada
Registration No.: 9868A
Date of registration: December 8, 2011

Certificated by FCC, USA
Registration No.: 370994
Date of registration: February 21, 2012

Certificated by CNAS China
Registration No.: CNAS L5783
Date of registration: August 8, 2012

Name of Firm : Keyway Testing Technology Co., Ltd.

Site Location : Building 1, Baishun Industrial Zone, Zhangmutou
Town, Dongguan, Guangdong, China

2.8. List of Test and Measurement Instruments

2.8.1. For conducted emission at the mains terminals test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI	101156	Apr. 08,17	Apr. 08,18
Artificial Mains Network	Rohde&Schwarz	ENV216	101315	Apr. 08,17	Apr. 08,18
RF Cable	FUJIKURA	3D-2W	944 Cable	Apr. 08,17	Apr. 08,18

2.8.2. For radiated emission test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI	101156	Apr. 08,17	Apr. 08,18
Bilog Antenna	ETS-LINDGREEN	3142D	135452	Apr. 12,17	Apr. 12,18
Spectrum Analyzer	Agilent	E4411B	MY4511304	Apr. 08,17	Apr. 08,18
3m Semi-anechoic Chamber	ETS-LINDGREEN	966	KW01	Apr. 09,17	Apr. 09,18
Signal Amplifier	SONOMA	310	187016	Apr. 08,17	Apr. 08,18
Signal Amplifier	Agilent	8449B	3008A00251	Apr. 08,17	Apr. 08,18
RF Cable	IMRO	IMRO-400	966 Cable 1#	N/A	N/A
MULTI-DEVICE Controller	ETS-LINDGREEN	2090	126913	N/A	N/A
Horn Antenna	SCHWARZBECK	BBHA9170	9170-068	Apr. 12,17	Apr. 12,18
Spectrum Analyzer	Agilent	E4408B	MY44211125	Apr. 08,17	Apr. 08,18
High Pass filter	Micro	HPM50111	324216	Apr. 08,17	Apr. 08,18
Constant temperature and humidity box	GF	GTH-800-40-1P	MAA9906-005	Apr. 08,17	Apr. 08,18
Attenuation	MCE	24-10-34	BN9258	Apr. 08,17	Apr. 08,18
Loop Antenna	ARA	PLA-1030/B	1029	Apr. 08,17	Apr. 08,18


3. TEST SET-UP AND OPERATION MODES

3.1. Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the Operating Instructions.

3.2. Block Diagram of Test Set-up

System Diagram of Connections between EUT and Simulators



(EUT: Powered speaker system)

3.3. Test Operation Mode and Test Software

Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	BT Link
Test Software	BlueTest 3

3.4. Special Accessories and Auxiliary Equipment

None

3.5. Test Environment:

Ambient conditions in the test laboratory:

Items	Actual
Temperature (°C)	20~25
Humidity (%RH)	50~65

4. MAXIMUM PEAK OUTPUT POWER

4.1. Limits

FCC: For frequency hopping systems operating in the 2400-2483.5 MHz, frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

IC: RSS-247§5.4(2)

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).


4.2. Test Procedure

For Peak power

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below
 - b. Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold
- For AV power
- a. The Transmitter output (antenna port) was connected to the power meter.
 - b. Turn on the EUT and power meter and then record the power value.
- Repeat above procedures on all channels needed to be tested.



4.3. Test Setup



Peak power:







4.4. Test Results


Test data						
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	Antenna Gain	EIRP (dBm)	LIMIT (dBm)
1Mbps						
CH00	2402	4.192	30	0	4.192	36
CH39	2441	5.121	30	0	5.121	36
CH78	2480	4.280	30	0	4.280	36
2Mbps						
CH00	2402	1.644	20.96	0	1.644	36
CH39	2441	2.824	20.96	0	2.824	36
CH78	2480	1.949	20.96	0	1.949	36
3Mbps						
CH00	2402	1.779	20.96	0	1.779	36
CH39	2441	2.975	20.96	0	2.975	36
CH78	2480	2.078	20.96	0	2.078	36











5. EMISSION TEST RESULTS

5.1. Conducted Emission at the Mains Terminals Test


5.1.1. Limit 15.207 limits & RSS-Gen §8.8

Frequency MHz	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

NOTE: 1.The lower limit shall apply at the transition frequencies.
2.The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.

5.1.2. Test Setup


- 1.The EUT was put on a wooden table which was 0.8 m high above the ground and connected to the AC mains through the Artificial Mains Network (AMN). Where the mains cable supplied by the manufacture was longer than 0.8 m, the excess was folded back and forth parallel to the cable at the center so as to form a bundle no longer than 0.4 m.
- 2.The EUT was kept 0.4 m from any other earthed conducting surface. Both sides of AC line were checked to find out the maximum conducted emission levels according to the test procedure during the conducted emission test.
- 3.The frequency range from 150 kHz to 30 MHz was investigated.
- 4.The bandwidth of the test receiver was set at 9 kHz.
- 5.Pretest for all mode, The test data of the worst case condition(s) was reported on the following page.



Remark: E.U.T. :Equipment Under Test
LISN: Line Impedance Stabilization Network
Test table height: 0.8m.


5.1.3. Test Result

EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	Line
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4(worst case)




	Freq	Level	Limit	Over	
	MHz	dBuV	Line	Limit	Remark
			dBuV	dB	
1	0.505	33.45	46.00	-12.55	Average
2	0.505	43.26	56.00	-12.74	QP
3	0.585	36.63	46.00	-9.37	Average
4	0.585	42.74	56.00	-13.26	QP
5	0.641	38.52	46.00	-7.48	Average
6	0.641	45.57	56.00	-10.43	QP
7	0.665	41.37	46.00	-4.63	Average
8	0.665	47.85	56.00	-8.15	QP
9	0.686	38.25	46.00	-7.75	Average
10	0.686	44.76	56.00	-11.24	QP
11	15.552	29.27	50.00	-20.73	Average
12	15.552	41.47	60.00	-18.53	QP

EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	Neutral
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4(worst case)




	Freq	Level	Limit	Over	
	MHz	dBuV	Line	Limit	Remark
			dBuV	dB	
1	0.505	36.82	46.00	-9.18	Average
2	0.505	43.81	56.00	-12.19	QP
3	0.555	38.20	46.00	-7.80	Average
4	0.555	44.69	56.00	-11.31	QP
5	0.641	40.01	46.00	-5.99	Average
6	0.641	45.27	56.00	-10.73	QP
7	0.665	42.99	46.00	-3.01	Average
8	0.665	47.58	56.00	-8.42	QP
9	0.694	40.17	46.00	-5.83	Average
10	0.694	44.39	56.00	-11.61	QP
11	15.226	29.62	50.00	-20.38	Average
12	15.226	40.09	60.00	-19.91	QP

EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	Line
Test Voltage :	AC 240V/50Hz	Test Mode:	Mode 4(worst case)



	Freq	Level	Limit	Over	Remark
	MHz	dBuV	Line	Limit	
			dBuV	dB	
1	0.266	33.58	51.25	-17.67	Average
2	0.266	43.69	61.25	-17.56	QP
3	0.585	35.55	46.00	-10.45	Average
4	0.585	45.78	56.00	-10.22	QP
5	0.672	37.27	46.00	-8.73	Average
6	0.672	46.38	56.00	-9.62	QP
7	0.720	39.96	46.00	-6.04	Average
8	0.720	49.35	56.00	-6.65	QP
9	1.106	30.33	46.00	-15.67	Average
10	1.106	41.47	56.00	-14.53	QP
11	15.885	32.00	50.00	-18.00	Average
12	15.885	42.95	60.00	-17.05	QP

EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	Neutral
Test Voltage :	AC 240V/50Hz	Test Mode:	Mode 4(worst case)



	Freq	Level	Limit	Over	
	MHz	dBuV	Line	Limit	Remark
	MHz	dBuV	dBuV	dB	
1	0.400	33.99	47.86	-13.87	Average
2	0.400	41.32	57.86	-16.54	QP
3	0.585	36.01	46.00	-9.99	Average
4	0.585	45.78	56.00	-10.22	QP
5	0.672	38.08	46.00	-7.92	Average
6	0.672	46.57	56.00	-9.43	QP
7	0.701	40.34	46.00	-5.66	Average
8	0.701	48.17	56.00	-7.83	QP
9	0.727	39.73	46.00	-6.27	Average
10	0.727	46.18	56.00	-9.82	QP
11	15.388	30.67	50.00	-19.33	Average
12	15.388	42.08	60.00	-17.92	QP

5.2. Radiated Emission Test

5.2.1. Limit 15.209 limits

Frequency MHZ	Distance Meters	Filed Strengths Limit	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0dB(μV)/m(Peak) 54.0dB(μV)/m(Average)	

5.2.2. Restricted bands of operation

MHz	MHz	MHz	GHz
0.009-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	
All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209,all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.			

5.2.3. Test Setup

The EUT was placed on a turn table which was 0.8 m above the ground blow 1G and 1.5m above 1G. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was set 3 m away from the receiving antenna which was mounted on an antenna tower. The measuring antenna moved up and down to find out the maximum emission level. It moved from 1 m to 4 m for both horizontal and vertical polarizations.

The EUT was tested in the Chamber Site. It was pre-scanned with a Peak detector from the spectrum, and all the final readings from the test receiver were measured with the Quasi-Peak detector.

The bandwidth of the EMI test receiver is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz, the EUT was placed on a turn table which was 1.5 m above the ground, for all test, used peak detector.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

Notes: 1. Emission Level = Antenna Factor + Cable Loss + Meter Reading-Preamp Factor.

2. Measurement Uncertainty: ± 3.2 dB at a level of confidence of 95%.

3. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.


4. For emissions below 1GHz, pretest for all mode, The test data of the worst case condition(s) was reported on the following pages.

5. EUT Pre-scan X/Y/Z orientation, only worst case is presented in the report (Z orientation).


6. We pretest all modulation, The worst modulation was GFSK, the worst data was show in the report.

Radiated Emission Test-Up


Below 30MHz



30MHz- 1GHz



Above 1GHz



EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Mode:	TX
Test Voltage :	AC 120V		

Below 30MHz

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})(\text{dB})$;

Limit line = specific limits(dBuv) + distance extrapolation factor.


30MHz - 1GHz			
EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Mode:	TX-GFSK-2480
Test Voltage :	AC 120V		

Vertical



	Freq	ReadAntenna	Cable		Limit	Over	
	MHz	Level	Factor	Loss	Level	Line	Limit Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1 !	32.18	18.60	17.51	0.29	36.40	40.00	-3.60 QP
2	48.43	22.54	9.44	0.12	32.10	40.00	-7.90 QP
3	58.13	26.16	7.58	0.13	33.87	40.00	-6.13 QP
4 !	91.17	28.68	9.16	0.16	38.00	43.50	-5.50 QP
5 !	104.69	29.15	9.46	0.18	38.79	43.50	-4.71 QP
6	195.87	18.43	10.63	0.30	29.36	43.50	-14.14 QP

Horizontal




	Freq	Read Level	Antenna Factor	Cable Loss	Level	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	32.91	7.54	17.08	0.27	24.89	40.00	-15.11	QP
2	110.51	23.94	9.26	0.19	33.39	43.50	-10.11	QP
3	131.85	22.38	8.32	0.22	30.92	43.50	-12.58	QP
4	145.43	20.12	8.73	0.23	29.08	43.50	-14.42	QP
5	175.04	26.98	10.25	0.24	37.47	43.50	-6.03	QP
6	188.11	23.78	10.16	0.27	34.21	43.50	-9.29	QP

NOTE: 1. Absolute Level= Reading Level+Antenna Factor+Cable Loss.
2. Over Limit= Absolute Level – Limit.
3. GFSK (CH78 channel) is the worst mode, only worst data is presented in the report.


30MHz - 1GHz			
EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Mode:	TX-GFSK-2480
Test Voltage :	AC 240V		

Vertical



	Freq	Read Level	Antenna Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1 !	34.85	20.56	15.94	0.23	36.73	40.00	-3.27	QP
2 !	47.46	25.22	9.84	0.12	35.18	40.00	-4.82	QP
3 !	84.32	27.75	8.48	0.15	36.38	40.00	-3.62	QP
4 !	88.20	28.51	8.90	0.16	37.57	43.50	-5.93	QP
5	104.69	22.49	9.46	0.18	32.13	43.50	-11.37	QP
6	159.98	21.21	9.20	0.23	30.64	43.50	-12.86	QP

Horizontal



	Freq	ReadAntenna	Cable		Limit	Over	
	Level	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1	34.85	10.80	15.94	0.23	26.97	40.00	-13.03 QP
2	85.29	28.23	8.58	0.16	36.97	40.00	-3.03 QP
3	107.60	18.78	9.37	0.18	28.33	43.50	-15.17 QP
4	131.85	19.33	8.32	0.22	27.87	43.50	-15.63 QP
5	156.10	20.54	9.12	0.23	29.89	43.50	-13.61 QP
6	167.74	19.71	9.90	0.23	29.84	43.50	-13.66 QP

Above 1GHz			
EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Mode:	TX-GFSK
Test Voltage :	AC 120V		

Frequency (MHz)	Meter Reading (dBμV)	Antenna Factor (dB)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
TX-2402									
4804	27.68	32.94	11.94	27.49	45.07	54	-8.93	Average	Vertical
4804	37.14	32.94	11.94	27.49	54.53	74	-19.47	peak	Vertical
7206	32.06	25.28	18.04	27.94	47.44	54	-6.56	Average	Vertical
7206	41.25	25.28	18.04	27.94	56.63	74	-17.37	peak	Vertical
4804	27.85	32.94	11.94	27.49	45.24	54	-8.76	Average	Horizontal
4804	38.19	32.94	11.94	27.49	55.58	74	-18.42	peak	Horizontal
7206	32.54	25.28	18.04	27.94	47.92	54	-6.08	Average	Horizontal
7206	41.62	25.28	18.04	27.94	57.00	74	-17.00	peak	Horizontal
TX-2441									
4882	31.58	32.11	12.15	27.53	48.31	54	-5.69	Average	Vertical
4882	42.57	32.11	12.15	27.53	59.30	74	-14.70	peak	Vertical
7323	32.84	24.33	18.09	27.96	47.30	54	-6.70	Average	Vertical
7323	41.47	24.33	18.09	27.96	55.93	74	-18.07	peak	Vertical
4882	32.05	32.11	12.15	27.53	48.78	54	-5.22	Average	Horizontal
4882	39.98	32.11	12.15	27.53	56.71	74	-17.29	peak	Horizontal
7323	30.08	24.33	18.09	27.96	44.54	54	-9.46	Average	Horizontal
7323	41.54	24.33	18.09	27.96	56.00	74	-18.00	peak	Horizontal
TX-2480									
4960	31.26	31.32	12.31	27.58	47.31	54	-6.69	Average	Vertical
4960	41.45	31.32	12.31	27.58	57.50	74	-16.50	peak	Vertical
7440	29.51	24.38	18.16	27.99	44.06	54	-9.94	Average	Vertical
7440	39.62	24.38	18.16	27.99	54.17	74	-19.83	peak	Vertical
4960	27.32	31.32	12.31	27.58	43.37	54	-10.63	Average	Horizontal
4960	38.36	31.32	12.31	27.58	54.41	74	-19.59	peak	Horizontal
7440	31.45	24.38	18.16	27.99	46.00	54	-8.00	Average	Horizontal
7440	41.68	24.38	18.16	27.99	56.23	74	-17.77	peak	Horizontal

NOTE:1.Absolute Level= ReadingLevel+antenna Factor+cable loss-preamp factor.

2.Over Limit= Absolute Level – Limit.

3.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported.

4.EUT Pre-scan X/Y/Z orientation, only worst case is presented in the report (Z orientation)

Above 1GHz			
EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Mode:	TX-8-DPSK
Test Voltage :	AC 120V		

Frequency	Meter Reading	Antenna Factor	Cable loss	Preamplifier factor	Emission Level	Limits	Margin	Detector Type	Comment
(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
TX-2402									
4804	30.24	32.94	11.94	27.49	47.63	54	-6.37	Average	Vertical
4804	41.56	32.94	11.94	27.49	58.95	74	-15.05	peak	Vertical
7206	31.85	25.28	18.04	27.94	47.23	54	-6.77	Average	Vertical
7206	41.76	25.28	18.04	27.94	57.14	74	-16.86	peak	Vertical
4804	31.69	32.94	11.94	27.49	49.08	54	-4.92	Average	Horizontal
4804	40.79	32.94	11.94	27.49	58.18	74	-15.82	peak	Horizontal
7206	28.63	25.28	18.04	27.94	44.01	54	-9.99	Average	Horizontal
7206	38.64	25.28	18.04	27.94	54.02	74	-19.98	peak	Horizontal
TX-2441									
4882	31.25	32.11	12.15	27.53	47.98	54	-6.02	Average	Vertical
4882	41.57	32.11	12.15	27.53	58.30	74	-15.70	peak	Vertical
7323	31.29	24.33	18.09	27.96	45.75	54	-8.25	Average	Vertical
7323	45.38	24.33	18.09	27.96	59.84	74	-14.16	peak	Vertical
4882	30.68	32.11	12.15	27.53	47.41	54	-6.59	Average	Horizontal
4882	42.25	32.11	12.15	27.53	58.98	74	-15.02	peak	Horizontal
7323	31.27	24.33	18.09	27.96	45.73	54	-8.27	Average	Horizontal
7323	41.39	24.33	18.09	27.96	55.85	74	-18.15	peak	Horizontal
TX-2480									
4960	32.06	31.32	12.31	27.58	48.11	54	-5.89	Average	Vertical
4960	41.32	31.32	12.31	27.58	57.37	74	-16.63	peak	Vertical
7440	30.14	24.38	18.16	27.99	44.69	54	-9.31	Average	Vertical
7440	40.52	24.38	18.16	27.99	55.07	74	-18.93	peak	Vertical
4960	31.57	31.32	12.31	27.58	47.62	54	-6.38	Average	Horizontal
4960	40.89	31.32	12.31	27.58	56.94	74	-17.06	peak	Horizontal
7440	31.42	24.38	18.16	27.99	45.97	54	-8.03	Average	Horizontal
7440	42.51	24.38	18.16	27.99	57.06	74	-16.94	peak	Horizontal

NOTE:1.Absolute Level= ReadingLevel+antenna Factor+cable loss-preamplifier factor.

2.Over Limit= Absolute Level – Limit.


3.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported.

4.EUT Pre-scan XYZ orientation, only worst case is presented in the report (Z orientation)

For radiated Bandedge test as follows:


1M bps			
EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Mode:	TX-2402
Test Voltage :	AC 120V		

Vertical



	Freq	ReadAntenna Level	Cable Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2390.00	29.85	28.72	3.36	35.61	74.00	-38.39	Peak
2	2400.00	45.45	28.72	3.38	51.23	74.00	-22.77	Peak

Horizontal



	Freq	ReadAntenna	Cable		Limit	Over	
	Level	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1	2390.00	32.68	28.72	3.36	38.44	74.00	-35.56 Peak
2	2400.00	46.59	28.72	3.38	52.37	74.00	-21.63 Peak

NOTE: 1.Absolute Level= Reading Level+Antenna Factor+Cable Loss-Preamplifier Factor,


Over Limit= Absolute Level – Limit;

2.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported.

3.If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.


1M bps			
EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Mode:	TX-2480
Test Voltage :	AC 120V		

Vertical



	Read	Antenna	Cable		Limit	Over	
Freq	Level	Factor	Loss	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1 2483.50	40.43	28.79	3.48	46.36	74.00	-27.64	Peak

Horizontal




	Freq	ReadAntenna Level	Cable Factor	Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2483.50	38.54	28.79	3.48	44.47	74.00	-29.53	Peak

NOTE: 1.Absolute Level= Reading Level+Antenna Factor+Cable Loss-Preamplifier Factor,
Over Limit= Absolute Level – Limit;
2.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported.
3.If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.


2M bps			
EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Mode:	TX-2402
Test Voltage :	AC 120V		

Vertical



	Freq	Read Level	Antenna Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2390.00	29.28	28.72	3.36	35.04	74.00	-38.96	Peak
2	2400.00	44.21	28.72	3.38	49.99	74.00	-24.01	Peak

Horizontal




	Freq	ReadLevel	Antenna Factor	Cable Loss	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2390.00	32.66	28.72	3.36	38.42	74.00	-35.58	Peak
2	2400.00	47.93	28.72	3.38	53.71	74.00	-20.29	Peak

NOTE: 1.Absolute Level= Reading Level+Antenna Factor+Cable Loss-Preamplifier Factor,
Over Limit= Absolute Level – Limit;
2.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported.
3.If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.


2M bps			
EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Mode:	TX-2480
Test Voltage :	AC 120V		

Vertical



	Freq	Read Level	Antenna Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2483.50	40.47	28.79	3.48	46.40	74.00	-27.60	Peak

Horizontal



	Freq	ReadAntenna	Cable		Limit	Over	
	Level	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1	2483.50	39.36	28.79	3.48	45.29	74.00	-28.71 Peak

NOTE: 1.Absolute Level= Reading Level+Antenna Factor+Cable Loss-Preamplifier Factor,


Over Limit= Absolute Level – Limit;

2.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported.

3.If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.


3M bps			
EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Mode:	TX-2402
Test Voltage :	AC 120V		

Vertical



	Freq	Read Level	Antenna Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2390.00	34.92	28.72	3.36	40.68	74.00	-33.32	Peak
2	2400.00	32.91	28.72	3.38	38.69	54.00	-15.31	Average
3	2400.00	50.82	28.72	3.38	56.60	74.00	-17.40	Peak

Horizontal



	Freq	ReadAntenna	Cable		Limit	Over	
	Level	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1	2390.00	32.72	28.72	3.36	38.48	74.00	-35.52 Peak
2	2400.00	46.79	28.72	3.38	52.57	74.00	-21.43 Peak

NOTE: 1.Absolute Level= Reading Level+Antenna Factor+Cable Loss-Preamplifier Factor,


Over Limit= Absolute Level – Limit;

2.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported.

3.If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.


3M bps			
EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Mode:	TX-2480
Test Voltage :	AC 120V		

Vertical



	Freq	Read Level	Antenna Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2483.50	36.95	28.79	3.48	42.88	74.00	-31.12	Peak

Horizontal



	Read	Antenna	Cable		Limit	Over	
Freq	Level	Factor	Loss	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2483.50	40.72	28.79	3.48	46.65	74.00	-27.35 Peak

NOTE: 1.Absolute Level= Reading Level+Antenna Factor+Cable Loss-Preamplifier Factor,
Over Limit= Absolute Level – Limit;

2.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported.

3.If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.

Spurious Emission in Restricted Band:(1-25G)

All the modulation modes have been tested and all other emissions more than 20dB below the limit, the worst result was report as below:

Polar (H/V)	Frequency	Meter Reading	Antenna Factor	Cable loss	Preamp factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1Mbps Non-hopping									
Vertical	3262	36.57	30.26	10.68	26.63	50.88	74	-23.12	PK
Horizontal	3262	38.56	30.26	10.68	26.63	52.87	74	-21.13	PK
Vertical	4032	31.69	31.55	10.52	27.02	46.74	74	-27.26	PK
Horizontal	4032	34.28	31.55	10.52	27.02	49.33	74	-24.67	PK
1Mbps hopping									
Vertical	3351	31.67	30.34	10.78	26.67	46.12	74	-27.88	PK
Horizontal	3351	35.42	30.34	10.78	26.67	49.87	74	-24.13	PK
Vertical	4130	31.53	30.69	10.95	27.08	46.09	74	-27.91	PK
Horizontal	4130	32.25	30.69	10.95	27.08	46.81	74	-27.19	PK

6. 20DB OCCUPY BANDWIDTH

6.1. Limits

According to FCC Section 15.247(a)(1)& RSS-247 §5.1(1)&RSS-Gen§6.6, the 20dB bandwidth is known as the 99% emission bandwidth, or 20dB bandwidth($10 \cdot \log 1\% = 20\text{dB}$)taking the RF output power

6.2. Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum, during the measurement, the Bluetooth module of the EUT is activated and controlled by the software, and is set to operate under test mode transmitting.

2. Set the spectrum analyzer:

Span: approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel

RBW $\geq 1\%$ of the 20dB bandwidth


VBW $\geq$ RBW

Sweep=auto

Detector function=peak

Trace=max hold

6.3. Test Setup




6.4. Test Results


EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	58%
Pressure:	1012 hPa	Test Voltage :	AC 120V
Test Mode :	CH00 / CH39 /C78(1Mbps)		

Frequency	20dB Bandwidth (kHz)	99% Bandwidth (KHz)	Result
2402 MHz	903.1	840.11	PASS
2441 MHz	878.7	832.94	PASS
2480 MHz	875.9	837.24	PASS

Test plot as follows:



CH39 -1Mbps




CH78 -1Mbps




EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	58%
Pressure:	1012 hPa	Test Voltage :	AC 120V
Test Mode :	CH00 / CH39 /C78(2Mbps)		

Frequency	20dB Bandwidth (MHz)	99% Bandwidth (MHz)	Result
2402 MHz	1.217	1.1613	PASS
2441 MHz	1.215	1.1607	PASS
2480 MHz	1.216	1.1606	PASS

Test plot as follows:



CH39-2Mbps




CH78-2Mbps




EUT:	Powered speaker system	Model Name :	TAPS1S
Temperature:	20 °C	Relative Humidity:	58%
Pressure:	1012 hPa	Test Voltage :	AC 120V
Test Mode :	CH00 / CH39 /CH78(3Mbps)		

Frequency	20dB Bandwidth (MHz)	99% Bandwidth (MHz)	Result
2402 MHz	1.206	1.1404	PASS
2441 MHz	1.208	1.1417	PASS
2480 MHz	1.203	1.1378	PASS

Test plot as follows:



CH39-3Mbps



CH78-3Mbps

