

Radio Frequency Exposure Report

On Behalf of

Novomill Creative Co., Ltd

213 6D-8/Rm 6D-8, Block 213, Chegongmiao Industrial park, Futian District,
ShenZhen, China

| | |
|-----------------|--|
| Product Name: | E-Button portable bluetooth speaker |
| Model/Type No.: | ES001 |
| Trade Name: | Novomill |
| FCC ID: | 2ANQJ-ES001 |
| Prepared By: | Shenzhen Hongcai Testing Technology Co., Ltd. 1st-3rd Floor, Building C, Shuanghuan Xin Yi Dai Hi-Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen, Guangdong, China Tel: +86-755-86337020 Fax:+86-755-86337028 |
| Report Number: | HCT17GR180E-3 |
| Tested Date: | July 07 ~ 11, 2017 |
| Issued Date: | July 11, 2017 |
| Tested By: | Michelle Shi/ <i>Michelle Shi</i> |

Reviewed By:

Owen Yang

Approved By:

Tony Wu

Owen.Yang
EMC Technical Supervisor

Tony Wu
EMC Technical Manager

TABLE OF CONTENTS

| | |
|--|----------|
| 1. GENERAL INFORMATION..... | 3 |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 3 |
| 1.2 APPLICABLE STANDARD | 4 |
| 1.3 LIMIT | 4 |
| 1.4 RF EXPOSURE | 5 |
| 1.5 CONCLUSION | 6 |



1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

| | |
|--------------------------|--|
| Applicant: | Novomill Creative Co., Ltd |
| Address of applicant: | 213 6D-8/Rm 6D-8, Block 213, Chegongmiao Industrial park, Futian District, ShenZhen, China |
| Manufacturer : | Novomill Creative Co., Ltd |
| Address of manufacturer: | 213 6D-8/Rm 6D-8, Block 213, Chegongmiao Industrial park, Futian District, ShenZhen, China |

General Description of E.U.T

| Items | Description |
|-------------------------|-------------------------------------|
| EUT Description: | E-Button portable bluetooth speaker |
| Model No.: | ES001 |
| Supplementary ModelNo.: | N/A |
| Trade Name: | Novomill |
| Frequency Band: | 2402~2480MHz |
| BT Module: | EDR,BLE |
| Number of Channels: | (EDR 79), (BLE 40) |
| Type of Modulation: | GFSK |
| Antenna Gain | 0dBi |
| Antenna Type: | PCB Antenna |
| Rated Voltage: | DC 3.7V from battery |

Remark: * The test data gathered are from the production sample provided by the manufacturer.

1.2 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §RSS-102, Devices that have a radiating element normally operating at separation distances greater than 20 cm between the user and the device shall undergo an RF exposure evaluation. SAR evaluation may be performed in lieu of an RF exposure evaluation for devices operating below 6 GHz with a separation distance of greater than 20 cm between the user and the device.

According to §1.1310, KDB447498 and §2.1093 RF exposure is required.

OET Bulletin 65 Supplement C [June 2001]: Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields

KDB447498 D01 General RF Exposure Guidance v06: RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices

1.3 Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²⁸ The minimum test separation distance defined in 4.1 f) is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander. To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified, typically in the SAR measurement or SAR analysis report, by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops and tablets, etc.²⁹"

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,} \text{ where}$$


- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation³¹
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance

is $< 5\text{mm}$, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion. According to KDB447498 D01 General RF Exposure Guidance v06 Appendix A: SAR Test Exclusion Thresholds for 100 MHz-6 GHz and $\leq 50\text{ mm}$, Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

| MHz | 5 | 10 | 15 | 20 | 25 | mm |
|------|----|----|-----|-----|-----|--|
| 150 | 39 | 77 | 116 | 155 | 194 | <i>SAR Test Exclusion Threshold (mW)</i> |
| 300 | 27 | 55 | 82 | 110 | 137 | |
| 450 | 22 | 45 | 67 | 89 | 112 | |
| 835 | 16 | 33 | 49 | 66 | 82 | |
| 900 | 16 | 32 | 47 | 63 | 79 | |
| 1500 | 12 | 24 | 37 | 49 | 61 | |
| 1900 | 11 | 22 | 33 | 44 | 54 | |
| 2450 | 10 | 19 | 29 | 38 | 48 | |
| 3600 | 8 | 16 | 24 | 32 | 40 | |
| 5200 | 7 | 13 | 20 | 26 | 33 | |
| 5400 | 6 | 13 | 19 | 26 | 32 | |
| 5800 | 6 | 12 | 19 | 25 | 31 | |

1.4 RF Exposure



TEST RESULTS Max BLE MODE:

| Test Frequency (MHz) | Output Power (dBm) | Output Power including Power Drift (dBm) | Output Power including Power Drift (mW) | Separation Distance (mm) | SAR test exclusion thresholds | Verdict |
|----------------------|--------------------|--|---|--------------------------|-------------------------------|---------|
| 2402 | -10.25 | -11.27 | 0.1 | 5 | 10 | PASS |
| 2440 | -12.04 | -12.58 | 0.1 | 5 | 10 | PASS |
| 2480 | -12.91 | -13.35 | 0.1 | 5 | 10 | PASS |

Note: The output power including power drift is come from tune-up tolerance: $\pm 0.5\text{dBm}$.
EDR mode and BLE mode can not be transmitted at the same time.

1.5 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06. and the SAR is not required.

