



ISED LISTED
REGISTRATION NUMBER
4621A-4

Test report No:
NIE: 58953RRF.001A2

Test report

USA FCC Part 15.247, 15.209

CANADA RSS-247, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz.

Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices. General Requirements and Information for the Certification of Radio Apparatus.

Identification of item tested	Wireless communication panel
Trademark	VLT®
Model and /or type reference	LCP 103
Other identification of the product	FCC ID: 2ANSELCP-103 IC: 24548-LCP103
Features	Not provided data
Applicant	DANFOSS DRIVES Ulsnaes 1, DK-6300 Graasten, Denmark
Test method requested, standard	USA FCC Part 15.247 10-1-17 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 10-1-17 Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 5 (April 2018). Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05 dated August 24, 2018. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Summary	IN COMPLIANCE

Approved by (name / position & signature)	A. Llamas RF Lab. Manager
Date of issue	2019-01-24
Report template No	FDT08_21

Index

Competences and guarantees4

General conditions4

Uncertainty4

Usage of samples5

Test sample description6

Identification of the client.....6

Testing period and place.....6

Document history6

Environmental conditions7

Remarks and comments8

Testing verdicts.....9

Summary9

Appendix A: Test results.10

Competences and guarantees

DEKRA Testing and Certification is a testing laboratory accredited by the National Accreditation Body (ENAC - Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: ISED 4621A-4.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification at the time of performance of the test.

DEKRA Testing and Certification is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification internal document PODT000.

Usage of samples

Samples undergoing test have been selected by: the client.

Sample M/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
58953/001	Wireless communication panel	LCP 103	---	2018-10-31

Auxiliary devices:

Control N°	Description	Model	Serial N°	Date of reception
58953/003	UFL to SMA cable	---	---	2018-10-31
58953/005	USB to RS-485 cable	---	---	2018-10-31
58953/006	RS-485 cable	---	---	2018-10-31
58953/007	Power supply cable	---	---	2018-10-31

1. Sample M/01 has undergone the following test(s):

All conducted tests indicated in Appendix A.

Sample M/02 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
58953/001	Wireless communication panel	LCP 103	---	2018-10-31

Auxiliary devices:

Control N°	Description	Model	Serial N°	Date of reception
58953/005	USB to RS-485 cable	---	---	2018-10-31
58953/006	RS-485 cable	---	---	2018-10-31
58953/007	Power supply cable	---	---	2018-10-31

1. Sample M/02 has undergone the following test(s):

All radiated tests indicated in Appendix A.

Test sample description

Description of product	VLT® Wireless Communication Panel LCP 103		
Rated power supply	Voltage and Frequency		
	☐	AC:	
	☒	DC:4.75-5.25Vdc, nominal 5Vdc	
Software version	SW version(product) 1.9 ; SW version(radio) SDK 1.3.0		
Hardware version	B4		
Mounting position	☐	Table top equipment	
	☐	Wall/Ceiling mounted equipment	
	☐	Floor standing equipment	
	☐	Hand-held equipment	
	☒	Other: Danfoss drives mounted equipment	
Accessories (not part of the test item)	Description	Type	Manufacturer
	UFL to SMA cable (58953/003)	---	---
	USB to RS-485 cable (58953/005)	---	---
	RS-485 cable (58953/006)	---	---
	Power supply cable (58953/007)	---	---

Identification of the client

WAPICE OY

Yliopistonranta 5, 3rd floor, FI-65200 Vaasa Finland.

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2018-11-14
Date (finish)	2018-11-19

Document history

Report number	Date	Description
58953RRF.001	2019-01-24	First release
58953RRF.001A1	2018-11-26	Second release: hardware version, model cable description
58953RRF.001A2	2019-01-24	Third release: Included information about the EUT data rate selected for the tests

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω
Normal site attenuation (NSA)	< ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 35 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω

Remarks and comments

The tests have been performed by the technical personnel: José Alberto Aranda and Ignacio Cabra.

Used instrumentation:

Conducted Measurements

		Last Cal. date	Cal. due date
1.	Spectrum analyser Agilent PSA E4440A	2017/10	2019/10
2.	DC power supply R&S NGPE 40/40	2018/02	2021/02

Radiated Measurements

		Last Cal. date	Cal. due date
1.	Semianechoic Absorber Lined Chamber ETS FACT3 200STP	N.A.	N.A.
2.	BiconicalLog antenna ETS LINDGREN 3142E	2018/07	2021/07
3.	Multi Device Controller MESSTECHNIK DAV-RR	N.A.	N.A.
4.	Double-ridge Guide Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D	2018/01	2021/01
5.	Broadband Horn antenna 18-40 GHz SCHWARZBECK BBHA 9170	2017/03	2020/03
6.	EMI Test Receiver R&S ESR7	2017/08	2019/08
7.	Spectrum analyser Rohde & Schwarz FSV40	2018/02	2020/02
8.	RF pre-amplifier 30 MHz-6 GHz Bonn Elektronik BLNA 0360-01N	2018/07	2019/07
9.	RF pre-amplifier 1-18 GHz Bonn Elektronik BLMA 0118-3A	2018/03	2019/03
10.	RF pre-amplifier 18-40 GHz NARDA JS44-18004000-33-8P	2018/02	2019/02

Testing verdicts

Not applicable :	N/A
Pass :	P
Fail :	F
Not measured :	N/M

Summary

FCC PART 15 PARAGRAPH / RSS-247			
Requirement – Test case		Verdict	Remark
Section 15.247 Subclause (a) (2) / RSS-247 5.2. (a)	6 dB Bandwidth	P	
Section 15.247 Subclause (b) / RSS-247 5.4. (d)	Maximum output power and antenna gain	P	
Section 15.247 Subclause (d) / RSS-247 5.5	Emission limitations conducted (Transmitter)	P	
Section 15.247 Subclause (d) / RSS-247 5.5.	Band-edge emissions compliance (Transmitter)	P	
Section 15.247 Subclause (e) / RSS-247 5.2. (b)	Power spectral density	P	
Section 15.247 Subclause (d) / RSS-247 5.5.	Emission limitations radiated (Transmitter)	P	
<u>Supplementary information and remarks:</u>			
The tests were requested only for WiFi mode 802.11n20.			

Appendix A: Test results.

TEST CONDITIONS.....	12
Occupied Bandwidth	14
Section 15.247 Subclause (a) (2) / RSS-247 5.2. (a). 6 dB Bandwidth	17
Section 15.247 Subclause (b) / RSS-247 5.4. (d). Maximum output power and antenna gain	20
Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations conducted (Transmitter).....	23
Section 15.247 Subclause (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter)	26
Section 15.247 Subclause (e) / RSS-247 5.2. (b) Power spectral density	27
Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations radiated (Transmitter)	31

TEST CONDITIONS

Power supply (V):

Vnominal = 5.0 Vdc

Type of power supply = DC voltage from external power supply.

Type of antenna = Internal antenna.

Declared Gain for antenna (maximum) = 1.9 dBi.

TEST FREQUENCIES:

Lowest channel (1): 2412 MHz

Middle channel (6): 2437 MHz

Highest channel (11): 2462 MHz

The sample was used to configure the EUT to continuously transmit at a specified output power in all channels.

The tests were requested only for WiFi mode 802.11n20.

The data rate corresponding to the MCS0 index (BPSK at 6.50 Mbps) for 802.11n20 was selected based on preliminary testing that identified the data rates corresponding to the worst cases for the performed tests.

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is connected to the spectrum analyzer



RADIATED MEASUREMENTS


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1 m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Radiated measurements setup $f < 1$ GHz



Radiated measurements setup $f > 1$ GHz



Occupied Bandwidth


RESULTS:

(see next plots).


Mode N20

	Lowest frequency	Middle frequency	Highest frequency
	2412 MHz	2437 MHz	2462 MHz
99% bandwidth (MHz)	17.626	18.840	17.596
-26 dBc bandwidth (MHz)	24.271	30.000	25.263
Measurement uncertainty (kHz)	<± 5		


Lowest Channel



Middle Channel



Highest channel



Section 15.247 Subclause (a) (2) / RSS-247 5.2. (a). 6 dB Bandwidth

SPECIFICATION

The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS:

6 dB Bandwidth (see next plots).


Mode N20

	Lowest frequency 2412 MHz	Middle frequency 2437 MHz	Highest frequency 2462 MHz
6 dB Spectrum bandwidth (MHz)	15.140	15.140	15.140
Measurement uncertainty (kHz)	<±8		


Verdict: PASS

6 dB BANDWIDTH.


Lowest Channel



Middle Channel



Highest Channel



Section 15.247 Subclause (b) / RSS-247 5.4. (d). Maximum output power and antenna gain

SPECIFICATION

For systems using digital modulation in the 2400-2483.5 MHz band: 1 watt (30 dBm).

The e.i.r.p. shall not exceed 4 W (36 dBm) (Canada).

RESULTS:

The maximum conducted output power was measured using the method according to point 8.3.2 (Maximum conducted (average) output power) of Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05 dated August 24, 2018.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

MAXIMUM OUTPUT POWER. See next plots.

Maximum declared antenna gain: 1.9 dBi.

Mode N20: AVG Conducted Output Power:


	Lowest frequency 2412 MHz	Middle frequency 2437 MHz	Highest frequency 2462 MHz
Maximum conducted power (dBm)	9.90	13.44	10.25
Maximum EIRP power (dBm)	11.80	15.34	12.15
Measurement uncertainty (dB)	<±0.78		

The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.


Verdict: PASS

CONDUCTED PEAK POWER.


Lowest frequency



Middle frequency



Highest frequency



Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations conducted (Transmitter)

SPECIFICATION

In any 100 kHz bandwidth outside the frequency band in which the digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.

RESULTS:

Reference Level Measurement

Mode N20


	Lowest frequency 2412 MHz	Middle frequency 2437 MHz	Highest frequency 2462 MHz
Reference Level Measurement (dBm)	0.06	4.18	0.16
Measurement uncertainty (dB)	<±0.78		

No radiated spurious emissions were found at less than 20 dB respect to the limit for all three channels.

Measurement uncertainty (dB): < 0.78


Verdict: PASS

Lowest frequency




Note: The peak shown in the plot above the limit is the carrier frequency.

Middle frequency



Note: The peak shown in the plot above the limit is the carrier frequency.

Highest frequency



Note: The peak shown in the plot above the limit is the carrier frequency.

Section 15.247 Subclause (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter)

SPECIFICATION

In any 100 kHz bandwidth outside the frequency band in which the digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.


RESULTS:

Note: Radiated measurements were used to show compliance with the limits in the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz.

LOW FREQUENCY SECTION. CONDUCTED.

Mode N20

See next plot.



Measurement uncertainty (dB)	< ±0.78
------------------------------	---------

Verdict: PASS

Section 15.247 Subclause (e) / RSS-247 5.2. (b) Power spectral density

SPECIFICATION

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS:

The maximum power spectral density level in the fundamental emission was measured using the method according to point 8.4 according to the Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05 dated August 24, 2018.


Power spectral density (see next plots).

	Lowest frequency 2412 MHz	Middle frequency 2437 MHz	Highest frequency 2462 MHz
Power spectral density (dBm)	-10.055	-6.201	-9.855
Measurement uncertainty (dB)	<±0.78		


Verdict: PASS

POWER SPECTRAL DENSITY


Lowest Channel



Middle Channel



Highest Channel



Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations radiated (Transmitter)

SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength (µV/m)	Field strength (dBµV/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz-1000 MHz.

The spurious signals detected do not depend on the operating channel.

Spurious levels operating (radiated) closest to limit.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dBμV/m)	Measurement Uncertainty (dB)
239.86	V	Quasi-peak	29.20	± 3.88
337.571	H	Quasi-peak	30.80	± 3.88
525.007	V	Quasi-peak	37.10	± 3.88

Frequency range 1 GHz-25 GHz

The results in the next tables show the maximum measured levels in the 1-25 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Spurious signals with peak levels above the average limit (54 dBμV/m at 3 m) are measured with average detector for checking compliance with the average limit.

CHANNEL 1: LOW (2412 MHz). Out-of-band spurious emissions in the 1-25 GHz and inside restricted band 2.31-2.39 GHz.

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dBμV/m)	Measurement Uncertainty (dB)
2.33297	H	Peak	54.31	± 3.70
		Average	42.75	± 3.70
2.56723	H	Peak	56.62	± 3.70
		Average	46.15	± 3.70
3.21583	V	Peak	48.80	± 3.70
4.01710	V	Peak	57.13	± 3.70
		Average	47.68	± 3.70
4.82537	H	Peak	49.22	± 3.70
5.62757	H	Peak	40.73	± 3.70
6.43210	H	Peak	46.66	± 3.70
12.86417	H	Peak	51.59	± 3.70
19.29605	H	Peak	41.73	± 3.70

CHANNEL 6: MIDDLE (2437 MHz). Out-of-band spurious emissions in the 1-25 GHz.


Spurious frequency (GHz)	Polarization	Detector	Emission Level (dBμV/m)	Measurement Uncertainty (dB)
2.35917	V	Peak	57.65	± 3.70
		Average	46.32	± 3.70
2.54990	H	Peak	58.81	± 3.70
		Average	49.48	± 3.70
3.24943	V	Peak	45.82	± 3.70
4.06283	V	Peak	59.98	± 3.70
		Average	51.23	± 3.70
4.86970	H	Peak	50.38	± 3.70
5.69010	V	Peak	46.03	± 3.70
6.49883	H	Peak	46.81	± 3.70
7.30850	V	Peak	48.99	± 3.70
12.99717	V	Peak	50.68	± 3.70
19.49585	H	Peak	41.43	± 3.70

CHANNEL 11: HIGH (2462 MHz). Out-of-band spurious emissions in the 1-25 GHz and inside restricted band 2.4835-2.5 GHz.

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dBμV/m)	Measurement Uncertainty (dB)
2.36563	V	Peak	56.50	± 3.70
		Average	46.04	± 3.70
2.48366	V	Peak	61.52	± 3.70
		Average	46.90	± 3.70
2.55930	V	Peak	56.98	± 3.70
		Average	47.11	± 3.70
3.28257	V	Peak	46.33	± 3.70
4.10577	V	Peak	57.17	± 3.70
		Average	49.38	± 3.70
4.92150	H	Peak	48.57	± 3.70
5.74470	V	Peak	42.83	± 3.70
6.56510	H	Peak	47.74	± 3.70
7.38830	V	Peak	45.93	± 3.70
13.13063	H	Peak	51.54	± 3.70
19.69625	H	Peak	40.12	± 3.70

Verdict: PASS


FREQUENCY RANGE 30 MHz-1000 MHz.



(This plot is valid for all three channels).


FREQUENCY RANGE 1 GHz to 3 GHz.

CHANNEL 1 (2412 MHz).




Note: The peak shown in the plot above the limit is the carrier frequency.

CHANNEL 6 (2437 MHz).



Note: The peak shown in the plot above the limit is the carrier frequency.


CHANNEL 11 (2462 MHz).




Note: The peak shown in the plot above the limit is the carrier frequency.

FREQUENCY RANGE 3 GHz to 17 GHz.


CHANNEL 1 (2412 MHz).



CHANNEL 6 (2437 MHz).




CHANNEL 11 (2462 MHz).




FREQUENCY RANGE 17 GHz to 26 GHz.


CHANNEL 1 (2412 MHz).



CHANNEL 6 (2437 MHz).




CHANNEL 11 (2462 MHz).



FREQUENCY RANGE 2.31 GHz to 2.39 GHz. (RESTRICTED BAND)

CHANNEL 1 (2412 MHz).



FREQUENCY RANGE 2.4835 GHz to 2.5 GHz. (BAND-EDGE AT RESTRICTED BAND).

CHANNEL 11 (2464 MHz).

