



MPE Report

Report No.:STS2502022H02

Issued for

NEEC Audio Barcelona S.L.

Motors 166-168 E- 08038 Barcelona Spain

Product Name: CONTROL TOUCH PANEL

Brand Name: eclar

Model Name: PULSO-6

Series Model(s): PULSO-4, PULSO-10

FCC ID: 2ANSNPULSO

Test Standards: FCC 47CFR §2.1091

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.



TEST REPORT

Applicant's Name : NEEC Audio Barcelona S.L.
Address : Motors 166-168 E- 08038 Barcelona Spain

Manufacturer's Name : Sunworld Technology Limited
Address : 4F, Building No.5, Longbi Industrial Park, No.27 Dafa Road, Dafpu Community, Bantian Street, Longgang District, Shenzhen, Guangdong, China

Product Description

Product Name : CONTROL TOUCH PANEL

Brand : eclar

Model Number : PULSO-6

Series Model(s) : PULSO-4, PULSO-10

Standards : FCC 47CFR §2.1091
447498 D04 Interim General RF Exposure Guidance v01

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.


Date of Test

Date of receipt of test item : 11 Feb. 2025

Date (s) of performance of tests : 24 Feb. 2025 ~ 14 May 2025

Date of Issue : 14 May 2025


Test Result : **Pass**

Testing Engineer : 

(Aaron Bu)

Technical Manager : 

(Tony Liu)

Authorized Signatory : 

(Bovey Yang)





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	6
2. FCC 47CFR §2.1091 REQUIREMENT	7
2.1 TEST STANDARDS	7
2.2 LIMIT	7
2.3 TEST RESULT	10

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	14 May 2025	STS2502022H02	ALL	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	CONTROL TOUCH PANEL															
Brand	ecler															
Model Name	PULSO-6															
Series Model(s)	PULSO-4, PULSO-10															
Model Difference	<p>The screen size and antenna are different</p> <table border="1"><tr><td>Model Name</td><td>PULSO-6</td><td>PULSO-4</td><td>PULSO-10</td></tr><tr><td>Screen Size</td><td>5.5 inches</td><td>4 inches</td><td>10 inches</td></tr><tr><td>Antenna Name</td><td>XH240180</td><td>XH240060</td><td>XH240179</td></tr></table>				Model Name	PULSO-6	PULSO-4	PULSO-10	Screen Size	5.5 inches	4 inches	10 inches	Antenna Name	XH240180	XH240060	XH240179
Model Name	PULSO-6	PULSO-4	PULSO-10													
Screen Size	5.5 inches	4 inches	10 inches													
Antenna Name	XH240180	XH240060	XH240179													
Product Description	<p>The EUT is CONTROL TOUCH PANEL</p> <table border="1"><tr><td>Operation Frequency:</td><td>2.4GWLAN : 802.11b/g/n(20MHz): 2412~2472MHz Bluetooth: 2402~2480 MHz</td></tr><tr><td>Modulation Type:</td><td>2.4GWLAN: 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM BLE: GFSK</td></tr><tr><td>Antenna gain:</td><td>2.4GWLAN/ BLE: PULSO-4: 2.62 dBi PULSO-6: 2.03 dBi PULSO-10: 3.9 dBi</td></tr><tr><td>Antenna Designation:</td><td>FPC Antenna</td></tr></table>				Operation Frequency:	2.4GWLAN : 802.11b/g/n(20MHz): 2412~2472MHz Bluetooth: 2402~2480 MHz	Modulation Type:	2.4GWLAN: 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM BLE: GFSK	Antenna gain:	2.4GWLAN/ BLE: PULSO-4: 2.62 dBi PULSO-6: 2.03 dBi PULSO-10: 3.9 dBi	Antenna Designation:	FPC Antenna				
Operation Frequency:	2.4GWLAN : 802.11b/g/n(20MHz): 2412~2472MHz Bluetooth: 2402~2480 MHz															
Modulation Type:	2.4GWLAN: 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM BLE: GFSK															
Antenna gain:	2.4GWLAN/ BLE: PULSO-4: 2.62 dBi PULSO-6: 2.03 dBi PULSO-10: 3.9 dBi															
Antenna Designation:	FPC Antenna															
Rating	Input: DC 12V, 2A Output: 5V															
Adapter	N/A															
Battery	N/A															
Hardware Version	RK3566_YC_P6602_V20															
Software Version	Portworld-P6602-HF-35540-B063-A0.720x1280-20240625-Z-V0.01															



1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

Follow the maximum permissible exposure (MPE) limits specified in 447498 D04 Interim General Radio Frequency Exposure Guidelines v01. The gain of the antenna used in the product was extracted from the supplied antenna data sheet and the maximum total power input to the antenna was also measured. Calculate the distance from the product to the MPE limit by the formula.

2.2 LIMIT

For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);



(C) Or using below table and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	1,920 R ² .
1.34-30	3,450 R ² /f ² .
30-300	3.83 R ² .
300-1,500	0.0128 R ² f.
1,500-100,000	19.2R ² .



For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of Part 1.1307 for Pth, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of Part 1.1307 for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

Pi = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

Pth,i = the exemption threshold power (Pth) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERPj = the ERP of fixed, mobile, or portable RF source j.

ERPth,j = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of Part 1.1307.

Evaluatedk = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limitk = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310.



2.3 TEST RESULT

Turn up

Mode	Detector	Tune up Power
BLE	AV	6±1dBm
2.4G WLAN	AV	14±1dBm

PULSO-6

Protocol	Fre. (GHz)	Separation distance (cm)	Tune up Power (dBm)	ANT Gain (dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)	Ratio	Result
BLE	2.44	20	7	2.03	9.03	6.88	0.005	0.768	0.0063	Pass
2.4G WLAN	2.462	20	15	2.03	17.03	14.88	0.031	0.768	0.0401	Pass

PULSO-4

Protocol	Fre. (GHz)	Separation distance (cm)	Tune up Power (dBm)	ANT Gain (dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)	Ratio	Result
BLE	2.44	20	7	2.62	9.62	7.47	0.006	0.768	0.0073	Pass
2.4G WLAN	2.462	20	15	2.62	17.62	15.47	0.035	0.768	0.0459	Pass

PULSO-10

Protocol	Fre. (GHz)	Separation distance (cm)	Tune up Power (dBm)	ANT Gain (dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)	Ratio	Result
BLE	2.44	20	7	3.9	10.9	8.75	0.007	0.768	0.0098	Pass
2.4G WLAN	2.462	20	15	3.9	18.9	16.75	0.047	0.768	0.0616	Pass

Note: 1. The Maximum power is less than the limit, complies with the exemption requirements.

2. ERP=EIRP-2.15

*****END OF THE REPORT*****