

RADIO REPORT FCC 47 CFR Part 15C ISED Canada RSS-247 Frequency hopping systems operating within the 2400 – 2483.5 MHz band	
Report Reference No	G0M-1903-8127-TFC247BT-V01
Testing Laboratory	Eurofins Product Service GmbH
Address	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation	    DAkkS - Registration number : D-PL-12092-01-03 (ISED) ISED Testing Laboratory site: 3470A-2 DAkkS - Registration number : D-PL-12092-01-04 (FCC) FCC Filed Test Laboratory, Reg.-No.: 96970
Applicant	peiker Consumer Electronics Evolution GmbH
Address	Gartenstraße 25 61352 Bad Homburg GERMANY
Test Specification	According to FCC/ISED rules
Standard	47 CFR Part 15C RSS-247, Issue 2, 2017-02 RSS-Gen, Issue 5, Amendment 1, 2019-03
Non-Standard Test Method	None
Equipment under Test (EUT):	
Product Description	Audio Communication Device
Model(s)	C3
Additional Model(s)	None
Brand Name(s)	None
Hardware Version(s)	1.00
Software Version(s)	1.00
FCC-ID	2ANUYC3
IC	n/a
Test Result	PASSED

Possible test case verdicts:		
required by standard but not tested	N/T	
not required by standard	N/R	
not applicable to EUT	N/A	
test object does meet the requirement	P(PASS)	
test object does not meet the requirement	F(FAIL)	
Testing:		
Test Lab Temperature	20 - 23 °C	
Test Lab Humidity	32 – 38 %	
Date of receipt of test item	2019-03-25	
Report:		
Compiled by	Wilfried Treffke	
Tested by (+ signature) (Responsible for Test)	Wilfried Treffke	
Approved by (+ signature) (Deputy Head of Lab)	Toralf Jahn	
Date of Issue	2019-08-28	
Total number of pages	71	
General Remarks:		
The test results presented in this report relate only to the object tested. The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report. This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.		
Additional Comments:		
There are two antennas. (Antenna 1 and Antenna 2) Antenna 1 is used for Bluetooth and Wifi (for transmit and receive mode). Antenna 2 is used for Wifi only for receive mode. (Antenna diversity)		

VERSION HISTORY

Version History			
Version	Issue Date	Remarks	Revised By
01	2019-08-28	Initial Release	

ABBREVIATIONS AND ACRONYMS

Acronyms	
Acronym	Description
BR	Bluetooth Basic Rate mode
EDR	Bluetooth Enhanced Data Rate mode
EUT	Equipment Under Test
FCC	Federal Communications Commission
ISED	Innovation, Science and Economic Development Canada
RBW	Resolution bandwidth
RMS	Root mean square
VBW	Video bandwidth
V _{NOM}	Nominal supply voltage


REPORT INDEX

1	Equipment (Test Item) Under Test.....	6
1.1	Photos – Equipment External	7
1.2	Photos – Equipment Internal	9
1.3	Photos – Test Setup.....	12
1.4	Support Equipment.....	13
1.5	Test Modes	14
1.6	Test Frequencies.....	15
1.7	Sample emission level calculation.....	16
2	Result Summary.....	17
3	Test Conditions and Results.....	18
3.1	Test Conditions and Results – Occupied bandwidth	18
3.2	Test Conditions and Results - AC powerline conducted emissions.....	21
3.3	Test Conditions and Results - Transmitter radiated emissions	24
3.4	Test Conditions and Results - Receiver radiated emissions	27
ANNEX A	Transmitter spurious emissions	30
ANNEX B	Receiver spurious emissions	62

1 Equipment (Test Item) Under Test

Description	Audio Communication Device	
Model	C3	
Additional Model(s)	None	
Brand Name(s)	None	
Serial Number(s)	None	
Hardware Version(s)	1.00	
Software Version(s)	1.00	
PMN	n/a	
HVIN	n/a	
FVIN	n/a	
HMN	n/a	
FCC-ID	2ANUYC3	
IC	n/a	
Equipment type	End Product	
Radio type	Transceiver	
Assigned frequency bands	2400 - 2483.5 MHz	
Radio technology	Bluetooth	
Modulation	GFSK, PI/4-DQPSK, 8-DPSK	
Number of antenna ports	2	
Radio Module	Type	WiLink™ 8 single band combo 2x2 MIMO Wi-Fi®, Bluetooth® & Bluetooth Smart module
	Model	WL1835MOD
	Manufacturer	Texas Instruments
	HW Version	Unspecified
	SW Version	Unspecified
Antenna 1	Type	Integrated
	Model	C3_1 (PCB antenna)
	Manufacturer	peiker Consumer Electronics Evolution GmbH
	Gain	2.5 dBi (customer declaration)
Antenna 2	Type	Integrated
	Model	C3_1 (PCB antenna)
	Manufacturer	peiker Consumer Electronics Evolution GmbH
	Gain	2.5 dBi (customer declaration)
Supply Voltage	V _{NOM}	3.7 VDC (battery)
Operating Temperature	T _{NOM}	25 °C
AC/DC-Adaptor	Model	None
	Vendor	None
	Input	None
	Output	None
Manufacturer	peiker Consumer Electronics Evolution GmbH Gartenstraße 25 61352 Bad Homburg GERMANY	



1.1 Photos – Equipment External




EUT Connector View



1.2 Photos – Equipment Internal



PCB Bottom View





RF Module



Label Battery



1.3 Photos – Test Setup



1.4 Support Equipment

Product Type	Device	Manufacturer	Model	Comment
SIM	Communication Tester	R&S	CMW270	
AE	Laptop	Dell	Latitude E6420	S/N HPJ4R1
AE	Power Supply	Dell	FA65NE0-00	S/N RX929
Description:				
AE	Auxiliary Equipment			
SIM	Simulator			
CBL	Connecting Cable			
SFT	Software			
Comment:				

1.5 Test Modes

Mode	Description
DH5 Single	Mode = Transmit Modulation = GFSK Spreading = None Packet type = DH5 Duty cycle = 78%
Receive	Mode = Receive
Comment:	

1.6 Test Frequencies

Designator	Mode	Channel	Frequency [MHz]
F1	Tx / Rx	0	2402
F2	Tx / Rx	39	2441
F3	Tx / Rx	78	2480

1.7 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation 16nalys specific data taken 16nalys product described in this document:

Reading:

This 16nalys reading obtained on the spectrum analyzer in dBμV. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This 16nalys antenna factor 16nalys receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB/m)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This 16nalys net field strength measurement (as shown above).

Limit:

This 16nalys FCC Class B radiated emission limit (in units of dBμV/m). The FCC limits are given in units of μV/m. The following formula is used to convert the units of μV/m to dBμV/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 \cdot \log(\mu\text{V/m})$$

Margin:

This 16nalys margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:

Reading + AF	= Net Reading	:	Net reading – FCC limit	= Margin
+21.5 dBμV + 26 dB/m	= 47.5 dBμV/m	:	47.5 dBμV/m – 57.0 dBμV/m	= -9.5 dB

2 Result Summary

FCC 47 CFR Part 15C, ISED RSS-247				
Product Standard Reference	Requirement	Reference Method	Result	Remarks
ISED RSS-Gen, Issue 5 (section 6.6)	Occupied Bandwidth	ANSI C63.10-2013	N/R	Informational only
FCC § 15.247(a)(1) ISED RSS-247 § 5.1 Issue 2	20 dB Bandwidth	ANSI C63.10-2013	N/T	
FCC § 15.247(a)(1)(iii) ISED RSS-247, Issue 2 (section 5.1)	Number of hopping frequencies	ANSI C63.10-2013	N/T	
FCC § 15.247(a)(1) ISED RSS-247, Issue 2 (section 5.1)	Frequency hopping channel separation	ANSI C63.10-2013	N/T	
FCC § 15.247(a)(1)(iii) ISED RSS-247, Issue 2 (section 5.1)	Time of occupancy (Dwell time)	ANSI C63.10-2013	N/T	
FCC § 15.247(b)(1) ISED RSS-247, Issue 2 (section 5.4)	Maximum peak conducted power	ANSI C63.10-2013	N/T	
FCC § 15.207 ISED RSS-247, Issue 2 (section 3.1)	AC power line conducted emissions	ANSI C63.10-2013	PASS	
FCC § 15.247(d) ISED RSS-247, Issue 2 (section 5.5)	Band edge compliance	ANSI C63.10-2013	N/T	
FCC § 15.247(d) ISED RSS-247, Issue 2 (section 5.5)	Conducted spurious emissions	ANSI C63.10-2013	N/T	
FCC § 15.247(d) FCC § 15.209 ISED RSS-Gen, Issue 5 (section 6.13)	Transmitter radiated spurious emissions	ANSI C63.10-2013	PASS	
ISED RSS-247, Issue 2 (section 3.1)	Receiver radiated spurious emissions	ANSI C63.10-2013	PASS	
Comment:				

Possible Test Case Verdicts	
PASS	Test object does meet the requirements
FAIL	Test object does not meet the requirements
N/T	Required by standard but not tested
N/R	Not required by standard for the test object

3 Test Conditions and Results

3.1 Test Conditions and Results – Occupied bandwidth


3.1.1 Information

Test Information	
Reference	ISED RSS-Gen, Issue 5 (section 6.6)
Measurement Method	ANSI C63.10 6.9.3
Operator	Wilfried Treffke
Date	2019-04-18

3.1.2 Limits

Limits
None (Informational only)

3.1.3 Setup



3.1.4 Equipment

Test Equipment					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSU 26	EF01407	2018-12	2019-12

3.1.5 Procedure


Test Procedure
1. EUT transmitter is activated in test mode under normal conditions 2. The spectrum 18analyser is set to peak detection and maximum hold with a span twice the emission spectrum 3. The resolution bandwidth is set to the range of 1 % to 5 % of the occupied bandwidth 4. The occupied bandwidth is measured with the build-in 18analyser function

3.1.6 Results

Test Results		
Mode	Frequency [MHz]	Bandwidth [MHz]
3-DH5	2480	1.145
comment	max value for occupied bandwidth is recorded	

Occupied Bandwidth

Project Number: G0M-1903-8127
 Applicant: peiker Consumer Electronics Evolution GmbH
 Model Description: Audio Communication Device
 Model: C3
 Test Sample ID: 23476
 Reference Standards: FCC 15.247, RSS-247
 Reference Method: ANSI C63.10:2013, Section 6.9.3
 Operational Mode: 3-DH5, Channel: 39, 2441 MHz
 Operating Conditions: Tnom/Vnom
 Operator: Wilfried Treffke
 Test Site: Eurofins Product Service GmbH
 Test Date: 2019-04-18
 Occupied Bandwidth [MHz]: 1.145



Date: 18.APR.2019 09:03:29

3.2 Test Conditions and Results - AC powerline conducted emissions

3.2.1 Information


Test Information	
Reference	FCC § 15.207; ISED RSS-247, Issue 2 (section 3.1)
Measurement Method	ANSI C63.10 6.2
Operator	Wilfried Treffke
Date	2019-04-17

3.2.2 Limits

Limits		
Frequency [MHz]	Quasi-Peak [dBμV]	Average [dBμV]
0.15 - 0.5	66 - 56*	56 - 46*
0.5 - 5	56	46
5 - 30	60	50

* Limit decreases linearly with the logarithm of the frequency

3.2.3 Setup



3.2.4 Equipment

Test Software			
Description	Manufacturer	Name	Version
EMC Software	DARE Instruments	RadiMation	2016.1.10


Test Equipment					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
EMI Receiver	R&S	ESU 26	EF00241	2017-07	2019-07
LISN	R&S	ESH3-Z5	EF00036	2017-01	2019-07

EMI voltage test in the ac-mains according to FCC part 15 C

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 22°C, Unom: 120 VAC
 LISN: ESH3-Z5 N
 Mode: BT basic; 2441 MHz
 Test Date: 2019-04-17
 Note:

Index 132



Peak Number	Frequency	Quasi-Peak	Quasi-Peak Limit	Quasi-Peak Difference	Quasi-Peak Status
1	150 kHz	49.57 dBµV	66 dBµV	-16.43 dB	Pass
2	16.465 MHz	40.54 dBµV	60 dBµV	-19.46 dB	Pass
3	21.169 MHz	40.21 dBµV	60 dBµV	-19.79 dB	Pass
4	2.278 MHz	27.73 dBµV	56 dBµV	-28.27 dB	Pass
5	195 kHz	48.54 dBµV	63.82 dBµV	-15.28 dB	Pass

Peak Number	Frequency	Average	Average Limit	Average Difference	Average Status
1	150 kHz	19.62 dBµV	56 dBµV	-36.38 dB	Pass
2	16.465 MHz	40.2 dBµV	50 dBµV	-9.8 dB	Pass
3	21.169 MHz	39.37 dBµV	50 dBµV	-10.63 dB	Pass
4	2.278 MHz	14.54 dBµV	46 dBµV	-31.46 dB	Pass
5	195 kHz	27.34 dBµV	53.82 dBµV	-26.48 dB	Pass

Test Report No.: G0M-1903-8127-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

EMI voltage test in the ac-mains according to FCC part 15 C

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 22°C, Unom: 120 VAC
 LISN: ESH3-Z5 L
 Mode: BT basic; 2441 MHz
 Test Date: 2019-04-17
 Note:

Index 133



Peak Number	Frequency	Quasi-Peak	Quasi-Peak Limit	Quasi-Peak Difference	Quasi-Peak Status
1	150 kHz	49.06 dBμV	66 dBμV	-16.94 dB	Pass
2	177 kHz	49.89 dBμV	64.63 dBμV	-14.73 dB	Pass
3	21.169 MHz	38.39 dBμV	60 dBμV	-21.61 dB	Pass
4	16.464 MHz	39.43 dBμV	60 dBμV	-20.57 dB	Pass
5	2.359 MHz	28.86 dBμV	56 dBμV	-27.14 dB	Pass
6	614.4 kHz	25.22 dBμV	56 dBμV	-30.78 dB	Pass

Peak Number	Frequency	Average	Average Limit	Average Difference	Average Status
1	150 kHz	18.78 dBμV	56 dBμV	-37.22 dB	Pass
2	177 kHz	25.52 dBμV	54.63 dBμV	-29.11 dB	Pass
3	21.169 MHz	37.48 dBμV	50 dBμV	-12.52 dB	Pass
4	16.464 MHz	38.77 dBμV	50 dBμV	-11.23 dB	Pass
5	2.359 MHz	16.74 dBμV	46 dBμV	-29.26 dB	Pass
6	614.4 kHz	11 dBμV	46 dBμV	-35 dB	Pass

3.3 Test Conditions and Results - Transmitter radiated emissions


3.3.1 Information


Test Information	
Reference	FCC § 15.247(d); FCC § 15.209; ISSED RSS-Gen, Issue 5 (section 6.13)
Measurement Method	ANSI C63.10 6.4, 6.5, 6.6
Operator	Wilfried Treffke
Date	2019-04-12

3.3.2 Limits

Limits			
Frequency [MHz]	Detector	Field strength [$\mu\text{V/m}$]	Measurement distance [m]
0.009 - 0.09	Average	$2400/F[\text{kHz}]$	300
0.09 - 0.110	Quasi-Peak	$2400/F[\text{kHz}]$	300
0.110 - 0.490	Average	$2400/F[\text{kHz}]$	300
0.490 - 1.705	Quasi-Peak	$24000/F[\text{kHz}]$	30
1.705 - 30.0	Quasi-Peak	30	30
30 - 88	Quasi-Peak	100	3
88 - 216	Quasi-Peak	150	3
216 - 960	Quasi-Peak	200	3
960 - 1000	Quasi-Peak	500	3
>1000	Average	500	3

3.3.3 Setup





3.3.4 Equipment

Test Software			
Description	Manufacturer	Name	Version
EMC Software	DARE Instruments	RadiMation	2015.2.4

Test Equipment 30 - 1000 MHz					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Anechoic Chamber	Frankonia	AC1	EF00062	2018-07	2021-07
Measurement Receiver	R&S	ESU 26	EF00887	2018-08	2019-08
Measurement Receiver	Agilent	N9038A-526/WXP	EF01070	2018-08	2019-08
Antenna	R&S	HK 116	EF00030	2016-04	2019-04
Antenna	R&S	HL 223	EF00187	2016-05	2019-05

Test Equipment > 1 GHz					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Anechoic Chamber	Frankonia	AC1	EF00062	2018-07	2021-07
Measurement Receiver	Agilent	N9038A-526/WXP	EF01070	2018-08	2019-08
Antenna	Schwarzbeck	BBHA 9120D	EF00018	2016-09	2019-09
Antenna	Amplifier Research	AT4560	EF01152	2018-10	2019-10

3.3.5 Procedure

Test Procedure < 30 MHz	
1.	EUT is placed on a non conducting support at the center of a turn table 0.8 m above the ground
2.	EUT set to test mode
3.	The EUT is rotated through 360°
4.	The emissions are measured with peak detector and max hold
5.	All significant emissions are measured again using the corresponding final detector

Test Procedure 30 - 1000 MHz	
1.	EUT is placed on a non conducting support at the center of a turn table 0.8 m above the ground
2.	EUT set to test mode
3.	The receiver is set to peak detection with max hold
4.	The EUT is rotated through 360° and the height of the antenna is varied from 1 m to 4 m
5.	All significant emissions are measured again using the corresponding final detector

Test Procedure > 1 GHz	
1.	EUT is placed on a non conducting support at the center of a turn table 1.5 m above the ground
2.	EUT set to test mode
3.	The receiver is set to peak detection with max hold
4.	The EUT is rotated through 360° and the height of the antenna is varied from 1 m to 4 m
5.	All significant emissions are measured again using the corresponding final detector

3.3.6 Results

Test Results - DH5						
Channel [MHz]	Emission [MHz]	Level [dBμV/m]	Det.	Pol.	Limit [dBμV/m]	Margin [dB]
2402	326.923	25.13	pk	ver	46.00	-20.87
2402	2352	52.72	pk	hor	74.00	-21.28
2402	2352	28.60	RMS	hor	54.00	-25.40
2402	2376.8	53.39	pk	ver	74.00	-20.61
2402	2376.8	38.62	RMS	ver	54.00	-15.38
2402	2376.9	59.81	pk	hor	74.00	-14.19
2402	2376.9	39.31	RMS	hor	54.00	-14.69
2402	2377	58.68	pk	hor	74.00	-15.32
2402	2377	32.28	RMS	hor	54.00	-21.72
2402	4801	46.50	pk	hor	74.00	-27.50
2402	4804	51.67	pk	ver	74.00	-22.33
2402	4804	48.12	RMS	ver	54.00	-05.88
2441	4882	49.67	pk	hor	74.00	-24.33
2441	4882	47.53	RMS	hor	54.00	-06.47
2441	4882	52.82	pk	ver	74.00	-21.18
2441	4882	51.18	RMS	ver	54.00	-02.82
2441	7323	50.31	pk	ver	74.00	-23.69
2441	7323	47.90	RMS	ver	54.00	-06.10
2480	2483.9	63.59	pk	hor	74.00	-10.41
2480	2483.9	42.94	RMS	hor	54.00	-11.06
2480	2505	57.47	pk	hor	95.00	-37.53
2480	4960	50.60	pk	hor	74.00	-23.40
2480	4960	48.91	RMS	hor	54.00	-05.09
2480	4960	54.11	pk	ver	74.00	-19.89
2480	4960	50.83	RMS	ver	54.00	-03.17
Comment	Test mode selection is based on pre-compliance measurement of all operational modes. The operational modes with GFSK modulation (DH5) were selected for compliance tests.					

3.4 Test Conditions and Results - Receiver radiated emissions


3.4.1 Information


Test Information	
Reference	ISED RSS-247, Issue 2 (section 3.1)
Measurement Method	ANSI C63.10 6.5, 6.6
Operator	Wilfried Treffke
Date	2019-04-12

3.4.2 Limits

Limits			
Frequency [MHz]	Detector	Field strength [dB μ V/m]	Measurement distance [m]
30 - 88	Quasi-Peak	100	3
88 - 216	Quasi-Peak	150	3
216 - 960	Quasi-Peak	200	3
960 - 1000	Quasi-Peak	500	3
>1000	Average	500	3

3.4.3 Setup





3.4.4 Equipment

Test Software			
Description	Manufacturer	Name	Version
EMC Software	DARE Instruments	RadiMation	2015.2.4

Test Equipment 30 - 1000 MHz					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Anechoic Chamber	Frankonia	AC1	EF00062	2018-07	2021-07
Measurement Receiver	R&S	ESU 26	EF00887	2018-08	2019-08
Measurement Receiver	Agilent	N9038A-526/WXP	EF01070	2018-08	2019-08
Antenna	R&S	HK 116	EF00030	2016-04	2019-04
Antenna	R&S	HL 223	EF00187	2016-05	2019-05

Test Equipment > 1 GHz					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Anechoic Chamber	Frankonia	AC1	EF00062	2018-07	2021-07
Measurement Receiver	Agilent	N9038A-526/WXP	EF01070	2018-08	2019-08
Antenna	Schwarzbeck	BBHA 9120D	EF00018	2016-09	2019-09

3.4.5 Procedure

Test Procedure 30 - 1000 MHz	
1. EUT is placed on a non conducting support at the center of a turn table 0.8 m above the ground 2. EUT set to test mode 3. The receiver is set to peak detection with max hold 4. The EUT is rotated through 360° and the height of the antenna is varied from 1 m to 4 m 5. All significant emissions are measured again using the corresponding final detector	

Test Procedure > 1 GHz

1. EUT is placed on a non conducting support at the center of a turn table 1.5 m above the ground
2. EUT set to test mode
3. The receiver is set to peak detection with max hold
4. The EUT is rotated through 360° and the height of the antenna is varied from 1 m to 4 m
5. All significant emissions are measured again using the corresponding final detector

3.4.6 Results

Test Results

Channel [MHz]	Emission [MHz]	Level [dBμV/m]	Det.	Pol.	Limit [dBμV/m]	Margin [dB]
2402 - 2480	533.333	29.25	pk	hor	46.00	-16.75
2402 - 2480	533.333	29.67	pk	ver	46.00	-16.33
2402 - 2480	898.718	28.98	pk	hor	46.00	-17.02
2402 - 2480	2663	34.66	pk	hor	53.98	-19.32
2402 - 2480	2663	34.19	pk	ver	53.98	-19.79
2402 - 2480	3736	35.99	pk	hor	53.98	-17.99
2402 - 2480	3736	35.91	pk	ver	53.98	-18.07


ANNEX A Transmitter spurious emissions

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Rohde & Schwarz HK 116, Horizontal
 Measurement distance: 3 m
 Mode: TX; BT classic; DH5; 2402 MHz
 Test Date: 2019-04-12
 Note:

Index 73




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Rohde & Schwarz HK 116, Vertical
Measurement distance: 3 m
Mode: TX; BT classic; DH5; 2402 MHz
Test Date: 2019-04-12
Note:

Index 74




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Rohde & Schwarz HL 223, Horizontal
Measurement distance: 3 m
Mode: TX; BT classic; DH5; 2402 MHz
Test Date: 2019-04-12
Note:

Index 75




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Rohde & Schwarz HL 223, Vertical
Measurement distance: 3 m
Mode: TX; BT classic; DH5; 2402 MHz
Test Date: 2019-04-12
Note:

Index 76




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
326.923 MHz	25.13 dBµV/m	46 dBµV/m	-20.87 dB	Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m converted to 3m
 Mode: TX; BT classic; DH5; 2402 MHz
 Test Date: 2019-04-12
 Note:

Index 77



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.352 GHz	52.72 dBµV/m	74 dBµV/m	-21.28 dB	Pass
2.377 GHz	58.68 dBµV/m	74 dBµV/m	-15.32 dB	Pass


Frequency	RMS	RMS Limit	RMS Difference	RMS Status
2.352 GHz	28.6 dBµV/m	54 dBµV/m	-25.4 dB	Pass
2.377 GHz	32.28 dBµV/m	54 dBµV/m	-21.72 dB	Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Vertical
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2402 MHz
Test Date: 2019-04-12
Note:

Index 82




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Horizontal
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2402 MHz
Test Date: 2019-04-12
Note: lower bandedge

Index 78




Frequency 2.3769 GHz	Peak 59.81 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -14.19 dB	Peak Status Pass
Frequency 2.3769 GHz	RMS 39.31 dBµV/m	RMS Limit 54 dBµV/m	RMS Difference -14.69 dB	RMS Status Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Vertical
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2402 MHz
Test Date: 2019-04-12
Note: lower bandedge

Index 83




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.3768 GHz	53.39 dBµV/m	74 dBµV/m	-20.61 dB	Pass
Frequency	RMS	RMS Limit	RMS Difference	RMS Status
2.3768 GHz	38.62 dBµV/m	54 dBµV/m	-15.38 dB	Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m converted to 3m
 Mode: TX; BT classic; DH5; 2402 MHz
 Test Date: 2019-04-12
 Note:

Index 79




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.801 GHz	46.5 dBµV/m	74 dBµV/m	-27.5 dB	Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 1 m converted to 3m
 Mode: TX; BT classic; DH5; 2402 MHz
 Test Date: 2019-04-12
 Note:

Index 84




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.804 GHz	51.67 dBµV/m	74 dBµV/m	-22.33 dB	Pass
Frequency	RMS	RMS Limit	RMS Difference	RMS Status
4.804 GHz	48.12 dBµV/m	54 dBµV/m	-5.88 dB	Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Horizontal
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2402 MHz
Test Date: 2019-04-12
Note:

Index 80




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Vertical
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2402 MHz
Test Date: 2019-04-12
Note:

Index 85




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Amplifier Research AT4560, Horizontal
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2402 MHz
Test Date: 2019-04-12
Note:

Index 81




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Amplifier Research AT4560, Vertical
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2402 MHz
Test Date: 2019-04-12
Note:

Index 86




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m converted to 3m
 Mode: TX; BT classic; DH5; 2441 MHz
 Test Date: 2019-04-12
 Note:

Index 87




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.3663 GHz	40.17 dBµV/m	74 dBµV/m	-33.83 dB	Pass
2.4908 GHz	43.6 dBµV/m	74 dBµV/m	-30.4 dB	Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Vertical
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2441 MHz
Test Date: 2019-04-12
Note:

Index 91




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Horizontal
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2441 MHz
Test Date: 2019-04-12
Note:

Index 88




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.882 GHz	49.67 dBµV/m	74 dBµV/m	-24.33 dB	Pass
Frequency	RMS	RMS Limit	RMS Difference	RMS Status
4.882 GHz	47.53 dBµV/m	54 dBµV/m	-6.47 dB	Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Vertical
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2441 MHz
Test Date: 2019-04-12
Note:

Index 92




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.882 GHz	52.82 dBµV/m	74 dBµV/m	-21.18 dB	Pass
7.323 GHz	50.31 dBµV/m	74 dBµV/m	-23.69 dB	Pass
Frequency	RMS	RMS Limit	RMS Difference	RMS Status
4.882 GHz	51.18 dBµV/m	54 dBµV/m	-2.82 dB	Pass
7.323 GHz	47.9 dBµV/m	54 dBµV/m	-6.1 dB	Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Horizontal
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2441 MHz
Test Date: 2019-04-12
Note:

Index 89




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Vertical
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2441 MHz
Test Date: 2019-04-12
Note:

Index 93




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Amplifier Research AT4560, Horizontal
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2441 MHz
Test Date: 2019-04-12
Note:

Index 90




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Amplifier Research AT4560, Vertical
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2441 MHz
Test Date: 2019-04-12
Note:

Index 94




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Horizontal
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2480 MHz
Test Date: 2019-04-12
Note:

Index 106




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.505 GHz	57.47 dBµV/m	95 dBµV/m	-37.53 dB	Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Vertical
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2480 MHz
Test Date: 2019-04-12
Note:

Index 101




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Horizontal
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2480 MHz
Test Date: 2019-04-12
Note: upper bandedge

Index 96



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.4839 GHz	63.59 dBµV/m	74 dBµV/m	-10.41 dB	Pass
Frequency	RMS	RMS Limit	RMS Difference	RMS Status
2.4839 GHz	42.94 dBµV/m	54 dBµV/m	-11.06 dB	Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Vertical
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2480 MHz
Test Date: 2019-04-12
Note: upper bandedge

Index 102




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Horizontal
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2480 MHz
Test Date: 2019-04-12
Note:

Index 97




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.96 GHz	50.6 dBµV/m	74 dBµV/m	-23.4 dB	Pass
Frequency	RMS	RMS Limit	RMS Difference	RMS Status
4.96 GHz	48.91 dBµV/m	54 dBµV/m	-5.09 dB	Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 1 m converted to 3m
 Mode: TX; BT classic; DH5; 2480 MHz
 Test Date: 2019-04-12
 Note:

Index 103




Frequency 4.96 GHz	Peak 54.11 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -19.89 dB	Peak Status Pass
Frequency 4.96 GHz	RMS 50.83 dBµV/m	RMS Limit 54 dBµV/m	RMS Difference -3.17 dB	RMS Status Pass

Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Horizontal
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2480 MHz
Test Date: 2019-04-12
Note:

Index 98




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Schwarzbeck BBHA 9120D, Vertical
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2480 MHz
Test Date: 2019-04-12
Note:

Index 104




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Amplifier Research AT4560, Horizontal
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2480 MHz
Test Date: 2019-04-12
Note:

Index 99




Spurious emissions according to FCC 47 e-CFR §15.247

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Amplifier Research AT4560, Vertical
Measurement distance: 1 m converted to 3m
Mode: TX; BT classic; DH5; 2480 MHz
Test Date: 2019-04-12
Note:

Index 105




ANNEX B Receiver spurious emissions

Spurious emissions according to RSS-247 Issue 2

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Rohde & Schwarz HK 116, Horizontal
 Measurement distance: 3 m
 Mode: RX; BT classic; 2441 MHz
 Test Date: 2019-04-12
 Note:

Index 79




Spurious emissions according to RSS-247 Issue 2

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
EUT Name: Audio Communication Device
Model: C3
Test Site: Eurofins Product Service GmbH
Operator: Wilfried Treffke
Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
Antenna: Rohde & Schwarz HK 116, Vertical
Measurement distance: 3 m
Mode: RX; BT classic; 2441 MHz
Test Date: 2019-04-12
Note:

Index 80




Spurious emissions according to RSS-247 Issue 2

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Rohde & Schwarz HL 223, Horizontal
 Measurement distance: 3 m
 Mode: RX; BT classic; 2441 MHz
 Test Date: 2019-04-12
 Note:

Index 81




Frequency	Peak	Peak Limit	Peak Difference	Status	Angle	Height
533.333 MHz	29.25 dBµV/m	46 dBµV/m	-16.75 dB	Pass	135 Degree	1.2 m
898.718 MHz	28.98 dBµV/m	46 dBµV/m	-17.02 dB	Pass	90 Degree	1.2 m

Spurious emissions according to RSS-247 Issue 2

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Rohde & Schwarz HL 223, Vertical
 Measurement distance: 3 m
 Mode: RX; BT classic; 2441 MHz
 Test Date: 2019-04-12
 Note:

Index 82




Frequency	Peak	Peak Limit	Peak Difference	Status	Angle	Height
533.333 MHz	29.67 dBμV/m	46 dBμV/m	-16.33 dB	Pass	225 Degree	1.2 m

Spurious emissions according to RSS-247 Issue 2

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m
 Mode: RX; BT classic; 2441 MHz
 Test Date: 2019-04-12
 Note:

Index 73




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.663 GHz	34.66 dBµV/m	53.98 dBµV/m	-19.32 dB	Pass
3.736 GHz	35.99 dBµV/m	53.98 dBµV/m	-17.99 dB	Pass

Spurious emissions according to RSS-247 Issue 2

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 1 m
 Mode: RX; BT classic; 2441 MHz
 Test Date: 2019-04-12
 Note:

Index 76




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.663 GHz	34.19 dBµV/m	53.98 dBµV/m	-19.79 dB	Pass
3.736 GHz	35.91 dBµV/m	53.98 dBµV/m	-18.07 dB	Pass

Spurious emissions according to RSS-247 Issue 2

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m
 Mode: RX; BT classic; 2441 MHz
 Test Date: 2019-04-12
 Note:


Index 74



Spurious emissions according to RSS-247 Issue 2

Project number: G0M-1903-8127
 Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 1 m
 Mode: RX; BT classic; 2441 MHz
 Test Date: 2019-04-12
 Note:

Index 77




Spurious emissions according to RSS-247 Issue 2

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m converted to 3m
 Mode: RX; BT classic; 2441 MHz
 Test Date: 2019-04-12
 Note:

Index 75



Spurious emissions according to RSS-247 Issue 2

Project number: G0M-1903-8127

Applicant: peiker Consumer Electronics Evolution GmbH
 EUT Name: Audio Communication Device
 Model: C3
 Test Site: Eurofins Product Service GmbH
 Operator: Wilfried Treffke
 Test Conditions: Tnom: 23°C, Vnom: 3.7 VDC (battery)
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 1 m converted to 3m
 Mode: RX; BT classic; 2441 MHz
 Test Date: 2019-04-12
 Note:

Index 78

