

cetecom
advanced



BNetzA-CAB-02/21-102

TEST REPORT

Test Report No.: 1-8851/24-01-02-TR01-R02



DAkkS
Deutsche
Akkreditierungsstelle
D-PL-12047-01-00

Testing Laboratory

cetecom advanced GmbH
Untertürkheimer Straße 6 – 10
66117 Saarbrücken/Germany
Phone: + 49 681 5 98 - 0
Fax: + 49 681 5 98 - 9075
Internet: <http://www.cetecomadvanced.com>
e-mail: mail@cetecomadvanced.com

Accredited Test Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkkS).
The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12047-01-00.
ISED Testing Laboratory Recognized Listing Number: DE0001
FCC designation number: DE0002

Applicant

The Safariland Group
4700 E. Airport Drive
CA 91761 Ontario
USA

Contact: Brad Medine
e-mail: brad.medine@safariland.com
Phone: +1 90 99 30 81 13

Manufacturer

The Safariland Group
4700 E. Airport Drive
CA 91761 Ontario
USA

Test Standard/s

FCC Part 15, subpart D: 2016

Isochronous UPCS Device 1920 – 1930 MHz

Industry Canada RSS-213, Issue 3: 2 GHz Licence-exempt Personal Communication Service Devices (LE-PCS)
2015

Test Item

Kind of product: Wireless module device
Product name: TAC_MESH
FCC ID: 2ANW7-TACMESH25
IC: 23268-TACMESH25
HVIN: TM-01
PMN: TAC-MESH
FVIN: RavenTalk_release_1.0.0_Keystone_25-03-31-b9
S/N serial number: Radiated: /
Conducted: /
HW hardware status: TM-01
SW software status: RavenTalk_release_1.0.0_Keystone_25-03-31-b9.Inq
Frequency [MHz]: 1920 -1930
Type of Modulation: Digital (OFDM)
Number of channels: 5 RF Channels, 5x12 = 60 TDMA Duplex Channels
Antenna: Internal omni direction chip antenna
Power Supply: Li-ion battery, 3.7 V
Temperature Range: -20°C to 50°C

Test Report authorised:

Test performed:

2025-08-18

Luckenbill, Andreas
Head of Radio and SAR Services

2025-08-18

Wolf, Joachim
Head of New Services

1 Table of contents

1	Table of contents.....	2
2	General information	4
2.1	Notes and disclaimer	4
2.2	Application details	4
3	Test standard/s:.....	4
4	Test Environment	5
5	Reporting statements of conformity – decision rule.....	5
6	Measurement uncertainty.....	6
7	Summary of Measurement Results	7
8	Test Set-up	8
8.1	Frequency Measurements	8
8.2	Timing Measurements	8
8.3	Conducted Emission Test	8
8.4	Radiated Emission Test.....	9
8.5	Power Line Conducted Emissions Test.....	11
8.6	Monitoring Tests.....	12
8.7	Radiated Output Power Test	12
9	Detailed Test Results	13
9.1	Power Line Conducted Emissions	13
9.2	Digital Modulation Techniques	16
9.3	Labeling Requirements.....	16
9.4	Antenna Requirements	17
9.5	Channel Frequencies	17
9.6	Automatic Discontinuation of Transmission.....	18
9.7	Peak Power Output	19
9.8	Emission Bandwidth B	24
9.9	Power Spectral Density	27
9.10	In-Band Unwanted Emissions, Conducted	30
9.11	Out-of-Band Emissions, Conducted.....	33
9.12	Carrier Frequency Stability	37
9.13	Frame Repetition Stability	38
9.14	Frame Period and Jitter.....	38
9.15	Monitoring Threshold, Least Interfered Channel	40
9.16	Threshold Monitoring Bandwidth	42
9.17	Reaction Time and Monitoring Interval	43
9.18	Time and Spectrum Window Access Procedure	45
9.19	Acknowledgments and Transmission duration.....	48
9.20	Dual Access Criteria Check	50
9.21	Alternative monitoring interval.....	51
9.22	Spurious Emissions (Radiated).....	51
9.23	Receiver Spurious Emissions	54

10	Test equipment and ancillaries used for tests.....	57
11	Observations	58
	Annex A: Photographs of the Test Set-up	58
	Annex B: External Photographs of the EUT	58
	Annex C: Internal Photographs of the EUT	58
	Annex D: Document History.....	59
	Annex E: Further Information	60

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. cetecom advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced GmbH.

The testing service provided by cetecom advanced GmbH has been rendered under the current "General Terms and Conditions for cetecom advanced GmbH".

cetecom advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced GmbH test report include or imply any product or service warranties from cetecom advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced GmbH.

All rights and remedies regarding vendor's products and services for which cetecom advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

2.2 Application details

Date of receipt of order: 2025-02-19
Date of receipt of test item: 2025-07-03
Start of test: 2025-07-07
End of test: 2025-07-30
Person(s) present during the test:

3 Test standard/s:

Test Standard	Version	Test Standard Description
FCC Part 15, subpart D	2016-06	Isochronous UPCS Device 1920 – 1930 MHz
Industry Canada RSS-213, Issue 3	2015-03	2 GHz Licence-exempt Personal Communication Service Devices (LE-PCS)
ANSI C63.17	2013-08	American National Standard for Methods of Measurement of the Electromagnetic and Operational Compatibility of Unlicensed Personal Communication Services (UPCS) Devices
ANSI C63.4	2014-06	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

4 Test Environment


Temperature:	+ 22 °C during room temperature tests + 85 °C during high temperature test - 40 °C during low temperature test
Relative humidity content:	38 %
Air pressure:	not relevant for this kind of testing

5 Reporting statements of conformity – decision rule

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed in chapter 3.

The measurement uncertainty is mentioned in this test report, see chapter 9, but is not taken into account - neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong."

measured value, measurement uncertainty, verdict



6 Measurement uncertainty

Measurement uncertainty		
Test case	Uncertainty	
Frequency and Timing	$\pm 1 \times 10^{-7}$	
Antenna Gain	± 3 dB	
Conducted Level Measurement	> 10 MHz	± 0.28 dB
	> 3.6 GHz	± 0.39 dB
	> 7.0 GHz	± 1.00 dB
	> 13.6 GHz	± 1.32 dB
Spurious emissions radiated below 30 MHz	± 3 dB	
Spurious emissions radiated 30 MHz to 1 GHz	± 3 dB	
Spurious emissions radiated 1 GHz to 12.75 GHz	± 3.7 dB	
Spurious emissions radiated above 12.75 GHz	± 4.5 dB	
Spurious emissions conducted below 30 MHz (AC conducted)	± 2.6 dB	

7 Summary of Measurement Results

<input checked="" type="checkbox"/>	No deviations from the technical specifications were ascertained
<input type="checkbox"/>	There were deviations from the technical specifications ascertained

CFR 47 Part 15 UPSC

Name of test	FCC CFR 47 Paragraph	IC RSS-213 Paragraph	Verdict
Digital Modulation Techniques	15.319(b)	6.1	Complies
Labeling requirements	15.19(a)(3)	RSS-GEN 5.2	Complies
Antenna requirements	15.317, 15.203	4.1(e)	Complies
Power Line Conducted Emission	15.107(a), 15.207(a)	6.3 RSS_GEN 7.2.2	Complies
Emission Bandwidth	15.323(a)	6.4	Complies
In-band Emission	15.323(d)	6.7.2	Complies
Out-of-band Emissions	15.323(d)	6.7.1	Complies
Peak Transmit Power	15.319(c)(e), 15.31(e)	6.5	Complies
Power Spectral Density	15.319(d)	4.3.2.1	Complies
Automatic discontinuation of transmission	15.319(f)	4.3.4(a)	Complies
Carrier frequency stability	15.323(f)	6.2	Complies
Frame repetition stability	15.323(e)	4.3.4(c)	Complies
Frame period and jitter	15.323(e)	4.3.4(c)	Complies
Monitoring threshold	15.323(c)(1);(9)	4.3.4(b)	Complies
Monitoring of intended transmit window and maximum reaction time	15.323(c)(1)	4.3.4	Complies
Threshold monitoring bandwidth	15.323(c)(7)	4.3.4	N/A
Reaction time and monitoring interval	15.323(c)(1);(5); (7)	4.3.4	Complies
Access criteria test interval	15.323(c)(4);(6)	4.3.4	Complies
Access criteria functional test	15.323(c)(4);(6)	4.3.4	Complies
Acknowledgments	15.323(c)(4)	4.3.4	Complies
Transmission duration	15.323(c)(3)	4.3.4	Complies
Dual access criteria	15.323(c)(10)	4.3.4	N/A ⁵
Alternative monitoring interval	15.323(c)(10);(11)	4.3.4	N/A ²
Spurious Emissions (Antenna Conducted)	15.323(d)	6.7.1	Complies ³
Spurious Emissions (Radiated)	15.319(g), 15.109(a), 15.209(a)	4.3.3 RSS-GEN 7.2.3	Complies ⁴
Receiver Spurious Emissions	N/A	6.8	Complies

¹ Only applicable for EUT that can initiate a communication link

² The client declares that the tested equipment does not implement this provision

³ The tested equipment has integrated antennas only


⁴ Only requirement FCC 15.109 for unintentional radiators was tested radiated

⁵ Only applicable for EUT that can initiate a duplex communication link

8 Test Set-up

8.1 Frequency Measurements

Test Set-up 1:




This setup is used for measuring Carrier Frequency Stability at nominal and extreme temperatures.

For long term Frequency Stability, the EUT was CW modulation mode.

8.2 Timing Measurements

Test Set-up 2:



This setup is used for measuring Frame Repetition Stability, Frame Period and Jitter.

8.3 Conducted Emission Test

Test Set-up 3:



This setup is used for all conducted emission tests.

8.4 Radiated Emission Test

30 MHz – 1GHz:

Test Set-up 4:


- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a no conducting table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premereasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.



1GHz – 10 GHz:

Test Set-up 5:


- The Equipment was setup to simulate a typical usage like described in the user manual / or described by manufacturer.
- If the EUT is a tabletop system, a no conducting table with 0,8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is: (see ANSI C 63.4)
 - < 18 GHz = 3 m
 - 18-26 GHz = 1,5 m
 - 26-40 GHz = 0,75 m
- The EUT was set into operation.

Premeasurement

- The turntable rotates continuous from 0° to 360°
- The antenna is polarized vertical and horizontal.
- In accordance to the antenna beam and the size of the EUT the antenna height changes in 30 cm steps, start at 1 meter. If it is not possible to tilt the emissions will be checked with a manually tilted antenna from top side.
- The analyzer scans quickly to find the maximum emissions of the EUT

Final measurement



- The final measurement will be performed with minimum the six highest peaks (depends on emissions and number of measured points below 1 GHz)
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with AV (Average / see ANSI C 63.4) detector
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit, and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.



8.5 Power Line Conducted Emissions Test


Test Set-up 6:

According to EMC basic standard **ANSI C 63.4**



8.6 Monitoring Tests

Test Set-up 6:




This test setup is used for all Monitoring and Time and Spectrum Access Procedure tests. The path loss from the signal generator to the EUT is measured with a power meter before the testing is started.

A clock signal is used to synchronize the Interference Generator to the start of the DECT frame, this signal always comes from the base station. If the EUT is a DECT Portable Part (i.e. a handset) the clock signal will come from the Companion Device.

8.7 Radiated Output Power Test

Test Set-up 7:



This setup is used for measuring the radiated output power in a fully anechoic chamber with a measurement distance of 1m.

9 Detailed Test Results

9.1 Power Line Conducted Emissions

Measurement Procedure:


ANSI C63.4-2014 using 50µH/50 ohms LISN.

Test Result: Pass

Measurement Data: See attached plots and tables

Requirement: FCC 15.207 (a)

Phase Line




Phase line tbl
Project ID: 1-8851/24-01-05

Frequency MHz	Quasi peak level dB μ V	Margin quasi peak dB	Limit QP dB μ V	Average level dB μ V	Margin average dB	Limit AV dB μ V
0.232088	24.15	38.23	62.375	11.82	41.84	53.655
0.239550	21.54	40.57	62.112	7.68	45.76	53.441
2.500688	13.79	42.21	56.000	10.06	35.94	46.000
5.922244	6.31	53.69	60.000	1.14	48.86	50.000

Project ID - 1-8851/24-01-05
EUT - TAC-MESH
Serial Number - 19
Operating mode - powered on and charging

Neutral Line



Neutral line tbl
Project ID: 1-8851/24-01-05

Frequency MHz	Quasi peak level dBµV	Margin quasi peak dB	Limit QP dBµV	Average level dBµV	Margin Average dB	Limit AV dBµV
0.209700	29.89	33.33	63.217	13.68	40.62	54.294
0.239550	31.23	30.88	62.112	18.05	35.39	53.441
2.500688	17.23	38.77	56.000	15.19	30.81	46.000
5.903588	8.11	51.89	60.000	8.99	41.01	50.000

Project ID - 1-8851/24-01-05
EUT - TAC-MESH
Serial Number - 19
Operating mode - powered on and charging

9.2 Digital Modulation Techniques

The tested equipment is based on DECT technology, the only difference is that the channel allocation is modified to operate in the 1920-1930 MHz band.

The EUT use Multi Carrier / Time Division Multiple Access / Time division duplex and Digital GFSK modulation.

For further details see the operational description provided by the applicant.

Requirement: FCC 15.319(b)

All transmissions must use only digital modulation techniques.

9.3 Labeling Requirements

See separate documents showing the label design and the placement of the label on the EUT.

Requirement: FCC 15.19

The FCC identifier shall be displayed on the label, and the device(s) shall bear the following statement in a conspicuous location on the device or in the user manual if the device is to small:

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label itself shall be of a permanent type, not a paper label, and shall last the lifetime of the equipment.

9.4 Antenna Requirements

Does the EUT have detachable antenna(s)? Yes No

If detachable, is the antenna connector(s) non-standard? Yes No

The tested equipment has only integral antennas. The conducted tests were performed on a sample with a temporary antenna connector.

Requirements: FCC 15.203, 14.204. 15.317

9.5 Channel Frequencies

UPCS CHANNEL	FREQUENCY (MHz)
Upper Band Edge	1930.000
0 (Highest)	1928.448
1	1926.720
2	1924.992
3	1923.264
4 (Lowest)	1921.536
Lower Band Edge	1920.000

Requirement: FCC 15.301

Within 1920-1930 MHz band for isochronous devices.

9.6 Automatic Discontinuation of Transmission

Does the EUT transmit control and Signaling Information?	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
Type of EUT:	<input checked="" type="checkbox"/> Initiating device	<input checked="" type="checkbox"/> Responding device

The following tests simulate the reaction of the EUT in case of either absence of information to transmit or operational failure after a connection with the companion device is established.

Number	Test	EUT Reaction	Verdict
1	Power removed from EUT	N/A	N/A
2	EUT switched Off	A	Pass
3	Hook-On by companion device	N/A	N/A
4	Hook-On by EUT	N/A	N/A
5	Power removed from companion device	N/A	N/A
6	Companion device switched Off	B	Pass

- A – Connection breakdown, Cease of all transmissions
- B – Connection breakdown, EUT transmits control and signaling information
- C – Connection breakdown, companion device transmits control and signaling information
- N/A – Not applicable (the EUT does not have an on/off switch and can not perform Hook-On)

Requirement: FCC 15.319(f)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. This provision is not intended to preclude transmission of control and signaling information or use or repetitive code used by certain digital modulation technologies to complete frame or burst intervals.

9.7 Peak Power Output

Measurement Procedure:

ANSI C63.17, clause 6.1.2.

Test Results: Pass

Measurement Data:

Maximum Conducted Output Power

Channel No.	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Maximum Radiated Output Power (dBm)	Maximum Antenna Gain (dBi)
4	1921.536	20.70	20.92	+0.2
2	1924.992	20.60	21.00	+0.4
0	1928.448	20.82	20.05	-0.8

Limit:

Conducted: $100 \mu\text{W} \times \text{SQRT}(B)$ where B is the measured Emission Bandwidth in Hz

FCC 15.319(c)(e): 21.4 dBm (137 mW)

RSS-213, Issue 2: 21.0 dBm (126 mW)


The antenna gain is below 3 dBi.

Requirements: FCC 15.319(c)(e). RSS-213, Issue 2


Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in Hertz.

The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.


Conducted Peak Output Power



Lower Channel




Upper Channel




Middle Channel


Radiated Peak Output Power



Lower Channel



Upper Channel



Middle Channel

9.8 Emission Bandwidth B

Measurement Procedure:

ANSI C63.17, clause 6.1.3.

Test Results: Pass

Measurement Data:

Channel No.	Frequency (MHz)	26 dB Bandwidth B (kHz)
4	1921.536	1844
0	1928.448	1872

Channel No.	Frequency (MHz)	99 % Bandwidth B (kHz)
2	1924.992	1582

Channel No.	Frequency (MHz)	6 dB Bandwidth B (kHz)
4	1921.536	N/A
0	1928.448	N/A
Channel No.	Frequency (MHz)	12 dB Bandwidth B (kHz)
4	1921.536	N/A
0	1928.448	N/A


Requirement: FCC 15.323(a)

The 26 dB Bandwidth B shall be larger than 50 kHz and less than 2.5 MHz.


Requirement: RSS-213 Issue 2, clause 6.4

The 20 dB Bandwidth B shall be larger than 50 kHz and less than 2.5 MHz.


No requirement for 6 dB and 12 dB Bandwidth. These values are only used for testing Monitoring Bandwidth if the Simple Compliance test fails (ANSI C63.17, clause 7.4).



Emission Bandwidth B, Lower Channel



Emission Bandwidth B, Upper Channel



99 % Bandwidth B, Middle Channel

9.9 Power Spectral Density

Measurement Procedure:

ANSI C63.17, clause 6.1.5.

Test Results: Pass

Measurement Data:

Channel No.	Frequency (MHz)	Power Spectral Density (dBm/3kHz)
4	1921.405568	-15.70
0	1928.157952	-14.16

Averaged over 100 sweeps.


Requirement: FCC 15.319(d)

The Power Spectral Density shall be less than 3 mW/3kHz (4.77 dBm) when averaged over at least 100 sweeps.

Power Spectral Density

Lower Channel:

Frequency of the maximum level was recorded under chapter 5.9.




Averaged, 100 Sweeps

Pulse power [dBm]	-15.70
Pulse power [mW]	0.03

Power Spectral Density

Upper Channel:

Frequency of the maximum level was recorded under chapter 5.9.



Averaged, 100 Sweeps

Pulse power [dBm]	-14.16
Pulse power [mW]	0.04

9.10 In-Band Unwanted Emissions, Conducted

Measurement Procedure:

ANSI C63.17, clause 6.1.6.1.

Test Results: Pass


Measurement Data:

See plots.


Requirement: FCC 15.323(d)

$B < f_2 \leq 2B$:	less than or equal to 30 dB below max. permitted peak power level
$2B < f_2 \leq 3B$:	less than or equal to 50 dB below max. permitted peak power level
$3B < f_2 \leq \text{UPCS Band Edge}$:	less than or equal to 60 dB below max. permitted peak power level


In-Band Unwanted Emissions, Conducted



Lower Channel



Upper Channel



Middle Channel

The BS spurious in-band transmission level is below the indicated limit.

9.11 Out-of-Band Emissions, Conducted

Measurement Procedure:

ANSI C63.17, clause 6.1.6.2.

Test Results: Pass

Measurement Data:



See plots.

Requirement: FCC 15.323(d)



$f \leq 1.25$ MHz outside UPSCS band:	≤ -9.5 dBm
1.25 MHz $\leq f \leq 2.5$ MHz outside UPSCS band:	≤ -29.5 dBm
$f \geq 2.5$ MHz outside UPSCS band:	≤ -39.5 dBm

Out-of-Band Unwanted Emissions, Conducted


Upper and Lower Channel:



Out-of-Band Unwanted Emissions, Conducted



Out-of-Band Unwanted Emissions, Conducted



The BS spurious out-of-band transmission level is below the indicated limit.

9.12 Carrier Frequency Stability

Measurement Procedure:

ANSI C63.17, clause 6.2.1.

Requirement: FCC 15.323(f)

Test Results: Pass

Measurement Data:

The Frequency Stability is measured with the CMD65. The CMD65 was logged by a computer programmed to get the new readings as fast as possible (about 3 readings per second) over the noted time period or number of readings. The peak-to-peak difference was recorded and the mean value and deviation in ppm was calculated.

The Carrier Frequency Stability over power Supply Voltage and over Temperature is measured also with the CMD65.

Carrier Frequency Stability over Time at Nominal Temperature

Average Mean Carrier Frequency (MHz)	Max. Diff. (kHz)	Min. Diff. (kHz)	Max Dev. (ppm)	Limit (ppm)
1924.991195	0.013	-0.006	0.01	±10

Deviation ppm = ((Max.Diff. – Mean.Diff.) / Mean Carrier Freq.) x 10⁶

Deviation (ppm) is calculated from 3000 readings with the CMD65.

Carrier Frequency Stability over Power Supply at Nominal Temperature

Voltage	Measured Carrier Frequency (MHz)	Difference (kHz)	Deviation (ppm)	Limit (ppm)
5.00 V DC	N/A			±10
5.75 V DC	N/A			
4.25 V DC	N/A			

Deviation ppm = ((Mean – Measured frequency) / Mean) x 10⁶

Carrier Frequency Stability over Temperature

Temperature	Measured Carrier Frequency (MHz)	Difference (kHz)	Deviation (ppm)	Limit (ppm)
T = +20°C	1924.991	Ref.	Ref.	±10
T = -40°C	1924.991	0.0	0.0	
T = +85°C	1924.991	0.0	0.0	

Deviation ppm = ((Mean – Measured frequency) / Mean) x 10⁶

9.13 Frame Repetition Stability

Measurement Procedure:

ANSI C63.17, clause 6.2.2.

Test Results: Pass

Measurement Data:

The Frame Repetition Stability is measured with the CMD65. The Frame Repetition Stability is 3 times the standard deviation.

Carrier Frequency (MHz)	Mean (Hz)	Standard Deviation (ppm)	Frame Repetition Stability (ppm)
1924.992	100.0013874448	4.9	14.6

Limit:

Frame Repetition Stability	±50 ppm (TDMA)
----------------------------	----------------

Ref. FCC 15.323(e). ANSI C63.17, clause 6.2.2.

9.14 Frame Period and Jitter

Measurement Procedure:

ANSI C63.17, clause 6.2.3.

Test Results: Pass

Measurement Data:

The Frame Repetition Stability is measured with the CMD65

Carrier Frequency (MHz)	Frame Period (ms)	Max Jitter (μs)	3xStandard Deviation of Jitter (μs)
1924.992	9.999856	0.1	0.28


Max Jitter = $(1/(\text{Frame Period} + \text{Pk-Pk})/2) - (1/\text{Frame Period})$, when Pk-Pk and Frame Period are in Hz.
 $3 \times \text{St.Dev.Jitter} = 3 \times (1/(\text{Frame Period} + \text{St.Dev})) - (1/\text{St.Dev}) \times 10^6$

Limit:


Frame Period	20 or 10 ms
Max Jitter	25 μs
3 times St.Dev. of Jitter	12.5 μs

Ref. FCC 15.323(e). ANSI C63.17, clause 6.2.3.


Histogram of Carrier Frequency Stability



Histogram of Frame Repetition Stability



Histogram of Frame Period and Jitter



9.15 Monitoring Threshold, Least Interfered Channel

Measurement Procedure:

ANSI C63.17, clause 7.3.2

Monitoring Threshold limits:

Lower Threshold:

$$T_L = 15 \log B - 184 + 30 - P_{EUT} \text{ (dBm)}$$

B is measured Emission Bandwidth in Hz

P_{EUT} is measured Transmitter Power in dBm

Calculated value:

Lower Threshold	-80.7 dBm
-----------------	-----------

Monitoring Threshold Test, FCC 15.323(c)(1)

ANSI C63.17 clause 7.3.1 ref.	Observation	Verdict
a) interference level > T _L + U _m (-74.7 dBm)	No Transmission	Pass
b) interference level < T _L + U _m (-74.7 dBm)	Transmission, interference level <= -79.0 dBm	Pass


Measurement Procedure:

ANSI C63.17, clause 7.3.3

Selected Channel Confirmation, FCC 15.323(c)(1) and (5)

ANSI C63.17 clause 7.3.3	Observation	Verdict
b) Shall not transmit on f_1	No transmission on f_1	Pass
d) Shall not transmit on f_2	EUT transmits on f_1	Pass

Comment: This test is only applicable for EUTs that can be an initiating device.

**7.3.3 Selected Channel Confirmation, connection 0.3 s after interferer removed**

9.16 Threshold Monitoring Bandwidth

This test is only required if a dedicated monitoring receiver is used. If the test is not carried out the manufacturer shall declare and provide evidence that the monitoring is made through the radio receiver used for communication.

Measurement Procedure:

Simple Compliance Test, ANSI C63.17, clause 7.4.1

More Detailed Test, ANSI C63.17, clause 7.4.2

The test is passed if **either** the Simple Compliance Test or the More Detailed Test is passed.

During this test the spectrum analyzer is observed visually to see if the EUT transmits or not.

Test Results:

Test performed	Observation	Verdict
Simple Compliance Test, at $\pm 30\%$ of B	N/A	N/A
More Detailed Test, at -6 dB points	N/A	N/A
More Detailed Test, at -12 dB points	N/A	N/A

The More Detailed Test must be pass at both the -6dB and -12 dB points if the Simple Compliance Test fails.

Comment: The tested EUT uses the same receiver for monitoring and communication, this test is therefore not required.

Limits: FCC 15.323(c)(7):

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission.

9.17 Reaction Time and Monitoring Interval

Measurement Procedure:

ANSI C63.17, clause 7.5

Test Results:

By administrative commands and out-of-operating region interference, the EUT is restricted to operate on carrier frequencies f_1 and f_2 .

Time-synchronized pulsed interference was then applied on f_1 at pulsed levels $TL + UM$ to check that the EUT does not transmit. The level was raised 6 dB for part d) with 35 μ s pulses. Additionally a CW signal was applied on f_2 with a level of TL .

The pulses are synchronized with the EUT timeslots and applied centered within all timeslots.

Pulse Width, ref. to ANSI C63.17 clause 7.5	Observation	Verdict
c) > largest of 50 μ s and $50 * \text{SQRT}(1.25/B)$	Transmission if level < $TL + UM$	Pass
d) > largest of 35 μ s and $35 * \text{SQRT}(1.25/B)$ and with interference level raised 6 dB	Transmission if level < $TL + UM + 6$	Pass

Comment: Since B is larger than 1.25 MHz, the test was performed with pulse lengths of 50 μ s and 35 μ s.


Note: EUT supports only operation on one single channel.

Limits: FCC 15.323(c)(1), (5) and (7)


The maximum reaction time must be less than $50 * \text{SQRT}(1.25/\text{emission bandwidth in MHz})$ microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microseconds.

If a signal is detected that is 6 dB or more above the applicable threshold level, the maximum reaction time shall be $35 * \text{SQRT}(1.25/\text{emission bandwidth in MHz})$ microseconds but shall not be required to be less than 35 microseconds.

Comment: This test is only applicable for EUTs that can be an initiating device.



50 μs Pulses



35 μs Pulses

9.18 Time and Spectrum Window Access Procedure

This requirement is only for EUTs which transmit unacknowledged control and signaling information

Measurement Procedure:

Timing for EUTs using control and signaling channel type transmissions: ANSI C63.17, clause 8.1

Test results:

Access Criteria, ref. to ANSI C63.17 clause 8.1.1	Observation	Verdict
b) Check that the EUT transmits on the interference free time slot	EUT transmits on the Interference free time slot	Pass
b) The EUT must terminate or pause in its repetitive transmission of the control and signaling channel on the open channel to repeat the access criteria not less frequently than every 30 s	Transmission stops every 0.6 s	Pass

If FCC 15.323(c)(6) option Random Waiting Interval is NOT implemented

Access Criteria, ref. to ANSI C63.17 clause 8.1.2	Observation	Verdict
b) Check that the EUT changes to interference free time slot when interference is introduced on the time slot in use	EUT changes to Interference free time slot, and stays there	Pass

If FCC 15.323(c)(6) option Random Waiting Interval is implemented

Access Criteria, ref. to ANSI C63.17 clause 8.1.3	Observation	Verdict
b-d) Check that the EUT uses random waiting interval before continuing transmission on an interfered time slot	N/A	N/A

Comment: The tested EUT does not support the Random Waiting Interval option.

Limits:


FCC 15.323(c)(4):

Once access to specific combined time and spectrum windows is obtained an acknowledgement from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgments must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which the time access criteria must be repeated.


FCC 15.323(c)(6):

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same windows after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available.

Access Criteria Check




8.1.1b) EUT Transmits on Unblocked Slot




8.1.1b) EUT Terminates Repetitive Transmission

Capture of transmission of base EUT control and signaling transmissions. The base EUT pauses in its transmission of the control and signaling channel to repeat the access criteria every 0.6 s seconds, meeting the requirement that it do so at least as often as every 30 seconds.

Access Criteria Check



8.1.2) EUT Changes to an Interference Free Timeslot, Before



8.1.2) EUT Changes to an Interference Free Timeslot, After

9.19 Acknowledgments and Transmission duration

Measurement Procedure:

Acknowledgments: ANSI C63.17, clause 8.2.1

Transmission Duration: ANSI C63.17, clause 8.2.2

During the test **Initial transmission without acknowledgments** the signal from the EUT to the companion device is blocked by circulators in addition to the tunable attenuator.

The test **Transmission time after loss of acknowledgments** is performed by cutting-off the signal from the companion device by a RF switch the time until the EUT stops transmitting.

The **Transmission Duration** test is performed by monitoring the slot in use and measuring the time until the EUT changes to a different slot.

Test Results:

Acknowledgments

Test ref. to ANSI C63.17 clause 8.2.1	Observation	Verdict
a) Initial transmission without acknowledgments	0.8 s	Pass
c) Transmission time after loss of acknowledgments	0.8 s	Pass


Transmission Duration

Test ref. to ANSI C63.17 clause 8.2.2	Observation	Verdict
b) Transmission duration on same time and frequency window	10 min	Pass


Comment: /

Limits: FCC 15.323(c)(3) and (4)

Occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria. Once access to specific combined time and spectrum windows is obtained an acknowledgment from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgments must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which the time access criteria must be repeated.



8.2.1a) Initial Transmission Time without Acknowledgments



8.2.1c) Transmission Time after Loss of Acknowledgments

9.20 Dual Access Criteria Check

Measurement Procedure:

EUTs that do not implement the Upper Threshold: ANSI C62.17, clause 8.3.1

EUTs that implement the Upper Threshold: ANSI C62.17, clause 8.3.2

This test is required for equipment that uses the access criteria in FCC 15.323(c)(10).

Test Results:

EUTs that do NOT implement the LIC algorithm:

Test ref. to ANSI C63.17 clause 8.3.1	Observation	Verdict
b) EUT is restricted to a single carrier f_1 for TDMA systems. The test is pass if the EUT can set up a communication link.	N/A	N/A
c) d) No transmission on interference-free receive time/spectrum window. All transmit slots blocked	N/A	N/A
e) f) No transmission on interference-free transmit time/spectrum window. All transmit slots blocked	N/A	N/A

EUTs that implement the LIC algorithm:

Test ref. to ANSI C63.17 clause 8.3.2	Observation	Verdict
b) EUT is restricted to a single carrier f_1 for TDMA systems. The test is pass if the EUT can set up a communication link.	N/A	N/A
c) d) Transmission on interference-free receive time/spectrum window.	N/A	N/A
e) f) Transmission on interference-free transmit time/spectrum window.	N/A	N/A

Comment: This test is only applicable for EUTs that can be an initiating device of a duplex connection.

Limits: FCC 15.323(c)(10)

An initiating device may attempt to establish a duplex connection by monitoring both, its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

9.21 Alternative monitoring interval

Test procedure described in ANSI C63.17, clause 8.4.

This test is required if the EUT implements the provision of FCC 15.323(c)(11).

Test Result:

Not tested. The tested EUT does not implement this provision. See manufacturer's declaration.

9.22 Spurious Emissions (Radiated)

Measurement Procedure:

FCC 15.209, FCC 15.109

Test Result: Pass


Measurement Data: See plots.

Requirement: FCC 15.109(b)

30 – 88 MHz:	90 μ V/m
88 – 216 MHz:	150 μ V/m
216 – 960 MHz:	210 μ V/m
960 – 1000 MHz:	300 μ V/m

Common Information

EUT: TAC-MESH
 Serial number: 18
 Test description: FCC part 15 class B
 Operating condition: Rx mode
 Operator name: LAN
 Comment: battery powered




Final_Result

Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimut h (deg)	Corr. (dB/m)
42.714	4.24	30.0	25.8	1000	120.0	200.0	H	292	15
56.826	4.54	30.0	25.5	1000	120.0	400.0	V	325	16
61.747	2.52	30.0	27.5	1000	120.0	363.0	H	238	13
499.540	8.80	36.0	27.2	1000	120.0	200.0	H	315	20
721.176	12.28	36.0	23.7	1000	120.0	400.0	H	286	23
947.669	15.27	36.0	20.7	1000	120.0	400.0	H	128	25

Common Information

EUT: TAC-MESH
 Serial number: 18
 Test description: FCC part 15 class B > 1GHz
 Operating condition: Rx mode
 Operator name: LAN
 Comment: battery powered



Final_Result

Frequency (MHz)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Pol	Azim uth (deg)	Corr. (dB/m)	Comment
11870.674	37.58	54.0	16.4	1000	1000.0	V	32	10	
12276.463	36.41	54.0	17.6	1000	1000.0	H	10	10	
13453.637	39.55	54.0	14.5	1000	1000.0	V	316	11	
13992.275	39.41	54.0	14.6	1000	1000.0	V	345	12	
14557.543	38.28	54.0	15.7	1000	1000.0	H	44	12	
14835.529	37.80	54.0	16.2	1000	1000.0	V	344	11	

The radiated spurious emission of the unintentional radiator is below the indicated limit.

9.23 Receiver Spurious Emissions

Measurement Procedure:

Industry Canada RSS-213 paragraph 6.8 and RSS-GEN paragraphs 4.8 and 6.

Test results:


Frequency MHz	Carrier No.	Measured Value Conducted dBm	Conducted Limit dBm	Margin dB
30 - 1000	all	-73.2	-57	16.2
> 1000	all	-69.7	-53	16.7

Requirements: RSS-GEN Issue 2, clause 6


The measurement can be performed either radiated or conducted.

When measured conducted: No spurious signals appearing at the antenna terminals shall exceed 2 nW per any 4 kHz spurious frequency in the band 30-1000 MHz, or 5 nW above 1 GHz.


When measured radiated: See table 1 in RSS-GEN Issue2, clause 6.



Receiver Spurious Emissions, Conducted, 100 kHz – 1 GHz



Receiver Spurious Emissions, Conducted, 1 GHz – 12 GHz

**Receiver Spurious Emissions, Conducted, 12 GHz – 20 GHz**

10 Test equipment and ancillaries used for tests

To simplify the identification of the test equipment and/or ancillaries which were used, the reporting of the relevant test cases only refer to the test item number as specified in the table below.

No.	Equipment	Manufacturer	Type	Serial No.	Inv. No.	Kind of Calib.	Last Calib.	Next Calib.
Conducted								
L-1	Spectrum Analyzer	R&S	FSV30	100763	300003950	k	12/2024	12/2025
L-2	Signal Generator	R&S	SMBV100A	257858	300004529	vlkl!	12/2023	12/2026
L-3	Signaling Unit	R&S	CMD 65	825486	300003611	vlkl!	12/2023	12/2025
L-4	Power Sensor	R&S	NRP-Z22	100031	400000188	vlkl!	01/2024	01/2026
L-5	Counter	Agilent	53132A	04060	300003211	vlkl!	12/2022	12/2025

No.	Equipment	Manufacturer	Type	Serial No.	Inv. No.	Kind of Calib.	Last Calib.	Next Calib.
Power Line Conducted Emission								
G-1	EMI Receiver	R&S	ESR3	102981	3000006318	k	12/2024	12/2025
G-2	VISN	R&S	ESH 3-Z5	893045/004	300000584	k	12/2024	12/2025

No.	Equipment	Manufacturer	Type	Serial No.	Inv. No.	Kind of Calib.	Last Calib.	Next Calib.
Radiated Emission								
F-1	EMI Receiver	R&S	ESR3	102587	300005771	k	12/2024	12/2025
F-2	Spectrum Analyzer	R&S	FSU26	200809	300003874	k	12/2024	12/2025
F-3	Trilog Antenna	Schwarzbeck	VULB9163	371	300003854	vlkl!	07/2024	07/2026
F-4	Horn antenna	EMCO	3115	9107-3697	300001605	vlkl!	03/2023	03/2025

Agenda: Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vlkl!	Attention: extended calibration interval	*	next calibration ordered / currently in progress
NK!	Attention: not calibrated		

11 Observations

No observations exceeding those reported with the single test cases have been made.

Annex A: Photographs of the Test Set-up

See additional PDF document Annex A-C.

Annex B: External Photographs of the EUT

See additional PDF document Annex A-C.

Annex C: Internal Photographs of the EUT

See additional PDF document Annex A-C.

Annex D: Document History

Version	Applied Changes	Date of Release
R01	Initial release	2025-08-04
R02	Type of Modulation	2025-08-18

Annex E: Further Information

Glossary

DUT	-	Device under Test
EMC	-	Electromagnetic Compatibility
EUT	-	Equipment under Test
FCC	-	Federal Communication Commission
FCC ID	-	Company Identifier at FCC
HW	-	Hardware
IC	-	Industry Canada
Inv. No.	-	Inventory number
N/A	-	not applicable
S/N	-	Serial Number
SW	-	Software