



FCC RF Test Report

APPLICANT : Circuit Board Design LLC
EQUIPMENT : Tablet
MODEL NAME : L5S83A
FCC ID : 2ANXB-5276
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product testing was completed on Mar. 12, 2018. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.



Approved by: Eric Shih / Manager

Sportun International (Shenzhen) Inc.
1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City
Guangdong Province 518055 China



TABLE OF CONTENTS

SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant	5
1.2 Product Feature of Equipment Under Test.....	5
1.3 Product Specification of Equipment Under Test.....	6
1.4 Modification of EUT	6
1.5 Testing Location	6
1.6 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 Descriptions of Test Mode	8
2.2 Test Mode	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 6dB and 99% Bandwidth Measurement	12
3.2 Peak Output Power Measurement	17
3.3 Power Spectral Density Measurement	18
3.4 Conducted Band Edges and Spurious Emission Measurement	23
3.5 Radiated Band Edges and Spurious Emission Measurement	28
3.6 AC Conducted Emission Measurement.....	32
3.7 Antenna Requirements	36
4 LIST OF MEASURING EQUIPMENT.....	37
5 UNCERTAINTY OF EVALUATION.....	38

APPENDIX A. CONDUCTED TEST RESULTS**APPENDIX B. RADIATED SPURIOUS EMISSION****APPENDIX C. RADIATED SPURIOUS EMISSION PLOTS****APPENDIX D. DUTY CYCLE PLOTS**



REVISION HISTORY



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass
3.1	-	99% Bandwidth	-	Pass
3.2	15.247(b)(3)	Peak Output Power	≤ 30dBm	Pass
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass
3.6	15.207	AC Conducted Emission	15.207(a)	Pass
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass



1 General Description

1.1 Applicant

Circuit Board Design LLC

4320 Winfield Road Cornerstone @ Cantera Suite 200 Warrenville, Illinois, 60555

1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet
Model Name	L5S83A
FCC ID	2ANXB-5276
EUT supports Radios application	WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 Bluetooth v3.0+EDR/Bluetooth v4.0 LE/ Bluetooth v4.1 LE/ Bluetooth v4.2 LE
SW Version	userdebug 6.0 NMAIN1 530

			SN
Radiated Emission	Sample	B#4	GOW0U0027516F07V
	Adapter	AP16#2	AH17320956836
Conducted Emission	Sample	B#1	GOW0U0027516F057
	Adapter	AP16#1	AH17320956997
Conducted	Sample	B#4	GOW0U0027516F07V



1.3 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	0.07 dBm (0.0010 W)
99% Occupied Bandwidth	1.02MHz
Antenna Type / Gain	Fixed internal Antenna with gain -0.10 dBi
Type of Modulation	Bluetooth LE : GFSK

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sportun International (Shenzhen) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0) and the FCC designation No. are CN5018 and CN5019.

Test Site	Sportun International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595		
Test Site No.	Sportun Site No.	FCC Test Firm Registration No.	
	TH01-SZ	CO01-SZ	251365

Test Site	Sportun International (Shenzhen) Inc.		
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District Shenzhen City Guangdong Province 518055 China TEL: +86-755-3320-2398		
Test Site No.	Sportun Site No.	FCC Test Firm Registration No.	
	03CH04-SZ	577730	

Note: The test site complies with ANSI C63.4 2014 requirement.



1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ANSI C63.10-2013

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

Channel	Frequency	Bluetooth – LE RF Output Power
		Data Rate / Modulation
		GFSK
		1Mbps
Ch00	2402MHz	0.07 dBm
Ch19	2440MHz	-0.10 dBm
Ch39	2480MHz	-0.56 dBm

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Y plane as worst plane) from all possible combinations.

- b. AC power line Conducted Emission was tested under maximum output power.



2.2 Test Mode


The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1 : Bluetooth Link + WLAN (2.4G) Link + Play MPEG4 from MicroSD card + USB Cable (Charging from Adapter AP-16) + MicroSD card


Remark: For Radiated Test Cases, The tests were performed with Earphone, Adapter and USB Cable.

2.3 Connection Diagram of Test System

<Bluetooth LE Tx Mode>



<AC Conducted Emission Mode>





2.4 Support Unit used in test configuration and system

Item	Equipment	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	DIR-820L	KA2IR820LA1	N/A	Unshielded, 1.8m
2.	Notebook	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	EO-MG900	N/A	N/A	N/A
4.	SD Card	MicroSD HC	FCC DoC	N/A	N/A
5.	Earphone	N/A	N/A	Unshielded, 1.2 m	N/A

2.5 EUT Operation Test Setup

For Bluetooth LE function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

$$= 5.0 + 10 = 15.0 \text{ (dB)}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Test data refer to Appendix A.


6 dB Bandwidth Plot on Channel 00



Date: 26.FEB.2018 11:50:54




6 dB Bandwidth Plot on Channel 19



Date: 26.FEB.2018 11:47:29

6 dB Bandwidth Plot on Channel 39




Date: 26.FEB.2018 11:55:45

3.1.6 Test Result of 99% Occupied Bandwidth

Test data refer to Appendix A.


99% Bandwidth Plot on Channel 00



Date: 26.FEB.2018 11:53:30




99% Occupied Bandwidth Plot on Channel 19



Date: 26.FEB.2018 11:48:43

99% Occupied Bandwidth Plot on Channel 39



Date: 26.FEB.2018 11:57:11

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Test data refers to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup






3.3.5 Test Result of Power Spectral Density

Test data refers to Appendix A.


3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 00






PSD 100kHz Plot on Channel 19



Date: 26.FEB.2018 11:48:00

PSD 100kHz Plot on Channel 39




Date: 26.FEB.2018 11:56:23




3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00






PSD 3kHz Plot on Channel 19



Date: 26.FEB.2018 11:47:45

PSD 3kHz Plot on Channel 39



Date: 26.FEB.2018 11:56:03

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 00



Date: 26.FEB.2018 11:52:34

High Band Edge Plot on Channel 39




Date: 26.FEB.2018 11:56:51



3.4.6 Test Result of Conducted Spurious Emission Plots


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00






Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 19



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 19





Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 39



Date: 12.MAR.2018 11:03:16

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 39



Date: 12.MAR.2018 11:03:25



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.



3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup






3.6.5 Test Result of AC Conducted Emission





Test Mode :	Mode 1	Temperature :	22~25°C
Test Engineer :	Peng wang	Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN (2.4G) Link + Play MPEG4 from MicroSD card + USB Cable (Charging from Adapter AP-16) + MicroSD card		



Site : C001-SZ
Condition: FCC 15C QP LISN_20170907_N NEUTRAL

Freq	Level	Over	Limit	Read	LISN	Cable	Remark
		Limit	Line	Level	Factor	Loss	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.85	31.42	-14.58	46.00	21.29	0.04	10.09 Average
2	0.85	35.92	-20.08	56.00	25.79	0.04	10.09 QP
3 *	18.04	36.86	-13.14	50.00	26.00	0.49	10.37 Average
4	18.04	43.76	-16.24	60.00	32.90	0.49	10.37 QP
5	19.74	35.42	-14.58	50.00	24.50	0.57	10.35 Average
6	19.74	43.22	-16.78	60.00	32.30	0.57	10.35 QP
7	21.49	33.28	-16.72	50.00	22.19	0.72	10.37 Average
8	21.49	44.18	-15.82	60.00	33.09	0.72	10.37 QP
9	23.14	32.84	-17.16	50.00	21.60	0.85	10.39 Average
10	23.14	44.64	-15.36	60.00	33.40	0.85	10.39 QP
11	24.92	30.70	-19.30	50.00	19.30	0.99	10.41 Average
12	24.92	44.70	-15.30	60.00	33.30	0.99	10.41 QP



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

The EUT is designed with SMA connector, connected with external Monopole antenna. And the EUT is professionally installed in the Vending Machine.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 20, 2017	Feb. 26, 2018~Mar. 12, 2018	Apr. 19, 2018	Conducted (TH01-SZ)
Pulse Power Senor	Anritsu	MA2411B	1207253	30MHz~40GHz	Dec. 26, 2017	Feb. 26, 2018~Mar. 12, 2018	Dec. 25, 2018	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Dec. 26, 2017	Feb. 26, 2018~Mar. 12, 2018	Dec. 25, 2018	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Apr. 20, 2017	Mar. 08, 2018	Apr. 19, 2018	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY551502 13	10Hz~44GHz	Apr. 20, 2017	Mar. 08, 2018	Apr. 19, 2018	Radiation (03CH04-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 14, 2017	Mar. 08, 2018	May 13, 2018	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	May 16, 2017	Mar. 08, 2018	May 15, 2018	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-128 5	1GHz~18GHz	Dec. 13, 2017	Mar. 08, 2018	Dec. 12, 2018	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	9170#679	15GHz~40GHz	May 17, 2017	Mar. 08, 2018	May 16, 2018	Radiation (03CH04-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 19, 2017	Mar. 08, 2018	Oct. 18, 2018	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-00101 800-30-10P-R	1989346	1GHz~18GHz	Jul. 27, 2017	Mar. 08, 2018	Jul. 26, 2018	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35-H G	1988315	18GHz~40GHz	Jul. 27, 2017	Mar. 08, 2018	Jul. 26, 2018	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY532701 56	500MHz~26.5GHz	Apr. 20, 2017	Mar. 08, 2018	Apr. 19, 2018	Radiation (03CH04-SZ)
AC Power Source	Chroma	61601	N/A	N/A	NCR	Mar. 08, 2018	NCR	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Mar. 08, 2018	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Mar. 08, 2018	NCR	Radiation (03CH04-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 26, 2017	Jan. 23, 2018	Dec. 25, 2018	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Dec. 26, 2017	Jan. 23, 2018	Dec. 25, 2018	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103892	9kHz~30MHz	Nov. 01, 2017	Jan. 23, 2018	Oct. 31, 2018	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000 891	100Vac~250Vac	Jul. 19, 2017	Jan. 23, 2018	Jul. 18, 2018	Conduction (CO01-SZ)

NCR: No Calibration Required



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.6dB
--	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1dB
--	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.8dB
--	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1dB
--	-------



Appendix A. Conducted Test Results

Bluetooth Low Energy

Test Engineer:	Rain Wang			Temperature:	24~26		°C
Test Date:	2018/2/26~2018/3/12			Relative Humidity:	50~53		%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.02	0.70	0.50	Pass
BLE	1Mbps	1	19	2440	1.02	0.71	0.50	Pass
BLE	1Mbps	1	39	2480	1.02	0.70	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	0.07	30.00	-0.10	-0.03	36.00	Pass
BLE	1Mbps	1	19	2440	-0.10	30.00	-0.10	-0.20	36.00	Pass
BLE	1Mbps	1	39	2480	-0.56	30.00	-0.10	-0.66	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.22	-0.86
BLE	1Mbps	1	19	2440	2.22	-1.00
BLE	1Mbps	1	39	2480	2.22	-1.53

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	-2.20	-17.21	-0.10	8.00	Pass
BLE	1Mbps	1	19	2440	-2.51	-17.37	-0.10	8.00	Pass
BLE	1Mbps	1	39	2480	-2.81	-17.79	-0.10	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.



Appendix B. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
												Avg.	
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2385.18	44.12	-29.88	74	40.45	27.37	4.78	28.48	139	58	P	H
		2389.59	34.96	-19.04	54	31.23	27.43	4.78	28.48	139	58	A	H
	*	2402	93.49	-	-	89.64	27.43	4.78	28.36	139	58	P	H
	*	2402	93.03	-	-	89.18	27.43	4.78	28.36	139	58	A	H
		2373.84	44.71	-29.29	74	41.1	27.37	4.72	28.48	322	84	P	V
		2383.395	34.96	-19.04	54	31.35	27.37	4.72	28.48	322	84	A	V
	*	2402	93.21	-	-	89.36	27.43	4.78	28.36	322	84	P	V
	*	2402	92.8	-	-	88.95	27.43	4.78	28.36	322	84	A	V
BLE CH 19 2440MHz		2322.32	44.08	-29.92	74	40.94	27.18	4.66	28.7	160	60	P	H
		2377.2	35.08	-18.92	54	31.47	27.37	4.72	28.48	160	60	A	H
	*	2440	94.5	-	-	90.31	27.61	4.82	28.24	160	60	P	H
	*	2440	94.04	-	-	89.85	27.61	4.82	28.24	160	60	A	H
		2487.12	44.95	-29.05	74	40.37	27.74	4.85	28.01	160	60	P	H
		2497.34	36.03	-17.97	54	31.28	27.8	4.85	27.9	160	60	A	H
		2374.12	44.83	-29.17	74	41.22	27.37	4.72	28.48	322	80	P	V
		2375.8	35.14	-18.86	54	31.53	27.37	4.72	28.48	322	80	A	V
	*	2440	94.45	-	-	90.26	27.61	4.82	28.24	322	80	P	V
	*	2440	93.91	-	-	89.72	27.61	4.82	28.24	322	80	A	V
		2494.54	45.19	-28.81	74	40.44	27.8	4.85	27.9	322	80	P	V
		2490.83	36.05	-17.95	54	31.41	27.8	4.85	28.01	322	80	A	V



BLE CH 39 2480MHz	*	2480	93.35	-	-	88.77	27.74	4.85	28.01	155	59	P	H
	*	2480	92.88	-	-	88.3	27.74	4.85	28.01	155	59	A	H
		2494.52	44.89	-29.11	74	40.14	27.8	4.85	27.9	155	59	P	H
		2491.84	35.87	-18.13	54	31.12	27.8	4.85	27.9	155	59	A	H
	*	2480	93.15	-	-	88.57	27.74	4.85	28.01	326	86	P	V
	*	2480	92.75	-	-	88.17	27.74	4.85	28.01	326	86	A	V
		2498.12	44.99	-29.01	74	40.24	27.8	4.85	27.9	326	86	P	V
		2484.12	36.48	-17.52	54	31.9	27.74	4.85	28.01	326	86	A	V
	Remark 1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	36.46	-37.54	74	57.69	31.44	5.55	58.22	150	0	P	H
		4804	36.3	-37.7	74	57.53	31.44	5.55	58.22	150	0	P	V
BLE CH 19 2440MHz		4880	36.32	-37.68	74	57.16	31.61	5.65	58.1	150	0	P	H
		7320	44.22	-29.78	74	58.64	36.19	7.26	57.87	150	0	P	H
		4880	37.1	-36.9	74	57.94	31.61	5.65	58.1	150	0	P	V
		7320	45.59	-28.41	74	60.01	36.19	7.26	57.87	150	0	P	V
BLE CH 39 2480MHz		4960	38.5	-35.5	74	58.68	31.82	5.96	57.96	150	0	P	H
		7440	44.16	-29.84	74	58.14	36.34	7.17	57.49	150	0	P	H
		4960	37.9	-36.1	74	58.08	31.82	5.96	57.96	150	0	P	V
		7440	43.61	-30.39	74	57.59	36.34	7.17	57.49	150	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
												Limit	Line
												(MHz)	(dB μ V/m)
2.4GHz BLE LF		30.97	24.74	-15.26	40	32.01	24.43	0.27	31.97	-	-	P	H
		98.87	19.71	-23.79	43.5	34.23	16.17	1.05	31.74	-	-	P	H
		260.86	23.19	-22.81	46	32.36	20.33	1.74	31.24	-	-	P	H
		571.26	27.46	-18.54	46	30.82	25.28	2.62	31.26	-	-	P	H
		791.45	31.38	-14.62	46	31.07	28.34	3.14	31.17	-	-	P	H
		899.12	33.59	-12.41	46	32.07	29.29	3.39	31.16	100	210	P	H
		49.4	26.83	-13.17	40	43.15	15.02	0.61	31.95	100	201	P	V
		96.93	22.71	-20.79	43.5	37.5	15.91	1.04	31.74	-	-	P	V
		260.86	22.65	-23.35	46	31.82	20.33	1.74	31.24	-	-	P	V
		515	26.09	-19.91	46	30.6	24.26	2.47	31.24	-	-	P	V
		700.27	28.85	-17.15	46	30.48	26.7	2.93	31.26	-	-	P	V
		827.34	31.43	-14.57	46	30.68	28.72	3.21	31.18	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

**A calculation example for radiated spurious emission is shown as below:**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

$$1. \text{ Level(dB μ V/m)} =$$

$$= \text{Antenna Factor(dB/m)} + \text{Cable Loss(dB)} + \text{Read Level(dB μ V)} - \text{Preamp Factor(dB)}$$

$$2. \text{ Over Limit(dB)} = \text{Level(dB μ V/m)} - \text{Limit Line(dB μ V/m)}$$

For Peak Limit @ 2390MHz:

$$1. \text{ Level(dB μ V/m)}$$

$$= \text{Antenna Factor(dB/m)} + \text{Cable Loss(dB)} + \text{Read Level(dB μ V)} - \text{Preamp Factor(dB)}$$

$$= 32.22(\text{dB/m}) + 4.58(\text{dB}) + 54.51(\text{dB μ V}) - 35.86 (\text{dB})$$

$$= 55.45 (\text{dB μ V/m})$$

$$2. \text{ Over Limit(dB)}$$

$$= \text{Level(dB μ V/m)} - \text{Limit Line(dB μ V/m)}$$

$$= 55.45(\text{dB μ V/m}) - 74(\text{dB μ V/m})$$

$$= -18.55(\text{dB})$$

For Average Limit @ 2390MHz:

$$1. \text{ Level(dB μ V/m)}$$

$$= \text{Antenna Factor(dB/m)} + \text{Cable Loss(dB)} + \text{Read Level(dB μ V)} - \text{Preamp Factor(dB)}$$

$$= 32.22(\text{dB/m}) + 4.58(\text{dB}) + 42.6(\text{dB μ V}) - 35.86 (\text{dB})$$

$$= 43.54 (\text{dB μ V/m})$$

$$2. \text{ Over Limit(dB)}$$

$$= \text{Level(dB μ V/m)} - \text{Limit Line(dB μ V/m)}$$

$$= 43.54(\text{dB μ V/m}) - 54(\text{dB μ V/m})$$

$$= -10.46(\text{dB})$$

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Radiated Spurious Emission Plots


Note symbol

-L	Low channel location
-R	High channel location



2.4GHz 2400~2483.5MHz


BLE (Band Edge @ 3m)





FCC RF Test Report





Report No. : FR7O2504-01B








FCC RF Test Report

Report No. : FR7O2504-01B

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Vertical	Fundamental
Peak		
Avg		









BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Horizontal	
Peak	 <p>Site : 03CH4-S2 Condition : PEAK_BE_74 3m HF_ANT_9120D-1474 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz</p>	
Avg.	 <p>Site : 03CH4-S2 Condition : AVG_BE_54 3m HF_ANT_9120D-1474 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz</p>	



FCC RF Test Report



Report No. : FR7O2504-01B


BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Vertical	Fundamental
Peak	 Site: 03CH04-SZ Condition: PEAK_BE_74 3m HF_ANT_9120D-1474 VERTICAL R9W:1000.000KHz V9W:3.000KHz	 Site: 03CH04-SZ Condition: PEAK_74 3m HF_ANT_9120D-1474 VERTICAL R9W:1000.000KHz V9W:3.000KHz
Avg.	 Site: 03CH04-SZ Condition: AVG_BE_74 3m HF_ANT_9120D-1474 VERTICAL R9W:1000.000KHz V9W:3.000KHz	 Site: 03CH04-SZ Condition: AVG_74 3m HF_ANT_9120D-1474 VERTICAL R9W:1000.000KHz V9W:3.000KHz



FCC RF Test Report

Report No. : FR7O2504-01B





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Vertical	Fundamental
Peak	 <p>Site: 03CH04-SZ Condition: PEAK_BE_74 3m HF_ANT_91200-1474 VERTICAL RBW:1000.000KHz VBW:3000.000KHz</p>	
Avg.	 <p>Site: 03CH04-SZ Condition: AVG_BE_54 3m HF_ANT_91200-1474 VERTICAL RBW:1000.000KHz VBW:3.000KHz</p>	





FCC RF Test Report


Report No. : FR7O2504-01B


BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Vertical	Fundamental
Peak	 <p>Site: 03CH04-S2 Condition: PEAK_BE_74 3m HF_ANT_9120D-1474 VERTICAL RBW:1000.000KHz VBW:3000.000KHz</p>	 <p>Site: 03CH04-S2 Condition: PEAK_74 3m HF_ANT_9120D-1474 VERTICAL RBW:1000.000KHz VBW:3000.000KHz</p>
Avg.	 <p>Site: 03CH04-S2 Condition: AVG_BE_54 3m HF_ANT_9120D-1474 VERTICAL RBW:1000.000KHz VBW:3.000KHz</p>	 <p>Site: 03CH04-S2 Condition: AVG_54 3m HF_ANT_9120D-1474 VERTICAL RBW:1000.000KHz VBW:3.000KHz</p>




2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)










Emission below 1GHz

2.4GHz BLE (LF)



Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth LE	60.05	0.377	2.653	3KHZ

Bluetooth LE

