

## RF exposure evaluation

### § 2.1093 Radiofrequency radiation exposure evaluation: Portable Devices.

**According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.**

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison

For BDR+EDR

Channel	Frequency (GHz)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)
CH 00	2.402	3.2±1	4.2	2.63
CH 39	2.441	4.5±1	5.5	3.55
CH 78	2.480	4.3±1.1	5.4	3.47

Channel	Frequency (GHz)	Power (dBm)	Max. Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 39	2.441	5.48	3.53	5	1.10	3.0

For BLE

Channel	Frequency (GHz)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)
CH 00	2.402	4±1	5	3.16
CH 19	2.440	4±1	5	3.16
CH 39	2.480	4±	5	3.16

Channel	Frequency (GHz)	Power (dBm)	Max. Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 19	2.44	4.84	3.05	5	0.95	3.0

**Result:**

**Base on the calculation value, No SAR measurement is required.**