

# RF Exposure Report

**FCC ID: 2ANXGT1PRO**

## RF Exposure Measurement

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

## RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0
Limits for Maximum Permissible Exposure (MPE)			

F= Frequency in MHz

## Friss Formula

Friss Transmission Formula:  $P_d = (P_{out} * G) / (4\pi r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi = 3.1416$

$R$  = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

## EUT Operation condition

EUT was enabled to transmit and receive at lowest, middle and highest channels.

EUT does not support simultaneous transmission of 2.4G WIFI and 5G WIFI

## Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.

## 2.4G WIFI

Mode	802.11b/g/n20:2412-2462MHz 802.11n40:2422-2452MHz
Detector	Peak
802.11b	24±1dBm
802.11g	24±1dBm
802.11n20	25±1dBm
802.11n40	24±1dBm

## ANT Gain (G)

Antenna number: 1

Antenna A gain : 3dBi

(gain of antenna in linear scale=1.995)

Protocol	ANT Gain(gain of antenna in linear scale)	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
802.11 b	1.995	2412	24.69	294.4422	0.1168617	1
802.11 g	1.995	2412	25.85	384.5918	0.1526413	1
802.11 n20	1.995	2412	25.91	389.942	0.1547647	1
802.11 n40	1.995	2452	25.08	322.1069	0.1278416	1

### 5.8G WIFI

Mode	802.11a/n20/n40/ac20/ac40/ac80: 5.525-5.85GHz
Detector	AV
802.11a	8.82dBm;
802.11n20 (mimo)	11±1dBm
802.11n40 (mimo)	11±1dBm
802.11ac20 (mimo)	11±1dBm
802.11ac40 (mimo)	11±1dBm
802.11ac80 (mimo)	11±1dBm

### ANT Gain (G)

Antenna number: 2

Antenna A gain : 3dBi

Antenna B gain : 3dBi

(gain of antenna in linear scale=1.9952)

MIMO technology Directional gain= 6.01dBi

(gain of antenna in linear scale=3.9902)

Protocol	ANT Gain(gain of antenna in linear scale)	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
802.11 a	1.9952	5745	8.82	7.62079	0.0030249	1
802.11 n20	3.9902	5785	11.216	13.23122	0.0105033	1
802.11 n40	3.9902	5755	11.294	13.47101	0.0106936	1
802.11 ac20	3.9902	5745	11.19	13.15225	0.0104406	1
802.11 ac40	3.9902	5795	11.167	13.08278	0.0103854	1
802.11 ac80	3.9902	5775	11.186	13.14014	0.0104309	1

According to the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know max MPE value 0.1547647 at distance 20cm.

This is less than the limit 1.0 So SAR testing is not required.