



These new models in our OD Series line are optimized for GSM/CDMA networks, and provide dual band operation. With Omni coverage, these antennas provide an excellent option for building out portions of networks, or for use as access/client nodes for Cellular data and telemetry.

These antenna are colinear arrays with elements stacked vertically. Our proven phasing techniques cancel out-of-phase current distribution. The result is improved system performance and high efficiency of transmitted power. This design maintains an omni pattern in the horizontal plane. The entire series of OD antennas require no ground plane for full performance.

The antennas are provided with offset bracket and the U Bolts for pole mounting. The U Bolts can accommodate up to a 2 1/2" outside diameter pole (6.4 cm). As an option, a variety of other mount brackets are available.

These antennas are durable and rugged. They can withstand the harsh environments of snow, wind, rain and ice.

Omni-Directional Dualband Cellular 824-1990 MHz

- Patented Design
- 4 dBi gain for 850/925 MHz Bands, 5 dBi for 1.8/1.9 GHz bands
- Rugged field proven outdoor design
- Mounting kit includes all hardware needed for pole mount (up to 2 1/2" diameter pipe)

Model #	Frequency (MHz)
OD-850/1900-BLK	824-894 MHz 1850-1990 MHz
OD-925/1800-BLK	870-960 MHz 1710-1880 MHz
<u>Color options available for above models</u> WHT-White or BLK-Black	
Model	Options
CA120/400-XX	10 ft LMR-400 N Male-N Plug (Male)
CA120/400-XC	10 ft LMR-400, N Male-SMA (Male)
CA240/400-XX	20 ft LMR-400 N Male-N Plug (Male)
CA240/400-XC	20 ft LMR-400 N Male-SMA (Male)
OD-WMK	Wall Mount Bracket, Right Angle
ACC-102643	Wall Bracket, 4" Stand off
ACC-TW-LP-005N	Surge Arrester, N Jack Female-Female
Note: Some accessories may only be available from the US office, please consult your sales representative.	

Specifications			
Frequency & Gain:		Antenna Diameter:	
824 - 960 MHz	4 dBi	1" (25 mm) main mast	
1710 - 1990 MHz	5 dBi	Antenna Termination:	
VSWR:		N Jack (Female) connector	
2:1 over band		Length/Weight:	
Nominal Impedance:		29.5 inches (74.9 cm)	
50 ohms		2.5 lbs (1.1 kg)	
Max. Power (continuous):		Mounting Kit:	
25 watts		Mast mount kit included	
Vertical Beamwidth (-3 dB point):		Mast Dimensions:	
850/900 MHz bands	35 degrees	Fits mast up to 2 1/2" OD	
1800/1900 MHz Bands	22 degrees	(6.4 cm outside diameter)	
Wind Loading (flat plate equiv.):		Material:	
30 sq. inches (194 sq.cm)		Fiberglass radome with aluminum body	
Rated Wind Velocity:		Options:	
125+ mph (200+ kph)		Wall Mount Brackets, Surge Arrestors and jumper cables available	
Operating Temp:		Shock and Vibration:	
-40° to +85° C		EN 300 019-2-4, IEC 60068	
Lightning Protection:		Water Ingress:	
External suggested		IPx5	