



TEST REPORT

Report No. : CHTEW20010113 Report verification: 
Project No. : SHT1911060704EW
FCC ID : 2ANY6-TE300
Applicant's name : Telo Systems Ltd
Address : 6/F, No.42 Liuxian 1st Road, Bao'an District, Shenzhen, China
Manufacturer : Telo Systems Ltd
Address : 6/F, No.42 Liuxian 1st Road, Bao'an District, Shenzhen, China
Test item description : Smart Phone
Trade Mark : Telo Systems
Model/Type reference : TE300
Listed Model(s) : -
Standard : FCC 47 CFR Part2.1093
IEEE Std C95.1, 1999 Edition
IEEE 1528: 2013
Date of receipt of test sample : Dec. 19, 2019
Date of testing : Dec. 19, 2019- Jan.09, 2020
Date of issue : Jan.10, 2020
Result : PASS

Compiled by
(position+printedname+signature).... : File administrators: Fanghui Zhu
Supervised by
(position+printedname+signature).... : Test Engineer: Xiaodong Zhao
Approved by
(position+printedname+signature).... : Manager: Hans Hu

Fanghui Zhu

Xiaodong Zhao

Hans Hu

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd
Address : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1.</u>	<u>Test Standards and Report version</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>Summary</u>	<u>4</u>
2.1.	Client Information	4
2.2.	Product Description	4
<u>3.</u>	<u>Test Environment</u>	<u>7</u>
3.1.	Test laboratory	7
3.2.	Test Facility	7
3.3.	Environmental conditions	7
<u>4.</u>	<u>Equipments Used during the Test</u>	<u>8</u>
<u>5.</u>	<u>Measurement Uncertainty</u>	<u>9</u>
<u>6.</u>	<u>SAR Measurements System Configuration</u>	<u>10</u>
6.1.	SAR Measurement Set-up	10
6.2.	DASY5 E-field Probe System	11
6.3.	Phantoms	12
6.4.	Device Holder	12
<u>7.</u>	<u>SAR Test Procedure</u>	<u>13</u>
7.1.	Scanning Procedure	13
7.2.	Data Storage and Evaluation	15
<u>8.</u>	<u>Position of the wireless device in relation to the phantom</u>	<u>17</u>
8.1.	Front-of-face	17
8.2.	Body Position	17
<u>9.</u>	<u>Dielectric Property Measurements & System Check</u>	<u>18</u>
9.1.	Tissue Dielectric Parameters	18
9.2.	System Check	20
<u>10.</u>	<u>SAR Exposure Limits</u>	<u>32</u>
<u>11.</u>	<u>Conducted Power Measurement Results</u>	<u>33</u>
11.1.	GSM	33
11.2.	WCDMA	34
11.3.	LTE	37
11.4.	WiFi	57
11.5.	Bluetooth	58
<u>12.</u>	<u>Maximum Tune-up Limit</u>	<u>59</u>
<u>13.</u>	<u>Measured and Reported SAR Results</u>	<u>69</u>
13.1.	Head SAR	71
13.2.	Body SAR	75
<u>14.</u>	<u>Simultaneous Transmission analysis</u>	<u>82</u>
14.1.	Front-of-face	83
14.2.	Body-worn	86
<u>15.</u>	<u>TestSetup Photos</u>	<u>95</u>
<u>16.</u>	<u>External and Internal Photos of the EUT</u>	<u>95</u>

1. Test Standards and Report version

1.1. Test Standards

The tests were performed according to following standards:

[FCC 47 Part 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices.

[IEEE Std C95.1, 1999 Edition](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz

[IEEE Std 1528™-2013](#): IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

FCC published RF exposure KDB procedures:

[865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04](#): SAR Measurement Requirements for 100 MHz to 6 GHz

[865664 D02 RF Exposure Reporting v01r02](#): RF Exposure Compliance Reporting and Documentation Considerations

[447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies

[248227 D01 802.11 Wi-Fi SAR v02r02](#): SAR Measurement Procedures for 802.11 a/b/g Transmitters

[941225 D01 3G SAR Procedures v03r01](#): SAR Measurement Procedures for 3G Devices

[941225 D05 SAR for LTE Devices v02r05](#): SAR Evaluation Considerations for LTE Devices

[TCB workshop](#) April, 2019; Page 19, Tissue Simulating Liquids (TSL)

1.2. Report version

Revision No.	Date of issue	Description
N/A	2020-01-09	Original

2. Summary

2.1. Client Information

Applicant:	Telo Systems Ltd
Address:	6/F, No.42 Liuxian 1st Road, Bao'an District, Shenzhen, China
Manufacturer:	Telo Systems Ltd
Address:	6/F, No.42 Liuxian 1st Road, Bao'an District, Shenzhen, China

2.2. Product Description

Name of EUT:	Smart Phone				
Trade Mark:	Telo Systems				
Model No.:	TE300				
Listed Model(s):	-				
Power supply:	DC 3.7V				
Device Category:	Portable				
Product stage:	Production unit				
RF Exposure Environment:	General Population/Uncontrolled				
IMEI:	357667106000180				
Hardware version:	ET031_V1.2				
Software version:	TE300_US_V2P_20191207				
Device Dimension:	Overall (Length x Width x Thickness): x x mm				
Maximum SAR Value(1g)					
Separation Distance:	Front-of-face:	25mm			
	Body-worn:	0mm			
Max Report SAR Value (W/kg):	Test location:	PCF	DTS	U-NII	Simultaneous Tx
	Front-of-face:	0.391	0.015	0.011	0.406
	Body-worn:	0.824	0.052	0.042	0.847
GSM					
Operation Band:	GSM850 PCS1900				
Support Network:	GSM,GPRS,EGPRS				
Operating Mode:	GSM:GMSK GPRS:GMSK EGPRS:8PSK				
GPRS Multi-Slot Class:	12				
EGPRS Multi-Slot Class:	12				
Antenna Type:	FPC				

WCDMA	
Operation Band:	FDD Band II FDD Band IV FDD Band V
Power Class:	Class 3
Operating Mode:	UMTS Rel. 99 (Voice & Data) HSDPA HSUPA
Antenna Type:	FPC
LTE	
Operation Band:	FDD Band 2 FDD Band 4 FDD Band 5 FDD Band 7 FDD Band 12 FDD Band 17 FDD Band 25 FDD Band 26
Power Class:	Class 3
Operating Mode:	QPSK 16QAM
Antenna Type:	FPC
WiFi 2.4G	
Operating Mode:	802.11b 802.11g 802.11n(HT20) 802.11n(HT40)
Antenna Type:	FPC
WiFi 5G	
Operation Band:	U-NII-1 U-NII-2A U-NII-2C
Operating Mode:	802.11a 802.11n(HT20) 802.11n(HT40)
Antenna Type:	FPC

Bluetooth	
Version:	BT4.0+EDR
Operating Mode:	GFSK $\pi/4$ DQPSK 8DPSK
Antenna Type:	FPC
Bluetooth	
Version:	BT4.0+BLE
Operating Mode:	GFSK
Antenna Type:	FPC
<i>Remark:</i> <i>1. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power.</i>	

3. Test Environment

3.1. Test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

3.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 762235.

IC-Registration No.: 5377A

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Ambient temperature	18 °C to 25 °C
Ambient humidity	30%RH to 70%RH
Air Pressure	950-1050mbar

4. Equipments Used during the Test

Used	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date (YY-MM-DD)	Due date (YY-MM-DD)
●	Data Acquisition Electronics DAEx	SPEAG	DAE4	1549	2019/03/19	2020/03/18
●	E-field Probe	SPEAG	EX3DV4	7494	2019/03/25	2020/03/24
●	Universal Radio Communication Tester	R&S	CMW500	137681	2019/06/27	2020/06/26
● Tissue-equivalent liquids Validation						
●	Dielectric Assessment Kit	SPEAG	DAK-3.5	1267	N/A	N/A
○	Dielectric Assessment Kit	SPEAG	DAK-12	1130	N/A	N/A
●	Network analyzer	Keysight	E5071C	MY46733048	2019/10/19	2020/10/18
● System Validation						
○	System Validation Antenna	SPEAG	CLA-150	4024	2018/02/21	2021/02/20
○	System Validation Dipole	SPEAG	D450V3	1102	2018/02/23	2021/02/22
●	System Validation Dipole	SPEAG	D750V3	1180	2018/02/07	2021/02/06
●	System Validation Dipole	SPEAG	D835V2	4d238	2018/02/19	2021/02/18
●	System Validation Dipole	SPEAG	D1750V2	1164	2018/02/06	2021/02/05
●	System Validation Dipole	SPEAG	D1900V2	5d226	2018/02/22	2021/02/21
●	System Validation Dipole	SPEAG	D2450V2	1009	2018/02/05	2021/02/04
●	System Validation Dipole	SPEAG	D2600V2	1150	2018/02/05	2021/02/04
●	System Validation Dipole	SPEAG	D5GHzV2	1273	2018/02/21	2021/02/20
●	Signal Generator	R&S	SMB100A	114360	2019/08/15	2020/08/14
●	Power Viewer for Windows	R&S	N/A	N/A	N/A	N/A
●	Power sensor	R&S	NRP18A	101010	2019/08/15	2020/08/14
●	Power sensor	R&S	NRP18A	101011	2019/08/15	2020/08/14
●	Power Amplifier	BONN	BLWA 0160-2M	1811887	2019/11/14	2020/11/13
●	Dual Directional Coupler	Mini-Circuits	ZHDC-10-62-S+	F975001814	2019/11/14	2020/11/13
●	Attenuator	Mini-Circuits	VAT-3W2+	1819	2019/11/14	2020/11/13
●	Attenuator	Mini-Circuits	VAT-10W2+	1741	2019/11/14	2020/11/13

Note:

1. The Probe, Dipole and DAE calibration reference to the Appendix B and C.
2. Referring to KDB865664 D01, the dipole calibration interval can be extended to 3 years with justification. The dipole are also not physically damaged or repaired during the interval.

5. Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

Therefore, the measurement uncertainty is not required.

6. SAR Measurements System Configuration

6.1. SAR Measurement Set-up

The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).

A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

A unit to operate the optical surface detector which is connected to the EOC.

The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.

The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2003.

DASY5 software and SEMCAD data evaluation software.


Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.

The generic twin phantom enabling the testing of left-hand and right-hand usage.

The device holder for handheld Mobile Phones.

Tissue simulating liquid mixed according to the given recipes.

System validation dipoles allowing to validate the proper functioning of the system.



6.2. DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

● Probe Specification


Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available.
Frequency	4 MHz to 10 GHz; Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 W/kg; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 6 GHz Dosimetry in strong gradient fields Compliance tests of Mobile Phones
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI



◆ Isotropic E-Field Probe

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change.

The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:



6.3. Phantoms

The phantom used for all tests i.e. for both system checks and device testing, was the twin-headed "SAM Phantom", manufactured by SPEAG. The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness increases to 6mm).

System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.



SAM-Twin Phantom

6.4. Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the DASY system.

The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.



Device holder supplied by SPEAG

7. **SAR Test Procedure**

7.1. **Scanning Procedure**

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT's output power and should vary max. $\pm 5\%$.

The “surface check” measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above $\pm 0.1\text{mm}$). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe (It does not depend on the surface reflectivity or the probe angle to the surface within $\pm 30^\circ$.)

Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot. Before starting the area scan a grid spacing of 15 mm x 15 mm is set. During the scan the distance of the probe to the phantom remains unchanged. After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

Zoom Scan

After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm.

Spatial Peak Detection

The procedure for spatial peak SAR evaluation has been implemented and can determine values of masses of 1g and 10g, as well as for user-specific masses. The DASY5 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maxima searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3-D space.

They are used in the Zoom Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation.

A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 5mm steps.

Table 1: Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v04

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 mm $\pm$ 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2)$ mm $\pm$ 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^{\circ} \pm 1^{\circ}$	$20^{\circ} \pm 1^{\circ}$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$ mm	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.2. Data Storage and Evaluation

Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors),s together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension “.DA4”. The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [W/kg], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	Sensitivity:	Normi, ai0, ai1, ai2
	Conversion factor:	ConvFi
	Diode compression point:	Dcpi
Device parameters:	Frequency:	f
	Crest factor:	cf
Media parameters:	Conductivity:	σ
	Density:	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

Vi:	compensated signal of channel (i = x, y, z)
Ui:	input signal of channel (i = x, y, z)
cf:	crest factor of exciting field (DASY parameter)
dcp _i :	diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$E - \text{fieldprobes : } E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$H - \text{fieldprobes : } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

Vi:	compensated signal of channel (i = x, y, z)
Normi:	sensor sensitivity of channel (i = x, y, z), [mV/(V/m)²] for E-field Probes
ConvF:	sensitivity enhancement in solution
aij:	sensor sensitivity factors for H-field probes
f:	carrier frequency [GHz]
Ei:	electric field strength of channel i in V/m
Hi:	magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1'000}$$


SAR: local specific absorption rate in W/kg
Etot: total field strength in V/m
 σ : conductivity in [mho/m] or [Siemens/m]
 ρ : equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

8. Position of the wireless device in relation to the phantom

8.1. Front-of-face


A typical example of a front-of-face device is a two-way radio that is held at a distance from the face of the user when transmitting. In these cases the device under test shall be positioned at the distance to the phantom surface that corresponds to the intended use as specified by the manufacturer in the user instructions. If the intended use is not specified, a separation distance of 25 mm between the phantom surface and the device shall be used.



Test positions for Front-of-face devices

8.2. Body Position

Devices that support transmission while used with body-worn accessories must be tested for body-worn accessory SAR compliance, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. Devices that are designed to operate on the body of users using lanyards and straps or without requiring additional body-worn accessories must be tested for SAR compliance using a conservative minimum test separation distance $\leq 5\text{mm}$ to support compliance.



Picture 4 Test positions for body-worn devices

9. Dielectric Property Measurements & System Check

9.1. Tissue Dielectric Parameters

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3-4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

The dielectric constant (ϵ_r) and conductivity (σ) of typical tissue-equivalent media recipes are expected to be within $\pm 5\%$ of the required target values; but for SAR measurement systems that have implemented the SAR error compensation algorithms documented in IEEE Std 1528-2013, to automatically compensate the measured SAR results for deviations between the measured and required tissue dielectric parameters, the tolerance for ϵ_r and σ may be relaxed to $\pm 10\%$. This is limited to frequencies ≤ 3 GHz.

Tissue Dielectric Parameters

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Tissue dielectric parameters for Head and Body				
Target Frequency (MHz)	Head		Body	
	ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$
750	41.9	0.89	55.5	0.96
835	41.5	0.90	55.2	0.97
1750	40.1	1.37	53.4	1.49
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
2600	39.0	1.96	52.5	2.16
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5800	35.3	5.27	48.2	6.00

IEEE Std 1528-2013

Refer to Table 3 within the IEEE Std 1528-2013

Dielectric Property Measurements Results:


Dielectric performance of Head tissue simulating liquid									
Frequency (MHz)	ϵ_r		$\sigma(\text{S/m})$		Delta (ϵ_r)	Delta (σ)	Limit	Temp ($^{\circ}\text{C}$)	Date
	Target	Measured	Target	Measured					
750	41.90	43.24	0.890	0.905	3.20%	1.63%	$\pm 5\%$	22.5	2019/12/23
835	41.50	42.98	0.900	0.935	3.57%	3.86%	$\pm 5\%$	22.5	2019/12/24
1750	40.10	41.18	1.370	1.364	2.69%	-0.44%	$\pm 5\%$	22.5	2019/12/25
1900	40.00	40.97	1.400	1.450	2.42%	3.57%	$\pm 5\%$	22.5	2019/12/26
2450	39.20	40.22	1.800	1.830	2.60%	1.67%	$\pm 5\%$	22.5	2020/1/4
2600	39.00	39.99	1.960	1.951	2.54%	-0.46%	$\pm 5\%$	22.5	2019/12/27
5200	36.00	35.60	4.660	4.482	-1.11%	-3.82%	$\pm 5\%$	22.5	2020/1/3
5300	35.90	35.43	4.760	4.594	-1.31%	-3.49%	$\pm 5\%$	22.5	2020/1/3
5500	35.64	35.11	4.963	4.811	-1.49%	-3.06%	$\pm 5\%$	22.5	2020/1/4

9.2. System Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are re-measured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

System Performance Check Measurement Conditions:

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0 ± 0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz and ≥ 10.0 cm for measurements > 3 GHz.
- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube was chosen for the cube.
- The results are normalized to 1 W input power.



System Performance Check Setup




Photo of Dipole Setup

System Check Result:

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within $\pm 10\%$ of the manufacturer calibrated dipole SAR target.

Head											
Frequency (MHz)	1g SAR			10g SAR			Delta (1g)	Delta (10g)	Limit	Temp (°C)	Date
	Target 1W	Normalize to 1W	Measured 250mW	Target 1W	Normalize to 1W	Measured 250mW					
750	8.22	8.64	2.16	5.39	5.68	1.42	5.11%	5.38%	$\pm 10\%$	22.5	2019/12/23
835	9.51	10.12	2.53	6.15	6.56	1.64	6.41%	6.67%	$\pm 10\%$	22.5	2019/12/24
1750	36.60	36.28	9.07	19.40	19.28	4.82	-0.87%	-0.62%	$\pm 10\%$	22.5	2019/12/25
1900	40.30	40.80	10.20	21.10	21.00	5.25	1.24%	-0.47%	$\pm 10\%$	22.5	2019/12/26
2450	51.50	47.20	11.80	24.10	22.28	5.57	-8.35%	-7.55%	$\pm 10\%$	22.5	2020/1/4
2600	55.60	55.20	13.80	25.00	24.68	6.17	-0.72%	-1.28%	$\pm 10\%$	22.5	2019/12/27

Head											
Frequency (MHz)	1g SAR			10g SAR			Delta (1g)	Delta (10g)	Limit	Temp (°C)	Date
	Target 1W	Normalize to 1W	Measured 100mW	Target 1W	Normalize to 1W	Measured 100mW					
5200	79.90	74.80	7.48	22.80	21.40	2.14	-6.38%	-6.14%	$\pm 10\%$	22.5	2020/1/3
5300	81.40	75.30	7.53	23.40	21.40	2.14	-7.49%	-8.55%	$\pm 10\%$	22.5	2020/1/3
5500	86.00	81.30	8.13	24.40	23.00	2.30	-5.47%	-5.74%	$\pm 10\%$	22.5	2020/1/4
5600	83.90	79.50	7.95	24.00	22.60	2.26	-5.24%	-5.83%	$\pm 10\%$	22.5	2020/1/4

Plots of System Performance Check

System Performance Check-Head 750MHz

DUT: D750V3; Type: D750V3; Serial: 1180

Date: 2019-12-23

Communication System: UID 0, A-CW (0); Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 750$ MHz; $\sigma = 0.904$ S/m; $\epsilon_r = 43.241$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.6°C; Liquid Temperature: 22.4°C;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.74, 10.74, 10.74) @ 750 MHz; Calibrated: 3/25/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 3/19/2019
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=15mm, Pin=250mW, dist=1.4mm (EX-Probe)/Area Scan (51x121x1):

Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 2.91 W/kg

Head/d=15mm, Pin=250mW, dist=1.4mm (EX-Probe)/Zoom Scan (7x7x7)


/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 58.91 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 3.46 W/kg

SAR(1 g) = 2.16 W/kg; SAR(10 g) = 1.42 W/kg

Maximum value of SAR (measured) = 2.97 W/kg



System Performance Check-Head 835MHz

DUT: D835V2; Type: D835V2; Serial: 4d238

Date: 2019-12-24

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835$ MHz; $\sigma = 0.935$ S/m; $\epsilon_r = 42.977$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.5°C; Liquid Temperature: 22.3°C;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.41, 10.41, 10.41) @ 835 MHz; Calibrated: 3/25/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 3/19/2019
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=15mm, Pin=250mW/Area Scan (41x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.44 W/kg


Head/d=15mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 54.33 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 4.13 W/kg

SAR(1 g) = 2.53 W/kg; SAR(10 g) = 1.64 W/kg

Maximum value of SAR (measured) = 3.52 W/kg



0 dB = 3.52 W/kg = 5.47 dBW/kg

System Performance Check-Head 1750MHz

DUT: D1750V2; Type: D1750V2; Serial: 1164

Date: 2019-12-25

Communication System: UID 0, CW (0); Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.364$ S/m; $\epsilon_r = 41.185$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 °C; Liquid Temperature: 22.2 °C;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.91, 8.91, 8.91) @ 1750 MHz; Calibrated: 3/25/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 3/19/2019
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm, Pin=250mW/Area Scan (41x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 14.1 W/kg


Head/d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 69.40 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 16.9 W/kg

SAR(1 g) = 9.07 W/kg; SAR(10 g) = 4.82 W/kg

Maximum value of SAR (measured) = 14.0 W/kg



System Performance Check-Head 1900MHz

DUT: D1900V2; Type: D1900V2; Serial: 5d226

Date:2019-12-26

Communication System: UID 0, CW (0); Frequency: 1900 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.45$ S/m; $\epsilon_r = 40.966$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.3°C;Liquid Temperature:22.1°C;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.57, 8.57, 8.57) @ 1900 MHz; Calibrated: 3/25/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 3/19/2019
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm,Pin=250mW/Area Scan (41x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 16.7 W/kg


Head/d=10mm,Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 82.72 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 19.5 W/kg

SAR(1 g) = 10.2 W/kg; SAR(10 g) = 5.25 W/kg

Maximum value of SAR (measured) = 16.0 W/kg



SystemPerformanceCheck-Head 2450MHz

DUT: D2450V2; Type: D2450V2; Serial: 1009

Date: 2020-01-04

Communication System: UID 0, CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2450$ MHz; $\sigma = 1.83$ S/m; $\epsilon_r = 40.217$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.2 °C; Liquid Temperature: 22.0 °C;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(7.9, 7.9, 7.9) @ 2450 MHz; Calibrated: 3/25/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 3/19/2019
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm, Pin=250mW/Area Scan (41x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 19.8 W/kg


Head/d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 70.26 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 24.1 W/kg

SAR(1 g) = 11.8 W/kg; SAR(10 g) = 5.57 W/kg

Maximum value of SAR (measured) = 19.5 W/kg



0 dB = 19.5 W/kg = 12.90 dBW/kg

SystemPerformanceCheck-Head 2600MHz

DUT: D2600V2; Type: D2600V2; Serial: 1150

Date: 2019-12-30

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.951$ S/m; $\epsilon_r = 39.99$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.1 °C; Liquid Temperature: 21.9 °C;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(7.69, 7.69, 7.69) @ 2600 MHz; Calibrated: 3/25/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 3/19/2019
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm,Pin=250mW/Area Scan (41x51x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 24.1 W/kg


Head/d=10mm,Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 100.8 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 29.5 W/kg

SAR(1 g) = 13.8 W/kg; SAR(10 g) = 6.17 W/kg

Maximum value of SAR (measured) = 23.6 W/kg



0 dB = 23.6 W/kg = 13.73 dBW/kg

SystemPerformanceCheck-Head 5200MHz

DUT: D5GHzV2; Type: D5GHzV2; Serial: 1273

Date: 2020-01-03

Communication System: UID 0, CW (0); Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5200$ MHz; $\sigma = 4.49$ S/m; $\epsilon_r = 35.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.1 °C; Liquid Temperature: 21.9 °C;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(5.56, 5.56, 5.56) @ 5200 MHz; Calibrated: 3/25/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 3/19/2019
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm, pin=100mW/Area Scan (41x41x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 18.9 W/kg


Head/d=10mm, pin=100mW/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 56.27 V/m; Power Drift = -0.28 dB

Peak SAR (extrapolated) = 30.9 W/kg

SAR(1 g) = 7.48 W/kg; SAR(10 g) = 2.14 W/kg

Maximum value of SAR (measured) = 17.7 W/kg



0 dB = 17.7 W/kg = 12.48 dBW/kg

SystemPerformanceCheck-Head 5300MHz

DUT: D5GHzV2; Type: D5GHzV2; Serial: 1273

Date: 2020-01-03

Communication System: UID 0, A-CW (0); Frequency: 5300 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5300$ MHz; $\sigma = 4.594$ S/m; $\epsilon_r = 35.429$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.2 °C; Liquid Temperature: 22.0 °C;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(5.37, 5.37, 5.37) @ 5300 MHz; Calibrated: 3/25/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 3/19/2019
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm, Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 18.6 W/kg


Head/d=10mm, Pin=100mW/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 64.93 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 32.2 W/kg

SAR(1 g) = 7.53 W/kg; SAR(10 g) = 2.14 W/kg

Maximum value of SAR (measured) = 17.9 W/kg



0 dB = 17.9 W/kg = 12.53 dBW/kg

SystemPerformanceCheck-Head 5500MHz

DUT: D5GHzV2; Type: D5GHzV2; Serial: 1273

Date: 2020-01-04

Communication System: UID 0, CW (0); Frequency: 5500 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5500$ MHz; $\sigma = 4.811$ S/m; $\epsilon_r = 35.113$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.3 °C; Liquid Temperature: 22.1 °C;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(5, 5, 5) @ 5500 MHz; Calibrated: 3/25/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 3/19/2019
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm, Pin=100mW/Area Scan (41x41x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 21.0 W/kg


Head/d=10mm, Pin=100mW/Zoom Scan(8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 64.84 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 36.3 W/kg

SAR(1 g) = 8.13 W/kg; SAR(10 g) = 2.3 W/kg

Maximum value of SAR (measured) = 20.3 W/kg



SystemPerformanceCheck-Head 5600MHz

DUT: D5GHzV2; Type: D5GHzV2; Serial: 1273

Date: 2020-01-04

Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 4.931$ S/m; $\epsilon_r = 34.929$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.4 °C; Liquid Temperature: 22.2 °C;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(4.89, 4.89, 4.89) @ 5600 MHz; Calibrated: 3/25/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 3/19/2019
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm,Pin=100mW/Area Scan (41x41x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 21.0 W/kg

Head/d=10mm,Pin=100mW/Zoom Scan 2 (8x8x7)/Cube 0: Measurement grid:


dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 64.97 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 36.1 W/kg

SAR(1 g) = 7.95 W/kg; SAR(10 g) = 2.26 W/kg

Maximum value of SAR (measured) = 19.4 W/kg



0 dB = 19.4 W/kg = 12.88 dBW/kg

10. SAR Exposure Limits

SAR assessments have been made in line with the requirements of Part2.1093.

Type Exposure	Limit (W/kg)	
	General Population/ Uncontrolled Exposure Environment	Occupational/ Controlled Exposure Environment
Spatial Average SAR (whole body)	0.08	0.4
Spatial Peak SAR (1g cube tissue for head and trunk)	1.6	8.0
Spatial Peak SAR (10g for limb)	4.0	20.0

Population/Uncontrolled Environments: are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments: are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

11. Conducted Power Measurement Results

11.1. GSM

1. Per KDB 447498 D01, the maximum output power channel is used for SAR testing and further SAR test reduction.
2. Per KDB 941225 D01, considering the possibility of e.g. 3rd party VoIP operation for Head and Body-worn SAR test reduction for GSM and GPRS modes is determined by the source-base time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.
3. Per KDB941225 D01, for hotspot SAR test reduction for GPRS modes is determined by the source-based time-averaged output power including tune-up tolerance, For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

Mode: GSM850		Burst Average Power (dBm)			Division Factors	Frame-Average Power (dBm)		
		CH128	CH190	CH251		CH128	CH190	CH251
		824.2MHz	836.6MHz	848.8MHz		824.2MHz	836.6MHz	848.8MHz
GSM Voice		31.00	31.31	31.25	-9.03	21.97	22.28	22.22
GPRS (GMSK)	1TXslot	30.46	30.70	30.52	-9.03	21.43	21.67	21.49
	2TXslots	30.00	30.21	30.02	-6.02	23.98	24.19	24.00
	3TXslots	30.02	30.23	30.09	-4.26	25.76	25.97	25.83
	4TXslots	29.53	29.71	29.56	-3.01	26.52	26.70	26.55
EGPRS (8PSK)	1TXslot	24.78	24.26	24.09	-9.03	15.75	15.23	15.06
	2TXslots	24.51	24.03	23.85	-6.02	18.49	18.01	17.83
	3TXslots	24.36	23.85	23.71	-4.26	20.10	19.59	19.45
	4TXslots	24.02	23.56	23.39	-3.01	21.01	20.55	20.38
Mode: PCS1900		Burst Average Power (dBm)			Division Factors	Frame-Average Power (dBm)		
		CH512	CH661	CH810		CH512	CH661	CH810
		1850.2MHz	1880MHz	1909.8MHz		1850.2MHz	1880MHz	1909.8MHz
GSM Voice		29.99	29.78	29.45	-9.03	20.96	20.75	20.42
GPRS (GMSK)	1TXslot	29.87	29.52	29.05	-9.03	20.84	20.49	20.02
	2TXslots	29.79	29.47	29.01	-6.02	23.77	23.45	22.99
	3TXslots	29.77	29.36	28.88	-4.26	25.51	25.10	24.62
	4TXslots	29.65	29.29	28.84	-3.01	26.64	26.28	25.83
EGPRS (8PSK)	1TXslot	25.88	25.11	24.71	-9.03	16.85	16.08	15.68
	2TXslots	25.77	25.08	24.61	-6.02	19.75	19.06	18.59
	3TXslots	25.74	25.05	24.51	-4.26	21.48	20.79	20.25
	4TXslots	25.43	24.77	24.25	-3.01	22.42	21.76	21.24

Note:

1) Division Factors

To Frame-Average Power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> Burst Average Power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> Burst Average Power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> Burst Average Power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> Burst Average Power divided by (8/4) => -3.01dB

11.2. WCDMA

1. The following tests were conducted according to the test requirements outlines in 3GPP TS34.121 specification.
2. The procedures in KDB 941225 D01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode to determine SAR test exclusion

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a) The EUT was connected to base station RS CMU200 referred to the setup configuration
- b) The RF path losses were compensated into the measurements
- c) A call was established between EUT and base station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each specific sub-test in the following table, C10.1.4, Quoted from the TS 34.121
 - ii. Set RMC 12.2Kbps + HSDPA mode
 - iii. Set Cell Power=-86dBm
 - iv. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - v. Select HSDPA uplink parameters
 - vi. Set Delta ACK, Delta NACK and Delta CQI=8
 - vii. Set Ack-Nack repetition Factor to 3
 - viii. Set CQI Feedback Cycle (K) to 4ms
 - ix. Set CQI repetition factor to 2
 - x. Power ctrl mode= all up bits
- d) The transmitter maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPCCH, DPCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a) The EUT was connected to base station RS CMU200 referred to the setup configuration
- b) The RF path losses were compensated into the measurements
- c) A call was established between EUT and base station with following setting:
 - i. Call configs = 5.2b, 5.9b, 5.10b, and 5.13.2B with QPSK
 - ii. Set Gain Factors (β_c and β_d) and parameters (AG index) were set according to each specific sub-test in the following table, C11.1.3, Quoted from the TS 34.121
 - iii. Set Cell Power=-86dBm
 - iv. Set channel type= 12.2Kbps + HSPA mode
 - v. Set UE Target power
 - vi. Set Ctrl mode=Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal the target E-TFCI of 75 for Sub-test 1, and other subtest's E-TFCI
- d) The transmitter maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{EC}	β_{ed} (Note 5) (Note 6)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly, it is set by Absolute Grant Value.

Setup Configuration

General Note:

- Per KDB 941225 D01, SAR for Head / Hotspot / Body-worn Exposure is measured using a 12.2Kbps RMC with TPC bit configured to all 1s
- Per KDB 941225 D01 RMC12.2Kbps setting is used to evaluate SAR. If the maximum output power and Tune-up tolerance specified for production units in HSDPA/HSUPA is $\leq 1/4$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC 12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA.

Mode		WCDMA Band II			WCDMA Band IV		
		Conducted Power (dBm)			Conducted Power (dBm)		
		CH9262	CH9400	CH9538	CH1312	CH1413	CH1513
		1852.4MHz	1880MHz	1907.6MHz	1712.4MHz	1732.6MHz	1752.6MHz
AMR 12.2K		23.84	23.85	23.66	24.74	24.82	24.89
RMC 12.2K		23.88	23.89	23.70	24.78	24.86	24.93
HSDPA	Subtest-1	22.90	22.88	22.59	23.70	23.84	23.88
	Subtest-2	22.28	22.39	22.20	23.36	23.50	23.56
	Subtest-3	22.34	22.41	22.22	23.21	23.54	23.59
	Subtest-4	22.29	22.43	22.21	23.41	23.46	23.51
HSUPA	Subtest-1	22.09	22.11	22.11	23.38	23.31	23.37
	Subtest-2	21.42	21.61	21.47	22.67	22.67	22.86
	Subtest-3	20.93	21.54	20.40	22.19	22.21	22.21
	Subtest-4	21.31	21.94	21.27	22.54	22.61	23.18
	Subtest-5	22.55	22.46	22.18	23.32	23.50	23.51

Mode		WCDMA Band V		
		Conducted Power (dBm)		
		CH4132	CH4183	CH4233
		826.4MHz	836.6MHz	846.6MHz
AMR 12.2K		23.30	23.30	23.50
RMC 12.2K		23.34	23.33	23.54
HSDPA	Subtest-1	22.51	22.45	22.57
	Subtest-2	22.07	22.03	22.23
	Subtest-3	22.12	22.07	22.18
	Subtest-4	22.12	21.86	22.18
HSUPA	Subtest-1	21.93	21.43	22.01
	Subtest-2	21.10	20.78	21.44
	Subtest-3	21.18	20.47	20.75
	Subtest-4	21.72	21.23	21.83
	Subtest-5	22.26	22.11	22.49

11.3. LTE

General Note:

1. CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel, bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r03, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r03, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r03, smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, smaller bandwidth SAR testing is not required.

LTE-FDD Band 2				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	18607	18900	19193
				1850.7MHz	1880MHz	1909.3MHz
1.4MHz	QPSK	1	0	23.76	23.65	23.38
			2	23.87	23.76	23.51
			5	23.73	23.76	23.41
		3	0	23.64	23.58	23.65
			1	23.74	23.44	23.63
			3	23.61	23.51	23.53
		6	0	22.57	22.52	22.50
	16QAM	1	0	22.92	23.02	22.72
			2	23.10	23.05	22.38
			5	23.02	22.92	22.79
		3	0	22.27	22.55	22.31
			1	22.30	22.57	22.30
			3	22.76	22.46	22.66
		6	0	21.79	21.70	21.32
Band-width	Modulation	RB allocation	RB offset	18615	18900	19185
				1851.5MHz	1880MHz	1908.5MHz
3MHz	QPSK	1	0	23.67	23.43	23.61
			8	23.45	23.37	23.40
			14	23.80	23.61	23.54
		8	0	22.69	22.60	22.67
			4	22.84	22.66	22.58
			7	22.71	22.64	22.48
		15	0	22.79	22.68	22.44
	16QAM	1	0	22.43	22.40	22.80
			8	22.64	22.72	22.66
			14	22.55	22.58	22.77
		8	0	21.70	21.73	21.70
			4	22.03	21.75	21.50
			7	21.65	21.74	21.67
		15	0	21.99	21.68	21.48

LTE-FDD Band 2				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	18625	18900	19175
				1852.5MHz	1880MHz	1907.5MHz
5MHz	QPSK	1	0	23.53	23.61	23.12
			12	23.52	23.72	23.24
			24	23.53	23.84	23.38
		12	0	22.71	22.66	22.55
			7	22.73	22.62	22.46
			13	22.61	22.57	22.45
		25	0	22.70	22.62	22.52
	16QAM	1	0	22.46	22.66	21.94
			12	22.79	22.58	21.96
			24	22.76	22.56	21.95
		12	0	21.81	21.55	21.46
			7	21.96	21.60	21.46
			13	21.81	21.55	21.47
		25	0	21.75	21.56	21.49
Band-width	Modulation	RB allocation	RB offset	18650	18900	19150
				1855MHz	1880MHz	1905MHz
10MHz	QPSK	1	0	23.85	23.69	23.43
			24	23.77	23.82	23.46
			49	23.79	23.88	23.34
		25	0	22.84	22.78	22.67
			24	22.81	22.73	22.67
			49	22.68	22.61	22.39
		50	0	22.72	22.64	22.60
	16QAM	1	0	23.12	23.06	22.34
			24	22.57	22.96	22.46
			49	22.57	23.02	22.76
		25	0	21.98	21.66	21.74
			24	21.95	21.92	21.74
			49	21.77	21.83	21.57
		50	0	21.94	21.77	21.69

LTE-FDD Band 2				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	18675	18900	19125
				1857.5MHz	1880MHz	1902.5MHz
15MHz	QPSK	1	0	24.14	23.90	23.63
			38	23.37	23.52	23.24
			74	23.73	23.67	23.25
		38	0	22.56	22.72	23.15
			18	22.62	22.68	22.21
			37	22.94	22.36	22.17
		75	0	22.67	22.59	22.41
	16QAM	1	0	22.83	23.08	22.55
			38	22.72	22.93	22.41
			74	22.90	22.74	22.21
		38	0	22.36	22.98	22.98
			18	22.68	22.35	22.26
			37	22.84	22.12	22.10
		75	0	21.54	21.61	21.43
Band-width	Modulation	RB allocation	RB offset	18700	18900	19100
				1860MHz	1880MHz	1900MHz
20MHz	QPSK	1	0	23.97	23.64	23.59
			49	24.15	23.89	23.47
			99	23.81	23.63	23.36
		50	0	22.68	22.58	22.59
			25	22.66	22.59	22.48
			50	22.70	22.46	22.41
		100	0	22.64	22.46	22.42
	16QAM	1	0	23.24	23.01	22.57
			49	23.21	23.11	22.53
			99	23.04	22.75	22.59
		50	0	21.76	21.69	21.44
			25	21.77	21.64	21.47
			50	21.84	21.53	21.46
		100	0	21.71	21.51	21.44

LTE-FDD Band 4				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	19957	20175	20393
				1710.7MHz	1732.5MHz	1754.3MHz
1.4MHz	QPSK	1	0	23.52	23.64	23.88
			2	23.60	24.03	24.24
			5	23.63	23.90	24.11
		3	0	23.51	24.09	24.10
			1	23.57	23.92	24.01
			3	23.58	23.88	23.96
		6	0	22.67	23.08	22.98
	16QAM	1	0	22.60	22.90	22.54
			2	22.79	22.57	22.36
			5	22.27	22.64	22.47
		3	0	22.51	22.95	23.09
			1	22.51	22.96	23.10
			3	22.51	22.89	23.02
		6	0	21.57	22.08	22.12
Band-width	Modulation	RB allocation	RB offset	19965	20175	20385
				1711.5MHz	1732.5MHz	1753.5MHz
3MHz	QPSK	1	0	23.50	23.90	24.02
			8	23.56	23.71	24.27
			14	23.64	23.80	24.34
		8	0	22.78	23.06	23.18
			4	22.85	22.92	23.21
			7	22.86	22.91	23.15
		15	0	22.86	22.98	23.01
	16QAM	1	0	22.64	22.87	23.20
			8	22.73	23.00	23.20
			14	22.49	22.95	23.30
		8	0	21.94	22.04	22.29
			4	21.92	22.02	22.09
			7	21.99	22.06	22.11
		15	0	21.88	21.91	22.16

LTE-FDD Band 4				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	19975	20175	20375
				1712.5MHz	1732.5MHz	1752.5MHz
5MHz	QPSK	1	0	23.89	23.94	23.93
			12	23.69	23.85	24.09
			24	23.87	24.03	24.10
		12	0	22.60	23.06	23.24
			7	22.72	22.98	23.27
			13	22.70	22.98	23.15
		25	0	22.64	23.04	23.24
	16QAM	1	0	22.48	23.02	22.93
			12	23.00	23.15	23.19
			24	22.83	23.10	22.94
		12	0	21.84	22.21	22.14
			7	21.65	22.18	22.28
			13	22.03	22.12	22.30
		25	0	21.58	22.17	22.49
Band-width	Modulation	RB allocation	RB offset	20000	20175	20350
				1715MHz	1732.5MHz	1750MHz
10MHz	QPSK	1	0	23.31	23.63	23.59
			24	23.52	23.27	23.84
			49	23.77	23.36	23.79
		25	0	22.48	22.50	22.61
			24	22.50	22.47	22.62
			49	22.54	22.46	22.73
		50	0	22.50	22.48	22.63
	16QAM	1	0	22.27	22.24	22.87
			24	22.39	22.53	22.88
			49	22.44	22.63	22.79
		25	0	21.49	21.70	21.60
			24	21.36	21.73	21.76
			49	21.43	21.70	21.89
		50	0	21.47	21.62	21.74

LTE-FDD Band 4				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	20025	20175	20325
				1717.5MHz	1732.5MHz	1747.5MHz
15MHz	QPSK	1	0	23.49	23.59	23.85
			38	23.57	23.40	23.87
			74	23.92	23.62	24.16
		38	0	22.18	22.58	22.86
			18	22.50	22.30	22.89
			37	22.57	22.39	22.52
		75	0	22.64	22.74	22.92
	16QAM	1	0	22.46	23.00	23.19
			38	22.37	22.83	23.03
			74	22.66	23.04	23.06
		38	0	22.24	23.00	22.90
			18	22.19	22.30	22.87
			37	22.34	22.39	22.17
		75	0	21.55	21.80	22.05
Band-width	Modulation	RB allocation	RB offset	20050	20175	20300
				1720MHz	1732.5MHz	1745MHz
20MHz	QPSK	1	0	23.51	23.98	23.81
			49	23.90	23.71	24.51
			99	23.85	23.83	23.59
		50	0	22.59	23.04	22.95
			25	22.65	22.86	22.95
			50	22.82	22.80	23.10
		100	0	22.67	22.89	23.01
	16QAM	1	0	22.48	23.21	22.79
			49	22.79	23.08	23.31
			99	22.98	23.13	22.81
		50	0	21.76	22.08	22.05
			25	21.63	22.03	22.09
			50	21.80	21.99	22.12
		100	0	21.77	21.99	22.08

LTE-FDD Band 5				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	20407	20525	20643
				8.4.7MHz	836.5MHz	848.3MHz
1.4MHz	QPSK	1	0	22.38	22.60	22.70
			2	22.51	22.52	22.59
			5	22.77	22.56	22.62
		3	0	22.46	22.71	22.77
			1	22.53	22.70	22.57
			3	22.65	22.55	22.61
		6	0	21.60	21.85	21.70
	16QAM	1	0	21.55	21.62	22.09
			2	21.94	21.90	22.15
			5	22.02	21.96	22.07
		3	0	21.69	21.91	21.59
			1	21.68	21.73	21.79
			3	21.72	21.73	21.73
		6	0	20.64	21.02	20.71
Band-width	Modulation	RB allocation	RB offset	20415	20525	20635
				825.5MHz	836.5MHz	847.5MHz
3MHz	QPSK	1	0	22.33	22.20	22.26
			8	22.48	22.17	22.15
			14	22.52	22.44	22.17
		8	0	21.37	21.66	21.65
			4	21.38	21.40	21.46
			7	21.56	21.37	21.29
		15	0	21.45	21.35	21.49
	16QAM	1	0	21.51	21.59	21.33
			8	21.59	21.44	21.37
			14	21.59	21.52	21.34
		8	0	20.57	20.49	20.50
			4	20.57	20.51	20.63
			7	20.53	20.66	20.41
		15	0	20.62	20.61	20.49

LTE-FDD Band 5				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	20425	20525	20625
				826.5MHz	836.5MHz	846.5MHz
5MHz	QPSK	1	0	22.30	22.31	22.22
			12	22.55	22.36	22.23
			24	22.36	22.37	22.09
		12	0	21.37	21.61	21.67
			7	21.41	21.43	21.63
			13	21.50	21.44	21.43
		25	0	21.41	21.45	21.47
	16QAM	1	0	21.47	21.36	21.07
			12	21.61	21.65	21.01
			24	21.77	21.61	21.45
		12	0	20.49	20.63	20.69
			7	20.57	20.57	20.62
			13	20.48	20.57	20.50
		25	0	20.45	20.57	20.58
Band-width	Modulation	RB allocation	RB offset	20450	20525	20600
				829MHz	836.5MHz	844MHz
10MHz	QPSK	1	0	22.18	22.50	22.58
			24	22.67	22.43	22.92
			49	22.24	22.59	22.34
		25	0	21.59	21.74	21.59
			24	21.49	21.60	21.56
			49	21.48	21.55	21.58
		50	0	21.48	21.50	21.51
	16QAM	1	0	21.33	21.76	21.89
			24	21.32	21.79	22.02
			49	21.21	21.66	21.31
		25	0	20.45	20.85	20.52
			24	20.51	20.76	20.61
			49	20.45	20.83	20.45
		50	0	20.51	20.47	20.49

LTE-FDD Band 7				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	20775	21100	21425
				2502.5MHz	2535MHz	2567.5MHz
5MHz	QPSK	1	0	22.77	22.65	22.54
			12	22.59	22.62	22.76
			24	22.73	22.64	22.82
		12	0	21.98	21.69	21.67
			7	21.94	21.66	21.71
			13	21.99	21.67	21.78
		25	0	21.96	21.72	21.67
	16QAM	1	0	21.81	21.72	21.63
			12	21.92	21.96	21.66
			24	21.81	21.81	21.72
		12	0	20.71	20.79	20.89
			7	20.79	20.78	20.91
			13	20.88	20.92	20.83
		25	0	20.99	20.57	20.78
Band-width	Modulation	RB allocation	RB offset	20800	21100	21400
				2505MHz	2535MHz	2565MHz
10MHz	QPSK	1	0	23.46	22.89	23.01
			24	23.12	22.90	22.93
			49	23.04	22.70	22.99
		25	0	22.38	21.93	21.90
			24	22.20	21.90	21.90
			49	22.17	21.93	21.98
		50	0	22.25	21.89	21.98
	16QAM	1	0	22.11	21.98	21.67
			24	22.38	21.64	21.94
			49	22.30	21.54	21.64
		25	0	21.26	21.00	20.99
			24	21.27	20.99	21.00
			49	21.19	20.84	20.97
		50	0	21.28	20.91	20.85

LTE-FDD Band 7				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	20825	21100	21375
				2507.5MHz	2535MHz	2562.5MHz
15MHz	QPSK	1	0	23.53	23.19	23.09
			38	23.23	22.91	23.00
			74	23.14	23.04	23.31
		38	0	22.43	22.43	21.86
			18	22.16	22.04	22.07
			37	22.32	22.16	22.63
		75	0	22.38	22.00	22.15
	16QAM	1	0	22.05	22.40	22.33
			38	22.09	22.01	22.03
			74	22.35	22.23	22.23
		38	0	22.48	22.12	22.37
			18	21.97	22.27	22.16
			37	22.08	22.18	22.69
		75	0	21.36	21.21	21.32
Band-width	Modulation	RB allocation	RB offset	20850	21100	21350
				2510MHz	2535MHz	2560MHz
20MHz	QPSK	1	0	23.52	23.25	23.26
			49	23.32	23.18	23.20
			99	23.31	23.19	23.79
		50	0	22.48	22.21	22.14
			25	22.41	22.15	22.24
			50	22.39	22.04	22.23
		100	0	22.37	22.10	22.12
	16QAM	1	0	22.76	22.63	22.31
			49	22.84	22.37	22.51
			99	22.53	22.24	22.15
		50	0	21.59	21.35	21.17
			25	21.59	21.16	21.24
			50	21.35	21.11	20.97
		100	0	21.45	21.21	21.21

LTE-FDD Band 12				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	23017	23095	23173
				699.7MHz	707.5MHz	715.3MHz
1.4MHz	QPSK	1	0	21.90	21.85	21.71
			2	21.91	21.98	21.93
			5	22.04	21.84	21.88
		3	0	21.82	21.78	21.70
			1	21.98	21.84	21.71
			3	21.97	21.88	21.81
		6	0	20.83	20.96	20.90
	16QAM	1	0	21.28	20.61	20.44
			2	21.41	20.96	20.85
			5	21.36	20.85	20.99
		3	0	20.65	20.58	20.51
			1	20.74	20.61	20.53
			3	20.61	20.79	20.70
		6	0	20.69	20.86	20.84
Band-width	Modulation	RB allocation	RB offset	23025	23095	23165
				700.5MHz	707.5MHz	714.5MHz
3MHz	QPSK	1	0	21.79	21.89	22.09
			8	22.02	21.70	22.07
			14	21.76	21.85	22.27
		8	0	20.81	20.93	20.88
			4	20.97	21.01	20.99
			7	21.04	20.98	20.92
		15	0	20.91	21.01	20.86
	16QAM	1	0	20.69	20.89	21.11
			8	20.75	21.08	21.03
			14	20.73	20.76	21.19
		8	0	20.98	20.40	20.90
			4	20.99	20.88	20.93
			7	20.95	20.90	20.88
		15	0	20.83	20.97	20.73

LTE-FDD Band 12				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	23035	23095	23155
				701.5MHz	707.5MHz	713.5MHz
5MHz	QPSK	1	0	21.75	21.93	21.76
			12	21.85	22.13	21.77
			24	22.01	21.94	21.99
		12	0	20.92	20.98	20.96
			7	20.92	21.06	20.99
			13	20.90	20.97	20.95
		25	0	20.98	20.89	21.09
	16QAM	1	0	20.79	20.96	20.77
			12	21.03	21.00	20.72
			24	21.13	20.69	20.80
		12	0	20.66	20.90	20.92
			7	20.94	20.99	20.80
			13	20.84	20.81	20.73
		25	0	20.79	20.88	20.79
Band-width	Modulation	RB allocation	RB offset	23060	23095	23130
				704MHz	707.5MHz	711MHz
10MHz	QPSK	1	0	21.83	22.02	22.23
			24	22.10	22.32	22.07
			49	22.03	22.01	22.08
		25	0	20.94	21.04	21.13
			24	20.99	21.10	21.05
			49	21.08	20.98	21.04
		50	0	20.97	21.03	21.10
	16QAM	1	0	20.98	21.33	21.04
			24	21.13	21.12	20.98
			49	20.65	21.20	20.99
		25	0	20.97	20.85	20.93
			24	20.95	20.74	20.81
			49	20.75	20.90	20.84
		50	0	20.95	20.80	20.70

LTE-FDD Band 17				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	23755	23790	23825
				706.5MHz	710MHz	713.5MHz
5MHz	QPSK	1	0	22.89	22.97	22.82
			12	22.93	23.15	23.10
			24	23.06	23.17	22.92
		12	0	22.10	22.24	22.20
			7	22.20	22.21	22.10
			13	22.19	22.17	22.14
		25	0	22.11	22.14	22.34
	16QAM	1	0	22.13	22.14	21.39
			12	22.29	22.13	22.16
			24	22.16	22.24	22.02
		12	0	21.38	21.22	21.14
			7	21.38	21.19	21.06
			13	21.26	21.13	21.28
		25	0	21.11	21.26	21.35
Band-width	Modulation	RB allocation	RB offset	23780	23790	23800
				709MHz	710MHz	711MHz
10MHz	QPSK	1	0	23.32	23.32	23.20
			24	23.01	23.16	23.11
			49	23.03	23.40	23.16
		25	0	22.27	22.22	22.29
			24	22.18	22.28	22.24
			49	22.17	22.25	22.16
		50	0	22.16	22.15	22.22
	16QAM	1	0	22.49	22.44	22.23
			24	22.19	22.15	22.18
			49	22.33	22.54	22.14
		25	0	21.15	21.26	21.18
			24	21.10	21.04	21.21
			49	21.09	21.31	21.16
		50	0	21.28	21.22	21.10

LTE-FDD Band 25				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	26047	26365	26683
				1850.7MHz	1882.5MHz	1914.3MHz
1.4MHz	QPSK	1	0	23.79	23.25	23.53
			2	23.68	23.52	23.14
			5	23.58	23.11	23.52
		3	0	23.53	23.33	23.12
			1	23.50	23.39	23.24
			3	23.43	23.36	23.41
		6	0	23.43	23.48	23.33
	16QAM	1	0	23.04	23.59	23.34
			2	22.97	23.44	23.31
			5	22.84	23.36	23.41
		3	0	22.62	23.34	23.31
			1	22.58	23.41	23.21
			3	22.53	23.25	23.24
		6	0	22.65	22.53	22.34
Band-width	Modulation	RB allocation	RB offset	26055	26365	26675
				1851.5MHz	1882.5MHz	1913.5MHz
3MHz	QPSK	1	0	23.47	23.34	23.64
			8	23.43	23.36	23.34
			14	23.45	23.24	23.36
		8	0	23.37	23.37	23.66
			4	23.37	23.58	23.36
			7	23.32	23.45	23.68
		15	0	23.33	23.43	23.39
	16QAM	1	0	22.76	22.56	22.36
			8	22.70	22.20	22.45
			14	22.67	22.69	22.85
		8	0	22.54	22.63	22.34
			4	22.52	22.56	22.85
			7	22.50	22.46	22.47
		15	0	22.42	22.44	22.52

LTE-FDD Band 25				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	26065	26365	26665
				1852.5MHz	1882.5MHz	1912.5MHz
5MHz	QPSK	1	0	24.56	24.38	24.56
			12	24.56	24.43	24.63
			24	24.12	24.57	24.12
		12	0	23.43	23.46	23.52
			7	23.43	23.48	23.36
			13	23.42	23.35	23.58
		25	0	23.39	23.46	23.37
	16QAM	1	0	23.04	23.40	23.52
			12	22.84	23.42	23.69
			24	23.01	23.42	23.66
		12	0	22.70	22.66	22.37
			7	22.67	22.68	22.37
			13	22.66	22.57	22.36
		25	0	22.57	22.53	23.36
Band-width	Modulation	RB allocation	RB offset	26090	26365	26640
				1855MHz	1882.5MHz	1910MHz
10MHz	QPSK	1	0	23.69	23.67	23.69
			24	23.43	23.52	23.63
			49	23.72	23.80	23.39
		25	0	23.17	23.59	23.75
			24	23.14	23.42	23.19
			49	23.55	23.32	23.23
		50	0	23.29	23.47	22.63
	16QAM	1	0	22.32	22.37	22.39
			24	22.71	22.63	22.37
			49	22.69	22.83	22.07
		25	0	22.37	22.58	22.31
			24	22.33	22.35	22.35
			49	22.74	22.38	22.39
		50	0	22.49	22.49	21.84

LTE-FDD Band 25				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	26115	26365	26615
				1857.5MHz	1882.5MHz	1907.5MHz
15MHz	QPSK	1	0	23.19	23.36	23.24
			38	23.65	23.33	23.82
			74	23.24	23.66	23.23
		38	0	23.47	23.69	23.25
			18	23.09	23.58	23.02
			37	23.25	22.78	23.63
		75	0	23.54	23.89	23.41
	16QAM	1	0	23.96	23.64	23.30
			38	23.03	23.57	23.21
			74	23.78	23.39	23.37
		38	0	23.63	23.90	23.24
			18	23.08	23.56	23.16
			37	23.19	23.37	23.96
		75	0	22.68	22.58	22.57
Band-width	Modulation	RB allocation	RB offset	26140	26365	26590
				1860MHz	1882.5MHz	1905MHz
20MHz	QPSK	1	0	22.31	22.38	22.71
			49	22.45	22.56	22.87
			99	22.53	22.40	22.68
		50	0	22.34	22.37	22.85
			25	22.32	22.70	22.82
			50	22.52	22.86	22.31
		100	0	22.43	22.69	23.09
	16QAM	1	0	22.03	22.68	22.92
			49	22.03	22.65	22.93
			99	22.31	22.73	22.87
		50	0	22.14	22.67	22.87
			25	22.07	22.36	22.03
			50	22.31	22.50	22.43
		100	0	23.23	23.45	23.37

LTE-FDD Band 26				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	26697	26865	27033
				814.7MHz	831.5MHz	848.3MHz
1.4MHz	QPSK	1	0	22.11	22.46	21.92
			2	22.21	22.38	21.61
			5	22.11	22.22	21.66
		3	0	21.63	21.55	21.91
			1	21.98	21.63	21.75
			3	21.53	22.49	21.65
		6	0	21.09	21.62	21.76
	16QAM	1	0	21.52	21.37	21.28
			2	21.48	21.75	21.24
			5	21.41	21.40	21.12
		3	0	21.02	21.47	21.67
			1	21.05	21.71	21.70
			3	21.12	21.65	21.29
		6	0	21.22	21.63	21.82
Band-width	Modulation	RB allocation	RB offset	26705	26865	27025
				815.5MHz	831.5MHz	847.5MHz
3MHz	QPSK	1	0	22.18	22.99	22.35
			8	22.13	22.25	22.41
			14	22.30	22.59	22.74
		8	0	21.03	21.87	21.01
			4	21.18	21.93	21.93
			7	21.26	21.41	21.68
		15	0	21.11	21.66	21.89
	16QAM	1	0	21.43	22.09	21.79
			8	21.26	21.43	21.80
			14	21.20	21.63	21.71
		8	0	21.24	20.88	20.93
			4	20.32	20.85	21.00
			7	20.34	20.77	20.88
		15	0	21.14	21.52	21.90

LTE-FDD Band 26				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	26715	26865	27015
				816.5MHz	831.5MHz	846.5MHz
5MHz	QPSK	1	0	21.96	21.37	21.77
			12	21.52	21.48	21.20
			24	21.46	21.81	21.55
		12	0	21.26	21.53	21.55
			7	21.24	21.55	21.33
			13	21.05	21.04	21.59
		25	0	21.60	21.32	21.64
	16QAM	1	0	21.14	21.80	21.78
			12	21.30	20.80	21.34
			24	21.30	21.16	21.55
		12	0	21.24	20.68	21.48
			7	21.32	21.52	21.49
			13	21.08	21.10	21.67
		25	0	21.75	21.35	21.59
Band-width	Modulation	RB allocation	RB offset	26740	26865	26990
				819MHz	831.5MHz	844MHz
10MHz	QPSK	1	0	21.99	21.52	21.94
			24	21.91	21.52	21.25
			49	21.33	21.95	21.58
		25	0	21.85	21.61	21.39
			24	21.55	21.54	21.85
			49	21.33	21.52	21.63
		50	0	20.53	21.30	20.91
	16QAM	1	0	21.48	21.93	21.87
			24	21.55	21.87	21.55
			49	21.78	21.10	21.63
		25	0	20.79	20.73	21.01
			24	20.69	20.61	20.99
			49	20.72	20.91	21.46
		50	0	20.65	20.48	20.89

LTE-FDD Band 26				Conducted Power(dBm)		
Band-width	Modulation	RB allocation	RB offset	26765	26865	26965
				821.5MHz	831.5MHz	841.5MHz
15MHz	QPSK	1	0	21.41	21.99	21.52
			38	21.56	21.66	21.78
			74	21.60	21.03	21.55
		38	0	21.52	21.69	21.38
			18	21.36	21.87	21.96
			37	21.54	21.13	21.85
		75	0	20.83	21.05	20.96
	16QAM	1	0	21.56	21.12	21.43
			38	21.51	21.57	21.06
			74	21.05	21.28	20.75
		38	0	21.43	21.64	21.29
			18	21.46	21.33	21.74
			37	21.27	21.89	21.87
		75	0	21.83	21.26	21.11

11.4. WiFi

For 2.4GHz WiFi SAR testing, highest average RF output power channel for the lowest data rate for 802.11b were for SAR evaluation.

The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures.

SAR testing is not required for OFDM mode(s) when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

WiFi 2.4G				
Mode	Channel	Frequency (MHz)	Conducted Peak Power (dBm)	Conducted Average Power (dBm)
802.11b	1	2412	13.27	11.56
	6	2437	13.89	11.67
	11	2462	15.20	13.41
802.11g	1	2412	14.61	12.58
	6	2437	14.99	12.61
	11	2462	13.63	11.42
802.11n (HT20)	1	2412	14.26	12.75
	6	2437	14.62	12.93
	11	2462	13.52	11.85

WiFi 5G U-NII-1			
Mode	Channel	Frequency (MHz)	Conducted Average Power (dBm)
802.11n (HT20)	36	5180	11.29
	40	5200	9.86
	48	5240	9.77
802.11a	36	5180	11.22
	40	5200	9.86
	48	5240	9.76
802.11n (HT40)	38	5190	11.40
	46	5230	10.21

WiFi 5G U-NII-2A			
Mode	Channel	Frequency (MHz)	Conducted Average Power (dBm)
802.11n (HT20)	52	5260	9.55
	56	5280	9.03
	64	5320	7.06
802.11a	52	5260	9.53
	56	5280	8.96
	64	5320	6.97
802.11n (HT40)	54	5270	9.81
	62	5310	8.15

WiFi 5G U-NII-2C			
Mode	Channel	Frequency (MHz)	Conducted Average Power (dBm)
802.11n (HT20)	100	5500	5.26
	120	5600	5.67
	140	5700	7.99
802.11a	100	5500	5.17
	120	5600	5.67
	140	5700	7.94
802.11n (HT40)	102	5510	5.91
	118	5590	6.21
	134	5670	7.79

11.5. Bluetooth

Bluetooth				
Mode	Channel	Frequency (MHz)	Conducted Peak Power (dBm)	Conducted Average Power (dBm)
GFSK	0	2402	8.39	7.85
	39	2441	9.18	8.62
	78	2480	5.77	5.24
$\pi/4$ QPSK	0	2402	8.47	8.01
	39	2441	9.34	8.85
	78	2480	5.82	5.43
8DPSK	0	2402	8.64	8.48
	39	2441	9.53	9.02
	78	2480	6.03	5.46
GFSK(BLE)	0	2402	-0.96	-0.97
	19	2440	-0.20	-0.21
	39	2480	-3.17	-3.19

12. Maximum Tune-up Limit

GSM		
Mode	Maximum Tune-up (dBm)	
	GSM850	PCS1900
GSM (GMSK, 1Tx Slot)	31.50	30.00
GPRS (GMSK, 1Tx Slot)	31.00	30.00
GPRS (GMSK, 2Tx Slots)	30.50	30.00
GPRS (GMSK, 3Tx Slots)	30.50	30.00
GPRS (GMSK, 4Tx Slots)	30.00	30.00
EGPRS (8PSK, 1Tx Slot)	25.00	26.00
EGPRS (8PSK, 2Tx Slots)	25.00	26.00
EGPRS (8PSK, 3Tx Slots)	24.50	26.00
EGPRS (8PSK, 4Tx Slots)	24.50	25.50

WCDMA			
Mode	Maximum Tune-up (dBm)		
	FDD Band II	FDD Band IV	FDD Band V
AMR 12.2Kbps	24.00	25.00	24.00
RMC 12.2Kbps	24.00	25.00	24.00
HSDPA Subtest-1	23.00	24.00	23.00
HSDPA Subtest-2	22.50	24.00	22.50
HSDPA Subtest-3	22.50	24.00	22.50
HSDPA Subtest-4	22.50	24.00	22.50
HSUPA Subtest-1	22.50	23.50	22.50
HSUPA Subtest-2	22.00	23.00	21.50
HSUPA Subtest-3	22.00	22.50	21.50
HSUPA Subtest-4	22.00	23.50	22.00
HSUPA Subtest-5	23.00	24.00	22.50

LTE				
Frequency Band	Band-width(MHz)	Modulation	RB allocation	Maximum Tune-up (dBm)
FDD Band 2	1.4	QPSK	1	24.00
			3	24.00
			6	23.00
		16QAM	1	23.50
			3	23.00
			6	22.00
	3	QPSK	1	24.00
			8	23.00
			15	23.00
		16QAM	1	23.00
			8	22.50
			15	22.00
	5	QPSK	1	24.00
			12	23.00
			25	23.00
		16QAM	1	23.00
			12	22.00
			25	22.00
	10	QPSK	1	24.00
			25	23.00
			50	23.00
		16QAM	1	23.50
			25	22.00
			50	22.00
	15	QPSK	1	24.50
			38	23.50
			75	23.00
		16QAM	1	23.50
			38	23.00
			75	22.00
	20	QPSK	1	24.50
			50	23.00
			100	23.00
		16QAM	1	23.50
			50	22.00
			100	22.00

LTE				
Frequency Band	Band-width(MHz)	Modulation	RB allocation	Maximum Tune-up (dBm)
FDD Band 4	1.4	QPSK	1	24.50
			3	24.50
			6	23.50
		16QAM	1	23.00
			3	23.50
			6	22.50
	3	QPSK	1	24.50
			8	23.50
			15	23.50
		16QAM	1	23.50
			8	22.50
			15	22.50
	5	QPSK	1	24.50
			12	23.50
			25	23.50
		16QAM	1	23.50
			12	22.50
			25	22.50
	10	QPSK	1	24.00
			25	23.00
			50	23.00
		16QAM	1	23.00
			25	22.00
			50	22.00
	15	QPSK	1	24.50
			38	23.00
			75	23.00
		16QAM	1	23.50
			38	23.00
			75	22.50
	20	QPSK	1	25.00
			50	23.50
			100	23.50
		16QAM	1	23.50
			50	22.50
			100	22.50

LTE				
Fequency Band	Band-width(MHz)	Modulation	RB allocation	Maximum Tune-up (dBm)
FDD Band 5	1.4	QPSK	1	23.00
			3	23.00
			6	22.00
		16QAM	1	22.50
			3	22.00
			6	21.50
	3	QPSK	1	23.00
			8	22.00
			15	21.50
		16QAM	1	22.00
			8	21.00
			15	21.00
	5	QPSK	1	23.00
			12	22.00
			25	21.50
		16QAM	1	22.00
			12	21.00
			25	21.00
	10	QPSK	1	23.00
			25	22.00
			50	22.00
		16QAM	1	22.50
			25	21.00
			50	21.00

LTE				
Fequency Band	Band-width(MHz)	Modulation	RB allocation	Maximum Tune-up (dBm)
FDD Band 7	5	QPSK	1	23.00
			12	22.00
			25	22.00
		16QAM	1	22.00
			12	21.00
			25	21.00
	10	QPSK	1	23.50
			25	22.50
			50	22.50
		16QAM	1	22.50
			25	21.50
			50	21.50
	15	QPSK	1	24.00
			38	23.00
			75	22.50
		16QAM	1	22.50
			38	23.00
			75	21.50
	20	QPSK	1	24.00
			50	22.50
			100	22.50
		16QAM	1	23.00
			50	22.00
			100	21.50

LTE				
Fequency Band	Band-width(MHz)	Modulation	RB allocation	Maximum Tune-up (dBm)
FDD Band 12	1.4	QPSK	1	22.50
			3	22.00
			6	21.00
		16QAM	1	21.50
			3	21.00
			6	21.00
	3	QPSK	1	22.50
			8	21.50
			15	21.50
		16QAM	1	21.50
			8	21.00
			15	21.00
	5	QPSK	1	22.50
			12	21.50
			25	21.50
		16QAM	1	21.50
			12	21.00
			25	21.00
	10	QPSK	1	22.50
			25	21.50
			50	21.50
		16QAM	1	21.50
			25	21.00
			50	21.00

LTE				
Fequency Band	Band-width(MHz)	Modulation	RB allocation	Maximum Tune-up (dBm)
FDD Band 17	5	QPSK	1	23.50
			12	22.50
			25	22.50
		16QAM	1	22.50
			12	21.50
			25	21.50
	10	QPSK	1	23.50
			25	22.50
			50	21.00
		16QAM	1	23.00
			25	21.50
			50	21.50

LTE				
Fequency Band	Band-width(MHz)	Modulation	RB allocation	Maximum Tune-up (dBm)
FDD Band 25	1.4	QPSK	1	24.00
			3	24.00
			6	23.50
		16QAM	1	24.00
			3	23.50
			6	23.00
	3	QPSK	1	24.00
			8	24.00
			15	21.00
		16QAM	1	23.00
			8	23.00
			15	23.00
	5	QPSK	1	25.00
			12	24.00
			25	23.50
		16QAM	1	24.00
			12	23.00
			25	23.50
	10	QPSK	1	24.00
			25	24.00
			50	21.00
		16QAM	1	23.00
			25	23.00
			50	22.50
	15	QPSK	1	24.00
			38	24.00
			75	24.00
		16QAM	1	24.00
			38	24.00
			75	23.00
	20	QPSK	1	23.00
			50	23.00
			100	21.00
		16QAM	1	23.00
			50	23.00
			100	23.50

LTE				
Frequency Band	Band-width(MHz)	Modulation	RB allocation	Maximum Tune-up (dBm)
FDD Band 26	1.4	QPSK	1	22.50
			3	22.50
			6	22.00
		16QAM	1	22.00
			3	22.00
			6	22.00
	3	QPSK	1	23.00
			8	22.00
			15	21.00
		16QAM	1	22.50
			8	21.50
			15	22.00
	5	QPSK	1	22.00
			12	22.00
			25	22.00
		16QAM	1	22.00
			12	22.00
			25	22.00
	10	QPSK	1	22.00
			25	22.00
			50	21.00
		16QAM	1	22.00
			25	21.50
			50	21.00
	15	QPSK	1	22.00
			38	22.00
			75	21.50
		16QAM	1	22.00
			38	22.00
			75	22.00

The allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2-1 due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3

Modulation	Channel bandwidth / Transmission bandwidth (N_{RB})						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3
256 QAM	≥ 1						≤ 5

WiFi 2.4G		
Mode	Channel	Maximum Tune-up (dBm) Conducted Average Power
802.11b	1	12.00
	6	12.00
	11	13.50
802.11g	1	13.00
	6	13.00
	11	11.50
802.11n(HT20)	1	13.00
	6	13.00
	11	12.00

WiFi 5G U-NII-1		
Mode	Channel	Maximum Tune-up (dBm) Conducted Average Power
802.11n (HT20)	36	11.50
	40	10.00
	48	10.00
802.11a	36	11.50
	40	10.00
	48	10.00
802.11n (HT40)	38	11.50
	46	10.50

WiFi 5G U-NII-2A		
Mode	Channel	Maximum Tune-up (dBm) Conducted Average Power
802.11n (HT20)	52	10.00
	56	9.50
	64	7.50
802.11a	52	10.00
	56	9.00
	64	7.00
802.11n (HT40)	54	10.00
	62	8.50

WiFi 5G U-NII-2C		
Mode	Channel	Maximum Tune-up (dBm) Conducted Average Power
802.11n (HT20)	100	5.50
	120	6.00
	140	8.00
802.11a	100	5.50
	120	6.00
	140	8.00
802.11n (HT40)	102	6.00
	118	6.50
	134	8.00

Bluetooth		
Mode	Channel	Maximum Tune-up (dBm) Conducted Average Power
GFSK	0	8.00
	39	9.00
	78	5.50
π/4QPSK	0	8.50
	39	9.00
	78	5.50
8DPSK	0	8.50
	39	9.50
	78	5.50
GFSK(BLE)	0	-0.50
	19	0.00
	39	-3.00

Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances $\leq 50\text{mm}$ are determined by:

$$[(\text{max. Power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR}$$

Band/Mode	F(GHz)	Position	Separation Distance (mm)	Exclusion Thresholds	SAR test exclusion
Bluetooth	2.45	Head	25	0.6	Yes
		Body	10	1.4	Yes

Per KDB 447498 D01, when the minimum test separation distance is $< 5\text{mm}$, a distance of 5mm is applied to determine SAR test exclusion.

The test exclusion threshold is ≤ 3 , SAR testing is not required.

13. Measured and Reported SAR Results

SAR Test Reduction criteria are as follows:

- Reported SAR(W/kg) for WWAN = Measured SAR *Tune-up Scaling Factor
- Reported SAR(W/kg) for Wi-Fi and Bluetooth = Measured SAR * Tune-up scaling factor * Duty Cycle scaling factor
- Duty Cycle scaling factor = 1 / Duty cycle (%)

KDB 447498 D01 General RF Exposure Guidance:

Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

- ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

KDB 941225 D01 SAR test for 3G SAR Test Reduction Procedure:

When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

GSM Guidance

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Please refer to section 9. for GSM power verification.

SAR is not required for EDGE (8PSK) mode because the maximum output power and tune-up limit is $\leq \frac{1}{4}$ dB higher than GPRS/EDGE (GMSK) or the adjusted SAR of the highest reported SAR of GPRS/EDGE (GMSK) is ≤ 1.2 W/kg.

W-CDMA Guidance

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC (Head) and other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC (Body-Worn Accessory) as the primary mode.

SAR measurement is not required for the HSDPA, HSUPA, DC-HSDPA and HSPA+. When primary mode and the adjusted SAR is ≤ 1.2 W/kg and secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode

KDB 941225 D05 SAR for LTE Devices:

SAR test reduction is applied using the following criteria:

- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB, and 50% RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel.
- When the reported SAR is > 0.8 W/kg, testing for other Channels is performed at the highest output power level for 1RB, and 50% RB configuration for that channel.
- Testing for 100% RB configuration is performed at the highest output power level for 100% RB configuration across the Low, Mid and High Channel when the highest reported SAR for 1 RB and 50% RB are > 0.8 W/kg. Testing for the remaining required channels is not needed because the reported SAR for 100% RB Allocation < 1.45 W/kg.
- Testing for 16-QAM and 64-QAM modulation is not required because the reported SAR for QPSK is < 1.45 W/Kg and its output power is not more than 0.5 dB higher than that of QPSK.

- Testing for the other channel bandwidths is not required because the reported SAR for the highest channel bandwidth is < 1.45 W/Kg and its output power is not more than 0.5 dB higher than that of the highest channel bandwidth.

KDB 248227 D01 SAR meas for 802.11:

When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

SAR test reduction for 802.11 Wi-Fi transmission mode configurations are considered separately for DSSS and OFDM. An initial test position is determined to reduce the number of tests required for certain exposure configurations with multiple test positions. An initial test configuration is determined for each frequency band and aggregated band according to maximum output power, channel bandwidth, wireless mode configurations and other operating parameters to streamline the measurement requirements. For 2.4 GHz DSSS, either the initial test position or DSSS procedure is applied to reduce the number of SAR tests; these are mutually exclusive. For OFDM, an initial test position is only applicable to next to the ear, UMPC mini-tablet and hotspot mode configurations, which is tested using the initial test configuration to facilitate test reduction. For other exposure conditions with a fixed test position, SAR test reduction is determined using only the initial test configuration.

The multiple test positions require SAR measurements in head, hotspot mode or UMPC mini-tablet configurations may be reduced according to the highest reported SAR determined using the initial test position(s) by applying the DSSS or OFDM SAR measurement procedures in the required wireless mode test configuration(s). The initial test position(s) is measured using the highest measured maximum output power channel in the required wireless mode test configuration(s). When the reported SAR for the initial test position is:

- ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and wireless mode combination within the frequency band or aggregated band. DSSS and OFDM configurations are considered separately according to the required SAR procedures.
- > 0.4 W/kg, SAR is repeated using the same wireless mode test configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions are tested.
 - For subsequent test positions with equivalent test separation distance or when exposure is dominated by coupling conditions, the position for maximum coupling condition should be tested.
 - When it is unclear, all equivalent conditions must be tested.
- For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, measure the SAR for these positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required test channels are considered.
 - The additional power measurements required for this step should be limited to those necessary for identifying subsequent highest output power channels to apply the test reduction.
- When the specified maximum output power is the same for both UNII 1 and UNII 2A, begin SAR measurements in UNII 2A with the channel with the highest measured output power. If the reported SAR for UNII 2A is ≤ 1.2 W/kg, SAR is not required for UNII 1; otherwise treat the remaining bands separately and test them independently for SAR.
- When the specified maximum output power is different between UNII 1 and UNII 2A, begin SAR with the band that has the higher specified maximum output. If the highest reported SAR for the band with the highest specified power is ≤ 1.2 W/kg, testing for the band with the lower specified output power is not required; otherwise test the remaining bands independently for SAR.

To determine the initial test position, Area Scans were performed to determine the position with the Maximum Value of SAR (measured). The position that produced the highest Maximum Value of SAR is considered the worst case position; thus used as the initial test position.

13.1. Head SAR

GSM850										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
GPRS (4Tx slots)	Front	128	824.2	29.53	30.00	1.114	-	-	-	-
		190	836.6	29.71	30.00	1.069	-0.12	0.366	0.391	1
		251	848.8	29.56	30.00	1.107	-	-	-	-

PCS1900										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
GPRS (4Tx slots)	Front	512	1850.2	29.65	30.00	1.084	0.00	0.238	0.258	2
		661	1880	29.29	30.00	1.178	-	-	-	-
		810	1909.8	28.84	30.00	1.306	-	-	-	-

WCDMA Band II										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2K	Front	9262	1852.4	23.88	24.00	1.028	-	-	-	-
		9400	1880	23.89	24.00	1.026	0.00	0.175	0.179	3
		9538	1907.6	23.70	24.00	1.072	-	-	-	-

WCDMA Band IV										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2K	Front	1312	1712.4	24.78	25.00	1.052	-	-	-	-
		1413	1732.6	24.86	25.00	1.033	-	-	-	-
		1513	1752.6	24.93	25.00	1.016	-0.12	0.200	0.203	4

WCDMA Band V										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2K	Front	4132	826.4	23.34	24.00	1.164	-	-	-	-
		4183	836.6	23.33	24.00	1.167	-	-	-	-
		4233	846.6	23.54	24.00	1.112	-0.01	0.334	0.371	5

LTE Band 2										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
20M QPSK 1RB	Front	18700	1860	24.15	24.50	1.084	-0.13	0.024	0.026	6
		18900	1880	23.89	24.50	1.151	-	-	-	-
		19100	1900	23.47	24.50	1.268	-	-	-	-
20M QPSK 50RB	Front	18700	1860	22.70	23.00	1.072	0.07	0.021	0.023	-
		18900	1880	22.46	23.00	1.132	-	-	-	-
		19100	1900	22.41	23.00	1.146	-	-	-	-

LTE Band 4										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
20M QPSK 1RB	Front	20050	1720	23.90	25.00	1.288	-	-	-	-
		20175	1732.5	23.71	25.00	1.346	-	-	-	-
		20300	1745	24.51	25.00	1.119	0.02	0.131	0.147	7
20M QPSK 50RB	Front	20050	1720	22.82	23.50	1.169	-	-	-	-
		20175	1732.5	22.80	23.50	1.175	-	-	-	-
		20300	1745	23.10	23.50	1.096	0.18	0.105	0.115	-

LTE Band 5										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
10M QPSK 1RB	Front	20450	829	22.67	23.00	1.079	-	-	-	-
		20525	836.5	22.43	23.00	1.140	-	-	-	-
		20600	844	22.92	23.00	1.019	-0.14	0.012	0.012	8
10M QPSK 25RB	Front	20450	829	21.59	22.00	1.099	-	-	-	-
		20525	836.5	21.74	22.00	1.062	0.04	0.010	0.011	-
		20600	844	21.59	22.00	1.099	-	-	-	-

LTE Band 7										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
20M QPSK 1RB	Front	20850	2510	23.31	24.00	1.172	-	-	-	-
		21100	2535	23.19	24.00	1.205	-	-	-	-
		21350	2560	23.79	24.00	1.050	0.15	0.013	0.014	9
20M QPSK 50RB	Front	20850	2510	22.48	22.50	1.005	0.11	0.010	0.010	-
		21100	2535	22.21	22.50	1.069	-	-	-	-
		21350	2560	22.14	22.50	1.086	-	-	-	-

LTE Band 12										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
10M QPSK 1RB	Front	23060	704	22.10	22.50	1.096	-	-	-	-
		23095	707.5	22.32	22.50	1.042	0.01	0.016	0.017	10
		23130	711	22.07	22.50	1.104	-	-	-	-
10M QPSK 25RB	Front	23060	704	20.94	21.50	1.138	-	-	-	-
		23095	707.5	21.04	21.50	1.112	-	-	-	-
		23130	711	21.13	21.50	1.089	0.05	0.012	0.013	-

LTE Band 17										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
10M QPSK 1RB	Front	23780	709	23.03	23.50	1.114	-	-	-	-
		23790	710	23.40	23.50	1.023	0.01	0.017	0.017	11
		23800	711	23.16	23.50	1.081	-	-	-	-
10M QPSK 25RB	Front	23780	709	22.27	22.50	1.054	-	-	-	-
		23790	710	22.22	22.50	1.067	-	-	-	-
		23800	711	22.29	22.50	1.050	0.12	0.012	0.013	-

LTE Band 25										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
20M QPSK 1RB	Front	26140	1860	22.45	23.00	1.135	-	-	-	-
		26365	1882.5	22.56	23.00	1.107	-	-	-	-
		26590	1905	22.87	23.00	1.030	-0.13	0.027	0.028	12
20M QPSK 50RB	Front	26140	1860	22.52	23.00	1.117	-	-	-	-
		26365	1882.5	22.86	23.00	1.033	0.08	0.022	0.023	-
		26590	1905	22.31	23.00	1.172	-	-	-	-

LTE Band 26										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
15M QPSK 1RB	Front	26775	822.5	21.41	22.00	1.146	-	-	-	-
		26865	831.5	21.99	22.00	1.002	-0.06	0.013	0.013	13
		26965	841.5	21.52	22.00	1.117	-	-	-	-
15M QPSK 38RB	Front	26775	822.5	21.36	22.00	1.159	-	-	-	-
		26865	831.5	21.87	22.00	1.030	-	-	-	-
		26965	841.5	21.96	22.00	1.009	0.13	0.009	0.009	-

WiFi 2.4G												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz									
802.11b	Front	1	2412	11.56	12.00	1.107	100%	1.00	-	-	-	-
		6	2437	11.67	12.00	1.079	100%	1.00	-	-	-	-
		11	2462	13.41	13.50	1.021	100%	1.00	0.13	0.015	0.015	14

WiFi 5G U-NII-1												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz									
802.11n (HT40)	Front	38	5190	11.40	11.50	1.023	100%	1.00	-0.01	0.011	0.011	15
		46	5230	10.21	10.50	1.069	100%	1.00	-	-	-	-

WiFi 5G U-NII-2A												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz									
802.11n (HT40)	Front	54	5270	9.81	10.00	1.045	100%	1.00	-0.18	0.007	0.007	16
		62	5310	8.15	8.50	1.084	100%	1.00	-	-	-	-

WiFi 5G U-NII-2C												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz									
802.11n (HT40)	Front	100	5500	5.26	5.50	1.057	100%	1.00	-	-	-	-
		120	5600	5.67	6.00	1.079	100%	1.00	-	-	-	-
		140	5700	7.99	8.00	1.002	100%	1.00	-0.19	0.009	0.009	17

13.2. Body SAR

GSM850										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
GPRS (4Tx slots)	Front	128	824.2	29.53	30.00	1.114	-	-	-	-
		190	836.6	29.71	30.00	1.069	-0.18	0.729	0.779	18
		251	848.8	29.56	30.00	1.107	-	-	-	-
	Rear	128	824.2	29.53	30.00	1.114	-	-	-	-
		190	836.6	29.71	30.00	1.069	0.01	0.526	0.563	-
		251	848.8	29.56	30.00	1.107	-	-	-	-
	Rear (Belt Clip)	128	824.2	29.53	30.00	1.114	-	-	-	-
		190	836.6	29.71	30.00	1.069	-0.02	0.539	0.577	-
		251	848.8	29.56	30.00	1.107	-	-	-	-

PCS1900										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
GPRS (4Tx slots)	Front	512	1850.2	29.65	30.00	1.084	-0.12	0.631	0.684	19
		661	1880	29.29	30.00	1.178	-	-	-	-
		810	1909.8	28.84	30.00	1.306	-	-	-	-
	Rear	512	1850.2	29.65	30.00	1.084	0.06	0.456	0.494	-
		661	1880	29.29	30.00	1.178	-	-	-	-
		810	1909.8	28.84	30.00	1.306	-	-	-	-
	Rear (Belt Clip)	512	1850.2	29.65	30.00	1.084	-0.01	0.467	0.506	-
		661	1880	29.29	30.00	1.178	-	-	-	-
		810	1909.8	28.84	30.00	1.306	-	-	-	-

WCDMA Band II										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2Kbps	Front	9262	1852.4	23.88	24.00	1.028	-	-	-	-
		9400	1880	23.89	24.00	1.026	-0.06	0.554	0.568	20
		9538	1907.6	23.70	24.00	1.072	-	-	-	-
	Rear	9262	1852.4	23.88	24.00	1.028	-	-	-	-
		9400	1880	23.89	24.00	1.026	0.07	0.400	0.410	-
		9538	1907.6	23.70	24.00	1.072	-	-	-	-
	Rear (Belt Clip)	9262	1852.4	23.88	24.00	1.028	-	-	-	-
		9400	1880	23.89	24.00	1.026	0.11	0.410	0.421	-
		9538	1907.6	23.70	24.00	1.072	-	-	-	-

WCDMA Band IV										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2Kbps	Front	1312	1712.4	24.78	25.00	1.052	0.08	0.765	0.805	-
		1413	1732.6	24.86	25.00	1.033	0.10	0.776	0.801	-
		1513	1752.6	24.93	25.00	1.016	0.04	0.811	0.824	21
	Rear	1312	1712.4	24.78	25.00	1.052	-	-	-	-
		1413	1732.6	24.86	25.00	1.033	-	-	-	-
		1513	1752.6	24.93	25.00	1.016	-0.12	0.422	0.429	-
	Rear (Belt Clip)	1312	1712.4	24.78	25.00	1.052	-	-	-	-
		1413	1732.6	24.86	25.00	1.033	-	-	-	-
		1513	1752.6	24.93	25.00	1.016	-0.14	0.478	0.486	-

WCDMA Band V										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2Kbps	Front	4132	826.4	23.34	24.00	1.164	-	-	-	-
		4183	836.6	23.33	24.00	1.167	-	-	-	-
		4233	846.6	23.54	24.00	1.112	-0.03	0.714	0.794	22
	Rear	4132	826.4	23.34	24.00	1.164	-	-	-	-
		4183	836.6	23.33	24.00	1.167	-	-	-	-
		4233	846.6	23.54	24.00	1.112	-0.01	0.394	0.438	-
	Rear (Belt Clip)	4132	826.4	23.34	24.00	1.164	-	-	-	-
		4183	836.6	23.33	24.00	1.167	-	-	-	-
		4233	846.6	23.54	24.00	1.112	0.05	0.499	0.555	-

LTE Band 2										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
20M QPSK 1RB	Front	18700	1860	24.15	24.50	1.084	-0.08	0.516	0.559	23
		18900	1880	23.89	24.50	1.151	-	-	-	-
		19100	1900	23.47	24.50	1.268	-	-	-	-
	Rear	18700	1860	24.15	24.50	1.084	0.01	0.373	0.404	-
		18900	1880	23.89	24.50	1.151	-	-	-	-
		19100	1900	23.47	24.50	1.268	-	-	-	-
	Rear (Belt Clip)	18700	1860	24.15	24.50	1.084	-0.17	0.382	0.414	-
		18900	1880	23.89	24.50	1.151	-	-	-	-
		19100	1900	23.47	24.50	1.268	-	-	-	-
20M QPSK 50RB	Front	18700	1860	22.70	23.00	1.072	0.06	0.502	0.538	-
		18900	1880	22.46	23.00	1.132	-	-	-	-
		19100	1900	22.41	23.00	1.146	-	-	-	-
	Rear	18700	1860	22.70	23.00	1.072	-0.11	0.362	0.388	-
		18900	1880	22.46	23.00	1.132	-	-	-	-
		19100	1900	22.41	23.00	1.146	-	-	-	-
	Rear (Belt Clip)	18700	1860	22.70	23.00	1.072	0.15	0.371	0.398	-
		18900	1880	22.46	23.00	1.132	-	-	-	-
		19100	1900	22.41	23.00	1.146	-	-	-	-

LTE Band 4										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
20M QPSK 1RB	Front	20050	1720	23.90	25.00	1.288	-	-	-	-
		20175	1732.5	23.71	25.00	1.346	-	-	-	-
		20300	1745	24.51	25.00	1.119	0.10	0.694	0.777	24
	Rear	20050	1720	23.90	25.00	1.288	-	-	-	-
		20175	1732.5	23.71	25.00	1.346	-	-	-	-
		20300	1745	24.51	25.00	1.119	0.03	0.501	0.561	-
	Rear (Belt Clip)	20050	1720	23.90	25.00	1.288	-	-	-	-
		20175	1732.5	23.71	25.00	1.346	-	-	-	-
		20300	1745	24.51	25.00	1.119	0.06	0.514	0.575	-
20M QPSK 50RB	Front	20050	1720	22.82	23.50	1.169	-	-	-	-
		20175	1732.5	22.80	23.50	1.175	-	-	-	-
		20300	1745	23.10	23.50	1.096	-0.13	0.647	0.709	-
	Rear	20050	1720	22.82	23.50	1.169	-	-	-	-
		20175	1732.5	22.80	23.50	1.175	-	-	-	-
		20300	1745	23.10	23.50	1.096	-0.07	0.467	0.512	-
	Rear (Belt Clip)	20050	1720	22.82	23.50	1.169	-	-	-	-
		20175	1732.5	22.80	23.50	1.175	-	-	-	-
		20300	1745	23.10	23.50	1.096	0.14	0.479	0.525	-

LTE Band 5										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
10M QPSK 1RB	Front	20450	829	22.67	23.00	1.079	-	-	-	-
		20525	836.5	22.43	23.00	1.140	-	-	-	-
		20600	844	22.92	23.00	1.019	-0.10	0.217	0.221	25
	Rear	20450	829	22.67	23.00	1.079	-	-	-	-
		20525	836.5	22.43	23.00	1.140	-	-	-	-
		20600	844	22.92	23.00	1.019	0.02	0.157	0.160	-
	Rear (Belt Clip)	20450	829	22.67	23.00	1.079	-	-	-	-
		20525	836.5	22.43	23.00	1.140	-	-	-	-
		20600	844	22.92	23.00	1.019	-0.15	0.161	0.164	-
10M QPSK 25RB	Front	20450	829	21.59	22.00	1.099	-	-	-	-
		20525	836.5	21.74	22.00	1.062	0.08	0.018	0.019	-
		20600	844	21.59	22.00	1.099	-	-	-	-
	Rear	20450	829	21.59	22.00	1.099	-	-	-	-
		20525	836.5	21.74	22.00	1.062	0.14	0.013	0.013	-
		20600	844	21.59	22.00	1.099	-	-	-	-
	Rear (Belt Clip)	20450	829	21.59	22.00	1.099	-	-	-	-
		20525	836.5	21.74	22.00	1.062	0.19	0.013	0.014	-
		20600	844	21.59	22.00	1.099	-	-	-	-

LTE Band 7										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
20M QPSK 1RB	Front	20850	2510	23.31	24.00	1.172	-	-	-	-
		21100	2535	23.19	24.00	1.205	-	-	-	-
		21350	2560	23.79	24.00	1.050	-0.09	0.029	0.030	-
	Rear	20850	2510	23.31	24.00	1.172	-	-	-	-
		21100	2535	23.19	24.00	1.205	-	-	-	-
		21350	2560	23.79	24.00	1.050	-0.10	0.100	0.105	26
	Rear (Belt Clip)	20850	2510	23.31	24.00	1.172	-	-	-	-
		21100	2535	23.19	24.00	1.205	-	-	-	-
		21350	2560	23.79	24.00	1.050	0.12	0.047	0.049	-
20M QPSK 50RB	Front	20850	2510	22.48	22.50	1.005	-0.05	0.024	0.024	-
		21100	2535	22.21	22.50	1.069	-	-	-	-
		21350	2560	22.14	22.50	1.086	-	-	-	-
	Rear	20850	2510	22.48	22.50	1.005	0.16	0.084	0.084	-
		21100	2535	22.21	22.50	1.069	-	-	-	-
		21350	2560	22.14	22.50	1.086	-	-	-	-
	Rear (Belt Clip)	20850	2510	22.48	22.50	1.005	0.07	0.040	0.040	-
		21100	2535	22.21	22.50	1.069	-	-	-	-
		21350	2560	22.14	22.50	1.086	-	-	-	-

LTE Band 12										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
10M QPSK 1RB	Front	23060	704	22.10	22.50	1.096	-	-	-	-
		23095	707.5	22.32	22.50	1.042	-0.09	0.061	0.064	27
		23130	711	22.07	22.50	1.104	-	-	-	-
	Rear	23060	704	22.10	22.50	1.096	-	-	-	-
		23095	707.5	22.32	22.50	1.042	0.18	0.044	0.046	-
		23130	711	22.07	22.50	1.104	-	-	-	-
	Rear (Belt Clip)	23060	704	22.10	22.50	1.096	-	-	-	-
		23095	707.5	22.32	22.50	1.042	0.03	0.045	0.047	-
		23130	711	22.07	22.50	1.104	-	-	-	-
10M QPSK 25RB	Front	23060	704	20.94	21.50	1.138	-	-	-	-
		23095	707.5	21.04	21.50	1.112	-	-	-	-
		23130	711	21.13	21.50	1.089	-0.16	0.049	0.053	-
	Rear	23060	704	20.94	21.50	1.138	-	-	-	-
		23095	707.5	21.04	21.50	1.112	-	-	-	-
		23130	711	21.13	21.50	1.089	0.12	0.035	0.039	-
	Rear (Belt Clip)	23060	704	20.94	21.50	1.138	-	-	-	-
		23095	707.5	21.04	21.50	1.112	-	-	-	-
		23130	711	21.13	21.50	1.089	0.04	0.036	0.039	-

LTE Band 17										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
10M QPSK 1RB	Front	23780	709	23.03	23.50	1.114	-	-	-	-
		23790	710	23.40	23.50	1.023	0.00	0.065	0.066	28
		23800	711	23.16	23.50	1.081	-	-	-	-
	Rear	23780	709	23.03	23.50	1.114	-	-	-	-
		23790	710	23.40	23.50	1.023	0.13	0.047	0.048	-
		23800	711	23.16	23.50	1.081	-	-	-	-
	Rear (Belt Clip)	23780	709	23.03	23.50	1.114	-	-	-	-
		23790	710	23.40	23.50	1.023	-0.17	0.048	0.049	-
		23800	711	23.16	23.50	1.081	-	-	-	-
10M QPSK 25RB	Front	23780	709	22.27	22.50	1.054	-	-	-	-
		23790	710	22.22	22.50	1.067	-	-	-	-
		23800	711	22.29	22.50	1.050	0.06	0.052	0.055	-
	Rear	23780	709	22.27	22.50	1.054	-	-	-	-
		23790	710	22.22	22.50	1.067	-	-	-	-
		23800	711	22.29	22.50	1.050	0.18	0.038	0.039	-
	Rear (Belt Clip)	23780	709	22.27	22.50	1.054	-	-	-	-
		23790	710	22.22	22.50	1.067	-	-	-	-
		23800	711	22.29	22.50	1.050	-0.01	0.038	0.040	-

LTE Band 25										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
20M QPSK 1RB	Front	26140	1860	22.45	23.00	1.135	-	-	-	-
		26365	1882.5	22.56	23.00	1.107	-	-	-	-
		26590	1905	22.87	23.00	1.030	-0.18	0.550	0.567	-
	Rear	26140	1860	22.45	23.00	1.135	-	-	-	-
		26365	1882.5	22.56	23.00	1.107	-	-	-	-
		26590	1905	22.87	23.00	1.030	-0.11	0.397	0.409	29
	Rear (Belt Clip)	26140	1860	22.45	23.00	1.135	-	-	-	-
		26365	1882.5	22.56	23.00	1.107	-	-	-	-
		26590	1905	22.87	23.00	1.030	0.05	0.407	0.419	-
20M QPSK 50RB	Front	26140	1860	22.52	23.00	1.117	-	-	-	-
		26365	1882.5	22.86	23.00	1.033	0.02	0.498	0.514	-
		26590	1905	22.31	23.00	1.172	-	-	-	-
	Rear	26140	1860	22.52	23.00	1.117	-	-	-	-
		26365	1882.5	22.86	23.00	1.033	0.17	0.360	0.371	-
		26590	1905	22.31	23.00	1.172	-	-	-	-
	Rear (Belt Clip)	26140	1860	22.52	23.00	1.117	-	-	-	-
		26365	1882.5	22.86	23.00	1.033	0.06	0.369	0.381	-
		26590	1905	22.31	23.00	1.172	-	-	-	-

LTE Band 26										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
15M QPSK 1RB	Front	26775	822.5	21.41	22.00	1.15	-	-	-	-
		26865	831.5	21.99	22.00	1.00	-0.06	0.076	0.076	30
		26965	841.5	21.52	22.00	1.12	-	-	-	-
	Rear	26775	822.5	21.41	22.00	1.15	-	-	-	-
		26865	831.5	21.99	22.00	1.00	0.15	0.055	0.055	-
		26965	841.5	21.52	22.00	1.12	-	-	-	-
	Rear (Belt Clip)	26775	822.5	21.41	22.00	1.146	-	-	-	-
		26865	831.5	21.99	22.00	1.002	-0.02	0.056	0.056	-
		26965	841.5	21.52	22.00	1.117	-	-	-	-
15M QPSK 38RB	Front	26775	822.5	21.36	22.00	1.16	-	-	-	-
		26865	831.5	21.87	22.00	1.03	-	-	-	-
		26965	841.5	21.96	22.00	1.01	-0.08	0.063	0.064	-
	Rear	26775	822.5	21.36	22.00	1.16	-	-	-	-
		26865	831.5	21.87	22.00	1.03	-	-	-	-
		26965	841.5	21.96	22.00	1.01	0.16	0.045	0.046	-
	Rear (Belt Clip)	26775	822.5	21.36	22.00	1.159	-	-	-	-
		26865	831.5	21.87	22.00	1.030	-	-	-	-
		26965	841.5	21.96	22.00	1.009	0.11	0.047	0.047	-

WiFi 2.4G												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz									
802.11b	Front	1	2412	11.56	12.00	1.107	100%	1.00	-	-	-	-
		6	2437	11.67	12.00	1.079	100%	1.00	-	-	-	-
		11	2462	13.41	13.50	1.021	100%	1.00	0.08	0.023	0.023	-
	Rear	1	2412	11.56	12.00	1.107	100%	1.00	-	-	-	-
		6	2437	11.67	12.00	1.079	100%	1.00	-	-	-	-
		11	2462	13.41	13.50	1.021	100%	1.00	-0.10	0.051	0.052	31
	Rear Belt clip	1	2412	11.56	12.00	1.107	100%	1.00	-	-	-	-
		6	2437	11.67	12.00	1.079	100%	1.00	-	-	-	-
		11	2462	13.41	13.50	1.021	100%	1.00	-0.02	0.036	0.037	-

WiFi 5G U-NII-1												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz									
802.11n (HT40)	Front	38	5190	11.40	11.50	1.023	100%	1.00	-0.18	0.017	0.018	-
		46	5230	10.21	10.50	1.069	100%	1.00	-	-	-	-
	Rear	38	5190	11.40	11.50	1.023	100%	1.00	-0.12	0.041	0.042	32
		46	5230	10.21	10.50	1.069	100%	1.00	-	-	-	-
	Rear (Belt Clip)	38	5190	11.40	11.50	1.023	100%	1.00	-0.17	0.028	0.029	-
		46	5230	10.21	10.50	1.069	100%	1.00	-	-	-	-

WiFi 5G U-NII-2A												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz									
802.11n (HT40)	Front	54	5270	9.81	10.00	1.045	100%	1.00	0.06	0.010	0.010	-
		62	5310	8.15	8.50	1.084	100%	1.00	-	-	-	-
	Rear	54	5270	9.81	10.00	1.045	100%	1.00	-0.18	0.012	0.013	33
		62	5310	8.15	8.50	1.084	100%	1.00	-	-	-	-
	Rear (Belt Clip)	54	5270	9.81	10.00	1.045	100%	1.00	0.11	0.010	0.010	-
		62	5310	8.15	8.50	1.084	100%	1.00	-	-	-	-

WiFi 5G U-NII-2C												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz									
802.11n (HT40)	Front	100	5500	5.26	5.50	1.057	100%	1.00	-	-	-	-
		120	5600	5.67	6.00	1.079	100%	1.00	-	-	-	-
		140	5700	7.99	8.00	1.002	100%	1.00	-0.11	0.012	0.012	-
	Rear	100	5500	5.26	5.50	1.057	100%	1.00	-	-	-	-
		120	5600	5.67	6.00	1.079	100%	1.00	-	-	-	-
		140	5700	7.99	8.00	1.002	100%	1.00	-0.10	0.013	0.013	34
	Rear (Belt Clip)	100	5500	5.26	5.50	1.057	100%	1.00	-	-	-	-
		120	5600	5.67	6.00	1.079	100%	1.00	-	-	-	-
		140	5700	7.99	8.00	1.002	100%	1.00	0.08	0.012	0.012	-

SAR Test Data Plots to the Appendix A.

14. Simultaneous Transmission analysis

No.	Simultaneous Transmission Configurations	Head	Body-worn	Note
1	GPRS (data) + Bluetooth (data)	Yes	Yes	
2	GPRS (data) + WIFI (data)	Yes	Yes	
3	WCDMA (data) + Bluetooth (data)	Yes	Yes	
4	WCDMA (data) + WIFI (data)	Yes	Yes	
5	LTE + Bluetooth (data)	Yes	Yes	
6	LTE + WIFI (data)	Yes	Yes	

General note:

1. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
2. EUT will choose either GSM or WCDMA LTE according to the network signal condition; therefore, they will not operate simultaneously at any moment.
3. The reported SAR summation is calculated based on the same configuration and test position
4. For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01 based on the formula below
 - a) $[(\text{max. Power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})/x}] \text{W/kg}$ for test separation distances $\leq 50\text{mm}$; when $x=7.5$ for 1-g SAR, and $x=18.75$ for 10-g SAR.
 - b) When the minimum separation distance is $<5\text{mm}$, the distance is used 5mm to determine SAR test exclusion
 - c) 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is $>50\text{mm}$.

Bluetooth Max power	Exposure position	Front-of-face	Body-worn
	Test separation	25mm	10mm
9.50 dBm	Estimated SAR (W/kg)	0.075	0.186

14.1. Front-of-face

PCF+ WLAN DTS					
WWAN Band		Exposure Position	Max SAR (W/kg)		Summed SAR
			PCF	WLAN DTS	(W/kg)
GSM	GSM850	Front	0.391	0.015	0.406
	PCS1900	Front	0.258	0.015	0.273
WCDMA	Band II	Front	0.179	0.015	0.194
	Band IV	Front	0.203	0.015	0.218
	Band V	Front	0.371	0.015	0.386
LTE	B2 1RB	Front	0.026	0.015	0.041
	B2 50RB	Front	0.023	0.015	0.038
	B4 1RB	Front	0.147	0.015	0.162
	B4 50RB	Front	0.115	0.015	0.130
	B5 1RB	Front	0.012	0.015	0.027
	B5 25RB	Front	0.011	0.015	0.026
	B7 1RB	Front	0.014	0.015	0.029
	B7 50RB	Front	0.010	0.015	0.025
	B12 1RB	Front	0.017	0.015	0.032
	B12 25RB	Front	0.013	0.015	0.028
	B17 1RB	Front	0.017	0.015	0.032
	B17 25RB	Front	0.013	0.015	0.028
	B25 1RB	Front	0.028	0.015	0.043
	B25 50RB	Front	0.023	0.015	0.038
	B26 1RB	Front	0.013	0.015	0.028
	B26 38RB	Front	0.009	0.015	0.024

PCF+ WLAN U-NII					
WWAN Band		Exposure Position	Max SAR (W/kg)		Summed SAR (W/kg)
			PCF	WLAN U-NII	
GSM	GSM850	Front	0.391	0.011	0.402
	PCS1900	Front	0.258	0.011	0.269
WCDMA	Band II	Front	0.179	0.011	0.190
	Band IV	Front	0.203	0.011	0.214
	Band V	Front	0.371	0.011	0.382
LTE	B2 1RB	Front	0.026	0.011	0.037
	B2 50RB	Front	0.023	0.011	0.034
	B4 1RB	Front	0.147	0.011	0.158
	B4 50RB	Front	0.115	0.011	0.126
	B5 1RB	Front	0.012	0.011	0.023
	B5 25RB	Front	0.011	0.011	0.022
	B7 1RB	Front	0.014	0.011	0.025
	B7 50RB	Front	0.010	0.011	0.021
	B12 1RB	Front	0.017	0.011	0.028
	B12 25RB	Front	0.013	0.011	0.024
	B17 1RB	Front	0.017	0.011	0.028
	B17 25RB	Front	0.013	0.011	0.024
	B25 1RB	Front	0.028	0.011	0.039
	B25 50RB	Front	0.023	0.011	0.034
	B26 1RB	Front	0.013	0.011	0.024
	B26 38RB	Front	0.009	0.011	0.020

PCF+ Bluetooth					
WWAN Band		Exposure Position	Max SAR (W/kg)		Summed SAR (W/kg)
			PCF	Bluetooth	
GSM	GSM850	Front	0.391	0.074	0.465
	PCS1900	Front	0.258	0.074	0.332
WCDMA	Band II	Front	0.179	0.074	0.253
	Band IV	Front	0.203	0.074	0.277
	Band V	Front	0.371	0.074	0.445
LTE	B2 1RB	Front	0.026	0.074	0.100
	B2 50RB	Front	0.023	0.074	0.097
	B4 1RB	Front	0.147	0.074	0.221
	B4 50RB	Front	0.115	0.074	0.189
	B5 1RB	Front	0.012	0.074	0.086
	B5 25RB	Front	0.011	0.074	0.085
	B7 1RB	Front	0.014	0.074	0.088
	B7 50RB	Front	0.010	0.074	0.084
	B12 1RB	Front	0.017	0.074	0.091
	B12 25RB	Front	0.013	0.074	0.087
	B17 1RB	Front	0.017	0.074	0.091
	B17 25RB	Front	0.013	0.074	0.087
	B25 1RB	Front	0.028	0.074	0.102
	B25 50RB	Front	0.023	0.074	0.097
	B26 1RB	Front	0.013	0.074	0.087
	B26 38RB	Front	0.009	0.074	0.083

14.2. Body-worn

PCF+ WLAN DTS					
WWAN Band		Exposure Position	Max SAR (W/kg)		Summed SAR (W/kg)
			PCF	WLAN DTS	
GSM	GSM850	Front	0.779	0.023	0.802
		Rear	0.563	0.052	0.615
		Rear (Belt Clip)	0.577	0.037	0.614
	PCS1900	Front	0.684	0.023	0.707
		Rear	0.494	0.052	0.546
		Rear (Belt Clip)	0.506	0.037	0.543
WCDMA	Band II	Front	0.568	0.023	0.591
		Rear	0.410	0.052	0.462
		Rear (Belt Clip)	0.421	0.037	0.458
	Band IV	Front	0.824	0.023	0.847
		Rear	0.429	0.052	0.481
		Rear (Belt Clip)	0.486	0.037	0.523
	Band V	Front	0.794	0.023	0.817
		Rear	0.438	0.052	0.490
		Rear (Belt Clip)	0.555	0.037	0.592
LTE	Band 2 20M QPSK_1RB	Front	0.559	0.023	0.582
		Rear	0.404	0.052	0.456
		Rear (Belt Clip)	0.414	0.037	0.451
	Band 2 20M QPSK_50RB	Front	0.538	0.023	0.561
		Rear	0.388	0.052	0.440
		Rear (Belt Clip)	0.398	0.037	0.435
	Band 4 20M QPSK_1RB	Front	0.777	0.023	0.800
		Rear	0.561	0.052	0.613
		Rear (Belt Clip)	0.575	0.037	0.612
	Band 4 20M QPSK_50RB	Front	0.709	0.023	0.732
		Rear	0.512	0.052	0.564
		Rear (Belt Clip)	0.525	0.037	0.562

LTE	Band 5 10M QPSK_1RB	Front	0.221	0.023	0.244
		Rear	0.160	0.052	0.212
		Rear (Belt Clip)	0.164	0.037	0.201
	Band 5 10M QPSK_25RB	Front	0.019	0.023	0.042
		Rear	0.013	0.052	0.065
		Rear (Belt Clip)	0.014	0.037	0.051
	Band 2 20M QPSK_1RB	Front	0.030	0.023	0.053
		Rear	0.105	0.052	0.157
		Rear (Belt Clip)	0.049	0.037	0.086
	Band 2 20M QPSK_50RB	Front	0.024	0.023	0.047
		Rear	0.084	0.052	0.136
		Rear (Belt Clip)	0.040	0.037	0.077
	Band 12 10M QPSK_1RB	Front	0.064	0.023	0.087
		Rear	0.046	0.052	0.098
		Rear (Belt Clip)	0.047	0.037	0.084
	Band 12 10M QPSK_25RB	Front	0.053	0.023	0.076
		Rear	0.039	0.052	0.091
		Rear (Belt Clip)	0.039	0.037	0.076
	Band 17 10M QPSK_1RB	Front	0.066	0.023	0.089
		Rear	0.048	0.052	0.100
		Rear (Belt Clip)	0.049	0.037	0.086
	Band 17 10M QPSK_25RB	Front	0.055	0.023	0.078
		Rear	0.039	0.052	0.091
		Rear (Belt Clip)	0.040	0.037	0.077

LTE	Band 25 20M QPSK_1RB	Front	0.567	0.023	0.590
		Rear	0.409	0.052	0.461
		Rear (Belt Clip)	0.419	0.037	0.456
	Band 25 20M QPSK_50RB	Front	0.514	0.023	0.537
		Rear	0.371	0.052	0.423
		Rear (Belt Clip)	0.381	0.037	0.418
	Band 26 15M QPSK_1RB	Front	0.076	0.023	0.099
		Rear	0.055	0.052	0.107
		Rear (Belt Clip)	0.056	0.037	0.093
	Band 26 15M QPSK_38RB	Front	0.064	0.023	0.087
		Rear	0.046	0.052	0.098
		Rear (Belt Clip)	0.047	0.037	0.084

PCF+ WLAN U-NII					
WWAN Band		Exposure Position	Max SAR (W/kg)		Summed SAR
			PCF	WLAN U-NII	(W/kg)
GSM	GSM850	Front	0.779	0.018	0.797
		Rear	0.563	0.042	0.605
		Rear (Belt Clip)	0.577	0.029	0.606
	PCS1900	Front	0.684	0.018	0.702
		Rear	0.494	0.042	0.536
		Rear (Belt Clip)	0.506	0.029	0.535
WCDMA	Band II	Front	0.568	0.018	0.586
		Rear	0.410	0.042	0.452
		Rear (Belt Clip)	0.421	0.029	0.450
	Band IV	Front	0.824	0.018	0.842
		Rear	0.429	0.042	0.471
		Rear (Belt Clip)	0.486	0.029	0.515
	Band V	Front	0.794	0.018	0.812
		Rear	0.438	0.042	0.480
		Rear (Belt Clip)	0.555	0.029	0.584
LTE	Band 2 20M QPSK_1RB	Front	0.559	0.018	0.577
		Rear	0.404	0.042	0.446
		Rear (Belt Clip)	0.414	0.029	0.443
	Band 2 20M QPSK_50RB	Front	0.538	0.018	0.556
		Rear	0.388	0.042	0.430
		Rear (Belt Clip)	0.398	0.029	0.427
	Band 4 20M QPSK_1RB	Front	0.777	0.018	0.795
		Rear	0.561	0.042	0.603
		Rear (Belt Clip)	0.575	0.029	0.604
	Band 4 20M QPSK_50RB	Front	0.709	0.018	0.727
		Rear	0.512	0.042	0.554
		Rear (Belt Clip)	0.525	0.029	0.554

LTE	Band 5 10M QPSK_1RB	Front	0.221	0.018	0.239
		Rear	0.160	0.042	0.202
		Rear (Belt Clip)	0.164	0.029	0.193
	Band 5 10M QPSK_25RB	Front	0.019	0.018	0.037
		Rear	0.013	0.042	0.055
		Rear (Belt Clip)	0.014	0.029	0.043
	Band 2 20M QPSK_1RB	Front	0.030	0.018	0.048
		Rear	0.105	0.042	0.147
		Rear (Belt Clip)	0.049	0.029	0.078
	Band 2 20M QPSK_50RB	Front	0.024	0.018	0.042
		Rear	0.084	0.042	0.126
		Rear (Belt Clip)	0.040	0.029	0.069
	Band 12 10M QPSK_1RB	Front	0.064	0.018	0.082
		Rear	0.046	0.042	0.088
		Rear (Belt Clip)	0.047	0.029	0.076
	Band 12 10M QPSK_25RB	Front	0.053	0.018	0.071
		Rear	0.039	0.042	0.081
		Rear (Belt Clip)	0.039	0.029	0.068
	Band 17 10M QPSK_1RB	Front	0.066	0.018	0.084
		Rear	0.048	0.042	0.090
		Rear (Belt Clip)	0.049	0.029	0.078
	Band 17 10M QPSK_25RB	Front	0.055	0.018	0.073
		Rear	0.039	0.042	0.081
		Rear (Belt Clip)	0.040	0.029	0.069


LTE	Band 25 20M QPSK_1RB	Front	0.567	0.018	0.585
		Rear	0.409	0.042	0.451
		Rear (Belt Clip)	0.419	0.029	0.448
	Band 25 20M QPSK_50RB	Front	0.514	0.018	0.532
		Rear	0.371	0.042	0.413
		Rear (Belt Clip)	0.381	0.029	0.410
	Band 26 15M QPSK_1RB	Front	0.076	0.018	0.094
		Rear	0.055	0.042	0.097
		Rear (Belt Clip)	0.056	0.029	0.085
	Band 26 15M QPSK_38RB	Front	0.064	0.018	0.082
		Rear	0.046	0.042	0.088
		Rear (Belt Clip)	0.047	0.029	0.076

PCF+BT					
WWAN Band		Exposure Position	Max SAR (W/kg)		Summed SAR
			PCF	BT	(W/kg)
GSM	GSM850	Front	0.779	0.186	0.965
		Rear	0.563	0.186	0.749
		Rear (Belt Clip)	0.577	0.186	0.763
	PCS1900	Front	0.684	0.186	0.870
		Rear	0.494	0.186	0.680
		Rear (Belt Clip)	0.506	0.186	0.692
WCDMA	Band II	Front	0.568	0.186	0.754
		Rear	0.410	0.186	0.596
		Rear (Belt Clip)	0.421	0.186	0.607
	Band IV	Front	0.824	0.186	1.010
		Rear	0.429	0.186	0.615
		Rear (Belt Clip)	0.486	0.186	0.672
	Band V	Front	0.794	0.186	0.980
		Rear	0.438	0.186	0.624
		Rear (Belt Clip)	0.555	0.186	0.741
LTE	Band 2 20M QPSK_1RB	Front	0.559	0.186	0.745
		Rear	0.404	0.186	0.590
		Rear (Belt Clip)	0.414	0.186	0.600
	Band 2 20M QPSK_50RB	Front	0.538	0.186	0.724
		Rear	0.388	0.186	0.574
		Rear (Belt Clip)	0.398	0.186	0.584
	Band 4 20M QPSK_1RB	Front	0.777	0.186	0.963
		Rear	0.561	0.186	0.747
		Rear (Belt Clip)	0.575	0.186	0.761
	Band 4 20M QPSK_50RB	Front	0.709	0.186	0.895
		Rear	0.512	0.186	0.698
		Rear (Belt Clip)	0.525	0.186	0.711

LTE	Band 5 10M QPSK_1RB	Front	0.221	0.186	0.407
		Rear	0.160	0.186	0.346
		Rear (Belt Clip)	0.164	0.186	0.350
	Band 5 10M QPSK_25RB	Front	0.019	0.186	0.205
		Rear	0.013	0.186	0.199
		Rear (Belt Clip)	0.014	0.186	0.200
	Band 2 20M QPSK_1RB	Front	0.030	0.186	0.216
		Rear	0.105	0.186	0.291
		Rear (Belt Clip)	0.049	0.186	0.235
	Band 2 20M QPSK_50RB	Front	0.024	0.186	0.210
		Rear	0.084	0.186	0.270
		Rear (Belt Clip)	0.040	0.186	0.226
	Band 12 10M QPSK_1RB	Front	0.064	0.186	0.250
		Rear	0.046	0.186	0.232
		Rear (Belt Clip)	0.047	0.186	0.233
	Band 12 10M QPSK_25RB	Front	0.053	0.186	0.239
		Rear	0.039	0.186	0.225
		Rear (Belt Clip)	0.039	0.186	0.225
	Band 17 10M QPSK_1RB	Front	0.066	0.186	0.252
		Rear	0.048	0.186	0.234
		Rear (Belt Clip)	0.049	0.186	0.235
	Band 17 10M QPSK_25RB	Front	0.055	0.186	0.241
		Rear	0.039	0.186	0.225
		Rear (Belt Clip)	0.040	0.186	0.226

LTE	Band 25 20M QPSK_1RB	Front	0.567	0.186	0.753
		Rear	0.409	0.186	0.595
		Rear (Belt Clip)	0.419	0.186	0.605
	Band 25 20M QPSK_50RB	Front	0.514	0.186	0.700
		Rear	0.371	0.186	0.557
		Rear (Belt Clip)	0.381	0.186	0.567
	Band 26 15M QPSK_1RB	Front	0.076	0.186	0.262
		Rear	0.055	0.186	0.241
		Rear (Belt Clip)	0.056	0.186	0.242
	Band 26 15M QPSK_38RB	Front	0.064	0.186	0.250
		Rear	0.046	0.186	0.232
		Rear (Belt Clip)	0.047	0.186	0.233

15. TestSetup Photos



Liquid depth in the SAM-Twin phantom



Front(25mm)



Front(10mm)



Rear(10mm)



Rear- Belt Clip(0mm)

16. External and Internal Photos of the EUT

Please reference to the report No.: CHTEW20010102

-----End of Report-----