

MPE Calculation

Regulation(s): Part 1.1310, Part 2.1091

Method: KDB447498 D01v06

RF feature(Mode)	Frequency range (MHz)			Max Target Power (dBm)	ANT Gain Including Cable Loss (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm ²)	Requirement (mW/cm ²)
Bluetooth(1 Mbps)	2 402.00	~	2 480.00	14.00	2.30	16.30	42.658	0.009	1.000
Bluetooth(2, 3 Mbps)	2 402.00	~	2 480.00	11.00	2.30	13.30	21.380	0.004	1.000
Bluetooth BLE(1, 2 Mbps)	2 402.00	~	2 480.00	10.00	2.30	12.30	16.983	0.003	1.000
		~							
		~							
		~							
		~							
		~							

Note: Please refer to the operation description for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 42.658 / (4 \times 20^2 \times \pi) \\
 &= 0.009 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna(20cm)

Part 1.1310

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)			Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averaging time (minutes)
0.3	~	1.34	614	1.63	*100	30
1.34	~	30	824/f	2.19 / f	*180 / f ²	30
30	~	300	27.5	0.073	0.2	30
300	~	1,500			f / 1500	30
1,500	~	100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC