



TEST REPORT

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR19-SRF0031 Page (1) of (46)	
1. Client ◦ Name : CITECH CO.,LTD. ◦ Address : 11F, 932, Yangjae-daero, Songpa-gu, Seoul, Republic of Korea ◦ Date of Receipt : 2018-12-03 2. Use of Report : - 3. Name of Product and Model : Premium Media Player / RS350 4. Manufacturer and Country of Origin : CITECH CO.,LTD. / Korea 5. FCC ID : 2ANYL-RS350 6. Date of Test : 2019-02-01 to 2019-02-22 7. Test Standards : FCC Part 15 Subpart C, 15.247 8. Test Results : Refer to the test result in the test report		
Affirmation	Tested by Name : Taekyong Nam (Signature)	Technical Manager Name : Bongok Ko (Signature)
2019-03-13 KCTL Inc. As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.		

Report revision history

Date	Revision	Page No
2019-03-13	Initial report	-

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document.

This test report is a general report that does not use the KOLAS accreditation mark and is not related to KOLAS accreditation.

KCTL

CONTENTS

1.	General information	4
2.	Device information	4
2.1.	Accessory information	5
2.2.	Information about derivative model.....	5
2.3.	Frequency/channel operations.....	5
3.	Antenna requirement	5
4.	Summary of tests	6
5.	Measurement uncertainty	6
6.	Measurement results explanation example	7
7	Test results	8
7.1.	Maximum peak output power.....	8
7.2.	Carrier frequency separation	10
7.3.	20dB channel bandwidth	13
7.4.	Number of hopping channels.....	17
7.5.	Time of occupancy(Dwell time).....	19
7.6.	Radiated spurious emissions & band edge.....	24
7.7.	AC Conducted emission	44
8.	Measurement equipment.....	46

1. General information

Client : CITECH CO.,LTD.
 Address : 11F, 932, Yangjae-daero, Songpa-gu, Seoul, Republic of Korea
 Manufacturer : CITECH CO.,LTD.
 Address : 11F, 932, Yangjae-daero, Songpa-gu, Seoul, Republic of Korea
 Laboratory : KCTL Inc.
 Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
 Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132
 VCCI Registration No. : R-3327, G-198, C-3706, T-1849
 Industry Canada Registration No. : 8035A-2
 KOLAS No.: KT231

2. Device information

Equipment under test : Premium Media Player
 Model : RS350
 Derivative model : RS350A, RS350B, RS350C, RS350D, RS350E, RS350F, RS350G, RS350H, RS350I, RS350J, RS350K, RS350L, RS350M, RS350N, RS350O, RS350P, RS350Q, RS350R, RS350S, RS350T, RS350U, RS350V, RS350W, RS350X, RS350Y, RS350Z
 Frequency range : Bluetooth(BDR/EDR)_2 402 MHz ~ 2 480 MHz
 WIFI(802.11b/g/n20)_2 412 MHz ~ 2 462 MHz
 WIFI(802.11a/n20)_5 180 MHz ~ 5 240 MHz (UNII-1)
 5 745 MHz ~ 5 825 MHz (UNII-3)
 Modulation technique : Bluetooth(BDR/EDR)_ GFSK, $\pi/4$ DQPSK, 8DPSK
 WIFI(802.11a/b/g/n20)_DSSS, OFDM
 Number of channels : Bluetooth(BDR/EDR)_79ch
 WIFI(802.11b/g/n20)_11ch (2.4 GHz)
 WIFI(802.11a/n20)_UNII-1_4ch
 WIFI(802.11a/n20)_UNII-3_5ch
 Power source : DC 12 V
 Antenna specification : Chip Antenna
 3.49 dBi (Bluetooth, WIFI 2.4 GHz), 2.64 dBi (WIFI 5 GHz)
 Software version : 1.3.06
 Hardware version : Rev 1.0
 Test device serial No. : N/A
 Operation temperature : 0 °C ~ 40 °C

2.1. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
SWITCHING ADAPTER	Chung Kwang Tech Inc.	ADS-25NP-12-112024E	-	AC 100 ~ 240 V

2.2. Information about derivative model

The difference between basic model and derivative models is:
Simplified derivation based on buyer's model name.

2.3. Frequency/channel operations

This device contains the following capabilities:
Bluetooth(BDR/EDR), WIFI(802.11a/b/g/n20)

Ch.	Frequency (MHz)
00	2 402
.	.
39	2 441
.	.
78	2 480

Table 2.3.1. Bluetooth(BDR/EDR) mode

15.247 Requirements for Bluetooth transmitter:

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
 - 1) This system is hopping pseudo-randomly.
 - 2) Each frequency is used equally on the average by each transmitter.
 - 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
 - 4) The receiver shifts frequencies in synchronization with the transmitted signals.
- 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
- 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

3. Antenna requirement

Requirement of FCC part section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The transmitter has permanently attached Chip antenna (internal antenna) on board.

4. Summary of tests

FCC Part section(s)	Parameter	Test results
15.247(b)(1), (4)	Maximum peak output power	Pass
15.247(a)(1)	Carrier frequency separation	Pass
15.247(a)(1)	20dB channel bandwidth	Pass
-	Occupied bandwidth	Pass
15.247(a)(iii) 15.247(b)(1)	Number of hopping channel	Pass
15.247(a) (iii)	Time of occupancy(dwell time)	Pass
15.205(a), 15.209(a)	Spurious emission	Pass
15.247(d),	Band-edge, restricted band	Pass

Notes:

1. All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
2. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
3. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that X orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in X orientation
4. The test procedure(s) in this report were performed in accordance as following.
 - ♦ ANSI C63.10-2013

5. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty	
Conducted RF power	1.76 dB	
Conducted spurious emissions	4.03 dB	
Radiated spurious emissions	9 kHz ~ 30 MHz:	2.28 dB
	30 MHz ~ 300 MHz	4.98 dB
	300 MHz ~ 1 000 MHz	5.14 dB
	1 GHz ~ 6 GHz	6.70 dB
	Above 6 GHz	6.60 dB
Conducted emissions	9 kHz ~ 150 kHz	3.66 dB
	150 kHz ~ 30 MHz	3.26 dB

6. Measurement results explanation example

The offset level is set in the spectrum analyzer to compensate the RF cable loss factor between EUT conducted output port and spectrum analyzer.

With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Frequency (MHz)	Factor(dB)	Frequency (MHz)	Factor(dB)
30	15.98	9 000	17.99
100	16.22	10 000	17.96
200	16.29	11 000	17.77
300	16.40	12 000	17.65
400	16.39	13 000	18.38
500	16.52	14 000	18.71
600	16.51	15 000	18.53
700	16.61	16 000	19.04
800	16.61	17 000	18.67
900	16.63	18 000	19.23
1 000	16.68	19 000	19.46
2 000	17.09	20 000	19.10
3 000	17.39	21 000	19.73
4 000	17.59	22 000	19.05
5 000	18.06	23 000	19.84
6 000	18.37	24 000	19.36
7 000	17.59	25 000	19.84
8 000	17.66	26 000	19.45


Note.

Offset(dB) = RF cable loss(dB) + Attenuator(dB) + Divider(dB)

7 Test results

7.1. Maximum peak output power

Test setup



Limit

According to §15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

According to §15.247(b)(1), for frequency hopping systems operating in the 2 400-2 483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725-5 850 MHz band: 1 watt. For all other frequency hopping systems in the 2 400-2 483.5 MHz band: 0.125 watts.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test procedure

ANSI C63.10-2013 - Section 7.8.5

Test settings

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

Use the following spectrum analyzer settings:

- 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 2) RBW > 20 dB bandwidth of the emission being measured.
- 3) VBW ≥ RBW.
- 4) Sweep: Auto.
- 5) Detector function: Peak.
- 6) Trace: Max hold.
- 7) Allow trace to stabilize.

Notes:

A peak responding power sensor is used, where the power sensor system video bandwidth is greater than the occupied bandwidth of the EUT.

Test results

Frequency(MHz)	Data rate(Mbps)	Measured output power(dBm)		Limit(dBm)
		Peak	Average ¹⁾	
2 402	1	-7.18	-10.21	30.00
2 441	1	-7.92	-5.47	
2 480	1	-4.27	-6.46	
2 402	2	-6.87	-11.54	30.00
2 441	2	-4.97	-9.03	
2 480	2	-3.77	-7.57	
2 402	3	-6.87	-11.55	30.00
2 441	3	-4.97	-9.08	
2 480	3	-3.77	-7.57	


Note.

1. Average(dB m) = Reading(dB m) + Duty Factor(dB)



7.2. Carrier frequency separation

Test setup



Limit

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test procedure

ANSI C63.10-2013 - Section 7.8.2

Test settings

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031

Page (11) of (46)

**Test results**

Frequency(MHz)	Data rate(Mbps)	Carrier frequency separation(MHz)	Limit(MHz)
2 402	1	1.000	0.920
2 441	1	1.000	0.925
2 480	1	1.000	0.920
2 402	3	1.000	0.883
2 441	3	1.000	0.886
2 480	3	1.000	0.883

KCTL

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031

Page (12) of (46)




GFSK




2 402 MHz


8DPSK




2 402 MHz




2 441 MHz



2 441 MHz



2 480 MHz




2 480 MHz

This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

7.3. 20dB channel bandwidth

Test setup



Limit

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test procedure

ANSI C63.10-2013 - Section 6.9.2

Test settings

The occupied bandwidth is measured as the width of the spectral envelope of the modulated signal, at an amplitude level reduced from a reference value by a specified ratio (or in decibels, a specified number of dB down from the reference value). Typical ratios, expressed in dB, are -6 dB, -20 dB, and -26 dB, corresponding to 6 dB BW, 20 dB BW, and 26 dB BW, respectively. In this subclause, the ratio is designated by “-xx dB.” The reference value is either the level of the unmodulated carrier or the highest level of the spectral envelope of the modulated signal, as stated by the applicable requirement. Some requirements might specify a specific maximum or minimum value for the “-xx dB” bandwidth; other requirements might specify that the “-xx dB” bandwidth be entirely contained within the authorized or designated frequency band.

- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.
Span: Two times and five times the OBW.
- RBW = 1 % to 5 % of the OBW and VBW ≥ 3 x RBW
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation.
- The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- Detector: peak
- Trace mode: max hold.
- Allow the trace to stabilize.
- Determine the “-xx dB down amplitude” using ((reference value) - xx). Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

Test results

Frequency(MHz)	Data rate(Mbps)	20 dB bandwidth(MHz)	99 % bandwidth(MHz)
2 402	1	0.920	0.912
2 441	1	0.925	0.916
2 480	1	0.920	0.912
2 402	3	1.324	1.211
2 441	3	1.329	1.211
2 480	3	1.324	1.216

KCTL

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031

Page (15) of (46)



20 dB bandwidth(MHz)



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031

Page (16) of (46)




99 % bandwidth(MHz)



7.4. Number of hopping channels

Test setup



Limit

According to §15.247(a)(1)(iii), Frequency hopping systems in the 2 400-2 483.5 MHz band shall use at least 15 channels.

Test procedure

ANSI C63.10-2013 - Section 7.8.3

Test settings

- Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- RBW: To identify clearly the individual channels, set the RBW to less than 30 % of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- VBW $\geq$ RBW.
- Sweep: Auto.
- Detector function: Peak.
- Trace: Max hold.
- Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Test results

Mode	Number of hopping channel	Limit
GFSK	79	≥ 15
$\pi/4$ DQPSK	79	≥ 15
8DPSK	79	≥ 15

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031


Page (18) of (46)

KCTL


Non-AFH



GFSK




$\pi/4$ DQPSK



8DPSK

7.5. Time of occupancy(Dwell time)

Test setup



Limit

According to §15.247(a)(1)(iii), frequency hopping systems in the 2 400-2 483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test procedure

ANSI C63.10-2013 - Section 7.8.4

Test settings

- Span: Zero span, centered on a hopping channel.
- RBW $\leq$ channel spacing and $\gg 1 / T$, where T is the expected dwell time per channel.
- Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- Detector function: Peak.
- Trace: Max hold.
- Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Test results**- Non-AFH**

Modulation	Frequency (MHz)	Pulse Width (ms)	Hopping rate (hop/s)	Number of Channels	Result (s)	Limit (s)
DH1	2 441	0.382	800.000	79	0.122	0.400
DH3	2 441	1.639	400.000	79	0.262	0.400
DH5	2 441	2.883	266.667	79	0.308	0.400
2-DH1	2 441	0.388	800.000	79	0.124	0.400
2-DH3	2 441	1.640	400.000	79	0.262	0.400
2-DH5	2 441	2.893	266.667	79	0.309	0.400
3-DH1	2 441	0.388	800.000	79	0.124	0.400
3-DH3	2 441	1.637	400.000	79	0.262	0.400
3-DH5	2 441	2.890	266.667	79	0.308	0.400

- AFH

Modulation	Frequency (MHz)	Pulse Width (ms)	Hopping rate (hop/s)	Number of Channels	Result (s)	Limit (s)
DH1	2 441	0.383	400.000	20	0.061	0.400
DH3	2 441	1.637	200.000	20	0.131	0.400
DH5	2 441	2.890	133.333	20	0.154	0.400
2-DH1	2 441	0.388	400.000	20	0.062	0.400
2-DH3	2 441	1.640	200.000	20	0.131	0.400
2-DH5	2 441	2.893	133.333	20	0.154	0.400
3-DH1	2 441	0.388	400.000	20	0.062	0.400
3-DH3	2 441	1.638	200.000	20	0.131	0.400
3-DH5	2 441	2.891	133.333	20	0.154	0.400

Notes:

1. Non-AFH

- Period Time: 0.4 sec x 79 channels = 31.6 sec
- Result (s)= (Hopping rate (hop/s/slot) / 79 channels) x 31.6 sec x Pulse width (ms)

2. AFH

- Period Time: 0.4 sec x 20 channels = 8 sec
- Result (s)= (Hopping rate (hop/s/slot) / 20 channels) x 8 sec x Pulse width (ms)

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031


Page (21) of (46)




Non-AFH(GFSK)




Non-AFH($\pi/4$ DQPSK)




DH1




2-DH1



DH3



2-DH3



DH5

2-DH5

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031


Page (22) of (46)




Non-AFH(8DPSK)




AFH(GFSK)




3-DH1




DH1



3-DH3



DH3



3-DH5

DH5

This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031


Page (23) of (46)




AFH($\pi/4$ DQPSK)




AFH(8DPSK)




2-DH1




3-DH1



2-DH3



3-DH3




2-DH5

3-DH5


7.6. Radiated spurious emissions & band edge

Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



Limit

According to section 15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength ($\mu V/m$)	Measurement distance (m)
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., Section 15.231 and 15.241.

According to section 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 - 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 - 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 - 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 - 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 - 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 - 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 - 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 - 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525	2 483.5 - 2 500	17.7 - 21.4
8.376 25 - 8.386 75	25	2 690 - 2 900	22.01 - 23.12
8.414 25 - 8.414 75	156.7 - 156.9	3 260 - 3 267	23.6 - 24.0
12.29 - 12.293	162.012 5 - 167.17	3 332 - 3 339	31.2 - 31.8
12.519 75 - 12.520 25	167.72 - 173.2	3 345.8 - 3 358	36.43 - 36.5
12.576 75 - 12.577 25	240 - 285	3 600 - 4 400	Above 38.6
13.36 - 13.41	322 - 335.4		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in section 15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in section 15.35 apply to these measurements.

Test procedure

ANSI C63.10-2013

Test settings**Peak field strength measurements**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in table
3. VBW $\geq (3 \times \text{RBW})$
4. Detector = peak
5. Sweep time = auto
6. Trace mode = max hold
7. Allow sweeps to continue until the trace stabilizes

Table. RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz to 120 kHz
> 1 000 MHz	1 MHz

Average field strength measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1 MHz
3. VBW = $1/T \geq 1$ Hz
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to run for at least 50 times(1/duty cycle) traces

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1 kHz ($\geq 1/T$) for Average detection (AV) at frequency above 1 GHz. (where T = pulse width)
2. $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m/D_s)$
 $f \geq 30$ MHz, extrapolation factor of 20 dB/decade of distance. $F_d = 20 \log(D_m/D_s)$

Where:

 F_d = Distance factor in dB D_m = Measurement distance in meters D_s = Specification distance in meters

3. Factors(dB) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or F_d (dB)
4. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
5. Average test would be performed if the peak result were greater than the average limit.
6. ¹⁾ mean is restricted band.

7. According to part 15.31(f)(2), an extrapolation factor of 40 dB/decade is applied because measured distance of radiated emission is 3 m.

Duty cycle correction factor calculation:

According to 7.5 Procedure for determining the average value of pulsed emissions

Duty Cycle Correction Factor Calculation

- Worst case : AFH mode
- Channel hop rate = 800 hops/second
- Hopping rate for DH5 mode = 800 hops/second / 5 (6 slots for DH5) = 133.33 hops/second
- Time per channel hop = $1 / 133.33 \text{ hops/second} = 7.50 \text{ ms}$
- Time to cycle through all channels = $7.50 \times 20 \text{ channels(AFH mode)} = 150 \text{ ms}$
- Number of times transmitter hits on one channel = $100 \text{ ms} / \text{Time to cycle through all channels (ms)}$
 $= 100 \text{ ms} / 150 \text{ ms} = 1 \text{ time}$
- Worst case Dwell time = 7.5 ms
- Duty Cycle Correction Factor = $20\log(7.5 \text{ ms}/100 \text{ ms}) = -22.5 \text{ dB}$

KCTL

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031

Page (28) of (46)

**Test results (Below 30 MHz) – Worst case: GFSK Low frequency**

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB)	(dB($\mu V/m$))	(dB($\mu V/m$))	(dB)
No spurious emissions were detected within 20 dB of the limit.									

Horizontal/Vertical

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031

Page (29) of (46)


Test results (Below 1 000 MHz) – Worst case: GFSK Low frequency

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Quasi peak data									
35.82	V	38.30	1.19	-36.01	21.72	-	25.20	40.00	14.80
94.87	V	45.30	2.07	-32.95	15.68	-	30.10	43.50	13.40
191.99	H	41.50	3.05	-30.51	15.26	-	29.30	43.50	14.20
259.41	H	42.30	3.58	-31.47	18.39	-	32.80	46.00	13.20
395.93	H	38.00	4.54	-30.64	21.60	-	33.50	46.00	12.50
563.14	V	33.20	5.50	-30.02	24.12	-	32.80	46.00	13.20

Horizontal/Vertical


This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr




Report No.:
KR19-SRF0031

Page (30) of (46)

KCTL**Test results (Above 1 000 MHz)****GFSK****Low Channel**

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data									
1 187.73 ¹⁾	H	56.75	2.65	- 36.04	24.55	-	47.91	74.00	26.09
1 979.38	H	51.67	3.41	- 36.19	27.72	-	46.61	74.00	27.39
2 387.11 ¹⁾	V	45.58	3.70	- 36.23	28.54	-	41.59	74.00	32.41
4 805.00 ¹⁾	V	62.08	5.34	- 60.83	32.80	-	39.39	74.00	34.61
7 205.66	V	60.41	6.71	- 61.37	35.91	-	41.66	74.00	32.34
Average Data									
No spurious emissions were detected within 20 dB of the limit.									




Horizontal/Vertical for Band-edge

Horizontal/Vertical for 1 GHz ~ 3.5 GHz**Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

Middle Channel

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB)	(dB($\mu V/m$))	(dB($\mu V/m$))	(dB)
Peak data									
1 188.91 ¹⁾	H	57.02	2.65	- 36.05	24.56	-	48.18	74.00	25.80
1 980.08	V	53.04	3.41	- 36.19	27.72	-	47.98	74.00	26.02
4 904.23 ¹⁾	V	65.19	5.41	- 61.10	32.85	-	42.35	74.00	31.65
7 323.92 ¹⁾	V	60.24	6.76	- 61.58	36.02	-	41.44	74.00	32.56
Average Data									
No spurious emissions were detected within 20 dB of the limit.									



Horizontal/Vertical for 1 GHz ~ 3.5 GHz**Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr




Report No.:
KR19-SRF0031

Page (34) of (46)

**High Channel**

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data									
1 188.36 ¹⁾	H	57.30	2.65	- 36.04	24.55	-	48.46	74.00	25.54
1 979.61	H	51.30	3.41	- 36.19	27.72	-	46.24	74.00	27.76
2 484.45 ¹⁾	V	54.61	3.77	- 35.92	28.72	-	51.18	74.00	22.82
4 959.97 ¹⁾	V	61.99	5.44	- 60.71	32.88	-	39.60	74.00	34.40
7 441.73 ¹⁾	H	58.79	6.81	- 61.80	36.14	-	39.94	74.00	34.06
Average Data									
No spurious emissions were detected within 20 dB of the limit.									

Horizontal/Vertical for Band-edge

Horizontal/Vertical for 1 GHz ~ 3.5 GHz**Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr




Report No.:
KR19-SRF0031

Page (36) of (46)

**8DPSK****Low Channel**

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data									
1 187.73 ¹⁾	H	57.94	2.65	- 36.04	24.55	-	49.10	74.00	24.90
1 979.69	H	53.81	3.41	- 36.19	27.72	-	48.75	74.00	25.25
2 385.86 ¹⁾	V	45.48	3.70	- 36.23	28.53	-	41.48	74.00	32.52
4 803.64 ¹⁾	H	62.71	5.34	- 60.83	32.80	-	40.02	74.00	33.98
7 205.66	V	62.00	6.71	- 61.37	35.91	-	43.25	74.00	30.75
Average Data									
No spurious emissions were detected within 20 dB of the limit.									




Horizontal/Vertical for Band-edge

Horizontal/Vertical for 1 GHz ~ 3.5 GHz**Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

Middle Channel

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB)	(dB($\mu V/m$))	(dB($\mu V/m$))	(dB)
Peak data									
1 188.20 ¹⁾	H	57.78	2.65	- 36.04	24.55	-	48.94	74.00	25.06
1 979.84	H	52.20	3.41	- 36.19	27.72	-	47.14	74.00	26.86
4 881.58 ¹⁾	V	60.28	5.39	- 61.06	32.84	-	37.45	74.00	36.55
7 323.92 ¹⁾	H	60.01	6.76	- 61.58	36.02	-	41.21	74.00	32.79
Average Data									
No spurious emissions were detected within 20 dB of the limit.									

KCTL

Horizontal/Vertical for 1 GHz ~ 3.5 GHz**Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031

Page (40) of (46)




**High Channel**

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data									
1 187.97 ¹⁾	H	56.97	2.65	- 36.04	24.55	-	48.13	74.00	25.87
1 979.92	H	53.38	3.41	- 36.19	27.72	-	48.32	74.00	25.68
2 484.53 ¹⁾	V	50.96	3.77	- 35.92	28.72	-	47.55	74.00	26.47
4 859.38 ¹⁾	V	63.91	5.38	- 61.00	32.83	-	41.12	74.00	32.88
7 436.75	V	60.96	6.81	- 61.80	36.14	-	42.11	74.00	31.89
Average Data									
No spurious emissions were detected within 20 dB of the limit.									

Horizontal/Vertical for Band-edge

This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

Horizontal/Vertical for 1 GHz ~ 3.5 GHz**Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031


Page (42) of (46)




Test results

GFSK


Conducted band-edge



Lowest




Highest




With Hopping Band-edge


Conducted spurious



Lowest



Middle



Highest

This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0031


Page (43) of (46)

KCTL


Test results

8DPSK


Conducted band-edge




Conducted spurious




Lowest




Lowest



Highest



Middle




With Hopping Band-edge

Highest

7.7. AC Conducted emission

Test setup




Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall be on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted limit (dB μ V/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

Measurement procedure

1. The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5m away from the side wall of the shielded room.
2. Each current-carrying conductor of the EUT power cord was individually connected through a 50 Ω /50 μ H LISN, which is an input transducer to a spectrum analyzer or an EMI/Field Intensity Meter, to the input power source.
3. Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
4. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
5. The measurements were made with the detector set to peak amplitude within a bandwidth of 10 kHz or to quasi-peak and average within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

Test results

Final Result

--- N Phase ---									
No.	Frequency	Reading QP	Reading CAV	c. f	Result QP	Result CAV	Limit QP	Limit AV	Margin
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]
1	0.15461	39.2	15.4	9.8	49.0	25.2	65.7	55.7	16.7
2	0.18407	36.9	15.8	10.0	46.9	25.8	64.3	54.3	17.4
3	0.22221	33.5	12.7	9.7	43.2	22.4	62.7	52.7	19.5
4	0.25767	30.7	8.6	9.6	40.3	18.2	61.5	51.5	21.2
5	0.55773	13.2	2.0	9.8	23.0	11.8	56.0	46.0	33.0
6	0.66672	8.9	1.1	9.8	18.7	10.9	56.0	46.0	37.3
7	1.13975	8.1	0.5	9.7	17.8	10.2	56.0	46.0	38.2
8	10.37218	6.3	0.4	10.0	16.3	10.4	60.0	50.0	43.7
9	14.33491	11.3	6.7	10.1	21.4	16.8	60.0	50.0	38.6
10	25.47647	10.2	5.0	10.1	20.3	15.1	60.0	50.0	39.7

--- L1 Phase ---									
No.	Frequency	Reading QP	Reading CAV	c. f	Result QP	Result CAV	Limit QP	Limit AV	Margin
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]
1	0.77759	8.9	0.3	9.8	18.7	10.1	56.0	46.0	37.3
2	1.44898	7.3	0.2	9.7	17.0	9.9	56.0	46.0	39.0
3	22.7733	7.0	0.4	10.1	17.1	10.5	60.0	50.0	42.9

8. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R & S	FSV30	100807	19.08.01
Spectrum Analyzer	R & S	FSV40	100989	20.01.04
Wideband Power Sensor	R & S	NRP-Z81	102398	20.01.25
Power Divider	Aeroflex/ Weinschel, Inc	1580-1	NX380	19.08.02
Bluetooth Tester	TESCOM	TC-3000B	3000B640056	20.01.25
ATTENUATOR	R & S	DNF Dämpfungsglied 10 dB in N-50 Ohm	31212	19.05.14
EMI TEST RECEIVER	R & S	ESCI	100732	19.08.23
Bi-Log Antenna	SCHWARZBECK	VULB 9168	583	20.05.04
Amplifier	SONOMA INSTRUMENT	310N	284608	19.08.23
COAXIAL FIXED ATTENUATOR	Agilent	8491B-003	2708A18758	20.05.04
Horn antenna	ETS.lindgren	3116	00086635	19.05.10
Horn antenna	ETS.lindgren	3117	161225	19.05.18
AMPLIFIER	L-3 Narda-MITEQ	AMF-7D-01001800 -22-10P	2003683	19.05.15
AMPLIFIER	L-3 Narda-MITEQ	JS44-18004000-33 -8P	2000997	19.08.02
LOOP Antenna	R & S	HFH2-Z2	100355	20.08.24
Antenna Mast	Innco Systems	MA4640-XP-ET	-	-
Turn Table	Innco Systems	DT2000	79	-
Antenna Mast	Innco Systems	MA4000-EP	303	-
Turn Table	Innco Systems	DT2000	79	-
TWO-LINE V - NETWORK	R&S	ENV216	101584	19.04.05
EMI TEST RECEIVER	R & S	ESCI	101408	19.08.23
Highpass Filter	WT	WT-A1698-HS	WT160411001	19.05.14
Vector Signal Generator	R & S	SMBV100A	257566	20.01.04
Signal Generator	R & S	SMR40	100007	19.05.15
Cable Assembly	RadiAll	2301761768000PJ	1724.659	-
Cable Assembly	gigalane	RG-400	-	-
Cable Assembly	HUER+SUHNER	SUCOFLEX 104	MY4342/4	-

End of test report