

FCC PART 15B, CLASS B TEST REPORT

For

SY Electronic Technical Co., Ltd.

4th Floor, 2 BLDG. East, Minqi Technology Park Pingshan 1st RD., Nanshan Shenzhen China

FCC ID: 2AO3B-HS100W01
Model: HS100W


Report Type: Original Report	Product Type: DefendX Wireless Indoor/Outdoor Camera
Report Number: RSZ180123001-00A	
Report Date: 2018-03-09	
Reviewed By: RF Engineer	Candy Li 
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	3
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT EXERCISE SOFTWARE	5
SPECIAL ACCESSORIES.....	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC §15.107 – AC LINE CONDUCTED EMISSIONS.....	10
APPLICABLE STANDARD	10
EUT SETUP	10
EMI TEST RECEIVER SETUP.....	10
TEST PROCEDURE	10
CORRECTED FACTOR & MARGIN CALCULATION	11
TEST RESULTS SUMMARY	11
TEST DATA	11
FCC §15.109 - RADIATED SPURIOUS EMISSIONS	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	17
TEST DATA	18

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The SY Electronic Technical Co., Ltd.'s product, model number: HS100W (FCC ID: 2AO3B-HS100W01) or the "EUT" in this report was a *DefendX Wireless Indoor/Outdoor Camera*, which was measured approximately: 10.6cm (L) × 8.8 cm (W) × 5.5cm (H), rated with input voltage: DC 3.7V*2 battery or DC 12V from Adapter. The highest operating frequency is 2480MHz.

Adapter Information:

Model: KT241120200H

Input: 100-240V~50/60Hz, 0.8A

Output: 12V, 2A.

**All measurement and test data in this report was gathered from production sample serial number: 1800083. (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2018-01-23.*

Objective

This test report is prepared on behalf of SY Electronic Technical Co., Ltd. in accordance with Part 2-Subpart J, Part 15-Subparts A, B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15 B.

Related Submittal(s)/Grant(s)

Part 15.247 DTS submissions with FCC ID: 2AO3B-HS100W01.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		uncertainty
Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 382179, the FCC Designation No. : CN5001.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a manufacturer testing fashion.

EUT operation mode 1: Downloading (data transfer with computer)

EUT operation mod 2: Charging&recording

EUT Exercise Software

“BurnIn test v5.3” exercise software was used.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	PC	VOSTRO 220S	127BP2X
TCL	Monitor	TFT1560PS	ALA560806C160409
DELL	Keyboard	L100	CNORH656658907BL05DC
DELL	Mouse	MOC5UO	G1900NKD
SAST	Modem	AEM-2100	0293


External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-Shielding Detachable USB Cable	1.5	Host PC	Mouse
Shielding Detachable Serial Cable	1.2	Host PC	Modem
Shielding Detachable K/B Cable	1.5	Host PC	Keyboard
Shielding Detachable VGA Cable	1.5	Host PC	LCD Monitor
Un-Shielding Detachable USB Cable with Magnet Ring	0.54	EUT	Host PC
Un-Shielding Un-Detachable DC Power Cable with Magnet Ring	1.7	EUT	Adapter


Block Diagram of Test Setup

For conducted emission:

Downloading Mode:



Charging&Recording mode:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Spurious Emissions	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
AC Line Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2017-08-04	2018-08-04
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2017-12-21	2018-12-21
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2017-11-29	2018-05-21
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
N/A	Conducted Emission Cable	N/A	UF A210B-1-0720-504504	2017-11-12	2018-05-12
Radiated Emission Test					
A.H.System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2017-04-24	2018-04-24
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2017-12-17	2020-12-16
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2017-05-21	2018-05-21
HP	Amplifier	HP8447E	1937A01046	2017-11-19	2018-05-21
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2018-01-11	2019-01-11
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2017-11-19	2018-05-21
Ducommun technologies	RF Cable	104PEA	218124002	2017-11-19	2018-05-21
Ducommun technologies	RF Cable	RG-214	1	2017-11-19	2018-05-21
Ducommun technologies	RF Cable	RG-214	2	2017-11-22	2018-05-22


*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.107 – AC LINE CONDUCTED EMISSIONS

Applicable Standard

According to FCC §15.107

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the host PC was connected to the first LISN and the other relevant equipments were connected to the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa


The testing was performed by Simon Wang on 2018-03-01.

EUT Operation Mode: Downloading

AC 120V/60 Hz, Line




Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
8.961130	37.1	20.0	60.0	22.9	QP
9.256630	37.0	20.0	60.0	23.0	QP
9.363190	37.7	20.0	60.0	22.3	QP
9.665010	37.9	20.0	60.0	22.1	QP
15.541590	37.6	20.1	60.0	22.4	QP
15.929970	37.2	20.1	60.0	22.8	QP
8.961130	36.5	20.0	50.0	13.5	Ave.
9.256630	29.6	20.0	50.0	20.4	Ave.
9.363190	37.3	20.0	50.0	12.7	Ave.
9.665010	37.4	20.0	50.0	12.6	Ave.
15.541590	29.8	20.1	50.0	20.2	Ave.
15.929970	29.9	20.1	50.0	20.1	Ave.

AC 120V/60 Hz, Neutral


Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.360510	36.0	20.2	58.7	22.7	QP
0.407850	39.1	20.2	57.7	18.6	QP
15.197130	38.8	20.1	60.0	21.2	QP
19.428990	38.4	20.2	60.0	21.6	QP
21.837370	41.1	20.1	60.0	18.9	QP
21.837750	40.9	20.1	60.0	19.1	QP
0.360510	24.6	20.2	48.7	24.1	Ave.
0.407850	30.2	20.2	47.7	17.5	Ave.
15.197130	31.3	20.1	50.0	18.7	Ave.
19.428990	34.3	20.2	50.0	15.7	Ave.
21.837370	33.6	20.1	50.0	16.4	Ave.
21.837750	34.0	20.1	50.0	16.0	Ave.

EUT Operation Mode: Charging&Recording

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.293500	34.4	20.2	60.4	26.0	QP
0.352750	37.8	20.2	58.9	21.1	QP
0.376330	36.0	20.2	58.4	22.4	QP
0.407910	39.3	20.2	57.7	18.4	QP
0.439430	33.0	20.2	57.1	24.1	QP
1.070070	32.0	20.1	56.0	24.0	QP
0.293500	28.8	20.2	50.4	21.6	Ave.
0.352750	28.4	20.2	48.9	20.5	Ave.
0.376330	20.8	20.2	48.4	27.6	Ave.
0.407910	29.9	20.2	47.7	17.8	Ave.
0.439430	16.6	20.2	47.1	30.5	Ave.
1.070070	24.7	20.1	46.0	21.3	Ave.

AC 120V/60 Hz, Neutral

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.355250	37.2	20.2	58.8	21.6	QP
0.360630	36.2	20.2	58.7	22.5	QP
0.411850	40.5	20.2	57.6	17.1	QP
0.467010	33.7	20.2	56.6	22.9	QP
0.494650	32.0	20.2	56.1	24.1	QP
0.991090	33.4	20.1	56.0	22.6	QP
0.355250	28.1	20.2	48.8	20.7	Ave.
0.360630	24.8	20.2	48.7	23.9	Ave.
0.411850	25.5	20.2	47.6	22.1	Ave.
0.467010	24.6	20.2	46.6	22.0	Ave.
0.494650	19.6	20.2	46.1	26.5	Ave.
0.991090	26.0	20.1	46.0	20.0	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude


FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Applicable Standard


FCC §15.109

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 12.4 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurment
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2018-03-01.

EUT Operation Mode: Downloading

30 MHz~1 GHz:



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
30.063812	22.91	112.0	H	338.0	0.3	40.00	17.09
433.091750	34.89	104.0	H	59.0	0.2	46.00	11.11
566.328750	35.95	203.0	H	50.0	4.4	46.00	10.05
632.996750	33.32	112.0	V	145.0	4.1	46.00	12.68
717.734875	40.73	114.0	V	357.0	7.0	46.00	5.27
867.054875	39.15	100.0	H	132.0	9.3	46.00	6.85

1 GHz – 12.4 GHz:


Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15B	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
2995.99	45.17	PK	218	2.0	H	2.36	47.53	74	26.47
2995.99	28.87	Ave.	218	2.0	H	2.36	31.23	54	22.77
2995.99	45.11	PK	70	1.6	V	2.36	47.47	74	26.53
2995.99	28.87	Ave.	70	1.6	V	2.36	31.23	54	22.77
5026.12	43.28	PK	205	2.3	H	7.82	51.10	74	22.90
5026.12	28.84	Ave.	205	2.3	H	7.82	36.66	54	17.34
5026.12	43.24	PK	341	1.4	V	7.82	51.06	74	22.94
5026.12	28.85	Ave.	341	1.4	V	7.82	36.67	54	17.33

Note:


- 1) Correction Factor=Antenna factor (RX) + cable loss – amplifier factor
- 2) Corrected Amplitude = Correction Factor + Reading
- 3) Margin = Limit - Corrected Amplitude

Pre-scan Peak as below:


Horizontal




Vertical



Pre-scan Average as below
Horizontal




Vertical



EUT Operation Mode: Charging&Recording

30 MHz~1 GHz:



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
30.432000	22.68	260.0	V	0.0	0.0	40.00	17.32
38.571375	19.18	104.0	V	206.0	-5.2	40.00	20.82
538.427000	26.95	363.0	V	113.0	4.4	46.00	19.05
693.289875	28.91	312.0	V	168.0	6.4	46.00	17.09
789.382375	30.80	367.0	V	125.0	8.7	46.00	15.20
893.004000	31.17	294.0	H	31.0	9.6	46.00	14.83

1 GHz – 12.4 GHz:


Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBuV/m)	FCC Part 15B	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H / V)			Limit (dBuV/m)	Margin (dB)
5040.08	42.45	PK	264	2.4	H	7.82	50.27	74	23.73
5040.08	29.12	Ave.	264	2.4	H	7.82	36.94	54	17.06
5040.08	43.17	PK	321	1.4	V	7.82	50.99	74	23.01
5040.08	29.26	Ave.	321	1.4	V	7.82	37.08	54	16.92
4878.12	43.02	PK	91	1.2	H	6.21	49.23	74	24.77
4878.12	29.03	Ave.	91	1.2	H	6.21	35.24	54	18.76
4878.12	43.24	PK	22	1.5	V	6.21	49.45	74	24.55
4878.12	29.15	Ave.	22	1.5	V	6.21	35.36	54	18.64

Note:


- 4) Correction Factor=Antenna factor (RX) + cable loss – amplifier factor
- 5) Corrected Amplitude = Correction Factor + Reading
- 6) Margin = Limit - Corrected Amplitude

Pre-scan Peak as below:


Horizontal




Vertical



Pre-scan Average as below
Horizontal



Vertical



***** END OF REPORT *****