



TEST REPORT

Reference No...... : WTX22X03047982W
FCC ID Number : FCC ID: 2AO3LB1385T24G
Applicant..... : MTMS (HK) LIMITED
Address..... : Room 1306, Block B, Veristrong Industrial Centre,
No. 34-36 Au Pui Wan Street, Fo Tan, New Territories, Hong Kong
Manufacturer : The same as Applicant
Address..... : The same as Applicant
Product Description : 2.4GHz Controller
Product Name : 2.4GHz Controller
Tested Model : B1385T
Rules/Standards : Part 15.249 of the FCC Rules
Received Date of Sample(s) : 2022-03-20
.....
Date of Test..... : 2022-03-25 to 2022-03-28
Date of Issue : 2022-03-28
Test Report Form No. ... : WTX_Part 15_249W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared by:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F, Building A, Hongwei Industrial Park Liuxian 2nd Road,

Bao'an District, Shenzhen, 518101, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Approved by:

Mike Shi (Project Engineer)

Silin Chen (Manager)

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE.....	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	12
3. ANTENNA REQUIREMENTS.....	13
3.1 STANDARD APPLICABLE.....	13
3.2 TEST RESULT.....	13
4. RADIATED EMISSIONS.....	14
4.1 STANDARD APPLICABLE.....	14
4.2 TEST PROCEDURE.....	14
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	17
4.4 SUMMARY OF TEST RESULTS/PLOTS	17
5. OUT OF BAND EMISSIONS.....	26
5.1 STANDARD APPLICABLE.....	26
5.2 TEST PROCEDURE.....	26
5.3 SUMMARY OF TEST RESULTS/PLOTS	26
6. EMISSION BANDWIDTH.....	30
6.1 STANDARD APPLICABLE.....	30
6.2 TEST PROCEDURE.....	30
6.3 SUMMARY OF TEST RESULTS/PLOTS	30
7. CONDUCTED EMISSIONS	33
7.1 TEST PROCEDURE.....	33
7.2 BASIC TEST SETUP BLOCK DIAGRAM.....	33
7.3 TEST RECEIVER SETUP	33
7.4 SUMMARY OF TEST RESULTS/PLOTS	33
APPENDIX PHOTOGRAPHS.....	34

Report version

Version No.	Date of Issue	Description
Rev.00	2022-03-28	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Description:	2.4GHz Controller
Product Name:	2.4GHz Controller
Tested Trade Name:	/
Tested Model:	B1385T
Adding Model(s):	/
Tested Sample No.:	WTX22X03047983W-1#
Power Source:	DC 4.5V (3 units of DC 1.5V AA-Size Battery)
Battery Capacity	/
Power Adapter Model:	/
Note: The test data is gathered from a production sample, provided by the manufacturer.	

Technical Characteristics of EUT	
Frequency Range:	2420-2462 MHz
Max. Field Strength:	90.36 dBuV/m
Modulation:	GFSK
Antenna Type:	Fixed 33mm-long Wire Antenna
Antenna Gain:	0 dBi
Note: The Antenna Gain is provided by the customer and can affect the validity of results.	

1.2 Test Standards

The tests were performed according to following standards:

Part 15.249 of the FCC Rules: Operation within the bands 902-928MHz, 2400-2483.5MHz, 5725-5875MHz, and 24.0-24.25GHz.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F, Building A, Hongwei Industrial Park Liuxian 2nd Road, Bao'an District, Shenzhen, 518101, China

Federal Communications Commission (FCC) - Test Firm Registration Number: 125990

The EMC Laboratory of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010 and Test Firm Registration Number is 125990.

Innovation, Science and Economic Development Canada (ISED) - ISED#/Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Innovation, Science and Economic Development Canada (ISED) for radio equipment testing with CAB identifier: CN0057 and ISED#/Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Lowest Channel	2420 MHz
TM2	Near Middle Channel	2441 MHz
TM3	Highest Channel	2462 MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With/Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With/Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-26GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
SEMT-1075	Communication Tester	Rohde & Schwarz	CMW500	148650	2022-03-22	2023-03-21
SEMT-1063	GSM Tester	Rohde & Schwarz	CMU200	114403	2022-03-22	2023-03-21
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2022-03-25	2023-03-24
SEMT-1079	Spectrum Analyzer	Agilent	N9020A	US47140102	2022-03-22	2023-03-21
SEMT-1080	Signal Generator	Agilent	83752A	3610A01453	2022-03-22	2023-03-21
SEMT-1081	Vector Signal Generator	Agilent	N5182A	MY47070202	2022-03-22	2023-03-21
SEMT-1028	Power Divider	Weinschel	1506A	PM204	2022-03-22	2023-03-21
SEMT-1082	Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2022-03-22	2023-03-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	/	/
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	/	/
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	/	/
SEMT-C004	Cable	Zheng DI	2M0RFC	/	/	/
SEMT-C005	Cable	Zheng DI	1M0RFC	/	/	/
SEMT-C006	Cable	Zheng DI	1M0RFC	/	/	/
☒ Chamber A: Below 1GHz						
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2022-03-22	2023-03-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2022-03-21	2023-03-20
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2022-01-07	2023-01-06
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2023-03-19
SEMT-1068	Broadband	Schwarz beck	VULB9163	9163-333	2021-03-20	2023-03-

	Antenna					19
☒ Chamber A: Above 1GHz						
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2022-03-22	2023-03-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2022-03-21	2023-03-20
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2022-03-21	2023-03-20
SEMT-1042	Horn Antenna	ETS	3117	00086197	2021-03-19	2023-03-18
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2021-04-27	2023-04-26
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2021-04-27	2022-04-26
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2022-03-22	2023-03-21
☐ Chamber B: Below 1GHz						
SEMT-1068	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2021-04-09	2023-04-08
SEMT-1067	Amplifier	Agilent	8447D	2944A10179	2022-03-21	2023-03-20
SEMT-1066	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2022-03-25	2023-03-24
☐ Chamber C: Below 1GHz						
SEMT-1319	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2022-01-07	2023-01-06
SEMT-1343	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2021-05-28	2023-05-27
SEMT-1333	Amplifier	HP	8447F	2944A03869	2022-03-21	2023-03-20
☐ Conducted Room 1#						
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2022-03-21	2023-03-20
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2022-03-25	2023-03-24
SEMT-1003	AC LISN	Schwarz beck	NSLK8126	8126-224	2022-03-21	2023-03-20
☐ Conducted Room 2#						
SEMT-1334	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2022-03-21	2023-03-20

Reference No.: WTX22X03047982W

SEMT-1336	LISN	Rohde & Schwarz	ENV 216	100097	2022-03-21	2023-03-20
-----------	------	-----------------	---------	--------	------------	------------

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
Part 15.203 of the FCC Rules	Antenna Requirement	Compliant
Part 15.205 of the FCC Rules	Restricted Band of Operation	Compliant
Part 15.207(a) of the FCC Rules	Conducted Emission	N/A
Part 15.209(a)(f) of the FCC Rules	Radiated Spurious Emissions	Compliant
Part 15.249(a) of the FCC Rules	Field Strength of Emissions	Compliant
Part 15.249(d) of the FCC Rules	Out of Band Emission	Compliant
Part 15.215(c) of the FCC Rules	Emission Bandwidth	Compliant

N/A: Not applicable.

3. Antenna Requirements

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a Fixed 33mm-long Wire Antenna, fulfill the requirement of this section.

4. Radiated Emissions

4.1 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of Harmonics (micro-volts/meter)
902-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


4.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle.

The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency:9kHz-30MHz
RBW=10kHz
VBW=30kHz
Sweep time=Auto
Trace=max hold
Detector function=peak

Frequency:30MHz-1GHz
RBW=120kHz
VBW=300kHz
Sweep time=Auto
Trace=max hold
Detector function=peak, QP

Frequency:Above 1GHz
RBW=1MHz
VBW=3MHz(Peak), 10Hz(AV)
Sweep time=Auto
Trace=max hold
Detector function=peak, AV

4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit of Part 15.249 of the FCC Rules}$$

4.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


➤ Spurious Emissions Below 1GHz

Test Channel	Lowest Channel	Polarity:	Horizontal
--------------	----------------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	30.6379	34.58	-9.30	25.28	40.00	-14.72	-	-	peak
2	51.6616	27.43	-7.20	20.23	40.00	-19.77	-	-	peak
3	99.1797	27.63	-8.88	18.75	43.50	-24.75	-	-	peak
4	212.2695	25.16	-9.37	15.79	43.50	-27.71	-	-	peak
5	375.9385	26.50	-4.61	21.89	46.00	-24.11	-	-	peak
6	620.7096	27.95	0.60	28.55	46.00	-17.45	-	-	peak

Test Channel	Lowest Channel	Polarity:	Vertical
--------------	----------------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	36.3814	26.78	-7.88	18.90	40.00	-21.10	-	-	peak
2	52.9453	25.91	-7.39	18.52	40.00	-21.48	-	-	peak
3	112.1305	25.89	-9.02	16.87	43.50	-26.63	-	-	peak
4	279.0436	25.42	-7.52	17.90	46.00	-28.10	-	-	peak
5	404.6665	26.24	-3.76	22.48	46.00	-23.52	-	-	peak
6	645.1195	27.47	0.87	28.34	46.00	-17.66	-	-	peak

Test Channel	Near Middle Channel	Polarity:	Horizontal
--------------	---------------------	-----------	------------




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	30.6379	34.58	-9.30	25.28	40.00	-14.72	-	-	peak
2	58.6126	26.83	-8.22	18.61	40.00	-21.39	-	-	peak
3	105.2718	28.10	-8.80	19.30	43.50	-24.20	-	-	peak
4	330.1949	27.35	-6.02	21.33	46.00	-24.67	-	-	peak
5	502.9395	28.62	-1.25	27.37	46.00	-18.63	-	-	peak
6	750.1083	28.99	1.76	30.75	46.00	-15.25	-	-	peak

Test Channel	Near Middle Channel	Polarity:	Vertical
--------------	---------------------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	37.9450	28.66	-7.50	21.16	40.00	-18.84	-	-	peak
2	105.2718	28.11	-8.80	19.31	43.50	-24.19	-	-	peak
3	196.5098	25.67	-9.81	15.86	43.50	-27.64	-	-	peak
4	355.4273	26.93	-5.24	21.69	46.00	-24.31	-	-	peak
5	533.8321	28.28	-0.74	27.54	46.00	-18.46	-	-	peak
6	737.0714	28.98	1.67	30.65	46.00	-15.35	-	-	peak

Test Channel	Highest Channel	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	31.7313	31.76	-9.03	22.73	40.00	-17.27	-	-	peak
2	47.4918	26.89	-6.97	19.92	40.00	-20.08	-	-	peak
3	91.8163	26.91	-10.24	16.67	43.50	-26.83	-	-	peak
4	209.3129	25.38	-9.44	15.94	43.50	-27.56	-	-	peak
5	480.5276	26.25	-1.79	24.46	46.00	-21.54	-	-	peak
6	776.8778	27.95	1.94	29.89	46.00	-16.11	-	-	peak

Test Channel	Highest Channel	Polarity:	Vertical
--------------	-----------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	31.9546	30.14	-8.97	21.17	40.00	-18.83	-	-	peak
2	47.1599	27.51	-6.97	20.54	40.00	-19.46	-	-	peak
3	105.2718	28.11	-8.80	19.31	43.50	-24.19	-	-	peak
4	224.5193	26.28	-9.02	17.26	46.00	-28.74	-	-	peak
5	401.8385	27.18	-3.84	23.34	46.00	-22.66	-	-	peak
6	737.0714	28.98	1.67	30.65	46.00	-15.35	-	-	peak

Remark: ‘-’Means’ the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(H/V)	
Lowest Channel-2420MHz							
2420	97.06	-10.66	86.40	114	-27.60	H	PK
2420	96.09	-10.66	85.43	94	-8.57	H	AV
4840	59.76	-6.03	53.73	74	-20.27	H	PK
4840	52.14	-6.03	46.11	54	-7.89	H	AV
7260	49.00	-1.64	47.36	74	-26.64	H	PK
7260	42.15	-1.64	40.51	54	-13.49	H	AV
2420	79.20	-10.66	68.54	114	-45.46	V	PK
2420	78.78	-10.66	68.12	94	-25.88	V	AV
4840	59.52	-6.03	53.49	74	-20.51	V	PK
4840	53.27	-6.03	47.24	54	-6.76	V	AV
7260	44.87	-1.64	43.23	74	-30.77	V	PK
7260	37.19	-1.64	35.55	54	-18.45	V	AV
Near Middle Channel-2441MHz							
2441	95.34	-10.63	84.71	114	-29.29	H	PK
2441	97.62	-10.63	86.99	94	-7.01	H	AV
4882	58.29	-5.90	52.39	74	-21.61	H	PK
4882	53.70	-5.90	47.80	54	-6.20	H	AV
7323	50.83	-1.58	49.25	74	-24.75	H	PK
7323	39.30	-1.58	37.72	54	-16.28	H	AV
2441	79.51	-10.63	68.88	114	-45.12	V	PK
2441	79.08	-10.63	68.45	94	-25.55	V	AV
4882	55.52	-5.90	49.62	74	-24.38	V	PK
4882	54.85	-5.90	48.95	54	-5.05	V	AV
7323	41.22	-1.58	39.64	74	-34.36	V	PK
7323	35.38	-1.58	33.80	54	-20.20	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Highest Channel-2462MHz							
2462	100.97	-10.61	90.36	114	-23.64	H	PK
2462	99.01	-10.61	88.40	94	-5.60	H	AV
4924	61.04	-5.81	55.23	74	-18.77	H	PK
4924	54.52	-5.81	48.71	54	-5.29	H	AV
7386	53.65	-1.52	52.13	74	-21.87	H	PK
7386	44.64	-1.52	43.12	54	-10.88	H	AV
2462	79.53	-10.61	68.92	114	-45.08	V	PK
2462	78.17	-10.61	67.56	94	-26.44	V	AV
4924	61.31	-5.81	55.50	74	-18.50	V	PK
4924	55.09	-5.81	49.28	54	-4.72	V	AV
7386	47.24	-1.52	45.72	74	-28.28	V	PK
7386	36.49	-1.52	34.97	54	-19.03	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz.

5. Out of Band Emissions

5.1 Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure

As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC Rules.


5.3 Summary of Test Results/Plots

Test mode	Frequency	Limit	Result
	(MHz)	(dBuV/dBc)	
Lowest	2310.00	<54dBuV	Pass
	2390.00	<54dBuV	Pass
	2400.00	<54dBuV	Pass
Highest	2483.50	<54dBuV	Pass
	2500.00	<54dBuV	Pass

The edge emissions are below the FCC 15.209 Limits or complies with the 15.249 requirements.


Please refer to the test plots as below:

Test Channel	Lowest Channel	Polarity:	Horizontal (worst case)
--------------	----------------	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	42.72	-10.82	31.90	54.00	-22.10	Ave Detector
	2310.000	53.19	-10.82	42.37	74.00	-31.63	Peak Detector
2	2390.000	42.76	-10.70	32.06	54.00	-21.94	Ave Detector
	2390.000	57.42	-10.70	46.72	74.00	-27.28	Peak Detector
3	2419.920	96.42	-10.66	85.76	/	/	Ave Detector
	2419.560	96.66	-10.66	86.00	/	/	Peak Detector


Test Channel	Highest Channel	Polarity:	Horizontal (worst case)
--------------	-----------------	-----------	-------------------------



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2461.975	99.94	-10.61	89.33	/	/	Ave Detector
	2461.660	99.75	-10.61	89.14	/	/	Peak Detector
2	2483.500	41.87	-10.58	31.29	54.00	-22.71	Ave Detector
	2483.500	60.61	-10.58	50.03	74.00	-23.97	Peak Detector
3	2500.000	41.80	-10.55	31.25	54.00	-22.75	Ave Detector
	2500.000	55.32	-10.55	44.77	74.00	-29.23	Peak Detector


Band edge

Test Channel	Lowest Channel	Polarity:	Horizontal (worst case)
--------------	----------------	-----------	-------------------------



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2400.000	48.17	-10.69	37.48	54.00	-16.52	Peak Detector
2	2419.925	96.50	-10.66	85.84	/	/	Peak Detector

Test Channel	Highest Channel	Polarity:	Horizontal (worst case)
--------------	-----------------	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.930	100.12	-10.61	89.51	/	/	Ave Detector
2	2483.500	48.12	-10.58	37.54	54.00	-16.46	Peak Detector

6. Emission Bandwidth

6.1 Standard Applicable

According to 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2 Test Procedure

According to the ANSI 63.10-2013, the emission bandwidth test method as follows:

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 1MHz, centered on a transmitting channel

RBW $\geq$ 1% 20dB Bandwidth, VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.

6.3 Summary of Test Results/Plots

Test Channel	20dB Bandwidth (MHz)
Lowest Channel	1.18
Near Middle Channel	1.04
Highest Channel	1.12

Please refer to the following test plots:

Lowest Channel	
Near Middle Channel	
Highest Channel	


7. Conducted Emissions

7.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

7.2 Basic Test Setup Block Diagram



7.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150kHz
Stop Frequency	30MHz
Sweep Speed	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth	9kHz
Quasi-Peak Adapter Mode	Normal

7.4 Summary of Test Results/Plots

Not applicable

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****