



Radio Frequency Exposure Evaluation Report

FOR:

Compology, Inc.

Model Name:

Oscar B01

Product Description:

Bluetooth tracking devices

FCC ID: 2AO44-B01

IC ID: 23661-B01

Per:

CFR Part Part1 (1.1307 & 1.1310), Part 2 (2.1091),
FCC KDB 447498 D01 General RF Exposure Guidance v06

ISED RSS-102 Issue 5

Report number: EMC_COMPO-015-20001_FCC_ISSED_MPE

DATE: 2020-02-18



CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: info@cetecom.com ♦ <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

1 Assessment

This RF Exposure evaluation report provides evidence for compliance of the below identified device with the RF Exposure limits for mobile devices as defined in FCC CFR Part 1 (1.1307 & 1.1310), Part 2 (2.1091) and IC standard RSS-102 issue 5 under worst case conditions (measured or rated RF output power, antenna gain, distance towards human body, multiple transmitter information as presented by the applicant).

In addition, maximum antenna gain or minimum distance towards the human body is calculated respectively, where relevant.

The device meets the limits as stipulated by the above given FCC and IC rule parts based on available specifications for worst case conditions at 20cm distance to the body.

Company	Description	Model #
Compology, Inc.	Bluetooth tracking device	Oscar B01

Report reviewed by: TCB Evaluator

Cindy Li

2020-02-18

Compliance

(Lab Manager)

Date	Section	Name	Signature
------	---------	------	-----------

Responsible for the Report:

Issa Ghanma

2020-02-18

Compliance

(EMC Engineer)

Date	Section	Name	Signature
------	---------	------	-----------

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
Lab Manager:	Cindy Li
Responsible Project Leader:	Trina Noor

2.2 Identification of the Client / Manufacturer

Client's Name:	Compology, Inc.
Street Address:	1045 Bryant Street, Suite 101
City/Zip Code	San Francisco, CA 94103
Country	USA

Identification of the Manufacturer

Manufacturer's Name:	AQS
Street Address:	401 Kato Terrace
City/Zip Code	Fremont, CA 94539
Country	USA

3 Equipment under Assessment

Model No:	Oscar B01
HW Version :	Rev_B
SW Version :	Fluffy-B009
Hardware Version Identification Number (HVIN):	Oscar B01
Product Marketing Name (PMN):	Oscar B01
Regulatory Band:	❖ <u>BT-LE:</u> <ul style="list-style-type: none"> Nominal band: 2400 MHz – 2483.5 MHz; Center to center: 2402 MHz (ch 0) – 2480 MHz (ch 39), 40 channels
Integrated Module Info:	❖ <u>BT-LE:</u> <ul style="list-style-type: none"> Module name: INP2045 Module FCC/IC ID: 2AVAL-INP2045/25715-INP2045
Antenna Type:	❖ <u>BT-LE:</u> <ul style="list-style-type: none"> Antenna peak gain: 2.63 dBi
Maximum Conducted Output Power:	❖ <u>BT-LE:</u> 5.53 mW
Power Supply/ Rated Operating Voltage Range:	VBattery: Vmin: 2.8 VDC/ Vnom: 3.67 VDC / Vmax: 3.9 VDC
Operating Temperature Range:	-40 °C to +85 °C
Sample Revision:	<input type="checkbox"/> Prototype Unit; <input checked="" type="checkbox"/> Production Unit; <input type="checkbox"/> Pre-Production

4 RF Exposure Limits and FCC and IC Basic Rules

For the specific described radio apparatus the following basic limits and rules apply for both, FCC and IC where not indicated differently.

4.1 Power Density Limits acc. to FCC 1.1310(e) / RSS-102 i5, cl. 4:

FCC

Frequency Range (MHz)	Power density (mW/cm ²)	Averaging time (minutes)
300 – 1500	$f \text{ (MHz)} / 1500$	30
1500 – 100000	1.0	30

IC

300 – 6000	$0.02619 \times f \text{ (MHz)}^{0.6834}$	6
------------	-------------------------------------------	---

4.2 Routine Environmental Evaluation Categorical Exclusion Limits acc. to FCC 2.1091(c) / RSS-102, cl. 2.5 (rounded to 1 decimal point):

FCC

operating frequency < 1.5GHz: excluded if ERP < 1.5W / 31.8dBm (EIRP: 33.9 dBm);

operating frequency > 1.5GHz: excluded if ERP < 3.0W / 34.8dBm (EIRP: 36.9 dBm);

IC

300MHz <= operating frequency < 6 GHz: excluded if EIRP < $0.0131 \times f \text{ (MHz)}^{0.6834} \text{ W}$

4.3 RF Exposure Estimation (MPE Estimation)

Having available the source based average output power and peak antenna gain or the ERP/EIRP of the specified device and for a known minimum distance of its radiating structures from the body of persons according to its use cases (at least 20cm) the power density at that distance can be estimated by the following formula for plane-wave equivalent conditions (far-field conditions), when ground reflection is neglected.

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (mW/cm² or W/m²)

P = power input to the antenna (mW or W)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm or m)

5 Evaluations

5.1 Analysis of RF Exposure for simultaneous transmission

- Evaluations are based on worst case power density limits for Canada.
- Calculations are made for 20cm.
- Evaluations are based on Pmax and tune-up tolerance from document "B01_8_Output Power Tune-up Information.pdf" provided by customer.

Radio	freq [MHz]	Max Conducted power [W]	Gain [dBi]	Gain [lin]	EIRP [W]	IC Limit [W/m2]	FCC Limit [W/m2]	Actual [W/m2]	How much of limit is used up
BT-LE	2400	0.01585	2.63	1.83	0.029	5.348	10.000	0.05772	1.08%

Note1: The calculation is based on the distance of 20cm

5.2 Conclusion:

The equipment is passing RF exposure requirements for 20cm distance.

6 Revision History

Date	Report Name	Changes to report	Report prepared by
2020-02-18	EMC_COMPO-015-20001_FCC_ISSED_MPE	Initial Release	Issa Ghanma

<<< The End >>>