

RF-EXPOSURE REPORT**FCC 47 CFR Part 2.1091
ISED RSS-102****RF-Exposure evaluation of mobile equipment****Report Reference No.**: G0M-1709-6886-TFC091ME-V01**Testing Laboratory**: Eurofins Product Service GmbHAddress: Storkower Str. 38c
15526 Reichenwalde
Germany**Accreditation**:

FCC Test Firm Designation Number: DE0008

IC Testing Laboratory site: 3470A-2

Applicant's name: Wincor Nixdorf Manufacturing GmbHAddress: Rohrdamm 7, Haus 16
13629 Berlin
GERMANY**Test specification:**Standard: 47 CFR 2.1091
KDB 447498 D01 v06:2015-10-23
RSS-102, Issue 5:2015-03**Equipment under test (EUT):**

Product description	NFC Reader	
Model No.	KIT-NFC-KIOSK	
Additional Model(s)	None	
Brand Name(s)	Wincor Nixdorf	
Hardware version	Rev. A	
Firmware / Software version	01.02	FCC-ID: QRIQFORCE IC: 4708A-QFORCE
Test result	Passed	

Possible test case verdicts:

- neither assessed nor tested: N/N
- required by standard but not appl. to test object.....: N/A
- required by standard but not tested.....: N/T
- not required by standard for the test object: N/R
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

Testing:

Test Lab Temperature: 20 – 23 °C

Test Lab Humidity: 32 – 38 %

Date of receipt of test item: 2017-11-27

Date (s) of assessment: 2018-03-15

Compiled by: Sebastian Suckow

Assessed by (+ signature): Sebastian Suckow
(Responsible for Assessment)



Approved by (+ signature): Toralf Jahn
(Deputy Head of Lab)



Date of issue: 2018-03-15

Total number of pages: 13

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Additional comments:

Version History

Version	Issue Date	Remarks	Revised by
01	2018-03-15	Initial Release	

REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	5
1.1	Standalone Radiation Sources	6
1.2	Test Equipment Used	7
2	RESULT SUMMARY	8
3	RADIATED FIELD MEASUREMENT	9
3.1	Test Conditions and Results – Electric and magnetic field strength	9
4	RF-EXPOSURE CLASSIFICATIONS	10
5	EVALUATION	11
5.1	MPE Evaluation Conditions – 47 CFR 2.1091 / RSS-102	11
5.2	Single-Transmitter Evaluation – 47 CFR 2.1091 / RSS-102	13

1 Equipment (Test item) Description

Description	NFC Reader
Model	KIT-NFC-KIOSK
Additional Model(s)	None
Brand Name(s)	Wincor Nixdorf
Serial number	None
Hardware version	Rev. A
Software / Firmware version	01.02
PMN	Diebold Nixdorf
HVIN	KIT-NFC-KIOSK
FVIN	N/A
HMN	N/A
FCC-ID	QRIQFORCE
IC	4708A-QFORCE
Equipment type	Radio module

1.1 Standalone Radiation Sources

Mode #	Description	
RFID	Frequency range [MHz]	13.553 - 13.567
	Channel spacing	100 kHz
	Modulations	ASK
	Maximum electric field [V/m @ 20cm]	1.30
	Maximum magnetic field [A/m @ 20cm]	0.048

1.2 Test Equipment Used

Field Strength Measurement					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Broadband Field Meter NBM-550	Narda Safety Test Solutions GmbH	2401/01B	EF00998	2017-07	2018-07
Magnetic field probe HF3061	Narda Safety Test Solutions GmbH	2402/05B	EF00999	2017-07	2018-07
EM Radiation Monitor	Narda Safety Test Solutions GmbH	EMR-20	EF00058	2017-09	2018-09

2 Result Summary

FCC 47 CFR Part 2.1091, IC RSS-102			
Product Specific Standard Section	Requirement	Result	Remarks
47 CFR 2.1091	Maximum permissible exposure @ 20cm below limit	PASS	
RSS-102	Maximum permissible exposure @ 20cm below limit	PASS	
Remarks:			

3 Radiated Field Measurement

3.1 Test Conditions and Results – Electric and magnetic field strength

ELECTRIC AND MAGNETIC FIELD STRENGTH									
Test frequency range		Tested frequencies							
		F_{MID}							
EUT test mode		RFID							
Measurement methode		radiated only							
Test procedure									
<ol style="list-style-type: none">1. EUT transmitter is activated in test mode under normal conditions2. The perimeter of the EUT is scanned with an electric and magnetic field probe at a fixed distance3. The electric and magnetic field strength is measured4. The maximum field strength values are recorded									
Test results									
Channel	Frequency [MHz]	Mode	Distance [m]	Max. electric field strength [V/m]	Max. magnetic field strength [A/m]				
F_{MID}	13.56	NFC	0.2	1.30	0.048				
Comments:									

4 RF-Exposure Classifications

Device Types	
Fixed	A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.
Mobile	A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. (47 CFR 2.1091)
Portable	A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. (47 CFR 2.1093)
Exposure Categories	
Occupational / Controlled	Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
General population / uncontrolled	Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

5 Evaluation

5.1 MPE Evaluation Conditions – 47 CFR 2.1091 / RSS-102

MPE EVALUATION ACC. TO 47 CFR 2.1091 / ISED RSS-102		VERDICT: PASS		
Assessment according to reference		Reference Method		
		KDB 447498 D01 / RSS-102 & Safety Code 6		
Device type		mobile		
Exposure category		General public		
ISED Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m ²]	Averaging time [min]
0.003-10*	170	180	-	Instantaneous*
0.1-10	-	1.6 / f	-	6**
1.29-10	193 / $f^{0.5}$	-	-	6**
10-20	61.4	0.163	-10	6
20-48	129.8 / $f^{0.25}$	0.3444 / $f^{0.25}$	44.72 / $f^{0.5}$	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 $f^{0.25}$	0.04138 $f^{0.25}$	0.6455 $f^{0.5}$	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000 / $f^{1.2}$
150000-300000	0.354 $f^{0.5}$	$9.40 \times 10^{-4} f^{0.5}$	$3.33 \times 10^{-4} f$	616000 / $f^{1.2}$
ISED Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m ²]	Averaging time [min]
0.003-10*	83	90	-	Instantaneous*
0.1-10	-	0.73 / f	-	6**
1.1-10	87 / $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07 / $f^{0.25}$	0.1540 / $f^{0.25}$	8.944 / $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000 / $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	$4.21 \times 10^{-4} f^{0.5}$	$6.67 \times 10^{-5} f$	616000 / $f^{1.2}$
* = Based on nerve stimulation				
** = Bases on specific absorption rate				

FCC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm ²]	Averaging time [min]
0.3 – 3.0	614	1.63	(100)*	6
3.0 - 30	1842 / f	4.89 / f	(900 / f ²)*	6
30 - 300	61.4	0.163	1.0	6
300 - 1500	N/A	N/A	f / 300	6
1500 - 100000	N/A	N/A	5.0	6
FCC Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm ²]	Averaging time [min]
0.3 – 1.34	614	1.63	(100)*	30
1.34 - 30	842 / f	2.19 / f	(180 / f ²)*	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	N/A	N/A	f / 1500	30
1500 - 100000	N/A	N/A	1.0	30

* = Plane wave equivalent power density; f in MHz

Assessment procedure
The evaluation is performed at a separation distance of 20 cm. The reference levels are taken from 47 CRF 1.1310 for FCC and RSS-102 for ISED according to the exposure category declared by customer.

For each radio and frequency band the worst case transmission mode with the highest output power is activated and the surrounding area around the EUT is scanned using an electric and a magnetic field probe at the distance given in the test report. The maximum electric and magnetic field strength values measured are compared to the corresponding reference levels. If both measured field strength values are below the reference levels the EUT has passed the RF-Exposure requirements.

5.2 Single-Transmitter Evaluation – 47 CFR 2.1091 / RSS-102

Assessment results – RFID	
Transmission mode	
Operating mode frequency range [MHz]	13.553 - 13.567
Assessment frequency (f) [MHz]	13.56
Compliance separation distance to EUT [m]	0.2
Electric Field	
Measured max. electric field strength [V/m]	1.30
Reference level [V/m]	27.46
Verdict	PASS
Magnetic Field	
Measured max. magnetic field strength [A/m]	0.047
Reference level [A/m]	0.0728
Verdict	PASS
Verdict	
The field strength level of the EUT are below the RF-Exposure reference level at the given compliance separation distance!	
Comments: ISED Limits used as worst case	