


Prüfbericht-Nr.: Test report no.:	60408756 001	Auftrags-Nr.: Order no.:	244242523	Seite 1 von 87 Page 1 of 87
Kunden-Referenz-Nr.: Client reference no.:	244061385	Auftragsdatum: Order date:	2020-06-02	
Auftraggeber: Client:	Bosch Sensortec GmbH Gerhard-Kindler-Strasse 9, 72770 Reutlingen, Germany			
Prüfgegenstand: Test item:	Application Board 3.0			
Bezeichnung / Typ-Nr.: Identification / Type no.:	APP 3.0 FCC ID: 2AO4I-APP30 IC: 26413-APP30			
Auftrags-Inhalt: Order content:	Complete test			
Prüfgrundlage: Test specification:	FCC CFR47 Part 15, Subpart C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02 RSS-Gen Issue 5, Amendment 1, March 2019 RSS-247 Issue 2, February 2017 ANSI C63.10: 2013			
Wareneingangsdatum: Date of sample receipt:	2020-06-05			
Prüfmuster-Nr.: Test sample no.:	A002888420-001			
Prüfzeitraum: Testing period:	Refer to test report			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
überprüft von: reviewed by:	genehmigt von: authorized by:			
Datum: 2021-03-03 Date:	Datum: 2021-03-03 Date:			
Stellung / Position:	Hongfei Wu / PE	Stellung / Position:	Elliot Zhang / Reviewer	
Sonstiges / Other:	HVIN: APP 3.0			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.				

V05

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 6dB & 99% BANDWIDTH

RESULT: Pass

5.1.3 PEAK OUTPUT POWER

RESULT: Pass

5.1.4 POWER SPECTRAL DENSITY

RESULT: Pass

5.1.5 CONDUCTED BAND EDGE AND OUT-OF BAND EMISSIONS

RESULT: Pass

5.2.1 CONDUCTED EMISSION

RESULT: Pass

5.3.1 RADIATED BAND-EDGE

RESULT: Pass

5.3.2 RADIATED SPURIOUS EMISSION

RESULT: Pass

Contents

1.	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS.....	4
2.	TEST SITES	4
2.1	TEST FACILITIES	4
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	5
2.3	TRACEABILITY	5
2.4	CALIBRATION	5
2.5	MEASUREMENT UNCERTAINTY	6
3.	GENERAL PRODUCT INFORMATION.....	7
3.1	PRODUCT FUNCTION AND INTENDED USE	7
3.2	RATINGS AND SYSTEM DETAILS.....	7
3.3	INDEPENDENT OPERATION MODES.....	8
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	8
3.5	SUBMITTED DOCUMENTS.....	8
4.	TEST SET-UP AND OPERATION MODES.....	9
4.1	PRINCIPLE OF CONFIGURATION SELECTION	9
4.2	TEST OPERATION AND TEST SOFTWARE.....	9
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	9
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	10
5.	TEST RESULTS	11
5.1	CONDUCTED TESTING AT ANTENNA PORT	11
5.1.1	<i>Antenna Requirement.....</i>	<i>11</i>
5.1.2	<i>6dB & 99% Bandwidth.....</i>	<i>13</i>
5.1.3	<i>Peak Output Power</i>	<i>18</i>
5.1.4	<i>Power Spectral Density</i>	<i>19</i>
5.1.5	<i>Conducted Band Edge and out-of Band Emissions.....</i>	<i>22</i>
5.2	EMISSION IN THE FREQUENCY RANGE UP TO 30MHZ.....	29
5.2.1	<i>Conducted Emission.....</i>	<i>29</i>
5.3	EMISSION IN THE FREQUENCY RANGE ABOVE 30MHZ	32
5.3.1	<i>Radiated Band-Edge</i>	<i>32</i>
5.3.2	<i>Radiated Spurious Emission.....</i>	<i>37</i>
6.	LIST OF TABLES	86
7.	LIST OF FIGURES	86

1. General Remarks

1.1 Complementary Materials

Null.

2. Test Sites

2.1 Test Facilities

TÜV Rheinland (Shanghai) Co., Ltd.

Shanghai TUV Rheinland Building No. 177, 178 Lane 777, West Guangzhong Rd, Jing'an District, Shanghai, China

The used test equipment is in accordance with CISPR 16 for measurement of radio interference.

The Federal Communications Commission has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance with the requirements of section 2.948 of the FCC rules. The description of the test facility is listed under FCC registration number 958801.

The Innovation, Science and Economic Development Canada has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance. The description of the test facility is listed under chambers filing number 2932F.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Due Date
3m Anechoic Chamber	Frankonia	SAC3	FJ129002	2022-05-13
EMI Test Receiver	R&S	ESCI	100280	2020-10-31
Spectrum Analyzer	R&S	FSV40	101258	2021-10-31
BiLog Antenna	Teseq	CBL 6112D	40530	2021-02-13
Log-periodic Antenna	R&S	HL050	100692	2021-02-16
Preamplifier	Taiwan EMC Instruments Corporation	EMC051845SE	980612	2021-03-05
Broadband Horn Antenna	Schwarzbeck	BBHA 9170	9170-305	2021-07-09
Preamplifier	Taiwan EMC Instruments Corporation	EMC184045SE	980596	2021-03-05
Spectrum Analyzer	Keysight	N9020A	MY54500180	2021-05-09
DC Power Supply	ALLPOWER	ADC50-20	99223	2020-10-12
Thermohygrometer	Testo	608-H1	1241320614	2020-10-13
EMI test receiver	R&S	ESIB26	G1811380	2021-03-06
Artificial main network	R&S	ENV432	G1830003	2020-11-01
EMC measurement software	R&S	EMC32	G1824845	N/A

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

Table 2: Measurement Uncertainty

Measurement Type	Frequency	Uncertainty
Antenna Port Conducted Emission	< 1GHz	±0.39dB
	> 1GHz	±0.68dB
Radiated Emission	9kHz – 30MHz	±2.93dB
	30MHz - 1GHz	±5.34dB
	> 1GHz	±5.40dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT (Equipment Under Test) is an application board which contains Bluetooth module.

For details refer to the User Manual and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Description of EUT	
Product Name:	Application Board 3.0
Model No.:	APP 3.0
Operation Voltage:	DC 5V (USB)
Technical Specification of Bluetooth LE 5.0	
Frequency Range:	2402 – 2480MHz
Modulation Type:	GFSK
Data Rate:	1Mb/s, 2Mb/s, 500kb/s, 125kb/s
Antenna Type:	PIFA Antenna
Antenna Gain:	2 dBi

3.3 Independent Operation Modes

Table 4: Independent Operation Modes

Test Mode	Channel	Frequency	Data Rate	Power Setting
TM1	00	2402	1 MB/s	0
TM2	19	2440	1 MB/s	0
TM3	39	2480	1 MB/s	0
TM4	00	2402	2 MB/s	0
TM5	19	2440	2 MB/s	0
TM6	39	2480	2 MB/s	0
TM7	00	2402	500 kB/s	0
TM8	19	2440	500 kB/s	0
TM9	39	2480	500 kB/s	0
TM10	00	2402	125 kB/s	0
TM11	19	2440	125 kB/s	0
TM12	39	2480	125 kB/s	0
TM13	Normal Operating Mode			

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Bill of Material
- PCB Layout
- Photo Document
- Circuit Diagram
- Instruction Manual
- Rating Label

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured at its power output according to Clause 4.2. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

Test software: SecureCRT

Table 5: Power parameter value

Data Rate	Channel Frequency [MHz]	Power Parameter Value	Data Rate	Channel Frequency [MHz]	Power Parameter Value
1 MB/s	2402	0	500 kB/s	2402	0
	2440	0		2440	0
	2480	0		2480	0
2 MB/s	2402	0	125 kB/s	2402	0
	2440	0		2440	0
	2480	0		2480	0

4.3 Special Accessories and Auxiliary Equipment

Table 6: Auxiliary Equipment

Product Name	Model Name	Manufactory
Shuttle Board	BMI088	BOSCH
Laptop	T450	Thinkpad

Note: Above auxiliary equipment was used for Conducted Emission test.

Prüfbericht - Nr.: 60408756 001
*Test Report No.***Seite 10 von 87**
Page 10 of 87

4.4 Countermeasures to achieve EMC Compliance

Null.

5. Test Results

5.1 Conducted Testing at Antenna Port

5.1.1 Antenna Requirement

RESULT:**Pass**

According to the manufacturer declared, the EUT has one PIFA antenna, the directional gain of antenna is 2dBi and the antenna is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Table 7: Antenna Requirement**FCC 15.203 – Antenna Requirement 1**

Requirement: No antenna other than that furnished by the responsible party shall be used with the device

Results: Antenna type: PIFA antenna

Verdict: Pass

FCC 15.204 – Antenna Requirement 2

Requirement: An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.

Results: Only one integral antenna can be used

Verdict: Pass

RSS-Gen 6.4 – External Controls

Requirement: The device shall not have any external controls accessible to the user that enable it to be adjusted, selected or programmed to operate in violation of the regulatory requirements, including RSS-Gen and the applicable RSSs.

Results: The device does not have any external controls accessible to the user that enable it to be adjusted, selected or programmed to operate in violation of the regulatory requirements, including RSS-Gen and the applicable RSSs.

Verdict: Pass

RSS-Gen 6.8 – Antenna Requirement

Requirement: When measurements at the antenna port are used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

Results:

a) Antenna type:	PIFA
b) Manufacture:	N/A
c) Model No.:	N/A
d) Gain with reference to an isotropic radiator:	2dBi

Verdict: Pass

5.1.2 6dB & 99% Bandwidth

RESULT:

Pass


Date of testing	: 2020-09-28
Ambient temperature	: 20.6°C
Relative humidity	: 58.6%
Atmospheric pressure	: 101kPa
Test requirement	: FCC Part 15.247(a)(2) RSS-247 Issue 2, February 2017, Clause 5.2(a)
Test procedure	: KDB 558074 D01v05r02 ANSI C63.10: 2013
Test voltage	: DC 5V
Test modes applied	: TM1 to TM12


Table 8: 6dB & 99% Bandwidth

Test Mode	CH.	Freq. [MHz]	6dB Bandwidth [kHz]	6dB Bandwidth Limit [kHz]	99% Bandwidth [MHz]
TM1	00	2402	733.2	≥ 500	1.0745
TM2	19	2440	741.7	≥ 500	1.0769
TM3	39	2480	720.2	≥ 500	1.0862
TM4	00	2402	1360.0	≥ 500	2.0903
TM5	19	2440	1310.0	≥ 500	2.1061
TM6	39	2480	1320.0	≥ 500	2.1039
TM7	00	2402	748.1	≥ 500	1.0572
TM8	19	2440	723.1	≥ 500	1.0586
TM9	39	2480	735.1	≥ 500	1.0758
TM10	00	2402	697.6	≥ 500	1.0875
TM11	19	2440	654.1	≥ 500	1.0897
TM12	39	2480	699.5	≥ 500	1.0948

Figure 1: 6dB Bandwidth




Figure 2: 99% Bandwidth




EIRP=Peak Conducted Output Power + Antenna Gain


5.1.4 Power Spectral Density


RESULT:**Pass**

Date of testing : 2020-09-28
Ambient temperature : 21.4°C
Relative humidity : 56.1%
Atmospheric pressure : 101kPa
Test requirement : FCC Part 15.247(e)
RSS-247 Issue 2, February 2017, Clause 5.2(b)
Test procedure : KDB 558074 D01v05r02
ANSI C63.10: 2013
Test voltage : DC 5V
Test modes applied : TM1 to TM12

Table 10: Power Spectral Density

Mode	CH.	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]
TM1	00	2402	-13.172	8
TM2	19	2440	-11.678	8
TM3	39	2480	-12.675	8
TM4	00	2402	-16.050	8
TM5	19	2440	-15.339	8
TM6	39	2480	-15.221	8
TM7	00	2402	-6.509	8
TM8	19	2440	-6.445	8
TM9	39	2480	-6.431	8
TM10	00	2402	-6.410	8
TM11	19	2440	-6.336	8
TM12	39	2480	-6.285	8

Figure 3: Power Spectral Density





Prüfbericht - Nr.: 60408756 001
Test Report No.**Seite 22 von 87**
Page 22 of 87

5.1.5 Conducted Band Edge and out-of Band Emissions

RESULT:**Pass**

Date of testing	: 2020-09-28
Ambient temperature	: 21.4°C
Relative humidity	: 56.1%
Atmospheric pressure	: 101kPa
Test requirement	: FCC Part 15.247(d) RSS-247 Issue 2, February 2017, Clause 5.5
Test procedure	: KDB 558074 D01v05r02 ANSI C63.10: 2013
Test voltage	: DC 5V
Test modes applied	: TM1 to TM12

Figure 4: Reference level





Figure 5: Conducted Spurious Emission
