


Prüfbericht-Nr.: Test report no.:	CN23QK66 001	Auftrags-Nr.: Order no.:	244512362	Seite 1 von 80 Page 1 of 80
Kunden-Referenz-Nr.: Client reference no.:	/	Auftragsdatum: Order date:	2023-05-04	
Auftraggeber: Client:	Bosch Sensortec GmbH Gerhard-Kindler-Strasse 9, 72770 Reutlingen, Germany			
Prüfgegenstand: Test item:	Application Board 3.1			
Bezeichnung / Typ-Nr.: Identification / Type no.:	APP 3.1 FCC ID: 2AO4I-APP31 IC: 26413-APP31			
Auftrags-Inhalt: Order content:	Complete test			
Prüfgrundlage: Test specification:	FCC CFR47 Part 15, Subpart C Section 15.247 RSS-Gen Issue 5, Amendment 2, February 2021 RSS-247 Issue 3, August 2023 ANSI C63.10: 2013			
Wareneingangsdatum: Date of sample receipt:	2023-04-27			
Prüfmuster-Nr.: Test sample no.:	A003464626-009			
Prüfzeitraum: Testing period:	Refer to test report			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	<i>Hongfei Wu</i>		genehmigt von: authorized by:	<i>Elliot Zhang</i>
Datum: Date:	2023-08-10		Ausstellungsdatum: Issue date:	2023-08-10
Stellung / Position:	PE/Hongfei Wu		Stellung / Position:	Reviewer/Elliot Zhang
Sonstiges / Other:	HVIN: APP 3.1			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN23QK66 001
Test report no.:

Seite 2 von 80
Page 2 of 80

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 6dB & 99% BANDWIDTH

RESULT: Pass

5.1.3 OUTPUT POWER

RESULT: Pass

5.1.4 POWER SPECTRAL DENSITY

RESULT: Pass

5.1.5 CONDUCTED BAND EDGE AND OUT-OF BAND EMISSIONS

RESULT: Pass

5.2.1 CONDUCTED EMISSION

RESULT: Pass

5.3.1 RADIATED BAND-EDGE

RESULT: Pass

5.3.2 RADIATED SPURIOUS EMISSION

RESULT: Pass

Contents

1.	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS.....	5
2.	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY	7
3.	GENERAL PRODUCT INFORMATION.....	8
3.1	PRODUCT FUNCTION AND INTENDED USE	8
3.2	RATINGS AND SYSTEM DETAILS.....	8
3.3	INDEPENDENT OPERATION MODES.....	9
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	9
4.	TEST SET-UP AND OPERATION MODES.....	10
4.1	PRINCIPLE OF CONFIGURATION SELECTION	10
4.2	TEST OPERATION AND TEST SOFTWARE.....	10
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	10
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	10
5.	TEST RESULTS	11
5.1	CONDUCTED TESTING AT ANTENNA PORT	11
5.1.1	<i>Antenna Requirement.....</i>	<i>11</i>
5.1.2	<i>6dB & 99% Bandwidth.....</i>	<i>13</i>
5.1.3	<i>Output Power</i>	<i>38</i>
5.1.4	<i>Power Spectral Density</i>	<i>39</i>
5.1.5	<i>Conducted Band Edge and out-of Band Emissions.....</i>	<i>52</i>
5.2	EMISSION IN THE FREQUENCY RANGE UP TO 30MHz.....	59
5.2.1	<i>Conducted Emission.....</i>	<i>59</i>
5.3	EMISSION IN THE FREQUENCY RANGE ABOVE 30MHz	62
5.3.1	<i>Radiated Band-Edge</i>	<i>62</i>
5.3.2	<i>Radiated Spurious Emission.....</i>	<i>67</i>
6.	LIST OF TABLES	80
7.	LIST OF FIGURES	80

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

2. Test Sites

2.1 Test Facilities

TÜV Rheinland (Shanghai) Co., Ltd.
 Shanghai TUV Rheinland Building No. 177, 178 Lane 777, West Guangzhong Rd, Jing'an District, Shanghai, China

The used test equipment is in accordance with CISPR 16 for measurement of radio interference.

The Federal Communications Commission has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance with the requirements of section 2.948 of the FCC rules. The description of the test facility is listed under FCC registration number 958801.

The Innovation, Science and Economic Development Canada has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance. The description of the test facility is listed under chambers filing number 2932F.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Equip.	Description	Model	Manufacturer	Due Date DD.MM.YYYY
G1811378	3m modified semi-anechoic chamber	SAC3	Frankonia	09.06.2024
EMC-C-204	Trilog broadband antenna	VULB 9163	Schwarzbeck	15.08.2025
G1825371	Preamplifier	EMC051845SE	Taiwan EMC Instruments Corporation	14.05.2024
G1825372	Preamplifier	EMC184045SE	Taiwan EMC Instruments Corporation	14.05.2024
G1822694	Broadband horn antenna	BBHA 9120 D	Schwarzbeck	23.03.2026
G1831065	Broadband horn antenna	BBHA 9170	Schwarzbeck	09.07.2023
G1822702	Spectrum analyser	FSV40	Rohde & Schwarz	04.11.2023
G1811391	EMI test receiver	ESCI	Rohde & Schwarz	29.09.2023
9023229	EMI test receiver	ESR3	Rohde&Schwarz	11.08.2023
G1811403	Artificial mains network	ENV216	Rohde&Schwarz	19.10.2023
software				
	EMC measurement software	EMC32 (Ver 10.20.01)	Rohde&Schwarz	NA
	EMC measurement software	EMC32 (Ver 11.40.00)	Rohde&Schwarz	NA

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

Table 2: Measurement Uncertainty

Measurement Type	Frequency	Uncertainty
Antenna Port Conducted Emission	< 1GHz	±0.39dB
	> 1GHz	±0.68dB
Conducted Emission	150kHz - 30MHz	±3.39dB
Radiated Emission	9kHz - 30MHz	±2.93dB
	30MHz - 1GHz	±5.34dB
	> 1GHz	±5.40dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT (Equipment Under Test) is an application board which contains Bluetooth module.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Description of EUT	
Product Name:	Application Board 3.1
Model No.:	APP 3.1
Operation Voltage:	DC 5V (USB)
Technical Specification of Bluetooth LE 5.0	
Frequency Range:	2402 – 2480MHz
Modulation Type:	GFSK
Data Rate:	1Mb/s, 2Mb/s, 500kb/s, 125kb/s
Antenna Type:	PCB Antenna
Antenna Gain:	2 dBi

Table 4: Operation Channel List

RF Channel	Frequency [MHz]	RF Channel	Frequency [MHz]	RF Channel	Frequency [MHz]	RF Channel	Frequency [MHz]
00	2402	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	19	2440	29	2460	39	2480

Test frequencies are lowest channel: 2402 MHz, middle channel: 2440 MHz and highest channel: 2480 MHz

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Bluetooth transmitting mode
- B. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

Test Software used: SecureCRT

Table 5: Power parameter value

Channel Frequency [MHz]	Power Parameter Value
2402	8
2440	8
2480	8

4.3 Special Accessories and Auxiliary Equipment

Table 6: Auxiliary Equipment

Equipment	Manufacturer	Model
Laptop	Lenovo	T14

4.4 Countermeasures to achieve EMC Compliance

Null.

5. Test Results

5.1 Conducted Testing at Antenna Port

5.1.1 Antenna Requirement

RESULT:**Pass**

According to the manufacturer declared, the EUT has one PCB antenna, the directional gain of antenna is 2 dBi and the antenna is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Table 7: Antenna Requirement

FCC 15.203 – Antenna Requirement 1	
Requirement:	No antenna other than that furnished by the responsible party shall be used with the device
Results:	Antenna type: PCB antenna
Verdict:	Pass

FCC 15.204 – Antenna Requirement 2	
Requirement:	An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.
Results:	Only one PCB antenna can be used
Verdict:	Pass

RSS-Gen 6.4 – External Control	
Requirement:	The device shall not have any external controls accessible to the user that enable it to be adjusted, selected or programmed to operate in violation of the regulatory requirements, including RSS-Gen and the applicable RSSs
Results:	The device does not have any transmitter external controls accessible to the user that can be adjusted and operated in violation of the limits of this standard.
Verdict:	PASS

Prüfbericht - Nr.: CN23QK66 001
Test Report No.**Seite 12 von 80**
Page 12 of 80**RSS-Gen 6.8 – Antenna Requirement**

Requirement: When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

Results:

a) Antenna Type:	PCB Antenna
b) Manufacture:	N/A
c) Model No.:	N/A
d) Gain with reference to an isotropic radiator:	2 dBi

Verdict: PASS

5.1.2 6dB & 99% Bandwidth**RESULT:****Pass**

Date of testing	:	2023-06-02
Ambient temperature	:	24.8°C
Relative humidity	:	52.2%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(a)(2) RSS-247 Issue 3, August 2023, Clause 5.2(a)
Test procedure	:	ANSI C63.10: 2013
Test voltage	:	DC 5V
Test modes applied	:	A


6dB Bandwidth, 1Mbps, 2402MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.752476	0.500000	---	2401.623762	2402.376238

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2402.000000	6.3	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
Sweeptime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	13 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.01 dB	0.50 dB


6dB Bandwidth, 1Mbps, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	0.772278	0.500000	---	2439.623762	2440.396040

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2440.000000	5.7	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43900 GHz	2.43900 GHz
Stop Frequency	2.44100 GHz	2.44100 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
SweepTime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	9 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.10 dB	0.50 dB


6dB Bandwidth, 1Mbps, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.752476	0.500000	---	2479.623762	2480.376238

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2480.000000	6.8	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
SweepTime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	10 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.02 dB	0.50 dB


6dB Bandwidth, 2Mbps, 2402MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.267326	0.500000	---	2401.366337	2402.633663

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2402.000000	5.0	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.40400 GHz	2.40400 GHz
Span	4.000 MHz	4.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 80
SweepTime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.37 dB	0.50 dB


6dB Bandwidth, 2Mbps, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	1.227722	0.500000	---	2439.405941	2440.633663

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2440.000000	5.1	PASS

6 dB Bandwidth



Setting	Instrument Value	Target Value
Start Frequency	2.43800 GHz	2.43800 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	4.000 MHz	4.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 80
SweepTime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	11 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.00 dB	0.50 dB


6dB Bandwidth, 2Mbps, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.386138	0.500000	---	2479.287129	2480.673267

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2480.000000	5.5	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47800 GHz	2.47800 GHz
Stop Frequency	2.48200 GHz	2.48200 GHz
Span	4.000 MHz	4.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 80
SweepTime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	11 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.28 dB	0.50 dB


6dB Bandwidth, 125kbps, 2402MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.752476	0.500000	---	2401.623762	2402.376238

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2402.000000	3.1	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
SweepTime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	7 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.12 dB	0.50 dB


6dB Bandwidth, 125kbps, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	0.752476	0.500000	---	2439.623762	2440.376238

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2440.000000	3.1	PASS

6 dB Bandwidth



Setting	Instrument Value	Target Value
Start Frequency	2.43900 GHz	2.43900 GHz
Stop Frequency	2.44100 GHz	2.44100 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
Sweeptime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	6 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.11 dB	0.50 dB


6dB Bandwidth, 125kbps, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.693070	0.500000	---	2479.663366	2480.356436

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2480.000000	5.0	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
SweepTime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	7 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.02 dB	0.50 dB


6dB Bandwidth, 500kbps, 2402MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.752476	0.500000	---	2401.623762	2402.376238

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2402.000000	6.2	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
SweepTime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.06 dB	0.50 dB


6dB Bandwidth, 500kbps, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	0.732674	0.500000	---	2439.643564	2440.376238

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2440.000000	6.2	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43900 GHz	2.43900 GHz
Stop Frequency	2.44100 GHz	2.44100 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
Sweeptime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	7 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.06 dB	0.50 dB


6dB Bandwidth, 500kbps, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.732674	0.500000	---	2479.643564	2480.376238

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2480.000000	6.6	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
SweepTime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	13 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.00 dB	0.50 dB


99% Occupied Channel Bandwidth, 1Mbps, 2402MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.075000	---	---	2401.457500	2402.532500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2402.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	10 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.16 dB	0.30 dB


99% Occupied Channel Bandwidth, 1Mbps, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	1.065000	---	---	2439.457500	2440.522500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2440.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43900 GHz	2.43900 GHz
Stop Frequency	2.44100 GHz	2.44100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	8 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.09 dB	0.30 dB


99% Occupied Channel Bandwidth, 1Mbps, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.075000	---	---	2479.467500	2480.542500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2480.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	10 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.11 dB	0.30 dB


99% Occupied Channel Bandwidth, 2Mbps, 2402MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	2.090000	---	---	2400.945000	2403.035000

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2402.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.40400 GHz	2.40400 GHz
Span	4.000 MHz	4.000 MHz
RBW	20.000 kHz	>= 20.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	400	~ 400
SweepTime	94.824 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	9 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.14 dB	0.30 dB


99% Occupied Channel Bandwidth, 2Mbps, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	2.070000	---	---	2438.955000	2441.025000

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2440.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43800 GHz	2.43800 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	4.000 MHz	4.000 MHz
RBW	20.000 kHz	>= 20.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	400	~ 400
SweepTime	94.824 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	9 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.21 dB	0.30 dB


99% Occupied Channel Bandwidth, 2Mbps, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	2.100000	---	---	2478.935000	2481.035000

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2480.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47800 GHz	2.47800 GHz
Stop Frequency	2.48200 GHz	2.48200 GHz
Span	4.000 MHz	4.000 MHz
RBW	20.000 kHz	>= 20.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	400	~ 400
SweepTime	94.824 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	11 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.17 dB	0.30 dB


99% Occupied Channel Bandwidth, 125kbps, 2402MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.080000	---	---	2401.462500	2402.542500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2402.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	8 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.19 dB	0.30 dB


99% Occupied Channel Bandwidth, 125kbps, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.080000	---	---	2401.462500	2402.542500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2402.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	8 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.19 dB	0.30 dB


99% Occupied Channel Bandwidth, 125kbps, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.085000	---	---	2479.462500	2480.547500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2480.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	10 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.15 dB	0.30 dB


99% Occupied Channel Bandwidth, 500kbps, 2402MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.045000	---	---	2401.482500	2402.527500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2402.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	8 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.24 dB	0.30 dB


99% Occupied Channel Bandwidth, 500kbps, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	1.045000	---	---	2439.482500	2440.527500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2440.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43900 GHz	2.43900 GHz
Stop Frequency	2.44100 GHz	2.44100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	8 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.30 dB	0.30 dB


99% Occupied Channel Bandwidth, 500kbps, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.045000	---	---	2479.482500	2480.527500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2480.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	6 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.15 dB	0.30 dB

5.1.3 Output Power

RESULT:

Pass

Date of testing	:	2023-06-02
Ambient temperature	:	24.8°C
Relative humidity	:	52.2%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(b)(3) RSS-247 Issue 3, August 2023, Clause 5.4(d)
Test procedure	:	ANSI C63.10: 2013
Test voltage	:	DC 5V
Test modes applied	:	A

Table 8: Peak Output Power

Data Rate	Frequency [MHz]	Peak Conducted Output Power [dBm]	Limit [dBm]
1Mbps	2402	6.83	30
	2440	7.05	30
	2480	7.22	30
2Mbps	2402	6.79	30
	2440	7.00	30
	2480	7.19	30
125kbps	2402	6.81	30
	2440	7.03	30
	2480	7.21	30
500kbps	2402	6.81	30
	2440	7.02	30
	2480	7.20	30

Note:

1. The cable loss=0.5dB was provided by the client, and was factored in the result Conducted Output Power
2. EIRP=Conducted Output Power + Antenna Gain (2dBi), which is far below the 4 W (36dBm).

5.1.4 Power Spectral Density


RESULT:**Pass**

Date of testing	:	2023-06-02
Ambient temperature	:	24.8°C
Relative humidity	:	52.2%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(e) RSS-247 Issue 3, August 2023, Clause 5.2(b)
Test procedure	:	ANSI C63.10: 2013
Test voltage	:	DC 5V
Test modes applied	:	A

Power Spectral Density, 1Mbps, 2402MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2402.000000	2402.062429	0.271	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40144 GHz	2.40144 GHz
Stop Frequency	2.40256 GHz	2.40256 GHz
Span	1.129 MHz	1.129 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	226	~ 226
SweepTime	1.130 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	5 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.16 dB	0.50 dB

Power Spectral Density, 1Mbps, 2440MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2440.000000	2440.062415	0.344	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43942 GHz	2.43942 GHz
Stop Frequency	2.44058 GHz	2.44058 GHz
Span	1.158 MHz	1.158 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	232	~ 232
SweepTime	1.160 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	6 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.14 dB	0.50 dB

Power Spectral Density, 1Mbps, 2480MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2480.000000	2480.062429	-0.754	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47944 GHz	2.47944 GHz
Stop Frequency	2.48056 GHz	2.48056 GHz
Span	1.129 MHz	1.129 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	226	~ 226
SweepTime	1.130 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	7 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.20 dB	0.50 dB

Power Spectral Density, 2Mbps, 2402MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2402.000000	2401.972486	-4.766	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40105 GHz	2.40105 GHz
Stop Frequency	2.40295 GHz	2.40295 GHz
Span	1.901 MHz	1.901 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	380	~ 380
SweepTime	1.910 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.24 dB	0.50 dB

Power Spectral Density, 2Mbps, 2440MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2440.000000	2440.122605	-4.188	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43908 GHz	2.43908 GHz
Stop Frequency	2.44092 GHz	2.44092 GHz
Span	1.842 MHz	1.842 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	368	~ 368
SweepTime	1.850 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	5 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.20 dB	0.50 dB

Power Spectral Density, 2Mbps, 2480MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2480.000000	2480.122453	-3.250	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47896 GHz	2.47896 GHz
Stop Frequency	2.48104 GHz	2.48104 GHz
Span	2.079 MHz	2.079 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	416	~ 416
SweepTime	2.080 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.28 dB	0.50 dB

Power Spectral Density, 125kbps, 2402MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2402.000000	2402.252213	0.451	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40144 GHz	2.40144 GHz
Stop Frequency	2.40256 GHz	2.40256 GHz
Span	1.129 MHz	1.129 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	226	~ 226
SweepTime	1.130 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	10 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.38 dB	0.50 dB

Power Spectral Density, 125kbps, 2440MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2440.000000	2439.752782	0.545	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43944 GHz	2.43944 GHz
Stop Frequency	2.44056 GHz	2.44056 GHz
Span	1.129 MHz	1.129 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	226	~ 226
SweepTime	1.130 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	6 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.30 dB	0.50 dB

Power Spectral Density, 125kbps, 2480MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2480.000000	2479.752594	0.866	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47948 GHz	2.47948 GHz
Stop Frequency	2.48052 GHz	2.48052 GHz
Span	1.040 MHz	1.040 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	208	~ 208
SweepTime	1.040 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	8 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.05 dB	0.50 dB

Power Spectral Density, 500kbps, 2402MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2402.000000	2401.752782	0.397	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40144 GHz	2.40144 GHz
Stop Frequency	2.40256 GHz	2.40256 GHz
Span	1.129 MHz	1.129 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	226	~ 226
SweepTime	1.130 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	9 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.19 dB	0.50 dB

Power Spectral Density, 500kbps, 2440MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2440.000000	2439.752723	0.445	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43945 GHz	2.43945 GHz
Stop Frequency	2.44055 GHz	2.44055 GHz
Span	1.099 MHz	1.099 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	220	~ 220
SweepTime	1.100 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	5 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.34 dB	0.50 dB

Power Spectral Density, 500kbps, 2480MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2480.000000	2479.752723	0.779	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47945 GHz	2.47945 GHz
Stop Frequency	2.48055 GHz	2.48055 GHz
Span	1.099 MHz	1.099 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	220	~ 220
SweepTime	1.100 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	5 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.18 dB	0.50 dB

5.1.5 Conducted Band Edge and out-of Band Emissions

RESULT:**Pass**

Date of testing	:	2023-06-02
Ambient temperature	:	24.8°C
Relative humidity	:	52.2%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) RSS-247 Issue 3, August 2023, Clause 5.5
Test procedure	:	ANSI C63.10: 2013
Test voltage	:	DC 5V
Test modes applied	:	A

Figure 1: Reference level


125kbps, 2402MHz







125kbps, 2440MHz

125kbps, 2480MHz

500kbps, 2402MHz

500kbps, 2440MHz

500kbps, 2480MHz


Figure 2: Conducted Spurious Emission










125kbps, 2402MHz

125kbps, 2440MHz

125kbps, 2480MHz

500kbps, 2402MHz

500kbps, 2440MHz

500kbps, 2480MHz


Figure 3: Conducted Band Edge





5.2 Emission in the Frequency Range up to 30MHz

5.2.1 Conducted Emission

RESULT:**Pass**


Date of testing	: 2023-05-29
Ambient temperature	: 21.5°C
Relative humidity	: 57.3%
Atmospheric pressure	: 101kPa
Test requirement	: FCC Part 15.207 (a) RSS-Gen Issue 5, Amendment 1, March 2019, Clause 8.8
Test procedure	: KDB 558074 D01v05r02 ANSI C63.10: 2013
Test voltage	: AC 120V, 60Hz (powered by laptop)
Test modes applied	: A

Figure 4: Conducted Emission, L

Final_Result_QPK

Frequency (MHz)	QuasiPeak (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.166875	50.89	65.12	14.23	L1	9.8
0.448125	46.17	56.91	10.74	L1	9.8
0.954375	30.06	56.00	25.94	L1	9.8
2.259375	28.77	56.00	27.23	L1	9.9
9.684375	29.27	60.00	30.73	L1	10.2
23.206875	36.81	60.00	23.19	L1	10.3

Final_Result_CAV

Frequency (MHz)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.166875	31.50	55.12	23.62	L1	9.8
0.358125	26.03	48.77	22.74	L1	9.8
0.448125	36.42	46.91	10.49	L1	9.8
2.113125	21.13	46.00	24.87	L1	9.8
2.945625	21.83	46.00	24.17	L1	9.9

Figure 5: Conducted Emission, N

Final_Result_QPK

Frequency (MHz)	QuasiPeak (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.504375	44.53	56.00	11.47	N	9.8
0.898125	39.85	56.00	16.15	N	9.8
2.124375	35.51	56.00	20.49	N	9.8
4.993125	32.26	56.00	23.74	N	9.9
9.245625	36.83	60.00	23.17	N	10.2
0.504375	44.53	56.00	11.47	N	9.8

Final_Result_CAV

Frequency (MHz)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.166875	27.73	55.12	27.39	N	9.8
0.504375	34.00	46.00	12.00	N	9.8
0.661875	30.05	46.00	15.95	N	9.8
1.280625	29.30	46.00	16.70	N	9.8
2.169375	28.13	46.00	17.87	N	9.8
4.993125	26.69	46.00	19.31	N	9.9

5.3 Emission in the Frequency Range above 30MHz

5.3.1 Radiated Band-Edge

RESULT:**Pass**


Date of testing	:	2023-06-01
Ambient temperature	:	22.6°C
Relative humidity	:	55.4%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) FCC Part 15.205(a) FCC Part 15.209(a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.9 RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.10 RSS-247 Issue 3, August 2023, Clause 5.5
Test procedure	:	ANSI C63.10: 2013
Test voltage	:	DC 5V
Test modes applied	:	A

Note:

All the test modes were applied, only the worst case were shown in this report.

Figure 6: Radiated Band-Edge, 1Mbps, 2402MHz, H

2310~2410 BE 1-18GHz_HL050_FSV40_Pre


Figure 7: Radiated Band-Edge, 1Mbps, 2402MHz, V

2310~2410 BE 1-18GHz_HL050_FSV40_Pre





Figure 8: Radiated Band-Edge, 1Mbps, 2480MHz, H

2470~2500 BE_1-18GHz_HL050_FSV40_Pre


Figure 9: Radiated Band-Edge, 1Mbps, 2480MHz, V

2470~2500 BE_1-18GHz_HL050_FSV40_Pre





Figure 10: Radiated Band-Edge, 2Mbps, 2402MHz, H

2310~2410 BE 1-18GHz_HL050_FSV40_Pre


Figure 11: Radiated Band-Edge, 2Mbps, 2402MHz, V

2310~2410 BE 1-18GHz_HL050_FSV40_Pre






Figure 12: Radiated Band-Edge, 2Mbps, 2480MHz, H

2470~2500 BE_1-18GHz_HL050_FSV40_Pre


Figure 13: Radiated Band-Edge, 2Mbps, 2480MHz, V

2470~2500 BE_1-18GHz_HL050_FSV40_Pre



Prüfbericht - Nr.: CN23QK66 001
Test Report No.**Seite 67 von 80**
Page 67 of 80


5.3.2 Radiated Spurious Emission

RESULT:**Pass**

Date of testing	:	2023-06-01~2022-06-09
Ambient temperature	:	22.6~24.0°C
Relative humidity	:	55.4~57.1%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) FCC Part 15.209(a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.9 RSS-247 Issue 3, August 2023, Clause 5.5
Test procedure	:	ANSI C63.10: 2013
Test voltage	:	DC 5V
Test modes applied	:	A

Note:

1. All the test modes were applied, only the worst case were shown in this report.
2. For the frequency range from 18GHz to 25GHz, no emission was found.

Figure 14: Radiated Spurious Emission, 1Mbps, 2402MHz


Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
30.363750	28.3	H	24.6	11.8	40.0
140.458750	32.8	H	18.2	10.7	43.5
298.447500	27.6	H	20.2	18.5	46.0
30.727500	28.1	V	24.5	11.9	40.0
140.943750	35.7	V	18.2	7.8	43.5
904.333750	33.9	V	28.9	12.1	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
2209.000000	40.2	H	-16.8	33.8	74.0
2306.500000	41.9	H	-16.6	32.1	74.0
4804.750000	44.6	H	-10.6	29.4	74.0
7206.250000	48.1	H	-6.6	25.9	74.0
9607.000000	44.9	H	-4.2	29.1	74.0
12009.125000	44.0	H	-2.3	30.0	74.0
17989.000000	54.3	H	12.5	19.7	74.0
1465.000000	40.2	V	-19.4	33.8	74.0
1858.000000	41.0	V	-18.1	33.0	74.0
2315.500000	39.0	V	-16.5	35.0	74.0
4803.250000	42.2	V	-10.6	31.8	74.0
7204.875000	49.5	V	-6.6	24.5	74.0
9608.375000	44.1	V	-4.1	29.9	74.0
12009.125000	44.4	V	-2.3	29.6	74.0
17918.875000	54.6	V	11.1	19.4	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
2209.000000	34.8	H	-16.8	19.2	54.0
2306.500000	32.2	H	-16.6	21.8	54.0
4804.750000	40.5	H	-10.6	13.5	54.0
7206.250000	40.0	H	-6.6	14.0	54.0
9607.000000	34.8	H	-4.2	19.2	54.0
12009.125000	33.7	H	-2.3	20.3	54.0
17989.000000	43.0	H	12.5	11.0	54.0
1465.000000	22.9	V	-19.4	31.1	54.0
1858.000000	23.1	V	-18.1	30.9	54.0
2315.500000	29.9	V	-16.5	24.1	54.0
4803.250000	36.7	V	-10.6	17.3	54.0
7204.875000	43.2	V	-6.6	10.8	54.0
9608.375000	36.3	V	-4.1	17.7	54.0
12009.125000	33.8	V	-2.3	20.2	54.0
17918.875000	41.9	V	11.1	12.1	54.0

Figure 15: Radiated Spurious Emission, 1Mbps, 2440MHz


Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
32.182500	27.4	H	23.8	12.6	40.0
141.550000	32.1	H	18.1	11.4	43.5
303.782500	26.9	H	20.3	19.1	46.0
30.606250	28.2	V	24.5	11.8	40.0
141.065000	35.5	V	18.2	8.0	43.5
895.846250	33.9	V	28.8	12.2	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1732.750000	37.2	H	-18.4	36.8	74.0
2311.750000	42.7	H	-16.6	31.3	74.0
4880.500000	42.9	H	-10.5	31.1	74.0
7319.000000	47.7	H	-6.6	26.3	74.0
9759.625000	44.3	H	-3.6	29.7	74.0
18000.000000	54.2	H	12.8	19.8	74.0
1928.500000	36.4	V	-17.8	37.6	74.0
2311.750000	42.0	V	-16.6	32.0	74.0
3390.250000	38.6	V	-14.1	35.4	74.0
4880.500000	41.9	V	-10.5	32.1	74.0
7319.000000	46.5	V	-6.6	27.5	74.0
9759.625000	44.2	V	-3.6	29.8	74.0
17995.875000	55.8	V	12.7	18.2	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1732.750000	21.2	H	-18.4	32.8	54.0
2311.750000	35.9	H	-16.6	18.1	54.0
4880.500000	36.1	H	-10.5	17.9	54.0
7319.000000	41.0	H	-6.6	13.0	54.0
9759.625000	34.2	H	-3.6	19.8	54.0
18000.000000	43.1	H	12.8	10.9	54.0
1928.500000	25.6	V	-17.8	28.4	54.0
2311.750000	34.0	V	-16.6	20.0	54.0
3390.250000	27.2	V	-14.1	26.8	54.0
4880.500000	32.8	V	-10.5	21.2	54.0
7319.000000	39.8	V	-6.6	14.2	54.0
9759.625000	34.3	V	-3.6	19.7	54.0
17995.875000	43.1	V	12.7	10.9	54.0

Figure 16: Radiated Spurious Emission, 1Mbps, 2480MHz


Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
32.425000	27.3	H	23.7	12.7	40.0
140.943750	33.0	H	18.2	10.5	43.5
296.750000	26.7	H	20.2	19.3	46.0
30.606250	28.2	V	24.5	11.8	40.0
140.943750	35.4	V	18.2	8.1	43.5
830.977500	33.1	V	28.5	12.9	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1750.750000	36.1	H	-18.4	37.9	74.0
2287.750000	38.8	H	-16.6	35.2	74.0
4959.250000	44.0	H	-10.4	30.0	74.0
7438.625000	44.8	H	-5.7	29.2	74.0
9920.500000	45.9	H	-3.1	28.1	74.0
17986.250000	54.0	H	12.5	20.0	74.0
1860.250000	42.9	V	-18.1	31.1	74.0
2257.750000	42.6	V	-16.7	31.4	74.0
4960.750000	42.9	V	-10.4	31.1	74.0
7438.625000	43.5	V	-5.7	30.5	74.0
9920.500000	44.1	V	-3.1	29.9	74.0
17994.500000	55.0	V	12.7	19.0	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1750.750000	29.6	H	-18.4	24.4	54.0
2287.750000	31.0	H	-16.6	23.0	54.0
4959.250000	38.2	H	-10.4	15.8	54.0
7438.625000	37.1	H	-5.7	16.9	54.0
9920.500000	36.8	H	-3.1	17.2	54.0
17986.250000	42.8	H	12.5	11.2	54.0
1860.250000	22.8	V	-18.1	31.2	54.0
2257.750000	23.0	V	-16.7	31.0	54.0
4960.750000	35.0	V	-10.4	19.0	54.0
7438.625000	33.9	V	-5.7	40.1	74.0
9920.500000	35.6	V	-3.1	38.4	74.0
17994.500000	43.4	V	12.7	30.6	74.0

Figure 17: Radiated Spurious Emission, 2Mbps, 2402MHz


Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
31.333750	27.9	H	24.2	12.1	40.0
142.156250	32.6	H	18.1	10.9	43.5
315.180000	27.5	H	20.7	18.5	46.0
30.485000	28.2	V	24.6	11.8	40.0
141.186250	35.6	V	18.2	7.9	43.5
854.257500	33.9	V	29.0	12.1	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1792.000000	37.2	H	-18.3	36.8	74.0
2296.000000	42.5	H	-16.6	31.5	74.0
4803.250000	44.7	H	-10.6	29.3	74.0
7206.250000	49.3	H	-6.6	24.7	74.0
9605.625000	44.2	H	-4.2	29.8	74.0
17994.500000	54.7	H	12.7	19.3	74.0
1864.000000	38.5	V	-18.0	35.5	74.0
2315.500000	40.0	V	-16.5	34.0	74.0
3322.000000	39.6	V	-14.1	34.4	74.0
4803.250000	42.6	V	-10.6	31.4	74.0
7206.250000	49.5	V	-6.6	24.5	74.0
9609.750000	44.4	V	-4.1	29.6	74.0
18000.000000	54.2	V	12.8	19.8	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1792.000000	23.5	H	-18.3	30.5	54.0
2296.000000	32.1	H	-16.6	21.9	54.0
4803.250000	38.2	H	-10.6	15.8	54.0
7206.250000	41.8	H	-6.6	12.2	54.0
9605.625000	34.1	H	-4.2	19.9	54.0
17994.500000	43.4	H	12.7	10.6	54.0
1864.000000	21.5	V	-18.0	32.5	54.0
2315.500000	29.6	V	-16.5	24.4	54.0
3322.000000	23.9	V	-14.1	30.1	54.0
4803.250000	34.3	V	-10.6	19.7	54.0
7206.250000	41.5	V	-6.6	12.5	54.0
9609.750000	34.3	V	-4.1	19.7	54.0
18000.000000	43.5	V	12.8	10.5	54.0

Figure 18: Radiated Spurious Emission, 2Mbps, 2440MHz


Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
32.546250	27.3	H	23.6	12.7	40.0
141.065000	32.7	H	18.2	10.8	43.5
322.576250	26.7	H	20.9	19.3	46.0
30.970000	28.0	V	24.4	12.0	40.0
140.580000	35.3	V	18.2	8.2	43.5
547.858750	30.6	V	26.7	15.4	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1767.250000	32.7	H	-18.4	41.3	74.0
2311.750000	38.1	H	-16.6	35.9	74.0
4879.000000	39.4	H	-10.5	34.6	74.0
7317.625000	44.7	H	-6.7	29.3	74.0
9761.000000	43.3	H	-3.6	30.7	74.0
17990.375000	54.6	H	12.6	19.4	74.0
1465.750000	40.2	V	-19.3	33.8	74.0
1862.500000	40.7	V	-18.0	33.3	74.0
2311.750000	40.3	V	-16.6	33.7	74.0
4881.250000	39.6	V	-10.5	34.4	74.0
7317.625000	47.1	V	-6.7	26.9	74.0
9758.250000	42.7	V	-3.6	31.3	74.0
17994.500000	54.1	V	12.7	19.9	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1767.250000	25.3	H	-18.4	28.7	54.0
2311.750000	29.7	H	-16.6	24.3	54.0
4879.000000	26.9	H	-10.5	27.1	54.0
7317.625000	35.7	H	-6.7	18.3	54.0
9761.000000	33.9	H	-3.6	20.1	54.0
17990.375000	43.1	H	12.6	10.9	54.0
1465.750000	21.6	V	-19.3	32.4	54.0
1862.500000	23.0	V	-18.0	31.0	54.0
2311.750000	32.5	V	-16.6	21.5	54.0
4881.250000	30.8	V	-10.5	23.2	54.0
7317.625000	38.7	V	-6.7	15.3	54.0
9758.250000	34.0	V	-3.6	20.0	54.0
17994.500000	42.8	V	12.7	11.2	54.0

Figure 19: Radiated Spurious Emission, 2Mbps, 2480MHz


Limit and Margin
QP

Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
31.697500	27.7	H	24.0	12.3	40.0
141.186250	33.4	H	18.2	10.1	43.5
302.327500	26.2	H	20.3	19.8	46.0
32.788750	27.1	V	23.5	12.9	40.0
140.943750	35.5	V	18.2	8.0	43.5
582.172500	30.6	V	26.6	15.4	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1995.250000	37.0	H	-17.5	37.0	74.0
2309.500000	38.4	H	-16.6	35.6	74.0
4959.250000	43.5	H	-10.4	30.5	74.0
7441.375000	46.7	H	-5.7	27.3	74.0
9917.750000	46.2	H	-3.1	27.8	74.0
17932.625000	54.9	H	11.4	19.2	74.0
1727.500000	39.5	V	-18.4	34.5	74.0
2125.750000	41.5	V	-17.2	32.5	74.0
3330.250000	39.6	V	-14.1	34.4	74.0
4960.750000	40.4	V	-10.4	33.6	74.0
7438.625000	43.4	V	-5.7	30.6	74.0
9917.750000	46.3	V	-3.1	27.7	74.0
17997.250000	54.4	V	12.7	19.6	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1995.250000	25.4	H	-17.5	28.6	54.0
2309.500000	28.8	H	-16.6	25.2	54.0
4959.250000	35.6	H	-10.4	18.4	54.0
7441.375000	37.8	H	-5.7	16.2	54.0
9917.750000	36.1	H	-3.1	17.9	54.0
17932.625000	42.7	H	11.4	11.3	54.0
1727.500000	18.3	V	-18.4	35.7	54.0
2125.750000	21.4	V	-17.2	32.6	54.0
3330.250000	23.7	V	-14.1	30.3	54.0
4960.750000	31.4	V	-10.4	22.6	54.0
7438.625000	33.6	V	-5.7	20.4	54.0
9917.750000	37.4	V	-3.1	16.6	54.0
17997.250000	43.1	V	12.7	11.0	54.0

6. List of Tables

Table 1: List of Test and Measurement Equipment	6
Table 2: Measurement Uncertainty	7
Table 3: Technical Specification of EUT	8
Table 4: Operation Channel List	8
Table 5: Power parameter value	10
Table 6: Auxiliary Equipment	10
Table 7: Antenna Requirement	11
Table 8: Peak Output Power	38

7. List of Figures

Figure 1: Reference level	53
Figure 2: Conducted Spurious Emission	55
Figure 3: Conducted Band Edge	57
Figure 4: Conducted Emission, L	60
Figure 5: Conducted Emission, N	61
Figure 6: Radiated Band-Edge, 1Mbps, 2402MHz, H	63
Figure 7: Radiated Band-Edge, 1Mbps, 2402MHz, V	63
Figure 8: Radiated Band-Edge, 1Mbps, 2480MHz, H	64
Figure 9: Radiated Band-Edge, 1Mbps, 2480MHz, V	64
Figure 10: Radiated Band-Edge, 2Mbps, 2402MHz, H	65
Figure 11: Radiated Band-Edge, 2Mbps, 2402MHz, V	65
Figure 12: Radiated Band-Edge, 2Mbps, 2480MHz, H	66
Figure 13: Radiated Band-Edge, 2Mbps, 2480MHz, V	66
Figure 14: Radiated Spurious Emission, 1Mbps, 2402MHz	68
Figure 15: Radiated Spurious Emission, 1Mbps, 2440MHz	70
Figure 16: Radiated Spurious Emission, 1Mbps, 2480MHz	72
Figure 17: Radiated Spurious Emission, 2Mbps, 2402MHz	74
Figure 18: Radiated Spurious Emission, 2Mbps, 2440MHz	76
Figure 19: Radiated Spurious Emission, 2Mbps, 2480MHz	78