

6 Safety Human Exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:

Pass

Test Specification

Test standard

: CFR47 FCC Part 2: Section 2.1093
CFR47 FCC Part 1: Section 1.1310
FCC KDB Publication 447498 D01 v06

➤ **FCC requirements**

FCC requirement: Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20cm normally can be maintained between the user and the device.

Measurement Record for CFR47 FCC Part 2.1093

The minimum distance for the EUT is less than 5mm.

The maximum specified e.i.r.p.: 75.402dBuv/m @3m = -19.8dBm=0.0104mW

Antenna Gain: 0dBi max

According to KDB 447498 D01 v06 4.3.1 a)

Exempted Power: 9.5mW, hence the EUT is compliance with the RF exposure.

The minimum distance for the EUT is less than 5mm.

The maximum specified e.i.r.p.: 75.402dBuv/m @3m = -19.8dBm=0.0104mW