



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20180700046E-02

Applicant: GANZHOU DEHUIDA TECHNOLOGY CO., LTD.

Address of Applicant: Dehuida Science and Technology Park, Huoyanshan Road, Anyuan District, Ganzhou City, Jiangxi Province, China

Manufacturer: GANZHOU DEHUIDA TECHNOLOGY CO., LTD.

Address of Manufacturer: Dehuida Science and Technology Park, Huoyanshan Road, Anyuan District, Ganzhou City, Jiangxi Province, China

Factory: GANZHOU DEHUIDA TECHNOLOGY CO., LTD

Address of Factory: No. 5 , 6, 7, 8, 9 Build, Dehuida Science and Technology Park, Huoyanshan Road, Anyuan District, Ganzhou City, Jianxi Province

Equipment Under Test (EUT):

Product: WiFi Speaker

Model No.: 79210PI

Brand Name: i-box

FCC ID: 2AO5X-79210PI

Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2018-07-12 to 2018-07-20

Date of Issue: 2018-07-20

Test Result : PASS*

Tested By:

Martin Lee

(Martin Lee)

Reviewed By:

(Jack Ai)

Approved By:

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20180700046E-02	Rev.01	Initial report	2018-07-20

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 RF EXPOSURE EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 Limits	5
4.1.2 Test Procedure.....	5
4.2 1.1.3 EUT RF EXPOSURE EVALUATION	6

3 General Information

3.1 Client Information

Applicant:	GANZHOU DEHUIDA TECHNOLOGY CO., LTD.
Address of Applicant:	Dehuida Science and Technology Park, Huoyanshan Road, Anyuan District, Ganzhou City, Jiangxi Province, China
Manufacturer:	GANZHOU DEHUIDA TECHNOLOGY CO., LTD.
Address of Manufacturer:	Dehuida Science and Technology Park, Huoyanshan Road, Anyuan District, Ganzhou City, Jiangxi Province, China
Factory:	GANZHOU DEHUIDA TECHNOLOGY CO., LTD
Address of Factory:	No. 5 , 6, 7, 8, 9 Build, Dehuida Science and Technology Park, Huoyanshan Road, Anyuan District, Ganzhou City, Jianxi Province

3.2 General Description of EUT

Product Name:	WiFi Speaker
Model No.:	79210PI
Trade Mark:	i-box
Hardware version:	V1.2
Software version:	V1.1
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Sample Type:	Mobile production
Test Software of EUT:	MT7628 QA 0.0.0.96(manufacturer declare)
Antenna Type:	Integral Antenna
Antenna Gain:	2.0dBi
Power Supply:	120V / 60Hz

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.2 1.1.3 EUT RF Exposure Evaluation

1) For WIFI

Antenna Gain: 2.0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.58 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

802.11b mode	
Test channel	Average Output Power (dBm)
Lowest(2412MHz)	13.54
Middle(2437MHz)	13.43
Highest(2462MHz)	13.48
802.11g mode	
Test channel	Average Output Power (dBm)
Lowest(2412MHz)	12.01
Middle(2437MHz)	11.94
Highest(2462MHz)	11.97
802.11n(HT20)mode	
Test channel	Average Output Power (dBm)
Lowest(2412MHz)	11.87
Middle(2437MHz)	11.76
Highest(2462MHz)	11.83
802.11n(HT40)mode	
Test channel	Average Output Power (dBm)
Lowest(2422MHz)	11.40
Middle(2437MHz)	11.32
Highest(2452MHz)	11.35

802.11b(worst case)

Channel	Frequency (MHz)	Max Conducted average Output Power (dBm)	Output Power to Antenna (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Lowest	2412	13.54	22.594	2.0	0.0071	1.0	PASS

Note: 1) Refer to report No. CQASZ20180700046E-01 for EUT test Max Conducted average Output Power value.

$$2) Pd = (Pout * G) / (4 * \pi * R^2) = (22.594 * 1.58) / (4 * 3.1416 * 20^2) = 0.0071$$