



FCC PART 15.247 TEST REPORT

For

Epik One America Corporation

170 Ocean Lane Dr. #705, Key Biscayne, FL 33149, Key Biscayne, Florida, United States

FCC ID: 2AO6ZX507T

Report Type: Original Report	Product Type: 4G Smart Phone
Report Number: RSZ190306003-00B	
Report Date: 2019-04-19	
Reviewed By: RF Engineer	Candy Li <i>Candy Li</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE	11
APPLICABLE STANDARD	11
FCC §15.203 – ANTENNA REQUIREMENT	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP.....	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
CORRECTED FACTOR & MARGIN CALCULATION	14
TEST RESULTS SUMMARY	14
TEST DATA	14
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	18
TEST PROCEDURE	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST RESULTS SUMMARY	19
TEST DATA	19
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST DATA	26

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST DATA	33
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST DATA	39
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST DATA	42
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT.....	58
APPLICABLE STANDARD	58
TEST PROCEDURE	58
TEST DATA	58
FCC §15.247(d) - BAND EDGES TESTING	59
APPLICABLE STANDARD	59
TEST PROCEDURE	59
TEST DATA	59

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	4G Smart Phone
Tested Model	X507T
Frequency Range	Bluetooth: 2402~2480MHz
Transmit Power	Bluetooth: 8.37dBm
Modulation Technique	Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Specification	Internal Antenna: -0.7dBi
Voltage Range	DC 3.7 V from battery or DC 5.0V from adapter
Date of Test	2019/03/11~2019/03/19
Sample serial number	190306003
Received date	2019/03/06
Sample/EUT Status	Good condition
Adapter information	Model: HL-0507D-UU Input: AC 100-240V, 50/60Hz, 0.15A Output: DC 5.0V, 700 mA

Objective

This test report is prepared on behalf of *Epik One America Corporation* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

Part 15.247 DTS and Part 22H /24E / 27 PCE submissions with FCC ID: 2AO6ZX507T.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r01.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.5dB
RF conducted test with spectrum		±1.5dB
AC Power Lines Conducted Emissions		±1.95dB
Radiated Emissions	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±3°C
Humidity		±6%
Supply voltages		±0.4%

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

No exercise software was made to the EUT tested.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2018-07-11	2019-07-11
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2018-12-21	2019-12-21
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2018-11-12	2019-11-12
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Un-known	Conducted Emission Cable	78652	UF A210B-1-0720-504504	2018-11-12	2019-11-12
Radiated Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2018-07-11	2019-07-11
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
Sonoma instrument	Amplifier	310 N	186238	2018-11-12	2019-11-12
Rohde & Schwarz	Signal Analyzer	FSV40	101473	2019-01-09	2020-01-08
COM-POWER	Pre-amplifier	PA-122	181919	2018-11-12	2019-11-12
A.H. System	Horn Antenna	SAS-200/571	135	2018-09-01	2021-08-31
Ducommun technologies	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2018-11-12	2019-11-12
Ducommun technologies	RF Cable	104PEA	218124002	2018-11-12	2019-11-12
Ducommun technologies	RF Cable	RG-214	1	2018-11-19	2019-05-21
Ducommun technologies	RF Cable	RG-214	2	2018-11-12	2019-11-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2017-12-29	2020-12-28
Heatsink Required	Amplifier	QLW-18405536-J0	15964001002	2018-11-12	2019-11-12
Sinoscite	Notch Filter	BSF2402-2480MN-0898-001	99632	2018-11-12	2019-11-12
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Agilent	USB wideband power meter	U2021XA	MY54250003	2018-06-23	2019-06-23
WEINSCHL	3dB Attenuator	6231	666	Each Time	
Rohde & Schwarz	Spectrum Analyzer	FSU26	200120	2018-12-24	2019-12-24
Ducommun technologies	RF Cable	RG-214	3	Each Time	

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

For worst case:

Frequency (MHz)	Maximum Tune-up power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
	(dBm)	(mW)				
2480	8.5	7.08	5	2.2	3.0	Yes

Result: No Standalone SAR test is required

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is -0.7 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2019-03-11.

EUT operation mode: Transmitting & charging (the worst case is 8DPSK Mode, High channel)

AC 120V/60 Hz, Line

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.165500	43.8	20.0	65.2	21.4	QP
0.175500	43.6	20.0	65.2	21.6	QP
0.332990	40.8	20.0	59.4	18.6	QP
0.427490	42.0	20.0	57.3	15.3	QP
0.431550	42.9	20.0	57.2	14.3	QP
0.526110	36.6	20.1	56.0	19.4	QP
0.165500	30.8	20.0	55.2	24.4	Ave.
0.175500	30.8	20.0	55.2	24.4	Ave.
0.332990	28.6	20.0	49.4	20.8	Ave.
0.427490	35.2	20.0	47.3	12.1	Ave.
0.431550	35.3	20.0	47.2	11.9	Ave.
0.526110	22.7	20.1	46.0	23.3	Ave.

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.431550	39.9	20.0	57.2	17.3	QP
0.463130	38.7	20.1	56.6	17.9	QP
0.514290	30.9	20.1	56.0	25.1	QP
0.561510	31.5	20.0	56.0	24.5	QP
0.979090	33.0	20.1	56.0	23.0	QP
1.038610	33.1	20.1	56.0	22.9	QP
0.431550	29.4	20.0	47.2	17.8	Ave.
0.463130	27.6	20.1	46.6	19.0	Ave.
0.514290	22.7	20.1	46.0	23.3	Ave.
0.561510	20.7	20.0	46.0	25.3	Ave.
0.979090	24.5	20.1	46.0	21.5	Ave.
1.038610	25.3	20.1	46.0	20.7	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, according to the DA 00-705 Released March 30, 2000, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Average

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	24~25 °C
Relative Humidity:	55~56 %
ATM Pressure:	101.0~101.3 kPa

The testing was performed by LeoHuang and Yecar Lu from 2019-03-12 to 2019-03-19.

EUT operation mode: Transmitting (Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK mode, the worst case is 8DPSK Mode)

30 MHz~1 GHz: (the worst case is 8DPSK Mode, High channel)



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
130.038000	21.15	307.0	H	97.0	-13.6	43.50	22.35
151.493750	15.24	255.0	H	59.0	-14.2	43.50	28.26
227.836875	18.22	102.0	H	245.0	-14.0	46.00	27.78
311.635750	27.11	103.0	H	290.0	-10.7	46.00	18.89
838.391250	29.66	322.0	H	125.0	5.8	46.00	16.34
957.752500	31.01	162.0	H	70.0	9.4	46.00	14.99

1 GHz - 25 GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2402 MHz)									
2390.00	27.80	PK	250	1.9	H	33.00	60.80	74	13.20
2390.00	13.90	Ave.	250	1.9	H	33.00	46.90	54	7.10
2483.50	27.66	PK	10	1.5	H	33.20	60.86	74	13.14
2483.50	13.85	Ave.	10	1.5	H	33.20	47.05	54	6.95
4804.00	42.56	PK	171	1.4	H	7.88	50.44	74	23.56
4804.00	28.40	Ave.	171	1.4	H	7.88	36.28	54	17.72
Middle Channel (2441 MHz)									
4882.00	41.85	PK	220	1.3	H	9.21	51.06	74	22.94
4882.00	27.89	Ave.	220	1.3	H	9.21	37.10	54	16.90
High Channel (2480 MHz)									
2390.00	28.01	PK	230	2.5	H	33.00	61.01	74	12.99
2390.00	14.90	Ave.	230	2.5	H	33.00	47.90	54	6.10
2483.50	29.85	PK	180	1.2	H	33.20	63.05	74	10.95
2483.50	16.50	Ave.	180	1.2	H	33.20	49.70	54	4.30
4960.00	42.28	PK	355	1.5	H	9.07	51.35	74	22.65
4960.00	28.33	Ave.	355	1.5	H	9.07	37.40	54	16.60

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude


The other spurious emission which is 20dB to the limit was not recorded.

And for the pre-scan is performed with the 2400-2483.5MHz band filter.

Pre-scan with High channel Peak Horizontal




Date: 19.MAR.2019 17:26:38




Date: 19.MAR.2019 21:47:33


Vertical




Date: 19.MAR.2019 17:31:12



Date: 19.MAR.2019 21:51:27


**Pre-scan for Average
Horizontal**

Date: 19.MAR.2019 17:33:29




Date: 19.MAR.2019 21:55:16

Vertical



Date: 19.MAR.2019 17:38:39



Date: 19.MAR.2019 21:58:46

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Shawn Xiao on 2019-03-13.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to following table and plots.

Channel	Channel Separation (MHz)	20 dBc BW (MHz)	Two-thirds of the 20 dB bandwidth (MHz)	Channel Separation Limit	Result
BDR(GFSK)					
Low	1.00	0.86	0.573	> two-thirds of the 20 dB bandwidth	Compliance
Middle	1.00	0.86	0.573	> two-thirds of the 20 dB bandwidth	Compliance
High	1.01	0.86	0.573	> two-thirds of the 20 dB bandwidth	Compliance
EDR($\pi/4$-DQPSK)					
Low	1.00	1.29	0.860	> two-thirds of the 20 dB bandwidth	Compliance
Middle	1.00	1.29	0.860	> two-thirds of the 20 dB bandwidth	Compliance
High	1.00	1.29	0.860	> two-thirds of the 20 dB bandwidth	Compliance
EDR(8DPSK)					
Low	1.00	1.28	0.853	> two-thirds of the 20 dB bandwidth	Compliance
Middle	1.00	1.28	0.853	> two-thirds of the 20 dB bandwidth	Compliance
High	1.00	1.28	0.853	> two-thirds of the 20 dB bandwidth	Compliance


Please refer to the following plots.

BDR (GFSK): Low Channel


Date: 13.MAR.2019 09:57:05

BDR (GFSK): Middle Channel


Date: 13.MAR.2019 09:59:10

BDR (GFSK): High Channel


Date: 13.MAR.2019 10:02:02

EDR ($\pi/4$ -DQPSK): Low Channel


Date: 13.MAR.2019 10:16:42

EDR ($\pi/4$ -DQPSK): Middle Channel


Date: 13.MAR.2019 10:11:19

EDR ($\pi/4$ -DQPSK): High Channel

Date: 13.MAR.2019 10:05:27


EDR (8DPSK): Low Channel

Date: 13.MAR.2019 10:20:45

EDR (8DPSK): Middle Channel

Date: 13.MAR.2019 10:23:52

EDR (8DPSK): High Channel



Date: 13.MAR.2019 10:29:16

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Shawn Xiao on 2019-03-13.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.86
	Middle	2441	0.86
	High	2480	0.86
EDR ($\pi/4$-DQPSK)	Low	2402	1.29
	Middle	2441	1.29
	High	2480	1.29
EDR (8DPSK)	Low	2402	1.28
	Middle	2441	1.28
	High	2480	1.28

BDR (GFSK): Low Channel


Date: 13.MAR.2019 09:54:21

BDR (GFSK): Middle Channel

Date: 13.MAR.2019 09:53:18


BDR (GFSK): High Channel

Date: 13.MAR.2019 09:52:35

EDR ($\pi/4$ -DQPSK): Low Channel


Date: 13.MAR.2019 09:44:27

EDR ($\pi/4$ -DQPSK): Middle Channel




Date: 13.MAR.2019 09:45:50

EDR ($\pi/4$ -DQPSK): High Channel




Date: 13.MAR.2019 09:47:19

EDR (8DPSK): Low Channel




Date: 13.MAR.2019 09:39:39

EDR (8DPSK): Middle Channel



Date: 13.MAR.2019 09:38:30

EDR (8DPSK): High Channel



Date: 13.MAR.2019 09:37:11

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Shawn Xiao on 2019-03-13.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15


BDR (GFSK): Number of Hopping Channels

Date: 13.MAR.2019 11:02:30

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels

Date: 13.MAR.2019 10:58:40

EDR (8DPSK): Number of Hopping Channels



Date: 13.MAR.2019 10:55:20

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWEELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

Test Data**Environmental Conditions**


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Shawn Xiao on 2019-03-13.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots

Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
BDR (GFSK)	DH 1	Low	0.42	0.134	0.4	Pass
		Middle	0.42	0.134	0.4	Pass
		High	0.42	0.134	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.68	0.269	0.4	Pass
		Middle	1.68	0.269	0.4	Pass
		High	1.68	0.269	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	2.93	0.313	0.4	Pass
		Middle	2.93	0.313	0.4	Pass
		High	2.93	0.313	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	2DH 1	Low	0.42	0.134	0.4	Pass
		Middle	0.42	0.134	0.4	Pass
		High	0.42	0.134	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH 3	Low	1.67	0.267	0.4	Pass
		Middle	1.67	0.267	0.4	Pass
		High	1.67	0.267	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH 5	Low	2.93	0.313	0.4	Pass
		Middle	2.93	0.313	0.4	Pass
		High	2.93	0.313	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH 1	Low	0.41	0.131	0.4	Pass
		Middle	0.41	0.131	0.4	Pass
		High	0.41	0.131	0.4	Pass
		Note: 3DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH 3	Low	1.67	0.267	0.4	Pass
		Middle	1.67	0.267	0.4	Pass
		High	1.67	0.267	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH 5	Low	2.93	0.313	0.4	Pass
		Middle	2.93	0.313	0.4	Pass
		High	2.93	0.313	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				


BDR (GFSK):**Pulse time, Low Channel, DH1**

Date: 13.MAR.2019 11:05:46

Pulse time, Middle Channel, DH1


Date: 13.MAR.2019 11:06:11

Pulse time, High Channel, DH1




Date: 13.MAR.2019 11:06:20

Pulse time, Low Channel, DH3




Date: 13.MAR.2019 11:12:50

Pulse time, Middle Channel, DH3




Date: 13.MAR.2019 11:12:41

Pulse time, High Channel, DH3




Date: 13.MAR.2019 11:12:27

Pulse time, Low Channel, DH5




Date: 13.MAR.2019 11:13:35

Pulse time, Middle Channel, DH5



Date: 13.MAR.2019 11:13:49


Pulse time, High Channel, DH5



Date: 13.MAR.2019 11:13:59


EDR ($\pi/4$ -DQPSK):

Pulse time, Low Channel, 2DH1




Date: 13.MAR.2019 11:07:18

Pulse time, Middle Channel, 2DH1




Date: 13.MAR.2019 11:07:09

Pulse time, High Channel, 2DH1




Date: 13.MAR.2019 11:06:59

Pulse time, Low Channel, 2DH3




Date: 13.MAR.2019 11:11:09

Pulse time, Middle Channel, 2DH3




Date: 13.MAR.2019 11:11:19

Pulse time, High Channel, 2DH3



Date: 13.MAR.2019 11:11:27

Pulse time, Low Channel, 2DH5



Date: 13.MAR.2019 11:14:52

Ref 18.5 dBm * Att 10 dB RBW 1 MHz VBW 3 MHz SWT 5 ms Delta 1 [T1] 1.80 dB

Offset 3.5 dB Marker 1 [T1] -63.89 dBm -25.961538 μs


1 PK MAXH TRG LVL 30dB

Center 2.441 GHz 500 μs/


Date: 13.MAR.2019 11:14:42

RBW 1 MHz
 VBW 3 MHz
 SWT 5 ms
 Delta 1 [T1] 3.53 dB
 2.934295 ms
 Ref 18.5 dBm
 Att 10 dB
 Offset 3.5 dB
 Marker 1 [T1] -62.50 dBm
 -25.961538 μs
 TRG 0.9 dBm
 1 PK MAXH
 3DB
 Center 2.48 GHz
 500 μs/

Date: 13.MAR.2019 11:14:28


**EDR (8DPSK):
Pulse time, Low Channel, 3DH1**

Date: 13.MAR.2019 11:08:05

Pulse time, Middle Channel, 3DH1


Date: 13.MAR.2019 11:08:18

Pulse time, High Channel, 3DH1




Date: 13.MAR.2019 11:08:28

Pulse time, Low Channel, 3DH3




Date: 13.MAR.2019 11:09:53

Pulse time, Middle Channel, 3DH3




Date: 13.MAR.2019 11:09:41

Pulse time, High Channel, 3DH3




Date: 13.MAR.2019 11:09:16

Pulse time, Low Channel, 3DH5




Date: 13.MAR.2019 11:15:18

Pulse time, Middle Channel, 3DH5



Date: 13.MAR.2019 11:15:31

Pulse time, High Channel, 3DH5



Date: 13.MAR.2019 11:15:45

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Shawn Xiao on 2019-03-13.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table.

Mode	Channel	Frequency (MHz)	Peak Output Power		Limit (mW)
			(dBm)	(mW)	
BDR (GFSK)	Low	2402	7.19	5.236	125
	Middle	2441	6.82	4.808	125
	High	2480	6.01	3.990	125
	Max	2410	7.46	5.572	125
EDR ($\pi/4$-DQPSK)	Low	2402	7.58	5.728	125
	Middle	2441	7.43	5.534	125
	High	2480	6.12	4.093	125
	Max	2409	7.82	6.053	125
EDR (8DPSK)	Low	2402	8.10	6.457	125
	Middle	2441	7.99	6.295	125
	High	2480	6.64	4.613	125
	Max	2411	8.37	6.871	125

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Shawn Xiao on 2019-03-13.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following plots.


**BDR (GFSK): Band Edge-Left Side
Hopping**

Date: 13.MAR.2019 10:36:22

Single


Date: 13.MAR.2019 10:34:57

BDR (GFSK): Band Edge-Right Side Hopping




Date: 13.MAR.2019 10:37:27

Single




Date: 13.MAR.2019 10:38:32

EDR ($\pi/4$ -DQPSK): Band Edge-Left Side Hopping




Date: 13.MAR.2019 10:42:23

Single




Date: 13.MAR.2019 10:42:54

EDR ($\pi/4$ -DQPSK): Band Edge-Right Side Hopping




Date: 13.MAR.2019 10:41:23


Single




Date: 13.MAR.2019 10:39:56

**EDR (8DPSK): Band Edge-Left Side
Hopping**


Date: 13.MAR.2019 10:45:20

Single

Date: 13.MAR.2019 10:44:26

**EDR (8DPSK): Band Edge-Right Side
Hopping**

Date: 13.MAR.2019 10:46:08

Single

Date: 13.MAR.2019 10:48:45

***** END OF REPORT *****