

RF EXPOSURE EVALUATION

1. TEST RESULT CERTIFICATION

Applicant	System Level Solutions (India) Pvt. Ltd.
Address	Plot#32, Zone-D/4, Phase-1, GIDC Estate, V.U. Nagar -388 121, Gujarat, India
manufacturer	System Level Solutions (India) Pvt. Ltd.
Address	Plot#32, Zone-D/4, Phase-1, GIDC Estate, V.U. Nagar -388 121, Gujarat, India
Factory	System Level Solutions (India) Pvt. Ltd.
Address	Plot#32, Zone-D/4, Phase-1, GIDC Estate, V.U. Nagar -388 121, Gujarat, India
Product Designation:	NLN100C-2
Brand Name:	Nebulae
Test Model:	PI0NN100C2100
FCC ID:	2AO93PI0NN100C1100
Date of Test:	May 10, 2020 to Oct. 09, 2020

2. TECHNICAL INFORMATION

A major technical description of EUT is described as following:

Operation Frequency	2.405 GHz to 2.480GHz
Modulation	O-QPSK
Antenna Designation	PCB Antenna(Comply with requirements of the FCC part 15.203)
Output power	5W/20W
Antenna gain	-3dBi
Power Supply	DC 3V by Dry cell or DC 5V by PC.

3. RF EXPOSURE MEASUREMENT

3.1 INTRODUCTION

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

The 1992 ANSI/IEEE standard (See Listed limit table) specifies a minimum separation distance of 20 cm for performing reliable field measurements to determine adherence to MPE limits.

If the minimum separation distance between a transmitter and nearby persons is more than 20 cm under normal operating conditions, compliance with MPE limits may be determined at such distance from the transmitter. When applicable, operation instructions and prominent warning labels may be used to alert the exposed persons to maintain a specified distance from the transmitter or to limit their exposure durations and usage conditions to ensure compliance.

3.2 FCC LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f ²)*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

*Note:

1. f= Frequency in MHz * Plane-wave Equivalent Power Density

2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

4. CLASSIFICATION OF THE ASSESSMENT METHODS

According to user manual, The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. So, this product under normal use is located on electromagnetic far field between the human body.

$$S = PG/4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

5. EUT OPERATION CONDITION

Make the EUT to transmit at Bottom channel, Middle channel and Top channel individually.

6. TEST RESULTS

Note: report the worst result in this part

Antenna Gain=-3dBi (Numeric 1), $\pi=3.141$

Frequency	Output Power	Output Power	Power Density	Power Density Limit	Result
MHz	dBm	mW	mW/cm ²	mW/cm ²	Pass/Fail
2440	9.042	8.02	0.000797915	1	Pass

Note:

1.The output power is refer to **AGC01125180410FE02**.