

TEST REPORT

Report Number	90475-25-72-25-PP002
Date of issue	2025.06.23
Prepared by (+signature).....	Pale
Reviewer (+signature).....	Duke
Approved by (+signature)	Jason
Testing Laboratory name	SLG-CPC Testlaboratory Co., Ltd.
Address	No. 11, Wu Song Road, Dongcheng District Dongguan, Guangdong Province, 523117, People's Republic of China
Applicant's name	MOKO TECHNOLOGY LIMITED
Address	Factory 201, 107 Pinshun Rd Guixiang community, Guanlan Street, Longhua, Shenzhen, China 518110
Manufacturer's name	MOKO TECHNOLOGY LIMITED
Address	Factory 201, 107 Pinshun Rd Guixiang community, Guanlan Street, Longhua, Shenzhen, China 518110
Factory's name	MOKO TECHNOLOGY LIMITED
Address	Factory 201, 107 Pinshun Rd Guixiang community, Guanlan Street, Longhua, Shenzhen, China 518110
Standard(s)	FCC 1.1310: §1.1307(b)
Test item description	Bluetooth Module
Trade Mark	MOKO SMART
Model/Type reference	MK18A, MK18B
FCC ID	2AO94-MK18
Date of receipt of test item	2025.05.14
Date (s) of performance of test:	2025.05.14- 2025.05.24
Test Report Form No.	FCC CFR Part 1_B1
Master TRF.....	Dated 2021-09
Summary of Test Results	Pass
The Summary of Test Results based on a technical opinion belongs to the standard(s).	

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SLG-CPC Testlaboratory Co., Ltd. The test results in the report only apply to the tested sample.

Table of Contents

1. EUT Specification	4
2. Test Requirement.....	5
3. Measurement Result.....	6

Modified History

Report No.	Revision Date	Summary
90475-25-72-25-PP002	2025.06.23	Original Report

1. EUT Specification

Product:	Bluetooth Module
Model Number:	MK18A, MK18B
Power supply:	<input checked="" type="checkbox"/> DC 3.3V <input type="checkbox"/> Adapter information
Modulation:	BLE(GFSK)
Frequency Range:	2402MHz~2480MHz
Number of Channels:	40channels
Antenna Gain:	MK18A :PCB antenna , 5.03dBi Gain MK18B :FPC antenna , 3.28dBi Gain
Antenna:	MK18A :PCB antenna MK18B :FPC antenna

2. Test Requirement

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where $\cdot f(\text{GHz})$ is the RF channel transmit frequency in GHz. • Power and distance are rounded to the nearest mW and mm before calculation¹⁷ • The result is rounded to one decimal place for comparison. The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

According to KDB447498D01 General RF Exposure Guidance v06
Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

3. Measurement Result

Operation Mode:	Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
				(dBm)	(mW)		
BLE 1MHz	GFSK - Lowest (2402MHz)	3.11	3±1	4	2.51	0.78	3.0
	GFSK - Middle (2440MHz)	3.98	3±1	4	2.51	0.78	
	GFSK - Highest (2480MHz)	4.01	4±1	5	3.16	1.00	
BLE 1MHz	GFSK - Lowest (2402MHz)	2.98	2±1	3	2.00	0.62	3.0
	GFSK - Middle (2440MHz)	3.20	3±1	4	2.51	0.78	
	GFSK - Highest (2480MHz)	3.86	3±1	4	2.51	0.79	

Conclusion: the calculated value ≤ 3.0 , SAR is exempted.

The Maximum power is less than the limit, complies with the exemption requirements, SAR is exempted.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: 90475-25-72-25-PP001.

THE END

声明 Statement

1. 本报告无授权批准人签字及盖章无效；

This report is invalid without the signature and seal of the authorized approver.

2. 未经许可本报告不得部分复制；

This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责；

The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.

4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用；

The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定的除外；

The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, SLG-CPC shall not assume any responsibility.

6. 对本检测报告若有异议，请于收到报告之日起 20 日内提出；

Objections shall be raised within 20 days from the date receiving the report.