

TEST REPORT

Reference No...... : WTS18S01101533-3W
FCC ID : 2AOC2-M6PLUS
Applicant..... : Procesadores y Partes en Retail S de R.L. de C.V.
Address..... : Paseo de los Laureles # 458, Ed. A Int 401 Col. Bosques de las Lomas, Deleg Cuajimalpa, Ciudad de Mexico, Mexico
Manufacturer : SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD
Address..... : A-SIDE A2 BUILDING 2/F ENET NEW INDUSTRIAL PARK, NO.20 DAFU INDUSTRIAL ZONE, AOBEL COMMUNITY, GUANLAN, LONGHUA NEW DISTRICT, SHENZHEN CHINA
Product..... : Smart Phone
Model(s) : M6 Plus
Brand Name..... : Tech Pad
Standards..... : FCC CFR47 Part 15.247: 2017
Date of Receipt sample : 2018-01-23
Date of Test : 2018-01-24 to 2018-03-09
Date of Issue..... : 2018-03-16
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Ford Wang

Ford Wang / Project Engineer

Approved by:



Philo Zhong

Philo Zhong / Manager

2 Laboratories Introduction

Waltek Services (Shenzhen) Co., Ltd is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation) of USA, Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CEC(California energy efficiency), IC(Industry Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek(ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.



Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. Electro Magnetic Compatibility (EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

Test Facility:**A. Accreditations for Conformity Assessment (International)**

Country/Region	Accreditation Body	Scope	Note
USA	A2LA (Certificate No.: 4243.01)	FCC ID \ DOC \ VOC	1
Canada		IC ID \ VOC	2
Japan		MIC-T \ MIC-R	-
Europe		EMCD \ RED	-
Taiwan		NCC	-
Hong Kong		OFCA	-
Australia		RCM	-
India		International Services	WPC
Thailand	NTC		-
Singapore	IDA		-
Note:			
1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476.			
2. IC Canada Registration No.: 7760A			

B. TCBs and Notify Bodies Recognized Testing Laboratory.

Recognized Testing Laboratory of ...	Notify body number
TUV Rheinland	Optional.
Intertek	
TUV SUD	
SGS	
Phoenix Testlab GmbH	0700
Element Materials Technology Warwick Ltd	0891
Timco Engineering, Inc.	1177
Eurofins Product Service GmbH	0681

3 Contents

	Page
1 COVER PAGE.....	1
2 LABORATORIES INTRODUCTION.....	2
3 CONTENTS	4
4 REVISION HISTORY	5
5 GENERAL INFORMATION.....	6
5.1 GENERAL DESCRIPTION OF E.U.T.	6
5.2 DETAILS OF E.U.T.	6
5.3 CHANNEL LIST	8
5.4 TEST MODE	9
6 TEST SUMMARY	10
7 EQUIPMENT USED DURING TEST	11
7.1 EQUIPMENTS LIST	11
7.2 DESCRIPTION OF SUPPORT UNITS	12
7.3 MEASUREMENT UNCERTAINTY	12
7.4 TEST EQUIPMENT CALIBRATION	12
8 CONDUCTED EMISSION	13
8.1 E.U.T. OPERATION	13
8.2 EUT SETUP.....	13
8.3 MEASUREMENT DESCRIPTION	13
8.4 CONDUCTED EMISSION TEST RESULT	14
9 RADIATED EMISSIONS.....	18
9.1 EUT OPERATION.....	18
9.2 TEST SETUP	19
9.3 SPECTRUM ANALYZER SETUP	20
9.4 TEST PROCEDURE	21
9.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	21
9.6 SUMMARY OF TEST RESULTS	22
10 CONDUCTED SPURIOUS EMISSIONS.....	38
10.1 TEST PROCEDURE.....	38
10.2 TEST RESULT	39
11 BAND EDGE MEASUREMENT	55
11.1 TEST PRODUCE	55
11.2 TEST RESULT	56
12 6 DB BANDWIDTH MEASUREMENT	61
12.1 TEST PROCEDURE:.....	61
12.2 TEST RESULT:	61
13 MAXIMUM PEAK OUTPUT POWER	70
13.1 TEST PROCEDURE:.....	70
13.2 TEST RESULT:	71
14 POWER SPECTRAL DENSITY	80
14.1 TEST PROCEDURE:.....	80
14.2 TEST RESULT:	80
15 ANTENNA REQUIREMENT	89
16 RF EXPOSURE.....	90
17 PHOTOGRAPHS OF TEST SETUP AND EUT.....	91

4 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS18S01101 533-3W	2018-01-23	2018-01-24 to 2018-03-09	2018-03-16	original	-	Valid

5 General Information

5.1 General Description of E.U.T.

Product:	Smart Phone
Model(s):	M6 Plus
Model Description:	N/A
GSM Band(s):	GSM 850/900/1800/1900MHz
GPRS/EGPRS Class:	12
WCDMA Band(s):	FDD Band II/V
LTE Band(s):	N/A
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40
Bluetooth Version:	Bluetooth v4.0 with BLE
GPS:	Support
NFC:	N/A
Hardware Version:	HCT_W178MB_A2
Software Version:	R01
Highest frequency (Exclude Radio):	1.2GHz
Storage Location:	Internal Storage
Note:	N/A

5.2 Details of E.U.T.

Operation Frequency:	GSM/GPRS/EDGE 850: 824~849MHz PCS/GPRS/EDGE 1900: 1850~1910MHz WCDMA Band II: 1850~1910MHz WCDMA Band V: 824~849MHz WiFi: 802.11b/g/n HT20: 2412~2462MHz 802.11n HT40: 2422~2452MHz Bluetooth: 2402~2480MHz
Max. RF output power:	GSM 850: 32.88dBm PCS1900: 29.79dBm WCDMA Band II: 22.82dBm WCDMA Band V: 22.86dBm WiFi(2.4G): 9.65dBm Bluetooth: 4.37dBm
Type of Modulation:	GSM,GPRS: GMSK EDGE: GMSK, 8PSK WCDMA: BPSK, 16QAM WiFi: CCK, OFDM

Antenna installation:	Bluetooth: GFSK, Pi/4 DQPSK, 8DPSK GSM/WCDMA: internal permanent antenna WiFi/Bluetooth: internal permanent antenna
Antenna Gain:	GSM 850: -1.1dBi PCS1900: -0.6dBi WCDMA Band II: -0.6dBi WCDMA Band V: -1.1dBi WiFi(2.4G): -0.7dBi Bluetooth: -0.6dBi
Ratings:	Battery DC 3.8V, 2700mAh DC 5V, 1.0A, charging from adapter (Adapter Input: 100-240V~50/60Hz 0.2A)
Adapter:	Manufacturer: Shenzhen ACT Industrial Co.,Ltd.

5.3 Channel List

WIFI

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

BT BLE

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	1	2404	2	2406	3	2408
4	2410	5	2412	6	2414	7	2416
8	2418	9	2420	10	2422	11	2424
12	2426	13	2428	14	2430	15	2432
16	2434	17	2436	18	2438	19	2440
20	2442	21	2444	22	2446	23	2448
24	2450	25	2452	26	2454	27	2456
28	2458	29	2460	30	2462	31	2464
32	2466	33	2468	34	2470	35	2472
36	2474	37	2476	38	2478	39	2480

5.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Power Spectral Density	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
6dB Bandwidth	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Band Edge	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Transmitter Spurious Emissions	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX

Table 2 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	BT BLE	1 Mbps	0/19/39	TX
Power Spectral Density	BT BLE	1 Mbps	0/19/39	TX
6dB Bandwidth	BT BLE	1 Mbps	0/19/39	TX
Band Edge	BT BLE	1 Mbps	0/19/39	TX
Transmitter Spurious Emissions	BT BLE	1 Mbps	0/19/39	TX

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product .

6 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.247(d) 15.205(a) 15.209(a)	PASS
Conducted Spurious Emissions	15.247(d)	PASS
Conducted Emissions	15.207(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3),(4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

7 Equipment Used during Test

7.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	2017-09-12	2018-09-11
2.	LISN	R&S	ENV216	101215	2017-09-12	2018-09-11
3.	Cable	Top	TYPE16(3.5M)	-	2017-09-12	2018-09-11
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	2017-09-12	2018-09-11
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	2017-09-12	2018-09-11
3.	Limiter	York	MTS-IMP-136	261115-001-0024	2017-09-12	2018-09-11
4.	Cable	LARGE	RF300	-	2017-09-12	2018-09-11
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP	100091	2017-04-29	2018-04-28
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	2017-04-09	2018-04-08
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2017-04-09	2018-04-08
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2017-09-12	2018-09-11
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2017-04-09	2018-04-08
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2017-04-09	2018-04-08
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2017-04-13	2018-04-12
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	2017-04-13	2018-04-12
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2017-04-13	2018-04-12
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2017-04-09	2018-04-08
3	Amplifier	Compliance direction systems inc	PAP-0203	22024	2017-04-13	2018-04-12
4	Cable	HUBER+SUHNER	CBL2	525178	2017-04-13	2018-04-12

RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	2017-09-12	2018-09-11
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	2017-09-12	2018-09-11
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	2017-09-12	2018-09-11

7.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

7.3 Measurement Uncertainty

Parameter	Uncertainty
Conducted Emission	± 3.64 dB(AC mains 150KHz~30MHz)
Radiated Spurious Emissions	± 5.08 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Radio Frequency	± 1 x 10 ⁻⁷ Hz
RF Power	± 0.42 dB
RF Power Density	± 0.7dB
Conducted Spurious Emissions	± 2.76 dB (9kHz~26500MHz)
Confidence interval: 95%. Confidence factor:k=2	

7.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

8 Conducted Emission

Test Requirement: FCC CFR 47 Part 15 Section 15.207
Test Method: ANSI C63.10:2013
Test Result: PASS
Frequency Range: 150kHz to 30MHz
Class/Severity: Class B
Limit:

Frequency (MHz)	Limit (dBμV)	
	uasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50


8.1 E.U.T. Operation

Operating Environment :
Temperature: 21.5 °C
Humidity: 51.9 % RH
Atmospheric Pressure: 101.2kPa

EUT Operation :
The test was performed in TX transmitting mode, the worst data were shown in the report.

8.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.



8.3 Measurement Description


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

8.4 Conducted Emission Test Result

An initial pre-scan was performed on the live and neutral lines.


Worst Mode: WIFI mode (802.11b mode low channel)

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1900	32.29	9.90	42.19	64.03	-21.84	QP	
2	0.1900	16.75	9.90	26.65	54.03	-27.38	AVG	
3	0.2580	26.45	10.01	36.46	61.49	-25.03	QP	
4	0.2580	13.01	10.01	23.02	51.49	-28.47	AVG	
5	0.5100	27.04	10.08	37.12	56.00	-18.88	QP	
6	0.5100	13.31	10.08	23.39	46.00	-22.61	AVG	
7	1.1340	27.88	10.31	38.19	56.00	-17.81	QP	
8	1.1340	15.50	10.31	25.81	46.00	-20.19	AVG	
9	3.7500	24.19	10.26	34.45	56.00	-21.55	QP	
10	3.7500	9.97	10.26	20.23	46.00	-25.77	AVG	
11	14.7540	27.02	10.38	37.40	60.00	-22.60	QP	
12	14.7540	8.37	10.38	18.75	50.00	-31.25	AVG	


Neutral line:




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1740	32.71	9.87	42.58	64.76	-22.18	QP	
2	0.1740	17.87	9.87	27.74	54.76	-27.02	AVG	
3	0.1980	31.32	9.91	41.23	63.69	-22.46	QP	
4	0.1980	17.12	9.91	27.03	53.69	-26.66	AVG	
5	0.5140	30.59	10.08	40.67	56.00	-15.33	QP	
6	0.5140	18.37	10.08	28.45	46.00	-17.55	AVG	
7	1.0900	31.22	10.24	41.46	56.00	-14.54	QP	
8	1.0900	15.46	10.24	25.70	46.00	-20.30	AVG	
9	4.7540	27.06	10.25	37.31	56.00	-18.69	QP	
10	4.7540	11.16	10.25	21.41	46.00	-24.59	AVG	
11	14.9180	19.05	10.38	29.43	60.00	-30.57	QP	
12	14.9180	5.15	10.38	15.53	50.00	-34.47	AVG	

Worst Mode: BLE mode (low channel)

Live line:



Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1740	33.24	9.87	43.11	64.76	-21.65	QP	
2	0.1740	18.17	9.87	28.04	54.76	-26.72	AVG	
3	0.5100	30.95	10.08	41.03	56.00	-14.97	QP	
4	0.5100	17.71	10.08	27.79	46.00	-18.21	AVG	
5	1.0820	31.56	10.23	41.79	56.00	-14.21	QP	
6	1.0820	15.85	10.23	26.08	46.00	-19.92	AVG	
7	2.3820	22.52	10.22	32.74	56.00	-23.26	QP	
8	2.3820	12.27	10.22	22.49	46.00	-23.51	AVG	
9	3.7620	26.33	10.26	36.59	56.00	-19.41	QP	
10	3.7620	10.46	10.26	20.72	46.00	-25.28	AVG	
11	14.9940	18.31	10.38	28.69	60.00	-31.31	QP	
12	14.9940	3.87	10.38	14.25	50.00	-35.75	AVG	

9 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

9.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in TX transmitting mode, the test data were shown in the report.


9.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



9.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
 IF Bandwidth.....10kHz
 Video Bandwidth.....10kHz
 Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep Speed Auto
 DetectorPK
 Resolution Bandwidth.....100kHz
 Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed Auto
 DetectorPK
 Resolution Bandwidth.....1MHz
 Video Bandwidth.....3MHz
 DetectorAve.
 Resolution Bandwidth.....1MHz
 Video Bandwidth.....10Hz

9.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

9.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

9.6 Summary of Test Results

Wifi:

Test Frequency: 9KHz~30MHz

Remark: only the worst data (802.11b/g/n Low channel mode) were recorded.

Frequency	Measurement results dBμV @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dBμV/m @30m	Limits dBμV/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
802.11b							
6.031	25.36	QP	21.84	40.00	7.20	29.54	-22.34
15.730	25.40	QP	21.35	40.00	6.75	29.54	-22.79
25.680	24.58	QP	20.67	40.00	5.25	29.54	-24.29
802.11g							
6.031	25.84	QP	21.84	40.00	7.68	29.54	-21.86
15.730	25.31	QP	21.35	40.00	6.66	29.54	-22.88
25.680	24.75	QP	20.67	40.00	5.42	29.54	-24.12
802.11n(HT20)							
6.031	25.37	QP	21.84	40.00	7.21	29.54	-22.33
15.730	25.29	QP	21.35	40.00	6.64	29.54	-22.90
25.680	24.84	QP	20.67	40.00	5.51	29.54	-24.03
802.11n(HT40)							
6.031	25.21	QP	21.84	40.00	7.05	29.54	-22.49
15.730	25.64	QP	21.35	40.00	6.99	29.54	-22.55
25.680	24.68	QP	20.67	40.00	5.35	29.54	-24.19

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Low Channel 2412MHz									
223.45	41.05	QP	49	1.8	H	-11.62	29.43	46.00	-16.57
223.45	36.26	QP	24	1.4	V	-11.62	24.64	46.00	-21.36
4824.00	50.44	PK	180	1.6	V	-1.06	49.38	74.00	-24.62
4824.00	46.32	Ave	180	1.6	V	-1.06	45.26	54.00	-8.74
7236.00	41.08	PK	298	1.6	H	1.33	42.41	74.00	-31.59
7236.00	41.96	Ave	298	1.6	H	1.33	43.29	54.00	-10.71
2325.58	45.89	PK	235	2.0	V	-13.19	32.70	74.00	-41.30
2325.58	38.93	Ave	235	2.0	V	-13.19	25.74	54.00	-28.26
2386.78	43.96	PK	121	1.6	H	-13.14	30.82	74.00	-43.18
2386.78	37.91	Ave	121	1.6	H	-13.14	24.77	54.00	-29.23
2484.01	44.45	PK	102	1.8	V	-13.08	31.37	74.00	-42.63
2484.01	38.82	Ave	102	1.8	V	-13.08	25.74	54.00	-28.26

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Middle Channel 2437MHz									
223.45	39.90	QP	250	1.2	H	-11.62	28.28	46.00	-17.72
223.45	36.37	QP	95	1.9	V	-11.62	24.75	46.00	-21.25
4874.00	50.49	PK	75	1.4	V	-0.62	49.87	74.00	-24.13
4874.00	45.73	Ave	75	1.4	V	-0.62	45.11	54.00	-8.89
7311.00	42.54	PK	63	1.4	H	2.21	44.75	74.00	-29.25
7311.00	40.89	Ave	63	1.4	H	2.21	43.10	54.00	-10.90
2325.60	45.58	PK	51	1.1	V	-13.19	32.39	74.00	-41.61
2325.60	37.64	Ave	51	1.1	V	-13.19	24.45	54.00	-29.55
2350.63	43.19	PK	237	1.1	H	-13.14	30.05	74.00	-43.95
2350.63	36.35	Ave	237	1.1	H	-13.14	23.21	54.00	-30.79
2489.17	44.39	PK	225	1.2	V	-13.08	31.31	74.00	-42.69
2489.17	38.37	Ave	225	1.2	V	-13.08	25.29	54.00	-28.71

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: High Channel 2462MHz									
223.45	40.98	QP	23	1.5	H	-11.62	29.36	46.00	-16.64
223.45	37.36	QP	97	1.9	V	-11.62	25.74	46.00	-20.26
4924.00	50.16	PK	113	1.7	V	-0.24	49.92	74.00	-24.08
4924.00	46.67	Ave	113	1.7	V	-0.24	46.43	54.00	-7.57
7386.00	43.36	PK	302	1.5	H	2.84	46.20	74.00	-27.80
7386.00	40.70	Ave	302	1.5	H	2.84	43.54	54.00	-10.46
2340.80	46.08	PK	166	1.0	V	-13.19	32.89	74.00	-41.11
2340.80	38.35	Ave	166	1.0	V	-13.19	25.16	54.00	-28.84
2352.34	44.43	PK	46	1.8	H	-13.14	31.29	74.00	-42.71
2352.34	37.82	Ave	46	1.8	H	-13.14	24.68	54.00	-29.32
2490.03	44.81	PK	6	1.4	V	-13.08	31.73	74.00	-42.27
2490.03	36.88	Ave	6	1.4	V	-13.08	23.80	54.00	-30.20

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Low Channel 2412MHz									
223.45	41.18	QP	209	2.0	H	-11.62	29.56	46.00	-16.44
223.45	37.67	QP	50	1.7	V	-11.62	26.05	46.00	-19.95
4824.00	49.69	PK	95	1.3	V	-1.06	48.63	74.00	-25.37
4824.00	45.30	Ave	95	1.3	V	-1.06	44.24	54.00	-9.76
7236.00	42.80	PK	324	1.7	H	1.33	44.13	74.00	-29.87
7236.00	42.07	Ave	324	1.7	H	1.33	43.40	54.00	-10.60
2338.17	46.45	PK	157	1.2	V	-13.19	33.26	74.00	-40.74
2338.17	37.63	Ave	157	1.2	V	-13.19	24.44	54.00	-29.56
2373.33	42.95	PK	101	1.5	H	-13.14	29.81	74.00	-44.19
2373.33	38.58	Ave	101	1.5	H	-13.14	25.44	54.00	-28.56
2485.51	43.96	PK	219	1.5	V	-13.08	30.88	74.00	-43.12
2485.51	37.04	Ave	219	1.5	V	-13.08	23.96	54.00	-30.04

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Middle Channel 2437MHz									
223.45	41.45	QP	70	1.0	H	-11.62	29.83	46.00	-16.17
223.45	38.27	QP	284	1.9	V	-11.62	26.65	46.00	-19.35
4874.00	49.61	PK	208	1.7	V	-0.62	48.99	74.00	-25.01
4874.00	43.83	Ave	208	1.7	V	-0.62	43.21	54.00	-10.79
7311.00	44.27	PK	264	1.6	H	2.21	46.48	74.00	-27.52
7311.00	41.97	Ave	264	1.6	H	2.21	44.18	54.00	-9.82
2317.32	45.11	PK	116	1.0	V	-13.19	31.92	74.00	-42.08
2317.32	39.69	Ave	116	1.0	V	-13.19	26.50	54.00	-27.50
2372.91	43.11	PK	224	1.0	H	-13.14	29.97	74.00	-44.03
2372.91	38.91	Ave	224	1.0	H	-13.14	25.77	54.00	-28.23
2490.26	43.42	PK	57	1.8	V	-13.08	30.34	74.00	-43.66
2490.26	37.95	Ave	57	1.8	V	-13.08	24.87	54.00	-29.13

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: High Channel 2462MHz									
223.45	40.73	QP	235	1.8	H	-11.62	29.11	46.00	-16.89
223.45	39.67	QP	247	1.8	V	-11.62	28.05	46.00	-17.95
4924.00	50.85	PK	233	1.9	V	-0.24	50.61	74.00	-23.39
4924.00	44.97	Ave	233	1.9	V	-0.24	44.73	54.00	-9.27
7386.00	43.44	PK	109	1.3	H	2.84	46.28	74.00	-27.72
7386.00	41.44	Ave	109	1.3	H	2.84	44.28	54.00	-9.72
2348.80	46.91	PK	110	1.4	V	-13.19	33.72	74.00	-40.28
2348.80	39.25	Ave	110	1.4	V	-13.19	26.06	54.00	-27.94
2356.66	44.41	PK	129	1.3	H	-13.14	31.27	74.00	-42.73
2356.66	37.60	Ave	129	1.3	H	-13.14	24.46	54.00	-29.54
2484.50	42.15	PK	338	1.0	V	-13.08	29.07	74.00	-44.93
2484.50	37.87	Ave	338	1.0	V	-13.08	24.79	54.00	-29.21

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: Low Channel 2412MHz									
223.45	39.28	QP	248	1.8	H	-11.62	27.66	46.00	-18.34
223.45	40.48	QP	289	1.8	V	-11.62	28.86	46.00	-17.14
4824.00	49.94	PK	139	2.0	V	-1.06	48.88	74.00	-25.12
4824.00	45.82	Ave	139	2.0	V	-1.06	44.76	54.00	-9.24
7236.00	43.55	PK	240	1.9	H	1.33	44.88	74.00	-29.12
7236.00	40.17	Ave	240	1.9	H	1.33	41.50	54.00	-12.50
2345.06	46.55	PK	167	1.9	V	-13.19	33.36	74.00	-40.64
2345.06	39.44	Ave	167	1.9	V	-13.19	26.25	54.00	-27.75
2388.95	44.80	PK	229	1.8	H	-13.14	31.66	74.00	-42.34
2388.95	36.05	Ave	229	1.8	H	-13.14	22.91	54.00	-31.09
2499.00	43.11	PK	197	1.6	V	-13.08	30.03	74.00	-43.97
2499.00	36.22	Ave	197	1.6	V	-13.08	23.14	54.00	-30.86

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: Middle Channel 2437MHz									
223.45	40.28	QP	235	1.8	H	-11.62	28.66	46.00	-17.34
223.45	41.21	QP	171	1.8	V	-11.62	29.59	46.00	-16.41
4874.00	50.37	PK	316	1.3	V	-0.62	49.75	74.00	-24.25
4874.00	44.91	Ave	316	1.3	V	-0.62	44.29	54.00	-9.71
7311.00	44.37	PK	340	1.5	H	2.21	46.58	74.00	-27.42
7311.00	41.05	Ave	340	1.5	H	2.21	43.26	54.00	-10.74
2321.33	46.85	PK	225	1.2	V	-13.19	33.66	74.00	-40.34
2321.33	39.70	Ave	225	1.2	V	-13.19	26.51	54.00	-27.49
2386.91	44.85	PK	73	1.5	H	-13.14	31.71	74.00	-42.29
2386.91	37.42	Ave	73	1.5	H	-13.14	24.28	54.00	-29.72
2484.59	43.13	PK	121	1.5	V	-13.08	30.05	74.00	-43.95
2484.59	36.51	Ave	121	1.5	V	-13.08	23.43	54.00	-30.57

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: High Channel 2462MHz									
223.45	40.56	QP	355	1.3	H	-11.62	28.94	46.00	-17.06
223.45	41.33	QP	160	1.9	V	-11.62	29.71	46.00	-16.29
4924.00	49.03	PK	23	1.3	V	-0.24	48.79	74.00	-25.21
4924.00	45.40	Ave	23	1.3	V	-0.24	45.16	54.00	-8.84
7386.00	43.19	PK	306	1.1	H	2.84	46.03	74.00	-27.97
7386.00	40.16	Ave	306	1.1	H	2.84	43.00	54.00	-11.00
2341.53	46.41	PK	337	2.0	V	-13.19	33.22	74.00	-40.78
2341.53	38.67	Ave	337	2.0	V	-13.19	25.48	54.00	-28.52
2365.91	42.23	PK	359	1.2	H	-13.14	29.09	74.00	-44.91
2365.91	36.19	Ave	359	1.2	H	-13.14	23.05	54.00	-30.95
2491.78	42.44	PK	259	1.8	V	-13.08	29.36	74.00	-44.64
2491.78	38.31	Ave	259	1.8	V	-13.08	25.23	54.00	-28.77

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: Low Channel 2422MHz									
223.45	40.37	QP	154	1.2	H	-11.62	28.75	46.00	-17.25
223.45	41.35	QP	30	1.8	V	-11.62	29.73	46.00	-16.27
4844.00	47.30	PK	80	1.3	V	-1.06	46.24	74.00	-27.76
4844.00	43.75	Ave	80	1.3	V	-1.06	42.69	54.00	-11.31
7266.00	40.42	PK	291	1.8	H	1.33	41.75	74.00	-32.25
7266.00	37.95	Ave	291	1.8	H	1.33	39.28	54.00	-14.72
2311.54	45.61	PK	315	2.0	V	-13.19	32.42	74.00	-41.58
2311.54	39.43	Ave	315	2.0	V	-13.19	26.24	54.00	-27.76
2382.36	43.73	PK	359	1.4	H	-13.14	30.59	74.00	-43.41
2382.36	38.76	Ave	359	1.4	H	-13.14	25.62	54.00	-28.38
2498.92	43.12	PK	335	1.2	V	-13.08	30.04	74.00	-43.96
2498.92	36.43	Ave	335	1.2	V	-13.08	23.35	54.00	-30.65

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: Middle Channel 2437MHz									
223.45	40.05	QP	251	1.8	H	-11.62	28.43	46.00	-17.57
223.45	40.68	QP	229	1.2	V	-11.62	29.06	46.00	-16.94
4874.00	47.69	PK	312	1.0	V	-0.62	47.07	74.00	-26.93
4874.00	43.23	Ave	312	1.0	V	-0.62	42.61	54.00	-11.39
7311.00	40.30	PK	118	1.1	H	2.21	42.51	74.00	-31.49
7311.00	38.04	Ave	118	1.1	H	2.21	40.25	54.00	-13.75
2322.39	45.10	PK	91	1.2	V	-13.19	31.91	74.00	-42.09
2322.39	38.77	Ave	91	1.2	V	-13.19	25.58	54.00	-28.42
2376.60	42.98	PK	330	1.5	H	-13.14	29.84	74.00	-44.16
2376.60	38.82	Ave	330	1.5	H	-13.14	25.68	54.00	-28.32
2499.98	42.05	PK	258	1.7	V	-13.08	28.97	74.00	-45.03
2499.98	36.31	Ave	258	1.7	V	-13.08	23.23	54.00	-30.77

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: High Channel 2452MHz									
223.45	40.32	QP	59	1.2	H	-11.62	28.70	46.00	-17.30
223.45	40.33	QP	341	1.1	V	-11.62	28.71	46.00	-17.29
4904.00	48.38	PK	164	1.5	V	-0.24	48.14	74.00	-25.86
4904.00	43.83	Ave	164	1.5	V	-0.24	43.59	54.00	-10.41
7356.00	40.33	PK	353	1.2	H	2.84	43.17	74.00	-30.83
7356.00	37.44	Ave	353	1.2	H	2.84	40.28	54.00	-13.72
2338.15	45.67	PK	122	1.3	V	-13.19	32.48	74.00	-41.52
2338.15	37.21	Ave	122	1.3	V	-13.19	24.02	54.00	-29.98
2373.18	43.27	PK	254	1.9	H	-13.14	30.13	74.00	-43.87
2373.18	38.66	Ave	254	1.9	H	-13.14	25.52	54.00	-28.48
2494.94	43.69	PK	48	1.0	V	-13.08	30.61	74.00	-43.39
2494.94	38.87	Ave	48	1.0	V	-13.08	25.79	54.00	-28.21

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

BT BLE:**Test Frequency: 9KHz~26MHz**

Remark: only the worst data (GFSK modulation Low channel mode) were recorded.

Frequency	Measurement results dBμV @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dBμV/m @30m	Limits dBμV/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
6.031	25.47	QP	21.84	40.00	7.31	29.54	-22.23
15.730	25.96	QP	21.35	40.00	7.31	29.54	-22.23
25.680	24.73	QP	20.67	40.00	5.40	29.54	-24.14

Test Frequency : 26MHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Low Channel 2402MHz									
269.33	34.12	QP	31	1.2	H	-13.35	20.77	46.00	-25.23
269.33	40.18	QP	312	1.4	V	-13.35	26.83	46.00	-19.17
4804.00	45.30	PK	136	1.5	V	-1.06	44.24	74.00	-29.76
4804.00	42.18	Ave	136	1.5	V	-1.06	41.12	54.00	-12.88
7206.00	45.20	PK	197	1.2	H	1.33	46.53	74.00	-27.47
7206.00	36.79	Ave	197	1.2	H	1.33	38.12	54.00	-15.88
2332.05	45.42	PK	265	1.6	V	-13.19	32.23	74.00	-41.77
2332.05	38.25	Ave	265	1.6	V	-13.19	25.06	54.00	-28.94
2350.27	42.12	PK	124	1.1	H	-13.14	28.98	74.00	-45.02
2350.27	38.78	Ave	124	1.1	H	-13.14	25.64	54.00	-28.36
2499.06	44.64	PK	179	1.8	V	-13.08	31.56	74.00	-42.44
2499.06	38.53	Ave	179	1.8	V	-13.08	25.45	54.00	-28.55

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Middle Channel 2440MHz									
269.33	34.83	QP	125	1.3	H	-13.35	21.48	46.00	-24.52
269.33	39.16	QP	241	2.0	V	-13.35	25.81	46.00	-20.19
4880.00	43.46	PK	339	1.2	V	-0.62	42.84	74.00	-31.16
4880.00	42.57	Ave	339	1.2	V	-0.62	41.95	54.00	-12.05
7320.00	45.07	PK	137	2.0	H	2.21	47.28	74.00	-26.72
7320.00	36.08	Ave	137	2.0	H	2.21	38.29	54.00	-15.71
2330.63	45.61	PK	330	1.9	V	-13.19	32.42	74.00	-41.58
2330.63	38.36	Ave	330	1.9	V	-13.19	25.17	54.00	-28.83
2387.45	42.69	PK	22	1.0	H	-13.14	29.55	74.00	-44.45
2387.45	36.56	Ave	22	1.0	H	-13.14	23.42	54.00	-30.58
2489.34	43.83	PK	58	1.1	V	-13.08	30.75	74.00	-43.25
2489.34	38.03	Ave	58	1.1	V	-13.08	24.95	54.00	-29.05

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
GFSK High Channel 2480MHz									
269.33	34.64	QP	56	1.2	H	-13.35	21.29	46.00	-24.71
269.33	38.46	QP	236	1.4	V	-13.35	25.11	46.00	-20.89
4960.00	43.47	PK	157	1.8	V	-0.24	43.23	74.00	-30.77
4960.00	41.48	Ave	157	1.8	V	-0.24	41.24	54.00	-12.76
7440.00	43.81	PK	77	1.1	H	2.84	46.65	74.00	-27.35
7440.00	36.29	Ave	77	1.1	H	2.84	39.13	54.00	-14.87
2337.12	46.14	PK	262	1.8	V	-13.19	32.95	74.00	-41.05
2337.12	38.31	Ave	262	1.8	V	-13.19	25.12	54.00	-28.88
2369.43	42.41	PK	46	1.6	H	-13.14	29.27	74.00	-44.73
2369.43	37.24	Ave	46	1.6	H	-13.14	24.10	54.00	-29.90
2488.00	43.25	PK	270	1.3	V	-13.08	30.17	74.00	-43.83
2488.00	38.78	Ave	270	1.3	V	-13.08	25.70	54.00	-28.30

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

10 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017
Test Result: PASS
Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:

Blow 30MHz:

RBW = 100kHz, VBW = 300kHz, Sweep = auto

Detector function = peak, Trace = max hold

Above 1GHz:

For WIFI mode

RBW = 100kHz, VBW = 300kHz, Sweep = auto

Detector function = peak, Trace = max hold

For BLE mode

RBW = 100kHz, VBW = 300kHz, Sweep = auto


Detector function = peak, Trace = max hold

10.2 Test Result


9KHz – 30MHz



802.11b



Low Channel




Middle Channel












802.11n HT20
Low Channel



Middle Channel










BLE

Low Channel




Middle Channel






Above 30MHz
802.11b
Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11g


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11n HT20


Low Channel

Fundamental



Middle Channel

Fundamental



High Channel


Fundamental



802.11n HT40


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



BLE


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel

Fundamental



11 Band Edge Measurement



Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017
Test Limit:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting

11.1 Test Produce


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

11.2 Test Result


Test result plots shown as follows:







TX 11g: Band edge-left side





TX 11g: Band edge-right side









12 6 dB Bandwidth Measurement

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017



12.1 Test Procedure:



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz



12.2 Test Result:



Operation mode	Test Channel	Bandwidth (MHz)
TX 11b	Channel 1	10.060
	Channel 6	10.060
	Channel 11	10.060
TX 11g	Channel 1	16.467
	Channel 6	16.417
	Channel 11	16.467
TX 11n HT20	Channel 1	17.623
	Channel 6	17.623
	Channel 11	17.623
TX 11n HT40	Channel 3	35.890
	Channel 6	35.890
	Channel 9	35.890
BLE	Channel 0	0.725
	Channel 19	0.731
	Channel 39	0.725



Test result plot:






















13 Maximum Peak Output Power

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017

13.1 Test Procedure:

KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017

section 9.1.1 (For BLE)

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the $RBW \geq DTS \text{ bandwidth}$.
- b) Set $VBW \geq 3 \times RBW$.
- c) Set $span \geq 3 \times RBW$
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

section 9.1.2 (For WIFI)

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.


- a) Set the $RBW = 1 \text{ MHz}$.
- b) Set the $VBW \geq 3 \times RBW$
- c) Set the $span \geq 1.5 \times DTS \text{ bandwidth}$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.

13.2 Test Result:


Operation mode	Channel Frequency (MHz)	Maximum Peak Output Power (dBm)	Limit
TX 11b	Low-2412	9.32	1W/30dBm
	Middle-2437	9.56	1W/30dBm
	High-2462	9.32	1W/30dBm
TX 11g	Low-2412	9.42	1W/30dBm
	Middle-2437	9.48	1W/30dBm
	High-2462	9.62	1W/30dBm
TX 11n HT20	Low-2412	9.50	1W/30dBm
	Middle-2437	9.31	1W/30dBm
	High-2462	9.56	1W/30dBm
TX 11n HT40	Low-2422	9.60	1W/30dBm
	Middle-2437	9.65	1W/30dBm
	High-2452	9.61	1W/30dBm
BLE	Low-2402	-3.70	1W/30dBm
	Middle-2440	-3.04	1W/30dBm
	High-2480	-4.83	1W/30dBm



Test Plot



Mode: TX 11b channel 1







Mode: TX 11b channel 6






















14 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017



14.1 Test Procedure:



KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017 section 10.2



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.



14.2 Test Result:



Operation mode	Channel Frequency (MHz)	Power Spectral (dBm per 3kHz)	Limit
TX 11b	Low-2412	-16.78	8dBm per 3kHz
	Middle-2437	-16.08	8dBm per 3kHz
	High-2462	-16.38	8dBm per 3kHz
TX 11g	Low-2412	-23.59	8dBm per 3kHz
	Middle-2437	-24.40	8dBm per 3kHz
	High-2462	-24.39	8dBm per 3kHz
TX 11n HT20	Low-2412	-24.20	8dBm per 3kHz
	Middle-2437	-24.15	8dBm per 3kHz
	High-2462	-24.39	8dBm per 3kHz
TX 11n HT40	Low-2422	-26.63	8dBm per 3kHz
	Middle-2437	-25.85	8dBm per 3kHz
	High-2452	-26.99	8dBm per 3kHz
BLE	Low-2402	-19.15	8dBm per 3kHz
	Middle-2440	-18.77	8dBm per 3kHz
	High-2480	-20.59	8dBm per 3kHz






















15 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfill the requirement of this section.

16 RF Exposure

Remark: refer to SAR test report: WTS18S01101533-1W.

17 Photographs of test setup and EUT.

Note: Please refer to appendix: WTS18S01101533W_Photo.

=====End of Report=====