

BRUNT

Mode 5 | Mode 7

Airjet

Your Air Purifier, Not for All

www.brunt.co

[illegible]

Package Content		Product Manual	
	Read the Manual for the hardware		Read the Manual for the software
	Power Cord (10A/125V) (depending on region)		Power Cord
	Power Cord (15A/250V) (depending on region)		Power Cord (15A/250V) (depending on region)
	Power Cord (15A/250V) (depending on region)		Power Cord (15A/250V) (depending on region)
	Power Cord (15A/250V) (depending on region)		Power Cord (15A/250V) (depending on region)
	Power Cord (15A/250V) (depending on region)		Power Cord (15A/250V) (depending on region)
	Power Cord (15A/250V) (depending on region)		Power Cord (15A/250V) (depending on region)
	Power Cord (15A/250V) (depending on region)		Power Cord (15A/250V) (depending on region)
	Power Cord (15A/250V) (depending on region)		Power Cord (15A/250V) (depending on region)
	Power Cord (15A/250V) (depending on region)		Power Cord (15A/250V) (depending on region)
	Power Cord (15A/250V) (depending on region)		Power Cord (15A/250V) (depending on region)
	Power Cord (15A/250V) (depending on region)		Power Cord (15A/250V) (depending on region)
	Power Cord (15A/250V) (depending on region)		Power Cord (15A/250V) (depending on region)
	Power Cord (15A/250V) (depending on region)		Power Cord (15A/250V) (depending on region)

H/W Functions

1) Power / Speed Button

	1	2	3	4	5	Hold 5 Sec
Appt's	Auto	Speed 1	Speed 2	Speed 3	Power Off	WV-Compressor Auto (10 min)
Appt's	Auto	Speed 1	Speed 2	Speed 3	Power Off	Child Lock (10 min)

* (Indicator for Speed): Speed the slower it reads it tends to dry even with all 4 nozzles open.

2) Power LED

	LED-Off	Green	Red
LED-Off	On	LED Blinking (10 min)	LED Blinking (10 min)
Appt's	Power Off (10 min)	Auto (10 min)	WV-Compressor (10 min) Child Lock (10 min)
Appt's	Power Off (10 min)	Auto (10 min)	WV-Compressor (10 min) Child Lock (10 min)

3) Air Control LED (Appt's)

	LED Blinking (10 min)	LED Blinking (10 min)	LED Blinking (10 min)
Appt's	On	On	On
Appt's	On	On	On

4) Car Lock Take off the cap and the cap is open to change the Appt.

5) Top Cover Appt Do not open anything including finger pad the cap top cover will damage the performance.

6) Leaking Hole Very hardy for leaking the Appt.


7) Make Off Make this include a good seal and the cap will stop the water if it springs holes and hole the cap. Appt will stop the water to perform properly.

How to Change the Filter


Most of Apigs are equipped with a color replacement system, which is a ribbon changing filter process. A filter means a banderole. For re-assembling, please follow the steps below.



1. Take Off
Take off the top cap from the top of the Apig.




2. Disconnect
Put the top cap on the side and pull the cap-NOV to separate the cover gill.




3. Take Out
Take out the filter.

Important Notes for Changing the Filter


Before you change the filter, please unplug the adaptor and make sure that the propeller is stopped.



Preventing Damage



Inside the Body



Assembly

Be careful assembling the cover gill back into the body because on the body, there is a notch for the gear and the gill. Otherwise, it can cause the damage on the Apigs.

IoT Smart Functions (Aijiet5 Only)

Based on AI5, through the smart functions, you can realize smart functions as well as remote control of the appliance.

Mobile Control (Wi-Fi)	Monitoring Interior, Outdoor, Camera / Weather, etc.	Troubleshooting Getting the problem solved in all of the appliance	Location Registration Control GPS location to control the appliance in all of the places for the device	Visual Control Watch Aijiet5 Appliance from the Internet
--	--	--	---	--

Smartphone Control Guide

*For more information on connecting your smartphone and the Appt, please see additional instructions for each application (Wi-Fi)

Download the
Appt from
Google Play
or the
App Store

2. Tap to Login

To connect your smartphone
with Appt, please tap to login
to Appt application first.

3. Connecting to Appt Wi-Fi

Go to Appt's Wi-Fi page
to connect your smartphone
to connect with your
Appt first.

4. Remote Controlling

When the connection is completed,
you can control the Appt
as well as remote control of
your appliance.

Pro Stand

Use the device you got for changing the direction of its purified air. Aijiet5 can also be directly blow into your face (This does not require a wire or a cordless).



[illegible][illegible][illegible]

IoTサービス機能（エアージャスト5専用）

エアージャストは様々なIoTサービスと連携し、様々なIoTサービスを利用することができます。








スマートフォン連携	クラウド連携	Wi-Fi連携	音声連携
   スマートフォン連携 Apple Storeから「IoTエアージャスト」アプリをダウンロードしてご利用ください。	 スマートフォン連携 専用アプリをダウンロードしてご利用ください。	 Wi-Fi連携 エアージャストはWi-Fiに接続してご利用ください。	 音声連携 エアージャストは、スマートスピーカーと連携してご利用ください。

支社(向きを要する)

新設する支社がない場合にも対応することができます。

詳しくはこちらをご覧ください。





[illegible][illegible]

하드웨어 기능 설명

① 머리 밴드

부품	1번	2번	3번	4번	5번	장착 상태
헤드밴드	3.0H	2.52	4.21	4.01	3.99-0.01	헤드밴드 높이는 2.52~4.21mm 범위 내에서 조정 가능
헤드밴드	5.3	2.51	3.72	4.01	3.99-0.01	-

* 3.72mm 이하의 크기로 조정할 수 없습니다 (헤드밴드 4번과 5번은 제외)

② 전면 렌즈

	렌즈 (L1)	표준 렌즈 (L2)	대형 렌즈 (L3)	대형 렌즈 (L4)	필드 렌즈 (L5)
렌즈 크기	3.0x3.0	3.0x3.0	3.0x3.0	3.0x3.0	3.0x3.0
렌즈 두께	2.0mm 이하	2.0mm 이하	2.0mm 이하	2.0mm 이하	2.0mm 이하
렌즈 재료	투명 플라스틱	투명 플라스틱	투명 플라스틱	투명 플라스틱	투명 플라스틱

③ 렌즈 선택 (L1부터 L5까지)

1) L1부터 L5까지의 렌즈를 선택할 수 있습니다 / 두 렌즈를 모두 선택할 수 없습니다

렌즈 선택	필드	표준	대형	표준	필드
렌즈 번호	1번	1번	1번	1번	1번

* 렌즈 번호 1번은 렌즈 L1부터 L5까지를 모두 지정할 수 없습니다 (렌즈 L1부터 L5까지를 모두 지정할 수 없습니다)

④ 렌즈 위치

렌즈 L1과 L2의 위치는 고정되고 L3, L4, L5의 위치는 조정 가능합니다

⑤ 고정 장치

렌즈를 렌즈 위치에서 이동할 수 없습니다

⑥ 렌즈 고정

렌즈를 렌즈 위치에서 이동할 수 없습니다

⑦ 렌즈 고정 장치

렌즈를 렌즈 위치에서 이동할 수 없습니다

필터 분리하기

비커, 약병, 용기 등 주입 용기를 세척하는 것은 매우 간단하며 거의 모든 용기들로 실행 가능합니다.

본 제품을 사용할 때는 다음 3가지 단계를 실행하십시오.

1. 필터 분리하기
2. 용기 세척을 위한 물 추가
3. 필터 분리

필터는 12시간 동안 건조하십시오.

필터 교체 시 주의 사항

필터 교체 시 다음 3가지 단계를 반드시 순서대로 실행하는 것은 필수로 확인하고 교체하십시오.

1. 용기 세척을 위한 물 추가
2. 용기 세척을 위한 물 추가
3. 필터 분리

용기 세척을 위한 물 추가 시 반드시 12시간 동안 건조하십시오.

용기 세척을 위한 물 추가 시 반드시 12시간 동안 건조하십시오.

용기 세척을 위한 물 추가 시 반드시 12시간 동안 건조하십시오.

[illegible][illegible]