



SAR TEST REPORT

No. I18Z61597-SEM01

For

Palm Ventures Group

HSUPA/HSDPA/UMTS Quad Band/GSM Quad Band/LTE 5 Bands mobile phone

Model Name: PVG100E/PVG100EU

With

Hardware Version: 03

Software Version: 3B1K-1

FCC ID: 2AOETPVG100E

Issued Date: 2018-11-13



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 51, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



REPORT HISTORY

Report Number	Revision	Issue Date	Description
I18Z61597-SEM01	Rev.0	2018-10-17	Initial creation of test report
I18Z61597-SEM01	Rev.1	2018-11-13	Remove 750MHz dipole calibration report

TABLE OF CONTENT

1 TEST LABORATORY	5
1.1 TESTING LOCATION	5
1.2 TESTING ENVIRONMENT	5
1.3 PROJECT DATA	5
1.4 SIGNATURE	5
2 STATEMENT OF COMPLIANCE	6
3 CLIENT INFORMATION	8
3.1 APPLICANT INFORMATION	8
3.2 MANUFACTURER INFORMATION	8
4 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	9
4.1 ABOUT EUT	9
4.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	9
4.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	9
5 TEST METHODOLOGY	10
5.1 APPLICABLE LIMIT REGULATIONS	10
5.2 APPLICABLE MEASUREMENT STANDARDS	10
6 SPECIFIC ABSORPTION RATE (SAR)	11
6.1 INTRODUCTION	11
6.2 SAR DEFINITION	11
7 TISSUE SIMULATING LIQUIDS	12
7.1 TARGETS FOR TISSUE SIMULATING LIQUID	12
7.2 DIELECTRIC PERFORMANCE	12
8 SYSTEM VERIFICATION	17
8.1 SYSTEM SETUP	17
8.2 SYSTEM VERIFICATION	18
9 MEASUREMENT PROCEDURES	19
9.1 TESTS TO BE PERFORMED	19
9.2 GENERAL MEASUREMENT PROCEDURE	21
9.3 WCDMA MEASUREMENT PROCEDURES FOR SAR	22
9.4 SAR MEASUREMENT FOR LTE	23
9.5 BLUETOOTH & Wi-FI MEASUREMENT PROCEDURES FOR SAR	23
9.6 POWER DRIFT	24
10 AREA SCAN BASED 1-G SAR	24
10.1 REQUIREMENT OF KDB	24
10.2 FAST SAR ALGORITHMS	24
11 CONDUCTED OUTPUT POWER	25

11.1	GSM MEASUREMENT RESULT	25
11.2	WCDMA MEASUREMENT RESULT.....	26
11.3	LTE MEASUREMENT RESULT	28
11.4	Wi-Fi AND BT MEASUREMENT RESULT	34
12	SIMULTANEOUS TX SAR CONSIDERATIONS	38
12.1	INTRODUCTION.....	38
12.2	TRANSMIT ANTENNA SEPARATION DISTANCES	38
12.3	SAR MEASUREMENT POSITIONS	39
12.4	STANDALONE SAR TEST EXCLUSION CONSIDERATIONS.....	39
13	EVALUATION OF SIMULTANEOUS.....	40
14	SAR TEST RESULT	41
14.1	SAR RESULTS	41
14.2	FULL SAR	49
14.3	WLAN EVALUATION.....	50
15	SAR MEASUREMENT VARIABILITY	53
16	MEASUREMENT UNCERTAINTY	54
16.1	MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (300MHz~3GHz)	54
16.2	MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (3~6GHz).....	55
16.3	MEASUREMENT UNCERTAINTY FOR FAST SAR TESTS (300MHz~3GHz).....	56
16.4	MEASUREMENT UNCERTAINTY FOR FAST SAR TESTS (3~6GHz)	57
17	MAIN TEST INSTRUMENTS.....	59
ANNEX A	GRAPH RESULTS.....	60
ANNEX B	SYSTEM VERIFICATION RESULTS.....	79
ANNEX C	SAR MEASUREMENT SETUP	88
ANNEX D	POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM	94
ANNEX E	EQUIVALENT MEDIA RECIPES	97
ANNEX F	SYSTEM VALIDATION	98
ANNEX G	PROBE CALIBRATION CERTIFICATE	99
ANNEX H	DIPOLE CALIBRATION CERTIFICATE.....	110
ANNEX I	EXTENDED CALIBRATION SAR DIPOLE.....	142
ANNEX J	ACCREDITATION CERTIFICATE.....	144

1 Test Laboratory

1.1 Testing Location

Company Name:	CTTL(Shouxiang)
Address:	No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191

1.2 Testing Environment

Temperature:	18°C~25 °C,
Relative humidity:	30%~ 70%
Ground system resistance:	< 0.5 Ω
Ambient noise & Reflection:	< 0.012 W/kg

1.3 Project Data


Project Leader:	Qi Dianyuan
Test Engineer:	Lin Xiaojun
Testing Start Date:	October 4, 2018
Testing End Date:	October 6, 2018

1.4 Signature



Lin Xiaojun

(Prepared this test report)



Qi Dianyuan

(Reviewed this test report)



Lu Bingsong

Deputy Director of the laboratory

(Approved this test report)

2 Statement of Compliance

The maximum results of SAR found during testing for Palm Ventures Group HSUPA/HSDPA/UMTS Quad Band/GSM Quad Band/LTE 5 Bands mobile phone PVG100E/PVG100EU is as follows:

Table 2.1: Highest Reported SAR (1g)

Exposure Configuration	Technology Band	Highest Reported SAR 1g (W/Kg)	Equipment Class
Head (Separation Distance 0mm) (receiver on WiFi on)	GSM 850	0.46	PCE
	PCS 1900	1.18	
	UMTS FDD 2	0.78	
	UMTS FDD 5	0.46	
	LTE Band 7	0.73	
	WLAN 2.4 GHz	0.30	DTS
Head (Separation Distance 0mm) (receiver on WiFi off)	UMTS FDD 2	1.04	PCE
	LTE Band 7	1.28	
Body worn (Separation Distance 15mm)	GSM 850	0.23	PCE
	PCS 1900	0.63	
	UMTS FDD 2	0.59	
	UMTS FDD 5	0.28	
	LTE Band 7	0.99	
	WLAN 2.4 GHz	0.24	DTS

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1g tissue according to the ANSI C95.1-1992.

For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and which provides a minimum separation distance of 15 mm between this device and the body of the user. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output.

The measurement together with the test system set-up is described in annex C of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report.

The highest reported SAR value is obtained at the case of (**Table 2.1**), and the values are: 1.28 W/kg (1g).

Table 2.2: The sum of reported SAR values for main antenna and WiFi

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Right hand, Touch cheek (GSM 1900)	1.18	0.30	1.48
Highest reported SAR value for Body	Rear (LTE Band7)	0.99	0.22	1.21

Table 2.3: The sum of reported SAR values for main antenna and BT

	Position	Main antenna	BT	Sum
Maximum reported SAR value for Head	Left hand, Touch cheek (LTE Band7)	1.28	<0.01	1.28
Maximum reported SAR value for Body	Rear (LTE Band7)	0.99	0.25	1.24

[1] - Estimated SAR for Bluetooth (see the table 13.3)

According to the above tables, the highest sum of reported SAR values is 1.48 **W/kg (1g)**. The detail for simultaneous transmission consideration is described in chapter 13.

3 Client Information

3.1 Applicant Information

Company Name:	Palm Ventures Group
Address /Post:	461 2nd Street - #C337-San Francisco - CA 94107
Contact Person:	Francois CHAMBON
E-mail:	francois@palmventuresgroup.com
Telephone:	+8618675503761
Fax:	/

3.2 Manufacturer Information

Company Name:	Palm Ventures Group
Address /Post:	461 2nd Street - #C337-San Francisco - CA 94107
Contact Person:	Francois CHAMBON
E-mail:	francois@palmventuresgroup.com
Telephone:	+8618675503761
Fax:	/

4 Equipment Under Test (EUT) and Ancillary Equipment (AE)

4.1 About EUT

Description:	HSUPA/HSDPA/UMTS Quad Band/GSM Quad Band/LTE 5 Bands mobile phone
Model name:	PVG100E/PVG100EU
Operating mode(s):	GSM 850/900/1800/1900 WCDMA850/900/1900/2100 LTE B1/3/7/8/20, BT, WLAN 825 – 848.8 MHz (GSM 850) 1850.2 – 1910 MHz (GSM 1900) 826.4–846.6 MHz (WCDMA 850 Band V) 1852.4–1907.6 MHz (WCDMA1900 Band II) 2502.5 – 2567.5 MHz (LTE Band 7) 2412 – 2462 MHz (Wi-Fi 2.4G)
Tested Tx Frequency:	
GRPS/EGPRS Multislot Class:	12
GRPS capability Class:	B
Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna
Product dimension	Long 96.6mm ;Wide 50.6mm ; Overall Diagonal 109.05mm

4.2 Internal Identification of EUT used during the test

EUTID	IMEI	HW Version	SW Version
1	352506100003201	03	3B1K-1
2	352506100003425	03	3B1K-1
3	352506100003243	03	3B1K-1
4	352506100002443	03	3B1K-1
5	352506100002864	03	3B1K-1

*EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test SAR with the EUT1 to 3 and conducted power with the EUT4&5.

4.3 Internal Identification of AE used during the test

AE ID	Description	Model	SN	Manufacturer
AE1	Battery	TLp007A1	/	BYD

*AE ID: is used to identify the test sample in the lab internally.

5 TEST METHODOLOGY

5.1 Applicable Limit Regulations

ANSI C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

IEEE 1528-2013: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

KDB648474 D04 Handset SAR v01r03: SAR Evaluation Considerations for Wireless Handsets.

KDB941225 D01 SAR test for 3G devices v03r01: SAR Measurement Procedures for 3G Devices

KDB941225 D05 SAR for LTE Devices v02r05: SAR Evaluation Considerations for LTE Devices

KDB248227 D01 802.11 Wi-Fi SAR v02r02: SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS

KDB865664 D01 SAR measurement 100 MHz to 6 GHz v01r04: SAR Measurement Requirements for 100 MHz to 6 GHz.

KDB865664 D02 RF Exposure Reporting v01r02: RF Exposure Compliance Reporting and Documentation Considerations

6 Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

7 Tissue Simulating Liquids

7.1 Targets for tissue simulating liquid


Table 7.1: Targets for tissue simulating liquid

Frequency(MHz)	Liquid Type	Conductivity(σ)	\pm 5% Range	Permittivity(ϵ)	\pm 5% Range
835	Head	0.90	0.86~0.95	41.5	39.4~43.6
835	Body	0.97	0.92~1.02	55.2	52.4~58.0
1900	Head	1.40	1.33~1.47	40.0	38.0~42.0
1900	Body	1.52	1.44~1.60	53.3	50.6~56.0
2450	Head	1.80	1.71~1.89	39.2	37.2~41.2
2450	Body	1.95	1.85~2.05	52.7	50.1~55.3
2600	Head	1.96	1.86~2.06	39.01	37.06~40.96
2600	Body	2.16	2.05~2.27	52.5	49.9~55.1
5250	Head	4.71	4.47~4.95	35.93	34.1~37.7
5250	Body	5.36	5.09~5.63	48.9	46.5~51.3
5600	Head	5.07	4.82~5.32	35.53	33.8~37.3
5600	Body	5.77	5.48~6.06	48.5	46.1~50.9
5750	Head	5.22	4.96~5.48	35.36	33.6~37.1
5750	Body	5.94	5.64~6.24	48.3	45.9~50.7

7.2 Dielectric Performance

Table 7.2: Dielectric Performance of Tissue Simulating Liquid

Measurement Date yyyy/mm/dd	Frequency	Type	Permittivity ϵ	Drift (%)	Conductivity σ (S/m)	Drift (%)
2018/10/4	835 MHz	Head	41.52	0.05	0.906	0.67
		Body	55.12	-0.14	0.97	0.00
2018/10/5	1900 MHz	Head	39.37	-1.58	1.4	0.00
		Body	53.91	1.14	1.513	-0.46
2018/10/6	2450 MHz	Head	38.65	-1.40	1.797	-0.17
		Body	53.13	0.82	1.939	-0.56
2018/10/6	2600 MHz	Head	38.63	-0.97	1.942	-0.92
		Body	51.64	-1.64	2.175	0.69



Picture 7-1 Liquid depth in the Head Phantom (835MHz)



Picture 7-2 Liquid depth in the Flat Phantom (835MHz)




Picture 7-3 Liquid depth in the Head Phantom (1900 MHz)



Picture 7-4 Liquid depth in the Flat Phantom (1900MHz)




Picture 7-5 Liquid depth in the Head Phantom (2450MHz)



Picture 7-6 Liquid depth in the Flat Phantom (2450MHz)



Picture 7-7 Liquid depth in the Head Phantom (2600 MHz Head)




Picture 7-8 Liquid depth in the Flat Phantom (2600MHz)

8 System verification

8.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 8.1 System Setup for System Evaluation



Picture 8.2 Photo of Dipole Setup

8.2 System Verification

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device.

The system verification results are required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR. The details are presented in annex B.

Table 8.1: System Verification of Head

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2018/10/4	835 MHz	6.06	9.37	6	9.24	-0.99%	-1.39%
2018/10/5	1900 MHz	21.0	40.0	21.12	39.2	0.57%	-2.00%
2018/10/6	2450 MHz	24.7	52.2	25.12	52.4	1.70%	0.38%
2018/10/6	2600 MHz	25.8	57.9	25.88	57.2	0.31%	-1.21%

Table 8.2: System Verification of Body

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2018/10/4	835 MHz	6.12	9.41	6.16	9.4	0.65%	-0.11%
2018/10/5	1900 MHz	21.5	40.5	21.52	40.56	0.09%	0.15%
2018/10/6	2450 MHz	23.8	50.4	23.4	49.72	-1.68%	-1.35%
2018/10/6	2600 MHz	24.8	55.5	25.04	56.32	0.97%	1.48%

9 Measurement Procedures

9.1 Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in picture 9.1.


Step 1: The tests described in 9.2 shall be performed at the channel that is closest to the center of the transmit frequency band (f_c) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in annex D),
- b) all configurations for each device position in a), e.g., antenna extended and retracted, and
- c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e., $N_c > 3$), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing highest peak spatial-average SAR determined in Step 1, perform all tests described in 9.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

Step 3: Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.



Picture 9.1 Block diagram of the tests to be performed

9.2 General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013. The results should be documented as part of the system validation records and may be requested to support test results when all the measurement parameters in the following table are not satisfied.

		≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface		5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location		$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
		≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$		≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$	≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$
Minimum zoom scan volume	x, y, z	≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.			
* When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.			

9.3 WCDMA Measurement Procedures for SAR

The following procedures are applicable to WCDMA handsets operating under 3GPP Release99, Release 5 and Release 6. The default test configuration is to measure SAR with an established radio link between the DUT and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other physical channel configurations (DPCCH & DPDCH_n), HSDPA and HSPA (HSUPA/HSDPA) modes according to output power, exposure conditions and device operating capabilities. Both uplink and downlink should be configured with the same RMC or AMR, when required. SAR for Release 5 HSDPA and Release 6 HSPA are measured using the applicable FRC (fixed reference channel) and E-DCH reference channel configurations. Maximum output power is verified according to applicable versions of 3GPP TS 34.121 and SAR must be measured according to these maximum output conditions. When Maximum Power Reduction (MPR) is not implemented according to Cubic Metric (CM) requirements for Release 6 HSPA, the following procedures do not apply.

For Release 5 HSDPA Data Devices:

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs}	CM/dB
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15	15/15	64	12/15	24/25	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

For Release 6 HSPA Data Devices

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs}	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (dB)	MPR (dB)	AG Index	E-TFCI
1	11/15	15/15	64	11/15	22/15	209/225	1039/225	4	1	1.5	1.5	20	75
2	6/15	15/15	64	6/15	12/15	12/15	12/15	4	1	1.5	1.5	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1:47/15}$	4	2	1.5	1.5	15	92
4	2/15	15/15	64	2/15	4/15	4/15	56/75	4	1	1.5	1.5	17	71
5	15/15	15/15	64	15/15	24/15	30/15	134/15	4	1	1.5	1.5	21	81

Rel.8 DC-HSDPA (Cat 24)

SAR test exclusion for Rel.8 DC-HSDPA must satisfy the SAR test exclusion requirements of Rel.5 HSDPA. SAR test exclusion for DC-HSDPA devices is determined by power measurements according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to qualify for SAR test exclusion.

9.4 SAR Measurement for LTE

SAR tests for LTE are performed with a base station simulator, Rohde & Rchwarz CMW500. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. All powers were measured with the CMW 500.

It is performed for conducted power and SAR based on the KDB941225 D05.

SAR is evaluated separately according to the following procedures for the different test positions in each exposure condition – head, body, body-worn accessories and other use conditions. The procedures in the following subsections are applied separately to test each LTE frequency band.

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

9.5 Bluetooth & Wi-Fi Measurement Procedures for SAR

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

9.6 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in section 14 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

10 Area Scan Based 1-g SAR

10.1 Requirement of KDB

According to the KDB447498 D01 v05, when the implementation is based the specific polynomial fit

algorithm as presented at the 29th Bioelectromagnetics Society meeting (2007) and the estimated 1-g SAR is $\leq 1.2 \text{ W/kg}$, a zoom scan measurement is not required provided it is also not needed for any other purpose; for example, if the peak SAR location required for simultaneous transmission SAR test exclusion can be determined accurately by the SAR system or manually to discriminate between distinctive peaks and scattered noisy SAR distributions from area scans.

There must not be any warning or alert messages due to various measurement concerns identified by the SAR system; for example, noise in measurements, peaks too close to scan boundary, peaks are too sharp, spatial resolution and uncertainty issues etc. The SAR system verification must also demonstrate that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR (See Annex B). When all the SAR results for each exposure condition in a frequency band and wireless mode are based on estimated 1-g SAR, the 1-g SAR for the highest SAR configuration must be determined by a zoom scan.

10.2 Fast SAR Algorithms

The approach is based on the area scan measurement applying a frequency dependent attenuation parameter. This attenuation parameter was empirically determined by analyzing a large number of phones. The MOTOROLA FAST SAR was developed and validated by the MOTOROLA Research Group in Ft. Lauderdale.

In the initial study, an approximation algorithm based on Linear fit was developed. The accuracy of the algorithm has been demonstrated across a broad frequency range (136-2450 MHz) and for both 1- and 10-g averaged SAR using a sample of 264 SAR measurements from 55 wireless handsets. For the sample size studied, the root-mean-squared errors of the algorithm are 1.2% and 5.8% for 1- and 10-g averaged SAR, respectively. The paper describing the algorithm in detail is expected to be published in August 2004 within the Special Issue of Transactions on MTT.

In the second step, the same research group optimized the fitting algorithm to an Polynomial fit whereby the frequency validity was extended to cover the range 30-6000MHz. Details of this study can be found in the BEMS 2007 Proceedings.

Both algorithms are implemented in DASY software.

11 Conducted Output Power

11.1 GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

Table 11-1 GSM850 #1

GSM850 #1								
Config	Tune-up	Measured Power (dBm)			Calculation	Frame Burst Power (dBm)		
		CH251 848.8 MHz	CH190 836.6 MHz	CH128 824.2 MHz		CH251 848.8 MHz	CH190 836.6 MHz	CH128 824.2 MHz
GSM Speech	33.50	32.58	32.57	32.79				
GPRS 1 Txslot	33.50	32.46	32.55	32.77	-9.03	23.43	23.52	23.74
GPRS 2 Txslots	30.00	29.11	29.06	29.25	-6.02	23.09	23.04	23.23
GPRS 3 Txslots	29.00	27.17	27.03	27.23	-4.26	22.91	22.77	22.97
GPRS 4 Txslots	27.00	25.82	25.79	25.86	-3.01	22.81	22.78	22.85
EGPRS GMSK 1 Txslot	33.50	31.96	32.20	32.26	-9.03	22.93	23.17	23.23
EGPRS GMSK 2 Txslots	30.00	29.13	29.12	29.28	-6.02	23.11	23.10	23.26
EGPRS GMSK 3 Txslots	28.50	27.14	27.08	27.26	-4.26	22.88	22.82	23.00
EGPRS GMSK 4 Txslots	27.00	25.89	25.83	25.82	-3.01	22.88	22.82	22.81
EGPRS 8PSK 1 Txslot	28.00	26.60	26.81	27.01	-9.03	17.57	17.78	17.98
EGPRS 8PSK 2 Txslots	27.00	25.54	25.88	25.78	-6.02	19.52	19.86	19.76
EGPRS 8PSK 3 Txslots	25.00	24.30	24.02	24.14	-4.26	20.04	19.76	19.88
EGPRS 8PSK 4 Txslots	24.00	22.31	22.50	22.43	-3.01	19.30	19.49	19.42

Table 11-2 PCS1900 #1

PCS1900 #1								
Config	Tune-up	Measured Power (dBm)			Calculation	Frame Burst Power (dBm)		
		CH810 1909.8 MHz	CH661 1880 MHz	CH512 1850.2 MHz		CH810 1909.8 MHz	CH661 1880 MHz	CH512 1850.2 MHz
GSM Speech	30.50	29.95	29.71	29.51				
GPRS 1 Txslot	30.50	29.63	29.70	29.59	-9.03	20.60	20.67	20.56
GPRS 2 Txslots	27.50	26.50	26.31	26.44	-6.02	20.48	20.29	20.42
GPRS 3 Txslots	25.50	24.57	24.53	24.49	-4.26	20.31	20.27	20.23
GPRS 4 Txslots	24.50	23.34	23.25	23.36	-3.01	20.33	20.24	20.35
EGPRS GMSK 1 Txslot	30.50	29.64	29.67	29.57	-9.03	20.61	20.64	20.54
EGPRS GMSK 2 Txslots	27.50	26.34	26.38	26.41	-6.02	20.32	20.36	20.39
EGPRS GMSK 3 Txslots	25.50	24.59	24.49	24.42	-4.26	20.33	20.23	20.16
EGPRS GMSK 4 Txslots	24.50	23.35	23.24	23.20	-3.01	20.34	20.23	20.19
EGPRS 8PSK 1 Txslot	27.00	25.54	25.51	25.34	-9.03	16.51	16.48	16.31
EGPRS 8PSK 2 Txslots	26.00	24.62	24.59	24.55	-6.02	18.60	18.57	18.53
EGPRS 8PSK 3 Txslots	24.00	23.04	22.89	22.91	-4.26	18.78	18.63	18.65
EGPRS 8PSK 4 Txslots	22.50	21.58	21.57	21.36	-3.01	18.57	18.56	18.35

NOTES:

Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 1Txslot for 850MHz and 1900MHz.

11.2 WCDMA Measurement result

Table 11-3 WCDMA1900-BII #1 (Receiver off)

WCDMA1900-BII #1			Measured Power (dBm)		
Item		Tune-up	CH9538 1907.6 MHz	CH9400 1880 MHz	CH9262 1852.4 MHz
WCDMA	RMC	24.00	23.50	23.40	23.49
HSUPA	subtest1	23.00	22.43	22.18	22.38
	subtest2	22.00	21.91	21.72	21.84
	subtest3	23.00	22.35	22.17	22.31
	subtest4	23.00	22.28	22.23	22.32
	subtest5	23.00	22.22	22.21	22.35
HSPA+	\	\	\	\	\
DC-HSDPA	subtest1	23.00	22.06	22.00	22.03
	subtest2	23.00	21.94	21.96	21.93
	subtest3	23.00	21.96	21.94	21.97
	subtest4	23.00	21.95	21.98	21.96

Table 11-4 WCDMA1900-BII #2 (Receiver on WiFi off)

WCDMA1900-BII #2			Measured Power (dBm)		
Item		Tune-up	CH9538 1907.6 MHz	CH9400 1880 MHz	CH9262 1852.4 MHz
WCDMA	RMC	21.00	20.48	20.35	20.57
HSUPA	subtest1	20.50	19.96	19.89	19.91
	subtest2	20.50	19.51	19.32	19.34
	subtest3	20.50	19.95	19.76	19.83
	subtest4	20.50	19.97	19.82	19.86
	subtest5	20.50	19.88	19.86	19.97
HSPA+	\	\	\	\	\
DC-HSDPA	subtest1	20.50	19.76	19.56	19.67
	subtest2	20.50	19.66	19.59	19.65
	subtest3	20.50	19.72	19.61	19.66
	subtest4	20.50	19.67	19.54	19.71

Table 11-5 WCDMA1900-BII #3 (Receiver on WiFi on)

WCDMA1900-BII #3			Measured Power (dBm)		
Item		Tune-up	CH9538 1907.6 MHz	CH9400 1880 MHz	CH9262 1852.4 MHz
WCDMA	RMC	19.50	18.55	18.38	18.46
HSUPA	subtest1	19.00	17.98	17.82	17.97
	subtest2	19.00	17.41	17.30	17.30
	subtest3	19.00	17.92	17.83	17.81
	subtest4	19.00	17.89	17.85	17.83
	subtest5	19.00	17.96	17.89	17.80
HSPA+	\	\	\	\	\
DC-HSDPA	subtest1	19.00	17.61	17.41	17.65
	subtest2	19.00	17.67	17.46	17.62
	subtest3	19.00	17.62	17.53	17.57
	subtest4	19.00	17.70	17.47	17.55

Table 11-6 WCDMA850-BV #1

WCDMA850-BV #1			Measured Power (dBm)		
Item		Tune-up	CH4233 846.6 MHz	CH4182 835.4 MHz	CH4132 826.4 MHz
WCDMA	RMC	24.00	22.99	22.94	22.88
HSUPA	subtest1	22.50	21.94	22.09	22.01
	subtest2	22.50	21.49	21.57	21.48
	subtest3	22.50	21.94	22.07	22.01
	subtest4	22.50	22.03	22.06	21.92
	subtest5	22.50	21.91	22.08	22.09
HSPA+	\	\	\	\	\
DC-HSDPA	subtest1	22.00	21.88	21.75	21.66
	subtest2	22.00	21.95	21.79	21.74
	subtest3	22.00	21.97	21.73	21.69
	subtest4	22.00	21.96	21.76	21.65

11.3 LTE Measurement result

Table 11-7 LTE2500-FDD7 #1 (Receiver off)

LTE2500-FDD7 #1				Measured Power (dBm) & MPR			
BandWidth	RB No./Start	Channel	Tune-up	QPSK		16QAM	
				Measured Power	MPR	Measured Power	MPR
5MHz	1H	21425	20.6	20.23	0	19.92	0
		21100	20.6	20.26	0	20.18	0
		20775	20.6	19.78	0	19.76	0
	1M	21425	20.6	20.55	0	20.14	0
		21100	20.6	20.53	0	20.56	0
		20775	20.6	20.53	0	20.49	0
	1L	21425	20.6	20.23	0	20.22	0
		21100	20.6	20.23	0	19.84	0
		20775	20.6	19.83	0	20.24	0
	12H	21425	20.6	20.31	0	20.28	0
		21100	20.6	20.33	0	20.13	0
		20775	20.6	20.27	0	20.22	0
	12M	21425	20.6	20.41	0	20.53	0
		21100	20.6	20.30	0	20.17	0
		20775	20.6	20.31	0	20.29	0
	12L	21425	20.6	20.39	0	20.27	0
		21100	20.6	20.27	0	20.19	0
		20775	20.6	20.26	0	20.56	0
	25	21425	20.6	20.43	0	20.48	0
		21100	20.6	20.29	0	20.48	0
		20775	20.6	20.26	0	20.41	0
10MHz	1H	21400	20.6	20.49	0	20.21	0
		21100	20.6	20.32	0	20.14	0
		20800	20.6	20.15	0	20.04	0
	1M	21400	20.6	20.57	0	20.58	0
		21100	20.6	20.51	0	20.17	0
		20800	20.6	20.22	0	20.21	0
	1L	21400	20.6	20.53	0	20.38	0
		21100	20.6	20.38	0	20.27	0
		20800	20.6	20.14	0	20.39	0
	25H	21400	20.6	20.41	0	20.38	0
		21100	20.6	20.32	0	20.41	0
		20800	20.6	20.26	0	20.53	0
	25M	21400	20.6	20.43	0	20.53	0
		21100	20.6	20.33	0	20.43	0
		20800	20.6	20.44	0	20.34	0
	25L	21400	20.6	20.41	0	20.50	0
		21100	20.6	20.25	0	20.40	0
		20800	20.6	20.29	0	20.20	0
	50	21400	20.6	20.46	0	20.42	0
		21100	20.6	20.34	0	20.26	0
		20800	20.6	20.30	0	20.27	0
15MHz	1H	21375	20.6	20.41	0	20.27	0
		21100	20.6	20.26	0	20.11	0
		20825	20.6	20.19	0	20.38	0
	1M	21375	20.6	20.52	0	20.59	0
		21100	20.6	20.32	0	20.18	0
		20825	20.6	20.27	0	20.45	0
	1L	21375	20.6	20.44	0	20.31	0
		21100	20.6	20.32	0	20.12	0
		20825	20.6	20.27	0	20.26	0
	36H	21375	20.6	20.41	0	20.34	0
		21100	20.6	20.37	0	20.32	0
		20825	20.6	20.27	0	20.33	0
	36M	21375	20.6	20.46	0	20.49	0
		21100	20.6	20.30	0	20.35	0
		20825	20.6	20.26	0	20.19	0
	36L	21375	20.6	20.40	0	20.44	0
		21100	20.6	20.33	0	20.30	0
		20825	20.6	20.26	0	20.23	0
	75	21375	20.6	20.44	0	20.46	0
		21100	20.6	20.33	0	20.28	0
		20825	20.6	20.24	0	20.25	0

20MHz	1H	21350	20.6	20.37	0	20.11	0
		21100	20.6	20.22	0	20.12	0
		20850	20.6	19.97	0	19.81	0
	1M	21350	20.6	20.48	0	20.33	0
		21100	20.6	20.38	0	20.11	0
		20850	20.6	20.13	0	20.20	0
	1L	21350	20.6	20.23	0	20.21	0
		21100	20.6	19.96	0	20.06	0
		20850	20.6	19.72	0	19.74	0
	50H	21350	20.6	20.45	0	20.45	0
		21100	20.6	20.30	0	20.30	0
		20850	20.6	20.19	0	20.35	0
	50M	21350	20.6	20.49	0	20.53	0
		21100	20.6	20.28	0	20.10	0
		20850	20.6	20.25	0	20.37	0
	50L	21350	20.6	20.38	0	20.12	0
		21100	20.6	20.30	0	20.16	0
		20850	20.6	20.24	0	20.07	0
	100	21350	20.6	20.39	0	20.42	0
		21100	20.6	20.30	0	20.30	0
		20850	20.6	20.22	0	20.19	0

Table 11-8 LTE2500-FDD7 #2 (Receiver on WiFi off)

LTE2500-FDD7 #2				Measured Power (dBm) & MPR			
BandWidth	RB No./Start	Channel	Tune-up	QPSK		16QAM	
				Measured Power	MPR	Measured Power	MPR
5MHz	1H	21425	21	20.28	0	20.05	0
		21100	21	20.30	0	19.88	0
		20775	21	20.22	0	19.83	0
	1M	21425	21	20.56	0	20.16	0
		21100	21	20.58	0	20.47	0
		20775	21	20.60	0	20.59	0
	1L	21425	21	20.51	0	20.14	0
		21100	21	20.35	0	19.90	0
		20775	21	20.17	0	20.33	0
	12H	21425	21	20.38	0	20.22	0
		21100	21	20.37	0	20.23	0
		20775	21	20.36	0	20.13	0
	12M	21425	21	20.45	0	20.56	0
		21100	21	20.51	0	20.45	0
		20775	21	20.48	0	20.40	0
	12L	21425	21	20.40	0	20.43	0
		21100	21	20.42	0	20.29	0
		20775	21	20.39	0	20.49	0
	25	21425	21	20.35	0	20.43	0
		21100	21	20.43	0	20.56	0
		20775	21	20.39	0	20.39	0
10MHz	1H	21400	21	20.44	0	20.41	0
		21100	21	20.53	0	20.08	0
		20800	21	20.34	0	20.22	0
	1M	21400	21	20.48	0	20.55	0
		21100	21	20.53	0	20.51	0
		20800	21	20.52	0	20.28	0
	1L	21400	21	20.48	0	20.01	0
		21100	21	20.50	0	20.29	0
		20800	21	20.35	0	20.20	0
	25H	21400	21	20.47	0	20.49	0
		21100	21	20.39	0	20.50	0
		20800	21	20.37	0	20.53	0
	25M	21400	21	20.56	0	20.53	0
		21100	21	20.46	0	20.34	0
		20800	21	20.39	0	20.52	0
	25L	21400	21	20.55	0	20.55	0
		21100	21	20.35	0	20.47	0
		20800	21	20.39	0	20.41	0
	50	21400	21	20.52	0	20.51	0
		21100	21	20.42	0	20.42	0
		20800	21	20.38	0	20.33	0
15MHz	1H	21375	21	20.29	0	20.03	0
		21100	21	20.26	0	20.05	0
		20825	21	20.22	0	20.44	0
	1M	21375	21	20.59	0	20.21	0
		21100	21	20.32	0	20.24	0
		20825	21	20.33	0	20.19	0
	1L	21375	21	20.58	0	20.28	0
		21100	21	20.45	0	20.18	0
		20825	21	20.48	0	20.11	0
	36H	21375	21	20.44	0	20.40	0
		21100	21	20.35	0	20.53	0
		20825	21	20.36	0	20.24	0
	36M	21375	21	20.52	0	20.56	0
		21100	21	20.34	0	20.39	0
		20825	21	20.35	0	20.26	0
	36L	21375	21	20.47	0	20.50	0
		21100	21	20.33	0	20.47	0
		20825	21	20.36	0	20.31	0
	75	21375	21	20.41	0	20.53	0
		21100	21	20.32	0	20.42	0
		20825	21	20.32	0	20.33	0

20MHz	1H	21350	21	20.45	0	20.21	0
		21100	21	20.24	0	20.21	0
		20850	21	19.74	0	19.84	0
	1M	21350	21	20.51	0	20.49	0
		21100	21	20.10	0	20.17	0
		20850	21	20.19	0	20.11	0
	1L	21350	21	20.37	0	19.96	0
		21100	21	19.96	0	20.15	0
		20850	21	19.80	0	19.90	0
	50H	21350	21	20.43	0	20.48	0
		21100	21	20.34	0	20.46	0
		20850	21	20.26	0	20.21	0
	50M	21350	21	20.41	0	20.47	0
		21100	21	20.31	0	20.41	0
		20850	21	20.31	0	20.42	0
	50L	21350	21	20.31	0	20.37	0
		21100	21	20.36	0	20.15	0
		20850	21	20.28	0	20.43	0
	100	21350	21	20.41	0	20.41	0
		21100	21	20.35	0	20.17	0
		20850	21	20.27	0	20.40	0

Table 11-9 LTE2500-FDD7 #3 (Receiver on WiFi on)

LTE2500-FDD7 #3				Measured Power (dBm) & MPR			
BandWidth	RB No./Start	Channel	Tune-up	QPSK		16QAM	
				Measured Power	MPR	Measured Power	MPR
5MHz	1H	21425	19	18.31	0	18.05	0
		21100	19	18.34	0	18.04	0
		20775	19	18.24	0	17.91	0
	1M	21425	19	18.64	0	18.41	0
		21100	19	18.65	0	18.21	0
		20775	19	18.51	0	18.78	0
	1L	21425	19	18.34	0	17.87	0
		21100	19	18.39	0	17.90	0
		20775	19	18.36	0	18.51	0
	12H	21425	19	18.39	0	18.50	0
		21100	19	18.43	0	18.56	0
		20775	19	18.34	0	18.36	0
	12M	21425	19	18.48	0	18.56	0
		21100	19	18.54	0	18.38	0
		20775	19	18.49	0	18.56	0
	12L	21425	19	18.50	0	18.36	0
		21100	19	18.40	0	18.35	0
		20775	19	18.41	0	18.58	0
	25	21425	19	18.46	0	18.61	0
		21100	19	18.50	0	18.64	0
		20775	19	18.46	0	18.68	0
10MHz	1H	21400	19	18.38	0	18.38	0
		21100	19	18.58	0	18.26	0
		20800	19	18.39	0	18.19	0
	1M	21400	19	18.59	0	18.82	0
		21100	19	18.87	0	18.81	0
		20800	19	18.70	0	18.28	0
	1L	21400	19	18.55	0	18.49	0
		21100	19	18.36	0	18.37	0
		20800	19	18.45	0	18.33	0
	25H	21400	19	18.52	0	18.59	0
		21100	19	18.50	0	18.48	0
		20800	19	18.46	0	18.48	0
	25M	21400	19	18.55	0	18.61	0
		21100	19	18.48	0	18.54	0
		20800	19	18.48	0	18.52	0
	25L	21400	19	18.54	0	18.63	0
		21100	19	18.47	0	18.33	0
		20800	19	18.46	0	18.50	0
	50	21400	19	18.48	0	18.54	0
		21100	19	18.46	0	18.49	0
		20800	19	18.50	0	18.48	0
15MHz	1H	21375	19	18.17	0	18.59	0
		21100	19	18.28	0	18.25	0
		20825	19	18.26	0	18.15	0
	1M	21375	19	18.83	0	18.81	0
		21100	19	18.76	0	19.00	0
		20825	19	18.44	0	18.31	0
	1L	21375	19	18.37	0	18.31	0
		21100	19	18.47	0	18.27	0
		20825	19	18.43	0	18.12	0
	36H	21375	19	18.46	0	18.40	0
		21100	19	18.42	0	18.42	0
		20825	19	18.42	0	18.46	0
	36M	21375	19	18.41	0	18.52	0
		21100	19	18.39	0	18.51	0
		20825	19	18.40	0	18.54	0
	36L	21375	19	18.49	0	18.38	0
		21100	19	18.48	0	18.31	0
		20825	19	18.43	0	18.52	0
	75	21375	19	18.42	0	18.52	0
		21100	19	18.41	0	18.50	0
		20825	19	18.39	0	18.49	0

20MHz	1H	21350	19	18.37	0	18.37	0
		21100	19	18.27	0	18.19	0
		20850	19	17.86	0	17.98	0
	1M	21350	19	18.80	0	18.49	0
		21100	19	18.53	0	18.28	0
		20850	19	18.39	0	18.27	0
	1L	21350	19	18.72	0	18.46	0
		21100	19	18.11	0	18.10	0
		20850	19	17.95	0	18.18	0
	50H	21350	19	18.52	0	18.60	0
		21100	19	18.44	0	18.40	0
		20850	19	18.41	0	18.53	0
	50M	21350	19	18.50	0	18.49	0
		21100	19	18.45	0	18.35	0
		20850	19	18.43	0	18.27	0
	50L	21350	19	18.51	0	18.32	0
		21100	19	18.45	0	18.41	0
		20850	19	18.46	0	18.36	0
	100	21350	19	18.53	0	18.51	0
		21100	19	18.46	0	18.44	0
		20850	19	18.31	0	18.47	0

11.4 Wi-Fi and BT Measurement result

The highest BT power is 12.04dBm and tune up is 12.5dBm.

The average conducted power for Wi-Fi is as following:

Table 11-10 WLAN2450 #1 Head

WLAN2450 #1						
Band	Mode	Channel	Frequency	Data Rate	Tune-up	Measured
WLAN 2.4G 20M	802.11b	11	2462 MHz	1Mbps	17.00	16.42
		6	2437 MHz		17.00	16.11
		1	2412 MHz		17.00	16.61
		11	2462 MHz	2Mbps	/	/
		6	2437 MHz		/	/
		1	2412 MHz		17.00	16.49
		11	2462 MHz	5.5Mbps	/	/
		6	2437 MHz		/	/
		1	2412 MHz		17.00	16.46
		11	2462 MHz	11Mbps	/	/
		6	2437 MHz		/	/
		1	2412 MHz		17.00	16.40
WLAN 2.4G 20M	802.11g	11	2462 MHz	6Mbps	16.50	15.73
		6	2437 MHz		16.50	15.36
		1	2412 MHz		16.50	15.18
		11	2462 MHz	9Mbps	16.50	15.72
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	12Mbps	16.50	15.71
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	18Mbps	16.50	15.69
		6	2437 MHz		/	/
		1	2412 MHz		/	/
WLAN 2.4G 20M	802.11n 20M	11	2462 MHz	24Mbps	16.50	15.66
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	36Mbps	16.50	15.94
		6	2437 MHz		16.50	15.84
		1	2412 MHz		16.50	15.63
		11	2462 MHz	48Mbps	16.50	15.91
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	54Mbps	16.50	15.89
		6	2437 MHz		/	/
		1	2412 MHz		/	/
WLAN 2.4G 20M	802.11n 20M	11	2462 MHz	MCS0	16.00	15.28
		6	2437 MHz		16.00	14.88
		1	2412 MHz		16.00	14.73
		11	2462 MHz	MCS1	16.00	15.25
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	MCS2	16.00	15.26
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	MCS3	16.00	15.23
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	MCS4	16.00	14.70
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	MCS5	16.00	14.69
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	MCS6	16.00	14.68
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	MCS7	16.00	14.69
		6	2437 MHz		/	/

WLAN 2.4G 40M	802.11n 40M	1	2412 MHz	MCS0	/	/
		9	2452 MHz		/	/
		6	2437 MHz		/	/
		3	2422 MHz		/	/
		9	2452 MHz	MCS1	/	/
		6	2437 MHz		/	/
		3	2422 MHz		/	/
		9	2452 MHz		/	/
		6	2437 MHz	MCS2	/	/
		3	2422 MHz		/	/
		9	2452 MHz		/	/
		6	2437 MHz		/	/
		3	2422 MHz	MCS3	/	/
		9	2452 MHz		/	/
		6	2437 MHz		/	/
		3	2422 MHz		/	/
		9	2452 MHz	MCS4	/	/
		6	2437 MHz		/	/
		3	2422 MHz		/	/
		9	2452 MHz		/	/
		6	2437 MHz	MCS5	/	/
		3	2422 MHz		/	/
		9	2452 MHz		/	/
		6	2437 MHz		/	/
		3	2422 MHz	MCS6	/	/
		9	2452 MHz		/	/
		6	2437 MHz		/	/
		3	2422 MHz		/	/
		9	2452 MHz	MCS7	/	/
		6	2437 MHz		/	/
		3	2422 MHz		/	/

Table 11-11 WLAN2450 #2 Body

WLAN2450 #2						
Band	Mode	Channel	Frequency	Data Rate	Tune-up	Measured
WLAN 2.4G 20M	802.11b	11	2462 MHz	1Mbps	20.20	19.85
		6	2437 MHz		20.20	19.97
		1	2412 MHz		20.20	19.51
		11	2462 MHz	2Mbps	/	/
		6	2437 MHz		20.20	19.84
		1	2412 MHz		/	/
		11	2462 MHz	5.5Mbps	/	/
		6	2437 MHz		20.20	19.88
		1	2412 MHz		/	/
		11	2462 MHz	11Mbps	/	/
		6	2437 MHz		20.20	19.72
		1	2412 MHz		/	/
WLAN 2.4G 20M	802.11g	11	2462 MHz	6Mbps	19.00	18.63
		6	2437 MHz		19.00	18.51
		1	2412 MHz		19.00	18.65
		11	2462 MHz	9Mbps	/	/
		6	2437 MHz		/	/
		1	2412 MHz		19.00	18.67
		11	2462 MHz	12Mbps	19.00	18.66
		6	2437 MHz		19.00	18.53
		1	2412 MHz		19.00	18.69
		11	2462 MHz	18Mbps	/	/
		6	2437 MHz		/	/
		1	2412 MHz		19.00	18.67
WLAN 2.4G 20M	802.11n 20M	11	2462 MHz	24Mbps	/	/
		6	2437 MHz		/	/
		1	2412 MHz		19.00	18.64
		11	2462 MHz	36Mbps	/	/
		6	2437 MHz		/	/
		1	2412 MHz		19.00	18.19
		11	2462 MHz	48Mbps	/	/
		6	2437 MHz		/	/
		1	2412 MHz		19.00	18.18
		11	2462 MHz	54Mbps	/	/
		6	2437 MHz		/	/
		1	2412 MHz		19.00	18.17
WLAN 2.4G 20M	802.11n 20M	11	2462 MHz	MCS0	17.00	16.18
		6	2437 MHz		17.00	16.17
		1	2412 MHz		17.00	15.88
		11	2462 MHz	MCS1	17.00	16.39
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	MCS2	17.00	16.43
		6	2437 MHz		17.00	15.96
		1	2412 MHz		17.00	15.91
		11	2462 MHz	MCS3	17.00	16.36
		6	2437 MHz		/	/
		1	2412 MHz		/	/
WLAN 2.4G 20M	802.11n 20M	11	2462 MHz	MCS4	17.00	15.84
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	MCS5	17.00	15.81
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	MCS6	17.00	15.78
		6	2437 MHz		/	/
		1	2412 MHz		/	/
		11	2462 MHz	MCS7	17.00	15.76
		6	2437 MHz		/	/


WLAN 2.4G 40M	802.11n 40M	1	2412 MHz	MCS0	/	/
		9	2452 MHz		/	/
		6	2437 MHz		/	/
		3	2422 MHz		/	/
		9	2452 MHz	MCS1	/	/
		6	2437 MHz		/	/
		3	2422 MHz		/	/
		9	2452 MHz		/	/
		6	2437 MHz	MCS2	/	/
		3	2422 MHz		/	/
		9	2452 MHz		/	/
		6	2437 MHz		/	/
		3	2422 MHz	MCS3	/	/
		9	2452 MHz		/	/
		6	2437 MHz		/	/
		3	2422 MHz		/	/
		9	2452 MHz	MCS4	/	/
		6	2437 MHz		/	/
		3	2422 MHz		/	/
		9	2452 MHz		/	/
		6	2437 MHz	MCS5	/	/
		3	2422 MHz		/	/
		9	2452 MHz		/	/
		6	2437 MHz		/	/
		3	2422 MHz	MCS6	/	/
		9	2452 MHz		/	/
		6	2437 MHz		/	/
		3	2422 MHz		/	/
		9	2452 MHz	MCS7	/	/
		6	2437 MHz		/	/
		3	2422 MHz		/	/

12 Simultaneous TX SAR Considerations

12.1 Introduction

The following procedures adopted from "FCC SAR Considerations for Cell Phones with Multiple Transmitters" are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter. For this device, the BT and Wi-Fi can transmit simultaneous with other transmitters.

12.2 Transmit Antenna Separation Distances



Picture 12.1 Antenna Locations

12.3 SAR Measurement Positions

According to the KDB941225 D06 Hot Spot SAR v01, the edges with less than 2.5 cm distance to the antennas need to be tested for SAR.

This product doesn't support Hotspot

SAR measurement positions						
Mode	Front	Rear	Left edge	Right edge	Top edge	Bottom edge
Main antenna	Yes	Yes	NO	No	NO	No
WLAN	Yes	Yes	NO	No	NO	No

12.4 Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Table 12.1: Standalone SAR test exclusion considerations

Band/Mode	F(GHz)	Position	SAR test exclusion threshold (mW)	RF output power		SAR test exclusion
				dBm	mW	
Bluetooth	2.441	Head	9.6	12.5	17.78	No
		Body	19.2	12.5	17.78	Yes
2.4GHz WLAN 802.11 b	2.45	Head	9.58	17	50.12	No
		Body	19.17	20.2	104.71	No

Note: The result of BT Head is lower than 0.01

13 Evaluation of Simultaneous

Table 2.2: The sum of reported SAR values for main antenna and WiFi

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Right hand, Touch cheek (GSM 1900)	1.18	0.30	1.48
Highest reported SAR value for Body	Rear (LTE Band7)	0.99	0.22	1.21

Table 2.3: The sum of reported SAR values for main antenna and BT

	Position	Main antenna	BT	Sum
Maximum reported SAR value for Head	Left hand, Touch cheek (LTE Band7)	1.28	<0.01	1.28
Maximum reported SAR value for Body	Rear (LTE Band7)	0.99	0.25	1.24

[1] - Estimated SAR for Bluetooth (see the table 13.3)

Table 13.3: Estimated SAR for Bluetooth

Mode/Band	F (GHz)	Position	Distance (mm)	Upper limit of power *		Estimated d_{1g} (W/kg)
				dBm	mW	
Bluetooth	2.441	Body	15	12.5	17.78	0.25

* - Maximum possible output power declared by manufacturer

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(\text{GHz})/X}$] W/kg for test separation distances ≤ 50 mm;
 where $x = 7.5$ for 1-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Conclusion:

According to the above tables, the sum of reported SAR values is < 1.6 W/kg. So the simultaneous transmission SAR with volume scans is not required.

14 SAR Test Result

It is determined by user manual for the distance between the EUT and the phantom bottom.

The distance is 15mm and just applied to the condition of body worn accessory.

It is performed for all SAR measurements with area scan based 1-g SAR estimation (Fast SAR). A zoom scan measurement is added when the estimated 1-g SAR is the highest measured SAR in each exposure configuration, wireless mode and frequency band combination or more than 1.2W/kg.

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} \times 10^{(P_{\text{Target}} - P_{\text{Measured}})/10}$$

Where P_{Target} is the power of manufacturing upper limit;

P_{Measured} is the measured power in chapter 11.

Mode	Duty Cycle		
Speech for GSM850/1900	1:8.3		
GPRS&EGPRS for GSM850/1900	1:8.3		
WCDMA<E	1:1		

14.1 SAR results

Table 14-1 GSM850 #1 Head

GSM850 #1 Head							
Ambient Temperature: 22.5			Liquid Temperature: 22.3				
Mode	Device orientation	SAR measurement	Measured SAR [W/kg]			Reported SAR [W/kg]	
			CH251 848.8 MHz	CH190 836.6 MHz	CH128 824.2 MHz		
GSM	Tune-up		33.50	33.50	33.50	Scaling factor*	
	Slot Average Power [dBm]		32.58	32.57	32.79	1.24	
	Left Cheek	1g SAR	0.37	0.323	0.295	0.46	
		10g SAR	0.263	0.23	0.208	0.33	
		Deviation	-0.06	0.1	-0.13	-0.06	
	Left Tilt	1g SAR		0.188		0.23	
		10g SAR		0.137		0.17	
		Deviation		-0.09		-0.09	
	Right Cheek	1g SAR		0.301		0.37	
		10g SAR		0.21		0.26	
		Deviation		-0.13		-0.13	
	Right Tilt	1g SAR		0.179		0.22	
		10g SAR		0.132		0.16	
		Deviation		0.02		0.02	
GSM	Worst Case	1g SAR					
		10g SAR					
		Deviation					

Table 14-2 GSM850 #1 Body

GSM850 #1 Body							
Ambient Temperature: 22.5			Liquid Temperature: 22.3				
Mode	Device orientation	SAR measurement	Measured SAR [W/kg]			Reported SAR [W/kg]	
			CH251 848.8 MHz	CH190 836.6 MHz	CH128 824.2 MHz		
GPRS 1 Txslot	Tune-up		33.50	33.50	33.50	Scaling factor*	
	Slot Average Power [dBm]		32.46	32.55	32.77	1.27 1.24 1.18	
	Front	1g SAR	0.102			0.13	
		10g SAR	0.07			0.09	
		Deviation	-0.04			-0.04	
	Rear	1g SAR	0.183	0.106	0.14	0.23 0.13 0.17	
		10g SAR	0.129	0.072	0.093	0.16 0.09 0.11	
		Deviation	-0.1	-0.1	0.07	-0.10 -0.10 0.07	
EGPRS GMSK 2 Txslots	Tune-up		30.00	30.00	30.00	Scaling factor*	
	Slot Average Power [dBm]		29.13	29.12	29.28	1.22 1.22 1.18	
	Rear	1g SAR	0.179			0.22	
		10g SAR	0.119			0.15	
		Deviation	-0.07			-0.07	
GPRS 1 Txslot	Rear	1g SAR					
		10g SAR					
		Deviation					

Table 14-3 PCS1900 #1 Head

PCS1900 #1 Head							
Ambient Temperature: 22.5			Liquid Temperature: 22.3				
Mode	Device orientation	SAR measurement	Measured SAR [W/kg]			Reported SAR [W/kg]	
			CH810 1909.8	CH661 1880 MHz	CH512 1850.2		
GSM	Tune-up		30.50	30.50	30.50	Scaling factor*	
	Slot Average Power [dBm]		29.95	29.71	29.51	1.14 1.20 1.26	
	Left Cheek	1g SAR	0.749	0.745	0.76	0.85 0.89 0.95	
		10g SAR	0.441	0.437	0.439	0.50 0.52 0.55	
		Deviation	-0.06	0.04	0.02	-0.06 0.04 0.02	
	Left Tilt	1g SAR		0.167		0.20	
		10g SAR		0.101		0.12	
		Deviation		0.07		0.07	
	Right Cheek	1g SAR	0.926	0.921	0.939	1.05 1.10 1.18	
		10g SAR	0.533	0.528	0.528	0.60 0.63 0.66	
		Deviation	-0.01	0.08	-0.02	-0.01 0.08 -0.02	
	Right Tilt	1g SAR		0.186		0.22	
		10g SAR		0.109		0.13	
		Deviation		0.1		0.10	
GSM	Worst Case	1g SAR					
		10g SAR					
		Deviation					

Table 14-4 PCS1900 #1 Body

PCS1900 #1 Body						
Ambient Temperature: 22.5			Liquid Temperature: 22.3			
Mode	Device orientation	SAR measurement	Measured SAR [W/kg]			Reported SAR [W/kg]
			CH810 1909.8	CH661 1880 MHz	CH512 1850.2	
GPRS 1 Txslot	Front	Tune-up	30.50	30.50	30.50	Scaling factor*
		Slot Average Power [dBm]	29.63	29.70	29.59	1.22
		1g SAR		0.429		0.52
	Rear	10g SAR		0.266		0.32
		Deviation		-0.08		-0.08
		1g SAR	0.518	0.506	0.463	0.63
		10g SAR	0.294	0.284	0.266	0.36
		Deviation	-0.17	0.11	0.01	-0.17
		Tune-up	30.50	30.50	30.50	Scaling factor*
EGPRS GMSK 1 Txslot	Rear	Slot Average Power [dBm]	29.64	29.67	29.57	1.22
		1g SAR	0.503			0.61
		10g SAR	0.292			0.36
		Deviation	-0.01			-0.01
GPRS 1 Txslot	Rear	1g SAR				
		10g SAR				
		Deviation				

Table 14-5 WCDMA1900-BII #2Head (Receiver on WiFi off)

WCDMA1900-BII #2Head						
Ambient Temperature: 22.5			Liquid Temperature: 22.3			
Mode	Device orientation	SAR measurement	Measured SAR [W/kg]			Reported SAR [W/kg]
			CH9538 1907.6 MHz	CH9400 1880 MHz	CH9262 1852.4 MHz	
RMC	Left Cheek	Tune-up	21.00	21.00	21.00	Scaling factor*
		Slot Average Power [dBm]	20.48	20.35	20.57	1.13
		1g SAR	0.734	0.739	0.742	0.83
	Left Tilt	10g SAR	0.462	0.474	0.476	0.52
		Deviation	0.03	0.04	0.01	0.03
		1g SAR		0.349		0.41
	Right Cheek	10g SAR		0.181		0.21
		Deviation		0.03		0.03
		1g SAR	0.903	0.89	0.939	1.02
	Right Tilt	10g SAR	0.522	0.518	0.535	0.59
		Deviation	0.08	0.06	0.06	0.06
		1g SAR		0.181		0.21
	Worst Case	10g SAR		0.116		0.13
		Deviation		0.11		0.11
		1g SAR				

Table 14-6 WCDMA1900-BII #3Head (Receiver on WiFi on)

WCDMA1900-BII #3Head							
Ambient Temperature: 22.5			Liquid Temperature: 22.3				
Mode	Device orientation	SAR measurement	Measured SAR [W/kg]			Reported SAR [W/kg]	
			CH9538 1907.6 MHz	CH9400 1880 MHz	CH9262 1852.4 MHz		
RMC	Tune-up		19.50	19.50	19.50	Scaling factor*	
	Slot Average Power [dBm]		18.55	18.38	18.46	1.24	
	Left Cheek	1g SAR		0.469		0.61	
		10g SAR		0.293		0.38	
		Deviation		-0.08		-0.08	
	Left Tilt	1g SAR		0.116		0.15	
		10g SAR		0.07		0.09	
		Deviation		0.11		0.11	
	Right Cheek	1g SAR	0.564	0.605	0.567	0.78	
		10g SAR	0.327	0.339	0.327	0.44	
		Deviation	0.05	-0.06	0.04	-0.06	
	Right Tilt	1g SAR		0.121		0.16	
		10g SAR		0.075		0.10	
		Deviation		-0.06		-0.06	
RMC	Worst Case	1g SAR					
		10g SAR					
		Deviation					

Table 14-7 WCDMA850-BV #1Head

WCDMA850-BV #1Head							
Ambient Temperature: 22.5			Liquid Temperature: 22.3				
Mode	Device orientation	SAR measurement	Measured SAR [W/kg]			Reported SAR [W/kg]	
			CH4233 846.6 MHz	CH4182 835.4 MHz	CH4132 826.4 MHz		
RMC	Tune-up		24.00	24.00	24.00	Scaling factor*	
	Slot Average Power [dBm]		22.99	22.94	22.88	1.26	
	Left Cheek	1g SAR	0.368	0.363	0.337	0.46	
		10g SAR	0.262	0.258	0.238	0.33	
		Deviation	0.11	0.04	0.05	0.04	
	Left Tilt	1g SAR		0.195		0.25	
		10g SAR		0.141		0.18	
		Deviation		-0.02		-0.02	
	Right Cheek	1g SAR		0.347		0.44	
		10g SAR		0.242		0.31	
		Deviation		0.03		0.03	
	Right Tilt	1g SAR		0.183		0.23	
		10g SAR		0.135		0.17	
		Deviation		0.01		0.01	
RMC	Worst Case	1g SAR					
		10g SAR					
		Deviation					

Table 14-8 WCDMA850-BV #1Body

WCDMA850-BV #1Body										
Ambient Temperature: 22.5			Liquid Temperature: 22.3							
Mode	Device orientation	SAR measurement	Measured SAR [W/kg]			Reported SAR [W/kg]				
			CH4233 846.6 MHz	CH4182 835.4 MHz	CH4132 826.4 MHz	CH4233 846.6 MHz	CH4182 835.4 MHz	CH4132 826.4 MHz		
RMC	Tune-up		24.00	24.00	24.00	Scaling factor*				
	Slot Average Power [dBm]		22.99	22.94	22.88	1.26	1.28	1.29		
	Front	1g SAR		0.156			0.20			
		10g SAR		0.109			0.14			
		Deviation		-0.11			-0.11			
	Rear	1g SAR	0.225	0.213	0.193	0.28	0.27	0.25		
		10g SAR	0.153	0.145	0.13	0.19	0.19	0.17		
		Deviation	-0.02	0.08	0.14	-0.02	0.08	0.14		
RMC	Worst case check	1g SAR								
RMC		10g SAR								
RMC		Deviation								
RMC	Worst case check	1g SAR								
RMC		10g SAR								
RMC		Deviation								
RMC	Worst case check	1g SAR								
RMC		10g SAR								
RMC		Deviation								

Table 14-9 LTE2500-FDD7 #1 Body

LTE2500-FDD7 #1 Body						
Ambient Temperature: 22.5				Liquid Temperature: 22.3		
Mode	Device orientation	SAR measurement	Measured SAR [W/kg]			Reported SAR [W/kg]
			21350	21100	20850	21350
20MHz QPSK1RB	Front	M	M	M	M	M
		Tune-up			Scaling factor*	
		20.60	20.60	20.60	1.03	1.05
	Rear	Measured Power [dBm]	20.48	20.38	20.13	1.11
		1g SAR	0.48		0.49	
		10g SAR	0.27		0.28	
20MHz QPSK50% RB	Front	Deviation	0.01		0.01	
		1g SAR	0.966	0.835	0.779	0.99
		10g SAR	0.518	0.437	0.406	0.53
	Rear	Deviation	-0.03	0.11	0.19	-0.03
		Measured SAR [W/kg]			Reported SAR [W/kg]	
		21350	21100	20850	21350	21100
20MHz QPSK100% RB	Front	M	H	M		
		Tune-up			Scaling factor*	
		20.60	20.60	20.60	1.03	1.07
	Rear	Measured Power [dBm]	20.49	20.30	20.25	1.08
		1g SAR	0.362		0.37	
		10g SAR	0.196		0.20	
20MHz QPSK1RB	Rear	Deviation	0.08		0.08	
		1g SAR	0.752		0.77	
		10g SAR	0.394		0.40	
	Worst case check	Deviation	0.02		0.02	
		Measured SAR [W/kg]			Reported SAR [W/kg]	
		21350	21100	20850	21350	21100
20MHz QPSK1RB	Front	M	H	M		
		Tune-up			Scaling factor*	
		20.60	20.60	20.60	1.05	1.07
	Rear	Measured Power [dBm]	20.39	20.30	20.22	1.09
		1g SAR	0.728		0.76	
		10g SAR	0.381		0.40	
20MHz QPSK1RB	Front	Deviation	0.18		0.18	
		1g SAR				
		10g SAR				
	Rear	Deviation				
		1g SAR				
		10g SAR				
	Worst case check	Deviation				
		1g SAR				
		10g SAR				
		Deviation				