



Test Mode: 03; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:80MHz; Channel:middle



Trace: (Discrete)


|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                    |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|--------------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark             |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                    |
| 1   | 5145.973 | 46.37  | 31.72   | 5.62  | 36.86  | 46.85  | 54.00  | -7.15     | HORIZONTAL Average |
| 2   | 5149.798 | 58.35  | 31.72   | 5.62  | 36.86  | 58.83  | 74.00  | -15.17    | HORIZONTAL Peak    |
| 3   | 5290.000 | 88.34  | 31.76   | 6.00  | 36.87  | 89.23  | -----  | -----     | HORIZONTAL Average |
| 4 * | 5290.000 | 100.08 | 31.76   | 6.00  | 36.87  | 100.97 | 68.20  | 32.77     | HORIZONTAL Peak    |
| 5   | 5350.229 | 48.34  | 31.77   | 6.05  | 36.88  | 49.28  | 54.00  | -4.72     | HORIZONTAL Average |
| 6   | 5353.899 | 60.48  | 31.77   | 6.05  | 36.88  | 61.42  | 74.00  | -12.58    | HORIZONTAL Peak    |

Test Mode: 03; Polarity: Vertical; Modulation: 802.11ax; Bandwidth: 80MHz; Channel: middle



| race: (Discrete) | Frequency (MHz) |           |               |           |              |        |           |           |           |         |
|------------------|-----------------|-----------|---------------|-----------|--------------|--------|-----------|-----------|-----------|---------|
|                  | Freq            | ReadLevel | AntennaFactor | CableLoss | PreampFactor | Level  | LimitLine | OverLimit | Pol/Phase | Remark  |
|                  | MHz             | dBuV      | dB/m          | dB        | dB           | dBuV/m | dBuV/m    | dB        |           |         |
| 1                | 5110.505        | 57.86     | 31.72         | 5.65      | 36.86        | 58.37  | 74.00     | -15.63    | VERTICAL  | Peak    |
| 2                | 5139.506        | 46.63     | 31.72         | 5.63      | 36.86        | 47.12  | 54.00     | -6.88     | VERTICAL  | Average |
| 3                | 5290.000        | 92.45     | 31.76         | 6.00      | 36.87        | 93.34  | -----     | -----     | VERTICAL  | Average |
| 4 *              | 5290.000        | 104.44    | 31.76         | 6.00      | 36.87        | 105.33 | 68.20     | 37.13     | VERTICAL  | Peak    |
| 5                | 5350.535        | 49.81     | 31.77         | 6.05      | 36.88        | 50.75  | 54.00     | -3.25     | VERTICAL  | Average |
| 6                | 5352.981        | 64.01     | 31.77         | 6.05      | 36.88        | 64.95  | 74.00     | -9.05     | VERTICAL  | Peak    |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                    |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|--------------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark             |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                    |
| 1   | 5458.831 | 59.14  | 31.79   | 6.26  | 36.88  | 60.31  | 74.00  | -13.69    | HORIZONTAL Peak    |
| 2   | 5459.190 | 46.61  | 31.79   | 6.26  | 36.88  | 47.78  | 54.00  | -6.22     | HORIZONTAL Average |
| 3   | 5469.519 | 64.61  | 31.80   | 6.31  | 36.88  | 65.84  | 68.20  | -2.36     | HORIZONTAL Peak    |
| 4   | 5500.000 | 94.77  | 31.80   | 6.40  | 36.88  | 96.09  | -----  | -----     | HORIZONTAL Average |
| 5 * | 5500.000 | 105.06 | 31.80   | 6.40  | 36.88  | 106.38 | 68.20  | 38.18     | HORIZONTAL Peak    |

Test Mode: 04; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



|     | Freq     | ReadAntenna<br>Level | Factor | Cable<br>Loss | Preamp<br>Factor | Level  | Limit<br>Line | Over<br>Limit | Pol/Phase | Remark  |
|-----|----------|----------------------|--------|---------------|------------------|--------|---------------|---------------|-----------|---------|
|     | MHz      | dBuV                 | dB/m   | dB            | dB               | dBuV/m | dBuV/m        | dB            |           |         |
| 1   | 5457.031 | 59.63                | 31.79  | 6.26          | 36.88            | 60.80  | 74.00         | -13.20        | VERTICAL  | Peak    |
| 2   | 5459.910 | 46.61                | 31.79  | 6.26          | 36.88            | 47.78  | 54.00         | -6.22         | VERTICAL  | Average |
| 3   | 5468.678 | 63.76                | 31.80  | 6.31          | 36.88            | 64.99  | 68.20         | -3.21         | VERTICAL  | Peak    |
| 4   | 5500.000 | 93.36                | 31.80  | 6.40          | 36.88            | 94.68  | -----         | -----         | VERTICAL  | Average |
| 5 * | 5500.000 | 103.59               | 31.80  | 6.40          | 36.88            | 104.91 | 68.20         | 36.71         | VERTICAL  | Peak    |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

|   |            | ReadAntenna |        | Cable | Preamp |        | Limit  | Over  |            |        |
|---|------------|-------------|--------|-------|--------|--------|--------|-------|------------|--------|
|   | Freq       | Level       | Factor | Loss  | Factor | Level  | Line   | Limit | Pol/Phase  | Remark |
|   | MHz        | dBuV        | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB    |            |        |
| 1 | * 5700.000 | 95.69       | 32.01  | 6.40  | 36.89  | 97.21  | 68.20  | 29.01 | HORIZONTAL | Peak   |
| 2 | 5725.000   | 58.44       | 32.07  | 6.25  | 36.89  | 59.87  | 68.20  | -8.33 | HORIZONTAL | Peak   |
| 3 | 5729.682   | 58.98       | 32.07  | 6.25  | 36.89  | 60.41  | 68.20  | -7.79 | HORIZONTAL | Peak   |


Test Mode: 04; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

|   |            | ReadAntenna |        | Cable | Preamp |        | Limit  | Over  |           |        |
|---|------------|-------------|--------|-------|--------|--------|--------|-------|-----------|--------|
|   | Freq       | Level       | Factor | Loss  | Factor | Level  | Line   | Limit | Pol/Phase | Remark |
|   | MHz        | dBuV        | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB    |           |        |
| 1 | * 5700.000 | 96.32       | 32.01  | 6.40  | 36.89  | 97.84  | 68.20  | 29.64 | VERTICAL  | Peak   |
| 2 | 5725.000   | 59.21       | 32.07  | 6.25  | 36.89  | 60.64  | 68.20  | -7.56 | VERTICAL  | Peak   |
| 3 | 5725.783   | 60.98       | 32.07  | 6.25  | 36.89  | 62.41  | 68.20  | -5.79 | VERTICAL  | Peak   |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                    |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|--------------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark             |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                    |
| 1   | 5452.116 | 58.89  | 31.79   | 6.26  | 36.88  | 60.06  | 74.00  | -13.94    | HORIZONTAL Peak    |
| 2   | 5459.791 | 45.77  | 31.79   | 6.26  | 36.88  | 46.94  | 54.00  | -7.06     | HORIZONTAL Average |
| 3   | 5469.880 | 64.48  | 31.80   | 6.31  | 36.88  | 65.71  | 68.20  | -2.49     | HORIZONTAL Peak    |
| 4   | 5500.000 | 97.19  | 31.80   | 6.40  | 36.88  | 98.51  | -----  | -----     | HORIZONTAL Average |
| 5 * | 5500.000 | 107.49 | 31.80   | 6.40  | 36.88  | 108.81 | 68.20  | 40.61     | HORIZONTAL Peak    |

Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                  |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|------------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark           |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                  |
| 1   | 5436.321 | 58.36  | 31.79   | 6.20  | 36.88  | 59.47  | 74.00  | -14.53    | VERTICAL Peak    |
| 2   | 5459.070 | 46.02  | 31.79   | 6.26  | 36.88  | 47.19  | 54.00  | -6.81     | VERTICAL Average |
| 3   | 5469.519 | 62.42  | 31.80   | 6.31  | 36.88  | 63.65  | 68.20  | -4.55     | VERTICAL Peak    |
| 4   | 5500.000 | 97.52  | 31.80   | 6.40  | 36.88  | 98.84  | -----  | -----     | VERTICAL Average |
| 5 * | 5500.000 | 107.62 | 31.80   | 6.40  | 36.88  | 108.94 | 68.20  | 40.74     | VERTICAL Peak    |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

|     |          | ReadAntenna |        | Cable | Preamp |        | Limit  | Over  |            |        |
|-----|----------|-------------|--------|-------|--------|--------|--------|-------|------------|--------|
|     | Freq     | Level       | Factor | Loss  | Factor | Level  | Line   | Limit | Pol/Phase  | Remark |
|     | MHz      | dBuV        | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB    |            |        |
| 1 * | 5700.000 | 101.88      | 32.01  | 6.40  | 36.89  | 103.40 | 68.20  | 35.20 | HORIZONTAL | Peak   |
| 2   | 5725.000 | 57.56       | 32.07  | 6.25  | 36.89  | 58.99  | 68.20  | -9.21 | HORIZONTAL | Peak   |
| 3   | 5728.582 | 58.86       | 32.07  | 6.25  | 36.89  | 60.29  | 68.20  | -7.91 | HORIZONTAL | Peak   |


Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



race: (Discrete)

|     | Freq     | ReadAntenna<br>Level Factor | Cable<br>Loss | Preamp<br>Factor | Level | Limit<br>Line | Over<br>Limit | Pol/Phase | Remark        |
|-----|----------|-----------------------------|---------------|------------------|-------|---------------|---------------|-----------|---------------|
|     | MHz      | dBuV                        | dB/m          | dB               | dB    | dBuV/m        | dBuV/m        | dB        |               |
| 1 * | 5700.000 | 102.76                      | 32.01         | 6.40             | 36.89 | 104.28        | 68.20         | 36.08     | VERTICAL Peak |
| 2   | 5725.000 | 57.63                       | 32.07         | 6.25             | 36.89 | 59.06         | 68.20         | -9.14     | VERTICAL Peak |
| 3   | 5730.082 | 60.52                       | 32.07         | 6.25             | 36.89 | 61.95         | 68.20         | -6.25     | VERTICAL Peak |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



race: (Discrete)

|     | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |            |         |
|-----|----------|-------------|--------|--------|--------|--------|--------|--------|------------|---------|
|     | MHz      | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark  |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |            |         |
| 1   | 5453.336 | 58.24       | 31.79  | 6.26   | 36.88  | 59.41  | 74.00  | -14.59 | HORIZONTAL | Peak    |
| 2   | 5459.761 | 46.47       | 31.79  | 6.26   | 36.88  | 47.64  | 54.00  | -6.36  | HORIZONTAL | Average |
| 3   | 5469.272 | 60.41       | 31.80  | 6.31   | 36.88  | 61.64  | 68.20  | -6.56  | HORIZONTAL | Peak    |
| 4   | 5510.000 | 92.08       | 31.80  | 6.40   | 36.88  | 93.40  | -----  | -----  | HORIZONTAL | Average |
| 5 * | 5510.000 | 101.82      | 31.80  | 6.40   | 36.88  | 103.14 | 68.20  | 34.94  | HORIZONTAL | Peak    |


Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                  |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|------------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark           |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                  |
| 1   | 5458.503 | 46.54  | 31.79   | 6.26  | 36.88  | 47.71  | 54.00  | -6.29     | VERTICAL Average |
| 2   | 5459.481 | 60.32  | 31.79   | 6.26  | 36.88  | 61.49  | 74.00  | -12.51    | VERTICAL Peak    |
| 3   | 5469.412 | 60.94  | 31.80   | 6.31  | 36.88  | 62.17  | 68.20  | -6.03     | VERTICAL Peak    |
| 4   | 5510.000 | 92.12  | 31.80   | 6.40  | 36.88  | 93.44  | -----  | -----     | VERTICAL Average |
| 5 * | 5510.000 | 102.28 | 31.80   | 6.40  | 36.88  | 103.60 | 68.20  | 35.40     | VERTICAL Peak    |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



race: (Discrete)

|     | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |       |            |        |
|-----|----------|-------------|--------|--------|--------|--------|--------|-------|------------|--------|
|     |          | Level       | Factor | Loss   | Factor | Level  | Line   | Limit | Pol/Phase  | Remark |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB    |            |        |
| 1 * | 5670.000 | 98.09       | 31.97  | 6.37   | 36.89  | 99.54  | 68.20  | 31.34 | HORIZONTAL | Peak   |
| 2   | 5725.000 | 56.95       | 32.07  | 6.25   | 36.89  | 58.38  | 68.20  | -9.82 | HORIZONTAL | Peak   |
| 3   | 5727.238 | 57.75       | 32.07  | 6.25   | 36.89  | 59.18  | 68.20  | -9.02 | HORIZONTAL | Peak   |


Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)


|     | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |           |        |
|-----|----------|-------------|--------|--------|--------|--------|--------|--------|-----------|--------|
|     |          | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 * | 5670.000 | 98.30       | 31.97  | 6.37   | 36.89  | 99.75  | 68.20  | 31.55  | VERTICAL  | Peak   |
| 2   | 5725.000 | 56.45       | 32.07  | 6.25   | 36.89  | 57.88  | 68.20  | -10.32 | VERTICAL  | Peak   |
| 3   | 5741.157 | 58.25       | 32.10  | 6.20   | 36.89  | 59.66  | 68.20  | -8.54  | VERTICAL  | Peak   |

Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low




|     |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over   |            |         |
|-----|----------|--------|---------|-------|--------|--------|--------|--------|------------|---------|
|     | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark  |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |            |         |
| 1   | 5452.595 | 45.78  | 31.79   | 6.26  | 36.88  | 46.95  | 54.00  | -7.05  | HORIZONTAL | Average |
| 2   | 5454.273 | 58.07  | 31.79   | 6.26  | 36.88  | 59.24  | 74.00  | -14.76 | HORIZONTAL | Peak    |
| 3   | 5469.639 | 61.87  | 31.80   | 6.31  | 36.88  | 63.10  | 68.20  | -5.10  | HORIZONTAL | Peak    |
| 4   | 5500.000 | 97.11  | 31.80   | 6.40  | 36.88  | 98.43  | -----  | -----  | HORIZONTAL | Average |
| 5 * | 5500.000 | 107.67 | 31.80   | 6.40  | 36.88  | 108.99 | 68.20  | 40.79  | HORIZONTAL | Peak    |

Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                  |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|------------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark           |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                  |
| 1   | 5414.618 | 58.49  | 31.79   | 6.06  | 36.88  | 59.46  | 74.00  | -14.54    | VERTICAL Peak    |
| 2   | 5452.715 | 45.66  | 31.79   | 6.26  | 36.88  | 46.83  | 54.00  | -7.17     | VERTICAL Average |
| 3   | 5469.759 | 62.55  | 31.80   | 6.31  | 36.88  | 63.78  | 68.20  | -4.42     | VERTICAL Peak    |
| 4   | 5500.000 | 97.93  | 31.80   | 6.40  | 36.88  | 99.25  | -----  | -----     | VERTICAL Average |
| 5 * | 5500.000 | 108.22 | 31.80   | 6.40  | 36.88  | 109.54 | 68.20  | 41.34     | VERTICAL Peak    |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

|      | Read     | Antenna | Cable | Preamp | Limit  | Over   |           |                       |
|------|----------|---------|-------|--------|--------|--------|-----------|-----------------------|
| Freq | Level    | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark                |
| MHz  | dBuV     | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                       |
| 1 *  | 5700.000 | 102.18  | 32.01 | 6.40   | 36.89  | 103.70 | 68.20     | 35.50 HORIZONTAL Peak |
| 2    | 5725.000 | 57.64   | 32.07 | 6.25   | 36.89  | 59.07  | 68.20     | -9.13 HORIZONTAL Peak |
| 3    | 5729.982 | 58.70   | 32.07 | 6.25   | 36.89  | 60.13  | 68.20     | -8.07 HORIZONTAL Peak |


Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

|     | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |       |           |        |
|-----|----------|-------------|--------|--------|--------|--------|--------|-------|-----------|--------|
|     | MHz      | Level       | Factor | Loss   | Factor | Level  | Line   | Limit | Pol/Phase | Remark |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB    |           |        |
| 1 * | 5700.000 | 102.63      | 32.01  | 6.40   | 36.89  | 104.15 | 68.20  | 35.95 | VERTICAL  | Peak   |
| 2   | 5725.000 | 57.49       | 32.07  | 6.25   | 36.89  | 58.92  | 68.20  | -9.28 | VERTICAL  | Peak   |
| 3   | 5731.082 | 59.25       | 32.07  | 6.25   | 36.89  | 60.68  | 68.20  | -7.52 | VERTICAL  | Peak   |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                    |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|--------------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark             |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                    |
| 1   | 5459.761 | 62.18  | 31.79   | 6.26  | 36.88  | 63.35  | 74.00  | -10.65    | HORIZONTAL Peak    |
| 2   | 5459.901 | 47.66  | 31.79   | 6.26  | 36.88  | 48.83  | 54.00  | -5.17     | HORIZONTAL Average |
| 3   | 5469.272 | 63.69  | 31.80   | 6.31  | 36.88  | 64.92  | 68.20  | -3.28     | HORIZONTAL Peak    |
| 4   | 5510.000 | 92.90  | 31.80   | 6.40  | 36.88  | 94.22  | -----  | -----     | HORIZONTAL Average |
| 5 * | 5510.000 | 103.20 | 31.80   | 6.40  | 36.88  | 104.52 | 68.20  | 36.32     | HORIZONTAL Peak    |


Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)


|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                  |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|------------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark           |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                  |
| 1   | 5458.503 | 61.86  | 31.79   | 6.26  | 36.88  | 63.03  | 74.00  | -10.97    | VERTICAL Peak    |
| 2   | 5459.622 | 48.06  | 31.79   | 6.26  | 36.88  | 49.23  | 54.00  | -4.77     | VERTICAL Average |
| 3   | 5469.412 | 64.45  | 31.80   | 6.31  | 36.88  | 65.68  | 68.20  | -2.52     | VERTICAL Peak    |
| 4   | 5510.000 | 93.56  | 31.80   | 6.40  | 36.88  | 94.88  | -----  | -----     | VERTICAL Average |
| 5 * | 5510.000 | 103.69 | 31.80   | 6.40  | 36.88  | 105.01 | 68.20  | 36.81     | VERTICAL Peak    |

Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High




|     | Freq     | ReadAntenna<br>Level | Factor | Cable<br>Loss | Preamp<br>Factor | Level  | Limit<br>Line | Over<br>Limit | Pol/Phase  | Remark |
|-----|----------|----------------------|--------|---------------|------------------|--------|---------------|---------------|------------|--------|
|     | MHz      | dBuV                 | dB/m   | dB            | dB               | dBuV/m | dBuV/m        | dB            |            |        |
| 1 * | 5670.000 | 97.90                | 31.97  | 6.37          | 36.89            | 99.35  | 68.20         | 31.15         | HORIZONTAL | Peak   |
| 2   | 5725.000 | 56.41                | 32.07  | 6.25          | 36.89            | 57.84  | 68.20         | -10.36        | HORIZONTAL | Peak   |

Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



|     | Freq     | ReadAntenna<br>Level | Factor | Cable<br>Loss | Preamp<br>Factor | Level  | Limit<br>Line | Over<br>Limit | Pol/Phase | Remark |
|-----|----------|----------------------|--------|---------------|------------------|--------|---------------|---------------|-----------|--------|
|     | MHz      | dBuV                 | dB/m   | dB            | dB               | dBuV/m | dBuV/m        | dB            |           |        |
| 1 * | 5670.000 | 98.59                | 31.97  | 6.37          | 36.89            | 100.04 | 68.20         | 31.84         | VERTICAL  | Peak   |
| 2   | 5725.000 | 56.98                | 32.07  | 6.25          | 36.89            | 58.41  | 68.20         | -9.79         | VERTICAL  | Peak   |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



race: (Discrete)

|     | Freq     | Read  | Antenna | Cable | Preamp | Limit  | Over   |           |                    |
|-----|----------|-------|---------|-------|--------|--------|--------|-----------|--------------------|
|     | MHz      | Level | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark             |
|     | MHz      | dBuV  | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                    |
| 1   | 5451.951 | 59.43 | 31.79   | 6.26  | 36.88  | 60.60  | 74.00  | -13.40    | HORIZONTAL Peak    |
| 2   | 5452.130 | 47.86 | 31.79   | 6.26  | 36.88  | 49.03  | 54.00  | -4.97     | HORIZONTAL Average |
| 3   | 5460.539 | 60.53 | 31.79   | 6.26  | 36.88  | 61.70  | 68.20  | -6.50     | HORIZONTAL Peak    |
| 4   | 5530.000 | 88.96 | 31.83   | 6.37  | 36.89  | 90.27  | -----  | -----     | HORIZONTAL Average |
| 5 * | 5530.000 | 99.04 | 31.83   | 6.37  | 36.89  | 100.35 | 68.20  | 32.15     | HORIZONTAL Peak    |


Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Trace: (Discrete)

|     | Freq     | Read  | Antenna | Cable | Preamp | Limit  | Over   |           |                  |
|-----|----------|-------|---------|-------|--------|--------|--------|-----------|------------------|
|     | MHz      | Level | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark           |
|     | MHz      | dBuV  | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                  |
| 1   | 5456.780 | 48.05 | 31.79   | 6.26  | 36.88  | 49.22  | 54.00  | -4.78     | VERTICAL Average |
| 2   | 5457.854 | 60.01 | 31.79   | 6.26  | 36.88  | 61.18  | 74.00  | -12.82    | VERTICAL Peak    |
| 3   | 5463.583 | 61.21 | 31.80   | 6.31  | 36.88  | 62.44  | 68.20  | -5.76     | VERTICAL Peak    |
| 4   | 5530.000 | 89.91 | 31.83   | 6.37  | 36.89  | 91.22  | -----  | -----     | VERTICAL Average |
| 5 * | 5530.000 | 98.71 | 31.83   | 6.37  | 36.89  | 100.02 | 68.20  | 31.82     | VERTICAL Peak    |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:High



Trace: (Discrete)

|     | Freq     | Read  | Antenna | Cable | Preamp |        | Limit  | Over  |            |        |
|-----|----------|-------|---------|-------|--------|--------|--------|-------|------------|--------|
|     |          | Level | Factor  | Loss  | Factor | Level  | Line   | Limit | Pol/Phase  | Remark |
|     | MHz      | dBuV  | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB    |            |        |
| 1 * | 5610.000 | 96.53 | 31.91   | 6.32  | 36.89  | 97.87  | 68.20  | 29.67 | HORIZONTAL | Peak   |
| 2   | 5732.788 | 57.87 | 32.07   | 6.25  | 36.89  | 59.30  | 68.20  | -8.90 | HORIZONTAL | Peak   |


Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:High



Trace: (Discrete)

|     | Freq     | Read<br>Level | Antenna<br>Factor | Cable<br>Loss | Preamp<br>Factor | Level  | Limit<br>Line | Over<br>Limit | Pol/Phase | Remark |
|-----|----------|---------------|-------------------|---------------|------------------|--------|---------------|---------------|-----------|--------|
|     | MHz      | dBuV          | dB/m              | dB            | dB               | dBuV/m | dBuV/m        | dB            |           |        |
| 1 * | 5610.000 | 96.99         | 31.91             | 6.32          | 36.89            | 98.33  | 68.20         | 30.13         | VERTICAL  | Peak   |
| 2   | 5751.660 | 57.60         | 32.10             | 6.20          | 36.89            | 59.01  | 68.20         | -9.19         | VERTICAL  | Peak   |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

|     |          | ReadAntenna |        | Cable | Preamp |        | Limit  | Over   |            |         |
|-----|----------|-------------|--------|-------|--------|--------|--------|--------|------------|---------|
|     | Freq     | Level       | Factor | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark  |
|     | MHz      | dBuV        | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |            |         |
| 1   | 5458.590 | 58.43       | 31.79  | 6.26  | 36.88  | 59.60  | 74.00  | -14.40 | HORIZONTAL | Peak    |
| 2   | 5459.070 | 46.43       | 31.79  | 6.26  | 36.88  | 47.60  | 54.00  | -6.40  | HORIZONTAL | Average |
| 3   | 5468.437 | 64.11       | 31.80  | 6.31  | 36.88  | 65.34  | 68.20  | -2.86  | HORIZONTAL | Peak    |
| 4   | 5500.000 | 96.88       | 31.80  | 6.40  | 36.88  | 98.20  | -----  | -----  | HORIZONTAL | Average |
| 5 * | 5500.000 | 109.32      | 31.80  | 6.40  | 36.88  | 110.64 | 68.20  | 42.44  | HORIZONTAL | Peak    |


Test Mode: 04; Polarity: Vertical; Modulation:802.11ax; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                  |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|------------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark           |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                  |
| 1   | 5459.670 | 58.15  | 31.79   | 6.26  | 36.88  | 59.32  | 74.00  | -14.68    | VERTICAL Peak    |
| 2   | 5459.791 | 46.27  | 31.79   | 6.26  | 36.88  | 47.44  | 54.00  | -6.56     | VERTICAL Average |
| 3   | 5469.880 | 64.39  | 31.80   | 6.31  | 36.88  | 65.62  | 68.20  | -2.58     | VERTICAL Peak    |
| 4   | 5500.000 | 97.59  | 31.80   | 6.40  | 36.88  | 98.91  | -----  | -----     | VERTICAL Average |
| 5 * | 5500.000 | 109.87 | 31.80   | 6.40  | 36.88  | 111.19 | 68.20  | 42.99     | VERTICAL Peak    |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

|     |          | ReadAntenna |        | Cable | Preamp |        | Limit  | Over  |            |        |
|-----|----------|-------------|--------|-------|--------|--------|--------|-------|------------|--------|
|     | Freq     | Level       | Factor | Loss  | Factor | Level  | Line   | Limit | Pol/Phase  | Remark |
|     | MHz      | dBuV        | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB    |            |        |
| 1 * | 5700.000 | 104.27      | 32.01  | 6.40  | 36.89  | 105.79 | 68.20  | 37.59 | HORIZONTAL | Peak   |
| 2   | 5725.000 | 61.12       | 32.07  | 6.25  | 36.89  | 62.55  | 68.20  | -5.65 | HORIZONTAL | Peak   |
| 3   | 5729.282 | 60.33       | 32.07  | 6.25  | 36.89  | 61.76  | 68.20  | -6.44 | HORIZONTAL | Peak   |


Test Mode: 04; Polarity: Vertical; Modulation:802.11ax; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

|     | Freq     | ReadAntenna<br>Level | Factor | Cable<br>Loss | Preamp<br>Factor | Level  | Limit<br>Line | Over<br>Limit | Pol/Phase | Remark |
|-----|----------|----------------------|--------|---------------|------------------|--------|---------------|---------------|-----------|--------|
|     | MHz      | dBuV                 | dB/m   | dB            | dB               | dBuV/m | dBuV/m        | dB            |           |        |
| 1 * | 5700.000 | 103.48               | 32.01  | 6.40          | 36.89            | 105.00 | 68.20         | 36.80         | VERTICAL  | Peak   |
| 2   | 5725.000 | 59.35                | 32.07  | 6.25          | 36.89            | 60.78  | 68.20         | -7.42         | VERTICAL  | Peak   |
| 3   | 5730.882 | 60.01                | 32.07  | 6.25          | 36.89            | 61.44  | 68.20         | -6.76         | VERTICAL  | Peak   |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:40MHz; Channel:Low



race: (Discrete)


|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                    |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|--------------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark             |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                    |
| 1   | 5458.364 | 58.98  | 31.79   | 6.26  | 36.88  | 60.15  | 74.00  | -13.85    | HORIZONTAL Peak    |
| 2   | 5459.481 | 46.69  | 31.79   | 6.26  | 36.88  | 47.86  | 54.00  | -6.14     | HORIZONTAL Average |
| 3   | 5469.552 | 60.91  | 31.80   | 6.31  | 36.88  | 62.14  | 68.20  | -6.06     | HORIZONTAL Peak    |
| 4   | 5510.000 | 91.99  | 31.80   | 6.40  | 36.88  | 93.31  | -----  | -----     | HORIZONTAL Average |
| 5 * | 5510.000 | 104.15 | 31.80   | 6.40  | 36.88  | 105.47 | 68.20  | 37.27     | HORIZONTAL Peak    |

Test Mode: 04; Polarity: Vertical; Modulation:802.11ax; Bandwidth:40MHz; Channel:Low



|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                  |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|------------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark           |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                  |
| 1   | 5459.761 | 59.48  | 31.79   | 6.26  | 36.88  | 60.65  | 74.00  | -13.35    | VERTICAL Peak    |
| 2   | 5459.901 | 46.88  | 31.79   | 6.26  | 36.88  | 48.05  | 54.00  | -5.95     | VERTICAL Average |
| 3   | 5469.552 | 62.63  | 31.80   | 6.31  | 36.88  | 63.86  | 68.20  | -4.34     | VERTICAL Peak    |
| 4   | 5510.000 | 92.57  | 31.80   | 6.40  | 36.88  | 93.89  | -----  | -----     | VERTICAL Average |
| 5 * | 5510.000 | 104.74 | 31.80   | 6.40  | 36.88  | 106.06 | 68.20  | 37.86     | VERTICAL Peak    |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:40MHz; Channel:High



race: (Discrete)

|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                 |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|-----------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark          |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                 |
| 1 * | 5670.000 | 100.24 | 31.97   | 6.37  | 36.89  | 101.69 | 68.20  | 33.49     | HORIZONTAL Peak |
| 2   | 5725.000 | 56.83  | 32.07   | 6.25  | 36.89  | 58.26  | 68.20  | -9.94     | HORIZONTAL Peak |
| 3   | 5741.017 | 58.36  | 32.10   | 6.20  | 36.89  | 59.77  | 68.20  | -8.43     | HORIZONTAL Peak |


Test Mode: 04; Polarity: Vertical; Modulation:802.11ax; Bandwidth:40MHz; Channel:High



Trace: (Discrete)


|     | Freq     | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Limit Level | Over Limit | Pol/Phase | Remark        |
|-----|----------|------------|----------------|------------|---------------|-------------|------------|-----------|---------------|
|     | MHz      | dBuV       | dB/m           | dB         | dB            | dBuV/m      | dB         |           |               |
| 1 * | 5670.000 | 100.91     | 31.97          | 6.37       | 36.89         | 102.36      | 68.20      | 34.16     | VERTICAL Peak |
| 2   | 5725.000 | 56.41      | 32.07          | 6.25       | 36.89         | 57.84       | 68.20      | -10.36    | VERTICAL Peak |
| 3   | 5750.314 | 58.03      | 32.10          | 6.20       | 36.89         | 59.44       | 68.20      | -8.76     | VERTICAL Peak |

Test Mode: 04; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:80MHz; Channel:Low




|     | Freq     | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |                    |
|-----|----------|--------|---------|-------|--------|--------|--------|-----------|--------------------|
|     | MHz      | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark             |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                    |
| 1   | 5447.484 | 59.32  | 31.79   | 6.20  | 36.88  | 60.43  | 74.00  | -13.57    | HORIZONTAL Peak    |
| 2   | 5457.675 | 48.15  | 31.79   | 6.26  | 36.88  | 49.32  | 54.00  | -4.68     | HORIZONTAL Average |
| 3   | 5467.526 | 60.82  | 31.80   | 6.31  | 36.88  | 62.05  | 68.20  | -6.15     | HORIZONTAL Peak    |
| 4   | 5530.000 | 88.80  | 31.83   | 6.37  | 36.89  | 90.11  | -----  | -----     | HORIZONTAL Average |
| 5 * | 5530.000 | 101.02 | 31.83   | 6.37  | 36.89  | 102.33 | 68.20  | 34.13     | HORIZONTAL Peak    |

Test Mode: 04; Polarity: Vertical; Modulation:802.11ax; Bandwidth:80MHz; Channel:Low



|     | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |           |         |
|-----|----------|-------------|--------|--------|--------|--------|--------|--------|-----------|---------|
|     | MHz      | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase | Remark  |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |           |         |
| 1   | 5455.349 | 61.08       | 31.79  | 6.26   | 36.88  | 62.25  | 74.00  | -11.75 | VERTICAL  | Peak    |
| 2   | 5458.212 | 48.17       | 31.79  | 6.26   | 36.88  | 49.34  | 54.00  | -4.66  | VERTICAL  | Average |
| 3   | 5466.092 | 60.88       | 31.80  | 6.31   | 36.88  | 62.11  | 68.20  | -6.09  | VERTICAL  | Peak    |
| 4   | 5530.000 | 89.78       | 31.83  | 6.37   | 36.89  | 91.09  | -----  | -----  | VERTICAL  | Average |
| 5 * | 5530.000 | 101.15      | 31.83  | 6.37   | 36.89  | 102.46 | 68.20  | 34.26  | VERTICAL  | Peak    |


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:80MHz; Channel:High



Trace: (Discrete)

|      | Read     | Antenna | Cable | Preamp | Limit  | Over   |           |                       |
|------|----------|---------|-------|--------|--------|--------|-----------|-----------------------|
| Freq | Level    | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark                |
| MHz  | dBuV     | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                       |
| 1 *  | 5610.000 | 99.33   | 31.91 | 6.32   | 36.89  | 100.67 | 68.20     | 32.47 HORIZONTAL Peak |
| 2    | 5748.003 | 58.73   | 32.10 | 6.20   | 36.89  | 60.14  | 68.20     | -8.06 HORIZONTAL Peak |


Test Mode: 04; Polarity: Vertical; Modulation:802.11ax; Bandwidth:80MHz; Channel:High



Trace: (Discrete)


|     |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over  |           |        |
|-----|----------|--------|---------|-------|--------|--------|--------|-------|-----------|--------|
|     | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit | Pol/Phase | Remark |
|     | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB    |           |        |
| 1 * | 5610.000 | 100.77 | 31.91   | 6.32  | 36.89  | 102.11 | 68.20  | 33.91 | VERTICAL  | Peak   |
| 2   | 5731.775 | 57.12  | 32.07   | 6.25  | 36.89  | 58.55  | 68.20  | -9.65 | VERTICAL  | Peak   |

Test Mode: 05; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




|   |          | Read  | Antenna | Cable | Preamp |        | Limit  | Over   |            |        |
|---|----------|-------|---------|-------|--------|--------|--------|--------|------------|--------|
|   | Freq     | Level | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV  | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 5649.827 | 57.30 | 31.95   | 6.35  | 36.89  | 58.71  | 68.20  | -9.49  | HORIZONTAL | Peak   |
| 2 | 5715.000 | 58.38 | 32.04   | 6.33  | 36.89  | 59.86  | 109.40 | -49.54 | HORIZONTAL | Peak   |
| 3 | 5725.000 | 67.06 | 32.07   | 6.25  | 36.89  | 68.49  | 122.20 | -53.71 | HORIZONTAL | Peak   |
| 4 | 5745.000 | 96.82 | 32.10   | 6.20  | 36.89  | 98.23  | 125.20 | -26.97 | HORIZONTAL | Peak   |

Test Mode: 05; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



|   |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over   |           |        |
|---|----------|--------|---------|-------|--------|--------|--------|--------|-----------|--------|
|   | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 5647.473 | 57.58  | 31.95   | 6.35  | 36.89  | 58.99  | 68.20  | -9.21  | VERTICAL  | Peak   |
| 2 | 5715.000 | 59.68  | 32.04   | 6.33  | 36.89  | 61.16  | 109.40 | -48.24 | VERTICAL  | Peak   |
| 3 | 5725.000 | 69.58  | 32.07   | 6.25  | 36.89  | 71.01  | 122.20 | -51.19 | VERTICAL  | Peak   |
| 4 | 5745.000 | 100.14 | 32.10   | 6.20  | 36.89  | 101.55 | 125.20 | -23.65 | VERTICAL  | Peak   |


Test Mode: 05; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

|   |          | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |            |        |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|------------|--------|
|   | Freq     | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 5825.000 | 95.02       | 32.23  | 6.04   | 36.90  | 96.39  | 125.20 | -28.81 | HORIZONTAL | Peak   |
| 2 | 5850.000 | 58.39       | 32.25  | 6.00   | 36.90  | 59.74  | 122.20 | -62.46 | HORIZONTAL | Peak   |
| 3 | 5860.000 | 57.71       | 32.27  | 5.96   | 36.90  | 59.04  | 109.40 | -50.36 | HORIZONTAL | Peak   |
| 4 | 5934.957 | 57.89       | 32.34  | 6.00   | 36.90  | 59.33  | 68.20  | -8.87  | HORIZONTAL | Peak   |


Test Mode: 05; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

|   |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over   |           |        |
|---|----------|--------|---------|-------|--------|--------|--------|--------|-----------|--------|
|   | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 5825.000 | 102.27 | 32.23   | 6.04  | 36.90  | 103.64 | 125.20 | -21.56 | VERTICAL  | Peak   |
| 2 | 5850.000 | 62.05  | 32.25   | 6.00  | 36.90  | 63.40  | 122.20 | -58.80 | VERTICAL  | Peak   |
| 3 | 5860.000 | 60.74  | 32.27   | 5.96  | 36.90  | 62.07  | 109.40 | -47.33 | VERTICAL  | Peak   |
| 4 | 5930.098 | 58.94  | 32.34   | 6.00  | 36.90  | 60.38  | 68.20  | -7.82  | VERTICAL  | Peak   |


Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|   |          | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |            |        |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|------------|--------|
|   | Freq     | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 5641.521 | 57.59       | 31.95  | 6.35   | 36.89  | 59.00  | 68.20  | -9.20  | HORIZONTAL | Peak   |
| 2 | 5715.000 | 62.02       | 32.04  | 6.33   | 36.89  | 63.50  | 109.40 | -45.90 | HORIZONTAL | Peak   |
| 3 | 5725.000 | 70.51       | 32.07  | 6.25   | 36.89  | 71.94  | 122.20 | -50.26 | HORIZONTAL | Peak   |
| 4 | 5745.000 | 102.91      | 32.10  | 6.20   | 36.89  | 104.32 | 125.20 | -20.88 | HORIZONTAL | Peak   |

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




|   |          | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |           |        |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|-----------|--------|
|   | Freq     | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 5640.276 | 57.49       | 31.95  | 6.35   | 36.89  | 58.90  | 68.20  | -9.30  | VERTICAL  | Peak   |
| 2 | 5715.000 | 61.32       | 32.04  | 6.33   | 36.89  | 62.80  | 109.40 | -46.60 | VERTICAL  | Peak   |
| 3 | 5725.000 | 70.71       | 32.07  | 6.25   | 36.89  | 72.14  | 122.20 | -50.06 | VERTICAL  | Peak   |
| 4 | 5745.000 | 103.34      | 32.10  | 6.20   | 36.89  | 104.75 | 125.20 | -20.45 | VERTICAL  | Peak   |

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



|   |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over   |            |        |
|---|----------|--------|---------|-------|--------|--------|--------|--------|------------|--------|
|   | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 5825.000 | 102.09 | 32.23   | 6.04  | 36.90  | 103.46 | 125.20 | -21.74 | HORIZONTAL | Peak   |
| 2 | 5850.000 | 58.90  | 32.25   | 6.00  | 36.90  | 60.25  | 122.20 | -61.95 | HORIZONTAL | Peak   |
| 3 | 5860.000 | 58.06  | 32.27   | 5.96  | 36.90  | 59.39  | 109.40 | -50.01 | HORIZONTAL | Peak   |
| 4 | 5928.532 | 58.18  | 32.34   | 6.00  | 36.90  | 59.62  | 68.20  | -8.58  | HORIZONTAL | Peak   |


Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|            | Read   | Antenna | Cable | Preamp | Limit  | Over   |           |               |
|------------|--------|---------|-------|--------|--------|--------|-----------|---------------|
| Freq       | Level  | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark        |
| MHz        | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |               |
| 1 5825.000 | 106.23 | 32.23   | 6.04  | 36.90  | 107.60 | 125.20 | -17.60    | VERTICAL Peak |
| 2 5850.000 | 68.79  | 32.25   | 6.00  | 36.90  | 70.14  | 122.20 | -52.06    | VERTICAL Peak |
| 3 5860.000 | 61.96  | 32.27   | 5.96  | 36.90  | 63.29  | 109.40 | -46.11    | VERTICAL Peak |
| 4 5939.035 | 58.60  | 32.34   | 6.00  | 36.90  | 60.04  | 68.20  | -8.16     | VERTICAL Peak |

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




|   |          | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |            |        |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|------------|--------|
|   | Freq     | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 5641.601 | 57.55       | 31.95  | 6.35   | 36.89  | 58.96  | 68.20  | -9.24  | HORIZONTAL | Peak   |
| 2 | 5715.000 | 72.80       | 32.04  | 6.33   | 36.89  | 74.28  | 109.40 | -35.12 | HORIZONTAL | Peak   |
| 3 | 5725.000 | 77.30       | 32.07  | 6.25   | 36.89  | 78.73  | 122.20 | -43.47 | HORIZONTAL | Peak   |
| 4 | 5755.000 | 100.94      | 32.10  | 6.20   | 36.89  | 102.35 | 125.20 | -22.85 | HORIZONTAL | Peak   |

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



|      | ReadAntenna | Cable  | Preamp | Limit  | Over   |        |        |           |               |
|------|-------------|--------|--------|--------|--------|--------|--------|-----------|---------------|
| Freq | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase | Remark        |
| MHz  | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |           |               |
| 1    | 5648.545    | 58.08  | 31.95  | 6.35   | 36.89  | 59.49  | 68.20  | -8.71     | VERTICAL Peak |
| 2    | 5715.000    | 74.93  | 32.04  | 6.33   | 36.89  | 76.41  | 109.40 | -32.99    | VERTICAL Peak |
| 3    | 5725.000    | 77.79  | 32.07  | 6.25   | 36.89  | 79.22  | 122.20 | -42.98    | VERTICAL Peak |
| 4    | 5755.000    | 101.82 | 32.10  | 6.20   | 36.89  | 103.23 | 125.20 | -21.97    | VERTICAL Peak |


Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

|      | Read     | Antenna | Cable | Preamp |        | Limit  | Over   |           |                 |
|------|----------|---------|-------|--------|--------|--------|--------|-----------|-----------------|
| Freq | Level    | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase | Remark          |
| MHz  | dBuV     | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |           |                 |
| 1    | 5795.000 | 100.20  | 32.19 | 6.10   | 36.89  | 101.60 | 125.20 | -23.60    | HORIZONTAL Peak |
| 2    | 5850.000 | 58.25   | 32.25 | 6.00   | 36.90  | 59.60  | 122.20 | -62.60    | HORIZONTAL Peak |
| 3    | 5860.000 | 59.28   | 32.27 | 5.96   | 36.90  | 60.61  | 109.40 | -48.79    | HORIZONTAL Peak |
| 4    | 5928.755 | 58.09   | 32.34 | 6.00   | 36.90  | 59.53  | 68.20  | -8.67     | HORIZONTAL Peak |


Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)


|   |          | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |           |        |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|-----------|--------|
|   | Freq     | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 5795.000 | 102.94      | 32.19  | 6.10   | 36.89  | 104.34 | 125.20 | -20.86 | VERTICAL  | Peak   |
| 2 | 5850.000 | 63.12       | 32.25  | 6.00   | 36.90  | 64.47  | 122.20 | -57.73 | VERTICAL  | Peak   |
| 3 | 5860.000 | 62.63       | 32.27  | 5.96   | 36.90  | 63.96  | 109.40 | -45.44 | VERTICAL  | Peak   |
| 4 | 5943.721 | 57.97       | 32.36  | 6.05   | 36.90  | 59.48  | 68.20  | -8.72  | VERTICAL  | Peak   |

Test Mode: 05; Polarity: Horizontal; Modulation: 802.11ac; Bandwidth: 20MHz; Channel: Low




|   |          | ReadAntenna |        | Cable | Preamp |        | Limit  | Over   |            |        |
|---|----------|-------------|--------|-------|--------|--------|--------|--------|------------|--------|
|   | Freq     | Level       | Factor | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV        | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 5646.227 | 58.82       | 31.95  | 6.35  | 36.89  | 60.23  | 68.20  | -7.97  | HORIZONTAL | Peak   |
| 2 | 5715.000 | 60.83       | 32.04  | 6.33  | 36.89  | 62.31  | 109.40 | -47.09 | HORIZONTAL | Peak   |
| 3 | 5725.000 | 72.05       | 32.07  | 6.25  | 36.89  | 73.48  | 122.20 | -48.72 | HORIZONTAL | Peak   |
| 4 | 5745.000 | 102.77      | 32.10  | 6.20  | 36.89  | 104.18 | 125.20 | -21.02 | HORIZONTAL | Peak   |

Test Mode: 05; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



|   |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over   |           |        |
|---|----------|--------|---------|-------|--------|--------|--------|--------|-----------|--------|
|   | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 5646.088 | 58.13  | 31.95   | 6.35  | 36.89  | 59.54  | 68.20  | -8.66  | VERTICAL  | Peak   |
| 2 | 5715.000 | 61.78  | 32.04   | 6.33  | 36.89  | 63.26  | 109.40 | -46.14 | VERTICAL  | Peak   |
| 3 | 5725.000 | 71.38  | 32.07   | 6.25  | 36.89  | 72.81  | 122.20 | -49.39 | VERTICAL  | Peak   |
| 4 | 5745.000 | 104.21 | 32.10   | 6.20  | 36.89  | 105.62 | 125.20 | -19.58 | VERTICAL  | Peak   |


Test Mode: 05; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

|   |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over   |            |        |
|---|----------|--------|---------|-------|--------|--------|--------|--------|------------|--------|
|   | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 5825.000 | 102.26 | 32.23   | 6.04  | 36.90  | 103.63 | 125.20 | -21.57 | HORIZONTAL | Peak   |
| 2 | 5850.000 | 59.59  | 32.25   | 6.00  | 36.90  | 60.94  | 122.20 | -61.26 | HORIZONTAL | Peak   |
| 3 | 5860.000 | 57.53  | 32.27   | 5.96  | 36.90  | 58.86  | 109.40 | -50.54 | HORIZONTAL | Peak   |
| 4 | 5940.133 | 58.12  | 32.34   | 6.00  | 36.90  | 59.56  | 68.20  | -8.64  | HORIZONTAL | Peak   |


Test Mode: 05; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|   |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over   |           |        |
|---|----------|--------|---------|-------|--------|--------|--------|--------|-----------|--------|
|   | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 5825.000 | 105.87 | 32.23   | 6.04  | 36.90  | 107.24 | 125.20 | -17.96 | VERTICAL  | Peak   |
| 2 | 5850.000 | 67.95  | 32.25   | 6.00  | 36.90  | 69.30  | 122.20 | -52.90 | VERTICAL  | Peak   |
| 3 | 5860.000 | 62.28  | 32.27   | 5.96  | 36.90  | 63.61  | 109.40 | -45.79 | VERTICAL  | Peak   |
| 4 | 5931.352 | 58.03  | 32.34   | 6.00  | 36.90  | 59.47  | 68.20  | -8.73  | VERTICAL  | Peak   |

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




|   | Freq     | Read<br>Level | Antenna<br>Factor | Cable<br>Loss | Preamp<br>Factor | Level  | Limit<br>Line | Over<br>Limit | Pol/Phase  | Remark |
|---|----------|---------------|-------------------|---------------|------------------|--------|---------------|---------------|------------|--------|
|   | MHz      | dBuV          | dB/m              | dB            | dB               | dBuV/m | dBuV/m        | dB            |            |        |
| 1 | 5645.206 | 57.36         | 31.95             | 6.35          | 36.89            | 58.77  | 68.20         | -9.43         | HORIZONTAL | Peak   |
| 2 | 5715.000 | 74.08         | 32.04             | 6.33          | 36.89            | 75.56  | 109.40        | -33.84        | HORIZONTAL | Peak   |
| 3 | 5725.000 | 77.60         | 32.07             | 6.25          | 36.89            | 79.03  | 122.20        | -43.17        | HORIZONTAL | Peak   |
| 4 | 5755.000 | 100.90        | 32.10             | 6.20          | 36.89            | 102.31 | 125.20        | -22.89        | HORIZONTAL | Peak   |

Test Mode: 05; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



|      | ReadAntenna | Cable  | Preamp | Limit  | Over   |        |        |           |               |
|------|-------------|--------|--------|--------|--------|--------|--------|-----------|---------------|
| Freq | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase | Remark        |
| MHz  | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |           |               |
| 1    | 5642.269    | 57.59  | 31.95  | 6.35   | 36.89  | 59.00  | 68.20  | -9.20     | VERTICAL Peak |
| 2    | 5715.000    | 76.87  | 32.04  | 6.33   | 36.89  | 78.35  | 109.40 | -31.05    | VERTICAL Peak |
| 3    | 5725.000    | 78.23  | 32.07  | 6.25   | 36.89  | 79.66  | 122.20 | -42.54    | VERTICAL Peak |
| 4    | 5755.000    | 102.18 | 32.10  | 6.20   | 36.89  | 103.59 | 125.20 | -21.61    | VERTICAL Peak |


Test Mode: 05; Polarity: Horizontal; Modulation: 802.11ac; Bandwidth: 40MHz; Channel: High



Trace: (Discrete)

|   |          | ReadAntenna |        | Cable | Preamp |        | Limit  | Over   |            |        |
|---|----------|-------------|--------|-------|--------|--------|--------|--------|------------|--------|
|   | Freq     | Level       | Factor | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV        | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 5795.000 | 99.96       | 32.19  | 6.10  | 36.89  | 101.36 | 125.20 | -23.84 | HORIZONTAL | Peak   |
| 2 | 5850.000 | 58.28       | 32.25  | 6.00  | 36.90  | 59.63  | 122.20 | -62.57 | HORIZONTAL | Peak   |
| 3 | 5860.000 | 57.89       | 32.27  | 5.96  | 36.90  | 59.22  | 109.40 | -50.18 | HORIZONTAL | Peak   |
| 4 | 5930.578 | 58.67       | 32.34  | 6.00  | 36.90  | 60.11  | 68.20  | -8.09  | HORIZONTAL | Peak   |


Test Mode: 05; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Trace: (Discrete)


|   |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over   |           |        |
|---|----------|--------|---------|-------|--------|--------|--------|--------|-----------|--------|
|   | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 5795.000 | 102.84 | 32.19   | 6.10  | 36.89  | 104.24 | 125.20 | -20.96 | VERTICAL  | Peak   |
| 2 | 5850.000 | 65.40  | 32.25   | 6.00  | 36.90  | 66.75  | 122.20 | -55.45 | VERTICAL  | Peak   |
| 3 | 5860.000 | 62.90  | 32.27   | 5.96  | 36.90  | 64.23  | 109.40 | -45.17 | VERTICAL  | Peak   |
| 4 | 5939.336 | 57.90  | 32.34   | 6.00  | 36.90  | 59.34  | 68.20  | -8.86  | VERTICAL  | Peak   |

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle




|   | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |            |        |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|------------|--------|
|   |          | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 5641.188 | 58.39       | 31.95  | 6.35   | 36.89  | 59.80  | 68.20  | -8.40  | HORIZONTAL | Peak   |
| 2 | 5721.677 | 75.01       | 32.04  | 6.33   | 36.89  | 76.49  | 114.62 | -38.13 | HORIZONTAL | Peak   |
| 3 | 5775.000 | 97.13       | 32.16  | 6.10   | 36.89  | 98.50  | 125.20 | -26.70 | HORIZONTAL | Peak   |
| 4 | 5851.808 | 71.81       | 32.25  | 6.00   | 36.90  | 73.16  | 118.08 | -44.92 | HORIZONTAL | Peak   |
| 5 | 5939.993 | 58.88       | 32.34  | 6.00   | 36.90  | 60.32  | 68.20  | -7.88  | HORIZONTAL | Peak   |

Test Mode: 05; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle




|   | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |           |        |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|-----------|--------|
|   |          | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 5646.241 | 59.96       | 31.95  | 6.35   | 36.89  | 61.37  | 68.20  | -6.83  | VERTICAL  | Peak   |
| 2 | 5724.390 | 77.41       | 32.07  | 6.25   | 36.89  | 78.84  | 120.81 | -41.97 | VERTICAL  | Peak   |
| 3 | 5775.000 | 98.82       | 32.16  | 6.10   | 36.89  | 100.19 | 125.20 | -25.01 | VERTICAL  | Peak   |
| 4 | 5850.267 | 77.55       | 32.25  | 6.00   | 36.90  | 78.90  | 121.59 | -42.69 | VERTICAL  | Peak   |
| 5 | 5937.178 | 59.51       | 32.34  | 6.00   | 36.90  | 60.95  | 68.20  | -7.25  | VERTICAL  | Peak   |

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:20MHz; Channel:Low




|   | Freq     | ReadAntenna<br>Level Factor | Cable<br>Loss | Preamp<br>Factor | Level | Limit<br>Line | Over<br>Limit | Pol/Phase | Remark          |
|---|----------|-----------------------------|---------------|------------------|-------|---------------|---------------|-----------|-----------------|
|   | MHz      | dBuV                        | dB/m          | dB               | dB    | dBuV/m        | dBuV/m        | dB        |                 |
| 1 | 5644.427 | 57.27                       | 31.95         | 6.35             | 36.89 | 58.68         | 68.20         | -9.52     | HORIZONTAL Peak |
| 2 | 5715.000 | 61.23                       | 32.04         | 6.33             | 36.89 | 62.71         | 109.40        | -46.69    | HORIZONTAL Peak |
| 3 | 5725.000 | 75.14                       | 32.07         | 6.25             | 36.89 | 76.57         | 122.20        | -45.63    | HORIZONTAL Peak |
| 4 | 5745.000 | 105.36                      | 32.10         | 6.20             | 36.89 | 106.77        | 125.20        | -18.43    | HORIZONTAL Peak |

Test Mode: 05; Polarity: Vertical; Modulation: 802.11ax; Bandwidth: 20MHz; Channel: Low



|   |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over   |           |        |
|---|----------|--------|---------|-------|--------|--------|--------|--------|-----------|--------|
|   | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 5644.842 | 57.36  | 31.95   | 6.35  | 36.89  | 58.77  | 68.20  | -9.43  | VERTICAL  | Peak   |
| 2 | 5715.000 | 61.97  | 32.04   | 6.33  | 36.89  | 63.45  | 109.40 | -45.95 | VERTICAL  | Peak   |
| 3 | 5725.000 | 74.77  | 32.07   | 6.25  | 36.89  | 76.20  | 122.20 | -46.00 | VERTICAL  | Peak   |
| 4 | 5745.000 | 106.14 | 32.10   | 6.20  | 36.89  | 107.55 | 125.20 | -17.65 | VERTICAL  | Peak   |

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:20MHz; Channel:High



race: (Discrete)


|   | Freq     | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Level  | Limit Line | Over Limit | Pol/Phase  | Remark |
|---|----------|------------|----------------|------------|---------------|--------|------------|------------|------------|--------|
|   | MHz      | dBuV       | dB/m           | dB         | dB            | dBuV/m | dBuV/m     | dB         |            |        |
| 1 | 5825.000 | 104.60     | 32.23          | 6.04       | 36.90         | 105.97 | 125.20     | -19.23     | HORIZONTAL | Peak   |
| 2 | 5850.000 | 63.47      | 32.25          | 6.00       | 36.90         | 64.82  | 122.20     | -57.38     | HORIZONTAL | Peak   |
| 3 | 5860.000 | 58.54      | 32.27          | 5.96       | 36.90         | 59.87  | 109.40     | -49.53     | HORIZONTAL | Peak   |
| 4 | 5932.919 | 58.20      | 32.34          | 6.00       | 36.90         | 59.64  | 68.20      | -8.56      | HORIZONTAL | Peak   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed on the reverse, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>, and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions.aspx#e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document may be reported to the Company at [fraud@sgs.com](mailto:fraud@sgs.com). The Company will be pleased to assist. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443.**


Test Mode: 05; Polarity: Vertical; Modulation:802.11ax; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|   | Freq     | ReadAntenna<br>Level | Factor | Cable<br>Loss | Preamp<br>Factor | Level  | Limit<br>Line | Over<br>Limit | Pol/Phase | Remark |
|---|----------|----------------------|--------|---------------|------------------|--------|---------------|---------------|-----------|--------|
|   | MHz      | dBuV                 | dB/m   | dB            | dB               | dBuV/m | dBuV/m        | dB            |           |        |
| 1 | 5825.000 | 108.46               | 32.23  | 6.04          | 36.90            | 109.83 | 125.20        | -15.37        | VERTICAL  | Peak   |
| 2 | 5850.000 | 72.27                | 32.25  | 6.00          | 36.90            | 73.62  | 122.20        | -48.58        | VERTICAL  | Peak   |
| 3 | 5860.000 | 63.03                | 32.27  | 5.96          | 36.90            | 64.36  | 109.40        | -45.04        | VERTICAL  | Peak   |
| 4 | 5931.195 | 58.35                | 32.34  | 6.00          | 36.90            | 59.79  | 68.20         | -8.41         | VERTICAL  | Peak   |

Test Mode: 05; Polarity: Horizontal; Modulation: 802.11ax; Bandwidth: 40MHz; Channel: Low



|   | Freq     | ReadAntenna<br>Level Factor | Cable<br>Loss | Preamp<br>Factor | Level | Limit<br>Line | Over<br>Limit | Pol/Phase | Remark          |
|---|----------|-----------------------------|---------------|------------------|-------|---------------|---------------|-----------|-----------------|
|   | MHz      | dBuV                        | dB/m          | dB               | dB    | dBuV/m        | dBuV/m        | dB        |                 |
| 1 | 5643.603 | 57.14                       | 31.95         | 6.35             | 36.89 | 58.55         | 68.20         | -9.65     | HORIZONTAL Peak |
| 2 | 5715.000 | 73.02                       | 32.04         | 6.33             | 36.89 | 74.50         | 109.40        | -34.90    | HORIZONTAL Peak |
| 3 | 5725.000 | 77.95                       | 32.07         | 6.25             | 36.89 | 79.38         | 122.20        | -42.82    | HORIZONTAL Peak |
| 4 | 5755.000 | 102.62                      | 32.10         | 6.20             | 36.89 | 104.03        | 125.20        | -21.17    | HORIZONTAL Peak |


Test Mode: 05; Polarity: Vertical; Modulation:802.11ax; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

|   |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over   |           |        |
|---|----------|--------|---------|-------|--------|--------|--------|--------|-----------|--------|
|   | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 5642.802 | 58.41  | 31.95   | 6.35  | 36.89  | 59.82  | 68.20  | -8.38  | VERTICAL  | Peak   |
| 2 | 5715.000 | 75.31  | 32.04   | 6.33  | 36.89  | 76.79  | 109.40 | -32.61 | VERTICAL  | Peak   |
| 3 | 5725.000 | 78.26  | 32.07   | 6.25  | 36.89  | 79.69  | 122.20 | -42.51 | VERTICAL  | Peak   |
| 4 | 5755.000 | 104.89 | 32.10   | 6.20  | 36.89  | 106.30 | 125.20 | -18.90 | VERTICAL  | Peak   |


Test Mode: 05; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

|   |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over   |            |        |
|---|----------|--------|---------|-------|--------|--------|--------|--------|------------|--------|
|   | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 5795.000 | 102.12 | 32.19   | 6.10  | 36.89  | 103.52 | 125.20 | -21.68 | HORIZONTAL | Peak   |
| 2 | 5850.000 | 61.42  | 32.25   | 6.00  | 36.90  | 62.77  | 122.20 | -59.43 | HORIZONTAL | Peak   |
| 3 | 5860.000 | 59.78  | 32.27   | 5.96  | 36.90  | 61.11  | 109.40 | -48.29 | HORIZONTAL | Peak   |
| 4 | 5942.625 | 58.41  | 32.36   | 6.05  | 36.90  | 59.92  | 68.20  | -8.28  | HORIZONTAL | Peak   |


Test Mode: 05; Polarity: Vertical; Modulation:802.11ax; Bandwidth:40MHz; Channel:High



Trace: (Discrete)


|   |          | Read   | Antenna | Cable | Preamp |        | Limit  | Over   |           |        |
|---|----------|--------|---------|-------|--------|--------|--------|--------|-----------|--------|
|   | Freq     | Level  | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV   | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 5795.000 | 105.00 | 32.19   | 6.10  | 36.89  | 106.40 | 125.20 | -18.80 | VERTICAL  | Peak   |
| 2 | 5850.000 | 64.41  | 32.25   | 6.00  | 36.90  | 65.76  | 122.20 | -56.44 | VERTICAL  | Peak   |
| 3 | 5860.000 | 62.29  | 32.27   | 5.96  | 36.90  | 63.62  | 109.40 | -45.78 | VERTICAL  | Peak   |
| 4 | 5928.208 | 58.25  | 32.34   | 6.00  | 36.90  | 59.69  | 68.20  | -8.51  | VERTICAL  | Peak   |

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:80MHz; Channel:middle



|   |          | ReadAntenna |        | Cable | Preamp |        | Limit  | Over   |            |        |
|---|----------|-------------|--------|-------|--------|--------|--------|--------|------------|--------|
|   | Freq     | Level       | Factor | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV        | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 5647.729 | 58.74       | 31.95  | 6.35  | 36.89  | 60.15  | 68.20  | -8.05  | HORIZONTAL | Peak   |
| 2 | 5721.979 | 74.84       | 32.04  | 6.33  | 36.89  | 76.32  | 115.31 | -38.99 | HORIZONTAL | Peak   |
| 3 | 5775.000 | 99.35       | 32.16  | 6.10  | 36.89  | 100.72 | 125.20 | -24.48 | HORIZONTAL | Peak   |
| 4 | 5856.432 | 71.84       | 32.27  | 5.96  | 36.90  | 73.17  | 110.40 | -37.23 | HORIZONTAL | Peak   |
| 5 | 5926.556 | 58.93       | 32.34  | 6.00  | 36.90  | 60.37  | 68.20  | -7.83  | HORIZONTAL | Peak   |

Test Mode: 05; Polarity: Vertical; Modulation: 802.11ax; Bandwidth: 80MHz; Channel: middle



|   |          | Read  | Antenna | Cable | Preamp |        | Limit  | Over   |           |        |
|---|----------|-------|---------|-------|--------|--------|--------|--------|-----------|--------|
|   | Freq     | Level | Factor  | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV  | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 5644.160 | 58.84 | 31.95   | 6.35  | 36.89  | 60.25  | 68.20  | -7.95  | VERTICAL  | Peak   |
| 2 | 5722.883 | 77.24 | 32.07   | 6.25  | 36.89  | 78.67  | 117.37 | -38.70 | VERTICAL  | Peak   |
| 3 | 5775.000 | 99.93 | 32.16   | 6.10  | 36.89  | 101.30 | 125.20 | -23.90 | VERTICAL  | Peak   |
| 4 | 5852.116 | 75.05 | 32.25   | 6.00  | 36.90  | 76.40  | 117.37 | -40.97 | VERTICAL  | Peak   |
| 5 | 5925.932 | 59.61 | 32.34   | 6.00  | 36.90  | 61.05  | 68.20  | -7.15  | VERTICAL  | Peak   |

**7.9 Radiated Emissions (below 1GHz)**

Test Requirement 47 CFR Part 15, Subpart C 15.209 &amp; 15.407(b)

Test Method: KDB 789033 D02 II G

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 0.009-0.490    | 2400/F(kHz)                      | 300                          |
| 0.490-1.705    | 24000/F(kHz)                     | 30                           |
| 1.705-30.0     | 30                               | 30                           |
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| Above 960      | 500                              | 3                            |

\*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

**7.9.1 E.U.T. Operation**

Operating Environment:

Temperature: 25.8 °C

Humidity: 63.2 % RH

Atmospheric Pressure: 1010 mbar

**7.9.2 Test Mode Description**

| Pre-scan /<br>Final test | Mode<br>Code | Description |
|--------------------------|--------------|-------------|
|--------------------------|--------------|-------------|

|            |    |                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------|----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test | 02 | TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of |
|------------|----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

## Pre-scan 03

IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.

TX mode (U-NII-2A)\_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.


## Pre-scan 04

TX mode (U-NII-2C)\_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.

## Pre-scan 05

TX mode (U-NII-3)\_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.

### 7.9.3 Test Setup Diagram




### 7.9.4 Measurement Procedure and Data

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.


Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- For emission below 1GHz, through the pre-scan found the worst case is the lowest channel of 802.11a. Only the worst case is recorded in the report.
- Scan from 9kHz to 1GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test Mode: 02; Polarity: Horizontal; Modulation: 802.11a; Bandwidth: 20MHz; Channel: Low



Test Mode: 02; Polarity: Vertical; Modulation: 802.11a; Bandwidth: 20MHz; Channel: Low



**7.10 Radiated Emissions (above 1GHz)**

Test Requirement 47 CFR Part 15, Subpart C 15.209 &amp; 15.407(b)

Test Method: KDB 789033 D02 II G

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 0.009-0.490    | 2400/F(kHz)                      | 300                          |
| 0.490-1.705    | 24000/F(kHz)                     | 30                           |
| 1.705-30.0     | 30                               | 30                           |
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| Above 960      | 500                              | 3                            |

\*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

**7.10.1 E.U.T. Operation**

Operating Environment:

Temperature: 21.5 °C

Humidity: 54.2 % RH

Atmospheric Pressure: 1010 mbar

**7.10.2 Test Mode Description**

Pre-scan / Mode  
Final test Code Description

Final test 02

TX mode (U-NII-1)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Guangzhou Branch Testing Laboratory

No.198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn  
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

**Final test 03**

IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.

TX mode (U-NII-2A)\_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.


**Final test 04**

TX mode (U-NII-2C)\_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.

**Final test 05**

TX mode (U-NII-3)\_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.

### 7.10.3 Test Setup Diagram



#### 7.10.4 Measurement Procedure and Data

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
4. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
5. Pretest the EUT at antenna 1 and antenna 2 and MIMO mode find the worst case is MIMO mode. only record the worst case test data 802.11a in this report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 02; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



|   |           | ReadAntenna |        | Cable | Preamp |        | Limit  | Over   |            |        |
|---|-----------|-------------|--------|-------|--------|--------|--------|--------|------------|--------|
|   | Freq      | Level       | Factor | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz       | dBuV        | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 1433.875  | 45.27       | 25.44  | 2.67  | 38.20  | 35.18  | 68.20  | -33.02 | HORIZONTAL | Peak   |
| 2 | 2018.618  | 45.87       | 26.13  | 3.11  | 37.69  | 37.42  | 68.20  | -30.78 | HORIZONTAL | Peak   |
| 3 | 3794.585  | 46.58       | 29.50  | 4.60  | 36.85  | 43.83  | 74.00  | -30.17 | HORIZONTAL | Peak   |
| 4 | 6316.105  | 45.08       | 33.51  | 5.95  | 36.97  | 47.57  | 68.20  | -20.63 | HORIZONTAL | Peak   |
| 5 | 10360.000 | 41.94       | 39.28  | 7.29  | 37.37  | 51.14  | 68.20  | -17.06 | HORIZONTAL | Peak   |
| 6 | 15540.000 | 38.76       | 39.05  | 9.88  | 35.39  | 52.30  | 74.00  | -21.70 | HORIZONTAL | Peak   |


Test Mode: 02; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|   | Freq      | Read  | Antenna | Cable | Preamp | Limit  | Over   |           |               |
|---|-----------|-------|---------|-------|--------|--------|--------|-----------|---------------|
|   | MHz       | Level | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark        |
|   | MHz       | dBuV  | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |               |
| 1 | 1338.565  | 45.47 | 25.29   | 2.60  | 38.27  | 35.09  | 74.00  | -38.91    | VERTICAL Peak |
| 2 | 2367.179  | 43.80 | 27.28   | 3.43  | 37.60  | 36.91  | 74.00  | -37.09    | VERTICAL Peak |
| 3 | 3131.998  | 48.22 | 28.51   | 3.95  | 37.14  | 43.54  | 68.20  | -24.66    | VERTICAL Peak |
| 4 | 6293.723  | 44.44 | 33.37   | 5.98  | 36.96  | 46.83  | 68.20  | -21.37    | VERTICAL Peak |
| 5 | 10360.000 | 42.16 | 39.28   | 7.29  | 37.37  | 51.36  | 68.20  | -16.84    | VERTICAL Peak |
| 6 | 15540.000 | 37.65 | 39.05   | 9.88  | 35.39  | 51.19  | 74.00  | -22.81    | VERTICAL Peak |

Test Mode: 02; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



|   |           | ReadAntenna |        | Cable | Preamp |        | Limit  | Over   |            |        |
|---|-----------|-------------|--------|-------|--------|--------|--------|--------|------------|--------|
|   | Freq      | Level       | Factor | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz       | dBuV        | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 1695.862  | 43.93       | 25.71  | 2.80  | 37.89  | 34.55  | 74.00  | -39.45 | HORIZONTAL | Peak   |
| 2 | 2264.619  | 45.13       | 26.98  | 3.27  | 37.63  | 37.75  | 74.00  | -36.25 | HORIZONTAL | Peak   |
| 3 | 4353.513  | 45.07       | 30.59  | 4.68  | 36.81  | 43.53  | 74.00  | -30.47 | HORIZONTAL | Peak   |
| 4 | 5553.567  | 45.23       | 31.84  | 6.35  | 36.89  | 46.53  | 68.20  | -21.67 | HORIZONTAL | Peak   |
| 5 | 10440.000 | 41.65       | 39.42  | 7.37  | 37.36  | 51.08  | 68.20  | -17.12 | HORIZONTAL | Peak   |
| 6 | 15660.000 | 39.35       | 38.86  | 9.87  | 35.39  | 52.69  | 74.00  | -21.31 | HORIZONTAL | Peak   |


Test Mode: 02; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)


|   | Freq      | Read  | Antenna | Cable | Preamp | Limit  | Over   |           |               |
|---|-----------|-------|---------|-------|--------|--------|--------|-----------|---------------|
|   | MHz       | Level | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark        |
|   | MHz       | dBuV  | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |               |
| 1 | 1666.398  | 44.54 | 25.66   | 2.80  | 37.91  | 35.09  | 74.00  | -38.91    | VERTICAL Peak |
| 2 | 1962.749  | 46.77 | 26.08   | 3.03  | 37.71  | 38.17  | 68.20  | -30.03    | VERTICAL Peak |
| 3 | 3127.270  | 47.91 | 28.50   | 3.94  | 37.14  | 43.21  | 68.20  | -24.99    | VERTICAL Peak |
| 4 | 5575.816  | 44.39 | 31.87   | 6.32  | 36.89  | 45.69  | 68.20  | -22.51    | VERTICAL Peak |
| 5 | 10440.000 | 42.56 | 39.42   | 7.37  | 37.36  | 51.99  | 68.20  | -16.21    | VERTICAL Peak |
| 6 | 15660.000 | 37.53 | 38.86   | 9.87  | 35.39  | 50.87  | 74.00  | -23.13    | VERTICAL Peak |

Test Mode: 02; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



|   |           | ReadAntenna |        | Cable | Preamp |        | Limit  | Over   |            |        |
|---|-----------|-------------|--------|-------|--------|--------|--------|--------|------------|--------|
|   | Freq      | Level       | Factor | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz       | dBuV        | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 1252.808  | 45.86       | 25.03  | 2.36  | 38.35  | 34.90  | 68.20  | -33.30 | HORIZONTAL | Peak   |
| 2 | 1823.591  | 46.75       | 25.97  | 2.98  | 37.80  | 37.90  | 68.20  | -30.30 | HORIZONTAL | Peak   |
| 3 | 3311.344  | 47.56       | 28.76  | 4.06  | 37.03  | 43.35  | 68.20  | -24.85 | HORIZONTAL | Peak   |
| 4 | 5246.306  | 45.69       | 31.75  | 5.74  | 36.87  | 46.31  | 68.20  | -21.89 | HORIZONTAL | Peak   |
| 5 | 10480.000 | 41.09       | 39.46  | 7.40  | 37.36  | 50.59  | 68.20  | -17.61 | HORIZONTAL | Peak   |
| 6 | 15720.000 | 37.55       | 38.78  | 9.87  | 35.39  | 50.81  | 74.00  | -23.19 | HORIZONTAL | Peak   |


Test Mode: 02; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

|   | Freq      | Read  | Antenna | Cable | Preamp | Limit  | Over   |           |               |
|---|-----------|-------|---------|-------|--------|--------|--------|-----------|---------------|
|   | MHz       | Level | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark        |
|   | MHz       | dBuV  | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |               |
| 1 | 1686.739  | 43.89 | 25.69   | 2.80  | 37.91  | 34.47  | 74.00  | -39.53    | VERTICAL Peak |
| 2 | 2368.083  | 44.20 | 27.28   | 3.43  | 37.60  | 37.31  | 74.00  | -36.69    | VERTICAL Peak |
| 3 | 3269.567  | 48.06 | 28.71   | 4.04  | 37.04  | 43.77  | 68.20  | -24.43    | VERTICAL Peak |
| 4 | 5547.815  | 45.05 | 31.84   | 6.35  | 36.89  | 46.35  | 68.20  | -21.85    | VERTICAL Peak |
| 5 | 10480.000 | 40.98 | 39.46   | 7.40  | 37.36  | 50.48  | 68.20  | -17.72    | VERTICAL Peak |
| 6 | 15720.000 | 37.00 | 38.78   | 9.87  | 35.39  | 50.26  | 74.00  | -23.74    | VERTICAL Peak |

Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

|   | Freq      | Read  | Antenna | Cable | Preamp | Limit  | Over   |           |                 |
|---|-----------|-------|---------|-------|--------|--------|--------|-----------|-----------------|
|   | MHz       | Level | Factor  | Loss  | Factor | Line   | Limit  | Pol/Phase | Remark          |
|   | MHz       | dBuV  | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB        |                 |
| 1 | 1183.291  | 46.95 | 24.60   | 2.37  | 38.40  | 35.52  | 74.00  | -38.48    | HORIZONTAL Peak |
| 2 | 2135.670  | 46.67 | 26.39   | 3.18  | 37.67  | 38.57  | 68.20  | -29.63    | HORIZONTAL Peak |
| 3 | 3399.635  | 46.78 | 28.84   | 4.10  | 36.98  | 42.74  | 68.20  | -25.46    | HORIZONTAL Peak |
| 4 | 6429.488  | 43.91 | 33.83   | 5.88  | 36.99  | 46.63  | 68.20  | -21.57    | HORIZONTAL Peak |
| 5 | 10360.000 | 41.08 | 39.28   | 7.29  | 37.37  | 50.28  | 68.20  | -17.92    | HORIZONTAL Peak |
| 6 | 15540.000 | 37.60 | 39.05   | 9.88  | 35.39  | 51.14  | 74.00  | -22.86    | HORIZONTAL Peak |