



Product Service

---

**Choose certainty.  
Add value.**

# Report On

RF Exposure Assessment of the  
Axnes Aviation AS  
PNG BST50 Wireless intercom extension for use in demanding high  
noise environments

FCC ID: 2AOHP BST50A

Document 75940027 Report 8 Issue 1

April 2018



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North,  
Fareham, Hampshire, United Kingdom, PO15 5RL  
Tel: +44 (0) 1489 558100. Website: [www.tuv-sud.co.uk](http://www.tuv-sud.co.uk)

**REPORT ON**

RF Exposure Assessment of the  
Axnes Aviation AS  
PNG BST50 Wireless intercom extension for use in demanding high  
noise environments

Document 75940027 Report 8 Issue 1

April 2018

**PREPARED FOR**

Axnes Aviation AS  
Terje Lovasvei 1  
Grimstad  
N-4879  
Norway

**PREPARED BY**

A handwritten signature in black ink that reads "David Guyett-Smith".

**David Guyett-Smith**  
Chief Safety Engineer - Technical Solutions

**APPROVED BY**

A handwritten signature in blue ink that reads "Matthew Russell".

**Matthew Russell**  
Authorised Signatory

**DATED**

10 April 2018



Product Service

## CONTENTS

Section	Page No
<b>1 REPORT SUMMARY .....</b>	<b>3</b>
1.1 Introduction .....	4
1.2 Regional Requirements .....	5
1.3 Product Information .....	6
1.3.1 Technical Description .....	6
1.3.2 Supported Features .....	6
1.3.3 Antennas.....	6
<b>2 TEST DETAILS .....</b>	<b>8</b>
2.1 Rationale for Assessment of the RF Exposure .....	9
2.2 Test Result Details.....	10
<b>3 DISCLAIMERS AND COPYRIGHT.....</b>	<b>11</b>
3.1 Disclaimers and Copyright.....	12



Product Service

## **SECTION 1**

### **REPORT SUMMARY**

RF Exposure Assessment of the  
Axnes Aviation AS

PNG BST50 Wireless intercom extension for use in demanding high noise environments



Product Service

## 1.1 INTRODUCTION

The information contained in this report is intended to show verification of the RF Exposure Assessment of the Axnes Aviation AS PNG BST50 Wireless intercom extention for use in demanding high noise environments to the requirements of the applied test specifications.

Objective	To perform RF Exposure Assessment to determine the Equipment Under Test's (EUT's) compliance of the applied rules.
Applicant	Axnes Aviation AS
Manufacturer	Axnes Aviation AS
Manufacturing Description	Wireless intercom extension for use in demanding high noise environments
Model Number(s)	PNG BST50
Test Specification/Issue/Date	CFR 47 Pt1.1310 (2016)



Product Service

## 1.2 REGIONAL REQUIREMENTS

The table below shows the regional requirements that are referenced in this test report. A full list of the requirements is shown in Annex A.

Report Reference	Regional Requirement
FCC	CFR 47 Pt1.1310 (2016)



Product Service

## 1.3 PRODUCT INFORMATION

### 1.3.1 Technical Description

The Equipment under test was a Axnes Aviation AS PNG BST50 Wireless intercom extension for use in demanding high noise environments. A full technical description can be found in the manufacturer's documentation.

All reported calculations were carried out on the relevant information supplied for the PNG BST50 Wireless intercom extension for use in demanding high noise environments to demonstrate compliance with the applied test specification(s). The sample assessed was found to comply with the requirements of the applied rules.

### 1.3.2 Supported Features

The following radio access technologies and frequency bands are supported by the equipment under test.

Radio Access Technology	UHF 16QAM
Frequency Band (MHz)	405.0125 to 469.9875

### 1.3.3 Antennas

The following antennas are supported by the equipment under test.

No.	Model	Gain(dBi)
1	UHF	5

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General Public and Occupational. The calculations shown in this report were made in accordance with the procedures specified in the applied test specification(s).

Required Compliance Boundary (m)	
Occupational	General Population
0.2	0.2

**Table 1 – Compliance Boundary Results**



Product Service

Regional Requirement	Calculated RF exposure level at compliance boundary of 0.2 m					
	S Field (W/m <sup>2</sup> )		E Field (V/m)		H Field (A/m)	
	Result	Limit	Result	Limit	Result	Limit
FCC*	0.1258	1.3500	N/A	N/A	N/A	N/A

\* Requirement and Result in mW/cm<sup>2</sup>

**Table 2 – Occupational Results**

The calculations show that the EUT complies with the occupational exposure levels described in CFR 47 Pt1.1310 (2016) at the point of investigation, 0.2 m.

Regional Requirement	Calculated RF exposure level at compliance boundary of 0.2 m					
	S Field (W/m <sup>2</sup> )		E Field (V/m)		H Field (A/m)	
	Result	Limit	Result	Limit	Result	Limit
FCC*	0.1258	0.2700	N/A	N/A	N/A	N/A

\* Requirement and Result in mW/cm<sup>2</sup>

**Table 3 – General Population Results**

The calculations show that the EUT complies with the general population exposure levels described in CFR 47 Pt1.1310 (2016) at the point of investigation, 0.2 m.



Product Service

## **SECTION 2**

### **TEST DETAILS**



Product Service

## 2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields.

The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in the relevant specifications.

The RF exposure assessment is based upon the following criteria:

The PNG BST50 Wireless intercom extension for use in demanding high noise environments operates with the following transmitters active on the antenna ports shown in Section 1.3.3. For each transmitter, the Radio Access Technology (RAT), EIRP inclusive of antenna gain and duty cycle, gain of the antenna and lowest frequency of operation are shown as they contribute to the calculation of S Field, E field and H field values according to the following formulas.

The power flux (S Field):

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2}$$

The electric field strength (E Field):

$$E = \frac{\sqrt{30PG_{(\theta, \phi)}}}{r}$$

The magnetic field strength (H Field):

$$H = \frac{E}{\eta_o}$$

Where:

P = Average Power (W)

G = Antenna Gain (dBi)

r = Distance (cm) or (m)

$\eta_o = 377$



Product Service

## 2.2 TEST RESULT DETAILS

The frequencies shown in the tables below have been chosen based on the lowest possible frequency that the EUT can transmit.

Antenna Port	Tx No.	Ant No.	RAT	EIRP (W)	Duty Cycle (%)	Gain (dBi)	Frequency (MHz)	RF Exposure Level at compliance boundary of 0.2 m		
								S Field (W/m <sup>2</sup> )	E Field (V/m)	H Field (A/m)
1	1	1	UHF 16QAM	0.632	50	5	405.0125	1.2581	21.7779	0.0578

**Table 4 – Occupational Transmitter Summary**

Antenna Port	Tx No.	Ant No.	RAT	EIRP (W)	Duty Cycle (%)	Gain (dBi)	Frequency (MHz)	RF Exposure Level at compliance boundary of 0.2 m		
								S Field (W/m <sup>2</sup> )	E Field (V/m)	H Field (A/m)
1	1	1	UHF 16QAM	0.632	50	5	405.0125	1.2581	21.7779	0.0578

**Table 5 – General Population Transmitter Summary**



Product Service

## **SECTION 3**

### **DISCLAIMERS AND COPYRIGHT**



Product Service

### 3.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of  
TÜV SÜD Product Service

© 2018 TÜV SÜD Product Service



Product Service

## **ANNEX A**

### **REGIONAL REQUIREMENTS**



Product Service

Frequency Range (MHz)	Power Density (mW/cm <sup>2</sup> )	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	$900/f^2$	$1842/f$	$4.89/f$
30 - 300	1	61.4	0.163
300 - 1500	$f/300$	-	-
1500 - 100000	5	-	-

**Table A.1 – CFR 47 Pt1.1310 (2016) Occupational Limits**

Frequency Range (MHz)	Power Density (mW/cm <sup>2</sup> )	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	$180/f^2$	$824/f$	$2.19/f$
30 - 300	0.2	27.5	0.073
300 - 1500	$f/1500$	-	-
1500 - 100000	1	-	-

**Table A.2 – CFR 47 Pt1.1310 (2016) General Population Limits**