



## EMC TEST REPORT

**Applicant** Daiichi Elektronik Sanayi ve Ticaret A.S.

**FCC ID** 2AOI6-VQC1006

**Product** A7+ 10.25inch w/DAB w/Wireless  
CP&AA&FM&AM

**Brand** Daiichi

**Model** VQC1006

**Report No.** EFTA25010109-IE-10-E1V1

**Issue Date** May 27, 2025

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2023)/ ANSI C63.4-2014**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

---

*Prepared by: Liu Wei*

*Approved by: Xu Kai*

---

**Eurofins TA Technology (Shanghai) Co., Ltd.**

*Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China*

*TEL: +86-021-50791141/2/3*

*FAX: +86-021-50791141/2/3-8000*

## Table of Contents

1	Test Laboratory .....	5
1.1	Notes of the Test Report.....	5
1.2	Test Facility.....	5
1.3	Testing Location.....	5
2	General Description of Equipment Under Test .....	6
2.1	Applicant and Manufacturer Information .....	6
2.2	General Information .....	6
2.3	Applied Standards .....	7
2.4	Test Mode .....	8
3	Test Case Results .....	9
3.1	Radiated Emission.....	9
3.2	Conducted Emission.....	14
4	Uncertainty Measurement.....	16
5	Main Test Instruments .....	17
ANNEX A:	The EUT Appearance .....	18
ANNEX B:	Test Setup Photos .....	19

Version	Revision Description	Issue Date
Rev.0	Initial issue of report.	March 31, 2025
Rev.1	Updated information.	May 27, 2025
Note: This revised report (Report No.: EFTA25010109-IE-10-E1V1) supersedes and replaces the previously issued report (Report No.: EFTA25010109-IE-10-E1). Please discard or destroy the previously issued report and dispose of it accordingly.		

## Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	NA <sup>Note 1</sup>
Date of Testing: January 9, 2025 ~ February 27, 2025			
Date of Sample Received: January 9, 2025			
<p>Note:</p> <ol style="list-style-type: none"><li>1. The equipment is not connected to the public network, so test items do not apply.</li><li>2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results.</li></ol> <p>Measurement Uncertainties were not taken into account and are published for informational purposes only.</p>			

## 1 Test Laboratory

### 1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

### 1.2 Test Facility

#### FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

#### A2LA (Certificate Number: 3857.01)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

### 1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.  
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Xu Kai  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <https://www.eurofins.com/electrical-and-electronics>  
E-mail: Kain.Xu@cpt.eurofinscn.com

## 2 General Description of Equipment Under Test

### 2.1 Applicant and Manufacturer Information

<b>Applicant</b>	Daiichi Elektronik Sanayi ve Ticaret A.S.
<b>Applicant address</b>	Ferhatpaşa mah. 16. Sok.No:38 Ataşehir/Istanbul
<b>Manufacturer</b>	Daiichi Elektronik Sanayi ve Ticaret A.S.
<b>Manufacturer address</b>	Ferhatpaşa mah. 16. Sok.No:38 Ataşehir/Istanbul

### 2.2 General Information

EUT Description			
Device Type	Fixed Device		
Model	VQC1006		
Lab internal SN	EFTA25010109-IE-10/S01		
HW Version	1.0.2		
SW Version	1.0.8		
Power Rating	DC 12V		
Connecting I/O Port(s)	Please refer to the User's Manual.		
Antenna Type	Internal Antenna		
Frequency	Band	Tx (MHz)	Rx (MHz)
	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 2.4GHz	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 5GHz (U-NII-1)	5150 ~ 5250	5150 ~ 5250
	Wi-Fi 5GHz (U-NII-3)	5725 ~ 5850	5725 ~ 5850
Note:			
1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.			

## 2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

### Test standards

FCC Code CFR47 Part15B (2023)

ANSI C63.4-2014

## 2.4 Test Mode

Test Mode	
Mode 1	External Power Supply + EUT +Bluetooth/ WLAN Receiver
Mode 2	External Power Supply + EUT+ Bluetooth pairing +PLAY MUSIC

Test Type	Test Mode	Worst Mode
Radiated Emission	Mode 1, 2	Mode 2
Conducted Emission	/	/

After technical evaluation or/and preliminary test, the test data of the worst-case condition was recorded in this report.

## 3 Test Case Results

### 3.1 Radiated Emission

#### Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	30% ~ 60%

#### Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:



RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK Detector: RBW=1MHz / VBW=3MHz/ Sweep=AUTO

(b) AVERAGE Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

**Test Setup**
**Below 1GHz**

**Above 1GHz**


Note: Area side: 2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

**Limits****Class B**

Frequency (MHz)	Field Strength (dB $\mu$ V/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5 <sup>th</sup> harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak


**Frequency range of radiated measurements**

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

## Test Results

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. The Emissions in the frequency band 18GHz – 40GHz is more than 20dB below the limit are not reported.

The following graphs display the maximum values of horizontal and vertical by software. For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.




Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
46.73	27.96	40.00	12.04	103.0	V	193.00	20
89.66	28.47	43.50	15.03	190.0	H	151.00	17
173.20	23.16	43.50	20.34	216.0	H	168.00	16
193.81	26.10	43.50	17.40	104.0	V	339.00	18
313.85	30.93	46.00	15.07	102.0	H	259.00	21
605.45	36.29	46.00	9.71	102.0	V	15.00	27

**Remark: 1. Correction Factor = Antenna factor + Insertion loss(cable loss)**

**2. Margin = Limit – Quasi-Peak**


**Radiated Emission from 1GHz to 18GHz**

Frequency (MHz)	MaxPeak (dB $\mu$ V/m)	Average (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1405.88	32.93	---	74.00	41.07	1000.00	125.0	V	81.00	-13
1609.88	---	20.84	54.00	33.16	1000.00	109.0	V	52.00	-12
1743.75	32.47	---	74.00	41.53	1000.00	184.0	H	185.00	-12
1743.75	---	19.91	54.00	34.09	1000.00	178.0	H	230.00	-12
3960.13	---	27.42	54.00	26.58	1000.00	224.0	V	0.00	-4
4021.75	38.89	---	74.00	35.11	1000.00	225.0	H	176.00	-4
6805.50	46.60	---	74.00	27.40	1000.00	103.0	V	28.00	5
6811.88	---	34.19	54.00	19.81	1000.00	191.0	V	0.00	5
8626.63	47.16	---	74.00	26.84	1000.00	115.0	V	178.00	7
8698.88	---	35.34	54.00	18.66	1000.00	224.0	H	0.00	7
11108.63	50.85	---	74.00	23.15	1000.00	200.0	H	154.00	9
11117.13	---	37.73	54.00	16.27	1000.00	116.0	V	28.00	9

**Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)**
**2. Margin = Limit – MaxPeak / Average**

## 3.2 Conducted Emission


### Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	30% ~ 60%

### Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

### Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage DC 12V.

### Limits

Frequency (MHz)	Class A (dB $\mu$ V)		Class B (dB $\mu$ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 to 56 *	56 to 46*
0.5 - 5	73	60	56	46
5 - 30	73	60	60	50

\*: Decreases with the logarithm of the frequency.

Note: The EUT should meet CLASS B limit.

**Test Results**

The equipment is not connected to the public network, so test items do not apply.

## 4 Uncertainty Measurement

Case	Uncertainty	Factor k
Radiated Emission 30MHz – 200MHz	4.17 dB	1.96
Radiated Emission 200MHz – 1GHz	4.84 dB	1.96
Radiated Emission 1GHz – 18GHz	4.35 dB	1.96
Radiated Emission 18GHz – 26.5GHz	5.90 dB	1.96
Radiated Emission 26.5GHz – 40GHz	5.92 dB	1.96

## 5 Main Test Instruments

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Expiration Time
Radiated Emission					
EMI Test Receiver	R&S	ESCI3	100948	2024-05-07	2025-05-06
Signal Analyzer	R&S	FSV40	101186	2024-05-07	2025-05-06
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	1023	2023-07-14	2026-07-13
Horn Antenna	SCHWARZBECK	BBHA 9120D	430	2024-07-18	2027-07-17
Software	R&S	EMC32	9.26.01	/	/

## ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

## ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.

\*\*\*\*\* END OF REPORT \*\*\*\*\*