



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V04

Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No.: CQASZ20210600782E-02
Applicant: Zhuhai Kaihao Electronics Co., Ltd
Address of Applicant: 2nd Floor, Building C, No.3 Pinggongyi Road, Zhuhai, Guangdong, China.
Equipment Under Test (EUT):
EUT Name: Robot Vacuum Cleaner
Model No.: S6 Series, S6-LBL, S6-LWT, S6-ECO, S6-MAX, S6-LGY, S6-LBU, S6-LSV, S6-LRG, S8-LBL, S8-LWT, S8-ECO, S8-MAX, S8-LGY, S8-LBU, S8-LSV, S8-LRG
Test Model No.: S6 Series
Brand Name: IMASS
FCC ID: 2AOIA-S6
Standards: 47 CFR Part 1.1307 47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06
Date of Test: 2021-06-01 to 2021-06-10
Date of Issue: 2021-06-10
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Rock Huang
(Rock Huang)

Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210600782E-02	Rev.01	Initial report	

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 MPE EVALUATION.....	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
4.1.1 <i>Limitst</i>	6
4.1.2 <i>Test Procedure</i>	6
4.1.3 <i>EUT RF Exposure</i>	7

3 General Information

3.1 Client Information

Applicant:	Zhuhai Kaihao Electronics Co., Ltd
Address of Applicant:	2nd Floor, Building C, No.3 Pinggongyi Road, Zhuhai, Guangdong, China.
Manufacturer:	Zhuhai Kaihao Electronics Co., Ltd
Address of Manufacturer:	2nd Floor, Building C, No.3 Pinggongyi Road, Zhuhai, Guangdong, China.
Factory:	Zhuhai Kaihao Electronics Co., Ltd
Address of Factory:	2nd Floor, Building C, No.3 Pinggongyi Road, Zhuhai, Guangdong, China.

3.2 General Description of EUT

Product Name:	Robot Vacuum Cleaner
Model No.:	S6 Series, S6-LBL, S6-LWT, S6-ECO, S6-MAX, S6-LGY, S6-LBU, S6-LSV, S6-LRG, S8-LBL, S8-LWT, S8-ECO, S8-MAX, S8-LGY, S8-LBU, S8-LSV, S8-LRG
Test Model No.:	S6 Series
Trade Mark:	IMASS
Hardware version:	VS6.02
Software version:	VS6.01
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422 MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n(HT40): 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Product Type:	☒ Mobile ☐ Portable ☐ Fix Location
Test Software of EUT:	AmebaD mptool 2V1
Antenna Type	internal antenna
Antenna Gain	0dBi
Power Supply:	Battery electric :YIYANG
	Battery electric :JINWANGDA
	Battery electric :J&T Technology

Model No.: S6 Series, S6-LBL, S6-LWT, S6-ECO, S6-MAX, S6-LGY, S6-LBU, S6-LSV, S6-LRG, S8-LBL, S8-LWT, S8-ECO, S8-MAX, S8-LGY, S8-LBU, S8-LSV, S8-LRG

Only the model S6 Series was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limitst

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For 2.4G WIFI

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

802.11b mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	5.27	4.5±1	5.5	3.548
Middle(2437MHz)	8.88	8±1	9	7.943
Highest(2462MHz)	10.11	9.5±1	10.5	11.220
802.11g mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	6.2	5.5±1	6.5	4.467
Middle(2437MHz)	9.55	9±1	10	10.000
Highest(2462MHz)	11.07	10.5±1	11.5	14.125
802.11n(HT20)mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	6.26	5.5±1	6.5	4.467
Middle(2437MHz)	9.72	9±1	10	10.000
Highest(2462MHz)	10.86	10±1	11	12.589
802.11n(HT40)mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2422MHz)	7.95	7±1	8	6.310
Middle(2437MHz)	9.68	9±1	10	10.000
Highest(2452MHz)	10.69	10±1	11	12.589

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
14.125	0	0.0028	1.0	PASS

Note: 1) Refer to report No. CQASZ20210600782E-01 for EUT test Max Conducted Average Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = 14.125 * 1 / (4 * 3.1416 * 20^2) = 0.0028$