

RF EXPOSURE REPORT

Equipment under test Fast Wireless Charger

Model name PWC-1

FCC ID 2AOJFPWC1

Applicant PNTELECOM CO.,LTD

Manufacturer WEIHAI PNTELECOM CO.,LTD

Date of test(s) 2018.01.02~2018.01.09, 01.18

Date of issue 2018.01.19

Issued to

PNTELECOM CO.,LTD
130 Anyangcheondong-ro, Dongan-gu,
Anyang-si, Gyeonggi-do, Korea
Tel: +82-31-448-8880 / Fax: +82-31-448-8882

Issued by

KES Co., Ltd.
3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	Report approval by :
	
Young-Jin Lee Test engineer	Hyeon-Su Jang Technical manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Revision history

Revision	Date of issue	Test report No.	Description
-	2018.01.15	KES-RF-18T0010	Initial
R1	2018.01.19	KES-RF-18T0010-R1	Retested E-Field & H-Field Strength

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



TABLE OF CONTENTS

1.	General information	4
1.1.	EUT description	4
1.2.	Test configuration.....	4
1.3.	Test frequency	4
1.4.	Test mode	4
1.5.	Information about derivative model.....	5
1.6.	Device modifications	5
1.7.	Accessory information	5
2.	Environmental evaluation and exposure limit.....	6
2.1.	Test Setup	7
2.2.	Test results.....	9
-	E-Field Strength at 10 cm from each edges the EUT	9
-	H-Field Strength at 10 cm from each edges the EUT	10
	Appendix A. Measurement equipment	11
	Appendix B. Test setup photo.....	12

1. General information

Applicant PNTTELECOM CO.,LTD
Applicant address 130 Anyangcheondong-ro, Dongan-gu, Anyang-si, Gyeonggi-do, Korea
Test site KES Co., Ltd.
Test site address 3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea
Test Facility FCC Accreditation Designation No.: KR0100, Registration No.: 444148
FCC rule part(s): Part 15C
FCC ID: 2AOJFPWC1
Test device serial No. ☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test Fast Wireless Charger
Frequency 0.121 MHz ~ 0.205 MHz // DC 5.0 V
0.128 MHz ~ 0.205 MHz // DC 9.0 V
Modulation type ASK
Model: PWC-1
Antenna specification Internal type(Coil antenna)
Power source DC 5.0 V, DC 9.0V

1.2. Test configuration

The **PNTTELECOM CO., LTD Fast Wireless Charger FCC ID: 2AOJFPWC1** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15C
ANSI C63.10-2013
KDB 680106 D01 V02

1.3. Test frequency

		Frequency Range
Power source	DC 5.0 V	0.121 MHz ~ 0.205 MHz
	DC 9.0 V	0.128 MHz ~ 0.205 MHz

1.4. Test mode

Mode	Charging current	Description
Charging mode With load	90%	Using Max load
	50%	Using Mid load
	10%	Using Min load

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



1.5. Information about derivative model

N/A

1.6. Device modifications

N/A

1.7. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
-	-	-	-	-

2. Environmental evaluation and exposure limit

Limits for Maximum Permissible Exposure (MPE)

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.


TABLE 1 - Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational / Control Exposures				
0.3 - 3.0	614	1.63	*(100)	6
3.0 - 30	1842/f	4.89/f	*(900/f ²)	6
30 - 300	61.4	0.613	1.0	6
300 - 1 500			f/300	6
1 500 - 100 000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
<u>0.3-1.34</u>	<u>614</u>	<u>1.63</u>	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f ²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1 500			f/1 500	30
1 500 - 100 000			1.0	30

Note.

1. f= frequency in MHz
2. “*” means Plane-wave equivalent power density

2.1. Test Setup



1. The test was performed on 360° turn table in anechoic chamber.
2. The probe was placed at distance 10 cm which is between the edge of the charger and the geometric center of the probe.
3. The highest emission level was recorded and compared with limit as soon as measurement of each point ; A, B, C, D, E were completed.
4. Point F is highest measured field from moving the probe around the device.
5. The EUT was measured according to the KDB 680106 D01v02.

Note.

Equipment Approval Considerations item 5.2 of KDB 680106 D01 v02.

a) Power transfer frequency is less than 1 MHz.

- The device operates at a frequency of 121 kHz to 205 kHz.

b) Output power from each primary coil is less than 5 watts.

- Output power from each primary coil : 5 watts or 9 watts.

c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.

- The transfer system including a charging system with single coil. .

d) Client device is inserted in or placed directly in contact with the transmitter.

- Client device is placed directly in contact with the transmitter.

e) The maximum coupling surface area of the transmit (charging) device is between 60 cm² and 400 cm².

- The EUT coupling surface area :

(Type : Circle)

$$\pi \times \text{Radius of width}^2 (\text{cm}^2) = 3.14 \times 5.00 (\text{cm}^2) = 101.66 \text{ cm}^2, 60 \text{ cm}^2 < 101.66 \text{ cm}^2 < 400 \text{ cm}^2$$

f) Aggregate leakage fields at 10 cm surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 30 % of the MPE limit.

- Refer to following test results.

The EUT E-Field Strength levels at 10 cm < 30 % of the MPE E-Field Strength limit 614 V/m

4.38V/m (Max. at 10 cm) < 184.20 V/m

The EUT H-Field Strength levels at 10 cm < 30 % of the MPE H-Field Strength limit 1.63 A/m

0.44 A/m (Max. at 10 cm) < 0.489 A/m

2.2. Test results

- E-Field Strength at 10 cm from each edges the EUT

5W

Test Mode		Point A (V/m)	Point B (V/m)	Point C (V/m)	Point D (V/m)	Point E (V/m)	Point F (V/m)
Charging mode	10 % load	3.72	3.65	3.84	3.66	4.10	4.12
	50 % load	3.66	3.49	3.60	3.51	4.09	4.13
	90 % load	3.52	3.51	3.72	3.49	3.98	4.05

9W

Test Mode		Point A (V/m)	Point B (V/m)	Point C (V/m)	Point D (V/m)	Point E (V/m)	Point F (V/m)
Charging mode	10 % load	3.88	3.76	3.85	3.70	4.29	4.38
	50 % load	3.85	3.77	3.91	3.54	4.12	4.30
	90 % load	3.48	3.50	3.61	3.29	4.10	4.08

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- H-Field Strength at 10 cm from each edges the EUT

5W

Test Mode		Point A (A/m)	Point B (A/m)	Point C (A/m)	Point D (A/m)	Point E (A/m)	Point F (A/m)
Charging mode	10 % load	0.28	0.33	0.25	0.27	0.37	0.42
	50 % load	0.27	0.31	0.24	0.26	0.35	0.39
	90 % load	0.25	0.29	0.28	0.30	0.34	0.38

9W

Test Mode		Point A (A/m)	Point B (A/m)	Point C (A/m)	Point D (A/m)	Point E (A/m)	Point F (A/m)
Charging mode	10 % load	0.30	0.34	0.29	0.28	0.40	0.45
	50 % load	0.29	0.33	0.25	0.26	0.38	0.42
	90 % load	0.29	0.29	0.28	0.31	0.39	0.42

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Appendix A. Measurement equipment

Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
Isotropic electric Field Probe	ETS LINDGREN	HI-6105	00151770	1 year	2018.03.21
Magnetic Field Sensor	HIOKI	0850-B1	3471	1 year	2018.06.12
Magnetic Field Hitester	HIOKI	FT3470-50	140430999	1 year	2018.06.12

Peripheral device

Device	Manufacturer	Model No.	S/N	Note
AC/DC Adapter	WEIHAI PNTELECOM	MCS-H06KP	PB7Y0000322	Output Power : 9.0V / 5.0 V
10/50/90% Load	PNTELECOM CO.,LTD	N/A	N/A	N/A