

RF Exposure Analysis

FCC ID: 2AOJL-MARK3

Analysis for FCC portable use

Standalone SAR test exclusion considerations are defined in KDB 447498D01 (v06) Chapter 4.3.1 where the 1-g head or body and 10-g extremity SAR exclusion threshold is defined by the following formula:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]^{*} [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

For the LEO the maximum conducted output power is 0dBm (1.0mW).

Applying the above data using the given KDB 447498 D01 formula, and minimum separation distance of 5mm, the following results:


$(1.0\text{mW} / 5 \text{ mm}) \times \sqrt{2.4 \text{ GHz}} = 0.31$ (i.e.: ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR)

This demonstrates the MARK 3 meets the criteria for 1-g head/ body and 10-g extremity SAR test exemption.

Conclusion

The MARK 3 can be used for Portable (or Mobile) usage.

15.09.2022



Arif Çilgin
Product Compliance Manager
Workaround GmbH