



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3) Date : Apr 25, 2018

Application No. : LW005460(4)

Applicant : Origami Group Limited
Unit 913, 9/F., Tower 2, Cheung Sha Wan Plaza,
833 Cheung Sha Wan Road, Kowloon,
Hong Kong

Sample Description :	Sample Description	Model No.
	ORII Voice Assistant Smart Ring	1001

Date Received : February 22, 2018

Test Period : March 8, 2018 – April 18, 2018

Test Method : 47 CFR Part 15 (10-1-17 Edition),
ANSI C63.10 – 2013,
ANSI C63.4 – 2014

Test Engineer : Mr. Leung Shu Kan, Ken

Conclusion : The submitted sample was found to comply with technical requirement of FCC
Part 15 Subpart C, section 15.247.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____


Mr. WONG Lap-pong, Andrew
Manager
Electrical Division

Page 1 of 61

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Table of Contents

Table of Contents	2
1 Product Information	4
1.1 General Information.....	4
1.2 Technical Information.....	4
1.3 Associated Electric Accessories Informatin	4
1.4 Associated Cables	5
2.0 Equipment Units Tested (EUT).....	5
3.0 Location of Test Facility.....	5
4.0 List of test equipment, supporting equipment and cables.....	6
4.1 Test equipment.....	6
4.2 Supporting equipment.....	7
4.3 Cables.....	7
4.4 Software	7
5.0 Measurement Uncertainty.....	7
6.0 Measurement	8
6.1 General Test condition.....	8
6.2 Number of hopping frequency	8
6.2.1 Measurement	8
6.2.2 Final Result	8
6.3 Band-edge measurement	9
6.3.1 Measurement	9
6.3.2 Final Result	10
6.4 Carrier Frequency Separation	11
6.4.1 Measurement	11
6.4.2 Final Result	11
6.5 Time of occupancy (dwell time)	12
6.5.1 Measurement	12
6.5.2 Final Result	12
6.6 Output Power	13
6.6.1 Measurement	13
6.6.2 Final Result	13
6.7 Occupied Bandwidth.....	14
6.7.1 Measurement	14
6.7.2 Final Result	14
6.8 Conducted Spurious emission (Transmitter).....	15
6.8.1 Measurement	15
6.8.2 Final Result	15
6.9 Radiated Spurious emission (Transmitter).....	16
6.9.1 Measurement	16
6.9.2 Final Result	17
6.11 Conducted Emission.....	18

FCC ID: 2A0JQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

6.10.1 Measurement	18
6.10.2 Final Result	18
7.0 Frequency Hopping System Requirement	19
APPENDIX A Test Result	21

FCC ID: 2AOJQ1001

Page 3 of 61

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatcl.com.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

1 Product Information

1.1 General Information

Product Description:	Model:
ORII Voice Assistant Smart Ring	1001

Primary function	: Using Bluetooth communication for handfree function with mobile phone
Power supply	: DC 3.7V (Li-ion rechargeable battery) DC 5.0V (Charging docking)
RF related function	: Bluetooth communication for handfree function
Electric Accessories sold with	: Charg docking
Interconnection cable associated sold with	: USB charging cable
Operating condition	: Not specified
Model difference	: Not applicable

1.2 Technical Information

Operating Frequency	: 2402 – 2480MHz
Digital Modulation	: FHSS (non-BLE mode)/Digital modulation (BLE mode)
Modulation	: GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel	: 79 (non-BLE mode)/ 40 (BLE mode)
Channel Bandwidth	: 1MHz (non-BLE mode)/ 2MHz (BLE mode)
Occupied Bandwidth	: 1.32MHz (non-BLE mode)/ 0.73MHz (BLE mode)
Signal Type	: Data
Number of Antenna	: One
Antenna Type	: PCB Type Antenna
Antenna Gain	: 1.5dBi
Rated Input Voltage	: DC 3.7V (Li-ion rechargeable battery), DC 5.0V (Charging docking)
RF Technology Used	: Bluetooth 4.0+EDR and BLE dual mode
Simplex or Duplex	: Half-duplex
Adaptivity	: FHSS adaptivity

1.3 Associated Electric Accessories Information

Charging docking with micro usb port

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

1.4 Associated Cables

USB cable : Cable Type: USB
Unshielded
Length: 23cm
Without ferrite

2.0 Equipment Units Tested (EUT)

Product Description : ORII Voice Assistant Smart Ring
Model : 1001
Serial No. : Not specified
Sample Type : Production Sample and engineering sample
Sample No. : RW009341-001(7) and RW009341-013(0)
Rationale of selection : Only one model number

3.0 Location of Test Facility

CMA Industrial Development Foundation Ltd.
Room 1302, Yan Hing Centre,
9-13 Wong Chuk Yeung,
Fo Tan, Shatin,
New Territories
Hong Kong.

FCC Accredited Lab (Designation Number: HK0004)
ISED Wireless Test Site (ISED Assigned Code: 4093A)

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

4.0 List of test equipment, supporting equipment and cables

4.1 Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date	Calibration Period
EMI Test Receiver	Rohde & Schwarz	ESCS30	100001	01 Feb 2019	1Year
EMI Test Receiver	Rohde & Schwarz	ESCI	100152	07 Dec 2018	1Year
Spectrum Analyzer	R&S	FSV40	100964	08 Feb 2019	1Year
Spectrum Analyzer	Rohde & Schwarz	FSP30	100628	27 Mar 2019	1Year
Broadband Antenna	Schaffner	CBL6112B	2692	28 Mar 2020	2Years
Loop Antenna	EMCO	6502	00056620	25 Jan 2020	2Years
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-531	21 Dec 2018	2Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9718	9718-119	21 Dec 2018	2Years
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170442	02 Aug 2018	2Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9719	9719-010	02 Aug 2018	2Years
Coaxial Cable	Schaffner	RG 213/U	N/A	18 May 2018	1Year
Coaxial Cable	Suhner	RG 214/U	N/A	18 May 2018	1Year
Coaxial Cable	Suhner	Sucoflex_104	N/A	21 Dec 2018	1Year
LISN	Rohde & Schwarz	ENV216	101323	16 Jan 2019	1Year
Coaxial Cable	Tyco Electronics	RG 58C/U	N/A	24 Oct 2018	1Year
Rohde & Schwarz TS8997 Testing System					
Spectrum Analyzer	Rohde & Schwarz	FSV 40	101190	09 Aug 2018	1Year
Vector Generator	Rohde & Schwarz	SMBV100A	262024	09 Aug 2018	1Year
Generator	Rohde & Schwarz	SMB100A	103230	09 Aug 2018	1Year
OSP	Rohde & Schwarz	OSP	OSP120 V02	09 Aug 2018	1Year

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

4.2 Supporting equipment

Equipment Name	Manufacturer	Model	Serial	Provided by
Test control board*	CSR	CSR USB-SPI	Not labelled	Applicant
AC/DC adaptor	Apple	A1299	Not specified	CMA

Remark: *only used for configure engineering mode

4.3 Cables

Cable Type	Length	Shielding	Ferrite used	Provided by
USB Cable*	1.62m	shielded	Two ferrite	Applicant

Remark: *only used for configure engineering mode

4.4 Software

Software Name	Version	Function	Provided by
CSR Bluetooth Test3	V2.6.8	Configure Engineering mode	Applicant

Remark: *only used for configure engineering mode

5.0 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor $k=2$, providing a level of confidence of approximately 95%.

Radiated emissions

Frequency	Uncertainty (U_{lab})
30MHz ~ 200MHz (Horizontal)	4.59dB
30MHz ~ 200MHz (Vertical)	4.49dB
200MHz ~ 1000MHz (Horizontal)	4.94dB
200MHz ~ 1000MHz (Vertical)	4.97dB
1GHz ~ 6GHz	4.52dB
6GHz ~ 18GHz	4.58dB

Line-conducted emissions

Frequency	Uncertainty (U_{lab})
150kHz~30MHz	2.80dB

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

6.0 Measurement

6.1 General Test condition

Temperature : 24.5°C
Test Voltage : DC3.7V and AC 120V, 60Hz (for conducted emission)
Humidity : 69.2%
Atmosphere Pressure : 101.3kPa

6.2 Number of hopping frequency

6.2.1 Measurement

Requirement : FCC Part 15 § 15.247(a)(1)(iii)
Measuring procedure : ANSI C63.10:2013, clause 7.8.3
Span : 83.5MHz
RBW : 300kHz
VBW : 300kHz
Frequency range : 2.4000 – 2.4835GHz
Modulation tested : GFSK
Packet Type tested : DH5
Additional measuring procedure : Nil

6.2.2 Final Result

No. of hopping channels measured	Limit	Result	Worst case mode
79	≥ 15	PASS	GFSK and DH5

Remark: Detail test result and equipment setting refer to appendix A, A3



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

6.3 Band-edge measurement

6.3.1 Measurement

- | | |
|-------------------------------------|---|
| Requirement | : FCC Part 15 §15.247(d) |
| Measuring procedure | : ANSI C63.10:2013, section 7.8.6 and 6.10 |
| Hopping mode | : Enabled and Disable |
| RBW | : 100kHz |
| VBW | : 300kHz |
| Frequency range | : 2310 – 2483.5MHz and 2400 – 2500MHz |
| Modulation tested | : GFSK, $\pi/4$ QDPSK, 8DPSK |
| Packet Type tested | : DH5 |
| Channel tested for non-hopping mode | : 2402MHz for lowed band edge and 2480MHz for higher band edge |
| Additional measuring procedure | : For lower band edge (2400MHz) <ol style="list-style-type: none">1. Using the “Measurement 1” setting shown below the scan plot within the frequency span from 2400 – 2483.5MHz to measure the maximum peak value of fundamental2. Using the “Measurement 2” setting shown below the scan plot within the frequency span from 2310 – 2400MHz to measure the bandedge reading3. Compare that reading in procedure with the limit which equal to the measured maximum peak in procedure 1 minus 20dB |
- For Upper bandedge (2483.5MHz)
- | | |
|--|---|
| | <ol style="list-style-type: none">1. Using the “Measurement 1” setting shown below the scan plot within the frequency span from 2400 – 2483.5MHz to measure the maximum peak value of fundamental2. Using the “Measurement 2” setting shown below the scan plot within the frequency span from 2483.5 – 2500MHz to measure the bandedge reading3. Compare that reading in procedure with the limit which equal to the measured maximum peak in procedure 1 minus 20dB |
|--|---|

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

6.3.2 Final Result

Bandedge frequency for lower bandedge (Worst Case)	Worst case (dBc) ²	Detector	Limit ¹ (dBc)	Result	Worst case
2399.725153MHz	51.0	Peak	≥ 20.0	PASS	GFSK and DH5
Bandedge frequency for higher bandedge (Worst Case)	Worst case in (dBc) ²	Detector	Limit ¹	Result	Worst case
2483.524924MHz	59.3	Peak	≥ 20.0	PASS	GFSK and DH5

Remark: 1) The limit is based on the transmitter demonstrated compliance with peak conducted power limit on section 6.4.2 of this report.

2) The Worst case dBc is the peak values measured in procedure 1 minus the worst case bandedge emission

3) Detail test result and equipment setting refer to appendix A, A4-7, A18-19, A28-29

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

6.4 Carrier Frequency Separation

6.4.1 Measurement

Requirement : FCC Part 15 §15.247(a)
Measuring procedure : ANSI C63.10:2013, section 7.8.2
Hopping mode : Enabled
RBW : 300kHz
VBW : 300kHz
Frequency range : 2440 – 2443MHz¹
Modulation tested : GFSK²
Packet Type tested : DH5
Additional measuring procedure : Nil
Remark : 1) Since the measured value is more than 1.5 times of limit, only middle channel is measured.
2) Since the modulation and packet type does not affect the channel separation, GFSK and DH5 are selected as represented modulation and data type

6.4.2 Final Result

Carrier Frequency Separation	Limit ¹	Result	Worst case mode
1.000000MHz	≥0.882255	PASS	GFSK and DH5

Remark: 1) Limit is 2/3 of the 20dB bandwidth in section 6.7 and conducted peak power is less than 0.125W in section 6.6 of this report.

2) Detail test result and equipment setting refer to appendix A, A8-10

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

6.5 Time of occupancy (dwell time)

6.5.1 Measurement

Requirement	: FCC Part 15 §15.247(a)
Measuring procedure	: ANSI C63.10:2013, section 7.8.4
Hopping mode	: Disable
RBW	: 500kHz
VBW	: 1MHz
Modulation tested	: GFSK ¹
Packet Type tested	: DH1, DH3, DH5
Channel tested for non-hopping mode	: 2441MHz
Additional measuring procedure	: 1) Setup engineering sample to channel 2441MHz and DH1 packet size to perform the measurement according to ANSI C63.10, section 7.8.4 2) Find the worst case packet size 3) Repeat procedure1 with the worst case packet size for channel 2402MHz and 2480MHz
Remark	: 1) Since the modulation does not affect the dwell time, GFSK is selected as represented modulation.

6.5.2 Final Result

Dwell time (worst case)	Limit	Result	Worst case mode
307.800ms	≤400ms	PASS	GFSK and DH5

Remark: 1) Detail test result and equipment setting refer to appendix A, A11-13



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

6.6 Output Power

6.6.1 Measurement

Requirement : FCC Part 15 §15.247(b) (1)
Measuring procedure : ANSI C63.10:2013, section 7.8.5
Hopping mode : Disable
Modulation tested : GFSK, $\pi/4$ QPSK, 8DPSK
Packet Type tested : DH5¹
Channel tested for non-hopping mode : 2402MHz, 2441MHz, 2480MHz
Additional measuring procedure : Nil
Remark : 1) Since the packet size does not affect the output power, DH5 is selected as represented packet size.

6.6.2 Final Result

(a) Maximum peak conducted output power

Maximum peak conducted output power	Limit(s) ¹	Result	Modulation
7.4dBm	≤ 21.0 dBm	PASS	GFSK
7.4dBm	≤ 21.0 dBm	PASS	$\pi/4$ QPSK
7.4dBm	≤ 21.0 dBm	PASS	8DPSK

Remark: 1) 0.125W (21.0dBm) limit is used for 2/3 20dB bandwidth requirement for channel separation.

2) Detail test result and equipment setting refer to appendix A, A14, A20, A24



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

6.7 Occupied Bandwidth

6.7.1 Measurement

Requirement : FCC Part 15 §15.247(a)
Measuring procedure : ANSI C63.10:2013, section 7.8.7 and 6.9.2
Hopping mode : Disable
Modulation tested : GFSK, $\pi/4$ QPSK, 8DPSK
Packet Type tested : DH5¹
Channel tested for non-hopping mode : 2402MHz, 2441MHz, 2480MHz
Additional measuring procedure : Nil
Remark : 1) Since the packet size does not affect the bandwidth, DH5 is selected as represented packet size.

6.7.2 Final Result

20dB bandwidth	Modulation
0.935323MHz	GFSK
1.323383MHz	$\pi/4$ QPSK
1.273632MHz	8DPSK

Remark: 1) Detail test result and equipment setting refer to appendixA, A15-17, A21-23, A25-27



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

6.8 Conducted Spurious emission (Transmitter)

6.8.1 Measurement

Requirement	: FCC Part 15 §15.247(d)
Measuring procedure	: ANSI C63.10:2013, section 5.5, 5.6, 7.8.8 and 11.12.2.1
Hopping mode	: Disable
RBW	: Refer to pre-measurement and final measurement setting
Detector	: Refer to pre-measurement and final measurement setting
Modulation tested	: GFSK ¹
Packet Type tested	: DH5 ²
Channel tested for non-hopping mode	: 2402MHz, 2441MHz, 2480MHz
Additional measuring procedure	: 1) Setup engineering sample to channel 2402MHz to perform the measurement according to ANSI C63.10, section 7.8.8 with pre-measurement setting 2) If the pre-measurement is over the limit, the final measurement is performed for the specific frequency according to final measurement setting or restricted band frequency 3) For non-restricted band frequency, peak detector and 100kHz RBW will be used for final measurement. 4) Repeat the procedure 1 to 3 for channel frequency of 2441MHz and 2480MHz
Remark	: 1) Since the GFSK generates a higher SPD with power level, GFSK is selected as represented modulation for testing. 2) Since DH5 generates a higher dwell time, DH5 is selected as representative packet size for testing

6.8.2 Final Result

Worst case spurious emission frequency	Worst case spurious emission power ¹	Limit ²	Margin	Result	Worst case mode
4881.984475MHz	-44.8dBm	-41.2dBm	3.6dB	PASS	GFSK and DH5

Remark: 1) Spurious emission power = measured conducted power + antenna gain(dBi) + ground reflection factor according to ANSI C63.10 section 11.12.2.2 for restricted band emission.

2) For restricted band emission, limit = restricted band field strength limit (dBuV/m) + 4,7dB – 104.8dB according to ANSI C63.10 section 11.12.2.2 For non-restricted band, limit = SPD/100kHz – 20dB.

3) Detail test result and equipment setting refer to appendix A, A30-38

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

6.9 Radiated Spurious emission (Transmitter)

6.9.1 Measurement

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 0.4m and 0.8m high above the ground for below 1GHz measurement and 1.5m high above the ground for above 1GHz measurement. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

For 30MHz to 300MHz, biconical antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. And the reference point of antenna shall be 1 m above the ground. Same procedure for frequency 300MHz to 1000MHz but Log-periodic antenna is used for final measurements.

For above 1GHz, horn antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. Preamplifier and High Pass filter was used for measurements. The reference point of antenna shall be 1 m above the ground.

The device was rotated through three X, Y, Z orthogonal to determine which attitude and configuration produce the highest emission during measurement for Radiated Emission measurement.

The Frequencies from fundamental up to the tenth harmonics were investigated, and emissions more 20dB below limit were not reported.

Bluetooth hopping with GFSK modulation and DH5packet type is selected as worst case mode for spurious radiated emission test from cabinet.

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

6.9.2 Final Result

a) Test mode: Bluetooth hopping

Polarization	Frequency (MHz)	Reading at 3m (dBμV)	Transducer Factor (dB/m)	Field Strength at 3m ¹ (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)	Detector (PK/QP/AV)
V	*2390.000	42.7	-6.7	36.0	54.0	-18.0	PK
V	2400.000	70.2	-4.7	65.5	74.0	-8.5	PK
V	2400.000	55.3	-4.7	50.6	54.0	-3.4	AV
V	2483.500	63.7	-4.7	59.0	74.0	-15.0	PK
V	2483.500	47.9	-4.7	43.2	54.0	-10.8	AV
V	*2500.000	39.5	-4.7	34.8	54.0	-19.2	PK
H	4804.276	58.3	2.3	60.6	74.0	-13.4	PK
H	4803.972	48.4	2.3	50.7	54.0	-3.3	AV
V	4881.632	57.0	2.3	59.3	74.0	-14.7	PK
V	4881.944	47.2	2.3	49.5	54.0	-4.5	AV
V	4959.648	51.8	2.8	54.6	74.0	-19.4	PK
V	4959.910	42.3	2.8	45.1	54.0	-8.9	AV
H	*7205.710	40.3	9.6	49.9	54.0	-4.1	PK
H	*7323.436	42.5	9.6	52.1	54.0	-1.9	PK
V	*7439.580	42.9	9.6	52.5	54.0	-1.5	PK

Remark: 1) Field Strength = Reading + transducer factor.

2) Other emission with more than 20dB margin are not reported in this report.

3) * Since the peak values of emission are below the average limit, no average value is measured for average limit.

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

6.11 Conducted Emission

6.10.1 Measurement

Requirement : FCC Part 15 §15.207(a)
Measuring procedure : ANSI C63.4:2014, section 7.3
Test mode : charging mode
RBW : 9kHz
VBW : 30kHz
Modulation tested : GFSK¹
Packet Type tested : DH5
Additional measuring procedure : Nil
Remark : Nil

6.10.2 Final Result

Worst case conducted emission frequency	Worst case conducted emission	Limit	Margin	Detector	Lines	Worst case mode	Result
0.5135MHz	35.77dBμV	45.99dBμV	-10.22dB	AV	N	Charging	PASS

Remark: 1) Detail test result and equipment setting refer to appendix A, A42-45



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

7.0 Frequency Hopping System Requirement

Test Requirement: Section 15.247(a)(1), (g), (h)

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom order list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmissions bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stage: 9
- Length of pseudorandom sequence: $2^9-1=511$ bits
- Longest sequence of zero: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence


An example of Pseudorandom Frequency Hopping Sequence as following:

FCC ID: 2AOJQ1001



TEST REPORT

Date : Apr 25, 2018



Compliance for section 15.247(g)

Compliance for section 15.247(h)

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in effort to avoid the simultaneous occupancy of the individual hopping frequencies by multiple transmitter.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

APPENDIX A Test Result

FCC ID: 2ADFFKSREUN
IC: 23562-KSREUN



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

FCC Part 47 §15.247 2400-2483.5 MHz 2015

Frequencies

BT CH 1 (2402 MHz)	BT CH 2 (2403 MHz)	BT CH 3 (2404 MHz)
BT CH 4 (2405 MHz)	BT CH 5 (2406 MHz)	BT CH 6 (2407 MHz)
BT CH 7 (2408 MHz)	BT CH 8 (2409 MHz)	BT CH 9 (2410 MHz)
BT CH 10 (2411 MHz)	BT CH 11 (2412 MHz)	BT CH 12 (2413 MHz)
BT CH 13 (2414 MHz)	BT CH 14 (2415 MHz)	BT CH 15 (2416 MHz)
BT CH 16 (2417 MHz)	BT CH 17 (2418 MHz)	BT CH 18 (2419 MHz)
BT CH 19 (2420 MHz)	BT CH 20 (2421 MHz)	BT CH 21 (2422 MHz)
BT CH 22 (2423 MHz)	BT CH 23 (2424 MHz)	BT CH 24 (2425 MHz)
BT CH 25 (2426 MHz)	BT CH 26 (2427 MHz)	BT CH 27 (2428 MHz)
BT CH 28 (2429 MHz)	BT CH 29 (2430 MHz)	BT CH 30 (2431 MHz)
BT CH 31 (2432 MHz)	BT CH 32 (2433 MHz)	BT CH 33 (2434 MHz)
BT CH 34 (2435 MHz)	BT CH 35 (2436 MHz)	BT CH 36 (2437 MHz)
BT CH 37 (2438 MHz)	BT CH 38 (2439 MHz)	BT CH 39 (2440 MHz)
BT CH 40 (2441 MHz)	BT CH 41 (2442 MHz)	BT CH 42 (2443 MHz)
BT CH 43 (2444 MHz)	BT CH 44 (2445 MHz)	BT CH 45 (2446 MHz)
BT CH 46 (2447 MHz)	BT CH 47 (2448 MHz)	BT CH 48 (2449 MHz)
BT CH 49 (2450 MHz)	BT CH 50 (2451 MHz)	BT CH 51 (2452 MHz)
BT CH 52 (2453 MHz)	BT CH 53 (2454 MHz)	BT CH 54 (2455 MHz)
BT CH 55 (2456 MHz)	BT CH 56 (2457 MHz)	BT CH 57 (2458 MHz)
BT CH 58 (2459 MHz)	BT CH 59 (2460 MHz)	BT CH 60 (2461 MHz)
BT CH 61 (2462 MHz)	BT CH 62 (2463 MHz)	BT CH 63 (2464 MHz)
BT CH 64 (2465 MHz)	BT CH 65 (2466 MHz)	BT CH 66 (2467 MHz)
BT CH 67 (2468 MHz)	BT CH 68 (2469 MHz)	BT CH 69 (2470 MHz)
BT CH 70 (2471 MHz)	BT CH 71 (2472 MHz)	BT CH 72 (2473 MHz)
BT CH 73 (2474 MHz)	BT CH 74 (2475 MHz)	BT CH 75 (2476 MHz)
BT CH 76 (2477 MHz)	BT CH 77 (2478 MHz)	BT CH 78 (2479 MHz)
BT CH 79 (2480 MHz)		

Hardware Setup: WMS Measurements\WMS Hardware Setup

Spectrum Analyzer:	SA FSV 40 (SA FSV 40) @ VISA (ADR TCPIP::192.168.48.148::INST0::INSTR), SN 1321.3008K39/101190, FW 2.30 SP4
Vector Generator:	VG SMBV100A (VG SMBV100A) @ VISA (ADR TCPIP::192.168.48.149::INST0::INSTR), SN 262024, FW 5.1.0
Generator:	SMB100A (SMB100A) @ VISA (ADR TCPIP::192.168.48.152::INST0::INSTR), SN 103230, FW Rev 2.20.1, 08/2012, CVI 2009

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

OSP: TS8997 OSP (OSP) @ VISA (ADR
TCPIP::192.168.48.147::INST0::INSTR), SN OSP120 V02,
101611, FW 2.55.150506

Power Meter: OSP-B157 Power Meter (OSP-B157 Power Meter) @ USB (ADR
20), SN 27873972, FW 3.1

FCC ID: 2AOJQ1001

Page A2 of 61

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatcl.com.
This document shall not be reproduced except in full or with written approval by CMA Testing

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Hopping Frequencies (Hopping mode)

Channels

Channels	Limit Min	Limit Max	Result
79	15	---	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	278	~ 278
SweepTime	1.000 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50	0.50
Run	27 / max. 150	max. 150
Stable	3 / 3	3

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Band Edge low (Hopping mode, $\pi/4$ DQPSK and 2-DH5)

Result


DUT Frequency (MHz)	Result
hopping	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2467.984291	-4.5

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2313.872848	-64.9	40.4	-24.5	PASS
2330.313715	-65.1	40.5	-24.5	PASS
2316.921155	-65.1	40.6	-24.5	PASS
2321.968351	-65.1	40.6	-24.5	PASS
2310.924486	-65.3	40.8	-24.5	PASS
2330.263742	-65.3	40.8	-24.5	PASS
2319.119933	-65.3	40.8	-24.5	PASS
2324.267074	-65.3	40.8	-24.5	PASS
2316.971127	-65.5	40.9	-24.5	PASS
2322.068295	-65.5	41.0	-24.5	PASS
2319.169906	-65.5	41.0	-24.5	PASS
2351.951694	-65.6	41.1	-24.5	PASS
2322.018323	-65.6	41.1	-24.5	PASS
2330.213770	-65.7	41.2	-24.5	PASS
2379.086619	-65.8	41.2	-24.5	PASS



FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 s	1.670 s
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	RMS	RMS
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 15	max. 15
Stable	3 / 3	3

Measurement 2

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1800	~ 1800
SweepTime	1.800 s	1.800 s
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	RMS	RMS
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 15	max. 15
Stable	3 / 3	3

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Band Edge high (Hopping mode, $\pi/4$ DQPSK and 2-DH5)

Result


DUT Frequency (MHz)	Result
hopping	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2438.152154	-4.8

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2484.073263	-65.0	40.2	-24.8	PASS
2493.694109	-65.2	40.4	-24.8	PASS
2495.040030	-65.2	40.4	-24.8	PASS
2497.283233	-65.4	40.6	-24.8	PASS
2498.878399	-65.5	40.7	-24.8	PASS
2495.089879	-65.5	40.7	-24.8	PASS
2497.582326	-65.5	40.7	-24.8	PASS
2493.743958	-65.6	40.8	-24.8	PASS
2497.333082	-65.6	40.8	-24.8	PASS
2487.911631	-65.6	40.8	-24.8	PASS
2498.928248	-65.7	40.9	-24.8	PASS
2484.023414	-65.7	40.9	-24.8	PASS
2487.861782	-65.8	41.0	-24.8	PASS
2497.632175	-65.8	41.0	-24.8	PASS
2491.799849	-65.8	41.0	-24.8	PASS



FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 s	1.670 s
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	RMS	RMS
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 15	max. 15
Stable	3 / 3	3

Measurement 2

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	330	~ 330
SweepTime	330.000 ms	330.000 ms
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	RMS	RMS
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 15	max. 15
Stable	3 / 3	3

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Carrier Frequency Separation (2402 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)	Result
2402.000000	0.970588	0.666667	---	2401.985294	2402.955882	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40400 GHz	2.40400 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	6.313 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	25 / max. 150	max. 150
Stable	10 / 10	10

FCC ID: 2A0JQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Carrier Frequency Separation (2441 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)	Result
2441.000000	1.000000	0.666667	---	2440.985294	2441.985294	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44300 GHz	2.44300 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	6.313 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	10 / max. 150	max. 150
Stable	10 / 10	10

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Carrier Frequency Separation (2479 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)	Result
2479.000000	1.000000	0.666667	---	2478.955882	2479.955882	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47800 GHz	2.47800 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	6.313 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	29 / max. 150	max. 150
Stable	10 / 10	10

FCC ID: 2A0JQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Time of Channel Occupancy (2441 MHz; GFSK and DH1)

Result

DUT Frequency (MHz)	Time (ms)	Limit Max (ms)	Limit Min (ms)	Threshold (dBm)	Result
2441.000000	127.930	---	0.000	-14.0	PASS



Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	0.000 dBm	0.000 dBm
Attenuation	10.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamplifier	off	off
Trigger	Extern	Extern
Trigger Offset	0.000 ms	0.000 ms

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Time of Channel Occupancy(2) (2441 MHz; GFSK and DH3)

Result

DUT Frequency (MHz)	Time (ms)	Limit Max (ms)	Limit Min (ms)	Threshold (dBm)	Result
2441.000000	264.910	---	0.000	-14.0	PASS



Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	0.000 dBm	0.000 dBm
Attenuation	10.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamplifier	off	off
Trigger	Extern	Extern
Trigger Offset	0.000 ms	0.000 ms

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Time of Channel Occupancy(3) (2441 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Time (ms)	Limit Max (ms)	Limit Min (ms)	Threshold (dBm)	Result
2441.000000	307.800	---	0.000	-14.0	PASS



Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	0.000 dBm	0.000 dBm
Attenuation	10.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamplifier	off	off
Trigger	Extern	Extern
Trigger Offset	0.000 ms	0.000 ms

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

RF output power (2402 MHz; 6dBm; GFSK and DH5)

Result

DUT Frequency (MHz)	Gated (dBm)	Limit Max (dBm)	DutyCycle (%)	Result
2402.000000	6.6	21.0	77.583	PASS



FCC ID: 2AOJQ1001

Page A14 of 61

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatcl.com.
This document shall not be reproduced except in full or with written approval by CMA Testing

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Emission Bandwidth 20 dB (2402 MHz; GFSK and DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2402.000000	0.935323	---	---	2401.522388	2402.457711	1.0	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	~ 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	200	~ 200
SweepTime	189.620 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	9 / max. 150	max. 150
Stable	5 / 5	5

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Emission Bandwidth 20 dB(2) (2402 MHz; $\pi/4$ DQPSK and 2-DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2402.000000	1.273632	---	---	2401.373134	2402.646766	-2.6	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	~ 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	200	~ 200
SweepTime	189.620 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	9 / max. 150	max. 150
Stable	5 / 5	5

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Emission Bandwidth 20 dB(3) (2402 MHz; 8DPSK and 3-DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2402.000000	1.273631	---	---	2401.343284	2402.616915	-2.6	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	~ 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	200	~ 200
SweepTime	189.620 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	7 / max. 150	max. 150
Stable	5 / 5	5

FCC ID: 2A0JQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Band Edge low (2402 MHz; $\pi/4$ DQPSK and 2-DH5)

Result


DUT Frequency (MHz)	Result
2402.000000	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2402.173698	-6.0

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.725153	-57.0	31.0	-26.0	PASS
2399.775125	-57.2	31.2	-26.0	PASS
2399.925042	-57.3	31.3	-26.0	PASS
2399.875069	-57.3	31.3	-26.0	PASS
2399.675180	-57.7	31.7	-26.0	PASS
2399.825097	-57.8	31.8	-26.0	PASS
2399.575236	-58.0	32.0	-26.0	PASS
2399.625208	-58.1	32.1	-26.0	PASS
2399.525264	-58.7	32.7	-26.0	PASS
2399.475292	-59.1	33.1	-26.0	PASS
2399.425319	-59.2	33.2	-26.0	PASS
2399.375347	-59.8	33.8	-26.0	PASS
2399.325375	-60.5	34.5	-26.0	PASS
2399.075514	-61.1	35.1	-26.0	PASS
2399.125486	-61.2	35.2	-26.0	PASS



FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 s	1.670 s
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	RMS	RMS
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 15	max. 15
Stable	3 / 3	3

Measurement 2

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1800	~ 1800
SweepTime	1.800 s	1.800 s
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	RMS	RMS
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 15	max. 15
Stable	3 / 3	3

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

RF output power (2441 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Gated (dBm)	Limit Max (dBm)	Duty Cycle (%)	Result
2441.000000	7.4	21.0	77.583	PASS



FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Emission Bandwidth 20 dB (2441 MHz; GFSK and DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2441.000000	0.935323	---	---	2440.522388	2441.457711	1.9	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	~ 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	200	~ 200
SweepTime	189.620 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	7 / max. 150	max. 150
Stable	5 / 5	5

FCC ID: 2A0JQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Emission Bandwidth 20 dB(2) (2441 MHz; $\pi/4$ DQPSK and 2-DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2441.000000	1.323383	---	---	2440.323383	2441.646766	-1.5	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	~ 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	200	~ 200
SweepTime	189.620 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	6 / max. 150	max. 150
Stable	5 / 5	5

FCC ID: 2A0JQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Emission Bandwidth 20 dB(3) (2441 MHz; 8DPSK and 3-DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2441.000000	1.273632	---	---	2440.333333	2441.606965	-1.4	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	~ 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	200	~ 200
SweepTime	189.620 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	7 / max. 150	max. 150
Stable	5 / 5	5

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

RF output power (2480 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Gated (dBm)	Limit Max (dBm)	Duty Cycle (%)	Result
2480.000000	7.1	21.0	77.581	PASS



FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Emission Bandwidth 20 dB (2480 MHz; GFSK and DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2480.000000	0.935323	---	---	2479.522388	2480.457711	1.5	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	~ 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	200	~ 200
SweepTime	189.620 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	6 / max. 150	max. 150
Stable	5 / 5	5

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Emission Bandwidth 20 dB(2) (2480 MHz; $\pi/4$ DQPSK and 2-DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2480.000000	1.313433	---	---	2479.323383	2480.636816	-1.7	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	~ 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	200	~ 200
SweepTime	189.620 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	8 / max. 150	max. 150
Stable	5 / 5	5

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0024542(3)

Date : Apr 25, 2018

Emission Bandwidth 20 dB(3) (2480 MHz; 8DPSK and 3-DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2480.000000	1.273632	---	---	2479.333333	2480.606965	-1.7	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	~ 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	200	~ 200
SweepTime	189.620 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	10 / max. 150	max. 150
Stable	5 / 5	5

FCC ID: 2A0JQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Band Edge high (2480 MHz; $\pi/4$ DQPSK and 2-DH5)

Result


DUT Frequency (MHz)	Result
2480.000000	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2479.977110	-4.8

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2483.524924	-64.1	39.3	-24.8	PASS
2483.574773	-64.6	39.8	-24.8	PASS
2483.824018	-64.8	40.0	-24.8	PASS
2483.724320	-64.9	40.0	-24.8	PASS
2483.624622	-65.0	40.2	-24.8	PASS
2483.674471	-65.0	40.2	-24.8	PASS
2483.774169	-65.1	40.3	-24.8	PASS
2483.973565	-65.4	40.6	-24.8	PASS
2483.873867	-65.4	40.6	-24.8	PASS
2484.073263	-65.6	40.8	-24.8	PASS
2483.923716	-65.7	40.8	-24.8	PASS
2484.222810	-65.7	40.8	-24.8	PASS
2484.023414	-65.7	40.9	-24.8	PASS
2484.172961	-65.7	40.9	-24.8	PASS
2484.322508	-66.0	41.2	-24.8	PASS



FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 s	1.670 s
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	RMS	RMS
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 15	max. 15
Stable	3 / 3	3

Measurement 2

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	330	~ 330
SweepTime	330.000 ms	330.000 ms
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	RMS	RMS
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 15	max. 15
Stable	3 / 3	3

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Tx Spurious Emission (2402 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Result
2402.000000	PASS

Final measurements

Frequency (MHz)	Level Pre Measurement (dBm)	level (dBm)	Limit (dBm)	Margin (dB)	Result
4803.993109	-46.0	-48.3	-41.2	7.0	PASS

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
4803.993109	-46.0	4.8	-41.2
4804.493054	-46.0	4.8	-41.2
4803.493165	-46.0	4.8	-41.2
4804.992999	-48.3	7.0	-41.2
4802.993220	-48.4	7.2	-41.2
2251.802928	-54.4	13.2	-41.2
2252.302749	-54.7	13.4	-41.2
2251.303106	-54.7	13.4	-41.2
4805.492943	-55.8	14.5	-41.2
2276.794002	-56.7	15.5	-41.2
2276.294181	-57.1	15.9	-41.2
2277.293824	-57.3	16.0	-41.2
2252.802571	-57.3	16.0	-41.2
4802.493275	-57.5	16.3	-41.2
12010.639960	-57.9	16.7	-41.2

Measurement Settings

Start Frequency (MHz)	Stop Frequency (MHz)	Pre Measurement	Final Measurement
30.000000	1000.000000	1	1
1000.000000	2400.000000	2	2
2400.000000	2483.500000	2	2
2483.500000	7000.000000	2	2
7000.000000	26000.000000	2	2

FCC ID: 2AOJQ1001




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018



× Limit [limit.Result:1] × Sum Level [trace.Result:1]
◆ Threshold [limit 2.Result:1] ◆ Critical [Over Limit.Result:1]

Pre Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	19400	~ 19400
SweepTime	19.400 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 150	max. 150
Stable	3 / 3	3

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Pre Measurement 2

Setting	Instrument Value	Target Value
RBW	1.000 MHz	<= 1.000 MHz
VBW	3.000 MHz	>= 3.000 MHz
SweepPoints	2800	~ 2800
SweepTime	2.800 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 150	max. 150
Stable	3 / 3	3

Final Measurement 2

Setting	Instrument Value	Target Value
Span	ZeroSpan	ZeroSpan
RBW	1.000 MHz	~ 1.000 MHz
VBW	3.000 MHz	~ 3.000 MHz
SweepPoints	10001	~ 10001
SweepTime	1.000 s	1.000 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	RMS	RMS
SweepCount	1	1
Filter	3 dB	3 dB
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Tx Spurious Emission (2441 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Result
2441.000000	PASS

Final measurements

Frequency (MHz)	Level Pre Measurement (dBm)	level (dBm)	Limit (dBm)	Margin (dB)	Result
4881.984475	-44.8	-77.9	-41.2	36.7	PASS

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
4881.984475	-44.8	3.6	-41.2
4882.484420	-44.8	3.6	-41.2
4881.484531	-45.0	3.8	-41.2
4880.984586	-46.7	5.5	-41.2
4882.984363	-47.2	6.0	-41.2
7323.870383	-50.7	9.5	-41.2
7323.276670	-51.0	9.7	-41.2
7322.682957	-51.2	10.0	-41.2
7322.089244	-51.7	10.5	-41.2
7324.464096	-53.1	11.9	-41.2
2291.288825	-53.3	12.1	-41.2
2290.789004	-53.3	12.1	-41.2
4883.484309	-53.8	12.6	-41.2
2290.289182	-53.9	12.7	-41.2
4880.484641	-54.7	13.4	-41.2

Measurement Settings

Start Frequency (MHz)	Stop Frequency (MHz)	Pre Measurement	Final Measurement
30.000000	1000.000000	1	1
1000.000000	2400.000000	2	2
2400.000000	2483.500000	2	2
2483.500000	7000.000000	2	2
7000.000000	26000.000000	2	2

FCC ID: 2AOJQ1001




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018



× Limit [limit.Result:1] × Sum Level [trace.Result:1]
◆ Threshold [limit 2.Result:1] ◆ Critical [Over Limit.Result:1]

Pre Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	19400	~ 19400
SweepTime	19.400 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 150	max. 150
Stable	3 / 3	3

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Pre Measurement 2

Setting	Instrument Value	Target Value
RBW	1.000 MHz	<= 1.000 MHz
VBW	3.000 MHz	>= 3.000 MHz
SweepPoints	2800	~ 2800
SweepTime	2.800 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 150	max. 150
Stable	3 / 3	3

Final Measurement 2

Setting	Instrument Value	Target Value
Span	ZeroSpan	ZeroSpan
RBW	1.000 MHz	~ 1.000 MHz
VBW	3.000 MHz	~ 3.000 MHz
SweepPoints	10001	~ 10001
SweepTime	1.000 s	1.000 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	RMS	RMS
SweepCount	1	1
Filter	3 dB	3 dB
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off

FCC ID: 2AOJQ1001

Page A35 of 61

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatcl.com.
This document shall not be reproduced except in full or with written approval by CMA Testing

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Tx Spurious Emission (2480 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Result
2480.000000	PASS

Final measurements

Frequency (MHz)	Level Pre Measurement (dBm)	level (dBm)	Limit (dBm)	Margin (dB)	Result
2483.749972	-38.5	-52.3	-41.2	11.1	PASS
4960.475786	-46.2	-50.5	-41.2	9.3	PASS

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
2483.749972	-38.5	-2.8	-41.2
2484.249917	-46.2	5.0	-41.2
4960.475786	-46.2	5.0	-41.2
4959.975841	-46.2	5.0	-41.2
4959.475897	-46.4	5.1	-41.2
4960.975731	-47.8	6.6	-41.2
4958.975952	-48.4	7.2	-41.2
7439.644397	-49.4	8.2	-41.2
7440.238110	-50.0	8.8	-41.2
7439.050684	-50.0	8.8	-41.2
7440.831823	-50.0	8.8	-41.2
2484.749862	-50.7	9.4	-41.2
2485.749751	-52.1	10.9	-41.2
2485.249806	-53.4	12.1	-41.2
2380.257051	-53.7	12.5	-41.2

Measurement Settings

Start Frequency (MHz)	Stop Frequency (MHz)	Pre Measurement	Final Measurement
30.000000	1000.000000	1	1
1000.000000	2400.000000	2	2
2400.000000	2483.500000	2	2
2483.500000	7000.000000	2	2
7000.000000	26000.000000	2	2

FCC ID: 2AOJQ1001




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018



× Limit [limit.Result:1] × Sum Level [trace.Result:1]
◆ Threshold [limit 2.Result:1] ◆ Critical [Over Limit.Result:1]

Pre Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	19400	~ 19400
SweepTime	19.400 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 150	max. 150
Stable	3 / 3	3

FCC ID: 2AOJQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Pre Measurement 2

Setting	Instrument Value	Target Value
RBW	1.000 MHz	<= 1.000 MHz
VBW	3.000 MHz	>= 3.000 MHz
SweepPoints	2800	~ 2800
SweepTime	2.800 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30	0.30
Run	3 / max. 150	max. 150
Stable	3 / 3	3

Final Measurement 2

Setting	Instrument Value	Target Value
Span	ZeroSpan	ZeroSpan
RBW	1.000 MHz	~ 1.000 MHz
VBW	3.000 MHz	~ 3.000 MHz
SweepPoints	10001	~ 10001
SweepTime	1.000 s	1.000 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	RMS	RMS
SweepCount	1	1
Filter	3 dB	3 dB
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off

FCC ID: 2AOJQ1001

Page A38 of 61

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatcl.com.
This document shall not be reproduced except in full or with written approval by CMA Testing

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

Conducted Emission


1) Bluetooth mode



RBW 9 kHz

MT 1 s

Att 10 dB AUTO PREAMP OFF



Date: 5.MAR.2018 14:53:12

FCC ID: 2A0JQ1001



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0024542(3)

Date : Apr 25, 2018

EDIT PEAK LIST (Final Measurement Results)			
Trace1:	FCC-QP		
Trace2:	FCC-AV		
Trace3:	---		
TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
1 Quasi Peak	204 kHz	30.57 L1 gnd	-32.87
1 Quasi Peak	325.5 kHz	28.66 N gnd	-30.90
1 Quasi Peak	513.5 kHz	37.21 L1 gnd	-18.78
2 Average	513.5 kHz	35.77 N gnd	-10.22
2 Average	801.5 kHz	15.43 N gnd	-30.56
1 Quasi Peak	855.5 kHz	20.76 L1 gnd	-35.23
2 Average	1.4945 MHz	19.50 N gnd	-26.49
1 Quasi Peak	1.6385 MHz	21.28 N gnd	-34.71
2 Average	2.48 MHz	18.22 N gnd	-27.77
1 Quasi Peak	2.8085 MHz	24.09 N gnd	-31.90
1 Quasi Peak	4.9955 MHz	24.80 N gnd	-31.19
2 Average	4.9955 MHz	20.25 N gnd	-25.74
2 Average	6.8045 MHz	17.47 L1 gnd	-32.52
1 Quasi Peak	7.529 MHz	25.21 L1 gnd	-34.78
1 Quasi Peak	17.591 MHz	43.15 N gnd	-16.84
2 Average	17.6225 MHz	29.89 N gnd	-20.10
1 Quasi Peak	18.176 MHz	42.92 N gnd	-17.07
2 Average	18.176 MHz	30.48 N gnd	-19.51

Date: 5.MAR.2018 14:53:00

***** End of Report *****

FCC ID: 2AOJQ1001

Page A40 of 61

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatcl.com.
This document shall not be reproduced except in full or with written approval by CMA Testing

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>