

FCC Test Report

Report No. : 1815C50364112501

Applicant : Anker Innovations Limited

Address : Unit 56, 8th Floor, Tower 2, Admiralty Centre,
18 Harcourt Road, Hong Kong

Product Name : Anker 633 Magnetic Battery(MagGo)

Report Date : 2025-09-08

Shenzhen Anbotek Compliance Laboratory Limited



Contents

- 1. General Information.....5
 - 1.1. Client Information5
 - 1.2. Description of Device (EUT)5
 - 1.3. Auxiliary Equipment Used During Test6
 - 1.4. Description of Test Modes6
 - 1.5. Description Of Test Setup7
 - 1.6. Test Equipment List8
 - 1.7. Measurement Uncertainty9
 - 1.8. Description of Test Facility9
 - 1.9. Disclaimer9
- 2. Summary of Test Results10
- 3. Conducted Emission Test11
 - 3.1. Test Standard and Limit11
 - 3.2. Test Setup11
 - 3.3. Test Procedure11
 - 3.4. Test Data11
- 4. Radiation Spurious Emission14
 - 4.1. Test Standard and Limit14
 - 4.2. Test Setup14
 - 4.3. Test Procedure15
 - 4.4. Test Data15
- 5. Antenna Requirement20
 - 5.1. Test Standard and Requirement20
 - 5.2. Antenna Connected Construction20
- APPENDIX I -- TEST SETUP PHOTOGRAPH21
- APPENDIX II -- EXTERNAL PHOTOGRAPH.....21
- APPENDIX III -- INTERNAL PHOTOGRAPH.....21

TEST REPORT

Applicant : Anker Innovations Limited
Manufacturer : Anker Innovations Limited
Product Name : Anker 633 Magnetic Battery(MagGo)
Model No. : A1641
Trade Mark : ANKER
Rating(s) : Battery Capacity: 7.7Vdc/38.5Wh(5000mAh, Two Cells in Series)
USB-C Input: 5V=3A/9V=2.22A(20W Max)
USB-C Output: 5V=3A/9V=2.22A(20W Max)
USB-A Output: 5V=3A/9V=2A(18W Max)
Wireless Output: 5W/7.5W
Total Output: 5V=3.6A Max

Test Standard(s) : 47 CFR Part 15 Subpart C

Test Method(s) : ANSI C63.10: 2020

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the 47 CFR Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt 2025-06-27

Date of Test 2025-06-27 to 2025-07-31

Prepared By Lene Chen
(Lene Chen)

Approved & Authorized Signer Hugo Chen
(Hugo Chen)

Revision History

| Report Version | Description | Issued Date |
|----------------|-------------------------|-------------|
| R00 | Original Issue.(Note 1) | 2025-09-08 |
| | | |
| | | |

Note 1:

This is a Class II application which was based on the original report 1815C40018612501. The difference between the original device and current one described as following:

1. Replace the battery cells

Based on the change, only EMC were retested. Other tests will retain the original test results.

1. General Information

1.1. Client Information

| | | |
|--------------|---|--|
| Applicant | : | Anker Innovations Limited |
| Address | : | Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong |
| Manufacturer | : | Anker Innovations Limited |
| Address | : | Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong |

1.2. Description of Device (EUT)

| | | |
|-------------------|---|--|
| Product Name | : | Anker 633 Magnetic Battery(MagGo) |
| Model No. | : | A1641 |
| Trade Mark | : | ANKER |
| Test Power Supply | : | DC 9V from adapter input AC 120V, 60Hz/ DC 7.7V battery inside |
| Test Sample No. | : | 1-2-1(Normal Sample), 1-2-2(Engineering Sample) |
| Adapter | : | N/A |

RF Specification

| | | |
|---------------------|---|-----------------------------|
| Operation Frequency | : | 111-147kHz |
| Modulation Type | : | FSK |
| Antenna Type | : | Inductive loop coil Antenna |

Remark: 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

1.3. Auxiliary Equipment Used During Test



| Title | Manufacturer | Model No. | Serial No. |
|------------------------|------------------------------------|-----------|-----------------|
| Xiaomi 33W adapter | Xiaomi | MDY-11-EX | SA62212LA04358J |
| Wireless charging load | Shenzhen Ouju Technology Co., Ltd. | CD2577 | / |

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Modes | Descriptions |
|---------------|----------------------------------|
| TM1 | Adapter+WPT Mode (7.5W 1% Load) |
| TM2 | Adapter+WPT Mode (7.5W 50% Load) |
| TM3 | Adapter+WPT Mode (7.5W 99% Load) |
| TM4 | Adapter+WPT Mode (5W 1% Load) |
| TM5 | Adapter+WPT Mode (5W 50% Load) |
| TM6 | Adapter+WPT Mode (5W 99% Load) |
| TM7 | WPT Mode (7.5W 1% Load) |
| TM8 | WPT Mode (7.5W 50% Load) |
| TM9 | WPT Mode (7.5W 99% Load) |
| TM10 | WPT Mode (5W 1% Load) |
| TM11 | WPT Mode (5W 50% Load) |
| TM12 | WPT Mode (5W 99% Load) |
| TM13 | Standby Mode |

1.5. Description Of Test Setup



1.6. Test Equipment List

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|--|-----------------|-------------------|------------------|------------|---------------|
| 1. | L.I.S.N. Artificial Mains Network | Rohde & Schwarz | ENV216 | 100055 | 2024-09-09 | 1 Year |
| 2. | Three Phase V- type Artificial Power Network | CYBERTEK | EM5040DT | E215040DT00 1 | 2025-01-13 | 1 Year |
| 3. | EMI Test Receiver | Rohde & Schwarz | ESCI | 100627 | 2025-01-13 | 1 Year |
| 4. | EMI Test Receiver | Rohde & Schwarz | ESR26 | 101481 | 2025-01-14 | 1 Year |
| 5. | MXA Spectrum Analysis | Agilent | N9020A | MY51170037 | 2024-09-09 | 1 Year |
| 6. | EMI Preamplifier | SKET Electronic | LNPA-0118G- 45 | SKET-PA-002 | 2025-01-13 | 1 Year |
| 7. | Double Ridged Horn Antenna | SCHWARZBECK | BBHA 9120D | 02555 | 2022-10-16 | 3 Year |
| 8. | Bilog Broadband Antenna | Schwarzbeck | VULB9163 | 345 | 2022-10-23 | 3 Year |
| 9. | Loop Antenna(9K- 30M) | Schwarzbeck | FMZB1519B | 00053 | 2024-09-12 | 1 Year |
| 10. | Horn Antenna | A-INFO | LB-180400-KF | J211060628 | 2024-01-22 | 3 Year |
| 11. | Pre-amplifier | SONOMA | 310N | 186860 | 2025-01-14 | 1 Year |
| 12. | EMI Test Software EZ-EMC | SHURPLE | N/A | N/A | N/A | N/A |
| 13. | MXA Spectrum Analysis | KEYSIGHT | N9020A | MY53280032 | 2024-09-09 | 1 Year |
| 14. | MXG RF Vector Signal Generator | Agilent | N5182A | MY47420647 | 2025-02-21 | 1 Year |
| 15. | Signal Generator | Agilent | E4421B | MY41000743 | 2025-02-21 | 1 Year |
| 16. | DC Power Supply | IVYTECH | IV3605 | 1804D360510 | 2024-09-09 | 1 Year |
| 17. | Constant Temperature Humidity Chamber | ZHONGJIAN | ZJ-KHWS80B | N/A | 2024-10-14 | 1 Year |
| 18. | Spectrum Analyzer | Rohde & Schwarz | FSV40-N | 102150 | 2025-04-25 | 1 Year |

1.7. Measurement Uncertainty

| Parameter | Uncertainty |
|--|--------------------------------------|
| Conducted emissions (AMN 150kHz~30MHz) | 3.8dB |
| Occupied Bandwidth | 925Hz |
| Radiated spurious emissions (Below 30MHz) | 3.53dB |
| Radiated spurious emissions (30MHz~1GHz) | Horizontal: 3.92dB; Vertical: 4.52dB |
| The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. | |

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 279531

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 279531.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.
7. The data in this report will be synchronized with the corresponding national market supervision and management departments and cross-border e-commerce platforms as required by regulatory agencies.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Summary of Test Results

| Standard Section | Test Item | Result |
|------------------|-------------------------|--------|
| 15.203 | Antenna Requirement | PASS |
| 15.207 | Conducted Emission Test | PASS |
| 15.205/15.209 | Spurious Emission | PASS |


Note: N/A” denotes test is not applicable in this Test Report

3. Conducted Emission Test

3.1. Test Standard and Limit

| | | | |
|--|---------------------------|--------------------------------|---------------|
| Test Standard | FCC Part15 Section 15.207 | | |
| Test Limit | Frequency | Maximum RF Line Voltage (dBuV) | |
| | | Quasi-peak Level | Average Level |
| | 150kHz~500kHz | 66 ~ 56 * | 56 ~ 46 * |
| | 500kHz~5MHz | 56 | 46 |
| | 5MHz~30MHz | 60 | 50 |
| Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency. | | | |

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.


The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report. Please to see the following pages.

Conducted Emission Test Data


Test Site: 1# Shielded Room
 Operating Condition: TM3
 Test Specification: DC 9V from adapter input AC 120V, 60Hz
 Comment: Live Line
 Temp.(°C)/Hum.(%RH): 24.6°C/59%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|--------------|-----------------|----------|--------|
| 1 | 0.3180 | 22.60 | 27.85 | 50.45 | 59.76 | -9.31 | QP | |
| 2 | 0.4100 | 13.91 | 27.82 | 41.73 | 47.65 | -5.92 | AVG | |
| 3 | 0.4180 | 20.85 | 27.83 | 48.68 | 57.49 | -8.81 | QP | |
| 4 | 0.5220 | 12.50 | 27.87 | 40.37 | 46.00 | -5.63 | AVG | |
| 5 | 1.0420 | 13.81 | 27.87 | 41.68 | 46.00 | -4.32 | AVG | |
| 6 | 1.2700 | 22.22 | 27.87 | 50.09 | 56.00 | -5.91 | QP | |
| 7 | 1.3700 | 14.08 | 27.87 | 41.95 | 46.00 | -4.05 | AVG | |
| 8 | 1.5940 | 19.87 | 27.86 | 47.73 | 56.00 | -8.27 | QP | |
| 9 | 1.7060 | 9.81 | 27.86 | 37.67 | 46.00 | -8.33 | AVG | |
| 10 | 2.0140 | 17.70 | 27.86 | 45.56 | 56.00 | -10.44 | QP | |
| 11 | 2.0460 | 8.02 | 27.86 | 35.88 | 46.00 | -10.12 | AVG | |
| 12 | 3.2020 | 13.05 | 27.86 | 40.91 | 56.00 | -15.09 | QP | |

Conducted Emission Test Data

Test Site: 1# Shielded Room
 Operating Condition: TM3
 Test Specification: DC 9V from adapter input AC 120V, 60Hz
 Comment: Neutral Line
 Temp.(°C)/Hum.(%RH): 24.6°C/59%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|--------------|-----------------|----------|--------|
| 1 | 0.2300 | 23.29 | 27.83 | 51.12 | 62.45 | -11.33 | QP | |
| 2 | 0.4700 | 11.70 | 27.86 | 39.56 | 46.51 | -6.95 | AVG | |
| 3 | 0.6260 | 12.25 | 27.88 | 40.13 | 46.00 | -5.87 | AVG | |
| 4 | 0.7420 | 22.28 | 27.88 | 50.16 | 56.00 | -5.84 | QP | |
| 5 | 1.2579 | 21.56 | 27.87 | 49.43 | 56.00 | -6.57 | QP | |
| 6 | 1.3619 | 13.11 | 27.87 | 40.98 | 46.00 | -5.02 | AVG | |
| 7 | 1.6340 | 19.36 | 27.86 | 47.22 | 56.00 | -8.78 | QP | |
| 8 | 1.7980 | 9.80 | 27.87 | 37.67 | 46.00 | -8.33 | AVG | |
| 9 | 1.9860 | 18.02 | 27.86 | 45.88 | 56.00 | -10.12 | QP | |
| 10 | 2.5579 | 8.61 | 27.86 | 36.47 | 46.00 | -9.53 | AVG | |
| 11 | 2.6900 | 15.44 | 27.86 | 43.30 | 56.00 | -12.70 | QP | |
| 12 | 4.7340 | 5.33 | 27.87 | 33.20 | 46.00 | -12.80 | AVG | |

4. Radiation Spurious Emission

4.1. Test Standard and Limit

| Test Standard | FCC Part15 C Section 15.209 and 15.205 | | | | |
|---------------|--|----------------------------------|----------------|------------|--------------------------|
| Test Limit | Frequency (MHz) | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark | Measurement distance (m) |
| | 0.009MHz~0.490MHz | 2400/F(kHz) | - | - | 300 |
| | 0.490MHz-1.705MHz | 24000/F(kHz) | - | - | 30 |
| | 1.705MHz-30MHz | 30 | - | - | 30 |
| | 30MHz~88MHz | 100 | 40.0 | Quasi-peak | 3 |
| | 88MHz~216MHz | 150 | 43.5 | Quasi-peak | 3 |
| | 216MHz~960MHz | 200 | 46.0 | Quasi-peak | 3 |
| | 960MHz~1000MHz | 500 | 54.0 | Quasi-peak | 3 |
| | Above 1000MHz | 500 | 54.0 | Average | 3 |
| - | | - | 74.0 | Peak | 3 |

Remark:

- (1)The lower limit shall apply at the transition frequency.
- (2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.


4.4. Test Data

PASS

Both coaxial and planar tests were conducted, and only the worst coplanar test data is reflected in the report.

Test Results (Between 9KHz – 150KHz)


Test Mode: TM3
Distance: 3m
Power Source: DC 7.7V battery inside
Polarization: Coplane
Temp.(°C)/Hum.(%RH): 25.1°C/49%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor () | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-----------|-----------------|----------------|-----------------|----------|--------|
| 1 | 0.0101 | -1.21 | 20.09 | 18.88 | 127.31 | -108.43 | peak | |
| 2 | 0.0199 | -1.93 | 20.29 | 18.36 | 121.46 | -103.10 | peak | |
| 3 | 0.0321 | -1.05 | 20.56 | 19.51 | 117.33 | -97.82 | peak | |
| 4 | 0.0351 | -6.12 | 20.49 | 14.37 | 116.56 | -102.19 | peak | |
| 5 | 0.0515 | -11.79 | 20.40 | 8.61 | 113.25 | -104.64 | peak | |
| 6 | 0.1200 | 24.85 | 20.34 | 45.19 | 105.95 | -60.76 | peak | |

Test Results (Between 0.15MHz – 30MHz)

Test Mode: TM3
Distance: 3m
Power Source: DC 7.7V battery inside
Polarization: Coplane
Temp.(°C)/Hum.(%RH): 25.1°C/49%RH




| No. | Freq. (MHz) | Reading (dBuV) | Factor () | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-----------|-----------------|----------------|-----------------|----------|--------|
| 1 | 0.3082 | -5.38 | 20.30 | 14.92 | 97.80 | -82.88 | peak | |
| 2 | 0.6683 | -4.54 | 20.26 | 15.72 | 71.11 | -55.39 | QP | |
| 3 | 1.2892 | -1.41 | 20.26 | 18.85 | 65.42 | -46.57 | QP | |
| 4 | 2.1668 | -6.97 | 20.28 | 13.31 | 69.50 | -56.19 | QP | |
| 5 | 3.7198 | -9.63 | 20.35 | 10.72 | 69.50 | -58.78 | QP | |
| 6 | 10.3972 | -12.64 | 20.52 | 7.88 | 69.50 | -61.62 | QP | |

Remark: According to FCC PART 15.209 (d), the emission limits for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, Radiated emission limits in these three bands are based on measurements employing an average detector.


Test Results (Between 30MHz –1000 MHz)

Test Mode: TM3
Distance: 3m
Power Source: DC 7.7V battery inside
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 22.5°C/55%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|---------------|-----------------|----------------|-----------------|----------|--------|
| 1 | 47.1599 | 30.96 | -16.92 | 14.04 | 40.00 | -25.96 | QP | |
| 2 | 56.5929 | 30.76 | -17.83 | 12.93 | 40.00 | -27.07 | QP | |
| 3 | 165.4866 | 41.96 | -22.03 | 19.93 | 43.50 | -23.57 | QP | |
| 4 | 185.1379 | 42.10 | -20.97 | 21.13 | 43.50 | -22.37 | QP | |
| 5 | 719.1995 | 34.32 | -8.68 | 25.64 | 46.00 | -20.36 | QP | |
| 6 | 972.3374 | 33.87 | -5.58 | 28.29 | 54.00 | -25.71 | QP | |

Test Mode: TM3
Distance: 3m
Power Source: DC 7.7V battery inside
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 22.5°C/55%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|---------------|-----------------|----------------|-----------------|----------|--------|
| 1 | 39.9942 | 31.11 | -15.95 | 15.16 | 40.00 | -24.84 | QP | |
| 2 | 53.1313 | 32.04 | -17.57 | 14.47 | 40.00 | -25.53 | QP | |
| 3 | 119.8556 | 36.82 | -20.88 | 15.94 | 43.50 | -27.56 | QP | |
| 4 | 179.3863 | 36.93 | -21.02 | 15.91 | 43.50 | -27.59 | QP | |
| 5 | 603.5392 | 33.44 | -9.64 | 23.80 | 46.00 | -22.20 | QP | |
| 6 | 714.1734 | 33.77 | -8.74 | 25.03 | 46.00 | -20.97 | QP | |

5. Antenna Requirement

5.1. Test Standard and Requirement

| | |
|---------------|--|
| Test Standard | FCC Part15 Section 15.203 |
| Requirement | 1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. |

5.2. Antenna Connected Construction

The antenna is a Inductive loop coil Antenna which permanently attached. It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----