

FCC Test Report

Report No. : 1811C50036812501

Applicant : Anker Innovations Limited

Address : Unit 56, 8th Floor, Tower 2, Admiralty Centre,
18 Harcourt Road, Hong Kong

Product Name : Anker SOLIX C1000 Gen 2 Portable Power
Station/Anker SOLIX C1000X Gen 2 Portable
Power Station

Report Date : 2025-05-21

Shenzhen Anbotek Compliance Laboratory Limited



Contents

1. General Information.....	6
1.1. Client Information	6
1.2. Description of Device (EUT)	6
1.3. Auxiliary Equipment Used During Test	8
1.4. Description of Test Configuration.....	8
1.5. Description of Test Setup.....	9
1.6. Test Equipment List	10
1.7. Measurement Uncertainty	11
1.8. Additional Instructions.....	11
1.9. Description of Test Facility	12
1.10. Disclaimer.....	12
2. Summary of Test Results	13
3. Conducted Emission Test	14
3.1. Test Standard and Limit	14
3.2. Test Setup	14
3.3. Test Procedure	14
3.4. Test Data	14
4. Radiated Spurious Emission and Band Edge Test.....	19
4.1. Test Standard and Limit	19
4.2. Test Setup	19
4.3. Test Procedure	20
4.4. Test Data	21
5. Maximum Conducted Output Power Test.....	30
5.1. Test Standard and Limit	30
5.2. Test Setup	30
5.3. Test Procedure	30
5.4. Test Data	30
6. 6dB Bandwidth and 99% Occupied Bandwidth Test.....	31
6.1. Test Standard and Limit	31
6.2. Test Setup	31
6.3. Test Procedure	31
6.4. Test Data	31
7. Power Spectral Density Test.....	32
7.1. Test Standard and Limit	32
7.2. Test Setup	32
7.3. Test Procedure	32
7.4. Test Data	32
8. Conducted Spurious Emission and Band Edge Test	33

- 8.1. Test Standard and Limit33
- 8.2. Test Setup33
- 8.3. Test Procedure33
- 8.4. Test Data33
- 9. Antenna Requirement34
 - 9.1. Test Standard and Requirement34
 - 9.2. Antenna Connected Construction34
- APPENDIX I -- TEST SETUP PHOTOGRAPH35
- APPENDIX II -- EXTERNAL PHOTOGRAPH.....35
- APPENDIX III -- INTERNAL PHOTOGRAPH.....35

Shenzhen Anbotek

TEST REPORT

Applicant : Anker Innovations Limited
Manufacturer : Anker Innovations Limited
Product Name : Anker SOLIX C1000 Gen 2 Portable Power Station/Anker SOLIX C1000X Gen 2 Portable Power Station
Model No. : A1763, A1765
Trade Mark : 
Rating(s) : Please see to page 7.
Test Standard(s) : 47 CFR Part 15.247
Test Method(s) : ANSI C63.10: 2020, KDB 558074 D01 15.247 Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the 47 CFR Part 15.247 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt 2025-03-12

Date of Test 2025-03-12 to 2025-03-26

Prepared By 

(Lene Chen)

Approved & Authorized Signer 

(Hugo Chen)

Revision History

Report Version	Description	Issued Date
R00	Original Issue.	2025-05-21

1. General Information

1.1. Client Information

Applicant	:	Anker Innovations Limited
Address	:	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong
Manufacturer	:	Anker Innovations Limited
Address	:	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong

1.2. Description of Device (EUT)

Product Name	:	Anker SOLIX C1000 Gen 2 Portable Power Station/Anker SOLIX C1000X Gen 2 Portable Power Station
Model No.	:	A1763, A1765 (Note: According to the model differences on page 7, we prepare "A1763" for all tests, and prepared "A1765" for conducted emission and radiated spurious emissions (below 1GHz) difference testing.)
Trade Mark	:	
Test Power Supply	:	AC 120V, 60Hz/ DC 60V/ DC 51.2V battery inside
Test Sample No.	:	A1763: 1-3-1(Normal Sample), 1-3-2(Engineering Sample) A1765: 1-3-3(Normal Sample)
Adapter	:	N/A
RF Specification		
Operation Mode	:	<input checked="" type="checkbox"/> BT BLE
Support Rate	:	<input checked="" type="checkbox"/> 1Mbps <input checked="" type="checkbox"/> 2Mbps
Operation Frequency	:	2402~2480MHz
Number of Channel	:	40 Channels
Modulation Type	:	GFSK
Antenna Type	:	FPC Antenna
Antenna Gain(Peak)	:	3.57dBi
Remark: 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		

Model differences:

Model No.	Product Name	Color	Number of AC Output Port	Antenna & Gain
A1763	Anker SOLIX C1000 Gen 2 Portable Power Station	Gray	5	FPC / 3.57dBi
A1765	Anker SOLIX C1000X Gen 2 Portable Power Station	Black	3	FPC / 3.40dBi

Rating(s):

A1763:

Anker SOLIX C1000 Gen 2 Portable Power Station
Model: A1763 Rated Capacity: 51.2Vdc 20000mAh/1024Wh
AC Input Voltage: 120V~14A Max, 60Hz
AC Input Power (Charging): 1200W Max
AC Input Power (Ultra Fast Charging): 1530W Max
AC Input Power (Bypass Mode): 1440W Max
XT60 Input: 11-28V = 8.2A; 28-50V = 14.5A (600W Max)
Car Charger Output: 12V = 10A USB-A 1 Output: 5V = 2.4A
USB-C 1 Output: 5V = 3A (15W Max)
USB-C 2 Output: 5V = 3A / 9V = 3A / 15V = 3A / 20V = 3A / 20V = 5A / 28V = 5A (140W Max)
USB-C 3 Output: 5V = 3A / 9V = 3A / 15V = 3A / 20V = 3A / 20V = 5A / 28V = 5A (140W Max)
AC Output (Inverter Mode):
120V~15A, 60Hz, 1800W Max, L+N+PE (Total) 120V~16.6A, 2000W
AC Output (Bypass Mode): 120V~12A Max, 60Hz, 1440W Max, L+N+PE
Discharging Temperature: -4°F~104°F / -20°C~40°C
Charging Temperature: 32°F~104°F / 0°C~40°C
FCC ID: 2AOKB-A1763 IC: 23451-A1763 CAN ICES-003 (B)/NMB-003(B)
Anker Innovations Limited / Made in China
Address: Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong

The device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interferences received, including interference that may cause undesired operation.

WARNING— Do not overcharge the internal battery. See Instruction Manual. Do not smoke, strike a match, or cause a spark in the vicinity of the power pack. Only charge the internal battery in a well ventilated area.
WARNING: Risk of Electric Shock and Risk of Fire. This device is not to be stored in a vehicle.
CAUTION— Risk of Injury To Persons. Do not use this product if the power cord or the battery cables are damaged in any way.
CAUTION— This device is not intended for use in a commercial repair facility.
CAUTION: Risk of Electric Shock. Connect only to properly grounded outlets.
DANGER! This device is not waterproof. Use indoors if it is raining or the ground is wet outside.
AVERTISSEMENT— Ne pas surcharger la batterie interne. Consulter le manuel d'utilisation. Il ne faut pas fumer, allumer une allumette ou produire des étincelles à proximité du bloc d'alimentation. Charger la batterie uniquement dans un endroit bien aéré.
AVERTISSEMENT: Risque de blessure aux personnes. Ne pas utiliser ce produit si le cordon d'alimentation ou les câbles de batterie sont endommagés de quelque façon.
MISE EN GARDE: Le dispositif n'est pas destiné à être utilisé dans un atelier de réparation commercial.
MISE EN GARDE: Risque de décharge électrique. Brancher l'unité uniquement à des prises de courant correctement mises à la masse.
DANGER! Cet appareil n'est pas étanche. Utilisez-le à l'intérieur s'il pleut ou si le sol est humide à l'extérieur.

800833
SGS ENERGY EFFICIENCY
Li-ion 32

ALWAYS HERE TO HELP
— <https://support.ankersolix.com> —
support@ankersolix.com
support.me@ankersolix.com
CED-CN@ankersolix.com

(US/CA) +1 (800)988 7973 English only
(États-Unis/Canada) +1 (800)988 7973 Anglais seulement
(UK) +44 (0)1616 056 301
(DE) +49 (800)000 2522
(日本) +81 03 4455 7823

A1765:

Anker SOLIX C1000X Gen 2 Portable Power Station
Model: A1765 Rated Capacity: 51.2Vdc 20000mAh/1024Wh
AC Input Voltage: 120V~14A Max, 60Hz
AC Input Power (Charging): 1200W Max
AC Input Power (Ultra Fast Charging): 1530W Max
AC Input Power (Bypass Mode): 1440W Max
XT60 Input: 11-28V = 8.2A; 28-50V = 14.5A (600W Max)
Car Charger Output: 12V = 10A USB-A 1 Output: 5V = 2.4A
USB-C 1 Output: 5V = 3A (15W Max)
USB-C 2 Output: 5V = 3A / 9V = 3A / 15V = 3A / 20V = 3A / 20V = 5A / 28V = 5A (140W Max)
USB-C 3 Output: 5V = 3A / 9V = 3A / 15V = 3A / 20V = 3A / 20V = 5A / 28V = 5A (140W Max)
AC Output (Inverter Mode):
120V~15A, 60Hz, 1800W Max, L+N+PE (Total) 120V~16.6A, 2000W
AC Output (Bypass Mode): 120V~12A Max, 60Hz, 1440W Max, L+N+PE
Discharging Temperature: -4°F~104°F / -20°C~40°C
Charging Temperature: 32°F~104°F / 0°C~40°C
FCC ID: 2AOKB-A1763 IC: 23451-A1763 CAN ICES-003 (B)/NMB-003(B)
Anker Innovations Limited / Made in China
Address: Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong

The device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interferences received, including interference that may cause undesired operation.

WARNING— Do not overcharge the internal battery. See Instruction Manual. Do not smoke, strike a match, or cause a spark in the vicinity of the power pack. Only charge the internal battery in a well ventilated area.
WARNING: Risk of Electric Shock and Risk of Fire. This device is not to be stored in a vehicle.
CAUTION— Risk of Injury To Persons. Do not use this product if the power cord or the battery cables are damaged in any way.
CAUTION— This device is not intended for use in a commercial repair facility.
CAUTION: Risk of Electric Shock. Connect only to properly grounded outlets.
DANGER! This device is not waterproof. Use indoors if it is raining or the ground is wet outside.
AVERTISSEMENT— Ne pas surcharger la batterie interne. Consulter le manuel d'utilisation. Il ne faut pas fumer, allumer une allumette ou produire des étincelles à proximité du bloc d'alimentation. Charger la batterie uniquement dans un endroit bien aéré.
AVERTISSEMENT: Risque de blessure aux personnes. Ne pas utiliser ce produit si le cordon d'alimentation ou les câbles de batterie sont endommagés de quelque façon.
MISE EN GARDE: Le dispositif n'est pas destiné à être utilisé dans un atelier de réparation commercial.
MISE EN GARDE: Risque de décharge électrique. Brancher l'unité uniquement à des prises de courant correctement mises à la masse.
DANGER! Cet appareil n'est pas étanche. Utilisez-le à l'intérieur s'il pleut ou si le sol est humide à l'extérieur.

800833
SGS ENERGY EFFICIENCY
Li-ion 32

ALWAYS HERE TO HELP
— <https://support.ankersolix.com> —
support@ankersolix.com
support.me@ankersolix.com
CED-CN@ankersolix.com

(US/CA) +1 (800)988 7973 English only
(États-Unis/Canada) +1 (800)988 7973 Anglais seulement
(UK) +44 (0)1616 056 301
(DE) +49 (800)000 2522
(日本) +81 03 4455 7823

1.3. Auxiliary Equipment Used During Test

Title	Manufacturer	Model No.	Serial No.
/	/	/	/

1.4. Description of Test Configuration


Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
00	2402	09	2420	18	2438	27	2456	36	2474
01	2404	10	2422	19	2440	28	2458	37	2476
02	2406	11	2424	20	2442	29	2460	38	2478
03	2408	12	2426	21	2444	30	2462	39	2480
04	2410	13	2428	22	2446	31	2464		
05	2412	14	2430	23	2448	32	2466		
06	2414	15	2432	24	2450	33	2468		
07	2416	16	2434	25	2452	34	2470		
08	2418	17	2436	26	2454	35	2472		

Note:


1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT was tested with channel 0, 19 and 39.

1.5. Description of Test Setup

CE



RE



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Sep. 09, 2024	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT00 1	Jan. 13, 2025	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Jan. 13, 2025	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Jan. 14, 2025	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Sep. 09, 2024	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G- 45	SKET-PA-002	Jan. 13, 2025	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
9.	Loop Antenna(9K-30M)	Schwarzbeck	FMZB1519B	00053	Sep. 12, 2024	1 Year
10.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Jan. 22, 2024	3 Year
11.	Pre-amplifier	SONOMA	310N	186860	Jan. 14, 2025	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Sep. 09, 2024	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY47420647	Jan. 14, 2025	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	Feb. 21, 2025	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D360510	Sep. 09, 2024	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Oct. 14, 2024	1 Year
18.	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102150	May. 06, 2024	1 Year

1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.2dB
Occupied Bandwidth	925Hz
Conducted Output Power	0.76dB
Power Spectral Density	0.76dB
Time	2%
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (Below 30MHz)	3.26dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.70dB; Vertical: 4.42dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.64dB 6G-18GHz: 4.82dB 18G-40GHz: 5.62dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Additional Instructions

Power level setup in software

EspRFTest TOOL

Operation Band:

Mode	Channel(MHz)	Power level	Transmitting type
BLE_1M	2402	default	data pack TX
BLE_1M	2440	default	data pack TX
BLE_1M	2480	default	data pack TX
BLE_2M	2402	default	data pack TX
BLE_2M	2440	default	data pack TX
BLE_2M	2480	default	data pack TX

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 279531

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 279531.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

1.10. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.
7. The data in this report will be synchronized with the corresponding national market supervision and management departments and cross-border e-commerce platforms as required by regulatory agencies.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Summary of Test Results


Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209/15.247(d)	Radiated Spurious Emission and Band Edge	PASS
15.247(b)(3)	Maximum Conduct Output Power	PASS
15.247(a)(2)	6dB Bandwidth	PASS
N/A	99% Occupied Bandwidth	Report only
15.247(e)	Maximum Power Spectral Density	PASS
15.247(d)	Conducted Spurious Emission and Band Edge	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		

3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.


3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report.

Please to see the following pages.

Conducted Emission Test Data

Test Mode **A1763**
Test Site: 1# Shielded Room
Operating Condition: BLE_2M (2480MHz)
Test Specification: AC 120V, 60Hz
Comment: Live Line
Temp.(°C)/Hum.(%RH): 22.1°C/50%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.2620	31.12	17.84	48.96	61.36	-12.40	QP	
2	0.2660	21.79	17.84	39.63	51.24	-11.61	AVG	
3	0.4380	30.60	17.83	48.43	57.10	-8.67	QP	
4	0.4420	19.35	17.83	37.18	47.02	-9.84	AVG	
5	0.5780	18.40	17.86	36.26	46.00	-9.74	AVG	
6	0.9420	31.01	17.86	48.87	56.00	-7.13	QP	
7	1.2220	17.89	17.85	35.74	46.00	-10.26	AVG	
8	1.3940	29.34	17.86	47.20	56.00	-8.80	QP	
9	1.5380	13.71	17.85	31.56	46.00	-14.44	AVG	
10	4.8900	24.74	17.86	42.60	56.00	-13.40	QP	
11	22.5700	28.53	18.38	46.91	60.00	-13.09	QP	
12	22.5700	18.87	18.38	37.25	50.00	-12.75	AVG	

Remark: Result=Reading+Factor Over Limit=Result-Limit

Conducted Emission Test Data

Test Mode **A1763**
Test Site: 1# Shielded Room
Operating Condition: BLE_2M (2480MHz)
Test Specification: AC 120V, 60Hz
Comment: Neutral Line
Temp.(°C)/Hum.(%RH): 22.1°C/50%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1539	36.79	17.83	54.62	65.78	-11.16	QP	
2	0.2460	21.35	17.82	39.17	51.89	-12.72	AVG	
3	0.2660	31.16	17.84	49.00	61.24	-12.24	QP	
4	0.4100	19.94	17.81	37.75	47.65	-9.90	AVG	
5	0.4300	30.05	17.82	47.87	57.25	-9.38	QP	
6	0.5700	18.40	17.86	36.26	46.00	-9.74	AVG	
7	1.1019	31.35	17.86	49.21	56.00	-6.79	QP	
8	1.1500	18.50	17.86	36.36	46.00	-9.64	AVG	
9	1.4140	26.60	17.86	44.46	56.00	-11.54	QP	
10	1.5060	14.66	17.85	32.51	46.00	-13.49	AVG	
11	1.9740	25.49	17.85	43.34	56.00	-12.66	QP	
12	4.8659	12.86	17.86	30.72	46.00	-15.28	AVG	

Remark: Result=Reading+Factor Over Limit=Result-Limit

Conducted Emission Test Data

Test Mode **A1765**
Test Site: 1# Shielded Room
Operating Condition: BLE_2M (2480MHz)
Test Specification: AC 120V, 60Hz
Comment: Live Line
Temp.(°C)/Hum.(%RH): 22.1°C/50%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.4420	32.01	17.83	49.84	57.02	-7.18	peak	
2	0.4420	22.29	17.83	40.12	47.02	-6.90	AVG	
3	0.5860	31.58	17.86	49.44	56.00	-6.56	peak	
4	0.6180	20.13	17.87	38.00	46.00	-8.00	AVG	
5	1.0339	33.04	17.86	50.90	56.00	-5.10	peak	
6	1.0540	20.77	17.86	38.63	46.00	-7.37	AVG	
7	1.3980	31.63	17.86	49.49	56.00	-6.51	peak	
8	4.8220	28.70	17.86	46.56	56.00	-9.44	peak	
9	4.8220	21.27	17.86	39.13	46.00	-6.87	AVG	
10	5.6779	25.76	17.87	43.63	50.00	-6.37	AVG	
11	6.1060	24.27	17.88	42.15	50.00	-7.85	AVG	
12	12.6420	34.69	18.07	52.76	60.00	-7.24	peak	

Remark: Result=Reading+Factor Over Limit=Result-Limit

Conducted Emission Test Data

Test Mode **A1765**
Test Site: **1# Shielded Room**
Operating Condition: **BLE_2M (2480MHz)**
Test Specification: **AC 120V, 60Hz**
Comment: **Neutral Line**
Temp.(°C)/Hum.(%RH): **22.1°C/50%RH**



No.	Freq. (MHz)	Reading (dBUV)	Factor (dB)	Result (dBUV)	Limit (dBUV)	Over Limit (dB)	Detector	Remark
1	0.1900	35.70	17.82	53.52	64.03	-10.51	peak	
2	0.2660	22.22	17.84	40.06	51.24	-11.18	AVG	
3	0.4260	31.67	17.82	49.49	57.33	-7.84	peak	
4	0.4420	21.90	17.83	39.73	47.02	-7.29	AVG	
5	0.6180	20.09	17.87	37.96	46.00	-8.04	AVG	
6	0.9820	20.46	17.86	38.32	46.00	-7.68	AVG	
7	1.0100	33.59	17.86	51.45	56.00	-4.55	peak	
8	1.3300	29.77	17.86	47.63	56.00	-8.37	peak	
9	1.3980	20.19	17.86	38.05	46.00	-7.95	AVG	
10	1.7140	15.70	17.85	33.55	46.00	-12.45	AVG	
11	1.7500	26.45	17.86	44.31	56.00	-11.69	peak	
12	12.7980	28.64	18.07	46.71	60.00	-13.29	peak	

Remark: Result=Reading+Factor Over Limit=Result-Limit

4. Radiated Spurious Emission and Band Edge Test

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205, 15.247(d)				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz~1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz~30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

- (1) The lower limit shall apply at the transition frequency.
- (2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz,Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:

RBW =1MHz, VBW =3MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

For average measurement:

–VBW=3*RBW, Detector= RMS, When duty cycle is no less than 98 percent

–VBW=3*RBW, Detector= RMS, When duty cycle is less than 98 percent and dutycycle is constant, average=peak level+correction factor(20log(dutycycle)).

–VBW≥1/T, when duty cycle is less than 98 percent and dutycycle is not constant, where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause duty cycle result.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, only the worst case is recorded in the report.

Test Results (1GHz-25GHz)

Test Mode: CH00			Test channel: Lowest			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	28.93	15.27	44.20	74.00	-29.80	Vertical
7206.00	28.91	18.09	47.00	74.00	-27.00	Vertical
9608.00	29.93	23.76	53.69	74.00	-20.31	Vertical
12010.00	*			74.00		Vertical
14412.00	*			74.00		Vertical
4804.00	28.56	15.27	43.83	74.00	-30.17	Horizontal
7206.00	29.61	18.09	47.70	74.00	-26.30	Horizontal
9608.00	28.32	23.76	52.08	74.00	-21.92	Horizontal
12010.00	*			74.00		Horizontal
14412.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	17.20	15.27	32.47	54.00	-21.53	Vertical
7206.00	17.96	18.09	36.05	54.00	-17.95	Vertical
9608.00	19.40	23.76	43.16	54.00	-10.84	Vertical
12010.00	*			54.00		Vertical
14412.00	*			54.00		Vertical
4804.00	16.89	15.27	32.16	54.00	-21.84	Horizontal
7206.00	18.64	18.09	36.73	54.00	-17.27	Horizontal
9608.00	17.83	23.76	41.59	54.00	-12.41	Horizontal
12010.00	*			54.00		Horizontal
14412.00	*			54.00		Horizontal

Test Results (1GHz-25GHz)

Test Mode: CH19			Test channel: Middle			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	28.48	15.42	43.90	74.00	-30.10	Vertical
7320.00	28.88	18.02	46.90	74.00	-27.10	Vertical
9760.00	29.43	23.80	53.23	74.00	-20.77	Vertical
12200.00	*			74.00		Vertical
14640.00	*			74.00		Vertical
4880.00	28.37	15.42	43.79	74.00	-30.21	Horizontal
7320.00	29.48	18.02	47.50	74.00	-26.50	Horizontal
9760.00	28.04	23.80	51.84	74.00	-22.16	Horizontal
12200.00	*			74.00		Horizontal
14640.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	17.29	15.42	32.71	54.00	-21.29	polarization
7320.00	17.82	18.02	35.84	54.00	-18.16	Vertical
9760.00	19.25	23.80	43.05	54.00	-10.95	Vertical
12200.00	*			54.00		Vertical
14640.00	*			54.00		Vertical
4880.00	17.00	15.42	32.42	54.00	-21.58	Vertical
7320.00	18.99	18.02	37.01	54.00	-16.99	Horizontal
9760.00	18.13	23.80	41.93	54.00	-12.07	Horizontal
12200.00	*			54.00		Horizontal
14640.00	*			54.00		Horizontal


Test Results (1GHz-25GHz)

Test Mode: CH39			Test channel: Highest			
Peak value:						
Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Over Limit (dB)	polarization
4960.00	28.61	15.58	44.19	74.00	-29.81	Vertical
7440.00	29.04	17.93	46.97	74.00	-27.03	Vertical
9920.00	30.13	23.83	53.96	74.00	-20.04	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	28.51	15.58	44.09	74.00	-29.91	Horizontal
7440.00	29.69	17.93	47.62	74.00	-26.38	Horizontal
9920.00	28.42	23.83	52.25	74.00	-21.75	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Over Limit (dB)	polarization
4960.00	18.41	15.58	33.99	54.00	-20.01	Vertical
7440.00	19.09	17.93	37.02	54.00	-16.98	Vertical
9920.00	19.90	23.83	43.73	54.00	-10.27	Vertical
12400.00	*			54.00		Vertical
14880.00	*			54.00		Vertical
4960.00	18.18	15.58	33.76	54.00	-20.24	Horizontal
7440.00	19.79	17.93	37.72	54.00	-16.28	Horizontal
9920.00	18.28	23.83	42.11	54.00	-11.89	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

Remark:

- 1.Result =Reading + Factor
2. Test frequency are from 1GHz to 25GHz, “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.
3. During the test, pre-scan the BLE_1M&BLE_2M, and found the BLE_1M is worse case, the report only record this mode.

Radiated Band Edge:



Remark:

1. During the test, pre-scan the BLE_1M and BLE_2M and found the BLE_2M modulation is worse case, the report only record this mode.
2. When the PK measure result value is less than the AVG limit value, the AV measure result values test not applicable.

Test for Duty Cycle.


Please refer to Appendix G of the Appendix Test Data.

5. Maximum Conducted Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	1W (30dBm)

5.2. Test Setup



5.3. Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

1. Set the RBW \geq DTS bandwidth.
2. Set the VBW $\geq 3 \times$ RBW.
3. Set the span $\geq 3 \times$ RBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

5.4. Test Data

Pass


Please refer to Appendix C of the Appendix Test Data.

6. 6dB Bandwidth and 99% Occupied Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(2)
Test Limit	≥500kHz

6.2. Test Setup



6.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
 - 6dB Bandwidth:
 - a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
 - b) Set the VBW ≥ [3 × RBW].
 - c) Detector = peak.
 - d) Trace mode = max-hold.
 - e) Sweep = No faster than coupled (auto) time.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

99% Occupied Bandwidth:

RBW=1~5% OBW, VBW=3*RBW, Sweep Time= Auto, Detector= Peak, Trace= Max hold

6.4. Test Data

Pass


Please refer to Appendix A&B of the Appendix Test Data.

7. Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (e)
Test Limit	8dBm/3kHz

7.2. Test Setup



7.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 30kHz, VBW $\geq 3 \times$ RBW, Span = 1.5x DTS BW
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

7.4. Test Data

Pass


Please refer to Appendix D of the Appendix Test Data.

8. Conducted Spurious Emission and Band Edge Test

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

8.2. Test Setup



8.3. Test Procedure

Using the following spectrum analyzer setting:

1. Set the RBW = 100kHz.
2. Set the VBW = 300kHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

8.4. Test Data

Pass

Please refer to Appendix E&F of the Appendix Test Data.

9. Antenna Requirement

9.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	<p>1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.</p>

9.2. Antenna Connected Construction

The antenna is a **FPC Antenna** which permanently attached, and the best case gain of the antenna is 3.57dBi. It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----